

FCC TEST REPORT FCC 47 CFR Part 15C Industry Canada RSS-210 Frequency hopping systems operating within the 2400 – 2483.5 MHz band	
Report Reference No.	G0M-1403-3710-TFC247BT-V01
Testing Laboratory	Eurofins Product Service GmbH
Address	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation	  A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A
Applicant's name	GN Netcom A/S
Address	Lautrupbjerg 7 2750 Ballerup DENMARK
Test specification:	
Standard	47 CFR Part 15C RSS-210, Issue 8, 2010-12 RSS-Gen, Issue 3, 2010-12 ANSI C63.4:2009
Equipment under test (EUT):	
Product description	Bluetooth headset
Model No.	BTE7
Additional Model(s)	None
Brand Name(s)	Jabra
Hardware version	28-04125
Firmware / Software version	020
	FCC-ID: BCE-BTE7 IC: 2386C-BTE7
Test result	Passed

Test Report No.: G0M-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Possible test case verdicts:

- neither assessed nor tested: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Test Lab Temperature.....: 20 – 23 °C

Test Lab Humidity: 32 – 38 %

Date of receipt of test item: 2014-04-04

Date (s) of performance of tests: 2014-04-04 - 2014-04-09

Compiled by: Wilfried Treffke

Tested by (+ signature).....: Wilfried Treffke 

(Responsible for Test)

Approved by (+ signature): Christian Weber 

Date of issue: 2014-04-25

Total number of pages: 128

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:

Version History

Version	Issue Date	Remarks	Revised by
01	2014-04-25	Initial Release	

REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Photos – Equipment External	6
1.2	Photos – Equipment internal	7
1.3	Photos – Test setup	9
1.4	Supporting Equipment Used During Testing	10
1.5	Test Modes	11
1.6	Test Equipment Used During Testing	13
1.7	Sample emission level calculation	15
2	RESULT SUMMARY	16
3	TEST CONDITIONS AND RESULTS	17
3.1	Test Conditions and Results – Occupied Bandwidth	17
3.2	Test Conditions and Results – 20 dB Bandwidth	24
3.3	Test Conditions and Results – Number of hopping frequencies	34
3.4	Test Conditions and Results – Frequency hopping channel separation	38
3.5	Test Conditions and Results – Time of occupancy (Dwell Time)	40
3.6	Test Conditions and Results – Maximum peak conducted power	42
3.7	Test Conditions and Results – AC power line conducted emissions	44
3.8	Test Conditions and Results – Band edge compliance	47
3.9	Test Conditions and Results – Conducted spurious emissions	61
3.10	Test Conditions and Results – Transmitter radiated emissions	68
3.11	Test Conditions and Results – Receiver radiated emissions	71
ANNEX A	Transmitter radiated spurious emissions	73
ANNEX B	Receiver radiated spurious emissions	121

1 Equipment (Test item) Description

Description	Bluetooth headset	
Model	BTE7	
Additional Model(s)	None	
Brand Name(s)	Jabra	
Serial number	None	
Hardware version	28-04125	
Software / Firmware version	020	
FCC-ID	BCE-BTE7	
IC	2386C-BTE7	
Equipment type	End product	
Radio type	Transceiver	
Radio technology	Bluetooth	
Operating frequency range	2402 - 2480 MHz	
Assigned frequency band	2400 - 2483.5 MHz	
Main test frequencies	F _{LOW}	2402 MHz
	F _{MID}	2441 MHz
	F _{HIGH}	2480 MHz
Spreading	FHSS	
Modulations	GFSK, PI/4-DQPSK, 8-PSK	
Number of channels	79 hopping channels at all	
Channel spacing	1 MHz	
Number of antennas	1	
Antenna	Type	integrated
	Model	PCB
	Manufacturer	GN Netcom
	Gain	0 dBi
Manufacturer	GN Netcom A/S Lautrupbjerg 7 2750 Ballerup DENMARK	
Power supply	V _{NOM}	3.7 VDC (Lithium Battery)
	V _{MIN}	3.2 VDC
	V _{MIN}	4.2 VDC
AC/DC-Adaptor	Model	N/A
	Vendor	N/A
	Input	N/A
	Output	N/A

1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments
AE	Bluetooth Tester	R & S	CBT	Signaling
*Note: Use the following abbreviations: AE : Auxiliary/Associated Equipment, or SIM : Simulator (Not Subjected to Test) CABL : Connecting cables				

1.5 Test Modes

Mode #	Description	
DH5-Sngl	General conditions:	EUT powered by laboratory power supply.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping stopped (single hopping channel) Modulation = GFSK Packet type = DH5 Data rate = 1 Mbps Duty cycle = 77 % Power level = Maximum
2DH5-Sngl	General conditions:	EUT powered by laboratory power supply.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping stopped (single hopping channel) Modulation = $\pi/4$ -DQPSK Packet type = 2DH5 Data rate = 2 Mbps Duty cycle = 77 % Power level = Maximum
3DH5-Sngl	General conditions:	EUT powered by laboratory power supply.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping stopped (single hopping channel) Modulation = 8-DPSK Packet type = 3DH5 Data rate = 3 Mbps Duty cycle = 77 % Power level = Maximum
DH5-Hop	General conditions:	EUT powered by laboratory power supply.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping Modulation = GFSK Packet type = DH5 Data rate = 1 Mbps Duty cycle = 77 % Power level = Maximum

2DH5-Hop	General conditions:	EUT powered by laboratory power supply.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping Modulation = $\pi/4$ -DQPSK Packet type = 2DH5 Data rate = 2 Mbps Duty cycle = 77 % Power level = Maximum
3DH5-Hop	General conditions:	EUT powered by laboratory power supply.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping Modulation = 8-DPSK Packet type = 3DH5 Data rate = 3 Mbps Duty cycle = 77 % Power level = Maximum
Receive	General conditions:	EUT powered by laboratory power supply.
	Radio conditions:	Mode = standalone receive Spreading = Hopping
AC-Powerline	General conditions:	EUT powered by commercial AC/DC-Adapter
	Radio conditions:	Mode = standalone transmit Spreading = Hopping Power level = Maximum

1.6 Test Equipment Used During Testing

Measurement Software			
Description	Manufacturer	Name	Version
EMC Test Software	Dare Instruments	Radimation	5.8.37

20dB Bandwidth					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Number of hopping frequencies					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Time of occupancy					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Maximum peak conducted power					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Band edge compliance					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Conducted spurious emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum analyzer	R&S	FSW43	EF00896	2014-02	2015-02

Radiated spurious emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Semi-anechoic chamber	Frankonia	AC 5	EF00395	-	-
Spectrum Analyzer	R&S	FSIQ26	EF00151	2014-03	2015-03
Biconical antenna	R&S	HK 116	EF00186	2014-02	2016-02
LPD antenna	R&S	HL 223	EF00202	2014-02	2016-02
Log periodical antenna	R&S	HL 025	EF00014	2014-01	2016-01

Test Report No.: G0M-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

AC powerline conducted emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
AMN	R&S	ESH2-Z5	EF00182	2012-10	2014-10
AMN	R&S	ESH3-Z5	EF00036	2012-11	2014-11
EMI Test Receiver	R&S	ESCS 30	EF00297	2013-11	2014-11

1.7 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dBμV. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dBμV/m). The FCC limits are given in units of μV/m. The following formula is used to convert the units of μV/m to dBμV/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 * \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:

Reading	+	AF	=	Net Reading	:	Net reading - FCC limit	=	Margin
21.5 dBμV	+	26 dB	=	47.5 dBμV/m	:	47.5 dBμV/m - 57.0 dBμV/m	=	-9.5 dB

2 Result Summary

FCC 47 CFR Part 15C, IC RSS-210				
Product Specific Standard Section	Requirement – Test	Reference Method	Result	Remarks
RSS-Gen 4.6.1	Occupied Bandwidth	RSS-Gen 4.6.1	N/R	Informational only
FCC § 15.247(a)(1) IC RSS-210 § A8.1	20 dB Bandwidth	Public notice DA 00-705	PASS	
FCC § 15.247(a)(1)(iii) IC RSS-210 § A8.1	Number of hopping frequencies	Public notice DA 00-705	PASS	
FCC § 15.247(a)(1) IC RSS-210 § A8.1	Frequency hopping channel separation	Public notice DA 00-705	PASS	
FCC § 15.247(a)(1)(iii) IC RSS-210 § A8.1	Time of occupancy (Dwell time)	Public notice DA 00-705	PASS	
FCC § 15.247(b)(1) IC RSS-210 § A8.4	Maximum peak conducted power	Public notice DA 00-705	PASS	
47 CFR 15.207 RSS-Gen 7.2.4	AC power line conducted emissions	ANSI C63.4	PASS	
FCC § 15.247(d) IC RSS-210 § A8.5	Band edge compliance	Public notice DA 00-705	PASS	
FCC § 15.247(d) IC RSS-210 § A8.5	Conducted spurious emissions	Public notice DA 00-705	PASS	
FCC § 15.247(d) FCC § 15.209 IC RSS-210 A8.5 IC RSS-Gen 4.9 IC RSS-Gen 7.2.5	Transmitter radiated spurious emissions	Public notice DA 00-705 / ANSI C 63.4	PASS	
IC RSS-Gen 4.10 IC RSS-Gen 6.1	Receiver radiated spurious emissions	ANSI C 63.4	PASS	
Remarks:				

3 Test Conditions and Results


3.1 Test Conditions and Results – Occupied Bandwidth

Occupied Bandwidth acc. IC RSS-Gen			Verdict: PASS
Test according to measurement reference	Reference Method		
	RSS-Gen 4.6.1		
Test frequency range	Tested frequencies		
	F _{LOW} / F _{MID} / F _{HIGH}		
Limits			
None (Informational only)			
Test setup			
Spectrum Analyzer EUT			
Test procedure			
1. EUT set to test mode (Communication tester is used if needed) 2. Span set to at least twice the emission spectrum 3. Resolution bandwidth set to 1 % of span 4. Occupied Bandwidth (99 %) measurement with spectrum analyzer built in measurement function			
Test results			
Channel	Frequency [MHz]	Mode	Occupied Bandwidth [kHz]
F _{LOW}	2402	DH5-Sngl	910
F _{MID}	2441	DH5-Sngl	910
F _{HIGH}	2402	DH5-Sngl	910
F _{LOW}	2402	3DH5-Sngl	1260
F _{MID}	2441	3DH5-Sngl	1218
F _{HIGH}	2480	3DH5-Sngl	1232
Comments:			

Occupied Bandwidth – DH5-Sngl F_{Low}

RSS Gen Occupied Bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	4.4.1 Occupied Bandwidth
Comment 1	Channel.: 0 / 2402 MHz
Comment 2	A spectrum analyzer with an integrated 99% power bandwidth function is used
Comment 3	GFSK




Comment: Occupied bandwidth: 910 KHz
Date: 7.APR.2014 15:16:31

Occupied Bandwidth – DH5-Sngl F_{MID}

RSS Gen Occupied Bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	4.4.1 Occupied Bandwidth
Comment 1	Channel.: 39 / 2441 MHz
Comment 2	A spectrum analyzer with an integrated 99% power bandwidth function is used
Comment 3	GFSK




Comment: Occupied bandwidth: 910 KHz
 Date: 7.APR.2014 15:18:45

Occupied Bandwidth – DH5-Sngl F_{HIGH}

RSS Gen Occupied Bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	4.4.1 Occupied Bandwidth
Comment 1	Channel.: 78 / 2480 MHz
Comment 2	A spectrum analyzer with an integrated 99% power bandwidth function is used
Comment 3	GFSK




Comment: Occupied bandwidth: 910 KHz
Date: 7.APR.2014 15:20:31

Occupied Bandwidth – 3-DH5-Sngl F_{LOW}

RSS Gen Occupied Bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	4.4.1 Occupied Bandwidth
Comment 1	Channel.: 0 / 2402 MHz
Comment 2	A spectrum analyzer with an integrated 99% power bandwidth function is used
Comment 3	8DPSK




Comment: Occupied bandwidth: 1260 KHz
Date: 7.APR.2014 15:22:01

Occupied Bandwidth – 3-DH5-Sngl F_{MID}

RSS Gen Occupied Bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	4.4.1 Occupied Bandwidth
Comment 1	Channel.: 39 / 2441 MHz
Comment 2	A spectrum analyzer with an integrated 99% power bandwidth function is used
Comment 3	8DPSK




Comment: Occupied bandwidth: 1218 KHz
Date: 7.APR.2014 15:24:09

Occupied Bandwidth – 3-DH5-Sngl F_{HIGH}

RSS Gen

Occupied Bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	4.4.1 Occupied Bandwidth
Comment 1	Channel.: 78 / 2480 MHz
Comment 2	A spectrum analyzer with an integrated 99% power bandwidth function is used
Comment 3	8DPSK



Comment: Occupied bandwidth: 1232 KHz
Date: 7.APR.2014 15:26:15

3.2 Test Conditions and Results – 20 dB Bandwidth

20 dB Bandwidth acc. FCC 15.247 / IC RSS-210				Verdict: PASS	
EUT requirement rule parts and clause	Reference				
	FCC 15.247(a)(1) / IC RSS-210 A8.1				
Test according to measurement reference	Reference Method				
	FCC Public Notice DA 00-705				
Test frequency range	Tested frequencies				
	F _{LOW} / F _{MID} / F _{HIGH}				
Limits					
Limit		Condition			
1.5 · Carrier spacing		Output power ≤ 125 mW / 21 dBm			
1.0 · Carrier spacing		125 mW / 21 dBm < Output power ≤ 1 W / 30 dBm			
Test setup					
Spectrum Analyzer EUT					
Test procedure					
1. EUT set to test mode (Communication tester is used if needed) 2. Span set to at least twice the emission spectrum 3. Detector set to peak and max hold 4. Envelope peak value of emission spectrum is selected 5. Marker on envelope of spectrum is set to level of -20 dB to the left of the peak 6. Marker on envelope of spectrum is set to level of -20 dB to the right of the peak 7. 20dB Bandwidth is determined by marker frequency separation					
Test results					
Channel	Frequency [MHz]	Mode	20 dB Bandwidth [MHz]	Limit [MHz]	Result
F _{LOW}	2402	DH5-Sngl	930.6	1.5	PASS
F _{MID}	2441	DH5-Sngl	930.6	1.5	PASS
F _{HIGH}	2480	DH5-Sngl	930.6	1.5	PASS
F _{LOW}	2402	2DH5-Sngl	1313.4	1.5	PASS
F _{MID}	2441	2DH5-Sngl	1313.4	1.5	PASS
F _{HIGH}	2480	2DH5-Sngl	1313.4	1.5	PASS
F _{LOW}	2402	3DH5-Sngl	1265	1.5	PASS
F _{MID}	2441	3DH5-Sngl	1265	1.5	PASS
F _{HIGH}	2480	3DH5-Sngl	1265	1.5	PASS
Comments:					


Test Report No.: G0M-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

20 dB Bandwidth – DH5-Sngl F_{LOW}

FCC part 15.247
20 dB bandwidth

EUT Bluetooth headset
Model BTE7
Approval Holder GN Netcom A/S / GOM-1403-3710
Temperature / Voltage Tnom / Vnom
Test Site / Operator Eurofins Product Service GmbH / Mr. Treffke
Test Specification FCC part 15 section 247(a)
Comment 1 20 dB bandwidth
Comment 2 Channel.: 0 / 2402 MHz / GFSK
Comment 3 pass



Comment: 20 dB bandwidth: 930.6 KHz
Date: 7.APR.2014 13:09:12


Test Report No.: GOM-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

20 dB Bandwidth – DH5-Sngl F_{MID}

FCC part 15.247
20 dB bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	20 dB bandwidth
Comment 2	Channel.: 39 / 2441 MHz / GFSK
Comment 3	pass



Comment: 20 dB bandwidth: 930.6 KHz
Date: 7.APR.2014 13:11:39


Test Report No.: GOM-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

20 dB Bandwidth – DH5-Sngl F_{HIGH}

FCC part 15.247
20 dB bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	20 dB bandwidth
Comment 2	Channel.: 78 / 2480 MHz / GFSK
Comment 3	pass




Comment: 20 dB bandwidth: 930.6 KHz
Date: 7.APR.2014 13:14:37

20 dB Bandwidth – 2-DH5-Sngl F_{Low}

FCC part 15.247
20 dB bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	20 dB bandwidth
Comment 2	Channel.: 0 / 2402 MHz / Pi/4 DQPSK
Comment 3	pass



Comment: 20 dB bandwidth: 1313.4 KHz
Date: 7.APR.2014 13:16:59


Test Report No.: G0M-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

20 dB Bandwidth – 2-DH5-Sngl F_{MID}

FCC part 15.247
20 dB bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	20 dB bandwidth
Comment 2	Channel.: 39 / 2441 MHz / Pi/4 DQPSK
Comment 3	pass



Comment: 20 dB bandwidth: 1313.4 KHz
Date: 7.APR.2014 13:19:29


Test Report No.: GOM-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

20 dB Bandwidth – 2-DH5-Sngl F_{HIGH}

FCC part 15.247
20 dB bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	20 dB bandwidth
Comment 2	Channel.: 78 / 2480 MHz / Pi/4 DQPSK
Comment 3	pass



Comment: 20 dB bandwidth: 1313.4 KHz
Date: 7.APR.2014 13:22:23


Test Report No.: GOM-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

20 dB Bandwidth – 3-DH5-Sngl F_{Low}

FCC part 15.247
20 dB bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	20 dB bandwidth
Comment 2	Channel.: 0 / 2402 MHz / 8DPSK
Comment 3	pass



Comment: 20 dB bandwidth: 1265 KHz
Date: 7.APR.2014 13:25:57


Test Report No.: GOM-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

20 dB Bandwidth – 3-DH5-Sngl F_{MID}

FCC part 15.247
20 dB bandwidth

EUT Bluetooth headset
Model BTE7
Approval Holder GN Netcom A/S / GOM-1403-3710
Temperature / Voltage Tnom / Vnom
Test Site / Operator Eurofins Product Service GmbH / Mr. Treffke
Test Specification FCC part 15 section 247(a)
Comment 1 20 dB bandwidth
Comment 2 Channel.: 39 / 2441 MHz / 8DPSK
Comment 3 pass



Comment: 20 dB bandwidth: 1269.4 KHz
Date: 7.APR.2014 13:27:45


Test Report No.: GOM-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

20 dB Bandwidth – 3-DH5-Sngl F_{HIGH}

FCC part 15.247
20 dB bandwidth

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	20 dB bandwidth
Comment 2	Channel.: 78 / 2480 MHz / 8DPSK
Comment 3	pass



Comment: 20 dB bandwidth: 1265 KHz
Date: 7.APR.2014 13:29:36

Test Report No.: GOM-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

3.3 Test Conditions and Results – Number of hopping frequencies


Number of hopping frequencies acc. FCC 15.247 / IC RSS-210		Verdict: PASS
EUT requirement rule parts and clause	Reference	
	FCC 15.247(a)(1)(iii) / IC RSS-210 A8.1	
Test according to measurement reference	Reference Method	
	FCC Public Notice DA 00-705	
Test frequency range	Tested frequencies	
	F _{LOW} - F _{HIGH}	
EUT test mode	DH5-Hop	
Limits		
Limit	Condition	
Number of hopping channels ≥ 15	Output power ≤ 125 mW / 21 dBm	
Number of hopping channels ≥ 75	125 mW / 21 dBm < Output power ≤ 1 W / 30 dBm	
Test setup		
Spectrum Analyzer EUT		
Test procedure		
1. EUT set to test mode (Communication tester is used if needed) 2. Span set to measurement frequency range 3. Detector set to peak and max hold 4. Resolution bandwidth is set small enough to resolve hopping channel emission spectra 5. The number of peaks is counted to determine number of hopping frequencies		
Test results		
Number of hopping frequencies	Limit	Result
79	≥ 15	PASS
Comments:		

Number of hopping frequencies - Range A

FCC part 15.247

Number of hopping frequencies


EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	Number of hopping frequencies
Comment 2	Channel.: 0-24
Comment 3	pass



Comment: Number of hopping frequencies
Date: 7.APR.2014 15:03:55

Number of hopping frequencies - Range B
FCC part 15.247
Number of hopping frequencies

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	Number of hopping frequencies
Comment 2	Channel.: 25-54
Comment 3	pass




Comment: Number of hopping frequencies
Date: 7.APR.2014 15:05:22

Number of hopping frequencies - Range C

FCC part 15.247

Number of hopping frequencies

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)
Comment 1	Number of hopping frequencies
Comment 2	Channel.: 55-78
Comment 3	pass



Comment: Number of hopping frequencies
Date: 7.APR.2014 15:06:39

3.4 Test Conditions and Results – Frequency hopping channel separation


Frequency hopping channel separation acc. FCC 15.247 / IC RSS-210		Verdict: PASS
EUT requirement rule parts and clause	Reference	
	FCC 15.247(a)(1) / IC RSS-210 A8.1	
Test according to measurement reference	Reference Method	
	FCC Public Notice DA 00-705	
Test frequency range	Tested frequencies	
	2441 & 2442 MHz	
EUT test mode	DH5-Hop	
Limits		
Limit	Condition	
≥ 25 kHz or ⅔ of 20 dB bandwidth	Output power ≤ 125 mW / 21 dBm	
≥ 25 kHz or 20 dB bandwidth	125 mW / 21 dBm < Output power ≤ 1 W / 30 dBm	
Test setup		
Spectrum Analyzer EUT		
Test procedure		
1. EUT set to test mode (Communication tester is used if needed) 2. Span set to measurement frequency range 3. Detector set to peak and max hold 4. Resolution bandwidth is set small enough to resolve hopping channel emission spectra 5. The two adjacent channel peaks are marked 6. Channel separation is determined from frequency separation of markers		
Test results		
Channel separation [kHz]	Limit [kHz]	Result
1000	≥ ⅔ · 930.6 = 620.4	PASS
Comments:		

Frequency hopping channel separation

FCC part 15.247

Carrier frequency separation

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(a)(1)
Comment 1	Carrier frequency separation
Comment 2	Channel.: 39/40 / 2441/2442 MHz
Comment 3	Hopping mode



Comment: Limit: > two-thirds of the 20 dB bandwidth ; Result: Pass
Date: 7.APR.2014 14:35:52

3.5 Test Conditions and Results – Time of occupancy (Dwell Time)


Time of occupancy (Dwell time) acc. FCC 15.247 / IC RSS-210				Verdict: PASS	
EUT requirement rule parts and clause		Reference			
		FCC 15.247(a)(1)(iii) / IC RSS-210 A8.1			
Test according to measurement reference		Reference Method			
		FCC Public Notice DA 00-705			
Test frequency range		Tested frequencies			
		2441 MHz			
EUT test mode		DH5-Hop			
Limits					
Limit					
Time of occupancy ≤ 0.4 s within 0.4 s · Number of hopping channels					
Test setup					
Spectrum Analyzer EUT					
Test procedure					
1. EUT set to test mode (Communication tester is used if needed) 2. Center frequency set to test channel center frequency 3. Span set to zero span and detector to peak and max hold 4. Resolution bandwidth is set to 100kHz and sweep time to observation period 5. Time of occupancy determined from number of peaks multiplied by single hop dwell time					
Test results					
Observation period [s]	No. of hops	Dwell time/hop [s]	Time of occupancy [s]	Limit [s]	Result
31.6	79	2.8976	0.229	≤ 0.4	PASS
Comments:					

Time of occupancy

FCC part 15.247

Time of occupancy (dwell time)

EUT Bluetooth headset
Model BTE7
Approval Holder GN Netcom A/S / G0M-1403-3710
Temperature / Voltage Tnom / Vnom
Test Site / Operator Eurofins Product Service GmbH / Mr. Treffke
Test Specification FCC part 15 section 247(a)
Comment 1 Time of occupancy
Comment 2 Channel.: 39 / 2441 MHz (Hopping mode)
Comment 3 79 events * 2.8976 ms result: 228.9 ms



Comment: Burst length=2.8976 ms
Date: 7.APR.2014 15:36:44

3.6 Test Conditions and Results – Maximum peak conducted power

Maximum peak conducted power acc. FCC 15.247 / IC RSS-210		Verdict: PASS
EUT requirement rule parts and clause	Reference	
	FCC 15.247(b)(1) / IC RSS-210 A8.4	
Test according to measurement reference	Reference Method	
	FCC Public Notice DA 00-705	
Test frequency range	Tested frequencies	
	F _{LOW} / F _{MID} / F _{HIGH}	
Measurement mode	Peak	
Maximum antenna gain	0 dBi ⇒ Limit correction = 0 dB	
Limits		
Limit	Condition	
1 W (30 dBm)	Number of hopping channels ≥ 75	
0.125 W (21 dBm)	75 > Number of hopping channels ≥ 15	
The conducted output power limit specified above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in the table, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.		
Test setup		
Spectrum Analyzer EUT		
Test procedure		
1. EUT set to test mode (Communication tester is used if needed) 2. Center frequency set to test channel center frequency 3. Span set to twice the 20 dB bandwidth and detector to peak and max hold 4. Resolution bandwidth is set to 3 MHz 5. Peak conducted power is determined from peak of spectrum envelope		

Test results								
Channel	Frequency [MHz]	Voltage	Mode	Peak power [dbm]	Peak power [W]	Limit [dBm]	Margin [dB]	Result
F _{LOW}	2402	3.7 VDC	DH5-Sngl	2.97	0.0020	30	-27.03	PASS
F _{MID}	2441	3.7 VDC	DH5-Sngl	4.79	0.0030	30	-25.21	PASS
F _{HIGH}	2480	3.7 VDC	DH5-Sngl	5.07	0.0032	30	-24.93	PASS
F _{LOW}	2402	3.7 VDC	2DH5-Sngl	-0.01	0.0010	30	-30.01	PASS
F _{MID}	2441	3.7 VDC	2DH5-Sngl	2.17	0.0016	30	-27.83	PASS
F _{HIGH}	2480	3.7 VDC	2DH5-Sngl	2.53	0.0018	30	-27.47	PASS
F _{LOW}	2402	3.7 VDC	3DH5-Sngl	0.47	0.0011	30	-29.53	PASS
F _{MID}	2441	3.7 VDC	3DH5-Sngl	2.77	0.0019	30	-27.23	PASS
F _{HIGH}	2480	3.7 VDC	3DH5-Sngl	2.77	0.0019	30	-27.23	PASS
Comments:								

3.7 Test Conditions and Results – AC power line conducted emissions


Power line conducted emissions acc. FCC 47 CFR 15.207 / IC RSS-Gen				Verdict: PASS	
Test according referenced standards		Reference Method			
		ANSI C63.4			
Fully configured sample scanned over the following frequency range		Frequency range			
		0.15 MHz to 30 MHz			
Points of Application		Application Interface			
AC Mains		LISN			
EUT test mode		AC-Powerline			
Limits and results					
Frequency [MHz]	Quasi-Peak [dBμV]	Result	Average [dBμV]	Result	
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS	
0.5 to 5	56	PASS	46	PASS	
5 to 30	60	PASS	50	PASS	
Comments:					
* Limit decreases linearly with the logarithm of the frequency.					

Conducted Emissions
EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1403-3710

Manufacturer: GN Netcom A/S
 EUT Name: Bluetooth Headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Zunke
 Test Conditions: Tnom: 22°C, Unom: 120 VAC (via AC/DC Adapter)
 LISN: ESH2-Z5 N
 Mode: charging
 Test Date: 2014-04-11
 Note:

Index 14




Conducted Emissions

EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1403-3710

Manufacturer: GN Netcom A/S
 EUT Name: Bluetooth Headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Zunke
 Test Conditions: Tnom: 22°C, Unom: 120 VAC (via AC/DC Adapter)
 LISN: ESH2-Z5 L
 Mode: charging
 Test Date: 2014-04-11
 Note:

Index 15



3.8 Test Conditions and Results – Band edge compliance

Band-edge compliance acc. FCC 15.247 / IC RSS-210		Verdict: PASS
EUT requirement rule parts and clause	Reference	
	FCC 15.247(d) / IC RSS-210 A8.5	
Test according to measurement reference	Reference Method	
	FCC Public Notice DA 00-705	
Test frequency range	Tested frequencies	
	F _{LOW} / F _{HIGH}	
Measurement mode	Peak	
Limits		
Limit	Condition	
≤ -20 dB/100 kHz	Peak power measurement detector = Peak	
≤ -30 dB/100 kHz	Peak power measurement detector = RMS	
Test setup		
Spectrum Analyzer EUT		
Test procedure		
1. EUT set to test mode (Communication tester is used if needed) 2. Span set around lower band edge and detector is set to peak and max hold 3. Resolution bandwidth is set to 100 kHz 4. Markers are set to peak emission levels within frequency band and outside frequency band 5. Band edge attenuation is determined from level difference		


Test results						
Channel	Frequency [MHz]	Mode	Level [dBc]	Limit [dBc]	Margin [dB]	Result
F _{LOW}	2402	DH5-Sngl	-35.42	-20	-15.42	PASS
F _{HIGH}	2480	DH5-Sngl	-37.08	-20	-17.08	PASS
F _{LOW}	2402	DH5-Hop	-34.29	-20	-14.29	PASS
F _{HIGH}	2480	DH5-Hop	-36.37	-20	-16.37	PASS
F _{LOW}	2402	2DH5-Sngl	-31.23	-20	-11.23	PASS
F _{HIGH}	2480	2DH5-Sngl	-33.09	-20	-13.09	PASS
F _{LOW}	2402	2DH5-Hop	-31.16	-20	-11.16	PASS
F _{HIGH}	2480	2DH5-Hop	-31.10	-20	-11.10	PASS
F _{LOW}	2402	3DH5-Sngl	-29.85	-20	-09.85	PASS
F _{HIGH}	2480	3DH5-Sngl	-33.50	-20	-13.50	PASS
F _{LOW}	2402	3DH5-Hop	-32.09	-20	-12.09	PASS
F _{HIGH}	2480	3DH5-Hop	-34.01	-20	-14.01	PASS
Comments:						

Band-edge compliance – DH5-Sngl F_{Low}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 0 / 2402 MHz / GFSK
Comment 3	Single frequency mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
Date: 7.APR.2014 13:38:35

Band-edge compliance – DH5-Sngl F_{HIGH}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 78 / 2480 MHz / GFSK
Comment 3	Single frequency mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
Date: 7.APR.2014 13:42:03

Band-edge compliance – DH5-Hop F_{LOW}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 0 / 2402 MHz GFSK
Comment 3	Hopping mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
 Date: 7.APR.2014 14:13:20

Band-edge compliance – DH5-Hop F_{HIGH}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 78 / 2480 MHz GFSK
Comment 3	Hopping mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
 Date: 7.APR.2014 14:15:34

Band-edge compliance – 2-DH5-Sngl F_{LOW}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	T _{nom} / V _{nom}
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 0 / 2402 MHz / Pi/4-DQPSK
Comment 3	Single frequency mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
 Date: 7.APR.2014 13:46:09

Band-edge compliance – 2-DH5-Sngl F_{HIGH}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 78 / 2480 MHz / Pi/4-DQPSK
Comment 3	Single frequency mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
 Date: 7.APR.2014 13:47:26

Band-edge compliance – 2-DH5-Hop F_{LOW}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 0 / 2402 MHz Pi/4-DQPSK
Comment 3	Hopping mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
Date: 7.APR.2014 14:17:12

Band-edge compliance – 2-DH5-Hop F_{HIGH}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 78 / 2480 MHz Pi/4-DQPSK
Comment 3	Hopping mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
 Date: 7.APR.2014 14:18:52

Band-edge compliance – 3-DH5-Sngl F_{LOW}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 0 / 2402 MHz / 8DPSK
Comment 3	Single frequency mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
 Date: 7.APR.2014 13:49:37

Band-edge compliance – 3-DH5-Sngl F_{HIGH}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 78 / 2480 MHz / 8DPSK
Comment 3	Single frequency mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
Date: 7.APR.2014 13:52:03

Band-edge compliance – 3-DH5-Hop F_{LOW}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 0 / 2402 MHz 8DPSK
Comment 3	Hopping mode




Comment: Limit: Marker Delta value >20 dB; Result: PASS
Date: 7.APR.2014 14:21:20

Band-edge compliance – 3-DH5-Hop F_{HIGH}

FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 78 / 2480 MHz 8DPSK
Comment 3	Hopping mode



Comment: Limit: Marker Delta value >20 dB; Result: PASS
 Date: 7.APR.2014 14:25:23


3.9 Test Conditions and Results – Conducted spurious emissions

Conducted spurious emissions acc. FCC 15.247 / IC RSS-210							Verdict: PASS	
EUT requirement rule parts and clause			Reference					
			FCC 15.247(d) / IC RSS-210 A8.5					
Test according to measurement reference			Reference Method					
			FCC Public Notice DA 00-705					
Test frequency range			Tested frequencies					
			10 MHz – 10 th Harmonic					
Measurement mode			Peak					
Limits								
Limit				Condition				
≤ -20 dB/100 kHz				Peak power measurement detector = Peak				
≤ -30 dB/100 kHz				Peak power measurement detector = RMS				
Test setup								
Spectrum Analyzer EUT								
Test procedure								
1. EUT set to test mode (Communication tester is used if needed) 2. Span it set according to measurement range 3. Resolution bandwidth is set to 100 kHz and detector to peak and max hold 4. Markers are set to peak emission levels within frequency band 5. Emission level is determined by second marker on emission peak 6. Attenuation is determined from level difference								
Test results								
Channel	Frequency [MHz]	Mode	Emission [MHz]	Emission Level [dBm]	Peak power [dBm]	Limit [dBm]	Margin [dB]	Result
F _{LOW}	2402	DH5-Sngl	No significant spurious emissions					PASS
F _{MID}	2441	DH5-Sngl	4889	-45.7	4.4	-15.6	-30.1	PASS
F _{HIGH}	2480	DH5-Sngl	No significant spurious emissions					PASS
F _{LOW}	2402	3DH5-Sngl	No significant spurious emissions					PASS
F _{MID}	2441	3DH5-Sngl	No significant spurious emissions					PASS
F _{HIGH}	2480	3DH5-Sngl	No significant spurious emissions					PASS
Comments:								

Conducted spurious emissions – DH5-Sngl F_{Low}

FCC part 15.247 (d)
Spurious Emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	T _{nom} / V _{nom}
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15.247 (d)
Comment 1	Spurious Emissions conducted
Comment 2	Channel : 2402 MHz
Comment 3	GFSK




Date: 7.APR.2014 15:40:49

Conducted spurious emissions – DH5-Sngl F_{MID}

FCC part 15.247 (d)
Spurious Emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / G0M-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15.247 (d)
Comment 1	Spurious Emissions conducted
Comment 2	Channel : 2441 MHz
Comment 3	GFSK



Date: 7.APR.2014 15:46:39


Test Report No.: G0M-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Conducted spurious emissions – DH5-Sngl F_{HIGH}

FCC part 15.247 (d)
Spurious Emissions

EUT	Bluetooth headset
Model	BTE7
Approval Holder	GN Netcom A/S / GOM-1403-3710
Temperature / Voltage	Tnom / Vnom
Test Site / Operator	Eurofins Product Service GmbH / Mr. Treffke
Test Specification	FCC part 15.247 (d)
Comment 1	Spurious Emissions conducted
Comment 2	Channel : 2480 MHz
Comment 3	GFSK




Date: 7.APR.2014 15:49:58

Conducted spurious emissions – 3-DH5-Sngl F_{Low}

FCC part 15.247 (d)
Spurious Emissions

EUT Bluetooth headset
Model BTE7
Approval Holder GN Netcom A/S / G0M-1403-3710
Temperature / Voltage Tnom / Vnom
Test Site / Operator Eurofins Product Service GmbH / Mr. Treffke
Test Specification FCC part 15.247 (d)
Comment 1 Spurious Emissions conducted
Comment 2 Channel : 2402 MHz
Comment 3 8DPSK




Date: 7.APR.2014 16:03:20

Conducted spurious emissions – 3-DH5-Sngl F_{MID}

FCC part 15.247 (d)
Spurious Emissions

EUT Bluetooth headset
Model BTE7
Approval Holder GN Netcom A/S / GOM-1403-3710
Temperature / Voltage Tnom / Vnom
Test Site / Operator Eurofins Product Service GmbH / Mr. Treffke
Test Specification FCC part 15.247 (d)
Comment 1 Spurious Emissions conducted
Comment 2 Channel : 2441 MHz
Comment 3 8DPSK




Date: 7.APR.2014 16:08:18

Conducted spurious emissions – 3-DH5-Sngl F_{HIGH}


FCC part 15.247 (d)
Spurious Emissions

EUT Bluetooth headset
Model BTE7
Approval Holder GN Netcom A/S / GOM-1403-3710
Temperature / Voltage Tnom / Vnom
Test Site / Operator Eurofins Product Service GmbH / Mr. Treffke
Test Specification FCC part 15.247 (d)
Comment 1 Spurious Emissions conducted
Comment 2 Channel : 2480 MHz
Comment 3 8DPSK



Date: 7.APR.2014 16:11:47

3.10 Test Conditions and Results – Transmitter radiated emissions

Transmitter radiated emissions acc. FCC 47 CFR 15.247 / IC RSS-210				Verdict: PASS
Test according referenced standards	Reference Method			
	FCC 15.247(d) / IC RSS-210 A8.5			
Test according to measurement reference	Reference Method			
	FCC Public Notice DA 00-705 / ANSI C63.4			
Test frequency range	Tested frequencies			
	30 MHz – 10 th Harmonic			
Limits				
Frequency range [MHz]	Detector	Limit [μV/m]	Limit [dBμV/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)). When average radiated emission measurements are specified, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.				
Test setup				
				

Test procedure

1. EUT set to test mode (Communication tester is used if needed)
2. Span it set according to measurement range
3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz
4. Markers are set to peak emission levels within restricted bands

Test results – Internal Antenna


Channel	Frequency [MHz]	Mode	Emission [MHz]	Level [dBμV/m]	Det.	Pol.	Limit [dBμV/m]	Limit dist. [m]*	Margin [dB]
F _{LOW}	2402	3DH5-Sngl	2370	40.16	pk	hor	74.00	3	-33.84
F _{LOW}	2402	3DH5-Sngl	2370	31.80	RMS	hor	54.00	3	-22.20
F _{MID}	2441	3DH5-Sngl	4882	53.61	pk	ver	74.00	3	-20.39
F _{MID}	2441	3DH5-Sngl	4882	44.66	avg	ver	54.00	3	-09.34
F _{HIGH}	2480	DH5-Sngl	2483.5	48.99	pk	hor	74.00	3	-25.01
F _{HIGH}	2480	DH5-Sngl	2483.5	42.01	RMS	hor	54.00	3	-11.99
F _{HIGH}	2480	DH5-Sngl	2483.5	56.11	pk	ver	74.00	3	-17.89
F _{HIGH}	2480	DH5-Sngl	2483.5	49.40	RMS	ver	54.00	3	-04.60
F _{HIGH}	2480	DH5-Sngl	4960	53.37	pk	hor	74.00	3	-20.63
F _{HIGH}	2480	DH5-Sngl	4960	44.54	avg	hor	54.00	3	-09.46
F _{LOW}	2402	DH5-Sngl	2370	42.94	pk	hor	74.00	3	-31.06
F _{LOW}	2402	DH5-Sngl	2370	33.31	RMS	hor	54.00	3	-20.69
F _{LOW}	2402	DH5-Sngl	2713	42.32	pk	hor	74.00	3	-31.68
F _{LOW}	2402	DH5-Sngl	4804	53.81	pk	hor	74.00	3	-20.19
F _{LOW}	2402	DH5-Sngl	4804	48.65	avg	hor	54.00	3	-05.35
F _{LOW}	2402	DH5-Sngl	4804	55.80	pk	ver	74.00	3	-18.20
F _{LOW}	2402	DH5-Sngl	4804	49.90	avg	ver	54.00	3	-04.10
F _{MID}	2441	DH5-Sngl	4882	57.76	pk	hor	74.00	3	-16.24
F _{MID}	2441	DH5-Sngl	4882	53.32	avg	hor	54.00	3	-00.68
F _{MID}	2441	DH5-Sngl	4882	56.02	pk	ver	74.00	3	-17.98
F _{MID}	2441	DH5-Sngl	4882	51.08	avg	ver	54.00	3	-02.92
F _{MID}	2441	DH5-Sngl	7322	55.46	pk	ver	74.00	3	-18.54
F _{MID}	2441	DH5-Sngl	7322	45.83	avg	ver	54.00	3	-08.17
F _{HIGH}	2480	DH5-Sngl	2483.5	55.17	pk	hor	74.00	3	-18.83
F _{HIGH}	2480	DH5-Sngl	2483.5	49.49	RMS	hor	54.00	3	-04.51
F _{HIGH}	2480	DH5-Sngl	2483.5	56.86	pk	ver	74.00	3	-17.14
F _{HIGH}	2480	DH5-Sngl	2483.5	50.67	RMS	ver	54.00	3	-03.33
F _{HIGH}	2480	DH5-Sngl	4960	58.16	pk	hor	74.00	3	-15.84

Test Report No.: G0M-1403-3710-TFC247BT-V01

Eurofins Product Service GmbH
Storkower Str. 38c, D-15526 Reichenwalde, Germany

F _{HIGH}	2480	DH5-Sngl	4960	53.34	avg	hor	54.00	3	-00.66
F _{HIGH}	2480	DH5-Sngl	4960	57.42	pk	ver	74.00	3	-16.58
F _{HIGH}	2480	DH5-Sngl	4960	52.68	avg	ver	54.00	3	-01.32
F _{HIGH}	2480	DH5-Sngl	7439	55.32	pk	ver	74.00	3	-18.68
F _{HIGH}	2480	DH5-Sngl	7439	46.13	avg	ver	54.00	3	-07.87
Comments: * Physical distance between EUT and measurement antenna.									

3.11 Test Conditions and Results – Receiver radiated emissions

Receiver radiated emissions acc. IC RSS-210				Verdict: PASS
Test according referenced standards	Reference Method			
	IC RSS-210 A8.5			
Test according to measurement reference	Reference Method			
	ANSI C63.4			
Test frequency range	Tested frequencies			
	30 MHz – 3 th Harmonic			
EUT test mode	Receive			
Limits				
Frequency range [MHz]	Detector	Limit [μV/m]	Limit [dBμV/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
Test setup				
				

Test procedure						
1. EUT set to receive mode (Communication tester is used if needed) 2. Span it set according to measurement range 3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz 4. Markers are set to peak emission levels						
Test results						
Channel	Frequency [MHz]	Emission [MHz]	Emission Level [db μ V/m]	Det.	Limit [db μ V/m]	Margin [μ V/m]
F _{LOW} - F _{HIGH}	scan mode	7.968	49.26**	pk	53.9	-4.64 dB
Comments: * Physical distance between EUT and measurement antenna. ** Emission level corresponds to ambient noise floor						


ANNEX A Transmitter radiated spurious emissions

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	BTE7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	TX; DH5; GFSK; 2402 MHz
Test Date:	2014-04-09
Note:	worst case

Index 37




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	BTE7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	TX; DH5; GFSK; 2402 MHz
Test Date:	2014-04-09
Note:	worst case

Index 38




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	BTE7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	TX; DH5; GFSK; 2402 MHz
Test Date:	2014-04-09
Note:	worst case

Index 35




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	BTE7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	TX; DH5; GFSK; 2402 MHz
Test Date:	2014-04-09
Note:	worst case

Index 36




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 5




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.713 GHz	42.32 dBμV/m	74 dBμV/m	-31.68 dB	Pass

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 9




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note: lower bandedge

Index 7




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.37 GHz	42.94 dBμV/m	74 dBμV/m	-31.06 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.37 GHz	33.31 dBμV/m	54 dBμV/m	-20.69 dB	Pass

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note: lower bandedge

Index 10




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 8




Frequency 4.804 GHz	Peak 53.81 dBμV/m	Peak Limit 74 dBμV/m	Peak Difference -20.19 dB	Peak Status Pass
Frequency 4.804 GHz	Average 48.65 dBμV/m	Average Limit 54 dBμV/m	Average Difference -5.35 dB	Average Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 11



Frequency 4.804 GHz	Peak 55.8 dBμV/m	Peak Limit 74 dBμV/m	Peak Difference -18.2 dB	Peak Status Pass
Frequency 4.804 GHz	Average 49.9 dBμV/m	Average Limit 54 dBμV/m	Average Difference -4.1 dB	Average Status Pass

Test Report No.: GOM-1403-3710-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 100 cm converted to 3m
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 23




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 100 cm converted to 3m
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 25




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Rohde & Schwarz HL 025, Horizontal
 Measurement distance: 100 cm
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 24




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Rohde & Schwarz HL 025, Vertical
 Measurement distance: 100 cm
 Mode: TX; DH5; GFSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 26




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 12




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 14




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 13



Frequency 4.882 GHz	Peak 57.76 dBμV/m	Peak Limit 74 dBμV/m	Peak Difference -16.24 dB	Peak Status Pass
Frequency 4.882 GHz	Average 53.32 dBμV/m	Average Limit 54 dBμV/m	Average Difference -0.68 dB	Average Status Pass

Test Report No.: G0M-1403-3710-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 15



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.882 GHz	56.02 dBμV/m	74 dBμV/m	-17.98 dB	Pass
7.322 GHz	55.46 dBμV/m	74 dBμV/m	-18.54 dB	Pass

Frequency	Average	Average Limit	Average Difference	Average Status
4.882 GHz	51.08 dBμV/m	54 dBμV/m	-2.92 dB	Pass
7.322 GHz	45.83 dBμV/m	54 dBμV/m	-8.17 dB	Pass

Test Report No.: G0M-1403-3710-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 100 cm converted to 3m
 Mode: TX; DH5; GFSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 27




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 100 cm converted to 3m
 Mode: TX; DH5; GFSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 29




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Rohde & Schwarz HL 025, Horizontal
 Measurement distance: 100 cm
 Mode: TX; DH5; GFSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 28




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Rohde & Schwarz HL 025, Vertical
 Measurement distance: 100 cm
 Mode: TX; DH5; GFSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 30




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 16




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 20




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
EUT Name: Bluetooth headset
Model: BTE7
Test Site: Eurofins Product Service GmbH
Operator: Mr. Treffke
Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
Antenna: Schwarzbeck BBHA 9120D, Horizontal
Measurement distance: 3 m
Mode: TX; DH5; GFSK; 2480 MHz
Test Date: 2014-04-09
Note: upper bandedge

Index 17




Frequency 2.4835 GHz	Peak 55.17 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -18.83 dB	Peak Status Pass
Frequency 2.4835 GHz	RMS 49.49 dBµV/m	RMS Limit 54 dBµV/m	RMS Difference -4.51 dB	RMS Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2480 MHz
 Test Date: 2014-04-09
 Note: upper bandedge

Index 21




Frequency 2.4835 GHz	Peak 56.86 dBμV/m	Peak Limit 74 dBμV/m	Peak Difference -17.14 dB	Peak Status Pass
Frequency 2.4835 GHz	RMS 50.67 dBμV/m	RMS Limit 54 dBμV/m	RMS Difference -3.33 dB	RMS Status Pass

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; DH5; GFSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 19



Frequency 4.96 GHz	Peak 58.16 dBµV/m	Peak Limit 74 dBµV/m	Peak Difference -15.84 dB	Peak Status Pass
Frequency 4.96 GHz	Average 53.34 dBµV/m	Average Limit 54 dBµV/m	Average Difference -0.66 dB	Average Status Pass

Test Report No.: G0M-1403-3710-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
EUT Name: Bluetooth headset
Model: BTE7
Test Site: Eurofins Product Service GmbH
Operator: Mr. Treffke
Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
Antenna: Schwarzbeck BBHA 9120D, Vertical
Measurement distance: 3 m
Mode: TX; DH5; GFSK; 2480 MHz
Test Date: 2014-04-09
Note:

Index 22



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
4.96 GHz	57.42 dBμV/m	74 dBμV/m	-16.58 dB	Pass
7.439 GHz	55.32 dBμV/m	74 dBμV/m	-18.68 dB	Pass


Frequency	Average	Average Limit	Average Difference	Average Status
4.96 GHz	52.68 dBμV/m	54 dBμV/m	-1.32 dB	Pass
7.439 GHz	46.13 dBμV/m	54 dBμV/m	-7.87 dB	Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 100 cm converted to 3m
 Mode: TX; DH5; GFSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 31




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 100 cm converted to 3m
 Mode: TX; DH5; GFSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 33




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Rohde & Schwarz HL 025, Horizontal
 Measurement distance: 100 cm
 Mode: TX; DH5; GFSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 32




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Rohde & Schwarz HL 025, Vertical
 Measurement distance: 100 cm
 Mode: TX; DH5; GFSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 34




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 39




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 42




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2402 MHz
 Test Date: 2014-04-09
 Note: lower bandedge

Index 40



Frequency 2.37 GHz	Peak 40.16 dBμV/m	Peak Limit 74 dBμV/m	Peak Difference -33.84 dB	Peak Status Pass
Frequency 2.37 GHz	RMS 31.8 dBμV/m	RMS Limit 54 dBμV/m	RMS Difference -22.2 dB	RMS Status Pass

Test Report No.: GOM-1403-3710-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2402 MHz
 Test Date: 2014-04-09
 Note: lower bandedge

Index 43




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 41




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2402 MHz
 Test Date: 2014-04-09
 Note:

Index 44




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 45




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 47




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 46




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2441 MHz
 Test Date: 2014-04-09
 Note:

Index 48



Frequency 4.882 GHz	Peak 53.61 dBμV/m	Peak Limit 74 dBμV/m	Peak Difference -20.39 dB	Peak Status Pass
Frequency 4.882 GHz	Average 44.66 dBμV/m	Average Limit 54 dBμV/m	Average Difference -9.34 dB	Average Status Pass

Test Report No.: GOM-1403-3710-TFC247BT-V01


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 49




Spurious emissions according to FCC 15.247

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 52




Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2480 MHz
 Test Date: 2014-04-09
 Note: upper bandedge

Index 50




Frequency 2.4835 GHz	Peak 48.99 dBμV/m	Peak Limit 74 dBμV/m	Peak Difference -25.01 dB	Peak Status Pass
Frequency 2.4835 GHz	RMS 42.01 dBμV/m	RMS Limit 54 dBμV/m	RMS Difference -11.99 dB	RMS Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2480 MHz
 Test Date: 2014-04-09
 Note: upper bandedge

Index 53




Frequency 2.4835 GHz	Peak 56.11 dBμV/m	Peak Limit 74 dBμV/m	Peak Difference -17.89 dB	Peak Status Pass
Frequency 2.4835 GHz	RMS 49.4 dBμV/m	RMS Limit 54 dBμV/m	RMS Difference -4.6 dB	RMS Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 51




Frequency 4.96 GHz	Peak 53.37 dBμV/m	Peak Limit 74 dBμV/m	Peak Difference -20.63 dB	Peak Status Pass
Frequency 4.96 GHz	Average 44.54 dBμV/m	Average Limit 54 dBμV/m	Average Difference -9.46 dB	Average Status Pass

Spurious emissions according to FCC 15.247

Project number: GOM-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; 3DH5; 8DPSK; 2480 MHz
 Test Date: 2014-04-09
 Note:

Index 54




ANNEX B Receiver radiated spurious emissions

Spurious emissions according to RSS-GEN

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Rohde & Schwarz HK 116, Horizontal
 Measurement distance: 3 m
 Mode: RX; scan mode
 Test Date: 2014-04-09
 Note:

Index 62




Spurious emissions according to RSS-GEN

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Rohde & Schwarz HK 116, Vertical
 Measurement distance: 3 m
 Mode: RX; scan mode
 Test Date: 2014-04-09
 Note:

Index 63




Spurious emissions according to RSS-GEN

Project number: G0M-1403-3710

Applicant:	GN Netcom A/S
EUT Name:	Bluetooth headset
Model:	BTE7
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	RX; scan mode
Test Date:	2014-04-09
Note:	

Index 60




Spurious emissions according to RSS-GEN

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Rohde & Schwarz HL 223, Vertical
 Measurement distance: 3 m
 Mode: RX; scan mode
 Test Date: 2014-04-09
 Note:

Index 61




Spurious emissions according to RSS-GEN

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: RX; scan mode
 Test Date: 2014-04-09
 Note:

Index 55




Spurious emissions according to RSS-GEN

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: RX; scan mode
 Test Date: 2014-04-09
 Note:

Index 58




Spurious emissions according to RSS-GEN

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: RX; scan mode
 Test Date: 2014-04-09
 Note:

Index 56




Spurious emissions according to RSS-GEN

Project number: G0M-1403-3710

Applicant: GN Netcom A/S
 EUT Name: Bluetooth headset
 Model: BTE7
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC rechargeable battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: RX; scan mode
 Test Date: 2014-04-09
 Note:

Index 59



Frequency	Peak	Peak Limit	Peak Difference	Status
7.968 GHz	49.26 dBµV/m	53.9 dBµV/m	-4.64 dB	Pass