



FCC CERTIFICATION TEST REPORT

Applicant	:	Dong Guan Jia Sheng Lighting Technology Co. Ltd.
Address of Applicant	:	HUMEN TOWN, SHUTIAN VILLAGE, DONGGUAN, GUANGDONG
Manufacturer	:	Dong Guan Jia Sheng Lighting Technology Co. Ltd.
Address of Manufacturer	:	HUMEN TOWN, SHUTIAN VILLAGE, DONGGUAN, GUANGDONG
Equipment under Test	:	LED LanternSpeaker ULTIMA
Model No.	:	SP0000113-01
FCC ID	:	2AZYT-SP0000113-01
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10:2020
Report No.	:	DDT-RE24112815-1E01
Issue Date	:	2024/12/14
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	10
2.6.	Test environment conditions	10
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	20 dB Bandwidth	13
4.1.	Block diagram of test setup	13
4.2.	Limits	13
4.3.	Test procedure	13
4.4.	Test result	14
4.5.	Test graphs	15
5.	99% Bandwidth	17
5.1.	Block diagram of test setup	17
5.2.	Limits	17
5.3.	Test procedure	17
5.4.	Test result	18
5.5.	Test graphs	19
6.	Maximum Peak Output Power	21
6.1.	Block diagram of test setup	21
6.2.	Limits	21
6.3.	Test procedure	21
6.4.	Test result	22
6.5.	Test graphs	23
7.	Carrier Frequency Separation	25
7.1.	Block diagram of test setup	25
7.2.	Limits	25
7.3.	Test procedure	25
7.4.	Test result	26
7.5.	Test graphs	27
8.	Dwell Time	28

8.1.	Block diagram of test setup	28
8.2.	Limits.....	28
8.3.	Test procedure.....	28
8.4.	Test result	29
8.5.	Test graphs.....	30
9.	Number of Hopping Channel.....	34
9.1.	Block diagram of test setup	34
9.2.	Limits.....	34
9.3.	Test procedure.....	34
9.4.	Test result	35
9.5.	Test graphs.....	36
10.	Band Edge Compliance (Conducted Method).....	37
10.1.	Block diagram of test setup	37
10.2.	Limit.....	37
10.3.	Test procedure.....	37
10.4.	Test result	38
10.5.	Test graphs.....	39
11.	RF Conducted Spurious Emissions.....	42
11.1.	Block diagram of test setup	42
11.2.	Limits.....	42
11.3.	Test procedure.....	42
11.4.	Test result	43
11.5.	Test graphs.....	44
12.	Duty cycle	50
12.1.	Block diagram of test setup	50
12.2.	Limit.....	50
12.3.	Test procedure.....	50
12.4.	Test result	51
12.5.	Test graphs.....	52
13.	Antenna Requirements	54
13.1.	Limit.....	54
13.2.	Result.....	54
14.	Radiated Emission.....	55
14.1.	Test equipment	55
14.2.	Block diagram of test setup	56
14.3.	Limits.....	57
14.4.	Assistant equipment used for test	58
14.5.	Test procedure.....	58

14.6.	Test result	60
14.7.	Test data	61
15.	Band Edge Compliance	69
15.1.	Test equipment	69
15.2.	Block diagram of test setup	70
15.3.	Limits	70
15.4.	Assistant equipment used for test	70
15.5.	Test procedure	70
15.6.	Test result	70
15.7.	Test data	71
16.	Power Line Conducted Emissions	75
16.1.	Test equipment	75
16.2.	Block diagram of test setup	75
16.3.	Limits	75
16.4.	Assistant equipment used for test	76
16.5.	Test procedure	76
16.6.	Test result	76
16.7.	Test data	77
17.	Test Setup Photograph	79
18.	Photos of the EUT	81

Test Report Declare

Applicant	:	Dong Guan Jia Sheng Lighting Technology Co. Ltd.
Address of Applicant	:	HUMEN TOWN, SHUTIAN VILLAGE, DONGGUAN, GUANGDONG
Equipment under Test	:	LED LanternSpeaker ULTIMA
Model No.	:	SP0000113-01
Manufacturer	:	Dong Guan Jia Sheng Lighting Technology Co. Ltd.
Address of Manufacturer	:	HUMEN TOWN, SHUTIAN VILLAGE, DONGGUAN, GUANGDONG

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10:2020

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24112815-1E01		
Date of Receipt:	2024/11/29	Date of Test:	2024/11/29 - 2024/12/13

Prepared By:

Jacky Huang

Jacky Huang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/12/14	

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	Maximum Peak Output Power	FCC Part 15: 15.247(b)(1),	/	Pass
2	20 dB Bandwidth	FCC Part 15: 15.247(a)(1),	/	Pass
3	Carrier Frequency Separation	FCC Part 15: 15.247(a)(1),	/	Pass
4	Number of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii),	/	Pass
5	Dwell Time	FCC Part 15: 15.247(a)(1)(iii),	/	Pass
6	RF Conducted Spurious Emissions	FCC Part 15: 15.247(d),	/	Pass
7	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d),	/	Pass
8	Band Edge Compliance	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d),	/	Pass
9	Power Line Conducted Emissions	FCC Part 15: 15.207(a),	/	Pass
10	Antenna Requirement	FCC Part 15: 15.203,	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: LED LanternSpeaker ULTIMA
Model Number	: SP0000113-01
Difference of model number	: /
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 5V/2A from USB type-C port or DC 3.7V from Li-ion battery
Hardware Version	: /
Software Version	: /
Antenna Type	: PCB antenna
Max Antenna Gain (dBi)	: -0.58

Note: This EUT support Bluetooth BR/EDR, this report only for Bluetooth BR/EDR.

Radio Specification	: Bluetooth BR/EDR
Operation Frequency	: 2402 MHz-2480 MHz
Modulation	: GFSK, $\pi/4$ DQPSK

Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475


20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: FCC_assist_1.0.2.2.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5 dB (According to the manufacturer's claims)

Tested mode, channel, information			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK hopping on Tx mode	10	CH0 to CH78	2402 to 2480
$\pi/4$ DQPSK hopping on Tx mode	10	CH0 to CH78	2402 to 2480
GFSK hopping off Tx mode	10	CH0	2402
	10	CH39	2441
	10	CH78	2480
$\pi/4$ DQPSK hopping off Tx mode	10	CH0	2402
	10	CH39	2441
	10	CH78	2480
Worst-case data rates were: GFSK mode: DH5, $\pi/4$ DQPSK mode: 2DH5.			

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method)
	5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
	1.66 dB ($8 \text{ GHz} \leq f < 26.5 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz)
	4.40 dB (6 GHz - 18 GHz)
	3.54 dB (18 GHz - 26 GHz)
	4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date	Cal. Interval
☒ RF Connected Test (RF Measurement System 2#)					
SPECTRUM ANALYZER	R&S	FSU26	201124	2025/07/08	1 Year
Power Sensor	R&S	NRP-Z22	101254	2025/07/08	1 Year
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A	N/A

4. 20 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 6.9.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 20 dB bandwidth measurement:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 2 times and 5 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold


- (5) Measure and record the results in the report.


4.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 2#
Ambient Condition:	24.3℃, 46.2%RH	Test Date:	2024.12.06-2024.12.06
Test Power Supply:	DC 5V	Sample Number:	S24112815-002

Test Mode	Antenna	Frequency [MHz]	20dB EBW [MHz]
DH5	Ant1	2402	0.96
		2441	0.95
		2480	0.95
2DH5	Ant1	2402	1.29
		2441	1.29
		2480	1.28


4.5. Test graphs





5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% bandwidth measurement:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Measure and record the results in the report.

5.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 2#
Ambient Condition:	24.3℃, 46.2%RH	Test Date:	2024.12.06-2024.12.06
Test Power Supply:	DC 5V	Sample Number:	S24112815-002

Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]
DH5	Ant1	2402	0.870	2401.5740	2402.4440
		2441	0.861	2440.5770	2441.4380
		2480	0.867	2479.5770	2480.4440
2DH5	Ant1	2402	1.179	2401.4210	2402.6000
		2441	1.179	2440.4210	2441.6000
		2480	1.179	2479.4210	2480.6000

DH5 Ant1 2402

Ref 20 dBm Att 20 dB SWT 15 ms Marker 1 [T1] -4.87 dBm

OBW8 0.000000000 kHz Temp 1 [T1 OBW] -23.23 dBm

2.401574000 GHz -23.08 dBm

2.402444000 GHz

Center 2.402 GHz 300 kHz/ Span 3 MHz

Date: 6.DEC.2024 10:00:46

DH5 Ant1 2441

Ref 20 dBm Att 20 dB SWT 15 ms Marker 1 [T1] -5.28 dBm

OBW8 1.000000000 kHz Temp 1 [T1 OBW] -23.72 dBm

2.440574000 GHz -23.44 dBm

2.441434000 GHz

Center 2.441 GHz 300 kHz/ Span 3 MHz

Date: 6.DEC.2024 10:02:20

DH5 Ant1 2480

Ref 20 dBm Att 20 dB SWT 15 ms Marker 1 [T1] -6.11 dBm


OBW8 7.000000000 kHz Temp 1 [T1 OBW] -23.44 dBm

2.479574000 GHz -23.43 dBm

2.480444000 GHz

Center 2.48 GHz 300 kHz/ Span 3 MHz

Date: 6.DEC.2024 10:03:48



2DH5 Ant1 2480

Ref 20 dBm

Att 20 dB

RBW 30 kHz

VBW 100 kHz

SWT 15 ms

Marker 1 [T1]

-6.03 dBm

2.480174000 GHz

20 Offset 1.5 dB

1.179000000 MHz

Temp 1 [T1 OSW]

-22.58 dBm

2.479420000 GHz

Temp 2 [T1 OSW]

-21.64 dBm

2.480600000 GHz


1VL

Center 2.48 GHz 300 kHz/ Span 3 MHz

Date: 6.DEC.2024 10:13:01

6. Maximum Peak Output Power

6.1. Block diagram of test setup



6.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

6.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 7.8.5.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	> 20 dB bandwidth of the emission being measured.
VBW:	VBW $\geq$ RBW.
Span:	Approximately five times the 20 dB bandwidth, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-to-peak function to set the marker to the peak of the emission and record the results in the report.


6.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 2#				
Ambient Condition:	24.3℃, 46.2%RH	Test Date:	2024.12.06-2024.12.06				
Test Power Supply:	DC 5V	Sample Number:	S24112815-002				

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
DH5	Ant1	2402	-1.93	≤20.97	-2.51	≤30	PASS
		2441	-2.39	≤20.97	-2.97	≤30	PASS
		2480	-3.21	≤20.97	-3.79	≤30	PASS
2DH5	Ant1	2402	-1.51	≤20.97	-2.09	≤30	PASS
		2441	-1.88	≤20.97	-2.46	≤30	PASS
		2480	-2.66	≤20.97	-3.24	≤30	PASS


6.5.Test graphs





7. Carrier Frequency Separation

7.1. Block diagram of test setup



7.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

7.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 7.8.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	approximately 30% of the channel spacing
VBW:	$VBW \geq RBW$.
Span:	Wide enough to capture the peaks of two adjacent channels.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-delta function to determine the separation between the peaks of the adjacent channels and record the results in the report.

7.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 2#		
Ambient Condition:	24.3℃, 46.2%RH	Test Date:	2024.12.06-2024.12.06		
Test Power Supply:	DC 5V	Sample Number:	S24112815-002		


Test Mode	Antenna	Frequency [MHz]	Result [MHz]	Limit [MHz]	Verdict
DH5	Ant1	Hop	0.997	≥0.640	PASS
2DH5	Ant1	Hop	0.990	≥0.860	PASS

7.5.Test graphs



8. Dwell Time

8.1. Block diagram of test setup



8.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

8.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 7.8.4.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	$\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$
VBW:	$VBW \geq RBW$.
Span:	Zero span, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Clear Write.
- (5) The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
- (6) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula Dwell time = total hops * pulse's on time.
- (7) Measure and record the results in the report.

8.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 2#
Ambient Condition:	24.3℃, 46.2%RH	Test Date:	2024.12.06-2024.12.06
Test Power Supply:	DC 5V	Sample Number:	S24112815-002

Test Mode	Antenna	Frequency [MHz]	Burst Width [ms]	Total Hops [Num]	Result [s]	Limit [s]	Verdict
DH1	Ant1	Hop	0.360	321	0.116	≤0.4	PASS
DH3	Ant1	Hop	1.605	151	0.242	≤0.4	PASS
DH5	Ant1	Hop	2.870	113	0.324	≤0.4	PASS
2DH1	Ant1	Hop	0.360	320	0.115	≤0.4	PASS
2DH3	Ant1	Hop	1.620	153	0.248	≤0.4	PASS
2DH5	Ant1	Hop	2.880	110	0.317	≤0.4	PASS

8.5.Test graphs



DH3 Ant1 Hop

Ref 20 dBm

Offset 1.5 dB

Att 20 dB

RBW 500 kHz

VSW 3 MHz

SWT 31.6 s

Marker 1 [T1]

-5.12 dBm

1.605000 ms

1 sec

0.000000

20

10

0

-10

-20

-30

-40

-50

-60

-70

-80

20

10

0

-10

-20

-30

-40

-50

-60

-70

-80

Center 2.441 GHz

3.16 s/

20

10

0

-10

-20

-30

-40

-50

-60

-70

-80

20

10

0

-10

-20

-30

-40

-50

-60

-70

-80

Center 2.441 GHz

3.16 s/

Date: 6.DEC.2024 11:16:32

DH3 Ant1 Hop

Ref 20 dBm

Offset 1.5 dB

Att 20 dB

RBW 1 MHz

VSW 3 MHz

SWT 15 ms

Delta 2 [T1]

-0.69 dB

1.605000 ms

Marker 1 [T1]

-5.12 dBm

1.605000 μ s

1 sec

0.000000

20

10

0

-10

-20

-30

-40

-50

-60

-70

-80

20

10

0

-10

-20

-30

-40

-50

-60

-70

-80

Center 2.441 GHz

1.5 ms/

20

10

0

-10

-20

-30

-40

-50

-60

-70

-80

20

10

0

-10

-20

-30

-40

-50

-60


-70

-80



Center 2.441 GHz

1.5 ms/


Date: 6.DEC.2024 11:06:04





DH5_Ant1_Hop








2DH5_Ant1_Hop



9. Number of Hopping Channel

9.1. Block diagram of test setup



9.2. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

9.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 7.8.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW: RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW: $VBW \geq RBW$.

Span: The frequency band of operation

Detector Mode: Peak

Sweep time: Auto

Trace mode: Max hold

- (5) Measure the hopping number and record the results in the report.
- (6) Measure and record the results in the report.

9.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 2#		
Ambient Condition:	24.3℃, 46.2%RH	Test Date:	2024.12.06-2024.12.06		
Test Power Supply:	DC 5V	Sample Number:	S24112815-002		


Test Mode	Antenna	Frequency [MHz]	Result [Num]	Limit [Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS

9.5. Test graphs



10. Band Edge Compliance (Conducted Method)

10.1. Block diagram of test setup



10.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

10.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.

10.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 2#
Ambient Condition:	24.3℃, 46.2%RH	Test Date:	2024.12.06-2024.12.06
Test Power Supply:	DC 5V	Sample Number:	S24112815-002

Mode	Frequency (MHz)	Verdict
DH5	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass
2DH5	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass

DH5 Ant1_Low 2402

Ref 20 dBm *Att 20 dB SWF 10 ms Marker 4 [T1] -50.23 dBm

*RBW 100 kHz *VBW 300 kHz

20 Offset 1.5 dB

Marker 1 [T1] -2.53 dBm 2.401981179 GHz

Marker 2 [T1] -54.14 dBm 2.400000000 GHz

Marker 3 [T1] -54.30 dBm 2.390000000 GHz

Start 2.31 GHz 10 MHz/ Stop 2.41 GHz

Date: 6.DEC.2024 10:00:56

DH5 Ant1_High 2480

Ref 20 dBm *Att 20 dB SWF 15 ms Marker 4 [T1] -50.58 dBm

*RBW 100 kHz *VBW 300 kHz

20 Offset 1.5 dB

Marker 1 [T1] -4.43 dBm 2.480048077 GHz

Marker 2 [T1] -50.58 dBm 2.483509615 GHz

Marker 3 [T1] -54.87 dBm 2.500000000 GHz

Start 2.47 GHz 3 MHz/ Stop 2.5 GHz

Date: 6.DEC.2024 10:03:58

DH5 Ant1_Low Hop 2402

Ref 20 dBm *Att 20 dB SWF 10 ms Marker 4 [T1] -51.52 dBm

*RBW 100 kHz *VBW 300 kHz

20 Offset 1.5 dB



Marker 1 [T1] -2.50 dBm 2.405924990 GHz

Marker 2 [T1] -51.71 dBm 2.400000000 GHz

Marker 3 [T1] -57. 2.390000000 GHz

Start 2.31 GHz 10 MHz/ Stop 2.41 GHz

Date: 6.DEC.2024 10:20:10





11. RF Conducted Spurious Emissions

11.1. Block diagram of test setup

Same as 10.1

11.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

11.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{Span/RBW}$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold


(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

11.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 2#
Ambient Condition:	24.3℃, 46.2%RH	Test Date:	2024.12.06-2024.12.06
Test Power Supply:	DC 5V	Sample Number:	S24112815-002

Mode	Frequency (MHz)	Verdict
DH5	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass
2DH5	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass

11.5. Test graphs














2DH5_Ant1_2480_1000~26500

Ref 20 dBm

Offset 1.5 dB

Att 20 dB

RBW 100 kHz

VBW 300 kHz

SWT 2.6 s

Marker 1 [T1]

-52.90 dBm

9.913950000 GHz

Marker 2 [T1]

-1.83 dBm

2.479850000 GHz

Start 1 GHz


2.55 GHz/

Stop 26.5 GHz

Date: 6.DEC.2024 10:13:50

12. Duty cycle

12.1. Block diagram of test setup



12.2. Limit

Just for Report.

12.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.

set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the middle hopping channel.

Resolution BW: 10 MHz.

Video BW: 10 MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Clear Write.

Sweep: Video Trigger

- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

- (3) Calculate dwell time follow below formula:


Duty cycle= Pulse's on time / Burst cycle



12.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 2#
Ambient Condition:	24.3℃, 46.2%RH	Test Date:	2024.12.06-2024.12.06
Test Power Supply:	DC 5V	Sample Number:	S24112815-002

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor [dB]
DH5	Ant1	2402	2.89	3.77	76.66	1.15
		2441	2.89	3.77	76.66	1.15
		2480	2.89	3.77	76.66	1.15
2DH5	Ant1	2402	2.90	3.77	76.92	1.14
		2441	2.90	3.77	76.92	1.14
		2480	2.90	3.76	77.13	1.13

12.5. Test graphs





13. Antenna Requirements

13.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

13.2. Result



The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


14. Radiated Emission

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31	1 Year
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22	1 Year
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18	2 Year
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31	1 Year
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31	1 Year
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31	1 Year
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/	/
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31	1 Year
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31	1 Year
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22	1 Year
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11	2 Year
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22	1 Year
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26	1 Year
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11	1 Year
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/08/25	1 Year

14.2. Block diagram of test setup





14.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak) 54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

14.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna (1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna (18 GHz-40 GHz)	1 m

According ANSI C63.10:2020 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2020 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2020 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with GFSK, $\pi/4$ DQPSK, the worst case is record and reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

14.6. Test result

PASS. (See below detailed test result)

14.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24112815-1E\FCC BELOW 1G\20241205-205811_H

Memo:

Sample Numbler:S24112815-001 Power Setting:10



Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.084	39.66	10.31	3.76	22.63	40.00	17.37	QP	Horizontal
2	49.981	29.4	12.99	3.88	15.17	40.00	24.83	QP	Horizontal
3	69.443	35.16	10.19	4.02	18.27	40.00	21.73	QP	Horizontal
4	119.991	35.86	10.00	4.33	19.07	43.50	24.43	QP	Horizontal
5	318.666	25.75	13.87	5.29	13.50	46.00	32.50	QP	Horizontal
6	563.517	24.7	17.82	6.24	17.26	46.00	28.74	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24112815-1E\FCC BELOW 1G\20241205-205859_V

Memo:

Sample Numbel:S24112815-001 Power Setting:10



Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.042	38.47	10.30	3.76	21.43	40.00	18.57	QP	Vertical
2	49.981	35.83	12.99	3.88	21.60	40.00	18.40	QP	Vertical
3	72.528	42.95	9.39	4.04	25.28	40.00	14.72	QP	Vertical
4	119.991	34.94	10.00	4.33	18.15	43.50	25.35	QP	Vertical
5	238.211	23.95	11.66	4.94	9.27	46.00	36.73	QP	Vertical
6	370.516	30.8	15.76	5.50	20.62	46.00	25.38	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5 2402MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G\1

Memo:

Sample Numble:S24112815-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3830.500	47.06	30.82	5.08	-39.64	43.32	74.00	30.68	PK	Horizontal
2	4801.200	53.37	32.53	5.53	-39.62	51.81	74.00	22.19	PK	Horizontal
3	7410.700	43.73	36.68	6.66	-40.63	46.44	74.00	27.56	PK	Horizontal
4	11174.500	42.29	39.23	8.24	-39.17	50.59	74.00	23.41	PK	Horizontal
5	16007.600	40.15	37.99	10.15	-39.41	48.88	74.00	25.12	PK	Horizontal
6	17813.000	37.01	40.94	12.66	-40.02	50.59	74.00	23.41	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5 2402MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G\2

Memo:

Sample Numbler:S24112815-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3901.900	46.45	31.20	5.07	-39.66	43.06	74.00	30.94	PK	Vertical
2	4801.200	48.63	32.53	5.53	-39.62	47.07	74.00	26.93	PK	Vertical
3	7507.600	44.25	36.48	6.71	-40.54	46.90	74.00	27.10	PK	Vertical
4	9143.000	41.62	38.50	7.35	-38.91	48.56	74.00	25.44	PK	Vertical
5	11312.200	42.48	39.21	8.33	-39.31	50.71	74.00	23.29	PK	Vertical
6	16053.500	41.36	37.95	10.16	-39.44	50.03	74.00	23.97	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5 2441MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G\3

Memo:

Sample Numbel:S24112815-001 Power Setting:10

Test Graph



Data List											
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	3893.400	47.29	31.16	5.07	-39.65	43.87	74.00	30.13	PK	Horizontal	
2	4879.400	52.63	33.33	5.58	-39.61	51.93	74.00	22.07	PK	Horizontal	
3	7628.300	44.34	36.56	6.77	-40.43	47.24	74.00	26.76	PK	Horizontal	
4	9098.800	42.44	38.50	7.33	-38.88	49.39	74.00	24.61	PK	Horizontal	
5	12080.600	42.43	39.28	8.80	-39.98	50.53	74.00	23.47	PK	Horizontal	
6	17870.800	36.90	41.58	12.82	-40.01	51.29	74.00	22.71	PK	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5 2441MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G4

Memo:

Sample Numble:S24112815-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3828.800	47.45	30.82	5.08	-39.64	43.71	74.00	30.29	PK	Vertical
2	4879.400	49.44	33.33	5.58	-39.61	48.74	74.00	25.26	PK	Vertical
3	7359.700	43.70	36.78	6.63	-40.68	46.43	74.00	27.57	PK	Vertical
4	10746.100	42.12	39.40	8.00	-39.15	50.37	74.00	23.63	PK	Vertical
5	12294.800	41.75	39.30	8.91	-39.94	50.02	74.00	23.98	PK	Vertical
6	17714.400	38.04	40.46	12.38	-40.03	50.85	74.00	23.15	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5 2480MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G\5

Memo:

Sample Numble:S24112815-001 Power Setting:10

Test Graph



Data List											
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	3869.600	47.08	31.02	5.07	-39.65	43.52	74.00	30.48	PK	Horizontal	
2	4957.600	51.22	33.12	5.62	-39.60	50.36	74.00	23.64	PK	Horizontal	
3	7434.500	44.56	36.63	6.67	-40.61	47.25	74.00	26.75	PK	Horizontal	
4	11288.400	41.87	39.20	8.31	-39.29	50.09	74.00	23.91	PK	Horizontal	
5	15657.400	40.96	38.54	9.92	-39.40	50.02	74.00	23.98	PK	Horizontal	
6	17782.400	37.31	40.73	12.57	-40.02	50.59	74.00	23.41	PK	Horizontal	

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5 2480MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G\6

Memo:

Sample Numbler:S24112815-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3847.500	46.87	30.89	5.08	-39.64	43.20	74.00	30.80	PK	Vertical
2	4957.600	47.28	33.12	5.62	-39.60	46.42	74.00	27.58	PK	Vertical
3	7415.800	43.14	36.67	6.66	-40.63	45.84	74.00	28.16	PK	Vertical
4	11511.100	43.48	39.18	8.45	-39.51	51.60	74.00	22.40	PK	Vertical
5	15749.200	40.82	38.40	9.98	-39.40	49.80	74.00	24.20	PK	Vertical
6	17831.700	35.91	41.15	12.71	-40.02	49.75	74.00	24.25	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

15. Band Edge Compliance

15.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18	2 Year
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22	1 Year
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31	1 Year
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31	1 Year
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22	1 Year
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11	2 Year
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/08/25	1 Year
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26	1 Year
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31	1 Year
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31	1 Year
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31	1 Year
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/	/
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31	1 Year
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/	/
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11	1 Year
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31	1 Year

15.2. Block diagram of test setup



15.3. Limits

All restriction band should comply with 15.209, other emission should be at least 20 dB below the fundamental.

15.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

15.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report. According to the results of the radiated Emission test, it can be judged that the Horizontal direction is the Worst case.

15.6. Test result

PASS. (See below detailed test result)

15.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5 2480MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G\7

Memo:

Sample Numbler:S24112815-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	17.56	27.53	3.62	0.00	48.71	74.00	25.29	PK	Horizontal
2	2484.172	18.44	27.54	3.62	0.00	49.60	74.00	24.40	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX 2DH5 2480MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G\8

Memo:

Sample Numbel:S24112815-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	16.82	27.53	3.62	0.00	47.97	74.00	26.03	PK	Horizontal
2	2483.704	19.29	27.53	3.62	0.00	50.44	74.00	23.56	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX DH5 2402MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G\10

Memo:

Sample Numbel:S24112815-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2355.390	20.17	27.12	3.55	0.00	50.84	74.00	23.16	PK	Horizontal
2	2390.000	15.58	27.26	3.57	0.00	46.41	74.00	27.59	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

LED LanternSpeaker ULTIMA

Model Number:

SP0000113-01

Test Mode:

TX 2DH5 2402MHz

Power Supply:

DC 5V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24112815-1E\FCC ABOVE 1G\11

Memo:

Sample Numbler:S24112815-001 Power Setting:10

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2351.270	18.80	27.11	3.55	0.00	49.46	74.00	24.54	PK	Horizontal
2	2390.000	15.82	27.26	3.57	0.00	46.65	74.00	27.35	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

16. Power Line Conducted Emissions

16.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
Two Line V-Network	R&S	ENV216	DDT-ZC02059	2025/07/08	1 Year
Δ -shaped artificial power network	SCHWARZBECK	PVDC 8301	DDT-ZC03939	2025/03/31	1 Year
RF Cable	Yuhu Technology	Z806-NJ-NJ-6M	DDT-ZC02004	2025/07/08	1 Year
EMI Test Receiver	R&S	ESCI/E3	DDT-ZC01297	2025/07/08	1 Year
Three-phase artificial power network	SCHWARZBECK	NSLK 8163	DDT-ZC01572	2025/07/08	1 Year
Two Line V-Network	R&S	ENV216	DDT-ZC02056	2025/07/08	1 Year
Pulse Limiter	SCHWARZBECK	VTSD 9561	DDT-ZC02128	2025/07/08	1 Year
Conducted Radiated Software	Audix	E3	DDT-ZC00562	/	/

16.2. Block diagram of test setup



16.3. Limits

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

16.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

16.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

16.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means Peak detection; “-----” means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

16.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 6# Shield Room

D:\2024 Report Date\Q24112815-1E\1212 CE.EM6

Test Date : 2024-12-12

Tested By : Gen Liu

EUT : LED LanternSpeaker ULTIMA

Model Number : SP0000113-01

Power Supply : AC 120V/60Hz


Test Mode : Bluetooth mode

Condition : Temp:21.6°C,Humi:52.8%

LISN : 2024 ENV216 3#/LINE

Memo :

Data: 2



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.15	18.41	9.78	0.07	9.83	38.09	65.91	-27.82	QP	LINE
2	0.15	6.06	9.78	0.07	9.83	25.74	55.91	-30.17	Average	LINE
3	0.23	13.35	9.76	0.06	9.83	33.00	62.61	-29.61	QP	LINE
4	0.23	3.64	9.76	0.06	9.83	23.29	52.61	-29.32	Average	LINE
5	0.70	12.15	9.75	0.07	9.83	31.80	56.00	-24.20	QP	LINE
6	0.70	8.36	9.75	0.07	9.83	28.01	46.00	-17.99	Average	LINE
7	0.78	20.20	9.75	0.05	9.84	39.84	56.00	-16.16	QP	LINE
8	0.78	14.97	9.75	0.05	9.84	34.61	46.00	-11.39	Average	LINE
9	1.24	8.41	9.74	0.12	9.84	28.11	56.00	-27.89	QP	LINE
10	1.24	0.82	9.74	0.12	9.84	20.52	46.00	-25.48	Average	LINE
11	2.27	7.60	9.75	0.11	9.84	27.30	56.00	-28.70	QP	LINE
12	2.27	1.46	9.75	0.11	9.84	21.16	46.00	-24.84	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site

: DDT 6# Shield Room

Test Date

: 2024-12-12

EUT

: LED LanternSpeaker ULTIMA

Power Supply

: AC 120V/60Hz

Condition

: Temp:21.6°C,Humi:52.8%

Tested By

: Gen Liu

Model Number

: SP0000113-01

Test Mode

: Bluetooth mode


LISN

: 2024 ENV216 3#/NEUTRAL

Memo

:

Data: 4



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.18	16.69	9.77	0.06	9.83	36.35	64.68	-28.33	QP	NEUTRAL
2	0.18	4.42	9.77	0.06	9.83	24.08	54.68	-30.60	Average	NEUTRAL
3	0.71	11.71	9.75	0.07	9.84	31.37	56.00	-24.63	QP	NEUTRAL
4	0.71	5.37	9.75	0.07	9.84	25.03	46.00	-20.97	Average	NEUTRAL
5	0.78	18.55	9.75	0.05	9.84	38.19	56.00	-17.81	QP	NEUTRAL
6	0.78	10.41	9.75	0.05	9.84	30.05	46.00	-15.95	Average	NEUTRAL
7	1.37	4.56	9.76	0.12	9.84	24.28	56.00	-31.72	QP	NEUTRAL
8	1.37	-0.14	9.76	0.12	9.84	19.58	46.00	-26.42	Average	NEUTRAL
9	1.76	7.30	9.77	0.11	9.84	27.02	56.00	-28.98	QP	NEUTRAL
10	1.76	0.37	9.77	0.11	9.84	20.09	46.00	-25.91	Average	NEUTRAL
11	2.24	4.23	9.77	0.11	9.84	23.95	56.00	-32.05	QP	NEUTRAL
12	2.24	-0.56	9.77	0.11	9.84	19.16	46.00	-26.84	Average	NEUTRAL

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

18. Photos of the EUT

Please refer to DDT-Q24112815-2E appendix I

-----End Report-----