




LENGTH CODE CHART

CABLE# & LENGTH	LENGTH SYMBOL	EXAMPLES OF PART# USED
CA-RSPNMAXXX	WHERE XXX = LENGTH IN FEET	CA-RSPNMA010 (10 FEET)
CA-RSPNMANXX	WHERE NXX = LENGTH IN INCHES	CA-RSPNMAN16 (16 INCHES)
CA-RSPNMAMXX	WHERE MXX = LENGTH IN METERS	CA-RSPNMAM07 (7 METERS)
CA-RSPNMAXMX	WHERE XMX = LENGTH IN DECIMEL METERS	CA-RSPNMA3M5 (3.5 METERS)

NOTES:

1. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY
2. CABLE ASSEMBLY SHALL RECIEVE INSERTION LOSS TEST#TP-0027
3. CABLE ASSEMBLY SHALL WITHSTAND PULL TEST OF 40lbs WITHOUT ANY SEPERATION OR ELECTRICAL FAILURE
4. CABLE SHALL BE RoHS COMPLIANT
5. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031
6. CENTER PIN OF CONNECTORS TO BE SOLDERED OR CRIMPED ONTO CABLE INNER CONDUCTOR

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES

OVERALL CABLE LENGTH TOLERANCE

≤ 12 [305] = +1 [25]/-0
 >12 [305] ≤ 60 [1524] = +2 [51] /-0
 >60 [1524] ≤ 120 [3048] = +4/-0
 >120 [3048] |U+2264300 [7620] = +6/-0
 >300 [76290] = +5%/-0

				SIZE A	TITLE: FABRICATION: CA-195R SERIES RP-SMA PLUG TO N-MALE ASSEMBLY with HEATSHRINK				
C	HL_4177	08/11/09	Changed Length Reference Points To Outside Ends of Connectors						
B	HL-ECN-0037	05/11/09	Change Tol. for Heatshrink from ±.06" & ±.15mm						
REV	ECN No.	DATE	DESCRIPTION	DRAWN BY	B.Puchaski 08/11/09		DRAWING No.	REV	
 Website: www.L-com.com Tel: 1-800-343-1455 Copyright © 2009 L-com, Inc. All rights reserved.				ORIGINATOR	B.Puchaski 08/07/08		F958	C	
				APPROVAL	M. Audus 08/11/09		PART No. CA-RSPNMA	VAR.	
				SCALE 1:1	SHEET 1/1	MATERIAL Noted	FILE No. F958-01		