



RF TEST REPORT

Applicant ZTE Corporation

FCC ID SRQ-ZTEBLADEA530

Product LTE/WCDMA/GSM(EDGE, GPRS)
Multi-Mode Digital Mobile Phone

Model BLADE A530

Marketing BLADE A530, ZTE BLADE A530,
A530, ZTE Blade A530, Blade A530

Report No. R1801A0031-R2V1

Issue Date February 11, 2018

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR 47 Part 24E (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Jiang peng Lan

Performed by: Jiangpeng Lan

Kai Xu

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the test report.....	4
1.2. Test facility.....	4
1.3. Testing Location	5
2. General Description of Equipment under Test.....	6
3. Applied Standards.....	8
4. Test Configuration.....	9
5. Test Case Results.....	11
5.1. RF Power Output.....	11
5.2. Effective Isotropic Radiated Power	16
5.3. Occupied Bandwidth	20
5.4. Band Edge Compliance.....	31
5.5. Peak-to-Average Power Ratio (PAPR)	42
5.6. Frequency Stability	45
5.7. Spurious Emissions at Antenna Terminals	50
5.8. Radiates Spurious Emission	64
6. Main Test Instruments	78

Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Isotropic Radiated power	24.232(c)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	2.1051 /24.238(a)	PASS
5	Peak-to-Average Power Ratio	24.232/KDB 971168 D01(5.7)	PASS
6	Frequency Stability	2.1055 / 24.235	PASS
7	Spurious Emissions at Antenna Terminals	2.1051 / 24.238(a)	PASS
8	Radiates Spurious Emission	2.1053 / 24.238(a)	PASS
Date of Testing: January 17, 2018~ February 2, 2018			
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard.			

1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

CNAS (accreditation number: L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

Client Information

Applicant	ZTE Corporation
Applicant address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China
Manufacturer	ZTE Corporation
Manufacturer address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

General information

EUT Description			
Model	BLADE A530		
IMEI	867671030002190		
Hardware Version	uecB		
Software Version	TEL_MX_BLADE_A530V1.0.0		
Power Supply	Battery/AC adapter		
Antenna Type	Internal Antenna		
Test Mode(s)	GSM1900; WCDMA Band II; LTE Band 2;		
Test Modulation	(GSM)GMSK,8PSK; (WCDMA)QPSK; (LTE)QPSK,16QAM		
GPRS Multislot Class	12		
EGPRS Multislot Class	12		
HSDPA UE Category	24		
HSUPA UE Category	7		
LTE Category	5		
Maximum E.I.R.P	GSM 1900:	21.94 dBm	
	WCDMA Band II:	15.88 dBm	
	LTE Band 2:	15.70 dBm	
Rated Power Supply Voltage	4.0V		
Extreme Voltage	Minimum: 3.6V Maximum: 4.3V		
Extreme Temperature	Lowest: -10°C Highest: +55°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM1900	1850 ~ 1910	1930 ~ 1990
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990
	LTE Band 2	1850 ~ 1910	1930 ~ 1990

EUT Accessory	
Adapter 1	Manufacturer: SHENZHEN RUIJING INDUSTRIAL CO LTD Model: STC-A51A-Z
Adapter 2	Manufacturer: DONGGUAN AOHAI POWER TECHNOLOGY CO., LTD. Model: STC-A51A-Z
Adapter 3	Manufacturer: Jiangsu Chenyang Electron Co., Ltd. Model: STC-A51A-Z
Battery 1	Manufacturer: Zhongshan Tianmao Battery Co.,Ltd. Model: Li3826T43P4h705949
Battery 2	Manufacturer: Jade Energy Technology (Zhuhai) Co., Ltd. Model: Li3826T43P4h705949
Earphone 1	Manufacturer: Shenzhen FDC Electronics Co. ,Ltd. Model:DEM-53
Earphone 2	Manufacturer: SANGFAI ELECTRICAL MANUFACTURE LIMITED Model: SF-880KM-53
USB Cable	Manufacturer: kingpower-tech 100cm Cable, Shielded
Note: The information of the EUT is declared by the manufacturer. 2. There is more than one Battery, each one should be applied throughout the compliance test respectively, and however, only the worst case (Battery 1) will be recorded in this report.	



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR47 Part 2 (2017)

FCC CFR 47 Part 24E (2017)

ANSI/TIA-603-E (2016)

KDB 971168 D01 Power Meas License Digital Systems v03

4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal polarization) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in GSM/WCDMA/LTE is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

	Test items	Modes/Modulation	
		GSM 1900	WCDMA Band II
Conducted Test cases	RF power output	GSM GPRS EGPRS	RMC HSDPA/ HSUPA/ DC-HSDPA/ HSPA+
	Occupied Bandwidth	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Band Edge Compliance	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Peak-to-Average Power Ratio	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Frequency Stability	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Spurious Emissions at Antenna Terminals	GSM	RMC
Radiated Test cases	Effective Isotropic Radiated power	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Radiates Spurious Emission	GSM	RMC



Test modes are chosen to be reported as the worst case configuration below for LTE Band 2

Test items	Bandwidth (MHz)						Modulation		RB			Test Channel		
	1.4	3	5	10	15	20	QPSK	16QAM	1	50%	100%	L	M	H
RF power output	O	O	O	O	O	O	O	O	O	O	O	O	O	O
Effective Isotropic Radiated power	O	O	O	O	O	O	O	O	-	-	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	O	O	-	-	O	O	O	O
Band Edge Compliance	O	O	O	O	O	O	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	O	O	O	-	-	O	O	O	O
Frequency Stability	O	O	O	O	O	O	O	O	-	-	O	-	O	-
Conducted Spurious Emissions	O	O	O	O	O	O	O	-	O	-	-	O	O	O
Radiates Spurious Emission	O	O	O	O	O	O	O	-	O	-	-	O	O	O
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.													

5. Test Case Results

5.1.RF Power Output


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

Test Results

GSM 1900		Conducted Power(dBm)		
		Channel 512	Channel 661	Channel 810
		1850.2(MHz)	1880(MHz)	1909.8(MHz)
GSM	Results	29.37	29.21	29.20
GPRS (GMSK)	1TXslot	29.37	29.20	29.19
	2TXslots	28.68	28.53	28.53
	3TXslots	26.94	26.80	26.81
	4TXslots	25.93	25.79	25.81
EGPRS (8PSK)	1TXslot	25.98	25.96	25.95
	2TXslots	24.88	24.96	24.92
	3TXslots	22.32	22.45	22.44
	4TXslots	21.79	21.89	21.82

WCDMA Band II		Conducted Power(dBm)		
		Channel 9262	Channel 9400	Channel 9538
		1852.4(MHz)	1880(MHz)	1907.6(MHz)
RMC	12.2k	22.97	23.01	23.12
	64k	22.91	22.89	22.96
	144k	22.82	22.84	22.95
	384k	22.81	22.85	22.96
HSDPA	Sub - Test 1	22.80	22.84	22.95
	Sub - Test 2	22.88	22.92	23.03
	Sub - Test 3	22.37	22.41	22.52
	Sub - Test 4	22.36	22.40	22.51
HSUPA	Sub - Test 1	22.85	22.89	23.00
	Sub - Test 2	20.84	20.88	20.99
	Sub - Test 3	21.77	21.81	22.08
	Sub - Test 4	20.76	20.80	21.07
	Sub - Test 5	22.91	22.95	23.06
DC-HSDPA	Sub - Test 1	22.90	22.90	23.01
	Sub - Test 2	22.89	22.89	23.00
	Sub - Test 3	22.38	22.38	22.49
	Sub - Test 4	22.37	22.47	22.47
HSPA+	16QAM	21.86	21.96	21.96

LTE Band 2				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				18607/1850.7	18900/1880	19193/1909.3
1.4MHz	QPSK	1	0	23.24	23.22	23.36
		1	2	23.40	23.38	23.40
		1	5	23.24	23.18	23.37
		3	0	23.45	23.37	23.48
		3	2	23.48	23.45	23.46
		3	3	23.37	23.34	23.45
		6	0	22.45	22.46	22.55
	16QAM	1	0	22.48	22.48	22.39
		1	2	22.70	22.45	22.47
		1	5	22.48	22.43	22.50
		3	0	22.43	22.33	22.49
		3	2	22.38	22.47	22.58
		3	3	22.31	22.44	22.45
		6	0	21.41	21.50	21.59
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				18615/1851.5	18900/1880	19185/1908.5
3MHz	QPSK	1	0	23.26	23.26	23.39
		1	7	23.43	23.43	23.44
		1	14	23.27	23.23	23.41
		8	0	22.55	22.49	22.61
		8	4	22.60	22.55	22.58
		8	7	22.47	22.45	22.55
		15	0	22.48	22.50	22.58
	16QAM	1	0	22.51	22.50	22.42
		1	7	22.73	22.50	22.51
		1	14	22.50	22.47	22.53
		8	0	21.54	21.46	21.61
		8	4	21.49	21.60	21.70
		8	7	21.41	21.56	21.58
		15	0	21.44	21.54	21.62
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				18625/1852.5	18900/1880	19175/1907.5
5MHz	QPSK	1	0	23.23	23.24	23.35
		1	13	23.41	23.39	23.41
		1	24	23.24	23.18	23.37
		12	0	22.52	22.44	22.57



		12	6	22.58	22.51	22.53
		12	13	22.45	22.43	22.51
		25	0	22.46	22.49	22.56
	16QAM	1	0	22.48	22.46	22.39
		1	13	22.70	22.48	22.48
		1	24	22.47	22.45	22.49
		12	0	21.52	21.42	21.58
		12	6	21.46	21.55	21.66
		12	13	21.38	21.51	21.54
		25	0	21.42	21.50	21.57
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				18650/1855	18900/1880	19150/1905
10MHz	QPSK	1	0	23.25	23.25	23.38
		1	25	23.44	23.44	23.45
		1	49	23.26	23.22	23.40
		25	0	22.55	22.49	22.61
		25	13	22.61	22.56	22.57
		25	25	22.47	22.47	22.56
		50	0	22.54	22.51	22.60
	16QAM	1	0	22.50	22.49	22.41
		1	25	22.73	22.52	22.51
		1	49	22.50	22.47	22.52
		25	0	21.55	21.47	21.62
		25	13	21.48	21.59	21.69
		25	25	21.41	21.56	21.58
		50	0	21.45	21.55	21.61
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				18675/1857.5	18900/1880	19125/1902.5
15MHz	QPSK	1	0	23.24	23.21	23.36
		1	38	23.42	23.43	23.42
		1	74	23.23	23.17	23.36
		36	0	22.53	22.45	22.58
		36	18	22.58	22.51	22.53
		36	39	22.44	22.44	22.52
		75	0	22.52	22.47	22.55
	16QAM	1	0	22.45	22.47	22.39
		1	38	22.71	22.49	22.49
		1	74	22.47	22.43	22.49
		36	0	21.52	21.45	21.59
		36	18	21.45	21.54	21.65



		36	39	21.39	21.52	21.55
		75	0	21.42	21.50	21.57
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				18700/1860	18900/1880	19100/1900
20MHz	QPSK	1	0	23.21	23.17	23.33
		1	50	23.41	23.39	23.40
		1	99	23.21	23.16	23.33
		50	0	22.50	22.40	22.54
		50	25	22.56	22.47	22.50
		50	50	22.41	22.39	22.48
		100	0	22.49	22.42	22.51
	16QAM	1	0	22.43	22.43	22.34
		1	50	22.67	22.47	22.45
		1	99	22.45	22.40	22.47
		50	0	21.49	21.41	21.56
		50	25	21.42	21.52	21.62
		50	50	21.36	21.47	21.51
		100	0	21.40	21.46	21.54

5.2. Effective Isotropic Radiated Power

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

The testing follows FCC KDB 971168 v03 Section 5.8 and ANSI/TIA-603-E (2016).

- Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.
- Key the transmitter, then rotate the EUT 360° azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).
- Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.
- Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading. $LOSS = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$
- Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation: $ERP \text{ (dBm)} = LVL \text{ (dBm)} + LOSS \text{ (dB)}$
- The maximum ERP is the maximum value determined in the preceding step.
- When calculating ERP, in addition to knowing the antenna radiation and matching characteristics, it is necessary to know the loss values of all elements (e.g. transmission line attenuation, mismatches, filters, combiners) interposed between the point where transmitter output power is measured, and the point where power is applied to the antenna. ERP can then be calculated as follows:
 $ERP \text{ (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBd)}$
 where: dBd refers to gain relative to an ideal dipole.
 $EIRP \text{ (dBm)} = ERP \text{ (dBm)} + 2.15 \text{ (dB.)}$

Test setup



Limits

Rule Part 24.232(c) Mobile and portable stations are limited to 2 watts EIRP.

Rule Part 24.232(e) Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

Limit (EIRP)	$\leq 2 \text{ W}$ (33 dBm)
--------------	-----------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 1.19 \text{ dB}$

Test Results:

The measurement is performed for both of horizontal and vertical antenna Polarization, and only the data of worst mode is recorded in this report.

Mode	Channel	Frequency (MHz)	Polarization	Output Power (dBm)	Losses (dB)	Antenna Gain (dBd)	EIRP (dBm)	Limit (dBm)	Conclusion
GSM 1900	Low	1850.2	Horizontal	-33.99	-53.21	1.92	21.14	33	Pass
	Mid	1880	Horizontal	-33.41	-53.42	1.94	21.94	33	Pass
	High	1909.8	Horizontal	-34.51	-53.67	1.90	21.06	33	Pass
GPRS 1900	Low	1850.2	Horizontal	-33.67	-53.21	1.92	21.46	33	Pass
	Mid	1880	Horizontal	-33.94	-53.42	1.94	21.42	33	Pass
	High	1909.8	Horizontal	-34.09	-53.67	1.90	21.48	33	Pass
EGPRS 1900	Low	1850.2	Horizontal	-35.71	-53.21	1.92	19.42	33	Pass
	Mid	1880	Horizontal	-35.88	-53.42	1.94	19.48	33	Pass
	High	1909.8	Horizontal	-35.94	-53.67	1.90	19.62	33	Pass
WCDMA Band II	Low	1852.4	Horizontal	-40.54	-53.19	1.92	14.57	33	Pass
	Mid	1880	Horizontal	-39.86	-53.42	1.94	15.49	33	Pass
	High	1907.6	Horizontal	-39.70	-53.66	1.92	15.88	33	Pass



LTE Band 2									
bandwidth	Channel	Frequency (MHz)	Polarization	Output Power (dBm)	Losses (dB)	Antenna Gain (dBd)	EIRP (dBm)	Limit (dBm)	Conclusion
1.4 MHz (QPSK)	Low	1850.7	Horizontal	-42.30	-54.89	1.90	14.49	33	Pass
	Mid	1880	Horizontal	-44.35	-56.66	1.92	14.24	33	Pass
	High	1909.3	Horizontal	-45.75	-58.09	1.91	14.25	33	Pass
3 MHz (QPSK)	Low	1851.5	Horizontal	-42.57	-54.93	1.91	14.26	33	Pass
	Mid	1880	Horizontal	-43.82	-56.66	1.94	14.79	33	Pass
	High	1908.5	Horizontal	-45.67	-58.08	1.91	14.32	33	Pass
5 MHz (QPSK)	Low	1852.5	Horizontal	-42.98	-55.14	1.92	14.08	33	Pass
	Mid	1880	Horizontal	-43.73	-56.41	1.94	14.62	33	Pass
	High	1907.5	Horizontal	-45.62	-57.97	1.90	14.25	33	Pass
10 MHz (QPSK)	Low	1855	Horizontal	-42.06	-55.09	1.91	14.94	33	Pass
	Mid	1880	Horizontal	-42.91	-56.66	1.94	15.70	33	Pass
	High	1905	Horizontal	-44.67	-58.01	1.92	15.27	33	Pass
15 MHz (QPSK)	Low	1857.5	Horizontal	-42.90	-55.24	1.93	14.27	33	Pass
	Mid	1880	Horizontal	-44.10	-56.41	1.94	14.25	33	Pass
	High	1902.5	Horizontal	-45.36	-57.69	1.92	14.25	33	Pass
20 MHz (QPSK)	Low	1860	Horizontal	-42.33	-55.35	1.93	14.95	33	Pass
	Mid	1880	Horizontal	-43.92	-56.66	1.94	14.69	33	Pass
	High	1900	Horizontal	-45.30	-57.86	1.92	14.49	33	Pass
1.4 MHz (16QAM)	Low	1850.7	Horizontal	-42.43	-54.89	1.90	14.36	33	Pass
	Mid	1880	Horizontal	-44.47	-56.66	1.92	14.11	33	Pass
	High	1909.3	Horizontal	-45.87	-58.09	1.91	14.12	33	Pass
3 MHz (16QAM)	Low	1851.5	Horizontal	-42.70	-54.93	1.91	14.14	33	Pass
	Mid	1880	Horizontal	-43.94	-56.66	1.94	14.66	33	Pass
	High	1908.5	Horizontal	-45.79	-58.08	1.91	14.20	33	Pass
5 MHz (16QAM)	Low	1852.5	Horizontal	-43.11	-55.14	1.92	13.95	33	Pass
	Mid	1880	Horizontal	-43.85	-56.41	1.94	14.50	33	Pass
	High	1907.5	Horizontal	-45.75	-57.97	1.90	14.12	33	Pass
10 MHz (16QAM)	Low	1855	Horizontal	-42.18	-55.09	1.91	14.82	33	Pass
	Mid	1880	Horizontal	-43.03	-56.66	1.94	15.57	33	Pass
	High	1905	Horizontal	-44.79	-58.01	1.92	15.14	33	Pass
15 MHz (16QAM)	Low	1857.5	Horizontal	-43.03	-55.24	1.93	14.14	33	Pass
	Mid	1880	Horizontal	-44.23	-56.41	1.94	14.12	33	Pass
	High	1902.5	Horizontal	-45.49	-57.69	1.92	14.12	33	Pass
20 MHz (16QAM)	Low	1860	Horizontal	-42.45	-55.35	1.93	14.83	33	Pass
	Mid	1880	Horizontal	-44.04	-56.66	1.94	14.56	33	Pass
	High	1900	Horizontal	-45.42	-57.86	1.92	14.36	33	Pass

5.3.Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 3kHz, VBW is set to 10kHz for GSM 1900,

RBW is set to 51kHz, VBW is set to 160kHz for WCDMA Band II,


RBW is set to 51kHz, VBW is set to 160kHz for LTE Band 2 (1.4MHz),

RBW is set to 100kHz,VBW is set to 300kHz for LTE Band 2 (3MHz/5MHz),

RBW is set to 300kHz,VBW is set to 1MHz for LTE Band 2 (10MHz/15MHz/20MHz).

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.

Test Result

Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
GSM 1900 (GSM)	512	1850.2	0.24646	0.3084
	661	1880.0	0.24691	0.3077
	810	1909.8	0.24735	0.3129
GPRS 1900 (GMSK)	512	1850.2	0.24686	0.3143
	661	1880.0	0.24246	0.3102
	810	1909.8	0.24306	0.3124
EGPRS 1900 (8-PSK)	512	1850.2	0.24453	0.3094
	661	1880.0	0.24825	0.3145
	810	1909.8	0.24465	0.3168
WCDMA Band II (RMC)	9262	1852.4	4.1802	4.716
	9400	1880	4.1507	4.693
	9538	1907.6	4.1861	4.701


LTE Band 2					
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
QPSK	1.4	18607	1850.7	1.1216	1.345
		18900	1880.0	1.1255	1.338
		19193	1909.3	1.1202	1.320
	3	18615	1851.5	2.7248	3.005
		18900	1880	2.7213	2.979
		19185	1908.5	2.7205	2.997
	5	18625	1852.5	4.5437	5.234
		18900	1880	4.5336	5.633
		19175	1907.5	4.5216	5.194
	10	18650	1855	9.0820	10.26
		18900	1880	9.0441	10.18
		19150	1905	9.0857	10.21
	15	18675	1857.5	13.535	15.22




		18900	1880	13.458	14.97
		19125	1902.5	13.500	15.22
	20	18700	1860	17.913	19.47
		18900	1880	17.888	19.52
		19100	1900	17.939	19.72
16QAM	1.4	18607	1850.7	1.1268	1.343
		18900	1880.0	1.1094	1.319
		19193	1909.3	1.1175	1.329
	3	18615	1851.5	2.7165	2.978
		18900	1880	2.7206	2.991
		19185	1908.5	2.7198	2.998
	5	18625	1852.5	4.5282	5.141
		18900	1880	4.5449	5.18
		19175	1907.5	4.5597	5.192
	10	18650	1855	9.1013	10.26
		18900	1880	9.0525	10.23
		19150	1905	9.0453	10.13
	15	18675	1857.5	13.52	15.04
		18900	1880	13.526	14.96
		19125	1902.5	13.478	14.92
	20	18700	1860	17.972	19.46
		18900	1880	17.913	19.74
		19100	1900	17.869	19.44




GSM1900 GSM CH-Low



GSM1900 GPRS CH-Low




GSM 1900 GSM CH-Middle




GSM 1900 GPRS CH-Middle



GSM 1900 GSM CH-High




GSM 1900 GPRS CH-High







GSM1900 EGPRS CH-Low




WCDMA Band II RMC CH-LOW




GSM 1900 EGPRS CH-Middle




WCDMA Band II RMC CH-Middle



GSM 1900 EGPRS CH-High




WCDMA Band II RMC CH-High







LTE Band 2 1.4MHz QPSK CH-Low




LTE Band 2 3MHz QPSK CH-Low




LTE Band 2 1.4MHz QPSK CH-Middle




LTE Band 2 3MHz QPSK CH-Middle



LTE Band 2 1.4MHz QPSK CH-High



LTE Band 2 3MHz QPSK CH-High



LTE Band 2 5MHz QPSK CH-Low




LTE Band 2 10MHz QPSK CH-Low




LTE Band 2 5MHz QPSK CH-Middle




LTE Band 2 10MHz QPSK CH-Middle









LTE Band 2 5MHz QPSK CH-High




LTE Band 2 10MHz QPSK CH-High







LTE Band 2 1.4MHz 16QAM CH-Low




LTE Band 2 3MHz 16QAM CH-Low




LTE Band 2 1.4MHz 16QAM CH-Middle




LTE Band 2 3MHz 16QAM CH-Middle




LTE Band 2 1.4MHz 16QAM CH-High




LTE Band 2 3MHz 16QAM CH-High




LTE Band 2 5MHz 16QAM CH-Low




LTE Band 2 10MHz 16QAM CH-Low




LTE Band 2 5MHz 16QAM CH-Middle




LTE Band 2 10MHz 16QAM CH-Middle




LTE Band 2 5MHz 16QAM CH-High




LTE Band 2 10MHz 16QAM CH-High




LTE Band 2 15MHz 16QAM CH-Low




LTE Band 2 20MHz 16QAM CH-Low




LTE Band 2 15MHz 16QAM CH-Middle




LTE Band 2 20MHz 16QAM CH-Middle



LTE Band 2 15MHz 16QAM CH-High



LTE Band 2 20MHz 16QAM CH-High



5.4. Band Edge Compliance


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The Average detector is used and RBW is set to 3kHz, VBW is set to 10kHz for GSM 1900, RBW is set to 51kHz, VBW is set to 160kHz for WCDMA Band II, RBW is set to 15kHz, VBW is set to 51kHz for LTE Band 2 (1.4MHz), RBW is set to 30kHz, VBW is set to 100kHz for LTE Band 2 (3MHz), RBW is set to 51kHz, VBW is set to 160kHz for LTE Band 2 (5MHz), RBW is set to 100kHz, VBW is set to 300kHz for LTE Band 2 (10MHz), RBW is set to 150kHz, VBW is set to 510kHz for LTE Band 2 (15MHz), RBW is set to 200kHz, VBW is set to 620kHz for LTE Band 2 (20MHz). Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------


Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684$ dB.




Test Result:


GSM1900 GSM CH-Low




GSM 1900 GSM CH-High




GSM1900 GPRS CH-Low




GSM 1900 GPRS CH-High




GSM1900 EGPRS CH-Low



GSM 1900 EGPRS CH-High




WCDMA Band II RMC CH-Low




WCDMA Band II RMC CH-High




LTE Band 2 1.4MHz QPSK 1RB CH-Low




LTE Band 2 1.4MHz QPSK 1RB CH-High



LTE Band 2 1.4MHz QPSK 100%RB CH-Low




LTE Band 2 1.4MHz QPSK 100%RB CH-High



LTE Band 2 3MHz QPSK 1RB CH-Low



LTE Band 2 3MHz QPSK 1RB CH-High



LTE Band 2 3MHz QPSK 100%RB CH-Low




LTE Band 2 3MHz QPSK 100%RB CH-High




LTE Band 2 5MHz QPSK 1RB CH-Low



LTE Band 2 5MHz QPSK 1RB CH-High




LTE Band 2 5MHz QPSK 100%RB CH-Low




LTE Band 2 5MHz QPSK 100%RB CH-High




LTE Band 2 10MHz QPSK 1RB CH-Low



LTE Band 2 10MHz QPSK 1RB CH-High



LTE Band 2 10MHz QPSK 100%RB CH-Low




LTE Band 2 10MHz QPSK 100%RB CH-High







LTE Band 2 15MHz QPSK 1RB CH-Low




LTE Band 2 15MHz QPSK 1RB CH-High




LTE Band 2 15MHz QPSK 100%RB CH-Low




LTE Band 2 15MHz QPSK 100%RB CH-High




LTE Band 2 20MHz QPSK 1RB CH-Low



LTE Band 2 20MHz QPSK 1RB CH-High




LTE Band 2 20MHz QPSK 100%RB CH-Low




LTE Band 2 20MHz QPSK 100%RB CH-High




LTE Band 2 1.4MHz 16QAM 1RB CH-Low




LTE Band 2 1.4MHz 16QAM 1RB CH-High



LTE Band 2 1.4MHz 16QAM 100%RB CH-Low



LTE Band 2 1.4MHz 16QAM 100%RB CH-High




LTE Band 2 3MHz 16QAM 1RB CH-Low



LTE Band 2 3MHz 16QAM 1RB CH-High



LTE Band 2 3MHz 16QAM 100%RB CH-Low



LTE Band 2 3MHz 16QAM 100%RB CH-High




LTE Band 2 5MHz 16QAM 1RB CH-Low




LTE Band 2 5MHz 16QAM 1RB CH-High




LTE Band 2 5MHz 16QAM 100%RB CH-Low




LTE Band 2 5MHz 16QAM 100%RB CH-High




LTE Band 2 10MHz 16QAM 1RB CH-Low



LTE Band 2 10MHz 16QAM 1RB CH-High



LTE Band 2 10MHz 16QAM 100%RB CH-Low



LTE Band 2 10MHz 16QAM 100%RB CH-High




LTE Band 2 15MHz 16QAM 1RB CH-Low



LTE Band 2 15MHz 16QAM 1RB CH-High



LTE Band 2 15MHz 16QAM 100%RB CH-Low



LTE Band 2 15MHz 16QAM 100%RB CH-High



LTE Band 2 20MHz 16QAM 1RB CH-Low




LTE Band 2 20MHz 16QAM 1RB CH-High





LTE Band 2 20MHz 16QAM 100%RB CH-Low



LTE Band 2 20MHz 16QAM 100%RB CH-High



5.5. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as PPK. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = \text{PPk (dBm)} - \text{PAvg (dBm)}.$$

Test Setup



Limits

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB in 24.232(d).

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

**Test Results**

Mode	Channel	Frequency (MHz)	Peak(dBm)	Avg(dBm)	PAPR(dB)	Limit(dB)	Conclusion
GSM 1900 (GSM)	512	1850.2	30.84	29.37	1.47	≤13	PASS
	661	1880	30.60	29.21	1.39	≤13	PASS
	810	1909.8	30.65	29.20	1.45	≤13	PASS
GPRS 1900 (GMSK)	512	1850.2	27.42	25.93	1.49	≤13	PASS
	661	1880	27.44	25.79	1.65	≤13	PASS
	810	1909.8	27.32	25.81	1.51	≤13	PASS
EGPRS 1900 (8-PSK)	512	1850.2	23.39	21.79	1.60	≤13	PASS
	661	1880	23.39	21.89	1.50	≤13	PASS
	810	1909.8	23.39	21.82	1.57	≤13	PASS
WCDMA Band II (RMC)	9262	1852.4	26.10	22.97	3.13	≤13	PASS
	9400	1880	26.04	23.01	3.03	≤13	PASS
	9538	1907.6	26.18	23.12	3.06	≤13	PASS



LTE Band 2		Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit(dB)	Conclusion
Modulation	Bandwidth							
QPSK	1.4MHz	18607	1850.7	27.12	22.45	4.67	≤13	PASS
		18900	1880.0	26.93	22.46	4.47	≤13	PASS
		19193	1909.3	27.87	22.55	5.32	≤13	PASS
	3MHz	18615	1851.5	28.09	22.48	5.61	≤13	PASS
		18900	1880	27.31	22.50	4.81	≤13	PASS
		19185	1908.5	27.46	22.58	4.88	≤13	PASS
	5MHz	18625	1852.5	28.15	22.46	5.69	≤13	PASS
		18900	1880	28.00	22.49	5.51	≤13	PASS
		19175	1907.5	28.17	22.56	5.61	≤13	PASS
	10MHz	18650	1855	27.37	22.54	4.83	≤13	PASS
		18900	1880	27.15	22.51	4.64	≤13	PASS
		19150	1905	28.01	22.60	5.41	≤13	PASS
	15MHz	18675	1857.5	27.83	22.52	5.31	≤13	PASS
		18900	1880	26.98	22.47	4.51	≤13	PASS
		19125	1902.5	27.49	22.55	4.94	≤13	PASS
16QAM	1.4MHz	18607	1850.7	27.02	21.41	5.61	≤13	PASS
		18900	1880.0	26.92	21.50	5.42	≤13	PASS
		19193	1909.3	27.04	21.59	5.45	≤13	PASS
	3MHz	18615	1851.5	26.06	21.44	4.62	≤13	PASS
		18900	1880	26.37	21.54	4.83	≤13	PASS
		19185	1908.5	27.25	21.62	5.63	≤13	PASS
	5MHz	18625	1852.5	26.96	21.42	5.54	≤13	PASS
		18900	1880	26.29	21.50	4.79	≤13	PASS
		19175	1907.5	26.37	21.57	4.80	≤13	PASS
	10MHz	18650	1855	27.10	21.45	5.65	≤13	PASS
		18900	1880	26.22	21.55	4.67	≤13	PASS
		19150	1905	26.08	21.61	4.47	≤13	PASS
	15MHz	18675	1857.5	26.74	21.42	5.32	≤13	PASS
		18900	1880	27.11	21.50	5.61	≤13	PASS
		19125	1902.5	26.38	21.57	4.81	≤13	PASS
	20MHz	18700	1860	26.28	21.40	4.88	≤13	PASS
		18900	1880	27.15	21.46	5.69	≤13	PASS
		19100	1900	27.05	21.54	5.51	≤13	PASS

5.6.Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +55°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +55°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

2. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.6 V and 4.3 V, with a nominal voltage of 4.0V.

Test setup



Limits

No specific frequency stability requirements in part 24.235

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.

Test Result

Mode	Test status	Test Results (ppm)		
		GSM(GMSK)	GPRS(GMSK)	EGPRS(8PSK)
GSM 1900 Middle Channel	-30°C/Normal Voltage	0.00116	0.00116	-0.00162
	-20°C/Normal Voltage	0.00280	0.00042	-0.00217
	-10°C/Normal Voltage	0.00121	0.00105	0.00122
	0°C/Normal Voltage	-0.00053	0.00067	0.00298
	10°C/Normal Voltage	0.00140	-0.00082	0.00308
	20°C/Normal Voltage	0.00130	0.00038	-0.00171
	30°C/Normal Voltage	-0.00287	0.00092	0.00333
	40°C/Normal Voltage	-0.00057	0.00100	0.00309
	50°C/Normal Voltage	0.00135	-0.00092	0.00297
	55°C/Normal Voltage	0.00370	0.00154	0.00413
	20°C/Min Voltage	0.00125	0.00107	0.00177
	20°C/Max Voltage	0.00222	0.00180	-0.00204
/	/	RMC		
WCDMA Band II Middle Channel	-30°C/Normal Voltage	0.00314		
	-20°C/Normal Voltage	0.00306		
	-10°C/Normal Voltage	0.00264		
	0°C/Normal Voltage	0.00339		
	10°C/Normal Voltage	0.00318		
	20°C/Normal Voltage	0.00221		
	30°C/Normal Voltage	0.00223		
	40°C/Normal Voltage	0.00321		
	50°C/Normal Voltage	0.00284		
	55°C/Normal Voltage	0.00598		
	20°C/Min Voltage	0.00224		
	20°C/Max Voltage	0.00361		

Bandwidth	Test status	LTE Band 2 Middle Channel Test Results (ppm)	
		QPSK	16QAM
1.4MHz	-30°C/Normal Voltage	-0.00095	0.00004
	-20°C/Normal Voltage	-0.00435	-0.00168
	-10°C/Normal Voltage	-0.00211	0.00031
	0°C/Normal Voltage	0.00078	-0.00295
	10°C/Normal Voltage	-0.00227	-0.00062
	20°C/Normal Voltage	-0.00156	0.00009
	30°C/Normal Voltage	-0.00063	-0.00294
	40°C/Normal Voltage	-0.00054	-0.00179
	50°C/Normal Voltage	-0.00058	0.00037
	55°C/Normal Voltage	-0.00186	0.00047
	20°C/Min Voltage	-0.00310	0.00170
	20°C/Max Voltage	-0.00201	0.00021
3MHz	-30°C/Normal Voltage	0.00016	0.00189
	-20°C/Normal Voltage	-0.00202	0.00010
	-10°C/Normal Voltage	0.00061	0.00149
	0°C/Normal Voltage	-0.00335	0.00157
	10°C/Normal Voltage	-0.00148	0.00026
	20°C/Normal Voltage	-0.00234	0.00154
	30°C/Normal Voltage	-0.00156	0.00066
	40°C/Normal Voltage	-0.00196	0.00165
	50°C/Normal Voltage	-0.00034	-0.00053
	55°C/Normal Voltage	-0.00220	0.00243
	20°C/Min Voltage	-0.00282	0.00010
	20°C/Max Voltage	-0.00186	-0.00023
5MHz	-30°C/Normal Voltage	-0.00140	-0.00030
	-20°C/Normal Voltage	-0.00013	0.00098
	-10°C/Normal Voltage	0.00069	0.00124
	0°C/Normal Voltage	-0.00193	0.00246
	10°C/Normal Voltage	-0.00146	0.00229
	20°C/Normal Voltage	-0.00259	0.00119
	30°C/Normal Voltage	-0.00232	0.00140
	40°C/Normal Voltage	-0.00040	0.00068
	50°C/Normal Voltage	-0.00199	0.00034
	55°C/Normal Voltage	-0.00043	0.00136
	20°C/Min Voltage	-0.00107	0.00093
	20°C/Max Voltage	-0.00073	-0.00010



10MHz	-30°C/Normal Voltage	-0.00280	-0.00030
	-20°C/Normal Voltage	-0.00169	0.00074
	-10°C/Normal Voltage	-0.00107	0.00125
	0°C/Normal Voltage	-0.00405	0.00182
	10°C/Normal Voltage	-0.00191	-0.00067
	20°C/Normal Voltage	-0.00293	0.00007
	30°C/Normal Voltage	-0.00156	0.00173
	40°C/Normal Voltage	-0.00106	-0.00069
	50°C/Normal Voltage	-0.00048	-0.00081
	55°C/Normal Voltage	-0.00238	0.00077
	20°C/Min Voltage	-0.00139	0.00046
	20°C/Max Voltage	-0.00213	-0.00143
15MHz	-30°C/Normal Voltage	0.00080	-0.00097
	-20°C/Normal Voltage	0.00042	0.00112
	-10°C/Normal Voltage	0.00025	0.00046
	0°C/Normal Voltage	-0.00257	-0.00004
	10°C/Normal Voltage	-0.00063	0.00019
	20°C/Normal Voltage	-0.00260	-0.00021
	30°C/Normal Voltage	-0.00193	-0.00011
	40°C/Normal Voltage	-0.00041	0.00030
	50°C/Normal Voltage	-0.00159	-0.00138
	55°C/Normal Voltage	-0.00249	-0.00022
	20°C/Min Voltage	-0.00215	0.00067
	20°C/Max Voltage	-0.00290	0.00186
20MHz	-30°C/Normal Voltage	-0.00202	-0.00061
	-20°C/Normal Voltage	-0.00250	0.00052
	-10°C/Normal Voltage	-0.00021	-0.00028
	0°C/Normal Voltage	-0.00012	0.00064
	10°C/Normal Voltage	-0.00013	-0.00145
	20°C/Normal Voltage	-0.00149	-0.00058
	30°C/Normal Voltage	-0.00238	-0.00146
	40°C/Normal Voltage	-0.00069	-0.00212
	50°C/Normal Voltage	-0.00264	0.00016
	55°C/Normal Voltage	-0.00273	0.00113
	20°C/Min Voltage	-0.00167	0.00094
	20°C/Max Voltage	-0.00020	0.00067

5.7. Spurious Emissions at Antenna Terminals


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used. set RBW 1MHz and VBW is 3MHz, Sweep is set to ATUO.

Test setup



Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB



2GHz-18GHz	1.407 dB
------------	----------


Test Result

Sweep from 9 kHz to 30MHz, and the emissions more than 20 dB below the permissible value are not reported.


If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.

The signal beyond the limit is carrier.


GSM 1900 CH-Low 30MHz~1GHz




GSM 1900 CH-Middle 30MHz~1GHz




GSM 1900 CH-Low 1GHz~3GHz




GSM 1900 CH-Middle 1GHz~3GHz



GSM 1900 CH-Low 3GHz~20GHz




GSM 1900 CH-Middle 3GHz~20GHz







GSM 1900 CH-High 30MHz~1GHz




WCDMA Band II CH-Low 30MHz~1GHz




GSM 1900 CH-High 1GHz~3GHz




WCDMA BAND II CH-Low 1GHz~3GHz




GSM 1900 CH-High 3GHz~20GHz




WCDMA BAND II CH-Low 3GHz~20GHz




WCDMA Band II CH- Middle 30MHz~1GHz




WCDMA Band II CH- High 30MHz~1GHz




WCDMA BAND II CH-Middle 1GHz~3GHz




WCDMA BAND II CH-High 1GHz~3GHz




WCDMA BAND II CH-Middle 3GHz~20GHz




WCDMA BAND II CH-High 3GHz~20GHz




LTE Band 2 1.4MHz CH-Low 30MHz~1GHz




LTE Band 2 1.4MHz CH-Middle 30MHz~1GHz




LTE Band 2 1.4MHz CH-Low 1GHz~3GHz




LTE Band 2 1.4MHz CH-Middle 1GHz~3GHz



LTE Band 2 1.4MHz CH-Low 3GHz~20GHz




LTE Band 2 1.4MHz CH-Middle 3GHz~20GHz







LTE Band 2 1.4MHz CH-High 30MHz~1GHz




LTE Band 2 3MHz CH-Low 30MHz~1GHz




LTE Band 2 1.4MHz CH-High 1GHz~3GHz




LTE Band 2 3MHz CH-Low 1GHz~3GHz




LTE Band 2 1.4MHz CH-High 3GHz~20GHz




LTE Band 2 3MHz CH-Low 3GHz~20GHz




LTE Band 2 3MHz CH-Middle 30MHz~1GHz




LTE Band 2 3MHz CH-High 30MHz~1GHz




LTE Band 2 3MHz CH-Middle 1GHz~3GHz




LTE Band 2 3MHz CH-High 1GHz~3GHz



LTE Band 2 3MHz CH-Middle 3GHz~20GHz




LTE Band 2 3MHz CH-High 3GHz~20GHz







LTE Band 2 5MHz CH-Low 30MHz~1GHz




LTE Band 2 5MHz CH-Middle 30MHz~1GHz




LTE Band 2 5MHz CH-Low 1GHz~3GHz




LTE Band 2 5MHz CH-Middle 1GHz~3GHz



LTE Band 2 5MHz CH-Low 3GHz~20GHz




LTE Band 2 5MHz CH-Middle 3GHz~20GHz







LTE Band 2 5MHz CH-High 30MHz~1GHz




LTE Band 2 10MHz CH-Low 30MHz~1GHz




LTE Band 2 5MHz CH-High 1GHz~3GHz




LTE Band 2 10MHz CH-Low 1GHz~3GHz



LTE Band 2 5MHz CH-High 3GHz~20GHz




LTE Band 2 10MHz CH-Low 3GHz~20GHz







LTE Band 2 10MHz CH-Middle 30MHz~1GHz




LTE Band 2 10MHz CH-High 30MHz~1GHz




LTE Band 2 10MHz CH-Middle 1GHz~3GHz




LTE Band 2 10MHz CH-High 1GHz~3GHz



LTE Band 2 10MHz CH-Middle 3GHz~20GHz




LTE Band 2 10MHz CH-High 3GHz~20GHz







LTE Band 2 15MHz CH-Low 30MHz~1GHz




LTE Band 2 15MHz CH-Middle 30MHz~1GHz




LTE Band 2 15MHz CH-Low 1GHz~3GHz




LTE Band 2 15MHz CH-Middle 1GHz~3GHz



LTE Band 2 15MHz CH-Low 3GHz~20GHz




LTE Band 2 15MHz CH-Middle 3GHz~20GHz







LTE Band 2 15MHz CH-High 30MHz~1GHz




LTE Band 2 20MHz CH-Low 30MHz~1GHz




LTE Band 2 15MHz CH-High 1GHz~3GHz




LTE Band 2 20MHz CH-Low 1GHz~3GHz



LTE Band 2 15MHz CH-High 3GHz~20GHz




LTE Band 2 20MHz CH-Low 3GHz~20GHz







LTE Band 2 20MHz CH-Middle 30MHz~1GHz




LTE Band 2 20MHz CH-High 30MHz~1GHz




LTE Band 2 20MHz CH-Middle 1GHz~3GHz




LTE Band 2 20MHz CH-High 1GHz~3GHz



LTE Band 2 20MHz CH-Middle 3GHz~20GHz



LTE Band 2 20MHz CH-High 3GHz~20GHz



5.8.Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement


1. The testing follows FCC KDB 971168 v03 Section 5.8 and ANSI/TIA-603-E (2016).
2. The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:

$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$
The measurement results are amend as described below:


$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.

Test setup

30MHz~~~ 1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the worst case was recorded.

Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

Test Result

GSM 1900 CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3700.5	-55.75	5.10	11.05	Horizontal	-49.81	-13.00	36.81	135
3	5550.2	-55.23	5.42	12.65	Horizontal	-47.96	-13.00	34.96	45
4	7400.3	-49.55	6.7	13.85	Horizontal	-42.38	-13.00	29.38	180
5	9252.0	-48.94	7.01	14.75	Horizontal	-41.22	-13.00	28.22	270
6	11103.8	-46.57	7.48	15.95	Horizontal	-38.13	-13.00	25.13	135
7	12949.9	-47.34	7.51	16.55	Horizontal	-38.35	-13.00	25.35	45
8	14801.6	-45.31	8.24	15.35	Horizontal	-38.21	-13.00	25.21	270
9	16653.4	-44.24	8.41	14.95	Horizontal	-37.74	-13.00	24.74	180
10	18502.0	-44.91	8.54	15.45	Horizontal	-38.00	-13.00	25.00	270
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2.The worst emission was found in the antenna is Horizontal position.									

GSM 1900 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3759.9	-55.95	5.10	11.05	Horizontal	-50.00	-13.00	37.00	135
3	5640.2	-53.53	5.42	12.65	Horizontal	-46.31	-13.00	33.31	45
4	7519.5	-49.15	6.7	13.85	Horizontal	-41.96	-13.00	28.96	180
5	9402.8	-48.14	7.01	14.75	Horizontal	-40.45	-13.00	27.45	270
6	11279.3	-44.77	7.48	15.95	Horizontal	-36.33	-13.00	23.33	135
7	13159.1	-46.64	7.51	16.55	Horizontal	-37.64	-13.00	24.64	45
8	15041.3	-44.31	8.24	15.35	Horizontal	-37.25	-13.00	24.25	270
9	16922.3	-43.34	8.41	14.95	Horizontal	-36.85	-13.00	23.85	180
10	18800.0	-44.21	8.54	15.45	Horizontal	-37.34	-13.00	24.34	270
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

GSM 1900 CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3819.6	-55.35	5.10	11.05	Horizontal	-49.38	-13.00	36.38	135
3	5729.1	-53.93	5.42	12.65	Horizontal	-46.71	-13.00	33.71	45
4	7640.4	-49.95	6.7	13.85	Horizontal	-42.85	-13.00	29.85	180
5	9547.9	-49.94	7.01	14.75	Horizontal	-42.20	-13.00	29.20	270
6	11457.0	-46.97	7.48	15.95	Horizontal	-38.47	-13.00	25.47	135
7	13367.3	-47.74	7.51	16.55	Horizontal	-38.72	-13.00	25.72	45
8	15279.8	-45.41	8.24	15.35	Horizontal	-38.35	-13.00	25.35	180
9	17188.9	-43.04	8.41	14.95	Horizontal	-36.54	-13.00	23.54	225
10	19098.0	-43.81	8.54	15.45	Horizontal	-36.94	-13.00	23.94	135

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

WCDMA Band II CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3704.8	-48.85	5.10	11.05	Horizontal	-42.87	-13.00	29.87	180
3	5553.8	-54.03	5.42	12.65	Horizontal	-46.80	-13.00	33.80	270
4	7409.6	-50.55	6.7	13.85	Horizontal	-43.40	-13.00	30.40	135
5	9262.0	-48.54	7.01	14.75	Horizontal	-40.80	-13.00	27.80	45
6	11114.4	-43.37	7.48	15.95	Horizontal	-34.90	-13.00	21.90	270
7	12966.8	-46.64	7.51	16.55	Horizontal	-37.60	-13.00	24.60	180
8	14819.2	-44.11	8.24	15.35	Horizontal	-37.00	-13.00	24.00	270
9	16671.6	-43.44	8.41	14.95	Horizontal	-36.90	-13.00	23.90	135
10	18524.0	-42.21	8.54	15.45	Horizontal	-35.30	-13.00	22.30	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



WCDMA Band II CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.0	-48.75	5.10	11.05	Horizontal	-42.76	-13.00	29.76	270
3	5640.0	-54.93	5.42	12.65	Horizontal	-47.72	-13.00	34.72	135
4	7520.0	-50.15	6.7	13.85	Horizontal	-43.00	-13.00	30.00	45
5	9400.0	-48.94	7.01	14.75	Horizontal	-41.20	-13.00	28.20	270
6	11280.0	-43.57	7.48	15.95	Horizontal	-35.10	-13.00	22.10	180
7	13160.0	-46.54	7.51	16.55	Horizontal	-37.50	-13.00	24.50	270
8	15040.0	-43.21	8.24	15.35	Horizontal	-36.10	-13.00	23.10	135
9	16920.0	-43.74	8.41	14.95	Horizontal	-37.20	-13.00	24.20	180
10	18800.0	-42.11	8.54	15.45	Horizontal	-35.20	-13.00	22.20	270

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

WCDMA Band II CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3815.2	-47.25	5.10	11.05	Horizontal	-41.31	-13.00	28.31	135
3	5726.3	-51.23	5.42	12.65	Horizontal	-43.99	-13.00	30.99	45
4	7630.4	-50.05	6.7	13.85	Horizontal	-42.90	-13.00	29.90	270
5	9538.0	-49.04	7.01	14.75	Horizontal	-41.30	-13.00	28.30	180
6	11445.6	-44.07	7.48	15.95	Horizontal	-35.60	-13.00	22.60	270
7	13353.2	-46.74	7.51	16.55	Horizontal	-37.70	-13.00	24.70	135
8	15260.8	-44.11	8.24	15.35	Horizontal	-37.00	-13.00	24.00	225
9	17168.4	-43.84	8.41	14.95	Horizontal	-37.30	-13.00	24.30	90
10	19076.0	-42.51	8.54	15.45	Horizontal	-35.60	-13.00	22.60	315

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 1.4MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3700.5	-47.75	5.10	11.05	Horizontal	-41.81	-13.00	28.81	45
3	5550.8	-50.03	5.42	12.65	Horizontal	-42.77	-13.00	29.77	225
4	7402.8	-50.15	6.7	13.85	Horizontal	-43.00	-13.00	30.00	135
5	9253.5	-47.44	7.01	14.75	Horizontal	-39.70	-13.00	26.70	180
6	11104.2	-46.87	7.48	15.95	Horizontal	-38.40	-13.00	25.40	180
7	12954.9	-46.64	7.51	16.55	Horizontal	-37.60	-13.00	24.60	270
8	14805.6	-42.71	8.24	15.35	Horizontal	-35.60	-13.00	22.60	270
9	16656.3	-43.34	8.41	14.95	Horizontal	-36.80	-13.00	23.80	180
10	18507.0	-41.81	8.54	15.45	Horizontal	-34.90	-13.00	21.90	270
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 2 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3759.0	-47.35	5.10	11.05	Horizontal	-41.36	-13.00	28.36	135
3	5638.9	-50.33	5.42	12.65	Horizontal	-43.13	-13.00	30.13	90
4	7520.0	-49.25	6.70	13.85	Horizontal	-42.06	-13.00	29.06	0
5	9400.0	-46.94	7.01	14.75	Horizontal	-39.20	-13.00	26.20	45
6	11280.0	-46.97	7.48	15.95	Horizontal	-38.50	-13.00	25.50	225
7	13160.0	-46.34	7.51	16.55	Horizontal	-37.30	-13.00	24.30	315
8	15040.0	-42.31	8.24	15.35	Horizontal	-35.20	-13.00	22.20	135
9	16920.0	-43.54	8.41	14.95	Horizontal	-37.00	-13.00	24.00	135
10	18800.0	-41.71	8.54	15.45	Horizontal	-34.80	-13.00	21.80	0
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 2 1.4MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3817.5	-47.85	5.10	11.05	Horizontal	-41.93	-13.00	28.93	270
3	5726.6	-50.83	5.42	12.65	Horizontal	-43.58	-13.00	30.58	270
4	7637.2	-49.65	6.70	13.85	Horizontal	-42.50	-13.00	29.50	315
5	9546.5	-47.44	7.01	14.75	Horizontal	-39.70	-13.00	26.70	225
6	11455.8	-46.67	7.48	15.95	Horizontal	-38.20	-13.00	25.20	0
7	13365.1	-46.14	7.51	16.55	Horizontal	-37.10	-13.00	24.10	180
8	15274.4	-43.01	8.24	15.35	Horizontal	-35.90	-13.00	22.90	180
9	17183.7	-43.04	8.41	14.95	Horizontal	-36.50	-13.00	23.50	90
10	19093.0	-42.11	8.54	15.45	Horizontal	-35.20	-13.00	22.20	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 3MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3700.1	-49.15	5.10	11.05	Horizontal	-43.15	-13.00	30.15	270
3	5550.8	-52.63	5.42	12.65	Horizontal	-45.40	-13.00	32.40	135
4	7406.0	-50.95	6.70	13.85	Horizontal	-43.80	-13.00	30.80	45
5	9257.5	-46.24	7.01	14.75	Horizontal	-38.50	-13.00	25.50	270
6	11109.0	-46.47	7.48	15.95	Horizontal	-38.00	-13.00	25.00	0
7	12960.5	-46.24	7.51	16.55	Horizontal	-37.20	-13.00	24.20	0
8	14812.0	-42.21	8.24	15.35	Horizontal	-35.10	-13.00	22.10	225
9	16663.5	-43.54	8.41	14.95	Horizontal	-37.00	-13.00	24.00	45
10	18515.0	-41.61	8.54	15.45	Horizontal	-34.70	-13.00	21.70	0

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



LTE Band 2 3MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.0	-47.95	5.10	11.05	Horizontal	-42.00	-13.00	29.00	90
3	5640.0	-52.33	5.42	12.65	Horizontal	-45.14	-13.00	32.14	135
4	7520.0	-49.45	6.70	13.85	Horizontal	-42.31	-13.00	29.31	225
5	9400.0	-46.64	7.01	14.75	Horizontal	-38.90	-13.00	25.90	90
6	11280.0	-46.87	7.48	15.95	Horizontal	-38.40	-13.00	25.40	315
7	13160.0	-46.54	7.51	16.55	Horizontal	-37.50	-13.00	24.50	135
8	15040.0	-42.71	8.24	15.35	Horizontal	-35.60	-13.00	22.60	0
9	16920.0	-42.74	8.41	14.95	Horizontal	-36.20	-13.00	23.20	315
10	18800.0	-41.41	8.54	15.45	Horizontal	-34.50	-13.00	21.50	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 3MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3817.0	-47.45	5.10	11.05	Horizontal	-41.46	-13.00	28.46	45
3	5725.5	-53.03	5.42	12.65	Horizontal	-45.80	-13.00	32.80	315
4	7634.0	-49.65	6.70	13.85	Horizontal	-42.50	-13.00	29.50	180
5	9542.5	-46.74	7.01	14.75	Horizontal	-39.00	-13.00	26.00	135
6	11451.0	-45.67	7.48	15.95	Horizontal	-37.20	-13.00	24.20	90
7	13359.5	-47.04	7.51	16.55	Horizontal	-38.00	-13.00	25.00	90
8	15268.0	-44.71	8.24	15.35	Horizontal	-37.60	-13.00	24.60	0
9	17176.5	-42.84	8.41	14.95	Horizontal	-36.30	-13.00	23.30	225
10	19085.0	-42.11	8.54	15.45	Horizontal	-35.20	-13.00	22.20	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 5MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3705.0	-49.45	5.10	11.05	Horizontal	-43.55	-13.00	30.55	90
3	5557.5	-49.93	5.42	12.65	Horizontal	-42.72	-13.00	29.72	225
4	7410.0	-49.55	6.70	13.85	Horizontal	-42.36	-13.00	29.36	135
5	9262.5	-47.24	7.01	14.75	Horizontal	-39.49	-13.00	26.49	270
6	11115.0	-47.27	7.48	15.95	Horizontal	-38.78	-13.00	25.78	135
7	12967.5	-46.34	7.51	16.55	Horizontal	-37.32	-13.00	24.32	45
8	14820.0	-42.11	8.24	15.35	Horizontal	-35.03	-13.00	22.03	45
9	16672.5	-44.24	8.41	14.95	Horizontal	-37.72	-13.00	24.72	0
10	18525.0	-42.01	8.54	15.45	Horizontal	-35.10	-13.00	22.10	180
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 2 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.0	-46.05	5.10	11.05	Horizontal	-40.15	-13.00	27.15	270
3	5640.0	-52.73	5.42	12.65	Horizontal	-45.51	-13.00	32.51	135
4	7520.0	-49.65	6.70	13.85	Horizontal	-42.49	-13.00	29.49	0
5	9400.0	-48.14	7.01	14.75	Horizontal	-40.45	-13.00	27.45	90
6	11280.0	-46.47	7.48	15.95	Horizontal	-37.96	-13.00	24.96	0
7	13160.0	-46.74	7.51	16.55	Horizontal	-37.68	-13.00	24.68	270
8	15040.0	-45.51	8.24	15.35	Horizontal	-38.45	-13.00	25.45	90
9	16920.0	-42.64	8.41	14.95	Horizontal	-36.11	-13.00	23.11	180
10	18800.0	-42.71	8.54	15.45	Horizontal	-35.80	-13.00	22.80	45
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 2 5MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3815.0	-47.35	5.10	11.05	Horizontal	-41.37	-13.00	28.37	45
3	5722.5	-50.03	5.42	12.65	Horizontal	-42.84	-13.00	29.84	315
4	7630.0	-48.85	6.70	13.85	Horizontal	-41.70	-13.00	28.70	315
5	9537.5	-46.64	7.01	14.75	Horizontal	-38.90	-13.00	25.90	135
6	11445.0	-47.17	7.48	15.95	Horizontal	-38.70	-13.00	25.70	315
7	13352.5	-46.14	7.51	16.55	Horizontal	-37.10	-13.00	24.10	315
8	15260.0	-41.41	8.24	15.35	Horizontal	-34.30	-13.00	21.30	180
9	17167.5	-43.44	8.41	14.95	Horizontal	-36.90	-13.00	23.90	90
10	19075.0	-41.91	8.54	15.45	Horizontal	-35.00	-13.00	22.00	315

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 10MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3710.0	-47.85	5.10	11.05	Horizontal	-41.88	-13.00	28.88	135
3	5565.0	-52.33	5.42	12.65	Horizontal	-45.10	-13.00	32.10	180
4	7420.0	-49.95	6.70	13.85	Horizontal	-42.80	-13.00	29.80	0
5	9275.0	-47.34	7.01	14.75	Horizontal	-39.60	-13.00	26.60	225
6	11130.0	-46.57	7.48	15.95	Horizontal	-38.10	-13.00	25.10	90
7	12985.0	-45.84	7.51	16.55	Horizontal	-36.80	-13.00	23.80	45
8	14840.0	-41.91	8.24	15.35	Horizontal	-34.80	-13.00	21.80	315
9	16695.0	-43.74	8.41	14.95	Horizontal	-37.20	-13.00	24.20	0
10	18550.0	-41.51	8.54	15.45	Horizontal	-34.60	-13.00	21.60	0

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.0	-45.65	5.10	11.05	Horizontal	-39.71	-13.00	26.71	315
3	5640.0	-48.93	5.42	12.65	Horizontal	-41.65	-13.00	28.65	90
4	7520.0	-49.35	6.70	13.85	Horizontal	-42.20	-13.00	29.20	0
5	9400.0	-47.04	7.01	14.75	Horizontal	-39.30	-13.00	26.30	90
6	11280.0	-46.97	7.48	15.95	Horizontal	-38.50	-13.00	25.50	90
7	13160.0	-46.24	7.51	16.55	Horizontal	-37.20	-13.00	24.20	270
8	15040.0	-42.51	8.24	15.35	Horizontal	-35.40	-13.00	22.40	135
9	16920.0	-43.84	8.41	14.95	Horizontal	-37.30	-13.00	24.30	90
10	18800.0	-41.71	8.54	15.45	Horizontal	-34.80	-13.00	21.80	0
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 2 10MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3810.0	-44.85	5.10	11.05	Horizontal	-38.90	-13.00	25.90	45
3	5715.0	-48.43	5.42	12.65	Horizontal	-41.24	-13.00	28.24	135
4	7620.0	-49.05	6.70	13.85	Horizontal	-41.90	-13.00	28.90	90
5	9525.0	-47.54	7.01	14.75	Horizontal	-39.80	-13.00	26.80	315
6	11430.0	-46.67	7.48	15.95	Horizontal	-38.20	-13.00	25.20	0
7	13335.0	-46.54	7.51	16.55	Horizontal	-37.50	-13.00	24.50	270
8	15240.0	-43.21	8.24	15.35	Horizontal	-36.10	-13.00	23.10	45
9	17145.0	-44.04	8.41	14.95	Horizontal	-37.50	-13.00	24.50	135
10	19050.0	-42.11	8.54	15.45	Horizontal	-35.20	-13.00	22.20	90
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									



LTE Band 2 15MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3715.0	-47.45	5.10	11.05	Horizontal	-41.46	-13.00	28.46	45
3	5572.5	-50.83	5.42	12.65	Horizontal	-43.59	-13.00	30.59	90
4	7430.0	-49.35	6.70	13.85	Horizontal	-42.24	-13.00	29.24	270
5	9287.5	-47.24	7.01	14.75	Horizontal	-39.50	-13.00	26.50	225
6	11145.0	-46.47	7.48	15.95	Horizontal	-37.99	-13.00	24.99	90
7	13002.5	-47.34	7.51	16.55	Horizontal	-38.30	-13.00	25.30	45
8	14860.0	-45.71	8.24	15.35	Horizontal	-38.56	-13.00	25.56	135
9	16717.5	-43.04	8.41	14.95	Horizontal	-36.51	-13.00	23.51	225
10	18575.0	-42.71	8.54	15.45	Horizontal	-35.85	-13.00	22.85	90

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 15MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.0	-45.15	5.10	11.05	Horizontal	-39.16	-13.00	26.16	135
3	5640.0	-50.23	5.42	12.65	Horizontal	-42.98	-13.00	29.98	135
4	7520.0	-48.95	6.70	13.85	Horizontal	-41.77	-13.00	28.77	45
5	9400.0	-47.94	7.01	14.75	Horizontal	-40.23	-13.00	27.23	270
6	11280.0	-46.07	7.48	15.95	Horizontal	-37.60	-13.00	24.60	135
7	13160.0	-47.04	7.51	16.55	Horizontal	-37.98	-13.00	24.98	45
8	15040.0	-43.91	8.24	15.35	Horizontal	-36.83	-13.00	23.83	180
9	16920.0	-43.84	8.41	14.95	Horizontal	-37.27	-13.00	24.27	180
10	18800.0	-43.41	8.54	15.45	Horizontal	-36.50	-13.00	23.50	45

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 2 15MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3805.0	-43.45	5.10	11.05	Horizontal	-37.50	-13.00	24.50	45
3	5707.5	-47.43	5.42	12.65	Horizontal	-40.23	-13.00	27.23	180
4	7610.0	-49.15	6.70	13.85	Horizontal	-41.98	-13.00	28.98	180
5	9512.5	-48.74	7.01	14.75	Horizontal	-41.00	-13.00	28.00	225
6	11415.0	-46.47	7.48	15.95	Horizontal	-38.00	-13.00	25.00	0
7	13317.5	-45.94	7.51	16.55	Horizontal	-36.93	-13.00	23.93	180
8	15220.0	-44.11	8.24	15.35	Horizontal	-36.96	-13.00	23.96	270
9	17122.5	-43.64	8.41	14.95	Horizontal	-37.11	-13.00	24.11	90
10	19025.0	-42.21	8.54	15.45	Horizontal	-35.30	-13.00	22.30	0
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 2 20MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3720.0	-47.45	5.10	11.05	Horizontal	-41.54	-13.00	28.54	180
3	5580.0	-51.33	5.42	12.65	Horizontal	-44.10	-13.00	31.10	45
4	7440.0	-49.35	6.70	13.85	Horizontal	-42.20	-13.00	29.20	135
5	9300.0	-47.74	7.01	14.75	Horizontal	-40.00	-13.00	27.00	180
6	11160.0	-46.57	7.48	15.95	Horizontal	-38.10	-13.00	25.10	225
7	13020.0	-47.64	7.51	16.55	Horizontal	-38.60	-13.00	25.60	270
8	14880.0	-43.41	8.24	15.35	Horizontal	-36.30	-13.00	23.30	0
9	16740.0	-43.64	8.41	14.95	Horizontal	-37.10	-13.00	24.10	180
10	18600.0	-42.81	8.54	15.45	Horizontal	-35.90	-13.00	22.90	135
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 2 20MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3760.0	-44.35	5.10	11.05	Horizontal	-38.36	-13.00	25.36	225
3	5640.0	-49.03	5.42	12.65	Horizontal	-41.79	-13.00	28.79	315
4	7520.0	-49.45	6.70	13.85	Horizontal	-42.30	-13.00	29.30	0
5	9400.0	-47.14	7.01	14.75	Horizontal	-39.40	-13.00	26.40	90
6	11280.0	-46.47	7.48	15.95	Horizontal	-38.00	-13.00	25.00	225
7	13160.0	-49.04	7.51	16.55	Horizontal	-40.00	-13.00	27.00	180
8	15040.0	-46.41	8.24	15.35	Horizontal	-39.30	-13.00	26.30	45
9	16920.0	-42.24	8.41	14.95	Horizontal	-35.70	-13.00	22.70	225
10	18800.0	-41.31	8.54	15.45	Horizontal	-34.40	-13.00	21.40	135
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 2 20MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3800.0	-45.75	5.10	11.05	Horizontal	-39.85	-13.00	26.85	0
3	5700.0	-53.53	5.42	12.65	Horizontal	-46.30	-13.00	33.30	180
4	7600.0	-49.65	6.70	13.85	Horizontal	-42.50	-13.00	29.50	135
5	9500.0	-49.54	7.01	14.75	Horizontal	-41.80	-13.00	28.80	225
6	11400.0	-44.97	7.48	15.95	Horizontal	-36.50	-13.00	23.50	315
7	13300.0	-45.54	7.51	16.55	Horizontal	-36.50	-13.00	23.50	0
8	15200.0	-44.71	8.24	15.35	Horizontal	-37.60	-13.00	24.60	90
9	17100.0	-41.94	8.41	14.95	Horizontal	-35.40	-13.00	22.40	225
10	19000.0	-41.01	8.54	15.45	Horizontal	-34.10	-13.00	21.10	135
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMU200	118133	2017-05-14	2018-05-13
Base Station Simulator	R&S	CMW500	113645	2017-05-14	2018-05-13
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	2017-05-14	2018-05-13
Spectrum Analyzer	Agilent	N9010A	MY47191109	2017-05-20	2018-05-19
Universal Radio Communication Tester	Agilent	E5515C	MY48367192	2017-05-20	2018-05-19
Signal Analyzer	R&S	FSV30	100815	2017-12-17	2018-12-16
EMI Test Receiver	R&S	ESCI	100948	2017-05-20	2018-05-19
Signal generator	R&S	SMB 100A	102594	2017-05-14	2018-05-13
Signal generator	R&S	SMR27	100365	2017-05-14	2018-05-13
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	100126	2014-12-06	2019-12-05
Climatic Chamber	Re Ce	PT-30B	20101891	2015-07-18	2018-07-17
Horn Antenna	ETS-Lindgren	3160-09	00102644	2015-01-30	2020-01-29
RF Cable	Agilent	SMA 15cm	0001	/	/
Preamplifier	R&S	SCU18	102327	2017-06-18	2018-06-17
Software	R&S	EMC32	V 8.52.0	/	/

*****END OF REPORT *****