



RF TEST REPORT

Applicant Quectel Wireless Solutions Co., Ltd.

FCC ID XMR2022BG955AGL

Product LTE Cat M1/NB1/GPRS/GNSS Module

Brand Quectel

Model BG955A-GL

Report No. R2208A0765-R2V1

Issue Date November 18, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2021)/ FCC CFR 47 Part 24E (2021)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Xu Ying

Approved by: Xu Kai

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

TABLE OF CONTENT

1. Test Laboratory	5
1.1. Notes of the test report	5
1.2. Test facility	5
1.3. Testing Location	5
2. General Description of Equipment under Test	6
2.1. Applicant and Manufacturer Information	6
2.2. General information	6
3. Applied Standards	8
4. Test Configuration	9
5. Test Case	10
5.1. RF Power Output and Effective Isotropic Radiated Power	10
5.2. Occupied Bandwidth	11
5.3. Band Edge Compliance	12
5.4. Peak-to-Average Power Ratio (PAPR)	13
5.5. Frequency Stability	14
5.6. Spurious Emissions at Antenna Terminals	16
5.7. Radiated Spurious Emission	17
6. Test Results	20
6.1. RF Power Output and Effective Isotropic Radiated Power	20
6.2. Occupied Bandwidth	21
6.3. Band Edge Compliance	28
6.4. Peak-to-Average Power Ratio (PAPR)	32
6.5. Frequency Stability	33
6.6. Spurious Emissions at Antenna Terminals	35
6.7. Radiated Spurious Emission	36
7. Main Test Instruments	39
ANNEX A: The EUT Appearance	40
ANNEX B: Test Setup Photos	41



Version	Revision description	Issue Date
Rev.0	Initial issue of report.	October 21, 2022
Rev.1	Update information.	November 18, 2022
Note: This revised report (Report No. R2208A0765-R2V1) supersedes and replaces the previously issued report (Report No. R2208A0765-R2). Please discard or destroy the previously issued report and dispose of it accordingly.		

Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Isotropic Radiated Power	2.1046 24.232(c)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge Compliance	2.1051 /24.238(a)	PASS
4	Peak-to-Average Power Ratio	24.232/KDB 971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 24.235	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 24.238(a)	PASS
7	Radiated Spurious Emission	2.1053 / 24.238(a)	PASS
Date of Testing: September 8, 2022~September 29, 2022 and October 18, 2022			
Date of Sample Received: September 6, 2022			
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

2.1. Applicant and Manufacturer Information

Applicant	Quectel Wireless Solutions Co., Ltd.
Applicant address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China, 200233
Manufacturer	Quectel Wireless Solutions Co., Ltd.
Manufacturer address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China, 200233

2.2. General information

EUT Description			
Model	BG955A-GL		
IMEI	868348060003740		
Hardware Version	R1.2		
Software Version	BG955AGLAAR02A01		
Power Supply	External power supply		
Antenna Type	External Antenna		
Antenna Gain	Mode	Frequency (MHz)	Gain (dBi)
	NB-IoT Band 2/25	1840	1.36
		1860	1.25
		1880	1.38
		1900	1.59
		1920	1.36
Test Mode(s)	NB-IoT Band 2/25		
Test Modulation:	BPSK, QPSK		
Category	NB 2		
Deployment:	Stand-alone; In-Band; Guard-Band		
Sub-carrier spacing:	3.75KHz, 15KHz		
Ntones:	single-tone, multi-tone		
Maximum E.I.R.P	NB-IoT Band 2:	25.12 dBm	
	NB-IoT Band 25:	24.84 dBm	
Rated Power Supply Voltage	DC 3.8V		
Operating Voltage	Minimum: 3.3V	Maximum: 4.3V	
Operating Temperature	Lowest:-35 °C	Highest: +75°C	
Testing Temperature	Lowest: -30°C	Highest: +50°C	
Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	NB-IoT Band 2	1850 ~ 1910	1930 ~ 1990
	NB-IoT Band 25	1850 ~ 1915	1930 ~ 1995



Note:

1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.

3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR 47 Part 24E (2021)

FCC CFR47 Part 2 (2021)

Reference standard:

ANSI C63.26-2015

KDB 971168 D01 Power Meas License Digital Systems v03r01

4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (Z axis, vertical polarization) and the worst case was recorded.

All modes as Subcarrier Spacing, modulations, Channel were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in NB-IoT is set based on the maximum RF Output Power.

The following testing in different mode is set to detail in the following table:

Test modes are chosen to be reported as the worst case configuration below for NB-IoT Band 2/25

Test items	Deployment mode	Subcarrier Spacing (kHz)		Modulation		Test Channel		
	Stand-alone	3.75	15	BPSK	QPSK	L	M	H
RF Power Output and Effective Isotropic Radiated Power	O	O	O	O	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	O	O
Band Edge Compliance	O	O	O	O	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	-	O	-
Frequency Stability	O	O	O	O	O	-	O	-
Spurious Emissions at Antenna Terminals	O	-	O	-	O	O	O	O
Radiated Spurious Emission	O	O	-	-	O	O	O	O
Note 1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.								

5. Test Case

5.1.RF Power Output and Effective Isotropic Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.


ERP can then be calculated as follows:

$EIRP \text{ (dBm)} = \text{Output Power (dBm)} + \text{Antenna Gain (dBi)}$

where:dBd refers to gain relative to an ideal dipole.

$EIRP \text{ (dBm)} = ERP \text{ (dBm)} + 2.15 \text{ (dB.)}$

Test Setup



Limits

No specific RF power output requirements in part 2.1046.

Rule Part 24.232(c) Mobile and portable stations are limited to 2 watts EIRP.

Rule Part 24.232(e) Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

Limit	$\leq 2 \text{ W}$ (33 dBm)
-------	-----------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4 \text{ dB}$ for RF power output, $k = 2$, $U = 1.19 \text{ dB}$ for EIRP.

Test Results

Refer to the section 6.1 of this report for test data.

5.2.Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to $\geq 1\%EBW$, VBW is set to 3x RBW.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.

Test Results

Refer to the section 6.2 of this report for test data.

5.3. Band Edge Compliance

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The Average detector is used and RBW is set to $\geq 1\%EBW$, VBW is set to 3x RBW.

Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684\text{dB}$.

Test Results

Refer to the section 6.3 of this report for test data.

5.4. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as PPK. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = \text{PPk (dBm)} - \text{PAvg (dBm)}.$$

Test Setup



Limits

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB in 24.232(d).

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

Test Results

Refer to the section 6.4 of this report for test data.

5.5.Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.


Frequency Stability (Voltage Variation)

The frequency stability shall be measured with variation of primary supply voltage as follows:

Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.3 V and 4.3V, with a nominal voltage of 3.8V.

Test setup



Limits

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.

Test Results

Refer to the section 6.5 of this report for test data.

5.6. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used.

RBW is set to 1 kHz (0.009MHz~ 0.15 MHz),

RBW is set to 10 kHz (0.15 MHz~ 30 MHz)


RBW is set to 100 kHz (30MHz~1000 MHz)

RBW is set to 1000 kHz (above 1000MHz)

Sweep is set to ATUO.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9kHz-1GHz	0.684 dB
9kHz~20GHz	1.407 dB

Test Results

Refer to the section 6.6 of this report for test data.

5.7. Radiated Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26-2015.
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, and the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:

$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$
The measurement results are amend as described below:


$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP

= EIRP-2.15dB.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup


9KHz~ 30MHz



30MHz~ 1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m

Limits

Rule Part 24.238(a) specifies that “on any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10} (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

Test Results

Refer to the section 6.7 of this report for test data.

6. Test Results

6.1.RF Power Output and Effective Isotropic Radiated Power

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Conducted Power (dBm) for low/mid/high channel			EIRP (dBm)		
				18602/1850.2	18900/1880.0	19198/1909.8	18602/1850.2	18900/1880.0	19198/1909.8
NB-IoT Band 2	BPSK	3.75	1@0	23.40	23.29	23.48	24.65	24.67	25.07
			1@47	23.38	23.27	23.45	24.63	24.65	25.04
		15	1@0	23.29	23.25	23.44	24.54	24.63	25.03
			1@11	23.26	23.28	23.43	24.51	24.66	25.02
	QPSK	3.75	1@0	23.41	23.30	23.53	24.66	24.68	25.12
			1@47	23.36	23.24	23.46	24.61	24.62	25.05
		15	1@0	23.21	23.20	23.45	24.46	24.58	25.04
			1@11	23.25	23.30	23.46	24.50	24.68	25.05
		15	12@0	21.06	20.97	21.11	22.31	22.35	22.70


Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Conducted Power (dBm) for low/mid/high channel			EIRP (dBm)		
				26042/1850.2	26365/1882.5	26688/1914.8	26042/1850.2	26365/1882.5	26688/1914.8
NB-IoT Band 25	BPSK	3.75	1@0	23.30	23.16	23.37	24.55	24.54	24.73
			1@47	23.28	23.15	23.35	24.53	24.53	24.71
		15	1@0	23.22	23.32	23.48	24.47	24.70	24.84
			1@11	23.24	23.34	23.34	24.49	24.72	24.70
	QPSK	3.75	1@0	23.37	23.11	23.40	24.62	24.49	24.76
			1@47	23.35	23.13	23.34	24.60	24.51	24.70
		15	1@0	23.21	23.41	23.35	24.46	24.79	24.71
			1@11	23.25	23.37	23.40	24.50	24.75	24.76
		15	12@0	21.08	21.12	21.18	22.33	22.50	22.54

6.2.Occupied Bandwidth

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Bandwidth(KHz) for low/mid/high channel					
				18602/1850.2		18900/1880.0		19198/1909.8	
				99% Power	-26dBc	99% Power	-26dBc	99% Power	-26dBc
NB-IoT Band 2	BPSK	3.75	1@0	39.47	38.53	38.90	36.91	38.10	35.97
	QPSK	3.75	1@0	42.99	41.64	43.51	41.62	45.25	42.35
	BPSK	15	1@0	74.05	91.94	81.76	102.20	75.70	98.03
	QPSK	15	1@0	73.85	101.80	77.46	102.60	75.73	103.00
	QPSK	15	12@0	186.63	252.90	187.58	261.70	186.81	267.00

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Bandwidth(KHz) for low/mid/high channel					
				26042/1850.2		26365/1882.5		26688/1914.8	
				99% Power	-26dBc	99% Power	-26dBc	99% Power	-26dBc
NB-IoT Band 25	BPSK	3.75	1@0	38.81	37.49	40.14	37.66	40.28	37.23
	QPSK	3.75	1@0	43.04	40.54	44.36	41.56	43.20	40.27
	BPSK	15	1@0	74.28	90.30	75.64	89.40	77.09	96.70
	QPSK	15	1@0	72.46	99.60	75.26	100.60	79.77	90.64
	QPSK	15	12@0	185.59	261.10	184.49	266.80	185.41	267.00


NB-IOT Band 2 BPSK 3.75kHz 1@0 CH-Low



NB-IOT Band 2 BPSK 15kHz 1@0 CH-Low




NB-IOT Band 2 BPSK 3.75kHz 1@0 CH-Middle




NB-IOT Band 2 BPSK 15kHz 1@0 CH-Middle




NB-IOT Band 2 BPSK 3.75kHz 1@0 CH-High



NB-IOT Band 2 BPSK 15kHz 1@0 CH-High




NB-IOT Band 2 QPSK 3.75kHz 1@0 CH-Low




NB-IOT Band 2 QPSK 15kHz 1@0 CH-Low




NB-IOT Band 2 QPSK 3.75kHz 1@0 CH-Middle




NB-IOT Band 2 QPSK 15kHz 1@0 CH-Middle



NB-IOT Band 2 QPSK 3.75kHz 1@0 CH-High




NB-IOT Band 2 QPSK 15kHz 1@0 CH-High



NB-IOT Band 2 QPSK 15kHz 12@0 CH-Low




NB-IOT Band 2 QPSK 15kHz 12@0 CH-Middle



NB-IOT Band 2 QPSK 15kHz 12@0 CH-High



NB-IOT Band 25 BPSK 3.75kHz 1@0 CH-Low



NB-IOT Band 25 BPSK 15kHz 1@0 CH-Low




NB-IOT Band 25 BPSK 3.75kHz 1@0 CH-Middle




NB-IOT Band 25 BPSK 15kHz 1@0 CH-Middle




NB-IOT Band 25 BPSK 3.75kHz 1@0 CH-High



NB-IOT Band 25 BPSK 15kHz 1@0 CH-High



NB-IOT Band 25 QPSK 3.75kHz 1@0 CH-Low



NB-IOT Band 25 QPSK 15kHz 1@0 CH-Low




NB-IOT Band 25 QPSK 3.75kHz 1@0 CH-Middle




NB-IOT Band 25 QPSK 15kHz 1@0 CH-Middle



NB-IOT Band 25 QPSK 3.75kHz 1@0 CH-High



NB-IOT Band 25 QPSK 15kHz 1@0 CH-High



NB-IOT Band 25 QPSK 15kHz 12@0 CH-Low




NB-IOT Band 25 QPSK 15kHz 12@0 CH-Middle




NB-IOT Band 25 QPSK 15kHz 12@0 CH-High




6.3. Band Edge Compliance




NB-IOT Band 2 QPSK 15kHz 1@0 CH-Low




NB-IOT Band 2 QPSK 15kHz 1@11 CH-High




NB-IOT Band 2 QPSK 15kHz 12@0 CH-Low




NB-IOT Band 2 QPSK 15kHz 12@0 CH-High




NB-IOT Band 25 BPSK 3.75kHz 1@0 CH-Low




NB-IOT Band 25 BPSK 3.75kHz 1@47 CH-High




NB-IOT Band 25 BPSK 15kHz 1@0 CH-Low




NB-IOT Band 25 BPSK 15kHz 1@11 CH-High




NB-IOT Band 25 QPSK 3.75kHz 1@0 CH-Low




NB-IOT Band 25 QPSK 3.75kHz 1@47 CH-High




NB-IOT Band 25 QPSK 15kHz 1@0 CH-Low




NB-IOT Band 25 QPSK 15kHz 1@11 CH-High



NB-IOT Band 25 QPSK 15kHz 12@0 CH-Low



NB-IOT Band 25 QPSK 15kHz 12@0 CH-High



6.4. Peak-to-Average Power Ratio (PAPR)

Mode	Modulation	Sub-carrier spacing (KHz)	Channel/ Frequency(MHz)	Peak-to-Average Power Ratio (PAPR)		
				Peak(dBm)	Avg(dBm)	PAPR(dB)
NB-IoT Band 2	BPSK	3.75	18900/1880.0	22.51	19.56	2.95
	QPSK	3.75	18900/1880.0	22.72	19.70	3.02
	BPSK	15	18900/1880.0	23.81	17.57	6.24
	QPSK	15	18900/1880.0	23.65	17.35	6.30

Mode	Modulation	Sub-carrier spacing (KHz)	Channel/ Frequency(MHz)	Peak-to-Average Power Ratio (PAPR)		
				Peak(dBm)	Avg(dBm)	PAPR(dB)
NB-IoT Band 25	BPSK	3.75	26365/1882.5	22.90	19.94	2.96
	QPSK	3.75	26365/1882.5	22.85	19.88	2.97
	BPSK	15	26365/1882.5	23.88	17.68	6.20
	QPSK	15	26365/1882.5	23.91	17.63	6.28

6.5. Frequency Stability

	Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
	Sub-carrier spacing(KHz)	3.75					
NB-IoT Band 2	Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
	Normal (25℃)	Normal	17.98	8.55	0.00957	0.00455	
	Extreme (50℃)		10.92	10.73	0.00581	0.00571	
	Extreme (40℃)		1.51	16.44	0.00080	0.00874	
	Extreme (30℃)		9.24	6.75	0.00491	0.00359	
	Extreme (20℃)		6.79	3.24	0.00361	0.00172	
	Extreme (10℃)		14.08	15.18	0.00749	0.00808	
	Extreme (0℃)		13.54	2.50	0.00720	0.00133	
	Extreme (-10℃)		7.02	12.81	0.00373	0.00682	
	Extreme (-20℃)		11.64	2.68	0.00619	0.00142	
	Extreme (-30℃)		8.24	14.76	0.00438	0.00785	
	25℃	LV	6.60	6.45	0.00351	0.00343	
		HV	1.14	1.10	0.00061	0.00059	

	Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
	Sub-carrier spacing(KHz)	3.75					
NB-IoT Band 25	Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
	Normal (25℃)	Normal	5.32	11.22	0.00283	0.00597	
	Extreme (50℃)		4.97	2.92	0.00264	0.00155	
	Extreme (40℃)		5.50	16.14	0.00292	0.00858	
	Extreme (30℃)		13.02	17.77	0.00693	0.00945	
	Extreme (20℃)		1.05	16.44	0.00056	0.00874	
	Extreme (10℃)		4.25	11.28	0.00226	0.00600	
	Extreme (0℃)		13.79	14.25	0.00734	0.00758	
	Extreme (-10℃)		14.86	7.41	0.00791	0.00394	
	Extreme (-20℃)		16.20	1.29	0.00862	0.00068	
	Extreme (-30℃)		17.55	8.90	0.00934	0.00474	
	25℃	LV	1.51	16.54	0.00080	0.00880	
		HV	17.03	13.41	0.00906	0.00713	

NB-IoT Band 2	Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
	Sub-carrier spacing(KHz)	15					
	Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
NB-IoT Band 2	Normal (25℃)	Normal	10.24	3.36	0.00545	0.00179	PASS
	Extreme (50℃)		10.33	3.41	0.00550	0.00181	PASS
	Extreme (40℃)		13.64	14.86	0.00725	0.00790	PASS
	Extreme (30℃)		17.70	6.74	0.00941	0.00358	PASS
	Extreme (20℃)		10.63	9.21	0.00566	0.00490	PASS
	Extreme (10℃)		2.47	4.75	0.00132	0.00253	PASS
	Extreme (0℃)		5.55	15.39	0.00295	0.00819	PASS
	Extreme (-10℃)		9.74	8.12	0.00518	0.00432	PASS
	Extreme (-20℃)		1.76	16.37	0.00094	0.00871	PASS
	Extreme (-30℃)		6.25	5.02	0.00332	0.00267	PASS
	25℃	LV	14.19	7.36	0.00755	0.00392	PASS
		HV	5.72	1.04	0.00304	0.00055	PASS


NB-IoT Band 25	Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
	Sub-carrier spacing(KHz)	15					
	Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
NB-IoT Band 25	Normal (25℃)	Normal	9.87	17.33	0.00525	0.00922	PASS
	Extreme (50℃)		4.97	1.82	0.00264	0.00097	PASS
	Extreme (40℃)		6.48	3.25	0.00344	0.00173	PASS
	Extreme (30℃)		10.38	12.31	0.00552	0.00655	PASS
	Extreme (20℃)		16.04	10.60	0.00853	0.00564	PASS
	Extreme (10℃)		12.92	3.41	0.00687	0.00181	PASS
	Extreme (0℃)		8.78	15.17	0.00467	0.00807	PASS
	Extreme (-10℃)		11.82	13.29	0.00629	0.00707	PASS
	Extreme (-20℃)		16.33	1.16	0.00868	0.00062	PASS
	Extreme (-30℃)		13.52	17.57	0.00719	0.00935	PASS
	25℃	LV	9.43	6.10	0.00502	0.00325	PASS
		HV	3.50	13.83	0.00186	0.00736	PASS

6.6. Spurious Emissions at Antenna Terminals


Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The signal beyond the limit is carrier.


NB-IoT Band 2 CH-Low 9kHz~20GHz




NB-IoT Band 25 CH-Low 9kHz~20GHz




NB-IoT Band 2 CH-Middle 9kHz~20GHz




NB-IoT Band 25 CH-Middle 9kHz~20GHz



NB-IoT Band 2 CH-High 9kHz~20GHz



NB-IoT Band 25 CH-High 9kHz~20GHz



6.7. Radiated Spurious Emission

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

NB-IoT Band 2 3.75KHz+QPSK CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3700.20	-48.92	5.10	11.05	Vertical	-42.97	-13.00	29.97	90
3	5550.30	-56.58	5.42	12.65	Vertical	-49.35	-13.00	36.35	0
4	7400.40	-56.00	6.70	13.85	Vertical	-48.85	-13.00	35.85	0
5	9250.50	-52.40	7.01	14.75	Vertical	-44.66	-13.00	31.66	45
6	11100.60	-53.50	7.48	15.95	Vertical	-45.03	-13.00	32.03	225
7	12950.70	-53.06	7.51	16.55	Vertical	-44.02	-13.00	31.02	90
8	14800.80	-49.35	8.24	15.35	Vertical	-42.24	-13.00	29.24	45
9	16650.90	-48.87	8.41	14.95	Vertical	-42.33	-13.00	29.33	135
10	18501.00	--	--	--	--	--	--	--	--

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.

NB-IoT Band 2 3.75KHz+QPSK CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3759.75	-48.63	5.10	11.05	Vertical	-42.68	-13.00	29.68	225
3	5640.00	-57.02	5.42	12.65	Vertical	-49.79	-13.00	36.79	315
4	7520.00	-54.69	6.70	13.85	Vertical	-47.54	-13.00	34.54	180
5	9400.00	-52.31	7.01	14.75	Vertical	-44.57	-13.00	31.57	0
6	11280.00	-52.38	7.48	15.95	Vertical	-43.91	-13.00	30.91	0
7	13160.00	-53.89	7.51	16.55	Vertical	-44.85	-13.00	31.85	45
8	15040.00	-51.41	8.24	15.35	Vertical	-44.30	-13.00	31.30	315
9	16920.00	-49.00	8.41	14.95	Vertical	-42.46	-13.00	29.46	90
10	18800.00	--	--	--	Vertical	--	--	--	--

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.

NB-IoT Band 2 3.75KHz+QPSK CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3819.80	-52.04	2.60	12.50	Vertical	-42.14	-13.00	29.14	90
3	5729.70	-59.49	3.30	12.50	Vertical	-50.29	-13.00	37.29	0
4	7639.60	-56.55	4.20	12.20	Vertical	-48.55	-13.00	35.55	0
5	9549.50	-55.14	4.30	11.10	Vertical	-48.34	-13.00	35.34	45
6	11459.40	-48.82	5.90	11.90	Vertical	-42.82	-13.00	29.82	315
7	13369.30	-51.79	5.70	14.00	Vertical	-43.49	-13.00	30.49	90
8	15279.20	-51.96	5.80	13.10	Vertical	-44.66	-13.00	31.66	45
9	17189.10	-49.31	6.10	14.60	Vertical	-40.81	-13.00	27.81	135
10	19099.00	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.

NB-IoT Band 25 3.75KHz+QPSK CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3700.20	-48.60	5.10	11.05	Vertical	-42.65	-13.00	29.65	180
3	5550.30	-57.83	5.42	12.65	Vertical	-50.60	-13.00	37.60	0
4	7400.40	-57.29	6.70	13.85	Vertical	-50.14	-13.00	37.14	315
5	9250.50	-54.06	7.01	14.75	Vertical	-46.32	-13.00	33.32	45
6	11100.60	-52.89	7.48	15.95	Vertical	-44.42	-13.00	31.42	270
7	12950.70	-53.33	7.51	16.55	Vertical	-44.29	-13.00	31.29	90
8	14800.80	-51.61	8.24	15.35	Vertical	-44.50	-13.00	31.50	180
9	16650.90	-49.96	8.41	14.95	Vertical	-43.42	-13.00	30.42	90
10	18501.00	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Vertical position.

NB-IoT Band 25 3.75KHz+QPSK CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3765.00	-47.55	5.10	11.05	Vertical	-41.60	-13.00	28.60	315
3	5647.50	-56.13	5.42	12.65	Vertical	-48.90	-13.00	35.90	90
4	7530.00	-53.28	6.70	13.85	Vertical	-46.13	-13.00	33.13	180
5	9412.50	-55.33	7.01	14.75	Vertical	-47.59	-13.00	34.59	45
6	11295.00	-53.20	7.48	15.95	Vertical	-44.73	-13.00	31.73	315
7	13177.50	-52.58	7.51	16.55	Vertical	-43.54	-13.00	30.54	0
8	15060.00	-51.84	8.24	15.35	Vertical	-44.73	-13.00	31.73	180
9	16942.50	-48.32	8.41	14.95	Vertical	-41.78	-13.00	28.78	90
10	18825.00	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.

NB-IoT Band 25 3.75KHz+QPSK CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3829.80	-49.91	5.10	11.05	Vertical	-43.96	-13.00	30.96	90
3	5744.70	-56.80	5.42	12.65	Vertical	-49.57	-13.00	36.57	315
4	7659.60	-54.72	6.70	13.85	Vertical	-47.57	-13.00	34.57	180
5	9574.50	-56.37	7.01	14.75	Vertical	-48.63	-13.00	35.63	90
6	11489.40	-52.65	7.48	15.95	Vertical	-44.18	-13.00	31.18	180
7	13404.30	-51.90	7.51	16.55	Vertical	-42.86	-13.00	29.86	0
8	15319.20	-51.52	8.24	15.35	Vertical	-44.41	-13.00	31.41	270
9	17234.10	-48.99	8.41	14.95	Vertical	-42.45	-13.00	29.45	90
10	19149.00	--	--	--	--	--	--	--	--

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.

7. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Climatic Chamber	ESPEC	SU-242	93000506	2021-12-12	2022-12-11
Comprehensive measuring instrument	R&S	CMW500	150415	2022-05-14	2023-05-13
Spectrum Analyzer	Keysight	N9020A	MY50510203	2021-12-12	2022-12-11
Universal Radio Communication Tester	Agilent	E5515C	GB44400275	2021-12-12	2022-12-11
Universal Radio Communication Tester	StarPoint	SP8315	SP8315-1225	2022-05-14	2023-05-13
Spectrum Analyzer	R&S	FSV3030	101411	2021-12-12	2022-12-11
Radiated Spurious Emissions					
Signal Analyzer	R&S	FSV30	100815	2021-12-12	2022-12-11
Loop antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	01439	2021-06-30	2024-06-29
Horn Antenna	Schwarzbeck	BBHA 9120D	1594	2020-12-17	2023-12-16
Horn Antenna	ETS-Lindgren	3160-09	00102643	2021-10-10	2024-10-09
Software	R&S	EMC32	10.35.10	/	/

*****END OF REPORT *****



ANNEX A: The EUT Appearance

The EUT Appearance is submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos is submitted separately.