

RF Exposure Evaluation for Mobile

Model: **Low Power Bluetooth® transmitter**

FCC ID: **2AXVQ-WILIOT1**

Standards
OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR §1.1307
FCC 47 CFR §1.1310

Test limits

As specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure.

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1,500	f/1500
1,500 – 100,000	1.0

Equation OET bulletin 65, page 18, edition 97-01:
$$S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

Where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Distance = 20cm

Operational Bands	Frequency (MHz)	Antenna Gain (dBi)	Antenna Gain -numeric- (mW/cm ²)	Output Power -conducted- (dBm)	Output Power -conducted- (mW)	FCC Limit (mW/cm ²)	Power Density value (mW/cm ²)	Margin to FCC Limit (mW/cm ²)
Bluetooth Low Energy	2426	-2.41	0.5741	-18.12	0.02	1.00	0.000002	0.999998

Yours Sincerely,

T.S. Sunar

Teoman Soner Sunar