



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	AirTies Wireless Networks
Applicant Address	Gülbahar Mah. Avni Dilligil Sok. Celik Is Merkezi ISTANBUL, 34394 Turkey
FCC ID	Z3WAIR4920
Manufacturer's company	SHENZHEN GONGJIN ELECTRONICS CO.,LTD.
Manufacturer Address	2F/3F/4F Baiying Building, 1019#Naihai RD, Nanshan Dist., Shenzhen, Guangdong, CHINA

Product Name	2 Port Gigabit Ethernet 11ac/11n Wireless Router
Brand Name	AirTies
Model No.	Air 4920
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Oct. 22, 2014
Final Test Date	Dec. 27, 2014
Submission Type	Original Equipment

Statement

Test result included is only for the IEEE 802.11n, IEEE 802.11b/g and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r02, KDB 662911 D01 v02r01, KDB644545 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies	7
3.5. Table for Test Modes	8
3.6. Table for Testing Locations.....	10
3.7. Table for Supporting Units	10
3.8. Table for Parameters of Test Software Setting	11
3.9. EUT Operation during Test	12
3.10. Duty Cycle.....	13
3.11. Test Configurations	14
4. TEST RESULT	17
4.1. AC Power Line Conducted Emissions Measurement.....	17
4.2. Maximum Conducted Output Power Measurement.....	21
4.3. Power Spectral Density Measurement	25
4.4. 6dB Spectrum Bandwidth Measurement	39
4.5. Radiated Emissions Measurement	52
4.6. Emissions Measurement	79
4.7. Antenna Requirements	108
5. LIST OF MEASURING EQUIPMENTS	109
6. MEASUREMENT UNCERTAINTY.....	111
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3
APPENDIX C. RADIATED EMISSION CO-LOCATION REPORT	C1 ~ C3

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR490527-05AA	Rev. 01	Initial issue of report	Feb. 03, 2015



1. CERTIFICATE OF COMPLIANCE

Product Name : 2 Port Gigabit Ethernet 11ac/11n Wireless Router
Brand Name : AirTies
Model No. : Air 4920
Applicant : AirTies Wireless Networks
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Oct. 22, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink, appearing to read 'Sam Chen', is written over a horizontal line.

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	10.68 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	2.9 dB
4.3	15.247(e)	Power Spectral Density	Complies	5.98 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.03 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.04 dB
4.7	15.203	Antenna Requirements	Complies	-

Note: The test configuration and test mode was written in this test report are designated by the applicant.

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

Items	Description
Product Type	For 2.4GHz Band: WLAN (2TX, 2RX) For 5GHz Band: WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n/ac
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	For 2.4GHz Band: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth For 5GHz Band: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth ; 1 for 80MHz bandwidth
Channel Band Width (99%)	For 2.4GHz Band: For Non-Beamforming Mode: MCS0 (HT20): 17.76 MHz ; MCS0 (HT40): 36.80 MHz For 5GHz Band: For Beamforming Mode: 802.11ac MCS0/Nss1 (VHT20): 33.86 MHz ; 802.11ac MCS0/Nss1 (VHT40): 64.40 MHz ; 802.11ac MCS0/Nss1 (VHT80): 76.20 MHz
Maximum Conducted Output Power	For 2.4GHz Band: For Non-Beamforming Mode: MCS0 (HT20): 22.75 dBm ; MCS0 (HT40): 16.52 dBm For 5GHz Band: For Beamforming Mode: 802.11ac MCS0/Nss1 (VHT20): 27.10 dBm ; 802.11ac MCS0/Nss1 (VHT40): 26.77 dBm ; 802.11ac MCS0/Nss1 (VHT80): 22.80 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11a/b/g

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	For Non-Beamforming Mode: 11b: 17.76 MHz ; 11g: 17.76 MHz ; 11a: 29.64 MHz
Maximum Conducted Output Power	For Non-Beamforming Mode: 11b: 24.50 dBm ; 11g: 21.38 dBm ; 11a: 23.02 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description
Beamforming Function	☒ With beamforming for 802.11n/ac in 5GHz. ☐ Without beamforming

Antenna and Band width

Antenna	Single (TX)			Two (TX)			Three (TX)		
Band width Mode	20 MHz	40 MHz	80 MHz	20 MHz	40 MHz	80 MHz	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X	X	X	X	X	X	X
IEEE 802.11b	V	X	X	X	X	X	X	X	X
IEEE 802.11g	V	X	X	X	X	X	X	X	X
IEEE 802.11n (2.4GHz)	X	X	X	V	V	X	X	X	X
IEEE 802.11n (5GHz)	X	X	X	X	X	X	V	V	X
IEEE 802.11ac	X	X	X	X	X	X	V	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20) (2.4GHz)	2	MCS0-15
802.11n (HT40) (2.4GHz)	2	MCS0-15
802.11n (HT20) (5GHz)	3	MCS0-23
802.11n (HT40) (5GHz)	3	MCS0-23
802.11ac (VHT20)	3	MCS 0-9/Nss1-3
802.11ac (VHT40)	3	MCS 0-9/Nss1-3
802.11ac (VHT80)	3	MCS 0-9/Nss1-3

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).
Then EUT support HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:
HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	MOSO	MSP-C1000IC12.0-12B-US	INPUT: 100-240V~50/60Hz, 0.5A max. OUTPUT: 12.0V, 1A
Adapter 2	MOSO	MSP-C1500IC12.0-18W-US	INPUT: 100-240V~50/60Hz, 0.7A max. OUTPUT: 12.0V, 1.5A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
					2.4GHz	5GHz
1	-	-	PCB Antenna	NA	2.5	-
2	Airgain	N2420S-T-G50U	PIFA Antenna	I-PEX	2.5	-
3	-	-	PCB Antenna	NA	-	0
4	-	-	PCB Antenna	NA	-	0
5	-	-	PCB Antenna	NA	-	0

Note: The EUT has five antennas. There are two antennas for 2.4GHz and three antennas for 5GHz.

<For 2.4GHz band>

For 802.11b/g mode:

Only Ant. 1 can be used as transmitting/receiving antenna.

For 802.11n mode:

Both Ant. 1 and Ant. 2 support transmit and receive functions.

Ant. 1 and Ant. 2 can transmit and receive signal simultaneously.

<For 5GHz band>


For 802.11a mode:

Only Ant. 3 can be used as transmitting/receiving antenna.

For 802.11n/ac mode:

Ant. 3, Ant. 4 and Ant. 5 support transmit and receive functions.

Ant. 3, Ant. 4 and Ant. 5 can transmit and receive signal simultaneously.



3.4. Table for Carrier Frequencies

For 2.4GHz Band:

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

For 5GHz Band:

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

For 80MHz bandwidth systems, use Channel 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For 2.4GHz Band:

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11n HT20	MCS0	1/6/11	1+2
	11n HT40	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Power Spectral Density	11n HT20	MCS0	1/6/11	1+2
	11n HT40	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
6dB Spectrum Bandwidth	11n HT20	MCS0	1/6/11	1+2
	11n HT40	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11n HT20	MCS0	1/6/11	1+2
	11n HT40	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	11n HT20	MCS0	1/6/11	1+2
	11n HT40	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1

For 5GHz Band:

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11ac VHT20	MCS0/Nss1	149/157/165	3+4+5
	11ac VHT40	MCS0/Nss1	151/159	3+4+5
	11ac VHT80	MCS0/Nss1	155	3+4+5
	11a/BPSK	6 Mbps	149/157/165	3
Power Spectral Density	11ac VHT20	MCS0/Nss1	149/157/165	3+4+5
	11ac VHT40	MCS0/Nss1	151/159	3+4+5
	11ac VHT80	MCS0/Nss1	155	3+4+5
	11a/BPSK	6 Mbps	149/157/165	3
6dB Spectrum Bandwidth	11ac VHT20	MCS0/Nss1	149/157/165	3+4+5
	11ac VHT40	MCS0/Nss1	151/159	3+4+5
	11ac VHT80	MCS0/Nss1	155	3+4+5
	11a/BPSK	6 Mbps	149/157/165	3
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11ac VHT20	MCS0/Nss1	149/157/165	3+4+5
	11ac VHT40	MCS0/Nss1	151/159	3+4+5
	11ac VHT80	MCS0/Nss1	155	3+4+5
	11a/BPSK	6 Mbps	149/157/165	3
Band Edge Emissions	11ac VHT20	MCS0/Nss1	149/157/165	3+4+5
	11ac VHT40	MCS0/Nss1	151/159	3+4+5
	11ac VHT80	MCS0/Nss1	155	3+4+5
	11a/BPSK	6 Mbps	149/157/165	3

Note 1: VHT20/VHT40 covers HT20/HT40, due to same modulation.

Note 2: There are two modes of EUT, one is beamforming mode, and the other is non-beamforming mode for 802.11n/ac in 5GHz, after evaluating, beamforming mode has been evaluated to be the worst case, so it was selected to test and record in this test report.

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. Normal Link with Adapter 1

Mode 2. Normal Link with Adapter 2

Mode 1 is the worst case, so it was selected to record in this test report.

For Radiated Emission test:

<Below 1G>

Mode 1. Normal Link with Adapter 1

Mode 2. Normal Link with Adapter 2

Mode 2 is the worst case, so it was selected to record in this test report.

<Above 1G>

Mode 1. CTX

For Co-location MPE and Radiated Emission Co-location Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to Appendix B) and Radiated Emission Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: 03CH01-CB (Below 1G)

Support Unit	Brand	Model	FCC ID
NB	DELL	M1340	E2K4965AGNM
NB	DELL	E6430	QDS-BRCM1049LE
NB	DELL	D420	E2KWM3945ABG
Flash Disk3.0	TDK	TF30	DoC

For Test Site No: 03CH01-CB (Above 1G)

For Non-Beamforming Mode:

Support Unit	Brand	Model	FCC ID
NB	DELL	M1340	E2K4965AGNM

For Beamforming Mode:

Support Unit	Brand	Model	FCC ID
NB	DELL	M1340	E2K4965AGNM
NB	DELL	E6430	QDS-BRCM1049LE
WLAN ac Dongle	Netgear	A6200	PY31220200

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
NB*3	DELL	E6430	DoC
Flash Disk3.0	TDK	TF30	DoC

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For 2.4GHz Band

For Non-Beamforming Mode:

Power Parameters of IEEE 802.11n MCS0 HT20

Test Software Version	Mtool 2.0.0.7		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 HT20	49	76	49

Power Parameters of IEEE 802.11n MCS0 HT40

Test Software Version	Mtool 2.0.0.7		
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 HT40	39	58	43

Power Parameters of IEEE 802.11b/g

Test Software Version	Mtool 2.0.0.7		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	72	100	76
IEEE 802.11g	60	83	65

For 5GHz Band

For Beamforming Mode:

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT20

Test Software Version	Mtool 2.0.0.7		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0/Nss1 VHT20	76	88	88

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT40

Test Software Version	Mtool 2.0.0.7	
Frequency	5755 MHz	5795 MHz
MCS0/Nss1 VHT40	67	88

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT80

Test Software Version	Mtool 2.0.0.7
Frequency	5775 MHz
MCS0/Nss1 VHT80	68

For Non-Beamforming Mode:

Power Parameters of IEEE 802.11a

Test Software Version	ART		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	86	88	88

3.9. EUT Operation during Test

For Non-Beamforming Mode:

The EUT was programmed to be in continuously transmitting mode.

For Beamforming Mode:

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:

During the test, the following programs under WIN XP were executed.

The program was executed as follows:

1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS.
3. Executed "Lantest.exe " to link with the remote workstation to receive and transmit packet by WLAN ac Dongle and transmit duty cycle no less 98%

3.10. Duty Cycle

For Non-Beamforming Mode:


Band	Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
2.4G	802.11n MCS0 HT20	1.908	1.944	98.15%	0.08	0.01
	802.11n MCS0 HT40	0.912	0.964	94.63%	0.24	1.10
	802.11b	1.000	1.000	100.00%	0.00	0.01
	802.11g	2.070	2.100	98.57%	0.06	0.01
5G	802.11a	2.050	2.090	98.09%	0.08	0.01

For Beamforming Mode:

Band	Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
5G	802.11ac MCS0/Nss1 VHT20	3.745	3.844	97.44%	0.11	0.27
	802.11ac MCS0/Nss1 VHT40	4.583	4.647	98.62%	0.06	0.01
	802.11ac MCS0/Nss1 VHT80	5.051	5.229	96.59%	0.15	0.20

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test and Radiation Emissions Test (Below1G) Configuration



Item	Connection	Shielded	Length	Remark
1	Power cable	No	1.5m	-
2	RJ-45 cable	No	1.5m	Load
3	RJ-45 cable	No	10m	-
4	Audio cable	No	1.6m	Load


3.11.2. Radiation Emissions (Above 1G) Test Configuration

For Non-Beamforming Mode



Item	Connection	Shielded	Length(m)
1	Power Cable	No	2m
2	RJ-45 Cable	No	10m

For Beamforming Mode



Item	Connection	Shielded	Length(m)
1	Power Cable	No	2m
2	RJ-45 Cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	22°C	Humidity	63%
Test Engineer	Edison Lin	Phase	Line
Configuration	Normal Link / Mode 1		



	Freq	Level	Over	Limit	Read	LISN	Cable		
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark	Pol/Phase
			dB	dBuV	dBuV	dB	dB		
1	0.15733	49.36	-16.24	65.60	39.24	9.96	0.16	QP	LINE
2	0.15733	31.65	-23.95	55.60	21.53	9.96	0.16	AVERAGE	LINE
3	0.16327	49.47	-15.83	65.30	39.35	9.96	0.16	QP	LINE
4	0.16327	33.51	-21.79	55.30	23.39	9.96	0.16	AVERAGE	LINE
5	0.17215	47.79	-17.06	64.86	37.67	9.96	0.16	QP	LINE
6	0.17215	29.62	-25.23	54.86	19.50	9.96	0.16	AVERAGE	LINE
7	0.17961	18.14	-36.36	54.50	8.02	9.96	0.16	AVERAGE	LINE
8	0.17961	42.29	-22.21	64.50	32.17	9.96	0.16	QP	LINE
9	0.18443	28.51	-25.77	54.28	18.39	9.96	0.16	AVERAGE	LINE
10	0.18443	42.79	-21.49	64.28	32.67	9.96	0.16	QP	LINE
11	0.19447	43.98	-19.86	63.84	33.86	9.96	0.16	QP	LINE
12	0.19447	29.27	-24.57	53.84	19.15	9.96	0.16	AVERAGE	LINE
13	0.61075	41.97	-14.03	56.00	31.81	9.97	0.19	QP	LINE
14	0.61075	35.32	-10.68	46.00	25.16	9.97	0.19	AVERAGE	LINE

Temperature	22°C	Humidity	63%
Test Engineer	Edison Lin	Phase	Neutral
Configuration	Normal Link / Mode 1		



	Freq	Level	Over	Limit	Read	LISN	Cable		
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark	Pol/Phase
			dB	dBuV	dBuV	dB	dB		
1	0.15321	50.99	-14.83	65.82	40.88	9.95	0.16	QP	NEUTRAL
2	0.15321	28.39	-27.43	55.82	18.28	9.95	0.16	AVERAGE	NEUTRAL
3	0.16327	51.62	-13.68	65.30	41.51	9.95	0.16	QP	NEUTRAL
4	0.16327	36.63	-18.67	55.30	26.52	9.95	0.16	AVERAGE	NEUTRAL
5	0.17215	48.96	-15.89	64.86	38.85	9.95	0.16	QP	NEUTRAL
6	0.17215	29.79	-25.06	54.86	19.68	9.95	0.16	AVERAGE	NEUTRAL
7	0.18152	41.45	-22.96	64.42	31.34	9.95	0.16	QP	NEUTRAL
8	0.18152	20.62	-33.79	54.42	10.51	9.95	0.16	AVERAGE	NEUTRAL
9	0.18541	45.21	-19.03	64.24	35.10	9.95	0.16	QP	NEUTRAL
10	0.18541	26.44	-27.80	54.24	16.33	9.95	0.16	AVERAGE	NEUTRAL
11	0.19447	46.18	-17.66	63.84	36.07	9.95	0.16	QP	NEUTRAL
12	0.19447	30.88	-22.96	53.84	20.77	9.95	0.16	AVERAGE	NEUTRAL
13	0.20614	42.97	-20.39	63.36	32.85	9.95	0.17	QP	NEUTRAL
14	0.20614	27.47	-25.89	53.36	17.35	9.95	0.17	AVERAGE	NEUTRAL
15	0.60112	41.04	-14.96	56.00	30.89	9.96	0.19	QP	NEUTRAL
16	0.60112	33.49	-12.51	46.00	23.34	9.96	0.19	AVERAGE	NEUTRAL

Note:

Level = Read Level + LISN Factor + Cable Loss

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r02 section 9.2.3.2 Measurement using a power meter (PM).
2. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

For Non-Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11n
Test Date	Nov. 28, 2014		

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 HT20

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Antenna 1	Antenna 2	Total		
1	2412 MHz	11.20	12.34	14.82	30.00	Complies
6	2437 MHz	18.95	20.41	22.75	30.00	Complies
11	2462 MHz	11.26	11.20	14.24	30.00	Complies

Configuration IEEE 802.11n MCS0 HT40

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Antenna 1	Antenna 2	Total		
3	2422 MHz	8.86	9.23	12.06	30.00	Complies
6	2437 MHz	13.86	13.12	16.52	30.00	Complies
9	2452 MHz	10.25	9.86	13.07	30.00	Complies

For Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11 ac
Test Date	Nov. 28, 2014		

For 5GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 VHT20

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Antenna 3	Antenna 4	Antenna 5	Total		
149	5745 MHz	19.62	20.32	20.01	24.76	30.00	Complies
157	5785 MHz	22.73	22.26	21.96	27.10	30.00	Complies
165	5825 MHz	22.09	22.32	21.70	26.82	30.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 4.77 \text{ dBi} < 6 \text{ dBi}, \text{ So Power Limit} = 30 \text{ dBm}$

Configuration IEEE 802.11ac MCS0/Nss1 VHT40

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Antenna 3	Antenna 4	Antenna 5	Total		
151	5755 MHz	17.35	18.16	17.66	22.51	30.00	Complies
159	5795 MHz	22.27	22.04	21.68	26.77	30.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 4.77 \text{ dBi} < 6 \text{ dBi}, \text{ So Power Limit} = 30 \text{ dBm}$

Configuration IEEE 802.11ac MCS0/Nss1 VHT80

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Antenna 3	Antenna 4	Antenna 5	Total		
155	5775 MHz	17.46	18.31	18.26	22.80	30.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 4.77 \text{ dBi} < 6 \text{ dBi}, \text{ So Power Limit} = 30 \text{ dBm}$

For Non-Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11a/b/g
Test Date	Nov. 28, 2014		

Configuration IEEE 802.11b / Antenna 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.66	30.00	Complies
6	2437 MHz	24.50	30.00	Complies
11	2462 MHz	18.13	30.00	Complies

Configuration IEEE 802.11g / Antenna 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	13.24	30.00	Complies
6	2437 MHz	21.38	30.00	Complies
11	2462 MHz	14.62	30.00	Complies

Configuration IEEE 802.11a / Antenna 3

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	22.73	30.00	Complies
157	5785 MHz	23.02	30.00	Complies
165	5825 MHz	22.86	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

For Non-Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11 n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 HT20

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Antenna 1	Antenna 2	Total		
1	2412 MHz	-13.86	-13.58	-10.71	8.00	Complies
6	2437 MHz	-6.03	-4.3	-2.07	8.00	Complies
11	2462 MHz	-13.81	-12.19	-9.91	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.51 \text{ dBi} < 6 \text{ dBi}$, So Power Density Limit = 8dBm/3kHz

Configuration IEEE 802.11n MCS0 HT40

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Antenna 1	Antenna 2	Total		
3	2422 MHz	-18.63	-18.49	-15.55	8.00	Complies
6	2437 MHz	-14.11	-13.53	-10.80	8.00	Complies
9	2452 MHz	-18.25	-17.88	-15.05	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.51 \text{ dBi} < 6 \text{ dBi}$, So Power Density Limit = 8dBm/3kHz

For Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11 ac

For 5GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 VHT20

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Antenna 3	Antenna 4	Antenna 5	Total		
149	5745 MHz	-6.32	-5.19	-5.72	-0.95	8.00	Complies
157	5785 MHz	-2.59	-2.75	-2.92	2.02	8.00	Complies
165	5825 MHz	-2.67	-2.6	-2.99	2.02	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 4.77\text{dBi} < 6\text{dBi}$, So Power Density Limit = 8dBm/3kHz

Configuration IEEE 802.11ac MCS0/Nss1 VHT40

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Antenna 3	Antenna 4	Antenna 5	Total		
151	5755 MHz	-9.63	-8.64	-9.15	-4.35	8.00	Complies
159	5795 MHz	-6.06	-6.44	-6.54	-1.57	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 4.77\text{dBi} < 6\text{dBi}$, So Power Density Limit = 8dBm/3kHz

Configuration IEEE 802.11ac MCS0/Nss1 VHT80

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Antenna 3	Antenna 4	Antenna 5	Total		
155	5775 MHz	-13.39	-12.64	-13.02	-8.23	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 4.77\text{dBi} < 6\text{dBi}$, So Power Density Limit = 8dBm/3kHz

For Non-Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b / Antenna 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
1	2412 MHz	-4.94	8.00	Complies
6	2437 MHz	1.07	8.00	Complies
11	2462 MHz	-4.11	8.00	Complies

Configuration IEEE 802.11g / Antenna 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
1	2412 MHz	-10.05	8.00	Complies
6	2437 MHz	-2.75	8.00	Complies
11	2462 MHz	-8.91	8.00	Complies

Configuration IEEE 802.11a / Antenna 3


Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
149	5745 MHz	-1.73	8.00	Complies
157	5785 MHz	-1.31	8.00	Complies
165	5825 MHz	-1.78	8.00	Complies

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


For Non-Beamforming Mode:

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Antenna 1




Date: 22.DEC.2014 17:47:31

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Antenna 2




Date: 22.DEC.2014 17:46:56

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Antenna 1



Date: 22.DEC.2014 17:52:19


Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Antenna 2



Date: 22.DEC.2014 17:52:55


For Beamforming Mode:

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 5785 MHz / Antenna 3




Date: 1.DEC.2014 22:50:32

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 5785 MHz / Antenna 4




Date: 1.DEC.2014 22:52:39

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 5785 MHz / Antenna 5




Date: 1.DEC.2014 22:48:28

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 5795 MHz / Antenna 3




Date: 1.DEC.2014 23:13:27

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 5795 MHz / Antenna 4




Date: 1.DEC.2014 23:16:33

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 5795 MHz / Antenna 5




Date: 1.DEC.2014 23:14:46

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / 5775 MHz / Antenna 3




Date: 1.DEC.2014 23:22:58

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / 5775 MHz / Antenna 4



Date: 1.DEC.2014 23:20:32


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / 5775 MHz / Antenna 5



Date: 1.DEC.2014 23:19:08


For Non-Beamforming Mode:

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Antenna 1




Date: 22.DEC.2014 17:36:26

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Antenna 1



Date: 22.DEC.2014 17:38:47

Power Density Plot on Configuration IEEE 802.11a / 5785 MHz / Antenna 3



Date: 1.DEC.2014 22:37:20

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth => 8.1 Option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

For Non-Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 HT20 / Antenna 1 + Antenna 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.68	17.76	500	Complies
6	2437 MHz	14.16	17.76	500	Complies
11	2462 MHz	12.80	17.76	500	Complies

Configuration IEEE 802.11n MCS0 HT40 / Antenna 1 + Antenna 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	32.96	36.20	500	Complies
6	2437 MHz	35.20	36.80	500	Complies
9	2452 MHz	30.08	36.40	500	Complies

For Beamforming Mode

Temperature	26°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac

For 5GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Antenna 3 + Antenna 4 + Antenna 5

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.32	19.32	500	Complies
157	5785 MHz	16.32	29.88	500	Complies
165	5825 MHz	16.32	33.86	500	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Antenna 3 + Antenna 4 + Antenna 5

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	34.40	37.40	500	Complies
159	5795 MHz	35.84	64.40	500	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Antenna 3 + Antenna 4 + Antenna 5

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
155	5775 MHz	73.92	76.20	500	Complies

For Non-Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b / Antenna 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	8.00	10.32	500	Complies
6	2437 MHz	9.60	17.76	500	Complies
11	2462 MHz	8.00	10.32	500	Complies

Configuration IEEE 802.11g / Antenna 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	14.00	16.56	500	Complies
6	2437 MHz	15.04	17.76	500	Complies
11	2462 MHz	13.76	16.65	500	Complies

Configuration IEEE 802.11a / Antenna 3


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	14.96	28.92	500	Complies
157	5785 MHz	15.68	28.92	500	Complies
165	5825 MHz	15.76	29.64	500	Complies

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


For Non-Beamforming Mode:

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2462 MHz / Antenna 1 + Antenna 2




Date: 22.DEC.2014 20:47:09

99% Occupied Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Antenna 1 + Antenna 2




Date: 22.DEC.2014 20:32:52

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40 / 2452 MHz / Antenna 1 + Antenna 2



Date: 22.DEC.2014 20:50:07

99% Occupied Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Antenna 1 + Antenna 2




Date: 22.DEC.2014 20:34:42

For Beamforming Mode:

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 5785 MHz /


Antenna 3 + Antenna 4 + Antenna 5



Date: 22.DEC.2014 21:43:19


99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 5825 MHz /

Antenna 3 + Antenna 4 + Antenna 5




Date: 22.DEC.2014 21:55:56

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 5755MHz / Antenna 3 + Antenna 4 + Antenna 5




Date: 22.DEC.2014 21:44:44

99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 5795MHz / Antenna 3 + Antenna 4 + Antenna 5




Date: 22.DEC.2014 21:58:50

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / 5775 MHz / Antenna 3 + Antenna 4 + Antenna 5



Date: 22.DEC.2014 21:46:35


99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / 5775 MHz / Antenna 3 + Antenna 4 + Antenna 5



Date: 22.DEC.2014 22:00:13


For Non-Beamforming Mode:

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz / Antenna 1




Date: 22.DEC.2014 20:41:10

99% Occupied Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz / Antenna 1




Date: 22.DEC.2014 20:28:51

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz / Antenna 1




Date: 22.DEC.2014 20:43:33

99% Occupied Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Antenna 1




Date: 22.DEC.2014 20:30:12

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5745 MHz / Antenna 3



Date: 22.DEC.2014 21:38:20

99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / 5825 MHz / Antenna 3



Date: 22.DEC.2014 21:54:21

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1GHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	Normal Link / Mode 2
Test Date	Dec. 27, 2014		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	Normal Link / Mode 2

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	Pol/Phase	deg	cm	
1	77.53	33.61	40.00	-6.39	57.92	0.64	32.36	7.41	HORIZONTAL	238	200	Peak
2	891.36	41.26	46.00	-4.74	49.49	2.15	31.90	21.52	HORIZONTAL	299	125	Peak
3	896.21	39.41	46.00	-6.59	47.53	2.16	31.84	21.56	HORIZONTAL	126	100	QP
4	899.12	37.64	46.00	-8.36	45.68	2.17	31.80	21.59	HORIZONTAL	121	100	QP
5	903.97	38.13	46.00	-7.87	46.05	2.17	31.71	21.62	HORIZONTAL	121	100	QP
6	910.76	41.32	46.00	-4.68	49.02	2.21	31.58	21.67	HORIZONTAL	271	125	QP
7	914.64	37.86	46.00	-8.14	45.47	2.21	31.51	21.69	HORIZONTAL	277	125	QP
8	928.22	41.62	46.00	-4.38	48.98	2.28	31.41	21.77	HORIZONTAL	282	125	QP
9	932.10	40.39	46.00	-5.61	47.74	2.28	31.42	21.79	HORIZONTAL	277	125	QP
10	935.98	41.70	46.00	-4.30	48.99	2.31	31.42	21.82	HORIZONTAL	282	125	QP
11	939.86	41.31	46.00	-4.69	48.58	2.31	31.42	21.84	HORIZONTAL	282	125	QP
12	946.65	40.19	46.00	-5.81	47.32	2.35	31.36	21.88	HORIZONTAL	279	100	QP
13	954.41	40.93	46.00	-5.07	47.91	2.38	31.29	21.93	HORIZONTAL	282	125	QP
14	960.23	42.57	54.00	-11.43	49.45	2.40	31.24	21.96	HORIZONTAL	104	100	QP

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna		T/Pos	A/Pos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	Pol/Phase	deg	cm	
1	44.55	38.77	40.00	-1.23	59.52	0.48	32.43	11.20	VERTICAL	264	100	QP
2	49.40	39.24	40.00	-0.76	61.89	0.50	32.52	9.37	VERTICAL	191	100	QP
3	53.28	39.59	40.00	-0.41	63.24	0.52	32.51	8.34	VERTICAL	360	100	QP
4	58.13	37.14	40.00	-2.86	61.85	0.55	32.50	7.24	VERTICAL	1	150	QP
5	62.98	39.19	40.00	-0.81	64.33	0.57	32.51	6.80	VERTICAL	37	100	QP
6	67.83	37.21	40.00	-2.79	62.33	0.60	32.52	6.80	VERTICAL	360	200	QP
7	72.68	37.89	40.00	-2.11	62.69	0.62	32.44	7.02	VERTICAL	280	100	QP
8	77.53	36.08	40.00	-3.92	60.42	0.64	32.36	7.38	VERTICAL	26	100	QP
9	813.76	42.98	46.00	-3.02	52.45	2.05	32.26	20.74	VERTICAL	198	150	Peak
10	892.33	41.60	46.00	-4.40	49.82	2.15	31.89	21.52	VERTICAL	76	150	QP
11	903.00	42.23	46.00	-3.77	50.17	2.17	31.73	21.62	VERTICAL	356	150	QP
12	913.67	42.36	46.00	-3.64	50.00	2.21	31.53	21.68	VERTICAL	76	150	QP
13	922.40	43.16	46.00	-2.84	50.57	2.26	31.41	21.74	VERTICAL	37	150	QP
14	930.16	41.21	46.00	-4.79	48.57	2.28	31.42	21.78	VERTICAL	87	150	QP
15	935.01	43.37	46.00	-2.63	50.67	2.31	31.42	21.81	VERTICAL	82	150	QP
16	942.77	43.46	46.00	-2.54	50.66	2.33	31.39	21.86	VERTICAL	222	125	QP
17	947.62	42.77	46.00	-3.23	49.88	2.35	31.35	21.89	VERTICAL	71	125	QP
18	953.44	43.45	46.00	-2.55	50.45	2.38	31.30	21.92	VERTICAL	171	125	QP
19	958.29	43.25	46.00	-2.75	50.16	2.40	31.26	21.95	VERTICAL	76	125	QP

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

For Non-Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11n MCS0 HT20 CH 1 / Antenna 1 + Antenna 2
Test Date	Dec. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	
1	4814.60	33.09	54.00	-20.91	29.08	5.85	33.36	35.20	Average	100	147	HORIZONTAL
2	4827.28	45.43	74.00	-28.57	41.37	5.87	33.39	35.20	Peak	100	147	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	
1	4814.64	33.15	54.00	-20.85	29.14	5.85	33.36	35.20	Average	100	360	VERTICAL
2	4814.64	46.09	74.00	-27.91	42.08	5.85	33.36	35.20	Peak	100	360	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11n MCS0 HT20 CH 6 / Antenna 1 + Antenna 2
Test Date	Dec. 20, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4872.70	37.04	54.00	-16.96	32.84	5.92	33.48	35.20	Average	148	258 HORIZONTAL
2	4878.10	48.95	74.00	-25.05	44.75	5.92	33.48	35.20	Peak	148	258 HORIZONTAL
3	7311.00	55.54	74.00	-18.46	47.33	7.13	36.51	35.43	Peak	112	221 HORIZONTAL
4	7312.50	41.40	54.00	-12.60	33.19	7.13	36.51	35.43	Average	112	221 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4872.88	51.55	74.00	-22.45	47.35	5.92	33.48	35.20	Peak	206	36 VERTICAL
2	4875.68	39.10	54.00	-14.90	34.90	5.92	33.48	35.20	Average	206	36 VERTICAL
3	7312.88	42.36	54.00	-11.64	34.15	7.13	36.51	35.43	Average	112	231 VERTICAL
4	7314.68	56.09	74.00	-17.91	47.88	7.13	36.51	35.43	Peak	112	231 VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11n MCS0 HT20 CH 11 / Antenna 1 + Antenna 2
Test Date	Dec. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4913.92	45.30	74.00	-28.70	41.01	5.95	33.54	35.20	Peak	100	117	HORIZONTAL
2	4942.56	33.25	54.00	-20.75	28.86	5.98	33.61	35.20	Average	45	117	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4910.24	45.75	74.00	-28.25	41.46	5.95	33.54	35.20	Peak	100	348	VERTICAL
2	4943.68	33.28	54.00	-20.72	28.89	5.98	33.61	35.20	Average	100	348	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11n MCS0 HT40 CH 3 / Antenna 1 + Antenna 2
Test Date	Dec. 20, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4826.96	45.89	74.00	-28.11	41.83	5.87	33.39	35.20	100	22	HORIZONTAL
2	4846.00	33.20	54.00	-20.80	29.10	5.88	33.42	35.20	100	22	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4844.32	33.09	54.00	-20.91	28.99	5.88	33.42	35.20	100	357	VERTICAL
2	4852.32	45.73	74.00	-28.27	41.61	5.90	33.42	35.20	100	357	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11n MCS0 HT40 CH 6 / Antenna 1 + Antenna 2
Test Date	Dec. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	4865.04	46.04	74.00	-27.96	41.89	5.90	33.45	35.20	Peak	100	343 HORIZONTAL
2	4893.52	33.40	54.00	-20.60	29.16	5.93	33.51	35.20	Average	100	343 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	4862.40	33.50	54.00	-20.50	29.35	5.90	33.45	35.20	Average	100	168 VERTICAL
2	4881.36	46.70	74.00	-27.30	42.50	5.92	33.48	35.20	Peak	100	168 VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11n MCS0 HT40 CH 9 / Antenna 1 + Antenna 2
Test Date	Dec. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4892.16	45.76	74.00	-28.24	41.52	5.93	33.51	35.20	Peak	100	115	HORIZONTAL
2	4894.88	33.34	54.00	-20.66	29.10	5.93	33.51	35.20	Average	45	115	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4892.00	33.39	54.00	-20.61	29.15	5.93	33.51	35.20	Average	100	184	VERTICAL
2	4895.20	45.83	74.00	-28.17	41.59	5.93	33.51	35.20	Peak	100	184	VERTICAL

For Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 149 / Antenna 3 + Antenna 4 + Antenna 5
Test Date	Nov. 13, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	11504.56	66.42	74.00	-7.58	51.33	10.72	39.40	308	232	Peak	HORIZONTAL
2	11505.60	53.84	54.00	-0.16	38.75	10.72	39.40	308	232	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	11492.40	65.05	74.00	-8.95	49.98	10.71	39.39	246	229	Peak	VERTICAL
2	11493.76	51.76	54.00	-2.24	36.68	10.72	39.39	246	229	Average	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 157 / Antenna 3 + Antenna 4 + Antenna 5
Test Date	Oct. 22, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11576.73	63.16	74.00	-10.84	48.02	10.76	39.44	35.06	215	228	Peak	HORIZONTAL
2	11578.39	50.30	54.00	-3.70	35.16	10.76	39.44	35.06	215	228	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11573.26	47.27	54.00	-6.73	32.13	10.76	39.44	35.06	225	219	Average	VERTICAL
2	11575.57	59.37	74.00	-14.63	44.23	10.76	39.44	35.06	225	219	Peak	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 165 / Antenna 3 + Antenna 4 + Antenna 5
Test Date	Nov. 13, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm		
1	11648.56	64.78	74.00	-9.22	49.53	10.81	39.48	35.04	221	227	Peak	HORIZONTAL
2	11649.36	51.59	54.00	-2.41	36.34	10.81	39.48	35.04	221	227	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm		
1	11648.56	48.63	54.00	-5.37	33.38	10.81	39.48	35.04	235	175	Average	VERTICAL
2	11656.56	60.82	74.00	-13.18	45.56	10.81	39.49	35.04	235	175	Peak	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 151 / Antenna 3 + Antenna 4 + Antenna 5
Test Date	Oct. 22, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm		
1	11485.40	45.85	54.00	-8.15	30.80	10.71	39.39	35.05	254	152	Average	HORIZONTAL
2	11492.92	58.88	74.00	-15.12	43.83	10.71	39.39	35.05	254	152	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	deg	cm		
1	11509.78	58.36	74.00	-15.64	43.29	10.72	39.40	35.05	242	157	Peak	VERTICAL
2	11510.07	42.99	54.00	-11.01	27.92	10.72	39.40	35.05	242	157	Average	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 159 / Antenna 3 + Antenna 4 + Antenna 5
Test Date	Nov. 13, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11599.76	66.85	74.00	-7.15	51.64	10.78	39.46	35.03	307	224	Peak	HORIZONTAL
2	11601.04	52.48	54.00	-1.52	37.27	10.78	39.46	35.03	307	224	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11573.60	46.70	54.00	-7.30	31.53	10.76	39.44	35.03	305	224	Average	VERTICAL
2	11605.52	58.71	74.00	-15.29	43.50	10.78	39.46	35.03	305	224	Peak	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 155 / Antenna 3 + Antenna 4 + Antenna 5
Test Date	Oct. 22, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11538.64	56.85	74.00	-17.15	41.75	10.73	39.42	35.05	241	164	Peak	HORIZONTAL
2	11543.34	44.93	54.00	-9.07	29.83	10.73	39.42	35.05	241	164	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11540.30	42.46	54.00	-11.54	27.36	10.73	39.42	35.05	53	132	Average	VERTICAL
2	11568.02	54.28	74.00	-19.72	39.15	10.75	39.44	35.06	53	132	Peak	VERTICAL

For Non-Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11b CH 1 / Antenna 1
Test Date	Dec. 19, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.87	48.59	74.00	-25.41	44.53	5.87	33.39	35.20	Peak	153	186	HORIZONTAL
2	4823.97	40.13	54.00	-13.87	36.07	5.87	33.39	35.20	Average	153	186	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.95	41.47	54.00	-12.53	37.41	5.87	33.39	35.20	Average	101	278	VERTICAL
2	4824.12	48.94	74.00	-25.06	44.88	5.87	33.39	35.20	Peak	101	278	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11b CH 6 / Antenna 1
Test Date	Dec. 19, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.96	49.53	54.00	-4.47	45.33	5.92	33.48	35.20	100	47	HORIZONTAL
2	4874.06	53.77	74.00	-20.23	49.57	5.92	33.48	35.20	100	47	HORIZONTAL
3	7311.04	50.04	74.00	-23.96	41.83	7.13	36.51	35.43	120	150	HORIZONTAL
4	7311.74	36.98	54.00	-17.02	28.77	7.13	36.51	35.43	120	150	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4873.97	53.97	54.00	-0.03	49.77	5.92	33.48	35.20	207	34	VERTICAL
2	4874.03	56.69	74.00	-17.31	52.49	5.92	33.48	35.20	207	34	VERTICAL
3	7311.68	37.89	54.00	-16.11	29.68	7.13	36.51	35.43	188	337	VERTICAL
4	7311.88	50.21	74.00	-23.79	42.00	7.13	36.51	35.43	188	337	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11b CH 11 / Antenna 1
Test Date	Dec. 19, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.95	48.81	74.00	-25.19	44.46	5.97	33.58	35.20	100	252	HORIZONTAL
2	4923.97	39.63	54.00	-14.37	35.28	5.97	33.58	35.20	100	252	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.94	39.59	54.00	-14.41	35.24	5.97	33.58	35.20	116	117	VERTICAL
2	4924.11	48.60	74.00	-25.40	44.25	5.97	33.58	35.20	116	117	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11g CH 1 / Antenna 1
Test Date	Dec. 20, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4824.13	46.54	74.00	-27.46	42.48	5.87	33.39	35.20	Peak	100	241	HORIZONTAL
2	4825.00	33.31	54.00	-20.69	29.25	5.87	33.39	35.20	Average	100	241	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.00	32.20	54.00	-21.80	28.14	5.87	33.39	35.20	Average	130	242	VERTICAL
2	4823.00	43.09	74.00	-30.91	39.03	5.87	33.39	35.20	Peak	130	242	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11g CH 6 / Antenna 1
Test Date	Dec. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4843.84	33.42	54.00	-20.58	29.32	5.88	33.42	35.20	Average	100	110	HORIZONTAL
2	4844.68	45.66	74.00	-28.34	41.56	5.88	33.42	35.20	Peak	100	110	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4840.08	46.58	74.00	-27.42	42.48	5.88	33.42	35.20	Peak	100	188	VERTICAL
2	4853.88	33.48	54.00	-20.52	29.33	5.90	33.45	35.20	Average	100	188	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11g CH 11 / Antenna 1
Test Date	Dec. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
			dBuV/m	dB	dBuV	dB	dB/m	dB				
1	4914.32	33.23	54.00	-20.77	28.94	5.95	33.54	35.20	Average	100	192	HORIZONTAL
2	4924.84	46.08	74.00	-27.92	41.73	5.97	33.58	35.20	Peak	100	192	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
			dBuV/m	dB	dBuV	dB	dB/m	dB				
1	4932.60	47.15	74.00	-26.85	42.80	5.97	33.58	35.20	Peak	100	328	VERTICAL
2	4934.00	33.10	54.00	-20.90	28.75	5.97	33.58	35.20	Average	100	328	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11a CH 149 / Antenna 3
Test Date	Nov. 11, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11489.64	60.15	74.00	-13.85	45.08	10.71	39.39	35.03	317	170	Peak	HORIZONTAL
2	11490.56	46.94	54.00	-7.06	31.87	10.71	39.39	35.03	317	170	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11486.48	45.75	54.00	-8.25	30.68	10.71	39.39	35.03	306	164	Average	VERTICAL
2	11488.72	59.88	74.00	-14.12	44.81	10.71	39.39	35.03	306	164	Peak	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11a CH 157 / Antenna 3
Test Date	Nov. 11, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	11569.00	57.74	74.00	-16.26	42.58	10.75	39.44	35.03	257	171	Peak
2	11571.44	44.99	54.00	-9.01	29.82	10.76	39.44	35.03	257	171	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11569.80	45.89	54.00	-8.11	30.72	10.76	39.44	35.03	319	246	Average	VERTICAL
2	11574.12	59.15	74.00	-14.85	43.98	10.76	39.44	35.03	319	246	Peak	VERTICAL

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11a CH 165 / Antenna 3
Test Date	Nov. 11, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11644.52	58.20	74.00	-15.80	42.97	10.79	39.48	35.04	246	220	Peak	HORIZONTAL
2	11648.40	45.37	54.00	-8.63	30.12	10.81	39.48	35.04	246	220	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11644.80	60.03	74.00	-13.97	44.80	10.79	39.48	35.04	306	197	Peak	VERTICAL
2	11648.52	45.50	54.00	-8.50	30.25	10.81	39.48	35.04	306	197	Average	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (30dBc in any 100 kHz bandwidth emission)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Radiated Out of Band Emission Measurement:

- Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

For Non-Beamforming Mode:

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11n MCS0 HT20 CH 1, 6, 11 / Antenna 1 + Antenna 2
Test date	Dec. 19, 2014		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor			cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			
1	2390.00	53.87	54.00	-0.13	21.73	4.09	28.05	0.00	Average	102	255 VERTICAL
2	2390.00	68.82	74.00	-5.18	36.68	4.09	28.05	0.00	Peak	102	255 VERTICAL
3	2410.80	97.73			65.53	4.11	28.09	0.00	Average	102	255 VERTICAL
4	2413.20	108.31			76.11	4.11	28.09	0.00	Peak	102	255 VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor			cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			
1	2388.60	71.11	74.00	-2.89	38.97	4.09	28.05	0.00	Peak	166	263 VERTICAL
2	2390.00	52.39	54.00	-1.61	20.25	4.09	28.05	0.00	Average	166	263 VERTICAL
3	2436.20	105.68			73.38	4.12	28.18	0.00	Average	166	263 VERTICAL
4	2436.20	116.79			84.49	4.12	28.18	0.00	Peak	166	263 VERTICAL
5	2483.50	53.25	54.00	-0.75	20.83	4.16	28.26	0.00	Average	166	263 VERTICAL
6	2483.80	69.95	74.00	-4.05	37.53	4.16	28.26	0.00	Peak	166	263 VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor			cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			
1	2461.20	96.43			64.07	4.14	28.22	0.00	Average	135	289 VERTICAL
2	2463.60	106.94			74.58	4.14	28.22	0.00	Peak	135	289 VERTICAL
3	2483.50	53.75	54.00	-0.25	21.33	4.16	28.26	0.00	Average	135	289 VERTICAL
4	2483.80	68.11	74.00	-5.89	35.69	4.16	28.26	0.00	Peak	135	289 VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11n MCS0 HT40 CH 3, 6, 9 / Antenna 1 + Antenna 2
Test date	Dec. 20, 2014		

Channel 3

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2386.00	53.96	54.00	-0.04	21.82	4.09	28.05	0.00	Average	100	272 VERTICAL
2	2388.80	68.69	74.00	-5.31	36.55	4.09	28.05	0.00	Peak	100	272 VERTICAL
3	2420.80	94.61			62.36	4.12	28.13	0.00	Average	100	272 VERTICAL
4	2423.20	103.92			71.67	4.12	28.13	0.00	Peak	100	272 VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2388.60	53.89	54.00	-0.11	21.75	4.09	28.05	0.00	Average	166	265 VERTICAL
2	2389.80	69.85	74.00	-4.15	37.71	4.09	28.05	0.00	Peak	166	265 VERTICAL
3	2435.80	97.98			65.68	4.12	28.18	0.00	Average	166	265 VERTICAL
4	2438.20	108.25			75.94	4.13	28.18	0.00	Peak	166	265 VERTICAL
5	2483.50	53.60	54.00	-0.40	21.18	4.16	28.26	0.00	Average	166	265 VERTICAL
6	2483.50	68.23	74.00	-5.77	35.81	4.16	28.26	0.00	Peak	166	265 VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 9

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2448.80	104.54			72.23	4.13	28.18	0.00	Peak	137	318 VERTICAL
2	2449.20	94.51			62.20	4.13	28.18	0.00	Average	137	318 VERTICAL
3	2484.00	53.73	54.00	-0.27	21.31	4.16	28.26	0.00	Average	137	318 VERTICAL
4	2488.80	66.84	74.00	-7.16	34.37	4.17	28.30	0.00	Peak	137	318 VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11b CH 1, 6, 11 / Antenna 1
Test Date	Dec. 19, 2014		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.60	60.85	74.00	-13.15	28.71	4.09	28.05	0.00	Peak	100	98	VERTICAL
2	2390.00	52.52	54.00	-1.48	20.38	4.09	28.05	0.00	Average	100	98	VERTICAL
3	2411.00	107.27			75.07	4.11	28.09	0.00	Peak	100	98	VERTICAL
4	2411.20	103.36			71.16	4.11	28.09	0.00	Average	100	98	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.00	51.38	54.00	-2.62	19.24	4.09	28.05	0.00	Average	101	70	VERTICAL
2	2390.00	60.99	74.00	-13.01	28.85	4.09	28.05	0.00	Peak	101	70	VERTICAL
3	2435.40	107.80			75.50	4.12	28.18	0.00	Average	101	70	VERTICAL
4	2436.20	112.03			79.73	4.12	28.18	0.00	Peak	101	70	VERTICAL
5	2483.50	52.53	54.00	-1.47	20.11	4.16	28.26	0.00	Average	101	70	VERTICAL
6	2483.50	62.16	74.00	-11.84	29.74	4.16	28.26	0.00	Peak	101	70	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2461.20	103.44			71.08	4.14	28.22	0.00	Average	100	111	VERTICAL
2	2463.00	107.42			75.06	4.14	28.22	0.00	Peak	100	111	VERTICAL
3	2483.50	53.18	54.00	-0.82	20.76	4.16	28.26	0.00	Average	100	111	VERTICAL
4	2483.50	61.28	74.00	-12.72	28.86	4.16	28.26	0.00	Peak	100	111	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	63%
Test Engineer	Lucas Huang / Andy Tsai	Configurations	IEEE 802.11g CH 1, 6, 11 / Antenna 1
Test Date	Dec. 19, 2014		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.40	67.66	74.00	-6.34	35.52	4.09	28.05	0.00	Peak	100	85	VERTICAL
2	2390.00	53.69	54.00	-0.31	21.55	4.09	28.05	0.00	Average	100	85	VERTICAL
3	2410.80	105.64			73.44	4.11	28.09	0.00	Peak	100	85	VERTICAL
4	2411.00	94.66			62.46	4.11	28.09	0.00	Average	100	85	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.40	70.47	74.00	-3.53	38.33	4.09	28.05	0.00	Peak	100	71	VERTICAL
2	2390.00	53.64	54.00	-0.36	21.50	4.09	28.05	0.00	Average	100	71	VERTICAL
3	2435.80	111.86			79.56	4.12	28.18	0.00	Peak	100	71	VERTICAL
4	2436.20	101.41			69.11	4.12	28.18	0.00	Average	100	71	VERTICAL
5	2483.50	53.54	54.00	-0.46	21.12	4.16	28.26	0.00	Average	100	71	VERTICAL
6	2490.60	68.83	74.00	-5.17	36.36	4.17	28.30	0.00	Peak	100	71	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2463.00	96.06			63.70	4.14	28.22	0.00	Average	100	108	VERTICAL
2	2463.00	106.11			73.75	4.14	28.22	0.00	Peak	100	108	VERTICAL
3	2483.80	53.70	54.00	-0.30	21.28	4.16	28.26	0.00	Average	100	108	VERTICAL
4	2485.00	66.64	74.00	-7.36	34.22	4.16	28.26	0.00	Peak	100	108	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


For Non-Beamforming Mode:

Plot on Configuration IEEE 802.11n MCS0 HT20 / Reference Level




Date: 20.DEC.2014 01:19:48

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2014 01:20:56

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2014 01:21:45

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2014 01:22:45

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2014 01:23:24

Plot on Configuration IEEE 802.11n MCS0 HT40 / Reference Level




Date: 20.DEC.2014 01:25:48

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2014 01:27:36

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2014 01:28:25

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 30MHz~2400MHz (down 30dBc)



Date: 20.DEC.2014 01:29:21


Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 2500MHz~26500MHz (down 30dBc)



Date: 20.DEC.2014 01:29:41


For Beamforming Mode:

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Reference Level




Date: 13.NOV.2014 01:20:09

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 13.NOV.2014 01:26:49

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 13.NOV.2014 01:28:15

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 165 / 30MHz~5725MHz (down 30dBc)




Date: 13.NOV.2014 01:30:37

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 165 / 5850MHz~40000MHz (down 30dBc)




Date: 13.NOV.2014 01:32:05

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Reference Level




Date: 13.NOV.2014 01:42:10

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 151 / 30MHz~5725MHz (down 30dBc)




Date: 13.NOV.2014 01:47:19

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 151 / 5850MHz~40000MHz (down 30dBc)




Date: 13.NOV.2014 01:48:12

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 159 / 30MHz~5725MHz (down 30dBc)




Date: 13.NOV.2014 01:44:28

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 159 / 5850MHz~40000MHz (down 30dBc)




Date: 13.NOV.2014 01:45:30

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Reference Level




Date: 13.NOV.2014 02:07:08

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / CH 155 / 30MHz~5725MHz (down 30dBc)



Date: 13.NOV.2014 02:07:55


Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / CH 155 / 5850MHz~40000MHz (down 30dBc)



Date: 13.NOV.2014 02:08:55


For Non-Beamforming Mode:

Plot on Configuration IEEE 802.11b / Reference Level




Date: 20.DEC.2014 01:03:20

Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2014 01:08:48

Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2014 01:07:54

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2014 01:09:11

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2014 01:10:01

Plot on Configuration IEEE 802.11g / Reference Level




Date: 20.DEC.2014 01:11:30

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2014 01:13:52

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2014 01:14:56

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 20.DEC.2014 01:15:39

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 20.DEC.2014 01:16:08

Plot on Configuration IEEE 802.11a / Reference Level




Date: 11.NOV.2014 20:05:09

Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 11.NOV.2014 20:18:57

Plot on Configuration IEEE 802.11a / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 11.NOV.2014 20:21:05

Plot on Configuration IEEE 802.11a / CH 165 / 30MHz~5725MHz (down 30dBc)



Date: 11.NOV.2014 20:23:07

Plot on Configuration IEEE 802.11a / CH 165 / 5850MHz~40000MHz (down 30dBc)



Date: 11.NOV.2014 20:23:44

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 23, 2014	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 23, 2013	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127650	9kHz ~ 30MHz	Nov. 17, 2014	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Nov. 23, 2013	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Nov. 17, 2014	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	Dec. 04, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	Dec. 04, 2014	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 26, 2014	Radiation (03CH01-CB)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jul. 28, 2014	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Oct. 28, 2014	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 22, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 15, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Dec. 16, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02009	1GHz ~ 26.5GHz	Dec. 17, 2014	Radiation (03CH01-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Apr. 22, 2014	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100080	9kHz ~ 40GHz	Dec. 30, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
MXE EMI Receiver	Agilent	N9038A	MY52260140	9kHz ~ 30MHz	Jan. 22, 2014	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO 2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec.12, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz - 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz - 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	1126203	300MHz~40GHz	Oct. 06, 2014	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1210004	300MHz~40GHz	Oct. 06, 2014	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

NCR means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%