

# Test Report

**Report No.:** MTi240612025-13E1

**Date of issue:** 2024-07-31

**Applicant:** ShangXing Technology (Shenzhen) Co., Ltd.

**Product name:** 3-in-1Foldable Magnetic Wireless Charger

**Model(s):** X40Q, X40, X40S, X40+, X40S+, X40SQ, X40Q+, X40SQ+, SQ312, X73, X74, X75

**FCC ID:** 2APDM-X40Q

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.cn>

The test report is only used for customer scientific research, teaching, internal quality control and other purposes, and is for internal reference only.



## Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

# Table of contents

<b>1</b>	<b>General Description .....</b>	<b>5</b>
1.1	Description of the EUT .....	5
1.2	Description of test modes .....	5
1.3	Environmental Conditions .....	7
1.4	Description of support units .....	7
1.5	Measurement uncertainty .....	7
<b>2</b>	<b>Summary of Test Result .....</b>	<b>8</b>
<b>3</b>	<b>Test Facilities and accreditations .....</b>	<b>9</b>
3.1	Test laboratory .....	9
<b>4</b>	<b>List of test equipment.....</b>	<b>10</b>
<b>5</b>	<b>Evaluation Results (Evaluation).....</b>	<b>11</b>
5.1	Antenna requirement .....	11
<b>6</b>	<b>Radio Spectrum Matter Test Results (RF) .....</b>	<b>12</b>
6.1	Conducted Emission at AC power line .....	12
6.2	20dB Occupied Bandwidth .....	15
6.3	Emissions in frequency bands (below 30MHz).....	22
6.4	Emissions in frequency bands (30MHz - 1GHz).....	27
	<b>Photographs of the test setup.....</b>	<b>30</b>
	<b>Photographs of the EUT.....</b>	<b>31</b>

<b>Test Result Certification</b>	
<b>Applicant:</b>	ShangXing Technology (Shenzhen) Co., Ltd.
Address:	Room 408, 4th Floor, Building 30. Wisdomland Business Park, Guankou 2nd road, Nantou, Nanshan, Shenzhen, China
<b>Manufacturer:</b>	ShangXing Technology (Shenzhen) Co., Ltd.
Address:	Room 408, 4th Floor, Building 30. Wisdomland Business Park, Guankou 2nd road, Nantou, Nanshan, Shenzhen, China
<b>Product description</b>	
Product name:	3-in-1 Foldable Magnetic Wireless Charger
Trademark:	N/A
Model name:	X40Q
Series Model(s):	X40, X40S, X40+, X40S+, X40SQ, X40Q+, X40SQ+, SQ312, X73, X74, X75
Standards:	47 CFR Part 15C
Test Method:	ANSI C63.10-2013
<b>Date of Test</b>	
Date of test:	2024-07-25 to 2024-07-29
Test result:	Pass

<b>Test Engineer</b>	:	<i>Letter. Lan.</i>
		(Letter Lan)
<b>Reviewed By</b>	:	<i>David. Lee</i>
		(David Lee)
<b>Approved By</b>	:	<i>Leon Chen</i>
		(Leon Chen)

## 1 General Description

### 1.1 Description of the EUT

Product name:	3-in-1Foldable Magnetic Wireless Charger
Model name:	X40Q
Series Model(s):	X40, X40S, X40+, X40S+, X40SQ, X40Q+, X40SQ+, SQ312, X73, X74, X75
Model difference:	All the models are the same circuit and module, except the model name.
Electrical rating:	Input: USB-C: DC 9V/3A, 12V/3A Output: Magnetic Wireless Charger: 5W/7.5W/10W/15W Air Pods Charger: 5W Apple Watch Charger: 3W/5W
Accessories:	N/A
Hardware version:	SXtech-X40Qi2-JXV-V1.0
Software version:	ABF4
Test sample(s) number:	MTi240612025-03S1001
<b>RF specification</b>	
Operating frequency range:	Transmitter1 (Phone): 115-205kHz &360kHz Transmitter2 (Air Pods): 115-205 kHz Transmitter3 (Watch): 300-350 kHz&1778kHz
Modulation type:	ASK
Antenna(s) type:	Coli

### 1.2 Description of test modes

No.	Emission test modes
Mode1	Wireless output(5W) +Air Pods(5W) +Watch(5W)
Mode2	Wireless output (7.5W) +Air Pods(5W) +Watch(5W)
Mode3	Wireless output(10W) +Air Pods(5W) +Watch(5W)
Mode4	Wireless output(15W) +Air Pods(5W) +Watch(5W)
Mode5	Wireless output(15W) +Air Pods(5W) +Watch(3W)
Mode6	Wireless output(10W) +Air Pods(5W) +Watch(3W)
Mode7	Wireless output (7.5W) +Air Pods(5W) +Watch(3W)
Mode8	Wireless output(5W) +Air Pods(5W) +Watch(3W)
Mode9	Wireless output(5W) +Air Pods(5W)
Mode10	Wireless output (7.5W) +Air Pods(5W)
Mode11	Wireless output(10W) +Air Pods(5W)
Mode12	Wireless output(15W) +Air Pods(5W)
Mode13	Wireless output(5W) +Watch(3W)
Mode14	Wireless output (7.5W) +Watch(3W)
Mode15	Wireless output(10W) +Watch(3W)
Mode16	Wireless output(15W) +Watch(3W)
Mode17	Wireless output(5W) +Watch(5W)

Mode18	Wireless output (7.5W) +Watch(5W)
Mode19	Wireless output(10W) +Watch(5W)
Mode20	Wireless output(15W) +Watch(5W)
Mode21	Air Pods(5W) +Watch(5W)
Mode22	Air Pods(5W) +Watch(3W)
Mode23	Air Pods(5W)
Mode24	Watch(5W)
Mode25	Watch(3W)
Mode26	Wireless output(5W)
Mode27	Wireless output (7.5W)
Mode28	Wireless output(10W)
Mode29	Wireless output(15W)
Mode30	stand by

### 1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

### 1.4 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
AC adapter(65W)	EP-TA865	/	SAMSUNG
Mobile Phone	iPhone 15	M2LQK7WHH0	Apple
Mobile phone	iPhone 12	F17DMBNE0DYM	Apple
Air Pods	MQD83CH/A	/	Apple
watch	watch S7	M0JVGQG1VP	Apple
watch	watch SE	/	Apple
Support cable list			
Description	Length (m)	From	To
/	/	/	/

### 1.5 Measurement uncertainty

Measurement	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	±3.1dB
Occupied channel bandwidth	±3 %
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15C	47 CFR Part 15.203	Pass
2	Conducted Emission at AC power line	47 CFR Part 15C	47 CFR Part 15.207(a)	Pass
3	20dB Occupied Bandwidth	47 CFR Part 15C	47 CFR Part 15.215(c)	Pass
4	Emissions in frequency bands (below 30MHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass
5	Emissions in frequency bands (30MHz - 1GHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass

### 3 Test Facilities and accreditations

#### 3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

#### 4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Conducted Emission at AC power line						
1	EMI Test Receiver	Rohde&schwarz	ESCI3	101368	2024-03-20	2025-03-19
2	Artificial mains network	Schwarzbeck	NSLK 8127	183	2024-03-21	2025-03-20
3	Artificial Mains Network	Rohde & Schwarz	ESH2-Z5	100263	2024-03-20	2025-03-19
20dB Occupied Bandwidth						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2024-03-20	2025-03-19
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2024-03-21	2025-03-20
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2024-03-21	2025-03-20
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2024-03-21	2025-03-20
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2024-03-21	2025-03-20
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2024-03-21	2025-03-20
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2024-03-21	2025-03-20
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2024-03-20	2025-03-19
9	DC Power Supply	Agilent	E3632A	MY40027695	2024-03-21	2025-03-20
Emissions in frequency bands (below 30MHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2024-03-20	2025-03-19
2	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2025-03-22
3	Amplifier	Hewlett-Packard	8447F	3113A06184	2024-03-20	2025-03-19
Emissions in frequency bands (30MHz - 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2024-03-20	2025-03-19
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2023-06-11	2025-06-10
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2025-03-22
4	Amplifier	Hewlett-Packard	8447F	3113A06184	2024-03-20	2025-03-19

## 5 Evaluation Results (Evaluation)

### 5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

#### 5.1.1 Conclusion:

The antenna of the EUT is permanently attached. The EUT complies with the requirement of FCC PART 15.203.
--

## 6 Radio Spectrum Matter Test Results (RF)


### 6.1 Conducted Emission at AC power line

Test Requirement:	Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2013 section 6.2		
Procedure:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

#### 6.1.1 E.U.T. Operation:


Operating Environment:					
Temperature:	26 °C	Humidity:	41 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5, Mode6, Mode7, Mode8, Mode9, Mode10, Mode11, Mode12, Mode13, Mode14, Mode15, Mode16, Mode17, Mode18, Mode19, Mode20, Mode21, Mode22, Mode23, Mode24, Mode25, Mode26, Mode27, Mode28, Mode29, Mode30				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode4) is recorded in the report				

#### 6.1.2 Test Setup Diagram:




**6.1.3 Test Data:**

Mode4 / Line: Line



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.3620	32.73	11.18	43.91	58.68	-14.77	QP	
2	0.3620	30.67	11.18	41.85	48.68	-6.83	AVG	
3	0.9260	22.82	12.46	35.28	56.00	-20.72	QP	
4	0.9700	12.48	12.56	25.04	46.00	-20.96	AVG	
5	1.7980	18.26	14.23	32.49	46.00	-13.51	AVG	
6	2.1980	26.29	10.64	36.93	56.00	-19.07	QP	
7	2.5180	31.76	10.64	42.40	56.00	-13.60	QP	
8	2.5180	29.70	10.64	40.34	46.00	-5.66	AVG	
9 *	3.2380	31.45	10.64	42.09	46.00	-3.91	AVG	
10	3.2940	33.22	10.65	43.87	56.00	-12.13	QP	
11	4.6739	23.70	10.65	34.35	46.00	-11.65	AVG	
12	5.8619	30.47	10.67	41.14	60.00	-18.86	QP	

Mode4 / Line: Neutral




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.2020	19.42	10.78	30.20	53.53	-23.33	AVG	
2		0.2100	31.96	10.80	42.76	63.21	-20.45	QP	
3		0.3620	33.41	11.18	44.59	58.68	-14.09	QP	
4		0.3620	31.54	11.18	42.72	48.68	-5.96	AVG	
5		1.0780	13.78	12.78	26.56	46.00	-19.44	AVG	
6		1.2900	23.14	13.20	36.34	56.00	-19.66	QP	
7		2.5180	31.72	10.64	42.36	56.00	-13.64	QP	
8		2.5180	29.45	10.64	40.09	46.00	-5.91	AVG	
9	*	3.2380	31.08	10.64	41.72	46.00	-4.28	AVG	
10		3.2980	35.58	10.65	46.23	56.00	-9.77	QP	
11		3.9540	29.40	10.65	40.05	56.00	-15.95	QP	
12		3.9540	24.11	10.65	34.76	46.00	-11.24	AVG	

## 6.2 20dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15.215(c)
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Test Method:	ANSI C63.10-2013, section 6.9.2
Procedure:	<p>a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.</p> <p>b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.</p> <p>c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than <math>[10 \log (OBW/RBW)]</math> below the reference level. Specific guidance is given in 4.1.5.2.</p> <p>d) Steps a) through c) might require iteration to adjust within the specified tolerances.</p> <p>e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.</p> <p>f) Set detection mode to peak and trace mode to max hold.</p> <p>g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).</p> <p>h) Determine the “-xx dB down amplitude” using <math>[(\text{reference value}) - xx]</math>. Alternatively, this calculation may be made by using the marker-delta function of the instrument.</p> <p>i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).</p> <p>j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.</p> <p>k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).</p>

**6.2.1 E.U.T. Operation:**

Operating Environment:					
Temperature:	21.7 °C	Humidity:	51.3 %	Atmospheric Pressure:	98 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5, Mode6, Mode7, Mode8, Mode9, Mode10, Mode11, Mode12, Mode13, Mode14, Mode15, Mode16, Mode17, Mode18, Mode19, Mode20, Mode21, Mode22, Mode23, Mode24, Mode25, Mode26, Mode27, Mode28, Mode29, Mode30				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode23, Mode24, Mode25, Mode27, Mode29) is recorded in the report				


**6.2.2 Test Setup Diagram:**


**6.2.3 Test Data:**

**Note:** Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Phone:7.5W

Frequency kHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
127.825	811	689



**Note:** Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Phone

Frequency kHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
359.545	810	694



**Note:** Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Watch 5W


Frequency MHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
1.77776	752	645



**Note:** Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Watch 3W


Frequency kHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
323.310	832	754



**Note:** Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

**Air Pods**

Frequency kHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
153.84	810	688




### 6.3 Emissions in frequency bands (below 30MHz)

Test Requirement:	47 CFR Part 15.209		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.</p>			
Test Method:	ANSI C63.10-2013 section 6.4		
Procedure:	ANSI C63.10-2013 section 6.4		

#### 6.3.1 E.U.T. Operation:


Operating Environment:			
Temperature:	22.5 °C	Humidity:	43 %
		Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5, Mode6, Mode7, Mode8, Mode9, Mode10, Mode11, Mode12, Mode13, Mode14, Mode15, Mode16, Mode17, Mode18, Mode19, Mode20, Mode21, Mode22, Mode23, Mode24, Mode25, Mode26, Mode27, Mode28, Mode29, Mode30		
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode4, Mode6) is recorded in the report		

#### 6.3.2 Test Setup Diagram:




**6.3.3 Test Data:**

Mode4 / Polarization: Coplanar




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.1150	31.29	21.01	52.30	126.41	-74.11	peak	
2	*	0.1150	28.74	21.01	49.75	106.41	-56.66	AVG	

## Mode4 / Polarization: Coplanar




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.3633	35.03	21.10	56.13	116.40	-60.27	peak	
2		0.3633	34.77	21.10	55.87	96.40	-40.53	AVG	
3	*	0.5762	35.40	21.17	56.57	72.40	-15.83	QP	
4		0.8045	29.28	21.26	50.54	69.51	-18.97	QP	
5		1.0375	24.12	21.34	45.46	67.30	-21.84	QP	
6		1.2688	19.92	21.35	41.27	65.56	-24.29	QP	
7		1.4953	16.09	21.36	37.45	64.14	-26.69	QP	
8		1.7805	26.33	21.38	47.71	69.50	-21.79	QP	

Mode6 / Polarization: Coplanar



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.1139	59.91	21.02	80.93	126.50	-45.57	peak	
2	*	0.1139	57.49	21.02	78.51	106.50	-27.99	AVG	
3		0.1454	31.37	21.02	52.39	124.37	-71.98	peak	
4		0.1454	28.76	21.02	49.78	104.37	-54.59	AVG	

Mode6 / Polarization: Coplanar




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.3320	35.40	21.09	56.49	117.19	-60.70	peak	
2		0.3320	33.25	21.09	54.34	97.19	-42.85	AVG	
3	*	0.5552	35.81	21.16	56.97	72.72	-15.75	QP	
4		0.7793	29.97	21.25	51.22	69.78	-18.56	QP	
5		0.9997	24.42	21.34	45.76	67.62	-21.86	QP	
6		1.2226	19.93	21.35	41.28	65.88	-24.60	QP	
7		1.4480	17.78	21.36	39.14	64.42	-25.28	QP	

**6.4 Emissions in frequency bands (30MHz - 1GHz)**

Test Requirement:	47 CFR Part 15.209		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.</p>			
Test Method:	ANSI C63.10-2013 section 6.5		
Procedure:	ANSI C63.10-2013 section 6.5		


**6.4.1 E.U.T. Operation:**

Operating Environment:			
Temperature:	22.5 °C	Humidity:	43 %
		Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5, Mode6, Mode7, Mode8, Mode9, Mode10, Mode11, Mode12, Mode13, Mode14, Mode15, Mode16, Mode17, Mode18, Mode19, Mode20, Mode21, Mode22, Mode23, Mode24, Mode25, Mode26, Mode27, Mode28, Mode29, Mode30		
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode3) is recorded in the report		

**6.4.2 Test Setup Diagram:**


**6.4.3 Test Data:**

Mode3 / Polarization: Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		40.9880	29.66	-7.18	22.48	40.00	-17.52	QP	
2		114.1138	36.14	-7.97	28.17	43.50	-15.33	QP	
3		138.3873	38.15	-8.56	29.59	43.50	-13.91	QP	
4		181.9202	36.27	-8.76	27.51	43.50	-15.99	QP	
5	*	231.7179	41.41	-6.24	35.17	46.00	-10.83	QP	
6		321.0608	33.53	-3.69	29.84	46.00	-16.16	QP	

## Mode3 / Polarization: Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	35.4993	44.34	-8.86	35.48	40.00	-4.52	QP	
2	!	41.8596	42.15	-6.94	35.21	40.00	-4.79	QP	
3		119.0180	39.47	-8.62	30.85	43.50	-12.65	QP	
4		135.9822	40.83	-9.61	31.22	43.50	-12.28	QP	
5		178.7584	40.22	-8.97	31.25	43.50	-12.25	QP	
6		222.1698	42.20	-7.57	34.63	46.00	-11.37	QP	

## Photographs of the test setup

Refer to Appendix - Test Setup Photos

## Photographs of the EUT

Refer to Appendix - EUT Photos

**----End of Report----**