ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY **CFS8DL6128RF-2**
SYOSSET, NY 11791 **FCC ID#_____**

DATE: 10/02/02 TESTED BY: John Fitzgerald APPROVED BY: KEN ADDY

TEST SAMPLE (model): 6128RF-2

TEST METHOD: ANSI C63.4-1992
TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) Fo= 345 MHZ
2) DETECTOR = PEAK.
3) FREQUENCY RANGE SCANNED TO 4 GHz.

4) CONVERTED READING = $10^{\left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20}\right]}$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
30								729
345	H	79.75	1.17	16	70145	10	7014.5	7,291
690	H	39.5	1.83	21.1	1322.8	10	132.28	729
1035	H	36.67	2.33	25.2	1621.8	10	162.18	500
1380	H	34.3	3.0	28.8	2041.7	10	204.17	500
1725	H	29.7	3.5	31.2	1659.5	10	165.95	729