

Rev: 01

Page: 1 of 29

Appendix B - DAE & Probe Calibration Certificate

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst S Service suisse d'étalonnage C Servizio svizzero di taratura Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

SGS-TW (Auden)

Accreditation No.: SCS 0108

Certificate No: DAE4-877_Mar21

Calibration procedure for the data acquisition Calibration date: March 22, 2021 This calibration certificate documents the traceability to national standards, which realize the physical procedure and the uncertainties with confidence probability are given on the following possibility and procedure in the closed laboratory facility: environment temperature (2) Calibration Equipment used (M&TE critical for calibration) Primary Standards ID # Cal Date (Certificate No.) Secondary Standards ID # Check Date (in house) Nuto DAE Calibration Unit SE UWS 053 AA 1001 O7-Jan-21 (in house check) SE UMS 006 AA 1002 O7-Jan-21 (in house check) Name Function	
Calibration procedure for the data acquisition Calibration procedure for the data acquisition Calibration date: March 22, 2021 This calibration certificate documents the traceability to national standards, which realize the physical procedure in the closed laboratory facility are given on the following public actions have been conducted in the closed laboratory facility: environment temperature (2) Calibration Equipment used (M&TE critical for calibration) Primary Standards ID # Cal Date (Certificate No.) Keithley Multimeter Type 2001 SN: 0810278 07-Sep-20 (No:28647) Secondary Standards ID # Check Date (in house) Auto DAE Calibration Unit SE UWS 053 AA 1001 07-Jan-21 (in house check) SE UMS 006 AA 1002 07-Jan-21 (in house check)	
This calibration certificate documents the traceability to national standards, which realize the phy: The measurements and the uncertainties with confidence probability are given on the following possible and the uncertainties with confidence probability are given on the following possible and the closed laboratory facility: environment temperature (2 Calibration Equipment used (M&TE critical for calibration) Primary Standards ID #	electronics (DAE)
The measurements and the uncertainties with confidence probability are given on the following policy and fo	
Primary Standards ID # Cal Date (Certificate No.) Keithley Multimeter Type 2001 SN: 0810278 07-Sep-20 (No:28647) Secondary Standards ID # Check Date (in house) Auto DAE Calibration Unit SE UWS 053 AA 1001 O7-Jan-21 (in house check) SE UMS 006 AA 1002 O7-Jan-21 (in house check)	ges and are part of the certificate.
Keithley Multimeter Type 2001 SN: 0810278 07-Sep-20 (No:28647) Secondary Standards ID # Check Date (in house) Auto DAE Calibration Unit SE UWS 053 AA 1001 07-Jan-21 (in house check) Calibrator Box V2.1 SE UMS 006 AA 1002 07-Jan-21 (in house check) Name Function	
Secondary Standards ID # Check Date (in house) Auto DAE Calibration Unit SE UWS 053 AA 1001 07-Jan-21 (in house check) Calibrator Box V2.1 SE UMS 006 AA 1002 07-Jan-21 (in house check) Name Function	Scheduled Calibration
Auto DAE Calibration Unit SE UWS 053 AA 1001 07-Jan-21 (in house check) SE UMS 006 AA 1002 07-Jan-21 (in house check) Name Function	Sep-21
Calibrator Box V2.1 SE UMS 006 AA 1002 07-Jan-21 (in house check) Name Function	Scheduled Check
	In house check: Jan-22 In house check: Jan-22
Calibrated by: Adrian Gehring Laboratory Technician	Signature
	AC
Approved by: Sven Kühn Deputy Manager	1.V. Blund
	Issued: March 22, 2021

Certificate No: DAE4-877_Mar21 Page 1 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Rev: 01

Page: 2 of 29

Calibration Laboratory of Schmid & Partner **Engineering AG** Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst S Service suisse d'étalonnage C Servizio svizzero di taratura Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary

DAE data acquisition electronics

information used in DASY system to align probe sensor X to the robot Connector angle

coordinate system.

Methods Applied and Interpretation of Parameters

- DC Voltage Measurement: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- Connector angle: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - DC Voltage Measurement Linearity: Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - Common mode sensitivity: Influence of a positive or negative common mode voltage on the differential measurement.
 - Channel separation: Influence of a voltage on the neighbor channels not subject to an input voltage.
 - AD Converter Values with inputs shorted: Values on the internal AD converter corresponding to zero input voltage
 - Input Offset Measurement: Output voltage and statistical results over a large number of zero voltage measurements.
 - Input Offset Current: Typical value for information; Maximum channel input offset current, not considering the input resistance.
 - Input resistance: Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - Low Battery Alarm Voltage: Typical value for information. Below this voltage, a battery alarm signal is generated.
 - Power consumption: Typical value for information. Supply currents in various operating modes.

Certificate No: DAE4-877 Mar21

Page 2 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Rev: 01

Page: 3 of 29

DC Voltage Measurement

A/D - Converter Resolution nominal

Calibration Factors	X	Υ	Z
High Range	405.003 ± 0.02% (k=2)	404.568 ± 0.02% (k=2)	405.016 ± 0.02% (k=2)
Low Range	3.98294 ± 1.50% (k=2)	3.98209 ± 1.50% (k=2)	3.97086 ± 1.50% (k=2)

Connector Angle

Connector Angle to be used in DASY system	323.0 ° ± 1 °

Certificate No: DAE4-877_Mar21

Page 3 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,件報先结里僅對剛建之樣是各書,同時件樣是僅是200千。未報先夫德未公司書面許可,不可執份複劃。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/lerms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/lerms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Rev: 01

Page: 4 of 29

Appendix (Additional assessments outside the scope of SCS0108)

1. DC Voltage Linearity

High Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Inp	ut 199991.71	1.54	0.00
Channel X + Inp	ut 20004.56	2.43	0.01
Channel X - Inpu	ıt -19998.27	2.75	-0.01
Channel Y + Inp	ut 199989.38	-0.70	-0.00
Channel Y + Inp	ut 20002.58	0.55	0.00
Channel Y - Inpu	t -20001.55	-0.30	0.00
Channel Z + Inp	ut 199989.94	0.12	0.00
Channel Z + Inp	ut 20003.68	1.77	0.01
Channel Z - Inpu	-20000.37	1.00	-0.00

Low Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	2002.15	0.83	0.04
Channel X + Input	202.00	0.23	0.11
Channel X - Input	-197.78	0.33	-0.17
Channel Y + Input	2001.53	0.17	0.01
Channel Y + Input	201.17	-0.58	-0.29
Channel Y - Input	-198.46	-0.27	0.14
Channel Z + Input	2001.67	0.43	0.02
Channel Z + Input	200.28	-1.32	-0.66
Channel Z - Input	-199.94	-1.67	0.84

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading (μV)	Low Range Average Reading (μV)
Channel X	200	13.71	13.05
	- 200	-12.03	-13.85
Channel Y	200	-18.74	-18.92
	- 200	17.80	18.21
Channel Z	200	20.10	20.01
	- 200	-22.88	-23.46

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X (μV)	Channel Y (μV)	Channel Z (μV)
Channel X	200		0.98	-3.31
Channel Y	200	6.59		1.23
Channel Z	200	9.17	4.46	+

Certificate No: DAE4-877_Mar21

Page 4 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有說明,什報告結果僅與10元。木報告表極大公司書面許可,不可部份複製。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

303 Idiwali Eta.



Rev: 01

Page: 5 of 29

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	16006	16610
Channel Y	15886	17452
Channel Z	15741	17385

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec Input $10M\Omega$

	Average (μV)	min. Offset (μV)	max. Offset (μV)	Std. Deviation (µV)
Channel X	0.63	-1.47	2.04	0.58
Channel Y	0.13	-1.40	1.36	0.59
Channel Z	-0.55	-2.04	1.72	0.70

6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

	Zeroing (kOhm)	Measuring (MOhm)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)	
Supply (+ Vcc)	+7.9	
Supply (- Vcc)	-7.6	

9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-8	-9

Certificate No: DAE4-877_Mar21

Page 5 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

台灣檢驗科技股份有限公司



Rev: 01

Page: 6 of 29



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有铅明,件報生结里做新聞过入樣具負責,同時件樣具做保留的干。大報生主概未公司書面許可,不可部份複劃。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Rev: 01

Page: 7 of 29

Calibration Laboratory of Engineering AG
Engineering AG
S004 Zurich, Switze





Accreditation No.: SCS 0108

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL NORMX,y,z ConvF DCP CF A, B, C, D Polarization

Itissue simulating liquid sensitivity in free space sensitivity in TSL / NORMx,y,z diode compression point creat factor (1/duty_cycle) of the RF signal modulation dependent linearization parameters or rotation around probe axis. S rotation around an axis that is in the plane normal to probe axis (st measurement center), i.e., 3 = 0 is normal to probe axis information used in DASY system to align probe sensor X to the robot coordinate system Polarization () Polarization 8

- Connector Angle

 Calibration is Performed According to the Following Standards:

 a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Davices: Measurement Techniques", June 2013

 b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from handhald and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2015

 c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication device used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010

 d) KDB 885664, "SAR Measurement Requirements for 100 MHz to 6 GHz", March 2010

- Methods Applied and Interpretation of Parameters:

 NORMx,y,z: Assessed for E-field polarization (# = 0 (f ≤ 900 MHz in TEM-cell; T > 1800 MHz: R22 waveguide).

 NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMs,y,z does not affect the E²-field uncertainty inside TSL (see below Corw?).
 - uncertainty inside TSL (see below ConvF). $NORM(N,y,z=NORMx,y,z^*)$ frequency response (see Frequency Response Chart). This linearization is implamented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF. DCPA,y,z: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media. PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.

 - PAR: s the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics, st., Dx,y.z.; VRx,y.z. A, B, C, D are numerical linearization parameters assessed based on the date of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode. Convir and Boundary Effect Parameters. Assessed in fall phantom using E-field (or Temperature Transfer Standard for f s 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMs.y. 2* Convir whereby the uncertainty corresponds to that given for Convir 5* frequency dependent Convir is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz. Spherical isotropy (3D deviation from isotropy): In a field of low gradients realized using a flat phantom exposed by a patch enterna.

 Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis), No tolerance required.

 Connector Anglic: The angle is assessed using the information gained by determining the NORMs (no uncertainty required).

Certificate No: EX3-7466 Jan21

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Rev: 01

Page: 8 of 29

January 29, 2021

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7466

Basic Calibration Para	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm (µV/(V/m) ²) ^A	0.45	0.39	0,61	± 10.1 %

UID	Communication System Name		dB.	d8√h∧	C	dB	WR mV	Max dev.	Max Unct (k=2)
0	CW	X	0.00	0.00	1.00	0.00	150.5	±2.2%	±4.7%
		Y	0.00	0.00	1.00		143.0		
		Z	0.00	0.00	1.00		156.1		
10352-	Pulse Waveform (200Hz. 10%)	X	6.41	75.26	13.91	10.00	60.0	±2.6%	# 9,6 %
AAA.	Total Transferred Control of the Control	Y	1.66	61.84	7.61		60.0		
3.50		Z	20.00	95.49	22.81		60.0		
10353-	Pulse Waveform (200Hz. 20%)	×	20.00	87.76	16.55	6.99	80.0	±2.1%	± 9.6 %
AAA.	1 464 (100 100 100 100 100 100 100 100 100 10	Y	0.78	60.01	5.70		80.0		
		Z	20.00	109.03	28.37		80.0		
10354-	Pulse Waveform (200Hz, 40%)	X	20.00	114.67	27.40	3.98	95.0	±20%	± 9.6 %
AAA.	1,000,000,000,000,000	Y	0.39	60.00	4.96		95.0		
		2	20.00	151.84	46.68		95.0	1000	
10355-	Pulse Waveform (200Hz, 60%)	X	0.17	152.80	100.00	2.22	120.0	±2.2 %	±9.6%
WA	The contract of the contract o	Y	0.25	61.07	5.62		120.0		1000
		2	2.52	160.00	62.06		120,0		
10387-	QPSK Waveform, 1 MHz	X	6.66	93.59	26.49	1,00	150.0	±2.9%	±9.6 %
AAA	90.5000.5000.000	Y	1.60	67.46	15.34		150.0		
		Z	2.22	71.55	18.47		150.0		
10385-	OPSK Waveform, 10 MHz	X	3.86	80.00	22.12	0.00	150.0	128%	± 9.6 %
AAA	1	Y	2.06	67.36	15.67		150.0		
	the second second second	Z	3.04	73.63	19.08		150.0		
10396-	64-QAM Waveform, 100 kHz	X	3.32	77.52	23.54	3.01	150.0	± 2.5 %	± 9.6 %
AAA		Y	1.82	64.05	15.97	200	150.0	200	
		2	2.79	71.10	20.57	-	150.0		
10399-	64-QAM Waveform, 40 MHz	X	3.98	70.45	18.12	0.00	150.0	± 2.8 %	±9.6 °
AAA		Y	3.42	66.88	15.76		150.0		100
		2	3.84	68.75	17.14		150,0		
10414-	WLAN CCDF, 64-QAM, 40MHz	X	4.99	67.25	16.87	0,00	150.0	12.8%	±9,65
AAA		Y	4,68	65.67	15.59		150.0	100	1
		Z	5.05	66.21	16.27		150.0		

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: EX3-7466_Jan21

Page 3 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

entanties of Norm X,Y,Z do not affect the E⁻¹-field uncentainty inside TSL (see Pages S, 6 and 7) all linearization parameter, uncertainty not required, rify is determined using the max, sevalution from Remain response applying rectargular distribution and is expressed for the occurre of the



Rev: 01

Page: 9 of 29

January 29, 2021

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7466

	C1 fF	C2 fF	α V~1	ms,V-i	ms,V-1	T3 ms	T4 V-2	T5	T.6
X	32.4	242.77	36.31	3,66	0.00	5.01	1.37	0.00	1.01
Y	30.4	225.35	35.05	3.07	0.00	4.90	0.00	0.11	1.00
7	47.2	365.07	38.23	8.11	0.00	5.10	0.00	0.33	1.01

Sensor Arrangement	Triangular
Connector Angle (°)	148,1
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2,5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Note: Measurement distance from surface can be increased to 3-4 mm for an Area Scan job.

Certificate No: EX3-7466_Jan21

Page 4 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Rev: 01

January 29, 2021

Page: 10 of 29

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7466

Calibration Parameter Determined in Head Tissue Simulating Madia

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m)	ConvF.X	ConvF Y	ConvF Z	Alpha ^G	Depth (mm)	Unc (k=2)
600	42.7	0.88	10.92	10.92	10.92	0.06	1.20	± 13.3 %
750	41.9	0.89	10.27	10.27	10.27	0.45	1.00	± 12.0 %
835	41.5	0.90	10.11	10.11	10,11	0.45	0.91	± 12.0 %
900	41.5	0.97	9,83	9.83	9.83	0.39	0.97	± 12.0 %
1450	40.5	1.20	9.46	9,46	9.46	0.30	0.80	± 12.0 %
1750	40.1	1.37	9.07	9.07	9.07	0.32	0.80	± 12.0 %
1900	40.0	1.40	8.71	8.71	8.71	0.29	0.80	± 12.0 %
2000	40.0	1.40	8.60	8.60	8.60	0.32	0.85	± 12.0 %
2300	39.5	1.67	8.47	8.47	8.47	0.28	0.90	± 12.0 %
2450	39.2	1.80	8.08	8.08	8.08	0.27	0.90	± 12.0 %
2600	39.0	1.96	7.82	7.82	7.82	0.38	0.90	± 12.0 %
3300	38.2	2.71	7.34	7.34	7,34	0.30	1.30	± 13.1 %
3500	37.9	2.91	7,10	7.10	7,10	0.35	1.30	±13.1%
3700	37.7	3.12	6.98	6.98	6.98	0.35	1.30	± 13.1 %
3900	37.5	3.32	6.80	6.80	6.80	0.35	1,60	±13,1%
4100	37.2	3,53	6.70	6.70	6.70	0.35	1.60	± 13.1 %
4200	37.1	3.63	6.59	6.59	6.59	0.40	1.70	± 13,1 %
4400	36.9	3.84	6.32	6.32	6.32	8.40	1.70	± 13.1 %
4600	36.7	4.04	6.34	6.34	6.34	0.40	1.70	±13.1%
4800	36.4	4.25	6.30	6.30	6.30	0.40	1.70	± 13.1 %
4950	36,3	4.40	6.04	6.04	6.04	0.40	1.80	± 13.1 %
5200	36.0	4,66	5.60	5.60	5,60	0.40	1.80	± 13.1 %
5300	35,9	4,76	5.50	5.50	5.50	0.40	1.80	± 13.1 %
5600	35,5	5.07	5.04	5.04	5.04	0.40	1.80	± 13.1 %
5800	35.3	5.27	5.02	5.02	5.02	0.40	1.80	± 13.1 %

Certificate No: EX3-7466_Jan21

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Rev: 01

Page: 11 of 29

January 29, 2021

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7466

. D. Comband to D. d. Thomas Shoulether Madi

f (MHz) E	Relative Permittivity	Conductivity (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^o	Depth (mm)	Unc (k=2)
600	56.1	0.95	11,08	11.08	11.08	0.10	1.20	± 13.3 %
750	55.5	0.96	10.56	10.56	10.56	0.39	0.83	± 12.0 %
835	55.2	0.97	10.29	10.29	10.29	0.40	0.80	± 12.0 %
900	55.0	1.05	9.98	9.98	9.98	0.26	1.08	± 12.0 %
1750	53.4	1.49	8,69	8.89	8.69	0.31	0.85	± 12.0 %
1900	53.3	1.52	8.30	8.30	8.30	0.17	1.27	± 12.0 %
2000	53.3	1.52	8.26	8.26	8.26	0.29	0.92	± 12.0 %
2300	52.9	1.81	8.22	8.22	8.22	0.34	0.88	± 12.0 %
2450	52.7	1.95	7.99	7.99	7.99	0.33	0.95	± 12.0 %
2600	52.5	2.16	7.85	7.85	7.85	0.32	0.95	± 12.0 %
3300	51.6	3.08	6.67	6,67	6.67	0.40	1.35	± 13.1 %
3500	51.3	3.31	6.65	6.65	6.65	0.40	1.35	± 13.1 %
3700	51.0	3.55	6.60	6,60	6.60	0.40	1.30	± 13.1 %
3900	51.2	3.78	6.23	8.23	6.23	0.40	1.70	± 13.1 %
4100	50.5	4.01	6.09	6.09	6.09	0,40	1.70	± 13.1.%
4200	50.4	4.13	5.88	5.88	5.88	0.50	1.80	± 13.1 %
4400	50.1	4.37	5.77	5.77	5.77	0.50	1.80	± 13.1 %
4600	49.8	4.60	5.69	5.69	5.69	0.50	1.80	±13.1%
4800	49.6	4.83	5.62	5.62	5.62	0.50	1.80	± 13.1 %
4950	49.4	5.01	5.39	5.39	5.39	0.50	1.90	± 13.1 %
5200	49.0	5.30	5.00	5.00	5.00	0.50	1.90	±13.1 %
5300	48.9	5.42	4.90	4.90	4.90	0.50	1.90	± 13.1 %
5600	48.5	5.77	4.30	4.30	4.30	0.50	1,90	± 13.1 %
5800	48.2	6.00	4.41	4.41	4.41	0.50	1.90	± 13.1 %

Certificate No: EX3-7466_Jan21

Page 6 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

www.sqs.com.tw



Rev: 01

Page: 12 of 29

EX3DV4- SN 7466

January 29, 2021

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7466

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) c	Relative Permittivity ^F	Conductivity (S/m) F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^d (mm)	Unc (k=2)
6500	34.5	6.07	5.70	5,70	5.70	0.20	2.50	± 18,6 %
7000	33.9	6.65	5.85	5.85	5.85	0.20	2.00	± 18.6 %
8000	32.7	7.84	5.60	5,60	5.60	0.40	1.80	± 18.6 %
9000	31.5	9.08	5.45	5.45	5.45	0.50	1.80	± 18.6 %

Certificate No: EX3-7466_Jan21

Page 7 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Rev: 01


Page: 13 of 29

EX3DV4- SN:7466

January 29, 2021

Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

Certificate No: EX3-7466_Jan21

Page 8 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.





Rev: 01

Page: 14 of 29

EX3DV4- \$N:7466 January 29, 2021

Receiving Pattern (\$\phi\$), 9 = 0°





Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

Certificate No: EX3-7466_Jan21

Page 9 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非兄有论时,此都华结里做影响就之缘是台香,同时此楼是做是2000子。木都华丰硕木公司事而纯可,不可驾份海顺。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.




Rev: 01


Page: 15 of 29

EX3DV4-SN:7466

January 29, 2021

Dynamic Range f(SAR_{head}) (TEM cell , feval= 1900 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Certificate No: EX3-7466_Jan21

Page 10 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

www.sqs.com.tw



Rev: 01

Page: 16 of 29

EX3DV4- SN:7466 January 29, 2021 **Conversion Factor Assessment** f = 1900 MHz, WGLS R22 (H_convF) Deviation from Isotropy in Liquid Error (ø, ð), f = 900 MHz -0.8 -0.6 -0.4 -0.2 0.0 0.2 0.4 0.6 Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Certificate No: EX3-7466_Jan21

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



Rev: 01

Page: 17 of 29

EX3DV4-SN:7466

January 29, 2021

Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc [±] (k=2)
0		CW	CW	0,00	±4.7 %
10010	CAA	SAR Validation (Square, 100ms, 10ms)	Test	10,00	±9.6 %
10011	CAB	UMTS-FDD (WCDMA)	WCDMA	2.91	±9.6 %
10012	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	± 9.6 %
10013	CAB	IEEE 802.11g WIFI 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9.46	± 9.6 %
10021	DAC	GSM-FDD (TDMA, GMSK)	GSM	9.39	± 9.6 %
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	± 9.6 %
10024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	± 9.6 %
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	± 9.6 %
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9,55	± 9.6 %
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4,80	±9.6%
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-2)	GSM	3,55	±9.6 %
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	GSM	7.78	±9.6%
10030	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Bluelooth	5.30	±9.6 %
10031	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	Billetooth	1.87	± 9.6 %
10032	CAA	(EEE 802.15.1 Bluetooth (GFSK, DH5)	Bluelooth	1.16	± 9.6 %
10033	CAA	(EEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	7.74	± 9.6 %
10034	CAA	(EEE 802.15.1 Bluetooth (Pl/4-DQPSK, DH3)	Bluetooth	4.53	±9.6 %
10035	CAA	IEEE 802.15.1 Bluetooth (PV4-DQPSK, DH5)	Bluetooth	3.83	± 9.6 %
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	8.01	±9.6%
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth	4.77	±9.6 %
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4.10	±9.6 %
10039	CAB	CDMA2000 (1xRTT, RC1)	CDMA2000	4.57	± 9.6 %
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, Pl/4-DQPSK, Halfrate)	AMPS	7.78	±9.6 %
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0.00	±9.6%
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	± 9.6 %
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	±9.6%
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mops)	TD-SCDMA	11.01	± 9.6 %
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	± 9.6 %
10059	CAB	IEEE 802.11b WiFI 2.4 GHz (DSSS, 2 Mbps)	WLAN	2.12	± 9.6 %
10060	CAB	IEEE 802.11b WIFI 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2.83	± 9.6 %
10061		IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	WLAN	3.60	±9.6%
10062	CAB	IEEE 802,11a/h WiFi 5 GHz (OFDM, 6 Mbps)	WLAN	8.68	± 9.6 %
10062	CAD	IEEE 802,11a/h WiFi 5 GHz (OFDM, 9 Mbps)	WLAN	8.63	±9.6%
10064	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	± 9.6 %
10065	CAD	IEEE 802.11a/n W/FI 5 GHz (OFDM, 12 Mbps)	WLAN	9.00	± 9.6 %
10000	CAD		WLAN	9.38	± 9.6 %
10066	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	WLAN	10.12	
10067	CAD	IEEE 802 11a/h WIFI 5 GHz (OFDM, 36 Mbps) IEEE 802 11a/h WIFI 5 GHz (OFDM, 48 Mbps)	WLAN	10.12	± 9.6 %
10068	CAD		WLAN	10.24	± 9.6 %
10069	CAD	IEEE 802.11a/n WiFi 5 GHz (OFDM, 54 Mbps)	WLAN		
10071	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9.83	±9.6 %
10072	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9.62	±9.69
10073	CAB	IEEE 802,11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)			±9,65
10074	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	WLAN	10.30	±9.65
10075	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10.77	± 9.6 %
10076	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	WLAN	10.94	±9,69
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	WLAN	11.00	±9,6 °
10081	CAB	COMA2000 (1xRTT, RC3)	CDMA2000	3.97	± 9.6 9
10082	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	AMPS	4.77	± 9.6 9
10090	DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	GSM	6.56	±9.69
10097	CAC	LIMTS-FDD (HSDPA)	WCDMA	3.98	± 9.6 9
10098	DAC	UMTS-FDD (HSUPA, Subtest 2)	WCDMA	3.98	±9.69

Cartificate No: EX3-7466_Jan21

Page 12 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Rev: 01

Page: 18 of 29

0099	I cac	EDGE-FDD (TDMA, BPSK, TN 0-4)	GSM	9.55	± 9.6 %
0100	CAC	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-FDD	5.67	±9.6 %
10101	CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz. 16-QAM)	LTE-FDD	6.42	±9.6%
0102	CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9.6 %
10103	DAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-TDD	9.29	±9.6%
10104	CAE	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-TDD	9.97	±9.6%
10105	CAE	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-TDD	10.01	±9.6%
10108	CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-FDD	5.80	± 9.6 %
10109	CAG	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	± 9.6 %
10110	CAG	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-FDD	5.75	± 9.6 %
10111	CAG	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-FDD	6.44	± 9.6 %
10112	CAG	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-FDD	6.59	±9.6 %
10113	CAG	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-FD0	6.62	±9.6 %
10114	CAG	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	WLAN	8.10	± 9.6 %
10115	CAG	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	WLAN	8.46	19.6%
10116	CAG	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	WLAN	8.15	± 9.6 %
10117	CAG	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	WLAN	8,07	±9.6 %
10115	CAD	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	WLAN	8,59	±9.6%
10119	CAD	IEEE 802.11n (HT Mixed, 135 Mbps. 64-QAM)	WLAN	8.13	±9.6%
10140	CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-FOD	6,49	± 9.6 %
10141	CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz. 64-QAM)	LTE-FDD	6.53	±9.6 %
10142	CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6 %
10143	CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-FDD	6.35	±9.6 %
10144	CAC	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-FDD	6.65	±9.6 %
10145	CAC	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-FDD	5.76	±9.6 %
10146	CAC	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.41	± 9.6 %
10147	CAC	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.72	±9.6%
10149	CAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	± 9.6 %
10150	CAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz. 64-QAM)	LTE-FDD	6.60	±9.6 %
10151	CAE	LTE-TDD (SC-FDMA, 50% RB, 20 MHz. QPSK)	LTE-TDD	9.28	± 9.6 %
10152	CAE	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-TDD	9.92	±9.6 %
10153	CAE	LTE-TOD (SC-FDMA, 50% RB, 20 MHz, 54-QAM)	LTE-TDD	10.05	± 9.6 %
10154	CAF	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-FDD	5.75	±9.6 %
10155	CAF	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	± 9.6 %
10156	CAF	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-FDD	5.79	± 9.6 %
10157	CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-FDD	6.49	± 9.6 %
10158	CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.62	± 9.6 %
10159	CAG	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-FDD	6,56	±9.6%
10160	CAG	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-FDD	5.82	± 9,6 %
10161	CAG	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-FDD	6.43	±9.6%
10162	CAG	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-FOD	6.58	±9.6 %
10166	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-F00	5.46	±9.6 %
10167	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-DAM)	LTE-FDD	6.21	±9.6 %
10168	CAG	LTE-FDD (SC-FDMA, 50% RB. 1.4 MHz. 64-QAM)	LTE-FDD	6.79	± 9.6 9
10169	CAG	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-FDD	5.73	±9.69
10170	CAG	LTE-FDD (SC-FDMA, 1 RB, 20 MHz. 16-QAM)	LTE-FDD	6.52	± 9.6 9
10171	CAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz. 64-QAM)	LTE-FDD	6.49	± 9.6 %
10172	CAE	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-TOD	9.21	± 9.6 %
10173	CAE	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6.9
10174	CAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz. 64-QAM)	LTE-TDD	10.25	±9,6.9
10175	CAF	LTE-FDD (SC-FDMA, 1 RB, 10 MHz. QPSK)	LTE-FDD	5.72	±9.69
10176	CAF	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6.9
10177	CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, OPSK)	LTE-FDD	5.73	±9.63
10178	CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-FDD	6.52	±9.63
10179	AAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz. 64-QAM)	LTE-FDD	6.50	±9.6 9
10180	CAG	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-FDD	6.50	±9.6 9

Certificate No: EX3-7466 Jan21

Page 13 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless ounerwise stated une results snown in this test report reter only to the sample(s) tested and such as ample(s) are retained for 90 days only. We #shaft #sh prosecuted to the fullest extent of the law.



Rev: 01

Page: 19 of 29

10181	1.00	LTE-FDD (SC-FDMA, 1 RB. 15 MHz, QPSK)	LTE-FDD	5.72	±9.6%
10181	CAG	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-FDD	6.52	±9.6 %
10183	CAG	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10183	CAG	LTE-FDD (SC-FDMA, 1 RB, 13 MHz, B4-QAM)	LTE-FDD	5.73	± 9.6 %
0185	CAG	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 18-QAM)	LTE-FDD	6.51	± 9.6 %
10185	CAI	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-FDD	6.50	± 9.6 %
10186	CAG	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, GP-GAM)	LTE-FDD	5.73	± 9.6 %
10188	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.50	±9.6 %
10189	CAE	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.09	±9.6 %
14.86	CAE	IEEE 802.11n (HT Greenfield, 9.5 Mbps, 975K)	WLAN	8.12	± 9.6 %
10194	AAD	IEEE 802.11n (HT Greenfield, 55 Mbps, 64-QAM)	WLAN	8.21	19.6%
10195	CAE	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	WLAN	8.10	19.6 %
10196	CAE	(EEE 802.11n (HT Mixed, 8.5 Mbps, 16-QAM)	WLAN	8.13	± 9.6 %
	AAE	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	WLAN	8.27	± 9.6 %
10198	CAF	IEEE 802.11n (HT Mixed, 65 Mops, 64-QAM)	WLAN	8.03	± 9.6 %
10219	CAF		WLAN	8.13	
10220	AAF	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM) IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	WLAN	8.13	± 9.6 %
10221	CAC	The state of the s	WLAN		
10222	CAC	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)		8.06	±9.6%
10223	CAD	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	WLAN	8,48	±9.6%
10224	CAD	JEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	WLAN	8.08	±9.6 %
10225	CAD	UMTS-FDD (HSPA+)	WCDMA	5.97	± 9.6 %
10226	CAD	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TOO	9.49	±9.6 %
10227	CAD	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.26	± 9.6 %
10228	CAD	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	9.22	±9.6 %
10229	DAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz., 16-QAM)	LTE-TOD	9.48	±9.6 %
10230	CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz., 64-QAM)	LTE-TDD	10.25	±9.6%
10231	CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-TOD	9.19	±9.65
10232	CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-TDD	9.48	±9.6 %
10233	CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10234	CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-TDD	9.21	± 9,6 %
10235	CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz. 16-QAM)	LTE-TDD	9.48	19.6%
10236	CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10237	CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-TOD	9.21	± 9.6 %
10238	CAB	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-TOO	9.48	± 9.6 %
10239	CAB	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-TOO	10.25	±9.67
10240	CAB	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-TOD	9.21	± 9.6 %
10241	CAB	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-TOO	9.82	± 9.6 %
10242	CAD	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-TOD	9,86	± 9.6 %
10243	CAD	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-TDD	9.46	± 9.6 %
10244	CAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TOD	10.06	±9.65
10245	CAG	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TOD	10.06	± 9.6 %
10246	CAG	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TOD	9.30	± 9.6 %
10247	CAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-TOD	9.91	1.9.61
10248	CAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-TOD	10.09	±9.61
10249	CAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-TDD	9.29	±9.63
10250	CAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-TDD	9.81	± 9.6 9
10251	CAF	LTE-TDD (SC-FDMA, 50% RB, 10 MHz; 64-QAM)	LTE-TDD	10.17	± 9.6.1
10252	CAF	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-TDD	9.24	± 9.6.3
10253	CAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz., 16-QAM)	LTE-TDD	9.90	±9.6 %
10254	CAB	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-TDD	10.14	±9.63
10255	CAB	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-TDD	9.20	± 9.6 %
10256	CAB	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.96	± 9.6 %
10257	CAD	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.08	± 9.6 5
10258	CAD	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	9.34	±9.65
10259	CAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	9.98	±9.63

Certificate No: EX3-7466_Jan21

Page 14 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless ounerwise stated une results snown in this test report reter only to the sample(s) tested and such as ample(s) are retained for 90 days only. We #shaft #sh prosecuted to the fullest extent of the law.



Rev: 01

Page: 20 of 29

0260	CAG	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	±9.6 %
0261	CAG	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	9.24	±9.6%
0262	CAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-TDD	9.83	±9.6 %
0262	CAG	LTE-TDD (SC-FDMA, 100% RB; 5 MHz, 64-QAM)	LTE-TDD	10.16	±9.6 %
0264	CAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-TDD	9.23	19.6 %
0265	CAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-TDD	9.92	± 9.6 %
0266	CAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-TOO	10.07	± 9.6 %
0267	CAF	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-TOO	9.30	±9.6 %
0268	CAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-TOO	10.06	± 9.6 %
0269	CAB	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-TDD	10.13	±9.6%
0270	CAB	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, OPSK)	LTE-TDD	9.58	± 9.6 %
0274	CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	WCDMA	4.87	± 9.6 %
0275	CAD	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	WCDMA	3.96	± 9.6 %
10277	CAD	PHS (QPSK)	PHS	11.81	± 9.6 %
10278	CAD	PHS (QPSK, BW 884MHz, Rolloff 0.5)	PHS	11.81	± 9.6 %
0279	CAG	PHS (QPSK, BW 884MHz, Rolloff 0.3ll)	PHS	12.18	± 9.6 %
0290	CAG	CDMA2000: RC1. SQ55. Full Rate	CDMA2000	3.91	± 9.6 %
10291	CAG	CDMA2000: RC3, SO55, Full Rate	CDMA2000	3.46	±9.6%
10292	CAG	CDMA2000; RC3, SO32, Full Rate	CDMA2000	3.39	±9.6 %
10293	CAG	CDMA2000, RC3, SO3, Full Rate	CDMA2000	3.50	±9.6 %
10295	CAG	CDMA2000, RC1, SQ3, 1/8th Rate 25 fr.	CDMA2000	12.49	± 9.6 %
10297	CAG	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-FOO	5.81	±9.6 %
10298	CAF	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FOO	5.72	±9.6 %
10299	CAF	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.39	±9.6%
10300	CAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	6.60	±9.6%
10301	CAC	IEEE 802.16e WIMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	WiMAX	12.03	±9.6%
10302	CAB	IEEE 802.16e WIMAX (29.18, 5ms, 10MHz, QPSK, PUSC, 3CTRL)	WIMAX	12.57	±9.6 %
10303	CAB	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	WIMAX	12.52	±9.6%
10304	CAA	IEEE 802.16e WIMAX (29.18, 5ms, 10MHz, 64QAM, PUSC)	WIMAX	11.86	±9.6%
10305	CAA	IEEE 802.16e WIMAX (31:15, 10ms, 10MHz, 64QAM, PUSC)	WiMAX	15.24	±9.6 %
10306	CAA	IEEE 802.16e WIMAX (29:18, 10ms, 10MHz, 64QAM, PUSC)	WiMAX	14.67	± 9.6 9
10307	AAB	IEEE 802.16e WIMAX (29:18, 10ms, 10MHz, QPSK, PUSC)	WMAX	14.49	± 9.6 %
1030B	AAB	IEEE 802.16e WIMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	WIMAX	14,46	±9.69
10309	AAB	IEEE 802 16e WIMAX (29:18, 10ms, 10MHz, 16QAM,AMC 2x3)	WiMAX	14.58	± 9.6 %
10310	AAB	IEEE 802.16e WIMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3	WMAX	14.57	± 9.6 %
10311	AAB	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-FDD	6.06	± 9.6 %
10313	AAD	I/DEN 1:3	IDEN	10.51	±9.69
10314	AAD	IDEN 1:6	IDEN	13.48	±9.65
10315	AAD	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc do)	WLAN	1.71	±9.63
10316	AAD	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc dc)	WLAN	8.36	±9.69
10317	AAA	IEEE 802.11a WIFI 5 GHz (OFDM, 6 Mbps, 96pc dc)	WLAN	8.36	±9.69
10352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	±9.69
10353	AAA	Pulse Waveform (200Hz, 20%)	Generic	6.99	±9.69
10354	AAA	Pulse Waveform (200Hz, 40%)	Generic	3.98	±9.69
10355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.22	±9.69
10356	AAA	Pulse Waveform (200Hz, 80%)	Generic	0.97	±9.69
10387	AAA	QPSK Waveform, 1 MHz	Generic	5.10	±9.69
10388	AAA	QPSK Waveform, 10 MHz	Generic	5.22	±9.69
10396	AAA	64-QAM Waveform, 100 kHz	Generic	6.27	±9.63
10399	AAA	64-QAM Waveform, 40 MHz	Generic	6.27	± 9.6 5
10400	AAD	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc dc)	WLAN	8.37	± 9.6 5
10401	AAA	IEEE 802.11ac W/FI (40MHz, 64-QAM, 99pc dc)	WLAN	8.60	± 9.6 9
10401		IEEE 802.11ac WiFi (80MHz, 64-QAM, 98pc dc)	WLAN	8.53	± 9.6 9
10402	AAA	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000	3.76	± 9.6 9
10403	AAB	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000	3.77	± 9.6 9
10404	PARB.	CDMA2000, RC3, SQ32, SCH0, Full Rate	CDMA2000	5.22	± 9.5 9

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless ounerwise stated une results snown in this test report reter only to the sample(s) tested and such as ample(s) are retained for 90 days only. We #shaft #sh prosecuted to the fullest extent of the law.

f (886-2) 2298-0488



Rev: 01

Page: 21 of 29

10410	AAA.	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, LL Sub=2,3,4,7,8,9)	LTE-TOD	7.82	±9.6%
0414	AAA	WLAN CCDF, 64-QAM, 40MHz	Generic	8.54	± 9.6 %
0415	AAA	IEEE 802.11b WIFI 2.4 GHz (DSSS, 1 Mbps, 99pc dc)	WLAN	1.54	+96%
0416	AAA	IEEE 802.11g WIFI 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc dc)	WLAN	8.23	± 9.6 %
0417	AAA	IEEE 802.11a/h WIFI 5 GHz (OFDM, 6 Mbps, 99pc do)	WLAN	8.23	±9.6%
0418	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc, Long)	WLAN	8.14	± 9.6 %
0419	AAA	IEEE 802 11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbds, 99pc, Short)	WLAN	8.19	± 9.6 %
0422	AAA	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	WLAN	8.32	± 9.6 %
0423	AAA	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	WLAN	8.47	± 9.6 %
0424	AAE	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	WLAN	8.40	±9.6 %
0425	AAE	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	WLAN	8.41	± 9.6 %
0426	AAE	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	WLAN	8.45	± 9.6 %
0427	AAB	IEEE 802.11n (HT Greenfield, 150 Mbps. 64-QAM)	WLAN.	8.41	2 9.6 %
0430	AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	LTE-FDD	8.28	± 9.6 %
0431	AAC	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	LTE-FDD	8.38	± 9.6 %
0432	AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	LTE-FOD	8.34	± 9.6 %
0433	AAC	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	LTE-FOO	8.34	±9.6%
0434	AAG	W-CDMA (BS Test Model 1, 64 DPCH)	WCDMA	8.60	±9.6 %
0435	AAA	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Sub)	LTE-TOD	7.82	± 9.6 %
0447	AAA	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.56	±9.6 %
044B	AAA	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clippin 44%)	LTE-FOD	7.53	±9.6%
0449	AAC	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Cliping 44%)	LTE-FDD	7.51	± 9.6 %
0450	AAA	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.48	±9.6%
0451	AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	WCDMA	7.59	±9.6%
0453	AAC	Validation (Square, 10ms, 1ms)	Test	10.00	± 9.6 %
0456	AAC	IEEE 802.11ac WIFI (160MHz, 64-QAM, 99pc dc)	WLAN	8.63	±9.6%
0457	AAC	UMTS-FDD (DC-HSDPA)	WCDMA	6.62	±9.6 %
10458	AAC	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	CDMA2000	8.55	±9.6 %
0459	AAC	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	CDMA2000	8.25	±9.6%
0460	AAC	UMTS-FDD (WCDMA, AMR)	WCDMA	2.39	±9.6%
10461	AAC	LTE-TDD (SC-FDMA, 1 RB. 1.4 MHz, QPSK, UL Sub)	LTE-TOD	7.82	±9.6 %
10462	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Sub)	LTE-TDD	8.30	±9.6 %
10463	AAD	LTE-TDD (SC-FDMA, 1 RB. 1,4 MHz, 64-QAM, UL Sub)	LTE-TDD	8.56	± 9.6 %
10464	AAD	LTE-TDD (SC-FDMA, 1 RB: 3 MHz, QPSK, UL Sub)	LTE-TDD	7.82	± 9.6 %
10465	AAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Sub)	LTE-TDD	8.32	196%
0468	AAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Sub)	LTE-TDO	8.57	± 9.6 %
0467	AAA	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Sub)	LTE-TDD	7.82	±9.6 %
0468	AAF	LTE-TDD (SC-FDMA, 1 RB: 5 MHz, 16-QAM, UL Sub)	LTE-TDD	8.32	± 9.6 %
10469	AAD	LTE-TDD (SC-FDMA, 1 RB; 5 MHz, 64-QAM, UL Sub)	LTE-TOD	8.56	± 9.6 %
0470	AAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Sub)	LTE-TOD	7.82	± 9.6 %
0471	AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Sub)	LTE-TOD	8.32	± 9.6 %
0472	AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Sub)	LTE-TOD	8.57	± 9.6 %
0473	AAA	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Sub)	LTE-TOO	7.82	± 9.6 %
10474	AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Sub)	LTE-TOO	8.32	± 9.6 %
0475	AAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Sub)	LTE-TOD	8.57	± 9.6.%
0477	AAC .	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Sub)	LTE-TOO	8.32	±9.6%
0478	AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Sub)	LTE-TOD	8.57	#9.6%
0479	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Sub)	LTE-TDD	7.74	±9.6 %
0480	AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Sub)	LTE-TOD	8.18	±9.6 %
10481	AAA	LTE-TDD (SC-FDMA, 50% RB, 1,4 MHz, 64-QAM, UL Sub)	LTE-TOO	8.45	± 9.6 %
0482	AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Sub)	LTE-TOD	7.71	± 9.6 %
0483	AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, Sub)	LTE-TDD	8.39	± 9.6 %
0484	AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Sub)	LTE-TOD	B.47	± 9.6 %
0485	AAB	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSIC UL Sub)	LTE-TOD	7.59	± 9.6 %
0486	AAB	LTE-TDD (SC-FDMA, 50% R8, 5 MHz, 16-QAM, UL Sub)	LTE-TOD	8.38	± 9.6 %
10487	AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 84-QAM, UL Sub)	LTE-TOD	8.60	± 9.6 %

Certificate No: EX3-7466 Jan21

Page 16 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be responsible to the full extent of the low. prosecuted to the fullest extent of the law.



Rev: 01

Page: 22 of 29

10488		LTE-TOD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Sub)	LTE-TDD	7.70	±9.6%
10489	AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Sub)	LTE-TDD	8.31	± 9.6 %
10490	AAC	LTE-TOD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Sub)	LTE-TOD	8.54	±9.6 %
10490	AAF	LTE-TOD (SC-FDMA, 50% RB, 15 MHz, OPSK, UL Sub)	LTE-TOD	7.74	± 9.6 %
10491	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Sub)	LTE-TOD	8.41	±9.6 %
10492	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Sub)	LTE-TOD	8.55	± 9.6 %
10493	AAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Sub)	LTE-TOD	7.74	± 9.6 %
10494	AAF	LTE-TOD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Sub)	LTE-TOD	8.37	± 9.6 %
10496	AAF	LTE-TOD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Sub)	LTE-TOD	8.54	± 9.6 %
10497	AAE	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Sub)	LTE-TOD	7.67	±9.6 %
10497	AAE	LTE-TDD (SC-FOMA, 100% RB, 1.4 MHz, 16-QAM, UL Sub)	LTE-TOD	8.40	±9.6%
10499	AAE	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Sub)	LTE-TOD	8.68	± 9.6 %
10500	AAC	LTE-TOD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Sub)	LTE-TDD	7,67	± 9.6 %
	AAF	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, GFSK, 0L Sub)	LTE-TOD	8.44	± 9.6 %
10501	AAF	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 10-QAM, UL Sub)	LTE-TOD	8.52	± 9.6 %
10503	AAB	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Sub)	LTE-TOD	7.72	±9.6 %
10503	AAB	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 0FSK, 0E 566)	LTE-TOD	8.31	±9.6 %
10504	AAB	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Sub)	LTE-TDD	8.54	± 9.6 %
10506	AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, OPSK, UL Sub)	LTE-TDD	7.74	± 9.6 %
10507	AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Sub)	LTE-TDD	8.36	± 9.6 %
10508	AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Sub)	LTE-TDD	8.55	± 9.6 %
10509	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Sub)	LTE-TDD	7.99	± 9.6 %
10510	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Sub)	LTE-TDD	8.49	±9.6%
10511	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Sub)	LTE-TOD	8.51	±9.6 %
10512	4	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Sub)	LTE-TOD	7.74	±9.6 %
10513	AAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Sub)	LTE-TOD	8.42	± 9.6 %
10514	AAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Sub)	LTE-TDD	8.45	±9.6 %
10515	AAE	IEEE 802 11b WiFi 2 4 GHz (DSSS, 2 Mbps, 99pc dc)	WLAN	1.58	± 9.6 %
10516	111	IEEE 802 11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc dc)	WLAN	1.57	± 9.6 %
10517	AAE	(EEE 802.11b WIFI 2.4 GHz (DSSS, 11 Mbps, 99pc.dc)	WLAN	1.58	±9.6 %
10518	AAF	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc dc)	WLAN	8.23	±9.6%
10519	AAF	IEEE 802.11a/h WIFI 5 GHz (OFDM, 12 Mbps, 98pc do)	WLAN	8.39	±9.6%
10520	AAB	IEEE B02.11a/h WIFI 6 GHz (OFDM, 18 Mbps, 99pc do)	WLAN	8.12	±9.6 %
10521	AAB	IEEE 802.11a/h WIFI 5 GHz (OFDM, 24 Mbps, 99pc do)	WLAN	7.97	±9.6%
10522		IEEE 802.11ah WIFI 5 GHz (OFDM, 24 Mbps, 99pc dc)	WLAN	8.45	±9.6 %
10523	AAB	IEEE 802 11a/n WiFi 5 GHz (OFDM, 48 Mbps, 99pc dc)	WLAN	8.08	± 9.6 %
10524	AAC	IEEE 802 11a/h WIFI 5 GHz (OFDM: 54 Mbps: 99pc do)	WIAN	8.27	± 9.6 %
10525	AAC	IEEE 802.11ac WIFI (20MHz, MCS0, 99pc dc)	WLAN	8.36	±9.6 %
10526	AAF	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc dc)	WLAN	8.42	± 9.6 %
10527	AAF	IEEE 802.11ac WIFI (20MHz, MCS2, 99pc dc)	WLAN	8.21	± 9.6 %
10528	AAF	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc dc)	WLAN	8.36	±9.6%
10529	AAF	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc dc)	WLAN	8.36	± 9.6 %
10521	AAF	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc dc)	WLAN	8.43	± 9.6 %
10532	AAF	IEEE 802.11ac WIFI (20MHz, MCS7, 99pc dc)	WLAN	8.29	± 9.6 %
10533	AAE	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc dc)	WLAN	8.38	± 9.6 %
10534	AAE	IEEE 802.11ac WiFI (40MHz, MCS0, 99pc dc)	WLAN	8.45	± 9.6 %
10535	AAE	IEEE 802 11ac WiFI (40MHz, MCS1, 99pc dc)	WLAN	8.45	±9.6 %
10536	AAF	IEEE 802 11ac WIFI (40MHz, MCS2, 99pc dc)	WLAN	8.32	± 9.6 %
10537	AAF	IEEE 802.11ac WiF) (40MHz, MCS3, 99pc dc)	WLAN	8.44	±9.6 %
10538	AAF	IEEE 802 11ac WIFI (40MHz, MCS4, 99pc dc)	WLAN	8.54	± 9.6 %
10540	AAA	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc dc)	WLAN	8.39	±9.6%
10541	AAA	IEEE 802.11ac WIFI (40MHz, MCS7, 99pc dc)	WLAN	8.46	±9.6%
10542	AAA	IEEE 802.11ac WIFI (40MHz, MCS8, 99pc dc)	WLAN	8.65	±9.6%
10543	AAC	(EEE 802.11ac WIF) (40MHz, MCS9, 99pc dc)	WEAN	8.65	± 9.6 %
10544	AAC	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc dc)	WEAN	8.47	± 9.6 %
10545	AAC	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc dc)	WLAN	8.55	± 9.6 %

Page 17 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless ounerwise stated une results snown in this test report reter only to the sample(s) tested and such as ample(s) are retained for 90 days only. We #shaft #sh prosecuted to the fullest extent of the law.

f (886-2) 2298-0488

台灣檢驗科技股份有限公司



Rev: 01

Page: 23 of 29

0546	T	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc dc)	WLAN	8.35	±9.6 %
0547	AAG	IEEE 802.11ac WIFI (80MHz, MCS2, 99pc dc)	WLAN	8.49	± 9.6 %
0548	AAC	IEEE 802.11ac WIFI (80MHz, MCS4, 99pc dc)	WLAN	8.37	± 9.6 %
	AAC	IEEE 802.11ac WIFI (80MHz, MCS4, 99pc dc)	WLAN	8.38	± 9.5 %
0550	AAC		WLAN	8.50	±9.5%
0551	AAC	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc do) IEEE 802.11ac WiFi (80MHz, MCS8, 99pc do)	WLAN	8.42	±9.5%
10552	AAC		WLAN	8.45	Se 416, 14
10553	AAC	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc dc)	WLAN	8.48	±9.6%
10554	AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc dc)	WLAN	8.46	±9.6%
10555	AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc dc) IEEE 802.11ac WiFi (160MHz, MCS2, 99pc dc)	WLAN	8.50	±9.6 %
10556	AAC		WLAN	8.52	
10557	AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc dc)	WLAN	8.61	±9,6%
10558	AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc dc)	15169 57	319.1	a a 10 10
10560	AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc dc)	WLAN	8.73	± 9.6 %
10561	AAC	IEEE 802.11ac WiFi (160MHz. MCS7, 99pc dc)	DOMEST C	8.56	± 9.6 %
10562	AAC	IEEE 802.11ac WiFI (160MHz, MCS8, 99pc dc)	WLAN	8.69	± 9.6 %
10563	AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc dc)	WLAN	8.77	± 9.6 %
10584	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc dc)	WLAN	8.25	±9.6 %
10565	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc dc)	WLAN	8.45	±9.6 %
10566	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc dc)	WLAN	8.13	± 9.6 %
10567	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc dc)	WLAN	8.00	± 9.6 %
10568	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc dc)	WLAN	8.37	±9.6 %
10569	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc dc)	WLAN	8.10	± 9.6 %
10570	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-QFDM, 54 Mbps, 99pc dc)	WLAN	8.30	± 9.6 %
10571	AAC	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc dc)	WLAN	1.99	± 9.6 %
10572	AAC	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc dc)	WLAN	1.99	± 9.6 %
10573	AAC	IEEE 802.11b WiFl 2.4 GHz (DSSS, 5.5 Mbps, 90pc dc)	WLAN	1.98	± 9.6 %
10574	AAC	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc dc)	WLAN	1.98	±9.6 %
10575	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc dc)	WLAN	8.59	±9.6 %
10576	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc dc)	WLAN	8.60	± 9.6 %
10577	AAC	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc dc)	WLAN	8.70	±9,6 %
10578	AAD	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc dc)	WLAN	8.49	±9.6 %
10579	AAD	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc dc)	WLAN	8,36	±9.6 %
10580	AAD	(EEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc dc)	WLAN	8.76	±9.6 %
10581	AAD	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc do)	WLAN	8,35	± 9.6 %
10582	AAD	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc dc)	WLAN	8.67	±9.6 %
10583	AAD	IEEE 802.11am WiFi 5 GHz (OFDM, 6 Mbps, 90pc dc)	WLAN	8.59	± 9.6 %
10564	AAD	IEEE 802.11a/h WIFI 5 GHz (OFDM, 9 Mbps, 90pc dc)	WLAN	8.60	± 9.fi.%
10585	AAD	IEEE 802.11a/h WIFI 5 GHz (OFDM, 12 Mbps, 90pc dc)	WLAN	8.70	±9.6%
10586	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc dc)	WLAN	8.49	±9.6 %
10587	AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc dc)	WLAN	8.36	±9.6 %
10588	AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc dc)	WLAN	8.76	± 9.6 %
10589	AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc dc)	WLAN	8.35	± 9.6 %
10590	AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc dc)	WLAN	8.67	± 9.6 %
10591	AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc dc)	WLAN	8.63	± 9.6 %
10592	AAA	IEEE 802,11n (HT Mixed, 20MHz, MCS1, 90pc dc)	WLAN	8.79	±9.6 %
10593	AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc dc)	WLAN	8.64	± 9.6 %
10594	AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc dc)	WLAN	8.74	± 9.6 %
10595	AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc dc)	WLAN	8,74	± 9.6 %
10596	AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc dc)	WLAN	8,71	19.6%
10597	AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc dc)	WLAN	8,72	±9.6 %
10598	AAA	(EEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc dc)	WLAN	8,50	±9.6 %
10599	AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc dc)	WLAN	8.79	±9.6%
10600	AAA	IEEE 802,11n (HT Mixed, 40MHz, MCS1, 90pc dc)	WLAN	88.8	± 9.6 %
10601	AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc dc)	WLAN	8.82	±9.6%
10602	AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc dc)	WLAN	8.94	±9.6%
10603	AAA	IEEE 802,11n (HT Mixed, 40MHz, MCS4, 90pc dc)	WLAN	9.03	±9.69

Certificate No: EX3-7466_Jan21

Page 18 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be responsible to the full extent of the low. prosecuted to the fullest extent of the law.

f (886-2) 2298-0488



Rev: 01

Page: 24 of 29

10604	AAA	IEEE 802,11n (HT Mixed, 40MHz, MCS5, 90pc dc)	WLAN	8.76	±9.6%
10605	AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc dc)	WLAN	8.97	± 9.6 %
10606	AAC	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc dc)	WLAN	8.82	± 9.6 %
10607	AAC	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc dc)	WLAN	8.64	± 9.6 %
10608	AAC	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc dc)	WLAN	8.77	± 9.6 %
0809	AAC	IEEE 802 11ac WiFi (20MHz, MCS2, 90pc dc)	WLAN	8.57	₹ 9.6 %
10610	AAC	IEEE 802 11ac WiFi (20MHz, MCS3, 90pc dc)	WLAN	8.78	±9.6 %
10611	AAC	IEEE 802 11ac WiFi (20MHz, MCS4, 90pc dc)	WLAN	8.70	±9.6%
10612	AAC	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc dc)	WLAN	8.77	± 9,6 %
10613	AAC	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc dc)	WLAN	8.94	±9.6%
10614	AAC	IEEE 802.11ac WiFI (20MHz, MCS7, 90pc dc)	WLAN	8.59	±9.6%
0615	AAC	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc dc)	WLAN	8.82	±9.6 %
10616	AAC	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc dc)	WLAN	8.82	± 9.6 %
10617	AAC	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc dc)	WLAN	B.81	±9.6%
10618	AAC	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc dc)	WLAN	8.58	±9.6%
10619	AAC	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc dc)	WLAN	8.86	± 9.6 %
10620	AAC	IEEE 802.11ac WIFI (40MHz, MCS4, 90pc dc)	WLAN	8.87	± 9.6 %
10621	AAC	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc dc)	WLAN	8.77	± 9.6 %
10622	AAC	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc dc)	WLAN	8.68	± 9.6 %
10623	AAC	IEEE 802.11ac WiFI (40MHz, MCS7, 90pc dc).	WLAN	8.82	± 9.6 %
10624	AAC	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc dc)	WLAN	8.96	± 9.6 %
10625	AAC	IEEE 802.11ac WiFI (40MHz. MCS9, 90pc dc)	WLAN	8.96	±9.6 %
10626	AAC	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc dc)	WLAN	8.83	±9.6 %
10627	AAC	IEEE B02.11ac WiFi (80MHz, MCS1, 90pc dc)	WLAN	8.88	±9.6 %
10628	AAC	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc dc)	WLAN	8.71	±9.6 %
10629	AAC	IEEE 802 11ac WIFI (80MHz, MCS3, 90pc dc)	WLAN	8.85	±9.6 %
10630	AAC	IEEE 802 11ac WiFi (80MHz, MCS4, 90pc dc)	WLAN	8.72	±9.6 %
10631	AAC	IEEE 802.11ac WIFI (80MHz, MCS5, 90pc dc)	WLAN	8.81	±9.6 %
10632	AAG	IEEE 802 11ac WIFI (80MHz, MCS6, 90pc dc)	WLAN	8.74	±9.6%
10633	AAC	IEEE 802.11ac WIFI (80MHz, MCS7, 90pc dc)	WLAN	8.83	±9.6%
10634	AAC	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc dc)	WLAN	8.80	±9.6%
10635	AAC	IEEE 802.11ac WIFI (80MHz, MCS9, 90pc dc)	WLAN	8.81	±9.6 %
10636	AAC	IEEE 802.11ac W/FI (160MHz, MCS0, 90pc dc)	WLAN	8.83	± 9.6 %
10637	AAC	IEEE 802.11ac WIFI (160MHz, MCS1, 90pc dc)	WLAN	8.79	± 9.6 %
10638	AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc dc)	WLAN	8.86	±9.6%
10639	AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc dc)	WLAN	8.85	±9.6%
10640	AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc dc)	WLAN	8.98	± 9.6 %
10641	AAC	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc dc)	WLAN	9.06	± 9.6 %
10842	AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc dc)	WLAN	9.06	± 9.6 %
10643	AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc dc)	WLAN	8.89	± 9.6 %
10644	AAC	(EEE 802.11ac WiFI (160MHz, MCS8, 90pc dc)	WLAN	9.05	± 9.6 %
10645	AAC	(EEE 802.11ac WiFi (160MHz, MCS9, 90pc dc)	WLAN	9.11	19.65
10646	AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Sub=2,7)	LTE-TDD	11.96	± 9.6 %
10647	AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Sub=2,7)	LTE-TDD	11.96	19.6%
10648	AAC	CDMA2000 (1x Advanced)	CDMA2000	3.45	±9.69
10652	AAC	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%).	LTE-TDD	6.91	±9,69
10653	AAC	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.42	±9.69
10654	AAC	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.96	±9.63
10655	AAC	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.21	±9.63
10658	AAC	Pulse Waveform (200Hz. 10%)	Test	10.00	± 9.6 5
10659	AAC	Pulse Waveform (200Hz, 20%)	Test	6.99	±9.65
10660	AAC	Pulse Waveform (200Hz. 40%)	Test	3,98	± 9.6 %
10661	AAC	Pulse Waveform (200Hz, 60%)	Test	2.22	± 9.6 9
10662	AAC	Pulse Wavelorm (200Hz, 80%)	Test	0.97	± 9.6 9
10670	AAC	Bluetpoth Low Energy	Bluetooth	2.19	± 9.6 9
10671	AAD	IEEE 802.11ax (20MHz, MCS0, 90pc dc)	WLAN	9.09	± 9.5 °

Certificate No: EX3-7466_Jan21

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless ounerwise stated une results snown in this test report reter only to the sample(s) tested and such as ample(s) are retained for 90 days only. We #shaft #sh prosecuted to the fullest extent of the law.



Rev: 01

Page: 25 of 29

			T 140 441	1 0.00	-000
10672	AAD	IEEE 802.11ax (20MHz, MGS1, 90pc dc)	WLAN	8.57	±9.6% ±9.6%
10673	AAD	IEEE 802.11ax (20MHz, MCS2, 90pc dc)		200	
10674	AAD	IEEE 802.11ax (20MHz, MCS3, 90pc dc)	WLAN	8.74	± 9.6 %
10675	AAD	IEEE 802.11ax (20MHz, MCS4, 90pc dc)	WLAN	8.90	± 9.6 %
10676	AAD	IEEE 802.11ax (20MHz, MCS5, 90pc dc)	WLAN	8.77	±9.6% ±9.6%
1D677	AAD	IEEE 802.11ax (20MHz, MCS6, 90pc dc)	35.00	741.0	25,710,70
10678	AAD	IEEE 802.11ax (20MHz, MCS7, 90pc dc)	WLAN	8.78	± 9.6 %
10679	AAD	IEEE 802.11ax (20MHz, MCS8, 90pc dc)	WLAN	8.89	±9.6%
10680	AAD	IEEE 802.11ax (20MHz, MCS9, 90pc dc)	WLAN	8.80	± 9.6 %
10681	AAG	IEEE 802.11ax (20MHz, MCS10, 90pc dc)	WLAN	8.62	±9.6 %
10682	AAF	IEEE 802.11ax (20MHz, MCS11, 90pt; dc)	WLAN	8.83	±9.6%
10683	AAA	IEEE 802.11ax (20MHz, MCS0, 99pc dc)	WLAN	8,42	± 9.6 %
10684	AAC	IEEE 802.11ax (20MHz, MCS1, 99pc dc)	WLAN	8.26	± 9.6 %
10685	AAC	IEEE 802.11ax (20MHz, MCS2, H9pc dc)	WLAN	8.33	±9.6 %
10686	AAC	IEEE 802.11ax (20MHz, MCS3, 99pc dc)	WLAN	8.28	± 9.6 %
10687	AAE	IEEE 802.11ax (20MHz, MCS4, 99pc dc)	WLAN	8.45	± 9.6 %
10688	AAE	IEEE 802.11ax (20MHz, MCS5, 99pc dc)	WLAN	8.29	± 9.6 %
10689	AAD	IEEE 802.11ax (20MHz, MCS6, 99pc dc)	WLAN	8.55	± 9.6 %
10690	AAE	IEEE 802,11ax (20MHz, MCS7, 99pc dc)	WLAN	8.29	± 9.6 %
10691	AAB	IEEE 802.11ax (20MHz, MCS8, 99pc dc)	WLAN	8.25	± 9.6 %
10692	AAA	IEEE 802.11ax (20MHz, MCS9, 99pc dc)	WLAN	8.29	±9.6 %
10693	AAA	TEEE 802.11ax (20MHz, MCS10, 99pc dc)	WLAN	8.25	± 9.6 %
10694	AAA	IEEE 802,11ax (20MHz, MCS11, 99pc dc)	WLAN	8.57	±9.6 %
10695	AAA	IEEE 802.11ax (40MHz, MCS0, 90pc dc)	WLAN	8.78	±9.6 %
10696	AAA	(EEE 802.11ax (40MHz, MCS1, 90pc dc)	WLAN	8.91	± 9.6 %
10897	AAA	(EEE 802,11ax (40MHz, MC\$2, 90pc dc)	WLAN	8.61	± 9.6 %
10698	AAA	IEEE 802.11ax (40MHz, MCS3, 90pc dc)	WLAN	8.89	±9.6%
10699	AAA	IEEE 802.11ax (40MHz, MCS4, 90pc dc)	WLAN	8,82	±9.6 %
10700	AAA	IEEE 802.11ax (40MHz, MCS5, 90pc dc)	WLAN	8.73	±9.6%
10701	AAA	IEEE 802.11ax (40MHz. MCS6, 90pc dc)	WLAN	8.86	±9.6 %
10702	AAA	IEEE 802.11ax (40MHz, MCS7, 90pc dc)	WLAN	8.70	±9.6 %
10703	AAA	IEEE 802.11ax (40MHz, MCS8, 90pc dc)	WLAN	8,82	±9.6 %
10704	AAA	IEEE 802.11ax (40MHz, MCS9, 90pc dc)	WLAN	8,56	±9.6 %
10705	AAA	IEEE 802.11ax (40MHz. MCS10, 90pc dc)	WLAN	8,69	±9.6 %
10706	AAC	IEEE 802.11ax (40MHz, MCS11, 90pc dc)	WLAN	8.66	± 9.6 %
10707	AAC	IEEE 802.11ax (40MHz, MCS0; 99pc dc)	WLAN	8.32	± 9.6 %
10708	AAC	IEEE 802.11ax (40MHz, MCS1, 99pc dc)	WLAN	8.55	± 9.6 %
10709	AAC	IEEE 802.11ax (40MHz, MCS2, 99pc dc)	WLAN	8.33	± 9.6 %
10710	AAC	IEEE 802.11ax (40MHz, MCS3, 99pc dc)	WLAN	8.29	± 9.6 %
10711	AAC	IEEE 802.11ax (40MHz, MCS4, 99pc dc)	WLAN	8.39	± 9.6 %
10712	AAC	IEEE 802.11ax (40MHz, MCS5, 99pc dc)	WLAN	8.67	±9.6 %
10713	AAC	IEEE 802.11ax (40MHz, MC56, 99pc dc)	WLAN	8.33	± 9.6 %
10714	AAC	IEEE 802.11ax (40MHz, MCS7, 99pc dc)	WLAN	8.26	± 9.6 %
10715	AAC	IEEE 802.11ax (40MHz, MCS8, 99pc dc)	WLAN	8.45	± 9.6 %
10716	AAC	IEEE 802.11ax (40MHz, MCS9, 99pc dc)	WLAN	8.30	±9.6 %
10717	AAC	IEEE 802.11ax (40MHz, MCS10, 99pc dc)	WLAN	8,48	± 9.6 %
10718	AAC	IEEE 802.11ax (40MHz, MCS11, 99pc do)	WLAN	8,24	± 9.6 %
10719	AAC	IEEE 802.11ax (80MHz, MCS0, 90pc dc)	WLAN	8.81	± 9.6 %
10720	AAC	(EEE 802 11ax (80MHz, MCS1, 90pc dc)	WLAN	8.87	±9,6%
10721	AAC	(EEE 802.11ax (80MHz, MCS2, 90pc dc)	WLAN	8.76	± 9.6 %
10722	AAC	(EEE 802.11ax (80MHz, MCS3, 90pc dc)	WLAN	8.55	± 9.6 %
10723	AAC	IEEE 802.11ax (80MHz, MCS4, 90pc dc)	WLAN	8.70	± 9.5 %
10724	AAC	IEEE 802.11ax (80MHz, MGS5, 90pc dc)	WLAN	8.90	±9.69
10725	AAC	IEEE 802.11ax (80MHz, MCS6, 90pc dc)	WLAN	8.74	±9.69
10726	AAC	IEEE 802.11ax (80MHz, MCS7, 90pc dc)	WLAN	8.72	±9.6.9
10727	AAC	IEEE 802.11ax (80MHz, MCS8, 90pc dc)	WLAN	8.66	±9.6 %

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

台灣檢驗科技股份有限公司



Rev: 01

Page: 26 of 29

0728	LAAR	IEEE 802.11ax (80MHz, MCS9, 90pc dc)	WLAN	8.65	± 9.6 %
0729	AAC	TEEE 802.11ax (80MHz. MCS10, 90pc do)	WLAN	8.64	± 9.6 %
0730	AAC	IEEE 802 11ax (80MHz, MCS11, 90pc dc)	WLAN	8.67	± 9.6 %
0731	AAC	IEEE 802 11ax (80MHz, MCS0, 99pc dc)	WLAN	8.42	± 9.6 %
0732	AAC	IEEE 802.11ax (80MHz, MCS1, 99pc do)	WLAN	8.46	± 9.6 %
10733	AAC	IEEE 802.11ax (80MHz, MCS2, 99pc dc)	WLAN	8.40	±9.6 %
10734	AAC	[EEE 802.11ax (80MHz, MCS3, 99pc dc)	WLAN	8.25	± 9.6 %
10735	AAC	IEEE 802.11ax (80MHz, MCS4, 99pc dc)	WLAN	8.33	± 9.6 %
10736	AAC	IEEE 802.11ax (80MHz, MCSS, 99pc dc)	WLAN	8.27	± 9.6 %
10737	AAC	IEEE 802.11ax (80MHz, MCS6, 99pc dc)	WLAN	8.36	±9.6 %
10738	AAC	(EEE 802.11ax (80MHz, MCS7, 99oc dc)	WLAN	8.42	±9.6%
10739	AAC	IEEE 802.11ax (80MHz, MCS8, 99pc dc)	WLAN	8.29	±9.6%
0740	AAC	(EEF 802.11ax (80MHz, MCS9, 99oc dc)	WLAN	8.48	±9.6%
10741	AAC	(EEE 802 11ax (80MHz, MCS10, 99pc dc)	WLAN	8.40	± 9.6 %
10742	AAG	IEEE 802 11ax (80MHz, MCS11, 99pc dc)	WLAN	8.43	± 9.6 %
10743	AAC	IEEE 802.11ax (160MHz, MCS0, 90pc dc)	WLAN	8.94	± 9.6 %
10744	AAC	IEEE 802.11ax (160MHz, MCS1, 90pc dc)	WLAN	9.16	± 9.6 %
10745	AAC	IEEE 802.11ax (160MHz, MCS2; 90pc dc)	WLAN	8.93	± 9.6 %
10746	AAC	IEEE 802.11ax (160MHz, MCS3, 90pc dc)	WLAN	9.11	± 9.6 %
10747	AAC	IEEE 802.11ax (160MHz, MCS4, 90pc dc)	WLAN	9.04	± 9.6 %
10748	MC	IEEE 802,11ax (160MHz, MCS5, 90pc dc)	WLAN	8.93	± 9.6 %
10749	AAC	IEEE 802.11ax (160MHz, MCS6, 90pc dc)	WLAN	8.90	± 9.6 %
10750	AAC	(EEE 802.11ax (160MHz, MCS7, 90pc dc)	WLAN	8.79	± 9.6 %
10751	AAC	IEEE 802.11ax (160MHz, MCS8, 90pc dc)	WLAN	8.82	± 9.6 %
10752	AAC	(EEE 802.11ax (160MHz, MCS9, 90pc dc)	WLAN	8.81	±9.6 %
10753	AAC	IEEE 802.11ax (160MHz, MCS10, 90pc dc)	WLAN	9.00	± 9.6 %
10754	AAC	(EEE 802.11ax (160MHz, MCS11, 90pc dc)	WLAN	8.94	±9.6 %
10755	AAC	IEEE 802.11ax (160MHz, MCS0, 99pc dq)	WLAN	8.64	±9.6%
10756	AAC	IEEE 802.11ax (160MHz, MCS1, 99pc dc)	WLAN	8.77	±9.6%
10757	AAC	IEEE 802.11ax (160MHz, MCS2, 99pc dc)	WLAN	8.77	±9.6%
10758	AAC	IEEE 802.11ax (160MHz, MCS3, 99pc dc)	WLAN	8.69	± 9.6 %
10759	AAC	IEEE 802.11ax (160MHz, MCS4, 99pc dc)	WLAN	8.58	± 9.6 %
10760	AAC	IEEE 802.11ax (160MHz, MC55, 99pc dc)	WLAN	8.49	± 9.6 %
10761	AAC	IEEE 802.11ax (160MHz, MCS6, 99pc do)	WLAN	8.58	± 9.6 %
10762	AAC	(EEE 802.11ax (160MHz, MCS7, 99pc dc)	WLAN	8.49	± 9.6 %
10763	AAC	IEEE 802.11ax (160MHz, MCS8, 99pc dc)	WLAN	8.53	± 9.6 %
10764	AAC	IEEE 802.11ax (160MHz, MCS9, 99pc dc)	WLAN	8.54	± 9.6 %
10765	AAC	IEEE 802.11ax (160MHz, MCS10, 99pc dc)	WLAN	8.54	±9.6 %
10766	AAC	IEEE 802.11ax (160MHz, MCS11, 99pc dc)	WLAN	8.51	± 9.6 %
10767	AAC	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	7.99	±9.6%
10768	AAC	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TOD	8.01	± 9.6 %
10769	AAC	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.01	± 9.6 %
10770	AAC	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	± 9.6 %
10771		5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	± 9.6 %
10772	AAC	5G NR (CP-OFDM: 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.23	± 9.6 %
10773	1111	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.03	±9.6%
10774	AAC	5G NR (CP-OFDM: 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6%
10775		5G NR (CP-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.63
10776	AAC	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	±9.6%
10777	AAC	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8,30	±9.63
10777	AAC	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 KHz)	5G NR FR1 TDD	8.34	±9.63
10778	AAC	5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.42	± 9.6 %
10779	AAC	5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 KHz) 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 KHz)	5G NR FR1 TDD	8.38	±9.63
10780	AAC	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 KHz) 5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 15 KHz)	5G NR FR1 TDD	8.38	±9.69
10781	AAC	5G NR (CP-OFDM: 50% RB: 40 MHz, QPSK: 15 KHz)	5G NR FR1 TDD	8.43	± 9.6 9
10782	AAC	5G NR (CP-OFDM, 50% RB, 50 MHz, QPSK, 15 KHz) 5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TOD	8.31	±9.6 9

Certificate No: EX3-7466_Jan21

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless ounerwise stated une results snown in this test report reter only to the sample(s) tested and such as ample(s) are retained for 90 days only. We #shaft #sh prosecuted to the fullest extent of the law.

f (886-2) 2298-0488



Rev: 01

Page: 27 of 29

0784	AAC	5G NR (CP-OFDM, 100% RB, 10 MHz, OPSK, 15 kHz)	5G NR FR1 TDD	8.29	± 9.6 %
0785	AAC	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.40	±9.6%
0786	AAC	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.35	± 9.6 %
0787	AAC	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 15 KHz)	5G NR FR1 TDD	8.44	±9.6%
0788	AAC	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 15 KHz)	5G NR FR1 TDD	8.39	±9.6 %
0789	AAC	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TOD	8.37	±9.6%
0790	AAC	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	± 9.6 %
0791	AAC	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.83	±9.6%
0792	AAC	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.92	±9.6 %
0793	AAC	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TOD	7.95	± 9.6 %
10794	AAC	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	± 9.6 %
10795	AAC	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.84	± 9.6 %
0796	AAC	5G NR (CP-OFDM, 1 RB, 30 MHz, OPSK, 30 kHz)	5G NR FR1 TDD	7.82	± 9.6 %
10797	AAC	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.01	± 9.6 %
0798	AAC	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	± 9.6 %
10799	AAC	5G NR (CP-DFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.93	± 9.6 %
10801	AAC	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	± 9.6 %
10802	AAC	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.87	± 9.6 %
10803	AAE	SG NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDO	7.93	± 9.6 %
10805	AAD	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDO	8.34	± 9.6 %
10806	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDO	8.37	± 9.6 %
10809	AAD	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	± 9.6 %
10810	AAD	5G NR (CP-OFDM: 50% RB, 40 MHz, QPSK: 30 kHz)	5G NR FR1 TDD	8.34	±9,6%
10812		5G NR (CP-OFDM, 50% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.6%
10817	AAD	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8:35	±9.6 %
10818	AAD	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6%
10619	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.33	±9.6 %
10820	AAD	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.30	±9.6%
10821	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TOD	8.41	± 9.6 %
10822	AAC	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TOD	8.41	± 9.6 %
10823	AAD	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.36	± 9.6 %
10824	MC	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.39	±9.6%
10825	AAD	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6 %
10827	AAD	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.42	± 9.6 %
10828	AAD	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.43	± 9.6 %
the service.	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.40	± 9.65
10829	AAD	5G NR (CP-OFDM, 188, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.63	±9.69
10831	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.73	±9.69
10831	AAD	5G NR (CP-OFDM, 1 RB, 10 MHz, CPSK, 60 kHz)	5G NR FR1 TDD	7.74	± 9.6 9
10832	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	± 9.6 9
10834	AAD	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.75	± 9.6 %
10835	AAD	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.69
13000	AAD	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TOD	7.66	±9.69
10836	AAE	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.68	±9.69
10839	AAD	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	± 9.6 %
10839	AAD	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.67	±9,63
10840	AAD	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.71	±9.63
	AAD	5G NR (CP-OFDM, 1 RB, 100 MRZ, GPSK, 60 KHZ)	5G NR FR1 TDD	8.49	±9,63
10843	AAD		5G NR FR1 TDD	8.34	±9.6 9
10844	AAD	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 60 kHz) 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	± 9.6 9
10846	AAD		5G NR FR1 TDD	8.34	± 9.6 9
10854	AAD	5G NR (CP-OFDM, 100% RB: 10 MHz, QPSK, 60 kHz)	5G NR FR1 TOD	8.36	± 9.6 °
10855	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD		
10856	AAD	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 60 kHz)		8.37	± 9.6 °
10857	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.35	± 9.6 °
10858	AAD	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 60 kHz) 5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.36	±9.6°

Certificate No: EX3-7466_Jan21

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless ounerwise stated une results snown in this test report reter only to the sample(s) tested and such as ample(s) are retained for 90 days only. We #shaft #sh prosecuted to the fullest extent of the law.

f (886-2) 2298-0488



Rev: 01

Page: 28 of 29

0880	LAAD	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	± 9.6 %
0861	AAD	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.40	± 9.6 %
0863	AAD	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 60 NHz)	5G NR FR1 TDD	8.41	± 9.6 %
10864	AAE	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	± 9.6 %
10865	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	± 9.6 %
10866	AAD	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	± 9.6 %
10868	AAD	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.89	± 9.6 %
10869	AAD	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	± 9.6 %
10870	AAD	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.86	± 9.6 %
10871	AAD	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	5.75	± 9.6 %
10872	AAD	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.52	±9.6%
10873	AAD	5G NR (DFT-s-DFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.6 %
10874	AAD	5G NR (DFT-s-DFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6 %
10875	AAD	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6%
10876	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.39	± 9.6 %
10877	AAD	5G NR (CP-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	7.95	± 9.6 %
10878	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.6 %
10879	AAD	5G NR (CP-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.12	±9.6 %
10880	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	B.38	± 9.6 %
10881	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	±9.6%
10882	AAD	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.96	± 9.6 %
10883	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.57	±9.6%
10884	AAD	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.53	±96%
10885	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±96%
10886	AAD	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6%
10887	AAD	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	± 9.6 %
10888	AAD	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.35	± 9.6 %
10889	AAD	5G NR (CP-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TOD	8.02	± 9.6 %
10890	AAD	5G NR (CP-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.40	± 9.6 %
10891	AAD	5G NR (CP-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.13	± 9.6 %
10892	AAD	5G NR (CP-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.65
10897	AAD	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.66	±9.65
10898	AAD	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, OPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.65
10899	AAD	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	± 9.6 %
10900	AAD	5G NR (DFT-s-OFDM, 1 RB. 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.65
10901	AAD	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.69
10902	AAD	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.69
10903	AAD	5G NR (DFT-6-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	± 9.6 9
10904	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	± 9.6 9
10905	AAD	5G NR (DFT-s-OFDM, 1 R8, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	± 9.6 9
10906	AAD	9G NR (DFT-s-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	± 9.6.9
10907	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, GFSR, 30 KHz)	5G NR FR1 TDD	5.78	±9.63
10908	AAD	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.93	± 9.6.9
10909	AAD	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDO	5.96	± 9.6.3
10910	AAD	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	± 9.6.3
10911	AAD	5G NR (DFT-s-OFDM: 50% RB, 25 MHz, QPSK: 30 kHz)	5G NR FR1 TDD	5.93	± 9.6 3
10912		5G NR (DFT-s-OFDM: 50% RB, 30 MHz, QPSK; 30 kHz)	5G NR FR1 TDD	5.84	± 9.6 %
10913	AAD	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	± 9.6 %
10913	AAD	5G NR (DFT-s-OFDM: 50% RB, 40 MHz, QFSK: 30 kHz)	5G NR FR1 TDD	5.85	19.63
10915	AAD	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	19.67
10916		5G NR (DFT-s-OFDM, 50% RB, 80 MHz, OPSK, 30 kHz)	5G NR FR1 TDD	5.87	19.67
10916	AAD	5G NR (DFT-s-OFDM, 50% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	19.6
10918	AAD	5G NR (DFT-s-OFDM, 100% RB, 110 MHz, QFSK, 30 kHz)	5G NR FR1 TDD	5.94	
10918	AAD	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, OPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.65
10919	AAD	6G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	-
109/20	AAD	6G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TOD	5.07	± 9.6 5

Certificate No: EX3-7466_Jan21

Page 23 of 24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless ounerwise stated une results snown in this test report reter only to the sample(s) tested and such as ample(s) are retained for 90 days only. We #shaft #sh prosecuted to the fullest extent of the law.

f (886-2) 2298-0488



Rev: 01

Page: 29 of 29

AAD AAD AAD AAD AAD AAD AAD AAD AAD AAD	5G NR (DFT-6-OFDM, 100% RB, 25 MHz, OPSK, 30 MHz) 5G NR (DFT-6-OFDM, 100% RB, 50 MHz, OPSK, 30 MHz) 5G NR (DFT-6-OFDM, 100% RB, 30 MHz, OPSK, 30 MHz) 5G NR (DFT-6-OFDM, 100% RB, 30 MHz, OPSK, 30 MHz) 5G NR (DFT-6-OFDM, 100% RB, 80 MHz, OPSK, 30 MHz) 5G NR (DFT-6-OFDM, 100% RB, 80 MHz, OPSK, 30 MHz) 5G NR (DFT-6-OFDM, 180, 50 MHz, OPSK, 30 MHz) 5G NR (DFT-6-OFDM, 180, 10 MHz, OPSK, 15 MHz) 5G NR (DFT-6-OFDM, 180, 10 MHz, OPSK, 15 MHz) 5G NR (DFT-6-OFDM, 180, 10 MHz, OPSK, 15 MHz)	5G NR FR1 TOD 5G NR FR1 FDD 5G NR FR1 FDD	5.84 5.84 5.95 5.84 5.94 5.52	±9.6 % ±9.6 % ±9.6 % ±9.6 % ±9.6 % ±9.6 %
AAD AAD AAD AAD AAD AAD AAD	SG NR (DFT-6-DFDM, 100% RB, 40 MHz, DPSK, 30 MHz) SG NR (DFT-6-DFDM, 100% RB, 50 MHz, DPSK, 30 MHz) SG NR (DFT-6-DFDM, 100% RB, 90 MHz, DPSK, 30 MHz) SG NR (DFT-6-DFDM, 100% RB, 90 MHz, DPSK, 30 MHz) SG NR (DFT-6-DFDM, 188, 50 MHz, DPSK, 30 MHz) SG NR (DFT-6-DFDM, 188, 50 MHz, DPSK, 15 MHz) SG NR (DFT-6-DFDM, 188, 50 MHz, DPSK, 15 MHz)	5G NR FR1 TDD 5G NR FR1 TDD 5G NR FR1 TDD 5G NR FR1 FDD	5.95 5.84 5.94 5.52	± 9.6 % ± 9.6 % ± 9.6 % ± 9.6 %
AAD AAD AAD AAD AAD AAD AAD	5G NR (DFT-a-OFDM, 100% RB, 50 MHz, OPSK, 30 kHz) 5G NR (DFT-a-OFDM, 100% RB, 80 MHz, OPSK, 30 kHz) 5G NR (DFT-a-OFDM, 100% RB, 80 MHz, OPSK, 30 kHz) 5G NR (DFT-a-OFDM, 1 RB, 5 MHz, OPSK, 15 kHz) 5G NR (DFT-a-OFDM, 1 RB, 5 MHz, OPSK, 15 kHz)	5G NR FR1 TDD 5G NR FR1 TDD 5G NR FR1 FDD	5.84 5.94 5.52	± 9.6 % ± 9.6 %
AAD AAD AAD AAD AAD	5G NR (DFT-6-OFDM, 100% RB, 60 MHz, OPSK, 30 kHz) 5G NR (DFT-6-OFDM, 100% RB, 60 MHz, OPSK, 30 kHz) 5G NR (DFT-6-OFDM, 1 RB, 5 MHz, OPSK, 15 kHz) 5G NR (DFT-6-OFDM, 1 RB, 10 MHz, OPSK, 15 kHz)	5G NR FR1 TDD 5G NR FR1 FDD	5.94	± 9.6 %
AAD AAD AAD AAD AAD	5G NR (DFT-s-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz) 5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz) 5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	
AAD AAD AAD	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz) 5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)			+9 B %
AAD AAD		5G NR FR1 FDD		
AAD -	SC NR /DET & DEDM 1 PR 15 MHz DPSK 15 kHz)		5.52	± 9.6 %
AAD		5G NR FR1 FDD	5.52	± 9.6 %
	5G NR (DFT-s-DFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	± 9.6 %
AAB	SG NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	± 9.6 %
AAA	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	± 9.6 %
AAA	5G NR (DFT-s-OFDM, 1 RB: 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	± 9.6 %
AAA				± 9.6 %
AAC				± 9.6 %
AAB		. 404 3 80 5 1 34 1 3 8 7		±9.6 %
AAB		0.00 (40) (40) (50)	0100	±9.6 %
AAB		7.4.1077.77.17.17.	91,474	±9,6%
AAB			410.4	±9.6%
AAB				±9.6%
AAB				±9.6 %
			4100	±9.6 % ±9.6 %
				±9.6 %
			20.00	± 9.6 %
				± 9.6 %
		The second second second		±9.6%
				±9.6 %
				± 9.6 %
			917.00	± 9.6 %
			7017070	± 9.6 %
				± 9.6 %
		5G NR FR1 FDD	8.23	± 9.6 %
		5G NR FR1 FDD	8.42	± 9.6 %
		5G NR FR1 FDD	8.14	±96%
	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.31	± 9.6 %
AAB	5G NR DL (CP-QFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.61	± 9.6 %
AAB	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.33	± 9.6 %
AAB	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.32	±9.6 %
AAB	5G NR DL (CP-QFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.36	±9.6 %
AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)		9.40	±9.6 %
AAB.	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)			±9.6 %
AAB	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)		9.29	± 9.6 %
AAB				±9.6 %
AAB				± 9.6 %
AAB				±9.6%
AAB	5G NR DL (CP-OFDM, TM 3.1, 100 MHz, 64-QAM, 30 KHz)	5G NR FR1 TOO	9.49	± 9.6.%
	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 KHz)	5G NR FR1 TDD	11.59	± 9.6 %
AAB	DO NA (CE-OFUM, 1 NB, 27 MHZ, QFSN, 12 KHZ)			
AAB	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz) 5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz) 5G NR (CP-OFDM, 100% RB, 100 MHz, 256-QAM, 30 kHz)	5G NR FR1 TDD 5G NR FR1 TDD	9.06	± 9.6 %
	AAA AAA AAB AAB AAB AAB AAB AAB AAB AAB	AAA. \$ 50 NR (DPT-4-OPDM, 1 RB, 50 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 5 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 15 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 15 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 15 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 50 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 15 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (DPT-4-OPDM, 100 W, RB, 20 MHz, 0 PSK, 15 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 8 MHz, 6 4-OAM, 15 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 8 MHz, 6 4-OAM, 15 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 8 MHz, 6 4-OAM, 30 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 18 MHz, 6 4-OAM, 30 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 18 MHz, 6 4-OAM, 30 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 18 MHz, 6 4-OAM, 18 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 18 MHz, 6 4-OAM, 18 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 18 MHz, 6 4-OAM, 30 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 18 MHz, 6 4-OAM, 30 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 18 MHz, 6 4-OAM, 30 kHz). AAB. \$ 50 NR (D (CP-OPDM, 11 3, 1, 18 MHz, 6 4-O	AAA 5 ONR (DPT-4-OPDM, 15R, 50 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 59% RR, 5 MMz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 59% RR, 5 MMz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 59% RR, 15 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 59% RR, 15 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 59% RR, 26 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 59% RR, 36 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 59% RR, 36 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 59% RR, 36 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 59% RR, 50 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 50 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 50 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 50 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 50 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 109% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 110% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 110% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 110% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 110% RR, 25 MHz, 0PSK, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-OPDM, 110% RR, 110 MHz, 64-OAM, 15 MHz) 50 NR FR1 FDD AAB 50 NR (DPT-4-O	AAA 5 ONR (DPT-4-OPEM, 15R, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.51 AAB 5 ONR (DPT-4-OPEM, 50% RB, 15M-20 (PSK, 15 kHz) 5 ONR FRI FDD 5.77 AAB 5 ONR (DPT-4-OPEM, 50% RB, 15M-20 (PSK, 15 kHz) 5 ONR FRI FDD 5.77 AAB 5 ONR (DPT-4-OPEM, 50% RB, 15 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.82 AAB 5 ONR (DPT-4-OPEM, 50% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.82 AAB 5 ONR (DPT-4-OPEM, 50% RB, 30 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 30 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 30 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 50% RB, 50 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.83 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.84 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.84 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.84 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.84 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.84 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.84 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.84 AAB 5 ONR (DPT-4-OPEM, 100% RB, 25 MHz, OPSK, 15 kHz) 5 ONR FRI FDD 5.8

- End of report -

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless ounerwise stated une results snown in this test report reter only to the sample(s) tested and such as ample(s) are retained for 90 days only. We #shaft #sh prosecuted to the fullest extent of the law.