Go to www.vtechphones.com to register your product for enhanced warranty support and the latest VTech

Quick start quide

VM923-2 Pan and Tilt

VM923

Video Baby Monitor

Adult setup is required.

CAUTION: Do not install the baby unit at a height Control 20 from Install and bady in an a hinging above 2 maters.

This product is that substitute for adult supervision of the report of the product is the parent of the parent of the responsibility. The product could class operating, and therefore you should not assume it will continue working, and therefore you should not assume it will continue working, and properly for any given period of time. Further, this is not a medical device and should not be used as such. This product is interinded to assist you in supervising your baby. Do not use this product near water. For example, do not use it next to a bath tub, wash bowl, kitchen sink, laundry tub or swimming pool, or in a wet basement

Follow all warnings and instructions marked on the product.

or shower. 6. CAUTION: Use only the battery provided. There may be a risk of explosion if a wrong type of battery is used for the original control of explosion if a wrong type of battery is used for the working of the properties and love and pressure all play in the control of the properties and the program of the parties of the properties of the control of battery into fife or a hor down, or rescharically quistings or criting or critical programs or critical programs and ordering the properties surrounding anytromment can result in an explosion or the basings of flammable liquid.

resident in an exposion of used battlery according to the model of used battlery according to the model of th

Zhuhai Great Power Energy Co., Ltd. Li-ion battery, 3.6V, 2600mAh, 9.36Wh; Model: ICR18650-2.6Ah-3.6V-1S1P

For pluggable equipment, the socket-outlet shall be installed near the equipment and shall be easily

accessible. Unplug this product from the wall outlief before cleaning. Do not use liquid or aerosol cleaners. Use a damp cloth for cleaning. Do not cut off the power adapters to replace them with other plug, as this causes a hazardous situation. Do not allow anything to rest on the power cords. Do not intall this product where the cords may be walked

IMPORTANT SAFETY INSTRUCTIONS wever push objects of any kind into this product through the slots because they may touch dangerous voltage points or create a short circuit. Never spill liquid

vollade points or craws a short forcial. Never shill see it is not considered to the control to time. ren should be supervised to ensure that they do lay with the product.

The product is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety. SAVE THESE INSTRUCTIONS

Use and store the product at a temperature between 32°F and 104°F.

Do not expose the product to extreme cold, heat or direct sunlight. Do not put the product close to a heating source.

or diset satisfielt. Do not put the product dose to a that starting should be expected to exceed whe at such as begind students or fise.


\*\*DATE AND MARRING—PROMISSION THAT STARTING AND THE STARTIN

personal computers, kitchen appliances and cordless telephones. Precautions for users of implanted cardiac pacemakers Cardiac pacemakers (applies only to digital cordless relatives of the cord of the cardiac pacemakers. devices; Wireless Technology Research, LLC (WTR), an independent research entity, led a multidisciplinary evaluation of the erence between portable wireless devices and inted cardiac pacemakers. Supported by the U.S. Food Drug Administration, WTR recommends to physicians

emaker. uld NOT place wireless devices directly over the emaker, such as in a breast pocket, when it is turned

ON.
WTR's evaluation did not identify any risk to bystanders with
narremakers from other persons using wireless devices. pacemakers from other persons using wireless devices. Electromagnetic fields (EMF) This VTech product complies with all standards regardin electromagnetic fields (EMF). If handled properly and according to the instructions in this user's manual, the


# WHAT'S IN THE BOX



# CONNECT THE BABY MONITOR

## MOTES

- The rechargeable battery in the parent unit is built-in Use only the power adapters supplied with this product.
- Make sure the baby monitor is not connected to a switch-controlled electric outlet
- make sale the day minimum is no contented to a switch-continued section. Content the power adapters in a vertical or floor mount position only. The adapters' prongs are n designed to hold the weight of baby monitor, so do not connect them to any ceiling, under-the-tion cabinet outlets. Otherwise, the adapters may not properly connect to the outlets.



# CONNECT THE BABY MONITOR (CONT'D)


Charge the parent unit battery When you have connected and turned on the parent unit, the battery will be charged automatically. **■Notes** 

BNOIS


Before using the baby monitor for the first time, charge the parent unit battery for 12 hours. When the parent unit battery is slight charged, the battery ison becomes sold to the the parent units butter in the parent units burned on. To shorten the charging time, turn the parent unit off which durging. The standby time varies depending on the senditivity level you set, your actual use and the age of the battery.

The battery icon indicates the battery status (see the following table). The screen displays In the battery has very little power and can only be used for a short time. The battery icon becomes
The battery is fully charged. To keep the battery charged, connect the unit to AC power when not in use solid .

# Power on or off the baby monitor



# POSITIONING THE BABY MONITOR



O CAUTION

○ CAUTION

The default volume of your parent unit
is level 3, and the maximum volume is
level 5. If you experience high-pitched screeching noise from your baby monitor while positioning:

Output

Description

Outpu

Make sure your baby unit and parent unit are more than 3 feet (1 meter) apart, OR Turn down the volume of your parent unit

Note owaves, cell phones and computers



Once you newer on both unit, your parent unit displays image from the baby unit, and the LINK LED light turns on.

light turns on.



01 00000000 01 000000 010 000 010 000

# Basic operation - Parent unit

### Use the menu Press MENU to enter the menu, or save a setting. You can use the parent unit for advanced settings or operations, such as to play or stop the baby unit's lullaby, or to adjust the baby

Parent unit; 3.6V, 3600mAh, 9.36Wh Li-lon battery Baby unit power adapter: Output: SV DC @ 1A Parent unit power adapter: Output: SV DC @ 1A

Crystal controlled PLL synthesizer

TECHNICAL SPECIFICATIONS

Turn off the screen

Press POWER/LCD OFF to switch off the


screen. You can still hear sound from the

maximum power allowed by FCC and IC. Actual operating range may vary according to environmental conditions at the time of use.

# Press ◀ or ▶ to scroll among the


unit's sound sensitivity

- selection
- and return to live view.



# Talk to your baby unit

Press and hold TALK and speak to your parent unit. Your voice is transmitted to the baby unit. Release **TALK** when done talking and hear your baby again



Transmit frequency

requency control

- Press ◀ or ▶ to choose ■■.
- selection.



# Adjust parent unit speaker volume


- 1. Press MENU when in idle mode
- Press ▲ or ▼ to select desired volume level, then press SELECT to confirm you



- 1. Press MENU when in idle mode Press ◀ or ▶ to choose □.
- Press ▲ or ▼ to choose press SELECT.
   Press ▲ or ▼ to choose (Zoom in) or
- (Zoom out), then press SELECT to confirm your selection.



# OVERVIEW - PARENT UNIT



- 3-level sound indicator light
- Arrow keys
- MENU/SELECT

- TALK/FXIT
- On when the parent unit is linked to the baby 8 Microphone Flashes when the link to the baby unit is lost. 9 Power jac Antenna
- Press and hold to talk to the baby unit. While in a submenu, 12 Speaker press to exit.
- 9 Power lack
  - 11 RESET Force reboot the parent unit.

# OVERVIEW - BABY UNIT



- Light sensor Camera
- Microphone POWER LED ligh ON/OFF switch
- Antenna Power jack 10 Slots for wall mountin
  - 11 PAIR/RESET key

## NEED HELP?

For operations and guides to help you use your video monitor and for the latest information and support, check out our onlin help topics and online FAQs.

Use your smartphone or mobile device to access our online help.

Go to https://help.vtechphones.com/v=023

Go to https://help.vtecnpinousscom/vm923-2; OR
Scan the OR code on the right, Launch the camera app or QR code scanner app
or your smarphone or tablet. Hold the device's camera up to the OR code and
frame it. Tap the notification to be redirected to the online help page.

If the OR code is not clearly displayed, adjust your camera's focus by moving
vour device closer or further away until ris clear.

You can also call our Customer Support at 1 (800) 595-9511 (in US) or 1 (800) 267-7377 (in Canada) for help



# ■ PARENT UNIT ICONS

| Connection status | Conn

Patrol mode Displays when the parent unit is in PATROL mode (For VM923-2 only).

Current view status
- Displays the baby unit number of the baby unit that is being viewed.

Zoom ø. Displays when the current image on the parent unit has zoomed in.

\$ Night vision Displays when the baby unit being viewed has activated the night vision feature. Talkback

 Displays when talking back to the baby units from parent unit. Lullaby
Displays when a lullaby is playing. Ø.

40. Displays when the parent unit speaker volume is set to zero. Displays when the parent unit is talking to the baby unit.

Real-time temperature Displays the real-time temperature detected by the baby unit in Fahrenheit (°F) or Celsius (°C) (e.g. 57°F or 14°C).

### Battery status

- → ② ② ② ③ 1 animates when the battery is charging.
   displays solid when the battery is fully charged.
   displays when the battery is low and needs charging.

# volume.

Main menu icons

Main Sub-menu

白沙

Zoom in and out of the video

Parent unit speaker volume

5600

 The parent unit display will dim to conserve energy after your chosen amount of time of inactivity.

Brightness Adjust the parent unit's LCD

60 • Turn on/off temperature alert

Set the parent unit to been



• Set the minimum/maximum



 Set temperature display in Fahrenheit (°F) or Celsius (°C)



Adjust the parent unit's speaker

Sound Detection

VX (Voice Activated Alert)

Sensitivity

### GO Sound-activated screen

Sound-activated screen

When it is on, and the baby
unit detects no sound, the
parent unit screen stays off
to save power. Once a sound
is detected, the parent unit
screen and speaker turns on
see and hear your baby. The
again after 50 seconds of no
sound detection.


NOTE

 When the parent unit screen is off and it receives alerts, for example, link lost between parent unit and baby unit, or battery is low, the parent unit screen and speaker will turn on for 10 seconds.





# PARENT UNIT ICONS (CONT'D)



mode, where the screen will cycle through display videos streamed from all the linked

haby unit cameras (For VM923-2

No Link to selected paired baby unit's camera

Camera

baby unit and the parent unit is lost.

The parent unit is

ing for baby units

or the link hetween the

## Parent Unit Indication Lights

 On when the parent unit is linked to the baby unit. Flashes when the link to the baby unit being viewed is

 On when the parent unit is connected to AC power, or the battery is charging. · Flashes when the paren unit battery is low and needs charging.

Off when the parent unit is disconnected from AC

# Sound sensitivity and sound activation

Adjust the sound sensitivity of the baby unit You can choose to hear sounds from the baby unit all the time or to hear sounds that exceed a certain level. You can use the

parent unit to adjust the microphone sensitivity of your baby unit. The higher the sensitivity level, the more sensitive the unit. The higher the sensitivity level, the more sensitive the baby unit is in detecting sounds that transmit to the parent unit The VOX sensitivity level is preset to the highest level.

**®** i ning 

	Highest	High	Medium	Low	Lowest •
DESCRIPTION	The parent unit speaker is constantly on, and you will hear all sounds (including background noises) from your baby's room.	The parent unit speaker turns on for soft babbling and louder sounds from your baby. It remains quiet when your baby sleeps soundly.	The parent unit speaker turns on for loud babbling and louder sounds from your baby. It remains quiet when your baby makes soft sounds.	The parent unit speaker turns on for crying and louder sounds from your baby. It remains quiet when your baby makes soft sounds.	The parent unit speaker turns on for loud crying or screeching sounds from your baby. It remains quiet when your baby makes soft sounds.

### Sound activated screen

When sound activation is on, the parent unit screen stays off to save power when the baby unit detects no sound. Once the baby unit detects sounds that are louder than the chosen sound ensitivity level, the parent unit screen turns on automatically. It will then turn off again after 50 seconds of no sound detection.







# DIM MODE

The dim mode is to help you save the parent unit power. Your parent unit display will dim automatically after 10 minutes of inactivity, in which there is neither key pressed nor alert received from the haby unit



MOTE

While the screen is dimmed, any keypress or alert message will trigger the screen to return to the preset brightness level. After 10 minutes of inactivity, it will resume to dim mode

# NIGHT VISION



The baby unit has infrared LEDs that allow you to see your baby clearly at night or in a dark room. When the baby t being viewed detects low light levels, the infrared LEDs are switched on automatically. The images from the baby unit are in black and white, and appears on the screen.

### ■ Notes It is normal to see a short white glare on


It is normal to see a short white glare on your parent unit screen as the baby unit is adapting to the dark environment. When the infrared LEDs are on, the images are in black and white. This is normal.

Depending on the surroundings and other interfering factors, like lighting, objects, colors and backgrounds, the display resolution may vary. Adjust the baby unit's angle or place the baby unit at a higher level to prevent glare and blurry display

# FOR VM923-2 ONLY

### Status check - Two baby units

If you are viewing baby unit | , the POWER LED light of baby unit | turns or As baby unit | | is not being viewed, its **POWER** LED light flashes.



## Change different views - Patrol

- 1. Press MENU when the parent unit is idle.
- 2 Proce of or byto choose
- Press ▼ or ▲ to choose then press SELECT to confirm your selection.



### Change different views - Single-cam

- 1. Press MENU when the parent unit is idle.
- 2. Press ◀or ▶ to choose .
- 3. Press ▼ or ▲ to choose between and ■, then press SELECT to confirm the camera unit you would like to view



# MOUNT THE BABY UNIT ON DRY WALL (OPTIONAL)

## **⊞Notes**

- Check for reception strength and camera angle before drilling the holes.
- The types of screws and anchors you the wall. You may need to purchase the screws and anchors separately to mount



angle before drilling the holes. Place the wall mount bracket on a wall and then use a pencil to mark two holes in parallel. 0



Drill two holes in the wall (7/23 inch drill bit If you drill the holes into a stud, go to step 3,

If you drill the holes into an object other than a stud, insert the wall anchors into the holes, Tap gently on the ends with a hammer until the wall anchors are flush with the wall.



screws with the holes in the wall as shown. Tighten the screw in the middle position is fixed. You can tighten the other screw in the top hole



Place the camera unit on the wall mount bracket, and then slide it forward until it locks into place. Connect the power supply not controlled by a wall switch



# Q FREQUENTLY ASKED QUESTIONS

Below are the questions most frequently asked about the baby monitor.

To lisconnect the power to the baby units and the parent unit.

2. Wait a few seconds before connecting power back to the baby units and the parent unit.

3. Turn on the baby units and the parent unit.

4. Wait for the parent unit to synchronize with the baby units. Allow up to one minute

Perhaps the baby unit is not connected to the power. Insert the appliance plug into the baby unit and put the adapter in a wall socket. Then, slide the OON/OFF switch to OON to switch on the baby unit and to establish connection with the parent unit.

Make sure the power is not controlled by a wall switch. You may have used the battery for a long time. See Warranty for repair/repla-

The screen is in black and white during night-time or in a dark room when the night vision feature is activated. This is normal. During night-time or in a dark room, the surroundings and other interfering factors, like lightings, objects, colors and backgrounds may affect the image quality on your parent unit screen. Adjust the baby unit's angle or place the baby unit at a higher level to prevent glare and blurry display. Why do I get glare or blurry display on my

baby at night? Why does the baby monitor produce a The parent unit and baby units may be too close to each other.

Move the parent unit away from the baby units until the noise stops; OR

Turn down the volume of your parent unit. high-pitched noise

The baby units may be out of range. Move the parent unit closer to the baby units (but not less than 3 feet).

The temperature of your baby's room may be too high or too low.

Why does the parent unit react too quickly to other sounds? The baby unit also picks up other sounds than those of your baby. Adjust the VOX sensitivity level to a lower level or lower the parent unit speaker volume.

The parent unit speaker volume may be too low. See **Adjust parent unit speaker volume** to increase the volume. You may have set a low VOX sensitivity level. See Adjust the sound sensitivity of the baby unit to set to a higher level.

The baby units may be out of range. Move the parent unit closer to the baby units (but not less than 3 feet).

If you power on only one baby unit, your parent unit may display  $\| \|_{L^2}$  and the LINK LED light will flash.

### THE RBRC SEAL

The RRRC Seal and 1 (800) 8 RATTERY® are registered trademarks of California Inc.

### FCC AND IC REGULATIONS

### ECC Part 15

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
 Consult the dealer or an experienced radior/IV technical for help.
 WARNING: Changes or modifications to this equipment not expressly approved by the party responsible for compliance could void the user's authority to expert the equipment.

This Class B digital apparatus complies with Canadian requirement: CAN ICES-3 (B)/NIMB-3(B)

### Industry Canada

erm "IC." before the certification/registration number only signifies that the Industry Canada technical specification product meets the applicable Innovation, Science and Economic Development Canada technical specifications

RF radiation exposure statement

### CALIFORNIA ENERGY COMMISSION BATTERY CHARGING TESTING MODE

This baby monitor meet the California Energy Commission (ECC) regulations for energy contumption. Your baby monitor is set up to comply with the energy-conserving standards right out of the lost. Follow the instructions to install and charge the battery. The CEC battery charging testing mode is activated while charging. Even if the parent unit is paired to baby units, the CEC battery charging testing mode is activated while it is powered off and charging.

### FOR CETL COMPLIANCE ONLY

Mesures de sécurité importantes La plaque signalétique appliquée est située au bas du socie de l'unité du bébé.

- ceux qui suivent : Observez toutes les instructions et mises en garde inscrites rur l'avescrall
- sur rappareii. L'installation par un adulte est requise. MISE FN GARDE: N'installez rass l'unité du héhé à une.
- State and SAMOLEY in United Type of time to be to de original Cop produit in enemplace pas la surveillance adulte de nourisson. La supérvisión du nourisson est la responsabilitá du parento cué also personne qui Coccupa de l'entire C. C. Compartino de la responsabilità viosa ne devirate pas présumer qu'il continuera de forticitome correctionent pendient une période de temps: clonele. De plus, in es l'agli par d'un inentument médical en ne deverait par publication de la compartino de la responsabilità supervisor viole beblica, produit en efective à vivas ai des supervisor viole beblica, produit en efective à vivas ai des supervisor viole beblica, produit en efective à vivas ai des participation de l'acceptant de l'acceptant de l'acceptant de produit de l'acceptant de l'acceptant de l'acceptant de produit de produit de l'acceptant de produit de produit de l'acceptant de produit de l'acceptant de produit de produit de l'acceptant de produit de l'acceptant de produit
- superviser votre bebb.

  N'ufflisor per cert appareil près de l'eau ni de toute autre source d'humidité, par exemple, près d'une balgnoire, cus el lessive, derré de cusses, dans un source s'on humide ni près d'une piscine, dans un soursoit humide ou une
- MISE EN GARDE: Utilise uniquement les piles fournies. Il oxiste un risque d'explosion d'un autre type de batterje coriste un risque d'explosion d'un autre type de batterje chi requirement regolares, afest les piles sudes s'aboli est ci requirement regolares, afest les piles sudes s'aboli en renseignements suivant le sceau du RBRC. N'utiliser que les d'acaptenteurs inclus avec co produit. N'utiliser que les d'acaptenteurs inclus avec co produit n'utiliser que les d'acaptenteurs inclus avec co produit n'utiliser que les voir securités en prés.

Adaptateur de l'unité du parent : Sorlie : SV DC 1A
VTech Telecommunications Ltd.
Modèle : VT0SEUS03100 Modelle : VTDSEUSOS100 Adaptateur de l'unité du bébé : Sortie : SV DC 1A VTech Telecommunications Ltd. Modèlle : VTDSEUSOS100

Modelle: VTDSEUMUSEU

Linion battery, 3.0V, 2600mAh, 9.36Wh;
Model: ICR18650-2.6Ah-3.6V-151P

Model: ICR18650-2.6Ah-3.6V-151P

- Model: ICR18650-2,6Ah-3,6V-1SIP Lorsqu'ils sont branchés dans une prise de courant, los adaptateurs secteur ont été conçué pour être orientés correctement, soit à la verticale ou au plancher. Les tro-nom pas été conçues pour supporter le potic du bloc d'alimentation et le maintenir en place si coluci est bran chair une prise au plationd, sous une table ou dans un
- producti, annu assurer una accessionité sécuritaire à la prise bibliancière ce produit de la prise de courant assent de procéder au nethroyage, Nullisce pas de nethyants en adrossic. Utilisce un chiffen humide pour le nethyants en adrossic de la condicire d'altres en Ne couper pas les condons d'altres en Ne couper pas les condons d'altres en Ne laisce au acun bojet reposers ni appuyer sur le cordon d'allres en la condicire de la condicire de pour la condicire de la condicire de pour la d'altres une de la condicire de pour la dissertation de la condicire de pour la dissertation de la condicire de pour la condicire de
- pietiner.

  Ne faltes fonctionner cet appareil qu'avec le type d'alimentation indiqué sur l'étiquerte. Si vous he con pas le type d'alimentation que vous possédez à votre domicile, consultez votre marchand ou votre compagilierale r'éléctririsé. Ne surchargez pas les prises de courant murales ni les rallonges électriques.
- an met saucurégoz plá ses printés de coulant muralés ni les passaucurégoz plá ses printés de coulant muralés ni les Ne places pas cel apparaile sur un charlot, muelle, répled, support de montage ni table chancelants.
  16. Let trous et ouvertures de boldine; studes 1 Parrière de Pour l'empécher de surchauffer, pale bloquez cous aucun proteote de couvertures et n'empécher par par un lis, davan préclace par s'adraition addicate de l'apparent en les places qu'un plus deve positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une source de positionnez par a proximité ni au-diseaux d'une par la compart de la compa

- des points de tension dangereux ou causer des courts-circuits qui peuvent dégénérer en incendies ou en risqu d'électrocution. Ne renversez lamais de liquide dans ce
- . réduire les risques d'électrocution, ne démontez appareil, mais apportez-le dans un centre de sen pas cer appareir, mais apponers-re dans un centre de servir autorisé. L'ouverture du boîtier ou le retrait de toutes pièce que confient cet appareir, à l'exception de l'accès autorisé à certaines portes du ouvertures, risque de vous exposer à des points de tension dangereux ou d'autres dangers. Un membratage incorrect peut par la suite présenter dès risque-
- d'électroculien. Vous devriez tester la réception chaque fois que vous mettre l'appareill en fonction. Examinez les composantes afin de vérifies si celles-ci ne sont pas endommagées. Il existe un très faible risque de perte de confidentialité avec certains appareils électroniques (suntres écoute-béb héléphones sens fils etc.). Pour l'éviter, s'assurer que le
- produit n'a jamais été utilisé avant l'achat, réinitialises de façon périodique, éteindre l'écoute-bébé quanc pas en cours d'utilisation pas en colars d'utilisation. Les enfants devraient être supervisés afin de vous assurer qu'ils ne jouent pas avec l'appareil. Le produit n'est pas conçu pour être utilisé par des personnes (incluant des enfants) aux capacités physiques, sensorielles ou mentales réduites ou qui manquent

## d'expérience et de connaissances, à moins qu'on leur ait donné suffisamment de supervision ou d'instructions relativement à l'utilisation de l'appareil par une personne ment à l'umanon de rapparer par di table de leur sécurité. CONSERVEZ CES INSTRUCTIONS

- Mises en garde

  1. Utilisez et entreposez le produit à une température entre
  0. C (32° F) et 40° C (304° F).
  2. Monages par est appareil à des froids ou des chalours.
- N'exposez pas cet appareil à des froids ou des chaleurs extrêmes, ainsi qu'à la lumière directe du soleil. Ne l'installez pas près d'une source de chauffage. Le bioc-piles ne doit pas être exposé à la chaleur excessive telle que la lumière du soleil ou au feu.
- salte que la lumière d'arceire de a se visibler d'accessive salte de la constitue de la constitue de la constitue de la constitue de la condition de la condition de la condition fact de la portide des enfants (si plus de 0,7 m). N'entiver pas Volumière de la condition fact de la portide des enfants (si plus de 0,7 m). N'entiver pas Volumière de la condition fact de la portide de la condition de

numenques sans til): L'organisme "Wireless Technology Research, LLC (WTR)", une firme de recherche indépendante, a mené une évaluation pluridisciplinaire des intérférences entre les téléphones sans plundiscipinaire des interterences entre les telephones sans fil portatifs et les stimulateurs cardiaques implantés dans l'organisme. Appuyée par l'Administration des aliments et drobues (FDM) des Ftats-Unis, la firme WTR recommande au

medecins: Avis aux détenteurs de stimulateurs cardiaques • Vous devriez maintenir les dispositifs sans fil à au moins six vous devinez maintenir les dispositifs sans fil à au moins six pouces du simulateur cardiaque, ils ne doivent PAS placer le téléphone sans fil directement sur le stimulateur cardiaque, tel que dans une poche de chemise, lorsque celui-c' est en marche. L'etude effectuée par l'organisme WRS n'a pas identifié de risque pour les défenteurs de simulateurs cardiaques causés les gens qui utilisent dispositifs sans fil à proximité de ceux-ci

### LIMITED WARRANTY

What does the limited warranty cover?

The manufacture of thir VIcher Podeck unwarent to the holder of a valid proof of purchase ("Consumer" or "you") that the Product and all accessories provided in the sales package ("Product") are fire from defects in material and vocinnarating, pursurant for the following terms and vocinnaria for the vocinnaria for Product purchased and used in the United States of America and Canada.

Crando.

What will Visch do if the Product is not free from defects in materials and workmanking during the limited warranty in the product is material and workmanking during the limited warranty broads. Visch's authorized service in presentative will repair or replace at Visch's option, and the product, we may replace the Product, and the Product of the Product, and the Product of the Prod

How long is the limited warranty period? How long is the immed warrany period. The limited warrany period of to the Product extends for ONE (I) YEAR from the date of purchase. If VEA frog is replaces a Malarially Defencie Product under the terms of respicace of the product of the product of the product for replaced or replacement Product for a period of either (a) 90 days from the date the repaired or replacement Product for a period of either (a) 100 days from the date the repaired or replacement Product is shipped to you or (b) the time remaining on the original one-years warranty, whichever is longer.

# What is not covered by this limited warranty?

- This limited warranty does not cover: Product that has been subjected to misuse, accident
- shipping or other physical damage, improper installation, abnormal operation or handling, neglect, inundation, fire, water or other liquid intrusion; or Product that has been damaged due to repair, alteration or modification by anyone other than an authorized service representative of VTech: or
- Product to the extent that the problem experienced is caused by signal conditions, network reliability, or cable or
- Product to the extent that the problem is caused by use with non-VTech accessories: or with non-VTech accessories; or

  5. Product whose warranty/quality stickers, product serial number plates or electronic serial numbers have been removed altered or rendered illenible; or
- Product purchased, used, serviced, or shipped for repair from outside the United States of America or Canada, or used for commercial or institutional purposes (including but not limited to Products used for rental purposes); or
- Product returned without a valid proof of purchase (see item 2 below); or Charges for installation or set up, adjustment of customer controls, and installation or repair of systems outside the

To obtain warranty service in the USA, please visit our website at www.vtechphones.com or call 1 (800) 595-9511. In Canada, go to www.vtechcanada.com or call 1 (800) 267-7377. NOTE: Before calling for service, please review the user's manual - a check of the Product's controls and features ma save you a service call.

save your a service can.

Except as provided by applicable law, you assume the risk
of loss or damage during transit and transportation and are
responsible for delivery or handling charges incurred in the
transport of the Product(s) to the service location. VTech will return repaired or replaced Product under this warranty. Transportation, delivery or handling charge warranty. Trainportation, delivery or handling charges are prepaid. Vieto- hassumen on risk for damage or loss of the Product in transit. If the Product failure is not covered by this limited warranty, or proof of purchase does not meet with the property of the product failure is not covered by further repair activity. You must pay for the cost of repair and return shipping costs for the repair of Products that are not covered by this limited warranty.

- What must you return with the Product to get warranty Return the entire original package and contents includ the Product to the VTech service location along with a description of the malfunction or difficulty; and
- Include a "valid proof of purchase" (sales receipt) identifying the Product purchased (Product model) and the date of purchase or receipt; and

Other limitations
This warranty is the complete and exclusive agreement obstiveen you and Viech. It supernedes all other written or concumunational residued to the Product. Viech provides of communications residued to the Product. Viech product of the product of the residue of the Viech responsibilities regarding the product. These are no other express varianties. No one is authorized to make modifications to this limited warranty and you should not they now any such modification. State (Providesine, State) (Provides Law Rights: This warranty gives you specific legal rights, and you may slot how define rights, which vary from state to state warranty green you may so the you define rights. When you from state to state warranty gives you specific regarding the product of the pr

you may also make office agree, we want to any process of the control of the cont

nay not apply to you Please retain your original sales receipt as proof of purchase.

# DISCLAIMER AND LIMITATION OF LIABILITY

VTech Communications, Inc. and its suppliers assume no responsibility for any damage or loss resulting from the use of this user's manual. VTech Communications, Inc. and its suppliers assume no responsibility for any loss or claims by third parties that may arise through the use of this product.

Company: VTech Communications, Inc.
Address: 9020 SW Washington Square Road - Ste 555 Tigard, OR 97223, United State:
Phone: 1 (800) 595-9511 in the U.S. or 1 (800) 267-7377 in Canada