

RF Exposure Evaluation

FCC ID: EOA-24HALOBTE13

The device is excluded from SAR evaluation and therefore deemed compliant with FCC RF exposure requirements as described below:

FCC KDB 447498 D01 v05r02

Section 4.3.1

“The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \left[\frac{1}{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz*
- Power and distance are rounded to the nearest mW and mm before calculation*
- The result is rounded to one decimal place for comparison*
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below*

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.”

The device has a maximum conducted output power of 0.722 mW (-1.41 dBm) at 2480.0 MHz. The antenna is a flexible circuit asymmetrical dipole with a peak gain of -7.0 dBi. The resulting effective radiated power is 0.144212 mW EIRP. The closest spacing of the antenna to the user's torso is < 5 cm. The table below shows the results of the calculation. The value of 0.045 is well below the exclusion threshold of 3.0, therefore the unit is excluded from SAR evaluation and deemed compliant with FCC RF exposure requirements.

EIRP (mW)	Test Separation (mm)	Transmit Frequency (GHz)	Exclusion Threshold	Specification
0.144212	5	2.480	0.045	≤ 3.0