

Report No.: TW2405137E

Applicant: Shenzhen Xinrui Weiye Electronics Co., Ltd.

Product: Wireless remote control

Model No.: XRT-45ask, XR45-2, XRJ15-2

Trademark: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.231

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.231 for the evaluation of electromagnetic

compatibility

Approved By

Terry Tang Manager

Dated: May 22, 2024


Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com



Report No: TW2405137E Page 2 of 34

Date: 2024-05-22



Special Statement:

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

CAB identifier: CN0033

Page 3 of 34

Report No: TW2405137E

Date: 2024-05-22



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	4
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards.	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test	10
6.1	Test Method and Test Procedure.	10
6.2	Configuration of the EUT	11
6.3	EUT Operation Condition.	11
6.4	Radiated Emission Limit	12
6.5	Test Result.	13
7.0	20dB Bandwidth Test	18
8.0	Deactivate Test	20
9.0	Duty Cycle	22
10.0	Antenna Requirement	27
11.0	FCC Label.	28
12.0	Photo of Testing	29

Report No: TW2405137E Page 4 of 34

Date: 2024-05-22



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: +86 755 83448688 Fax: +86 755 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 744189 For 3m Anechoic Chamber

1.2 Applicant Details

Applicant: Shenzhen Xinrui Weiye Electronics Co., Ltd.

Address: 301, Building B, No. 163, Huawang Road, Langkou Community, Dalang Street, Longhua

District, Shenzhen

1.3 Description of EUT

Product: Wireless remote control

Manufacturer: Shenzhen Xinrui Weiye Electronics Co., Ltd.

Address: 301, Building B, No. 163, Huawang Road, Langkou Community, Dalang

Street, Longhua District, Shenzhen

Trademark: N/A

Model Number: XRT-45ask

Additional Model Name XR45-2, XRJ15-2

Additional Trademark N/A

Rating: DC3.0V, 1pc CR2032 button battery

Operation Frequency: 433.92MHz

Modulation Type: OOK

Hardware Version: XR-J15-45V1.0

Software Version: v1.2

Serial No: 20230726001TX

Antenna Designation PCB Antenna with Gain 2.0dBi

1.4 Submitted Sample: 3 Samples

1.5 Test Duration

2024-05-14 to 2024-05-22

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: TW2405137E Page 5 of 34

Date: 2024-05-22



1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty =6.0dB

Occupied Channel Bandwidth Uncertainty = 5%

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

The sample tested by

Print Name: Andy Xing

Andy -xing

Page 6 of 34

Report No: TW2405137E

Date: 2024-05-22



2.0 Test Equipment					
Instrument Type Manufacturer Model		Serial No.	Date of Cal.	Due Date	
ESPI Test Receiver R&S ESPI 3		100379	2023-07-14	2024-07-13	
LISN	R&S	EZH3-Z5	100294	2023-07-14	2024-07-13
LISN	R&S	EZH3-Z5	100253	2023-07-14	2024-07-13
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2023-07-14	2024-07-13
Loop Antenna	EMCO	6507	00078608	2022-07-18	2025-07-17
Spectrum	R&S	FSIQ26	100292	2023-07-14	2024-07-13
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2022-07-18	2025-07-17
Horn Antenna	R&S	BBHA 9120D	9120D-631	2022-07-18	2024-07-17
Power meter	Anritsu	ML2487A	6K00003613	2023-07-14	2024-07-13
Power sensor	Anritsu	MA2491A	32263	2023-07-14	2024-07-13
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2022-07-18	2025-07-17
9*6*6 Anechoic			N/A	2022-07-26	2025-07-25
EMI Test Receiver	RS	ESVB	826156/011	2023-07-14	2024-07-13
EMI Test Receiver	RS	ESCS 30	834115/006	2023-07-14	2024-07-13
Spectrum	HP/Agilent	E4407B	MY50441392	2023-07-14	2024-07-13
Spectrum	RS	FSP	1164.4391.38	2023-07-14	2024-07-13
RF Cable	Zhengdi	ZT26-NJ-NJ-8M/FA	1	2023-07-14	2024-07-13
RF Cable	Zhengdi	7m	1	2023-07-14	2024-07-13
Pre-Amplifier	Schwarebeck	BBV9743	#218	2023-07-14	2024-07-13
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2023-07-14	2024-07-13
LISN	SCHAFFNER	NNB42	00012	2023-07-14	2024-07-13
ESPI Test Receiver	R&S	ESPI 3	100379	2023-07-14	2024-07-13
LISN	R&S	EZH3-Z5	100294	2023-07-14	2024-07-13

2.2 Automation Test Software

For Conducted Emission Test

Name	Version		
EZ-EMC	Ver.EMC-CON 3A1.1		

For Radiated Emissions

Name	Version	
EMI Test Software BL410-EV18.91	V18.905	
EMI Test Software BL410-EV18.806 High Frequency	V18.06	

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: TW2405137E Page 7 of 34

Date: 2024-05-22



3.0 Technical Details

3.1 Summary of test results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.203	Antenna	Pass	Compliant
	requirements		
FCC Part 15, Paragraph 15.207	Conducted	N/A	N/A
	Emission Test		
ECC Port 15 Pour oranh 15 200	General	Pass	Commliant
FCC Part 15, Paragraph 15.209	Requirement		Compliant
FGC Port 15 Ports and 15 221 (b)	Radiated	Pass	Committee
FCC Part 15, Paragraph 15.231 (b)	Emission Test		Compliant
FCC Part 15, Paragraph 15.231 (c)	20dB	Pass	Compliant
	Bandwidth		
	Testing		
FCC Part 15, Paragraph 15.231 (a1)	Deactivate	Pass	Compliant
	Testing		

3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.231, ANSI C63.4:2014 and ANSI C63.10:2013

4.0 EUT Modification

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES


Report No: TW2405137E

Date: 2024-05-22



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2014. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2014.

Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2014. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC ID	
Wireless remote	Shenzhen Xinrui Weiye Electronics	XRT-45ask, XR45-2,	2DCTA VD2100 1	
control	Co., Ltd.	XRJ15-2	2BCTA-YP3100-1	

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
N/A				

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: TW2405137E Page 9 of 34

Date: 2024-05-22



5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2014.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition
- 5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency	Limits (dB µ V)			
(MHz)	Quasi-peak Level	Average Level		
$0.15 \sim 0.50$	66.0~56.0*	56.0~46.0*		
$0.50 \sim 5.00$	56.0	46.0		
5.00 ~ 30.00	60.0	50.0		

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results N/A

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz. (The average detector is necessary when the Quasi-peak emission level beyond the average Limit.)

Note: EUT powered by CR2032 button battery, this test item not applicable.

Report No: TW2405137E Page 10 of 34

Date: 2024-05-22




6 Radiated Emission Test

6.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at TIMEWAY EMC Laboratory. This site is on file with the FCC laboratory division, Registration No.744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 5 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup

For radiated emissions from 9kHz to 30MHz




Page 11 of 34

Report No: TW2405137E


Date: 2024-05-22



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating ConditionSame as section 5.4 of this report.

Report No: TW2405137E Page 12 of 34

Date: 2024-05-22



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

A FCC Part 15 Subpart C Paragraph 15.231(a) Limit

Fundamental Frequency (MHz)	Field Strength of		Field Strength of Spurious		
	Fundamental		Emission		
	uV/m dBuV/m u		uV/m	dBuV/m	
40.66-40.70	2250	67.04	225	47.04	
70-130	1250	61.94	125	41.94	
130-174	1250-3750	61.94-71.48	125-375	41.94-51.48	
174-260	3750	71.48	375	51.48	
260-470	3750-12500	71.48-81.94	375-1250	51.48-61.94	
Above 470	12500	81.94	1250	61.94	

Note: 1. F

- 1. RF Field Strength $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.
- 4.Linear interpolations for frequency ranges 130-174MHz and 260-470MHz
- 5.the above field strength limits are specified at a distance of 3-meters and the tighter limits apply at the band edges
- 6. New batteries were installed in the equipment under test for radiated emission testing.
- 7. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Page 13 of 34

Report No: TW2405137E

Date: 2024-05-22



B. Frequencies in restricted band are compiled to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-5G, the final emission level got using PK detector. And Average = peak(dBuV/m) |duty| duty cycle factor | (dB)

6.5 Test result

A Fundamental and Harmonics Radiated emission data

Product: Wireless remote control		Test Mode: Keep		Transmitting	
Test Item:	Fundamental Radiated Emission Spurious Emission Data	and	Temperature:	25℃	
Test Voltage:	DC3.0V		Humidity:	56%	
Test Result:	Pass				
Frequency	Emission PK/AV]	Horizontal / Verti	ical	Limits PK/AV
(MHz)	(dBuV/m)				(dBuV/m)
433.92	83.65 (PK)/72.53(AV)		Н		100.8/80.8
433.92*	69.99 (PK)		V		100.8/80.8
867.84*	42.54 (PK)		Н		80.8/60.6
867.84*	38.73 (PK)		V		80.8/60.6
1301.76*	40.20 (PK)		Н		74/54
1301.76*	40.04 (PK)		V		74/54
1735.68*	34.30 (PK)		Н		80.8/60.8
1735.68			V		80.8/60.8
2169.6*	40.52 (PK)		Н		80.8/60.8
2169.6*	44.85 (PK)		V		80.8/60.8
2603.52		Н			80.8/60.8
2603.52*	43.57 (PK)		V		80.8/60.8
3037.44*	46.77 (PK)		Н		80.8/60.8
3037.44*	52.31 (PK)		V		80.8/60.8
3471.36			Н		80.8/60.8

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2024-05-22

ST	NG LAD
	1 12
EW	
THE REAL PROPERTY.	

3471.36	 V	80.8/60.8
3905.28	 Н	74/54
3905.28	 V	74/54
4339.2	 Н	74/54
4339.2	 V	74/54


Note: H=Horizontal, V=Vertical, AV=PK- | duty cycle factor | =PK -11.12

B. General Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Margin	Detector	Table	Height	Antenna	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(Degree)	(cm)		
1	50.365	23.71	-11.39	40.0	16.29	Peak	357.00	100	Horizontal	Pass
2	60.305	20.80	-12.99	40.0	19.20	Peak	236.00	100	Horizontal	Pass
3	100.792	20.77	-13.46	43.5	22.73	Peak	190.00	100	Horizontal	Pass
4	235.104	22.90	-12.52	46.0	23.10	Peak	10.00	100	Horizontal	Pass
5	433.904	83.65	-8.03	46.0	-37.65	Peak	331.00	100	Horizontal	N/A
6	867.628	42.54	-2.35	46.0	3.46	Peak	351.00	100	Horizontal	Pass

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

^{*} The measured PK emissions level less than the AV limit. So, no necessary to take down the AV emission level

Report No: TW2405137E Page 15 of 34

Date: 2024-05-22




B. General Radiated Emission Data

Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Margin	Detector	Table	Height	Antenna	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(Degree)	(cm)		
1	51.820	23.12	-11.42	40.0	16.88	Peak	263.00	100	Vertical	Pass
2	92.549	20.05	-14.57	43.5	23.45	Peak	346.00	100	Vertical	Pass
3	113.884	20.56	-14.22	43.5	22.94	Peak	201.00	100	Vertical	Pass
4	255.954	23.58	-12.02	46.0	22.42	Peak	277.00	100	Vertical	Pass
5	433.904	69.99	-8.03	46.0	-23.99	Peak	342.00	100	Vertical	N/A
6	867.628	38.73	-2.35	46.0	7.27	Peak	352.00	100	Vertical	Pass

Page 16 of 34


Date: 2024-05-22

Report No: TW2405137E



Test Plot above 1G

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	1302.424	40.20	-8.24	74.0	-33.80	Peak	359.00	100	Horizontal	Pass
2	1736.066	34.30	-7.28	74.0	-39.70	Peak	50.00	100	Horizontal	Pass
3	2169.708	40.52	-3.55	74.0	-33.48	Peak	102.00	100	Horizontal	Pass
4	2399.650	41.52	-3.57	74.0	-32.48	Peak	297.00	100	Horizontal	Pass
5	3036.991	46.77	-2.48	74.0	-27.23	Peak	117.00	100	Horizontal	Pass

Report No: TW2405137E Page 17 of 34

Date: 2024-05-22



Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	1301.175	40.04	-8.24	74.0	-33.96	Peak	275.00	100	Vertical	Pass
2	2169.708	44.85	-3.55	74.0	-29.15	Peak	42.00	100	Vertical	Pass
3	2603.349	43.57	-3.31	74.0	-30.43	Peak	280.00	100	Vertical	Pass
4	3036.991	52.31	-2.48	74.0	-21.69	Peak	1.00	100	Vertical	Pass

Report No: TW2405137E Page 18 of 34

Date: 2024-05-22



7.0 20dB Bandwidth Testing

7.1 Requirement

Per 15.231(c) and RSS-210 A1, The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

7.2 Test Procedure

With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna which was connected to the spectrum analyzer with the START and STOP frequencies set to the EUT's operation band.

7.3 Test Data

Frequency (MHz)	20dB Bandwidth Emission (kHz)	Limit (kHz)	Result
433.92	215	1084.8	Pass

Limit=Frequency x 0.25%=433.92x 0.25%=1084.8kHz


Refer to attached plots:

Report No: TW2405137E Page 19 of 34

Date: 2024-05-22



20dB Bandwidth



Date: 20.MAY.2024 17:25:17

Report No: TW2405137E Page 20 of 34

Date: 2024-05-22




8.0 Deactivate Test

8.1 Requirement

Per 15.231(a) (1)

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

8. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing The deactivation test was performed in the 3 meters chamber B test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.231(e) limits.

8.3 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.


Page 21 of 34

Report No: TW2405137E

Date: 2024-05-22



8.4 Test Data Refer to attached plots:



Date: 20.MAY.2024 17:35:27

8.5 Test result

Pass

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: TW2405137E Page 22 of 34

Date: 2024-05-22



9.0 Duty Cycle

9.1 Limit

No dedicated limit specified in the Rules

9.2 Test Procedure

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer=operating frequency.
- 4. Set the spectrum analyzer as RBW = VBW=1000kHz, Span=0Hz, Adjust Sweep=100ms.
- 5. Repeat above procedures until all frequency measured were complete.

9.3 Test Data

Base on the worst case

Tp = 43.768ms

Ton1= 0.321*19=6.099(ms)

Ton2 =1.012*6=6.072(ms)

Duty cycle=Ton/Tp=12.171/43.768=0.2781=27.81%


Duty cycle factor = $20 * \log (\text{duty cycle}) = 20 * \log (0.2781) = -11.12 \text{dB}$

Report No: TW2405137E Page 23 of 34

Date: 2024-05-22



Testing Plots:



Date: 20.MAY.2024 17:26:41

Report No: TW2405137E Page 24 of 34

Date: 2024-05-22



RF Att 20 dB RBW 100 kHz Ref Lvl VBW 100 kHz 10 dBm SWT 50 ms Unit dBm 10 SGL -10-20 1MAX 1MA -4C -50 -60 -70 -80 -90 Center 433.92 MHz 5 ms/

20.MAY.2024

Date:


17:28:17

Report No: TW2405137E Page 25 of 34

Date: 2024-05-22



 T_{on1}




Date: 20.MAY.2024 17:28:57

Report No: TW2405137E Page 26 of 34

Date: 2024-05-22



 T_{on2}



Date: 20.MAY.2024 17:29:18

Report No: TW2405137E Page 27 of 34

Date: 2024-05-22



10.0 Antenna Requirement

10.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

10.2 Antenna Connected constructions

The antenna is PCB Printed antenna which is built-in. The antenna gain is 2.0dBi. So it meets the requirement of 15.203

Report No: TW2405137E Page 28 of 34

Date: 2024-05-22




11.0 FCC ID Label

FCC ID: 2BCTA-YP3100-1

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Report No: TW2405137E

Date: 2024-05-22



12.0. Photo of testing

- 12.1 Conducted test View—N/A
- 12.2 Radiated emission test view



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 30 of 34

Report No: TW2405137E

Date: 2024-05-22



Photo for the EUT



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 31 of 34

Report No: TW2405137E

Date: 2024-05-22



Photo for the EUT



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Page 32 of 34

Report No: TW2405137E

Date: 2024-05-22



Photo for the EUT



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 33 of 34

Report No: TW2405137E

Date: 2024-05-22



Photo for the EUT



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Report No: TW2405137E

Date: 2024-05-22



Photo for the EUT



-End of the report-

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to