

MPE REPORT

FCC ID:2ARBY-CS100-AO

Date of issue: Sept. 09, 2020

Report number: MTi20082519-1E4

Sample description: Smart Air Fryer Toaster Oven

Model(s): CS100-AO

Applicant: Arovast corporation

Address: 1202 N Miller St, Suite A, Anaheim, CA 92806, USA

Date of test: Aug.28, 2020 to Sept. 09, 2020

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel:(86-755)88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>

E-mail: mti@51mti.com

Address: 101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.



TEST RESULT CERTIFICATION	
Applicant's name:	Arovast corporation
Address:	1202 N Miller St, Suite A, Anaheim, CA 92806, USA
Manufacture's name:	Foshan Genzhuo Electrical Appliances Co., Ltd
Address:	D-21-1 Promoter Region, Shunde Western Ecology Industrial Zone, Hailing Village. xingtian Town, Shunde District, Foshan, Guangdong
Product name:	Smart Air Fryer Toaster Oven
Trademark:	COSORI
Model and/or type reference:	CS100-AO
Serial model:	N/A
RF exposure procedures:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Danny Xu

Sept. 09, 2020

Reviewed by:

Leo Su

Sept. 09, 2020

Approved by:

Tom Xue

Sept. 09, 2020



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

BT:

Operation frequency: 2402-2480MHz

Modulation type: GFSK, $\pi/4$ -DQPSK, 8DPSK

BLE:

Operation frequency: 2402-2480MHz

Modulation type: GFSK

WIFI:

Operation Frequency: 802.11b/g/n HT20: 2412-2462MHz, 802.11n HT40: 2422-2452MHz,

Power density limited: 1mW/ cm²

Antenna Type: FPC Antenna;

antenna gain: 2.5dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(2.5/10)}=1.78$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	5.859	6±1	7	5.012	2.50	1.78	0.0018	1
2441		5.925	6±1	7	5.012	2.50	1.78	0.0018	1
2480		6.379	6±1	7	5.012	2.50	1.78	0.0018	1
2402	π/4-DQPSK	4.243	5±1	6	3.981	2.50	1.78	0.0014	1
2441		5.248	5±1	6	3.981	2.50	1.78	0.0014	1
2480		5.637	5±1	6	3.981	2.50	1.78	0.0014	1
2402	8DPSK	5.715	6±1	7	5.012	2.50	1.78	0.0018	1
2441		5.734	6±1	7	5.012	2.50	1.78	0.0018	1
2480		6.082	6±1	7	5.012	2.50	1.78	0.0018	1

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	0.013	1±1	2	1.585	2.5	1.78	0.0006	1
2440		1.004	1±1	2	1.585	2.5	1.78	0.0006	1
2480		1.322	1±1	2	1.585	2.5	1.78	0.0006	1



Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm2)	(mW/cm2)
		Ant A	Ant A	(dBm)	(mW)	Numeric		
2412	802.11b	16.2	17±1	18	63.095734	1.78	0.02234	1
2437		16.58	17±1	18	63.095734	1.78	0.02234	1
2462		17.02	17±1	18	63.095734	1.78	0.02234	1
2412	802.11g	15.24	16±1	17	50.118723	1.78	0.01775	1
2437		15.58	16±1	17	50.118723	1.78	0.01775	1
2462		16.04	16±1	17	50.118723	1.78	0.01775	1
2412	802.11n H20	15.04	15±1	16	39.810717	1.78	0.01410	1
2437		15.49	15±1	16	39.810717	1.78	0.01410	1
2462		15.91	15±1	16	39.810717	1.78	0.01410	1
2422	802.11n H40	15.51	16±1	17	50.118723	1.78	0.01775	1
2437		16.27	16±1	17	50.118723	1.78	0.01775	1
2452		16.06	16±1	17	50.118723	1.78	0.01775	1

Simultaneous transmit

BT+BLE+2.4GWiFi=0.0018+0.0006+0.02234=0.02474

Conclusion:

For the max result: $0.02474 \leq 1.0$ for 1g SAR, No SAR is required.

----END OF REPORT----