





GSM TEST REPORT No.24T04Z102259-010

for

TCL Communication Ltd.

GSM/UMTS/LTE/NR Mobile phone

Model Name: T702Z

FCC ID: 2ACCJH184

with

Hardware Version: 03

Software Version: 9L3N

Issued Date: 2024-11-25

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191. Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504 Email: <u>cttl_terminals@caict.ac.cn</u>, website: <u>www.caict.ac.cn</u>





REPORT HISTORY

Report Number	Revision	Description	Issue Date
24T04Z102259-010	Rev.0	1 st edition	2024-11-25

Note: the latest revision of the test report supersedes all previous version.





CONTENTS

1.	TEST LABORATORY	ł
1.1.	INTRODUCTION & ACCREDITATION	1
1.2.	TESTING LOCATION	1
1.3.	TESTING ENVIRONMENT	1
1.4	PROJECT DATA	1
1.5.	SIGNATURE	1
2.	CLIENT INFORMATION	5
2.1.	APPLICANT INFORMATION	5
2.2.	MANUFACTURER INFORMATION	5
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1.	ABOUT EUT	5
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
4.	REFERENCE DOCUMENTS	7
4.1.	DOCUMENTS SUPPLIED BY APPLICANT	7
4.2.	REFERENCE DOCUMENTS FOR TESTING	7
5.	SUMMARY OF TEST RESULT 8	3
6.	TEST EQUIPMENTS UTILIZED)
AN	NEX A: MEASUREMENT RESULTS1()
A	A.1 OUTPUT POWER)
A	1.2 Emission Limit	5
A	A.3 FREQUENCY STABILITY)
	A.4 OCCUPIED BANDWIDTH	
	A.5 Emission Bandwidth	
	A.6 BAND EDGE COMPLIANCE	
	A.7 CONDUCTED SPURIOUS EMISSION	
Α	A.8 PEAK-TO-AVERAGE POWER RATIO	3
AN	NEX B: ACCREDITATION CERTIFICATE)





1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under American Association for Laboratory Accreditation (A2LA) with lab code 7049.01, and is also an FCC accredited test laboratory (CN1349), and ISED accredited test laboratory (CAB identifier:CN0066). The detail accreditation scope can be found on A2LA website.

1.2. Testing Location

Location 1: CTTL (huayua	n North Roa	ad)			
Address:	No. 52, H	luayuan North	n Road, H	aidian Dist	rict, Beijing,
	P. R. Chir	na 100191			
Location 2: CTTL (BDA)					
Address:	No.18A,	Kangding	Street,	Beijing	Economic-Technology
	Development Area, Beijing, P. R. China 100176				


1.3. <u>Testing Environment</u>

Normal Temperature:	15-35 ℃
Relative Humidity:	20-75%

1.4. Project Data

Testing Start Date:	2024-09-29
Testing End Date:	2024-11-21

1.5. Signature



Wang Xing (Prepared this test report)



Zhou Yu (Reviewed this test report)

赵慧麟

Zhao Hui Lin (Approved this test report)





2. Client Information

2.1. Applicant Information

Company Name:	TCL Communication Ltd.
Address /Post:	5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
	Park, Shatin, NT, Hong Kong
Contact:	Ting Wang
Email:	ting.wang.hz@tcl.com
Telephone:	+86 752 2639091
Fax:	0086-755-36612000-81722

2.2. Manufacturer Information

Company Name:	TCL Communication Ltd.
Address /Post:	5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Address /Post.	Park, Shatin, NT, Hong Kong
Contact:	Ting Wang
Email:	ting.wang.hz@tcl.com
Telephone:	+86 752 2639091
Fax:	0086-755-36612000-81722





3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT	
Description	GSM/UMTS/LTE/NR Mobile phone
Model Name	T702Z
FCC ID	2ACCJH184
Antenna	Embedded
Output power	27.72 dBm maximum EIRP measured for PCS1900
Extreme Voltage	3.6VDC to 4.4VDC (nominal: 3.85VDC)
Extreme Temperature	-10°C to +55°C
Note: Ormen an enter l'at interes	and an end of the second state of the second s

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

3.2. Internal Identification of EUT used during the test					
EUT ID*	IMEI	HW Version	SW Version	Date of receipt	
UT21a	016605000205334/ 016605000205342	03	9L3N	2024-09-29	
	016605000206134/				
UT56a	016605000206142/	03	9L3N	2024-10-18	

UT56a was used for emission limit test and UT21a was used for other testing cases. *EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	
AE1	Battery	
AE2	Battery	
AE1		
Model		TLp049C9(CAC4900033C9)
Manufact	urer	FENGHUA
Capacita	nce	5010mAh
AE2		
Model		TLp049D7(CAC4900007C7)
Manufact	urer	VEKEN
Capacita	nce	5010mAh
	and to identify th	a taat aamala in tha lah internally

*AE ID: is used to identify the test sample in the lab internally.





4. <u>Reference Documents</u>

4.1. Documents supplied by applicant

EUT parameters are supplied by the customer, which are the bases of testing. CAICT is not responsible for the accuracy of customer supplied technical information that may affect the test results (for example, antenna gain and loss of customer supplied cable).

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-23
		Edition
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-23
		Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment	2016
	Measurement and Performance Standards	
ANSI C63.26	American National Standard for Compliance Testing of	2015
	Transmitters Used in Licensed Radio Services	
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF	v03r01
	LICENSED DIGITAL TRANSMITTERS	





5. Summary of Test Result

GSM850

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	22.913	Р
2	Emission Limit	2.1051/22.917	Р
3	Frequency Stability	2.1055	Р
4	Occupied Bandwidth	2.1049	Р
5	Emission Bandwidth	22.917	Р
6	Band Edge Compliance	22.917	Р
7	Conducted Spurious Emission	22.917	Р

PCS1900

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	24.232	Р
2	Emission Limit	2.1051/24.238	Р
3	Frequency Stability	2.1055	Р
4	Occupied Bandwidth	2.1049	Р
5	Emission Bandwidth	24.238	Р
6	Band Edge Compliance	24.238	Р
7	Conducted Spurious Emission	24.238	Р
8	Peak-to-Average Power Ratio	24.232	Р

Terms used in Verdict column

Р	Pass. The EUT complies with the essential requirements in the standard.		
NP	Not Performed. The test was not performed by CTTL.		
NA	Not Applicable. The test was not applicable.		
BR	Re-use test data from basic model report.		
F	Fail. The EUT does not comply with the essential requirements in the		
	standard.		

All the test results are based on normal power.

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.

Explanation of worst-case configuration

The worst-case scenario for all measurements is based on the conducted output power measurement investigation results unless otherwise stated. The test results shown in the following sections represent the worst case emission.





6. Test Equipments Utilized

Description	Туре	Series Number	Manufacture	Cal Due Date	Calibration Interval
Universal Radio Communication Tester	CMU200	108646	R&S	2024-12-28	1 year
Spectrum Analyzer	FSU	200030	R&S	2025-05-08	1 year
Climate chamber	SH-241	92004642	ESPEC	2025-10-29	1 year
Test Receiver	FSV30	101525	R&S	2025-01-18	1 year
EMI Antenna	VULB 9163	9163-482	Schwarzbeck	2025-05-19	1 year
EMI Antenna	9117	167	Schwarzbeck	2025-10-15	1 year
EMI Antenna	LB-7180-NF	J2030013000005	A-INFO	2025-05-16	1 year
EMI Antenna	3115	00146404	ETS-Lindgren	2025-05-16	1 year
Universal Radio Communication Tester	CMW500	143008	R&S	2025-01-18	1 year
Signal Generator	SMF100A	101295	R&S	2025-02-04	1 year

Note: Only the latest Cal Due Dates of equipments are listed above and all equipments are in valid calibration period when used.





Annex A: Measurement Results

A.1 Output Power

A.1.1 Summary

During the process of testing, the EUT was controlled via communication tester to ensure max power transmission and proper modulation.

In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.

The results below include a correction factor for cable loss that is provided by the customer.

A.1.2.2 Measurement Result GSM850

GSM(GMSK)

Frequency (MHz)	Power Step	Output power (dBm)	
824.2	5	30.81	
836.6	5	30.74	
848.8	5	30.85	

GPRS(GMSK,1Slot)

Frequency (MHz)	Power Step	Output power (dBm)	
824.2	3	30.65	
836.6	3	30.54	
848.8	3	31.01	

EGPRS(8PSK,1Slot)

Frequency (MHz)	Power Step	Output power (dBm)	
824.2	6	27.26	
836.6	6	27.38	
848.8	6	27.39	





PCS1900 GSM(GMSK)

Frequency (MHz)	Power Step	Output power (dBm)		
1850.2	0	29.29		
1880.0	0	29.32		
1909.8	0	29.24		

GPRS(GMSK,1Slot)

Frequency (MHz)	Power Step	Output power (dBm)	
1850.2	3	29.17	
1880.0	3	29.30	
1909.8	3	29.18	

EGPRS(8PSK,1Slot)

Frequency (MHz)	Power Step	Output power (dBm)	
1850.2	5	26.26	
1880.0	5	26.29	
1909.8	5	26.12	





A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts".

Part 24.232(c) specifies "Mobile and portable stations are limited to 2 watts EIRP".

A.1.3.2 Method of Measurement

According to KDB 412172 D01 and ANSI C63.26 the relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$ERP \text{ or } EIRP = P_T + G_T - L_C$

where;

• ERP or EIRP = effective radiated power or equivalent isotropically radiated

power(expressed in the same units as P_T.

- P_T = transmitter output power, in this report the unit express as dBm;
- G_T = gain of the transmitting antenna, in dBd(ERP) or dBi(EIRP);
- L_{c} = signal attenuation in the connecting cable between the transmitter and antenna, in

dB.

Alternatively, the EIRP can be determined from Equation above and then converted to ERP based on the maximum antenna gain relationship by applying the following equation:

ERP = EIRP - 2.15dB

Note: The antenna gain information was provided by the client. The laboratory is not responsible for identifying its authenticity during the test.





A.1.3.3 Limits and Measurement Results GSM 850-ERP

Modulation	Power Step	Burst Peak ERP (dBm)
GSM	5	
GPRS	3	≤38.45dBm (7W)
EGPRS	6	

GSM(GMSK)

Frequency (MHz)	Power Step	Output power (dBm)	ERP(dBm) (G _T – L _C =-3.8)
824.2	5	30.81	24.86
836.6	5	30.74	24.79
848.8	5	30.85	24.90

GPRS(GMSK,1Slot)

	Power	Output power (dBm)	ERP(dBm)
Frequency (MHz)	Step	Output power (dBm)	$(G_T - L_C = -3.8)$
824.2	3	30.65	24.70
836.6	3	30.54	24.59
848.8	3	31.01	25.06

EGPRS(8PSK,1Slot)

Frequency (MHz)	Power	Output nower (dPm)	ERP(dBm)
	Step	Output power (dBm)	(G _T − L _C =-3.8)
824.2	6	27.26	21.31
836.6	6	27.38	21.43
848.8	6	27.39	21.44





PCS1900-EIRP

Modulation	Power Step	Burst Peak EIRP (dBm)		
GSM	0			
GPRS	3	≤33dBm (2W)		
EGPRS	5			

PCS1900-EIRP

GSM(GMSK)

Frequency (MHz)	Power	Output power (dBm)	EIRP(dBm)
	Step		$(G_T - L_C = -1.6)$
1850.2	0	29.29	27.69
1880	0	29.32	27.72
1909.8	0	29.24	27.64

GPRS(GMSK,1Slot)

Frequency (MHz)	Power	Output nower (dPm)	EIRP(dBm)
	Step	Output power (dBm)	$(G_T - L_C = -1.6)$
1850.2	3	29.17	27.57
1880	3	29.30	27.70
1909.8	3	29.18	27.58

EGPRS(8PSK,1Slot)

Frequency (MHz)	Power Step	Output power (dBm)	EIRP(dBm) (G _T – L _C =-1.6)
1850.2	5	26.26	24.66
1880	5	26.29	24.69
1909.8	5	26.12	24.52

Note: Expanded measurement uncertainty is U = 0.578 dB, k = 2.





A.2 Emission Limit


A.2.1 Measurement Method

The measurement procedures in TIA-603E-2016 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

The procedure of radiated spurious emissions is as follows:


For measurements performed at frequencies less than or equal to 1 GHz, the EUT was placed on a 80cm-high non-conductive support; For measurements performed at frequencies above 1GHz, EUT was placed on a 1.5-meter-high non-conductive support. A measurement antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. In the initial test, the height of the measurement antenna was varied from 1 m to 4 m for the relative positioning that produces the maximum radiated signal level. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



- 1. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 2. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.







In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. The height of measurement antenna varied between 1 m to 4 m to maximize the received signal amplitude for each emission that was detected and measured in the initial test. A power (P_{Mea}) is applied to the input of the substitution antenna and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test was performed with the measurement antenna in both vertical and horizontal polarization.

- The Path loss (P_{pl}) between the Signal Source and the Substitution Antenna and the Substitution Antenna Gain (G_a) were recorded after test. A amplifier was connected in for the test. The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.
- 4. The measurement results are obtained as described below:

Power (EIRP) =
$$P_{Mea} - P_{pl} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

A.2.2 Measurement Limit

Part 22.917 and Part 24.238 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.





A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 band (824.2MHz, 836.6MHz, 848.8MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900, GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Re	sults Table
----------------------	-------------

Frequency	Channel	Frequency Range	Result
	Low	9kHz-10GHz	Pass
GSM 850MHz	Middle	9kHz-10GHz	Pass
	High	9kHz-10GHz	Pass
GSM 1900MHz	Low	9kHz-20GHz	Pass
	Middle	9kHz-20GHz	Pass
	High	9kHz-20GHz	Pass

A.2.5 Sweep Table

Subrange	RBW	VBW
9~150 kHz	0.2kHz	0.6kHz
150kHz~30MHz	9kHz	27kHz
30MHz~1 GHz	100KHz	300KHz
1~20 GHz	1 MHz	3 MHz





A.2.6 Measurement Result

GSM Mode Channel 128/824.2MHz

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.00	-50.38	2.61	9.48	2.15	-45.66	-13.00	32.66	V
2472.50	-42.51	4.33	10.36	2.15	-38.63	-13.00	25.63	V
4120.50	-53.18	4.75	10.06	2.15	-50.02	-13.00	37.02	Н
6589.50	-51.15	7.18	10.36	2.15	-50.12	-13.00	37.12	V
7407.00	-46.86	8.06	10.10	2.15	-46.97	-13.00	33.97	V
8244.00	-50.41	7.59	11.20	2.15	-48.95	-13.00	35.95	Н

GSM Mode Channel 190/836.6MHz

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.00	-47.51	2.78	9.45	2.15	-42.99	-13.00	29.99	V
2510.00	-41.11	4.42	10.30	2.15	-37.38	-13.00	24.38	V
4183.00	-51.17	4.07	10.07	2.15	-47.32	-13.00	34.32	Н
6699.00	-52.85	6.21	10.50	2.15	-50.71	-13.00	37.71	V
7536.50	-47.89	7.46	10.27	2.15	-47.23	-13.00	34.23	V
8364.00	-49.25	8.22	11.30	2.15	-48.32	-13.00	35.32	Н

GSM Mode Channel 251/848.8MHz

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.50	-51.05	2.91	9.41	2.15	-46.70	-13.00	33.70	V
2547.00	-43.98	4.60	10.30	2.15	-40.43	-13.00	27.43	V
4243.50	-50.76	4.95	10.27	2.15	-47.59	-13.00	34.59	Н
6785.00	-52.88	6.39	10.37	2.15	-51.05	-13.00	38.05	V
7650.50	-49.91	6.86	10.40	2.15	-48.52	-13.00	35.52	Н
8484.00	-48.08	8.88	11.30	2.15	-47.81	-13.00	34.81	Н





GSM Mode Channel 512/1850.2MHz

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.50	-53.54	3.47	10.40	-46.61	-13.00	33.61	Н
5550.50	-43.16	5.32	11.20	-37.28	-13.00	24.28	Н
7388.50	-50.04	8.16	10.05	-48.15	-13.00	35.15	Н
9263.50	-49.88	8.85	11.70	-47.03	-13.00	34.03	Н
11115.00	-48.68	9.83	12.62	-45.89	-13.00	32.89	V
12936.50	-47.07	12.45	12.76	-46.76	-13.00	33.76	V

GSM Mode Channel 661/1880.0MHz

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.00	-53.01	3.81	10.16	-46.66	-13.00	33.66	Н
5639.50	-42.96	5.61	11.38	-37.19	-13.00	24.19	Н
7527.00	-50.27	7.71	10.25	-47.73	-13.00	34.73	Н
9401.50	-49.10	9.09	11.51	-46.68	-13.00	33.68	Н
11294.50	-47.78	10.61	12.61	-45.78	-13.00	32.78	V
13156.00	-44.23	13.22	12.54	-44.91	-13.00	31.91	Н

GSM Mode Channel 810/1909.8MHz

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3820.00	-50.62	3.93	9.96	-44.59	-13.00	31.59	Н
5729.00	-43.71	5.89	11.34	-38.26	-13.00	25.26	Н
7626.50	-52.17	6.69	10.35	-48.51	-13.00	35.51	V
9560.00	-50.15	8.60	11.90	-46.85	-13.00	33.85	Н
11458.50	-46.25	12.36	12.54	-46.07	-13.00	33.07	V
13368.50	-41.87	13.09	12.43	-42.53	-13.00	29.53	V

Note: Peak EIRP (dBm) = PMea(dBm) - Path Loss(dB) + Antenna Gain(dBi)

Note: Expanded measurement uncertainty is U = 3.44 dB, k = 2.





A.3 Frequency Stability

A.3.1 Method of Measurement

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at +20 °C and rated supply voltage. Two reference points are established at the applicable unwanted emissions limit using a RBW equal to the RBW required by the unwanted emissions specification of the applicable regulatory standard. These reference points measured using the lowest and highest channel of operation shall be identified as F_L and F_H respectively.

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of CMU200.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -30°C.
- 3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of each band, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10[°]C increments from -30[°]C to +50[°]C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at +50°C.
- 7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10[°]C decrements from +50[°]C to -30[°]C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5° during the measurement procedure.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of the lower, higher and nominal voltage. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.





A.3.2 Measurement results GSM 850

Frequency Error vs Temperature

Temperature(℃)	Voltage(V)	F∟(MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
20		3.85 824.030	848.970		riequency enor(ppin)
50				3.42	0.0041
40				2.52	0.0030
30	3.85			2.32	0.0028
10				0.26	0.0003
0				-12.40	0.0148
-10				-19.63	0.0235
-20				-18.02	0.0215
-30				-16.85	0.0201

Frequency Error vs Voltage

	-				
Voltage(V)	Temperature(℃)	F∟(MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
3.6	20	924 020	949 070	0.84	0.0010
4.4	20	824.030	848.970	3.10	0.0037

PCS 1900

Frequency Error vs Temperature

Temperature(°C)	Voltage(V)	F∟(MHz)	F _H (MHz)	Offset(Hz)	
20					Frequency error(ppm)
50				-2.52	0.0013
40				-2.07	0.0011
30	3.85 1850.037	3.85 1850.037	1909.966	-1.03	0.0005
10				-3.88	0.0021
0				7.10	0.0038
-10				-4.52	0.0024
-20				-14.79	0.0079
-30				-13.43	0.0071
E					

Frequency Error vs Voltage

	U				
Voltage(V)	Temperature(℃)	F∟(MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
3.6	20	1950 027	1000.066	-3.68	0.0020
4.4	20	1850.037	1909.966	0.58	0.0003

Note: Expanded measurement uncertainty is U = 0.01 PPM, k = 2.





A.4 Occupied Bandwidth

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequency. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages. The measurement method is from ANSI C63.26:

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts.

b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set \ge 3 × RBW.

c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.

d) Set the detection mode to peak, and the trace mode to max-hold.






GSM 850 (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
824.2	249.20
836.6	244.39
848.8	244.39

GSM 850 (99%)


Channel 128-Occupied Bandwidth (99% BW)



Date: 8.0CT.2024 10:41:42








Channel 190-Occupied Bandwidth (99% BW)

Date: 8.0CT.2024 10:42:10





Date: 8.0CT.2024 10:42:37






GPRS 850 (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
824.2	245.19
836.6	244.39
848.8	242.79

GPRS 850 (99%)


Channel 128-Occupied Bandwidth (99% BW)



Date: 8.0CT.2024 11:20:48








Channel 190-Occupied Bandwidth (99% BW)

Date: 8.0CT.2024 11:21:15





Date: 8.0CT.2024 11:21:43






EGPRS 850-8PSK (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
824.2	263.62
836.6	258.01
848.8	258.01

EGPRS 850-8PSK (99%)


Channel 128-Occupied Bandwidth (99% BW)



Date: 8.0CT.2024 14:29:25








Channel 190-Occupied Bandwidth (99% BW)

Date: 8.0CT.2024 14:29:52





Date: 8.0CT.2024 14:30:20






PCS 1900 (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	243.59
1880.0	246.79
1909.8	247.60

PCS 1900 (99%)


Channel 512-Occupied Bandwidth (99% BW)



Date: 8.0CT.2024 14:37:55








Channel 661-Occupied Bandwidth (99% BW)

Date: 8.0CT.2024 14:38:23





Date: 8.0CT.2024 14:38:50






GPRS 1900 (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	245.19
1880.0	245.19
1909.8	248.40

GPRS 1900 (99%)


Channel 512-Occupied Bandwidth (99% BW)



Date: 8.0CT.2024 15:17:02









Channel 661-Occupied Bandwidth (99% BW)

Date: 8.0CT.2024 15:17:30





Date: 8.0CT.2024 15:17:57






EGPRS 1900-8PSK (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	247.60
1880.0	253.21
1909.8	251.60

EGPRS 1900-8PSK (99%)


Channel 512-Occupied Bandwidth (99% BW)



Date: 8.0CT.2024 15:37:26








Channel 661-Occupied Bandwidth (99% BW)

Date: 8.0CT.2024 15:37:54





Date: 8.0CT.2024 15:38:21

Note: Expanded measurement uncertainty is U = 3428 Hz, k = 2.





A.5 Emission Bandwidth

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

The measurement method is from ANSI C63.26:

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement.

b) The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\ge 3 \times RBW$.

c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.

d) The dynamic range of the spectrum analyzer at the selected RBW shall be more than 10 dB below the target "-X dB" requirement, i.e., if the requirement calls for measuring the -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference level.

e) Set spectrum analyzer detection mode to peak, and the trace mode to max hold.






GSM 850 (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)
824.2	317.31
836.6	314.90
848.8	319.71

GSM 850 (-26dBc)


Channel 128-Emission Bandwidth (-26dBc BW)




Date: 8.0CT.2024 10:43:55








Channel 190-Emission Bandwidth (-26dBc BW)







Date: 8.0CT.2024 10:44:50






GPRS 850 (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)	
824.2	313.30	
836.6	311.70	
848.8	315.71	

GPRS 850 (-26dBc)


Channel 128-Emission Bandwidth (-26dBc BW)




Date: 8.0CT.2024 11:22:56








Channel 190-Emission Bandwidth (-26dBc BW)







Date: 8.0CT.2024 11:23:51






EGPRS 850-8PSK (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)	
824.2	341.35	
836.6	325.32	
848.8	320.51	

EGPRS 850-8PSK (-26dBc)


Channel 128-Emission Bandwidth (-26dBc BW)



Date: 8.0CT.2024 14:31:33








Channel 190-Emission Bandwidth (-26dBc BW)

Date: 8.0CT.2024 14:32:01





Date: 8.0CT.2024 14:32:29






PCS 1900 (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)	
1850.2	312.50	
1880.0	314.10	
1909.8	313.30	

PCS 1900 (-26dBc)


Channel 512-Emission Bandwidth (-26dBc BW)




Date: 8.0CT.2024 14:40:08








Channel 661-Emission Bandwidth (-26dBc BW)







Date: 8.0CT.2024 14:41:03






GPRS 1900 (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)	
1850.2	313.30	
1880.0	314.10	
1909.8	310.10	

GPRS 1900 (-26dBc)


Channel 512-Emission Bandwidth (-26dBc BW)



Date: 8.0CT.2024 15:19:11








Channel 661-Emission Bandwidth (-26dBc BW)

Date: 8.0CT.2024 15:19:39





Date: 8.0CT.2024 15:20:07






EGPRS 1900-8PSK (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)	
1850.2	311.70	
1880.0	311.70	
1909.8	312.50	

EGPRS 1900-8PSK (-26dBc)


Channel 512-Emission Bandwidth (-26dBc BW)



Date: 8.0CT.2024 15:39:35








Channel 661-Emission Bandwidth (-26dBc BW)

Date: 8.0CT.2024 15:40:03





Date: 8.0CT.2024 15:40:31

Note: Expanded measurement uncertainty is U = 3428 Hz, k = 2.





A.6 Band Edge Compliance

A.6.1 Measurement limit

Part 22.917 and Part 24.238 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to KDB 971168, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

The spectrum analyzer readings are corrected by [10 log (1/duty cycle)] for the non-continuous transmitting scenario.





A.6.2 Measurement result GSM 850



Date: 8.0CT.2024 10:52:52




Date: 8.0CT.2024 11:07:50





GPRS 850 Channel 128



Date: 8.0CT.2024 11:31:48




Date: 8.0CT.2024 11:38:59






PCS 1900 Channel 512




Date: 8.0CT.2024 14:49:04



Date: 8.0CT.2024 15:04:03



Date: 8.0CT.2024 15:28:04



Date: 8.0CT.2024 15:35:14

Note: Expanded measurement uncertainty is U = 0.622 dB, k = 2.





A.7 Conducted Spurious Emission

A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. In measuring unwanted emissions, the spectrum shall be investigated from 30 MHz or the lowest radio frequency signal generated in the equipment, whichever is lower, without going below 9 kHz, up to at least the frequency given below:

(a) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

(b) If the equipment operates at or above 10 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.

- 2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
- 3. The number of sweep points of spectrum analyzer is greater than $2 \times \text{span/RBW}$.

A. 7.2 Measurement Limit

Part 22.917 and Part 24.238 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.






A.7.3 Measurement result

GSM850


Channel 128: 30MHz – 8.49GHz

NOTE: peak above the limit line is the carrier frequency.



Date: 8.0CT.2024 11:17:10

Channel 190: 30MHz – 8.49GHz NOTE: peak above the limit line is the carrier frequency.




Date: 8.OCT.2024 11:17:51





Channel 251: 30MHz – 8.49GMHz NOTE: peak above the limit line is the carrier frequency.




Date: 8.0CT.2024 11:18:32






PCS1900 Channel 512: 30MHz – 19.10GHz NOTE: peak above the limit line is the carrier frequency.



Date: 8.0CT.2024 15:13:24

Channel 661: 30MHz – 19.10GHz NOTE: peak above the limit line is the carrier frequency.




Date: 8.0CT.2024 15:14:05





Channel 810: 30MHz – 19.10GHz NOTE: peak above the limit line is the carrier frequency.



Date: 8.0CT.2024 15:14:46

Note: Expanded measurement uncertainty is U = 0.622 dB, k = 2.





A.8 Peak-to-Average Power Ratio

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB

a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;

- b) Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Record the maximum PAPR level associated with a probability of 0.1%.

Measurement results

Modulation	Frequency (MHz)	PAPR (dB)
PCS1900	1880.0	8.01
GPRS1900	1880.0	8.01
EGPRS1900(8PSK)	1880.0	10.61

Note: Expanded measurement uncertainty is U = 0.578 dB, k = 2.





Annex B: Accreditation Certificate



END OF REPORT