



FCC ID: 2AR5R-DL711BT  
Report No.: T181105N04-RP1-2

Page: 1 / 64  
Rev.: 01

## FCC 47 CFR PART 15 SUBPART C AND ANSI C63.10: 2013

### TEST REPORT

For

### PORTABLE TURNTABLE SYSTEM

Model: SPiN

Brand: RELOOP

Issued for

**Global Distribution GmbH & Co. KG**

**Schuckert Str. 28, 48153 Muenster, Germany**

Issued by

**Compliance Certification Services Inc.**

**Tainan Lab.**

**No.8, Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)**

**TEL: 886-6-580-2201**

**FAX: 886-6-580-2202**

**Issued Date: February 12, 2019**

---

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. Ltd. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.  
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部分複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T181105N04-RP1-2

Page: 2 / 64  
Rev.: 01

### **REVISION HISTORY**

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	January 29, 2019	Initial Issue	ALL	Sunny Chang
01	February 12, 2019	See the following note rev.01	ALL	Sunny Chang

**Note:**

Rev.00 Issue Date: January 29, 2019

Original Report

Rev.01 Issue Date: February 12, 2019

Add test 9k-30M Rad test data



## **TABLE OF CONTENTS**

<b>1. TEST REPORT CERTIFICATION</b>	<b>4</b>
<b>2. TEST RESULT SUMMARY</b>	<b>5</b>
<b>3. EUT DESCRIPTION</b>	<b>6</b>
3.1 DESCRIPTION OF EUT & POWER	6
<b>4. DESCRIPTION OF TEST MODES</b>	<b>7</b>
<b>5. TEST METHODOLOGY</b>	<b>8</b>
<b>6. FACILITIES AND ACCREDITATIONS</b>	<b>8</b>
6.1 FACILITIES	8
6.2 EQUIPMENT	8
6.3 LABORATORY ACCREDITATIONS LISTINGS	8
6.4 TABLE OF ACCREDITATIONS AND LISTINGS	9
6.5 MEASUREMENT EQUIPMENT USED	10
<b>7. CALIBRATION AND UNCERTAINTY</b>	<b>11</b>
7.1 MEASURING INSTRUMENT CALIBRATION	11
7.2 MEASUREMENT UNCERTAINTY	11
<b>8. SETUP OF EQUIPMENT UNDER TEST</b>	<b>12</b>
8.1 SETUP CONFIGURATION OF EUT	12
8.2 SUPPORT EQUIPMENT	13
8.3 EUT OPERATING CONDITION	15
<b>9. APPLICABLE LIMITS AND TEST RESULTS</b>	<b>16</b>
9.1 6DB BANDWIDTH	16
9.2 MAXIMUM PEAK OUTPUT POWER	20
9.3 DUTY CYCLE	26
9.4 POWER SPECTRAL DENSITY	30
9.5 CONDUCTED SPURIOUS EMISSION	34
9.6 RADIATED EMISSIONS	40
9.7 POWERLINE CONDUCTED EMISSIONS	55
<b>10. ANTENNA REQUIREMENT</b>	<b>59</b>
10.1 STANDARD APPLICABLE	59
10.2 ANTENNA CONNECTED CONSTRUCTION	59
<b>APPENDIX I SETUP PHOTOS</b>	<b>60</b>

## 1. TEST REPORT CERTIFICATION

**Applicant** : **Global Distribution GmbH & Co. KG**  
Schuckert Str. 28, 48153 Muenster, Germany

**Manufacturer** : **1)Ya Horng Electronic Co., Ltd.**  
No. 35, Shalun, Jon Sha Village, Anding Dist., Tainan City  
745, Taiwan (R.O.C.)  
**2)Atten Electronic(Dongguan) Co., Ltd**  
No. 34, Gaoyu South Road, Tangxia Town, Dongguan City,  
Guangdong Province, P. R. China.  
**3)Ya Horng ( Dongguan ) Electronic Co.,Ltd.**  
No. 34, Gaoyu South Road, Tangxia Town, Dongguan City,  
Guangdong Province, P. R. China.

**Equipment Under Test** : PORTABLE TURNTABLE SYSTEM


**Model Number** : SPiN

**Brand Name** : RELOOP

**Date of Test** : November 23, 2018 ~ November 26, 2018  
February 11, 2019


APPLICABLE STANDARD	
STANDARD	TEST RESULT
FCC Part 15 Subpart C AND ANSI C63.10: 2013	No non-compliance noted

Approved by:



**Jeter Wu**  
Assistant Manager

Reviewed by:



**Eric Huang**  
Section Manager



Report No.: T181105N04-RP1-2

Page: 5 / 64  
Rev.: 01

## 2. TEST RESULT SUMMARY

FCC Standard Section	Report Section	Test Item	Result
15.247(a)	9.1	6dB BANDWIDTH	Pass
15.247(b)	9.2	MAXIMUM PEAK OUTPUT POWER	Pass
-	9.3	DUTY CYCLE	-
15.247(e)	9.4	POWER SPECTRAL DENSITY	Pass
15.247(d)	9.5	CONDUCTED SPURIOUS EMISSION	Pass
15.205(a)	9.6	RADIATED EMISSIONS	Pass
15.207(a)	9.7	POWERLINE CONDUCTED EMISSIONS	Pass
15.203	10	ANTENNA REQUIREMENT	Pass



Report No.: T181105N04-RP1-2

Page: 6 / 64  
Rev.: 01

### 3. EUT DESCRIPTION

#### 3.1 DESCRIPTION OF EUT & POWER

Product Name	PORTABLE TURNTABLE SYSTEM
Model Number	SPiN
Brand Name	RELOOP
Received Date	September 18, 2018
Operating Frequency Range	GFSK Mode : 2402MHz~2480MHz
Transmit Power	GFSK Mode : 1.10dBm (1.2885mW)
Channel Spacing	GFSK Mode : 2 MHz
Channel Number	GFSK Mode : 40 Channels
Transmit Data Rate	GFSK Mode : 1 Mbps
Type of Modulation	GFSK
Antenna Type	Manufacturer: BRITO TECHNOLOGY Type: PCB ANTENNA Model: TN-180BT Gain: 1.45 dBi
Power Source	DC 5V (Powered by Adapter)
Firmware Version	ICYHFRP10
Software Version	N/A
Reported Date	December 07, 2018

- REMARK:** 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.  
2. This submittal(s) (test report) is intended for **FCC ID: 2AR5R-DL711BT** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.  
3. For more details, please refer to the user manual.

## 4. DESCRIPTION OF TEST MODES

The EUT is a PORTABLE TURNTABLE SYSTEM.

The RF Chip is manufactured by CSR

The antenna peak gain 1.45 dBi (highest gain) were chosen for full testing.

### GFSK mode

The EUT had been tested under operating condition.

There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2402
Middle	2442
High	2480

GFSK mode: 1Mbps long data rates (worst case) were chosen for full testing.

## 5. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10 and FCC CFR 47 15.207, 15.209 and 15.247 and KdB 558074.

## 6. FACILITIES AND ACCREDITATIONS

### 6.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.8, Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.7:1992, ANSI C63.10: 2013 and CISPR Publication 22.

### 6.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 6.3 LABORATORY ACCREDITATIONS LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by Taiwan Accreditation Foundation for the specific scope of accreditation under Lab Code: 1109 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by TAF or any agency of the Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: TW1109).





Report No.: T181105N04-RP1-2

Page: 9 / 64  
Rev.: 01

## 6.4 TABLE OF ACCREDITATIONS AND LISTINGS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

<b>Taiwan</b>	TAF
---------------	-----

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

<b>Canada</b>	Industry Canada
<b>Germany</b>	TUV NORD
<b>Taiwan</b>	BSMI
<b>USA</b>	FCC
<b>Japan</b>	VCCI

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

## 6.5 MEASUREMENT EQUIPMENT USED

### For §9.7

Chamber 966 Room (Radiation Test)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Active Loop Antenna	ETS-LINDREN	6502	8905-2356	07/19/2019
Amplifier	HP	8447F	2443A01671	01/21/2019
Bi-Log Antenna	Sunol	JB1	A070506-2	02/08/2019
Cable	RosnoI+Suhner	SUCOFLEX 104PEA	SN25737 /4PEA	01/26/2019
Double Ridged Guide Horn Antenna	ETS-LINDGREN	3116	00078900	03/19/2019
EMI Test Receiver	R&S	ESCI	100960	10/30/2019
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/04/2019
Hi-Pass Filter	MICRO-TRONICS	BRM50702-01	018	01/21/2019
Horn Antenna	Com-Power	AH-118	071032	04/18/2019
Pre-Amplifier	EMCI	EMC012645	980098	01/21/2019

### For §9.1~9.6

Chamber 966 Room (Conductor Test)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/04/2019
Power Meter	Anritsu	ML2487A	6K00003888	05/01/2019
Power Sensor	Anritsu	MA2491A	033265	05/01/2019
SMA Cable + 10dB Attenuator	CCS	SMA + 10dB Att	O6	01/21/2019

### For §9.8

Conducted Emission room #1				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
BNC Coaxial Cable	CCS	BNC50	11	01/23/2019
EMI Test Receiver	R&S	ESCS 30	100348	01/30/2019
LISN	SCHWARZBECK	NNLK8130	8130124	11/30/2018
LISN	FCC	FCC-LISN-50-32-2	08009	05/23/2019
Pulse Limiter	R&S	ESH3-Z2	100116	01/23/2019
Test S/W	e-3 (5.04211j)			

## 7. CALIBRATION AND UNCERTAINTY

### 7.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 7.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz Test Site : OATS-6	$\pm 3.21\text{dB}$
Radiated Emission, 200 to 1000 MHz Test Site : OATS-6	$\pm 3.09\text{dB}$
Radiated Emission, 1 to 8 GHz	$\pm 2.65\text{dB}$
Radiated Emission, 8 to 18 GHz	$\pm 2.66\text{dB}$
Radiated Emission, 18 to 26.5 GHz	$\pm 2.65\text{dB}$
Radiated Emission, 26 to 40 GHz	$\pm 3.03\text{dB}$
Power Line Conducted Emission	$\pm 1.91\text{dB}$
Band Width	136.49kHz
Peak Output Power MU	$\pm 1.34\text{dB}$
Band Edge MU	$\pm 0.30\text{dBuV}$
Channel Separation MU	361.69Hz
Duty Cycle MU	0.064ms
Frequency Stability MU	0.223kHz


This measurement uncertainty is confidence of approximately 95%,  $k=2$

## 8. SETUP OF EQUIPMENT UNDER TEST


### 8.1 SETUP CONFIGURATION OF EUT

#### EMI

##### 【Bluetooth+Table+AUX+REC】



#### RF



## 8.2 SUPPORT EQUIPMENT

### For EMI test

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1	iPad mini	Apple	A1219	DoC	N/A
2	iPod nano	Apple	MA477TA/A	DoC	USB cable, unshd, 1.4m
3	Flash Disk	Kingston	DTIG3/8GB	DoC	N/A
4	Speaker System	T.C.SATR	TCS2285	DoC	Audio cable, unshd, 1.4m
5	Adapter	GPE	GPE013B-0 50200-Z1	N/A	N/A

No.	Signal cable description	
A	DC Power	Unshielded, 1.0m 1 pcs. with 1 core.
B	Audio	Shielded, 1.0m 1 pcs.
C	Audio	Shielded, 1.0m 1 pcs.
D	Audio	Shielded, 1.0m 2 pcs.

**For RF test**

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1	Speaker System	T.C.SATR	TCS2285	DoC	Audio cable, unshd, 1.4m
2	Adapter	GPE	GPE0138-05 0200-Z	DoC	Audio cable, unshd, 1.4m
3	Flash Disk	SanDisk	SPCE600-01 6G	DoC	N/A

No.	Signal cable description	
A	USB	Shielded, 1.1m 1 pcs. with 1 core.
B	Audio	Shielded, 0.5m 1 pcs.
C	Audio	Unshielded, 1m 1 pcs.
D	Audio	Unshielded, 0.7m 1 pcs.
E	Audio	Unshielded, 0.8m 1 pcs.
F	Command	Unshielded, 0.2m 1 pcs.
G	USB	Shielded, 1.7m 1 pcs. with 1 core

**Note:**

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3) shd. = shielded; unshd. = unshielded

### 8.3 EUT OPERATING CONDITION

#### RF Setup

1. Set up all computers like the setup diagram.
2. The “CSR BlueSuite 2.4.8”, “Blue Test 3” software was used for testing.
3. Choose Transport “SPI” and Port “USB SPI (10003)”.

#### TX Mode:

##### GFSK(DH1):

CFG PKT > Packet Type : 4 , Packet Type : 27

TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 230,0 (200,0)

##### GFSK(DH3):

CFG PKT > Packet Type : 11 , Packet Type : 183

TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 230,0 (200,0)

##### GFSK(DH5):

CFG PKT > Packet Type : 15 , Packet Type : 339

TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 230,0 (200,0)

##### 8-DPSK(3DH1):

CFG PKT > Packet Type : 24 , Packet Type : 83

TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 255,50

##### 8-DPSK(3DH3):

CFG PKT > Packet Type : 27 , Packet Type : 552

TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 255,50

##### 8-DPSK(3DH5):

CFG PKT > Packet Type : 31 , Packet Type : 1021

TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 255,50

#### DSSS:

BLE TEST TX > Channel :0 (0,20,39)

Length : 37

Bit pattern : 0

#### RX Mode:

##### GFSK , 8-DPSK:

RXDATA1

##### DSSS:

BLE TEST RX

4. All of the function are under run.
5. Start test.


## 9. APPLICABLE LIMITS AND TEST RESULTS

### 9.1 6dB BANDWIDTH

#### LIMIT

§ 15.207(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

#### TEST SETUP



#### TEST PROCEDURE

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



**TEST RESULTS**

No non-compliance noted.


<b>Model Name</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Temp &amp; Humidity</b>	26.3°C, 45%	<b>Test Date</b>	2018/11/26


**GFSK mode**

<b>Channel</b>	<b>Channel Frequency (MHz)</b>	<b>6dB Bandwidth (kHz)</b>	<b>Minimum Limit (kHz)</b>	<b>Pass / Fail</b>
Low	2402	697.00	500	PASS
Middle	2442	697.00	500	PASS
High	2480	696.00	500	PASS

- NOTE :**
1. At final test to get the worst-case emission at 1Mbps long.
  2. The cable assembly insertion loss of 11.1dB (including 10 dB pad and 1.1 dB cable) was entered as an offset in the spectrum analyzer to allow for direct reading of power.

**6dB BANDWIDTH ( GFSK MODE )**





## 9.2 MAXIMUM PEAK OUTPUT POWER

### LIMIT

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following :

§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands : 1 watt.

§ 15.247(b) (4) Except as shown in paragraphs (c) of this section , if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section , as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### TEST SETUP

#### For Peak Power



#### For Average Power





Report No.: T181105N04-RP1-2

Page: 21 / 64  
Rev.: 01

## **TEST PROCEDURE**

The tests were performed in accordance with KdB 558074 9.1.1

### **9.2.1 Measurement Procedure PK2:**

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq$  3 RBW.
- c) Set span  $\geq$  3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

### **Average Power**

Connect the EUT to power meter, set the center frequency of the power meter to the channel center frequency.

**TEST RESULTS**

No non-compliance noted.

<b>Model Name</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Temp &amp; Humidity</b>	26.3°C, 45%	<b>Test Date</b>	2018/11/26

**GFSK mode**

<b>Channel</b>	<b>Channel Frequency (MHz)</b>	<b>Peak Power (dBm)</b>	<b>Peak Power Limit (dBm)</b>	<b>Pass / Fail</b>
Low	2402	-2.37	30.00	PASS
Middle	2442	0.87	30.00	PASS
High	2480	1.10	30.00	PASS

**NOTE :** 1. At final test to get the worst-case emission at 1Mbps long.  
2. The cable assembly insertion loss of 11.1dB (including 10 dB pad and 1.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.



Report No.: T181105N04-RP1-2

Page: 23 / 64  
Rev.: 01


## Average Power Data

Model Name	SPiN	Test By	Ted Huang
Temp & Humidity	26.3°C, 45%	Test Date	2018/11/26


### GFSK mode

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	-4.91
Middle	2442	-1.65
High	2480	-1.36

### MAXIMUM PEAK OUTPUT POWER ( GFSK MODE )








## 9.3 DUTY CYCLE

### LIMIT

Nil (No dedicated limit specified in the Rules)

### TEST SETUP



### TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value. Set  $VBW \geq RBW$ . Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)



Report No.: T181105N04-RP1-2

Page: 27 / 64  
Rev.: 01

## **TEST RESULTS**

No non-compliance noted.

<b>Model Name</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Temp &amp; Humidity</b>	26.3°C, 45%	<b>Test Date</b>	2018/11/26


### **GFSK Mode**


	us	Times	Ton	Total Ton time(ms)
Ton1	420.000	1	420	
Ton2		0	0	
Ton3			0	0.42
TP				0.65

Ton	0.42
TP(Ton+Toff)	0.65
Duty Cycle	0.646153846
Duty Factor	1.896640662

## TEST PLOT

### Duty Cycle






## 9.4 POWER SPECTRAL DENSITY

### LIMIT

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST SETUP



### TEST PROCEDURE

The tests were performed in accordance with 558074 D01 15.247 Meas Guidance v05

#### 10.2 Method PKPSD (peak PSD):

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \text{ RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

**TEST RESULTS**

No non-compliance noted.



<b>Model Name</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Temp &amp; Humidity</b>	26.3°C, 45%	<b>Test Date</b>	2018/11/26

**GFSK mode**


Channel	Frequency (MHz)	PPSD/100kHz (dBm)	PPSD/3kHz (dBm)	Limit (dBm)	Margin (dB)	Result
Low	2402	-2.61	-17.84	8.00	-25.84	PASS
Middle	2442	0.65	-14.58	8.00	-22.58	PASS
High	2480	0.95	-14.28	8.00	-22.28	PASS

**NOTE :** 1. At final test to get the worst-case emission at 1Mbps long.  
2. The cable assembly insertion loss of 11.1dB (including 10 dB pad and 1.1 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.

## POWER SPECTRAL DENSITY ( GFSK MODE)








## 9.5 CONDUCTED SPURIOUS EMISSION

### LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### TEST SETUP



### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 1 MHz. The video bandwidth is set to 1 MHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


### TEST RESULTS

No non-compliance noted.

# TEST DATA


Model Name	SPiN	Test By	Ted Huang
Temp & Humidity	26.3°C, 45%	Test Date	2018/11/26


## OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT




Report No.: T181105N04-RP1-2

Page: 36 / 64  
Rev.: 01








Report No.: T181105N04-RP1-2

Page: 39 / 64  
Rev.: 01





## 9.6 RADIATED EMISSIONS

### 9.6.1 TRANSMITTER RADIATED SUPURIOUS EMISSIONS

#### LIMITS

§ 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41			

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



**Report No.:** T181105N04-RP1-2

§ 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3


\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz, However, operation within these frequency bands is permitted under other sections of this Part, e-g, Sections 15.231 and 15.241.

§ 15.209 (b) In the emission table above, the tighter limit applies at the band edges.


## TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission from below 1GHz.

### 9kHz ~ 30MHz




### 30MHz ~ 1GHz



Report No.: T181105N04-RP1-2

The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



## TEST PROCEDURE

- The EUT was placed on the top of a rotating table 0.8/1.5 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- The tests were performed in accordance with 558074 D01 15.247 Meas Guidance v05



**Report No.:** T181105N04-RP1-2

Page: 44 / 64  
Rev.: 01

**NOTE :**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.


**TEST RESULTS**

No non-compliance noted.

Report No.: T181105N04-RP1-2

**9.6.2 WORST-CASE RADIATED EMISSION BELOW 1 GHz****BELOW 1 GHz (9kHz ~ 30MHz)**


<b>Product Name</b>	PORTABLE TURNTABLE SYSTEM	<b>Test Date</b>	2019/02/11
<b>Model Name</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Test Mode</b>	TX	<b>Temp &amp; Humidity</b>	23.4°C, 56%



**BELOW 1 GHz (30MHz ~ 1GHz)**

<b>Product Name</b>	PORTABLE TURNTABLE SYSTEM	<b>Test Date</b>	2018/11/23
<b>Model Name</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Test Mode</b>	TX	<b>Temp &amp; Humidity</b>	26.5°C, 54%


Vertical

**Remark:**

1. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).
2. Radiated emissions measured were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).

Product Name	PORTABLE TURNTABLE SYSTEM	Test Date	2018/11/23
Model Name	SPiN	Test By	Ted Huang
Test Mode	TX	Temp & Humidity	26.5°C, 54%

### Horizontal



### Remark:

1. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).
2. Radiated emissions measured were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).

Report No.: T181105N04-RP1-2

### 9.6.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHz

<b>Product Name</b>	PORTABLE TURNTABLE SYSTEM	<b>Test Date</b>	2018/11/26
<b>Model</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Test Mode</b>	GFSK TX (CH Low)	<b>TEMP&amp; Humidity</b>	26.3°C, 45%

#### Horizontal

TX / GFSK mode / CH Low					Measurement Distance at 3m			Horizontal polarity		
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	
* 1380.40	58.35	26.00	2.21	45.12	0.44	41.89	74.00	-32.11	P	
* 1380.40	48.51	26.00	2.21	45.12	0.44	32.05	54.00	-21.95	A	
* 4803.80	58.96	32.91	4.37	44.32	0.22	52.15	74.00	-21.85	P	
* 4803.80	51.31	32.91	4.37	44.32	0.22	44.50	54.00	-9.50	A	
7205.38	56.92	38.70	5.50	44.04	0.27	57.35	74.00	-16.65	P	
7205.38	46.96	38.70	5.50	44.04	0.27	47.39	54.00	-6.61	A	

<b>Product Name</b>	PORTABLE TURNTABLE SYSTEM	<b>Test Date</b>	2018/11/26
<b>Model</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Test Mode</b>	GFSK TX (CH Low)	<b>TEMP&amp; Humidity</b>	26.3°C, 45%

#### Vertical

TX / GFSK mode / CH Low					Measurement Distance at 3m			Vertical polarity		
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	
* 1328.28	61.50	25.78	2.16	45.16	0.44	44.72	74.00	-29.28	P	
* 1328.28	51.74	25.78	2.16	45.16	0.44	34.96	54.00	-19.04	A	
* 4804.01	57.70	32.91	4.37	44.32	0.22	50.89	74.00	-23.11	P	
* 4804.01	48.10	32.91	4.37	44.32	0.22	41.30	54.00	-12.70	A	
7205.57	56.49	38.70	5.50	44.04	0.27	56.93	74.00	-17.07	P	
7205.57	46.69	38.70	5.50	44.04	0.27	47.13	54.00	-6.87	A	

#### REMARK:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: 2.4GHz~2.5GHz Filter Insertion Loss
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:  
Level = Reading + AF + Cable – Preamp + Filter – Dist, Margin = Level-Limit
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.
6. \*=Restricted bands of operation



<b>Product Name</b>	PORTABLE TURNTABLE SYSTEM	<b>Test Date</b>	2018/11/26
<b>Model</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Test Mode</b>	GFSK TX (CH Middle)	<b>TEMP&amp; Humidity</b>	26.3°C, 45%

## Horizontal

TX / GFSK mode / CH Middle					Measurement Distance at 3m				Horizontal polarity	
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	
* 1379.86	58.58	26.00	2.21	45.12	0.44	42.11	74.00	-31.89	P	
* 1379.86	48.63	26.00	2.21	45.12	0.44	32.16	54.00	-21.84	A	
* 4883.58	59.37	33.15	4.42	44.34	0.23	52.83	74.00	-21.17	P	
* 4883.58	52.50	33.15	4.42	44.34	0.23	45.95	54.00	-8.05	A	
* 7325.42	56.73	39.11	5.53	43.93	0.27	57.70	74.00	-16.30	P	
* 7325.42	48.21	39.11	5.53	43.93	0.27	49.18	54.00	-4.82	A	

<b>Product Name</b>	PORTABLE TURNTABLE SYSTEM	<b>Test Date</b>	2018/11/26
<b>Model</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Test Mode</b>	GFSK TX (CH Middle)	<b>TEMP&amp; Humidity</b>	26.3°C, 45%

## Vertical

TX / GFSK mode / CH Middle					Measurement Distance at 3m				Vertical polarity	
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)	
* 1328.68	62.43	25.78	2.16	45.16	0.44	45.65	74.00	-28.35	P	
* 1328.68	52.36	25.78	2.16	45.16	0.44	35.58	54.00	-18.42	A	
* 4883.84	58.34	33.15	4.42	44.34	0.23	51.80	74.00	-22.20	P	
* 4883.84	50.38	33.15	4.42	44.34	0.23	43.84	54.00	-10.16	A	
* 7326.42	56.04	39.11	5.53	43.93	0.27	57.03	74.00	-16.97	P	
* 7326.42	46.51	39.11	5.53	43.93	0.27	47.49	54.00	-6.51	A	

## REMARK:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: 2.4GHz~2.5GHz Filter Insertion Loss
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:  
Level = Reading + AF + Cable – Preamp + Filter – Dist, Margin = Level-Limit
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.
6. \*=Restricted bands of operation

<b>Product Name</b>	PORTABLE TURNTABLE SYSTEM	<b>Test Date</b>	2018/11/26
<b>Model</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Test Mode</b>	GFSK TX (CH High)	<b>TEMP&amp; Humidity</b>	26.3°C, 45%

## Horizontal

TX / GFSK mode / CH High				Measurement Distance at 3m				Horizontal polarity	
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)
* 1381.52	58.75	26.00	2.21	45.12	0.45	42.29	74.00	-31.71	P
* 1381.52	48.88	26.00	2.21	45.12	0.45	32.42	54.00	-21.58	A
* 4959.79	58.79	33.38	4.46	44.36	0.24	52.51	74.00	-21.49	P
* 4959.79	51.02	33.38	4.46	44.36	0.24	44.73	54.00	-9.27	A
* 7439.27	56.37	39.49	5.56	43.83	0.27	57.86	74.00	-16.14	P
* 7439.27	47.01	39.49	5.56	43.83	0.27	48.50	54.00	-5.50	A

<b>Product Name</b>	PORTABLE TURNTABLE SYSTEM	<b>Test Date</b>	2018/11/26
<b>Model</b>	SPiN	<b>Test By</b>	Ted Huang
<b>Test Mode</b>	GFSK TX (CH High)	<b>TEMP&amp; Humidity</b>	26.3°C, 45%

## Vertical

TX / GFSK mode / CH High				Measurement Distance at 3m				Vertical polarity	
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark
(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(P/Q/A)
* 1328.62	61.68	25.78	2.16	45.16	0.44	44.90	74.00	-29.10	P
* 1328.62	52.13	25.78	2.16	45.16	0.44	35.35	54.00	-18.65	A
* 4959.68	58.54	33.38	4.46	44.36	0.24	52.26	74.00	-21.74	P
* 4959.68	49.46	33.38	4.46	44.36	0.24	43.17	54.00	-10.83	A
* 7439.73	55.56	39.50	5.56	43.83	0.27	57.05	74.00	-16.95	P
* 7439.73	45.58	39.50	5.56	43.83	0.27	47.08	54.00	-6.92	A

## REMARK:


1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: 2.4GHz~2.5GHz Filter Insertion Loss
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:  
Level = Reading + AF + Cable – Preamp + Filter – Dist, Margin = Level-Limit
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.
6. \*=Restricted bands of operation

Report No.: T181105N04-RP1-2

## 9.6.4 RESTRICTED BAND EDGES


Detector mode : Peak

Polarity : Horizontal




Detector mode : Average

Polarity : Horizontal




Detector mode : Peak

Polarity : Vertical




Detector mode : Average

Polarity : Vertical




Detector mode : Peak

Polarity : Horizontal




Detector mode : Average

Polarity : Horizontal




Detector mode : Peak

Polarity : Vertical



Detector mode : Average

Polarity : Vertical






## 9.7 POWERLINE CONDUCTED EMISSIONS

### LIMITS

§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted limit (dB $\mu$ v)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.5 - 5	56	46
5 - 30	60	50

**TEST SETUP****TEST PROCEDURE**

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80cm above the horizontal ground plane. The EUT IS CONFIGURED IN ACCORDANCE WITH ANSI C63.10.

The resolution bandwidth is set to 9 kHz for both quasi-peak detection and average detection measurements.

Line conducted data is recorded for both NEUTRAL and LINE.



Report No.: T181105N04-RP1-2


## TEST RESULTS

No non-compliance noted.

Model No.	SPiN	Test Mode	Bluetooth+Table+AUX+REC
Environmental Conditions	24.8 , 62% RH	Resolution Bandwidth	9 kHz
Tested by	Andy Yang		

## LINE

(The chart below shows the highest readings taken from the final data.)




REMARKS : 1. Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB)  
2. Over Limit (dBuV) = Measured Level (dBuV) – Limits (dBuV)

<b>Model No.</b>	SPiN	<b>Test Mode</b>	Bluetooth+Table+AUX+REC
<b>Environmental Conditions</b>	24.8 , 62% RH	<b>Resolution Bandwidth</b>	9 kHz
<b>Tested by</b>	Andy Yang		

**NEUTRAL**

(The chart below shows the highest readings taken from the final data.)



REMARKS : 1. Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB)  
 2. Over Limit (dBuV) = Measured Level (dBuV) – Limits (dBuV)



Report No.: T181105N04-RP1-2

Page: 59 / 64  
Rev.: 01

## 10. ANTENNA REQUIREMENT

### 10.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 10.2 ANTENNA CONNECTED CONSTRUCTION

Manufacturer: BRITO TECHNOLOGY

Type: PCB ANTENNA

Model: TN-180BT

Gain: 1.45 dBi

**=== END of Report ===**