RF Exposure Evaluation Report

Equipment under Test:Transmitter

Model No. : 7147V, 7147VS

FCC ID : EZS7147V

IC: 1513A-7147V

Applicant: FCC:Voxx Electronics Corporation

IC: Voxx Electronics

Address: FCC:2365 Pontiac Road, Auburn Hills, Michigan, 48326, United

States

IC: 2365 Pontiac Road Auburn Hills MI 48326 USA(excluding

The states of Alaska)

Date of Receipt: October 23, 2024

Date of Report: November 13, 2024

Prepared by

Central Research Technology Co. EMC Test Laboratory

No.11, Lane41, Fushuen St., Jungshan Chiu, Taipei, Taiwan, 104, R.O.C.





PREPARED BY: Auth (DATE: November 13, 2024

(Cathy Chen/ Technical Manager)

APPROVED BY: , DATE: November 13, 2024

(Sam Chien /Authorized Signatory)

This report shall not be reproduced, except in full, without written approval of Central Research Technology Co.. It may be duplicated completely in its entirely for legal use with the permission of the applicant. The test result in this report is based on the information provided by manufacturer and applies only to the sample tested.

CENTRAL RESEARCH TECHNOLOGY CO. 11, Lane 41, Fushuen St., Jungshan Chiu, Taipei 104, Taiwan

TEL.: 886-2-25872719 FAX.: 886-2-25850364

1 Requirement for Compliance

According to KDB 447498 D04 v01 and RSS-102 issue 6:

FCC requirement:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption

IC requirement

Frequenc y (MHz)	≤ 5 mm (mW)	10 mm (mW)	15 mm (mW)	20 mm (mW)	25 mm (mW)	30 mm (mW)	35 mm (mW)	40 mm (mW)	45 mm (mW)	> 50 mm (mW)
≤ 300	45	116	139	163	189	216	246	280	319	362
450	32	71	87	104	124	147	175	208	248	296

2 Calcaulation

Frequency	Max	Limit			
Range	Po	ower	(mW)		
(MHz)	(dBm)	(mW)	FCC	IC @5mm	
433.92	-11.26	0.07	1	33.39	

P (dBm) = E (dBuV/m) - 95.2 = 83.94 - 95.2 = -11.26 dBm

IC limit @5mm: 32 mW (450 MHz), 45 mW(300 MHz) use linear interpolation to get limit.

3 Result

According to result, the SAR testing for this device is not required.

~ End of Report ~

CENTRAL RESEARCH TECHNOLOGY CO.

11, Lane 41, Fushuen St., Jungshan Chiu, Taipei 104, Taiwan

TEL.: 886-2-25872719 FAX.: 886-2-25850364