

Band Edge Conducted measurement



Band Edge Conducted Measurement



5.6.4 Test Procedure (Radiated)

1. Antenna and Turntable test procedure same as Radiated Emission Measurement.
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN: 100MHz
RBW: 1MHz
VBW: 1MHz
Center frequency: 2.395GHz, 2.48 GHz.
2. Using Peak Search to read the peak power of Carrier frequencies after Maximum Hold function is completed.
3. Find the next peak frequency outside the operation frequency band.
4. For peak frequency emission level measurement in Restricted Band ,
Change RBW: 1MHz ,
VBW: 10Hz,
Span: 100MHz.
5. Get the spectrum reading after Maximum Hold function is completed.

5.6.5 Test Setup (Radiated)

Same as *Radiated Emission Measurement*

5.6.6 Test Data:**Table Band Edge measurement (Radiated)**

Channel	Frequency (MHz)	Spectrum Reading (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit: > 20dB (dBC)	Limit (dBuV/m)	Equip. Setup VBW	Pass or Fail
1(peak mode)	2409.3	65.63	31.67	97.30	---	-----	1MHz	-----
Outside band	2400.0	42.57	31.67	74.24	23.06	-----	1MHz	Pass
1(average mode)	2410.6	51.77	31.67	83.44	---	-----	10Hz	-----
Restricted band	2390.0	9.7	31.67	41.37	-----	54	10Hz	Pass
11(peak mode)	2461.9	63.52	31.64	95.16	----	-----	1MHz	-----
Outside band	2476.4	32.52	31.64	64.16	31.00	-----	1MHz	Pass
11(average mode)	2463.3	49.97	31.64	81.64	----	-----	10Hz	-----
Restricted band	2483.5	10.23	31.64	41.87	-----	54	10Hz	Pass

Note: The Spectrum plot of emission level measurement in Restricted band is attached.

Emission Level = Spectrum Reading + Correction Factor

Correction Factor = Antenna Factor + cable loss – amplifier gain

Both Horizontal and Vertical polarization have been tested and the worst data is listed above.

Band Edge measurement for radiated emission in Restricted Band(Radiated)

Peak Mode (Channel 1)



Band Edge measurement for radiated emission in Restricted Band(Radiated)

Average Mode (Channel 1)



Band Edge measurement for radiated emission in Restricted Band(Radiated)

Peak Mode (Channel 11)



Band Edge measurement for radiated emission in Restricted Band(Radiated)

Average Mode (Channel 11)



5.7 RF Exposure Measurement [Section 15.247(b)(4) & 1.1307(b)]


See the SAR report

5.8 DSSS Peak Power Spectral Density [Section 15.247(d)]

5.8.1 Test Procedure

1. The Transmitter output of EUT was connected to the spectrum analyzer.
 Equipment mode: Spectrum analyzer
 Detector function: Peak mode
 SPAN:1.5MHz
 RBW: 3KHz
 VBW: 30KHz
 Center frequency: fundamental frequency tested.
 Sweep time= 500 sec.
2. Using Peak Search to read the peak power after Maximum Hold function is completed.


5.8.2 Test Setup





5.8.3 Test Data:

Table Maximum Peak Output Power Density

Chennel	Spectrum Reading (dBm/3KHz)	Cable Loss (dB)	Peak Power Output (dBm/3KHz)	Limit (dBm/3KHz)	Pass/Fail
1	-17.46	1.1	-16.36	8	Pass
6	-18.31	1.1	-17.21	8	Pass
11	-17.80	1.1	-16.70	8	Pass







6. TEST RESULTS (Bluetooth)

6.1 Maximum Peak Output Power [Section 15.247 (b)(1)]

6.1.1 Test Procedure

The Transmitter output of EUT was connected to the peak power analyzer.

6.1.2 Test Setup



6.1.3 Test Data:

Table Maximum Peak Output Power

Chennel	Frequency (MHz)	Peak Power Output (mW)	Peak Power Output (dBm)	Limit (dBm)	Pass/Fail
0	2402	2.20	3.43	30	Pass
39	2441	2.32	3.65	30	Pass
78	2480	2.21	3.45	30	Pass

6.2 Radiated Emission Measurement [Section [15.247(c)(4)]

6.2.1 EUT Configuration

The equipment under test was set up on the 10 meter chamber with measurement distance of 3 meters. The EUT was placed on a non-conductive table 80cm above ground.

Any changes made to the configuration, or modifications made to the EUT, during testing are noted in the following test record.

6.2.2 Test Procedure

The system was set up as described above, with the EMI diagnostic software running. We found the maximum readings by varying the height of antenna and then rotating the turntable. Both polarization of antenna, horizontal and vertical, are measured.

30M to 1GHz: The highest emissions between 30 MHz to 1000 MHz were also analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. While doing so, the interconnecting cables and major parts of the system were moved around, the antenna height was varied between one and four meters, its polarization was varied between vertical and horizontal, and the turntable was slowly rotated, to maximize the emission.

1GHz – 25GHz: The highest emissions were also analyzed in details by operating the spectrum analyzer and/or EMI receiver in peak mode to determine the precise amplitude of the emission. While doing so, the interconnecting cables and major parts of the system were moved around, the antenna height was varied between one and four meters, its polarization was varied between vertical and horizontal, and the turntable was slowly rotated, to maximize the emission. During test the EMI receiver and spectrum was setup according to *EMI Receiver/Spectrum Analyzer Configuration*.

For the test of 2nd to 10th harmonics frequencies, the equipment setup was also refer to *EMI Receiver/Spectrum Analyzer Configuration*. The frequencies were tested using Peak mode first, if the test data is higher than the emissions limit, an additional measurement using Average mode will be performed and the average reading will be compared to the limit and record in test report.

6.2.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range Tested:	30MHz~1000MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth (RBW):	120KHz
Video Bandwidth (VBW)	1MHz
Frequency Range Tested:	1GHz – 25 GHz
Detector Function:	Peak Mode
Resolution Bandwidth (RBW):	1MHz
Video Bandwidth (VBW)	1MHz
Frequency Range Tested:	1GHz – 25 GHz
Detector Function:	Average Mode
Resolution Bandwidth (RBW):	1MHz
Video Bandwidth (VBW)	10 Hz

6.2.4 Test Data (above 1GHz) :**1GHz~ 25 GHz (Horizontal), The Emission Data While Bluetooth Channel 10 : 2412 MHz & 802.11b WLAN Channel 1 : 2412 MHz operating**

Meter Reading		Correction Factor			Corrected Emissions			Antenna	Turntable
Freq. (MHz)	Ampl. (dBuV) (pk)	Ant. (dB/m)	Cable (dB)	Pre-Ampl. (dB)	Ampl. (dBuV/m)	Limit (dBuV/m) (av)	Margin (dB)	Height (cm)	Position (°)
1002.5	54.88	24.51	0.68	46.00	34.07	54.00	-19.93	100	92
2311.19	49.06	30.58	1.12	46.21	34.55	54.00	-19.45	102	89
4265.73	42.66	32.74	1.77	46.37	30.80	54.00	-23.20	100	41
6968.53	36.60	39.82	2.31	46.33	32.41	54.00	-21.59	100	23
8606.39	40.12	40.87	2.61	42.55	41.05	54.00	-12.95	104	134
11507.5	36.24	42.40	3.03	41.61	40.06	54.00	-13.94	100	78

‘pk’ ---- peak, ‘av’ ----average

1GHz~ 25 GHz (Vertical), , The Emission Data While Bluetooth Channel 10 : 2412 MHz & 802.11b WLAN Channel 1 : 2412 MHz operating

Meter Reading		Correction Factor			Corrected Emissions			Antenna	Turntable
Freq. (MHz)	Ampl. (dBuV) (pk)	Ant. (dB/m)	Cable (dB)	Pre-Am pl. (dB)	Ampl. (dBuV/m)	Limit (dBuV/m) (av)	Margin (dB)	Height (cm)	Position (°)
1332.17	58.29	25.90	0.79	46.15	38.82	54.00	-15.18	100	65
1601.9	56.71	27.44	0.88	46.22	38.81	54.00	-15.19	102	67
4087.41	42.34	32.24	1.71	46.20	30.10	54.00	-23.90	100	73
6972.03	37.30	39.84	2.31	46.32	33.13	54.00	-20.87	100	183
9643.36	45.44	39.20	2.78	42.07	45.34	54.00	-8.66	107	28
11495.5	35.23	42.38	3.02	41.58	39.06	54.00	-14.94	100	44

‘pk’ ---- peak, ‘av’ ----average

Note:

The Spectrum noise level + Correction Factor < Limit - 6 dB

Margin = Corrected Amplitude – Limit

Corrected Amplitude = Radiated Amplitude + Antenna Correction Factor + Cable Loss -

Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

All frequencies from 1GHz to 25 GHz have been tested.

The worst data of the Radiated Emission over 1GHz are listed above when the bluetooth device is co-located with the WLAN device.

**1GHz~ 25 GHz (Horizontal), The Emission Data While Bluetooth Channel 10 : 2412 MHz
& 802.11g WLAN Channel 1 : 2412 MHz operating**

Meter Reading		Correction Factor			Corrected Emissions			Antenna	Turntable
Freq. (MHz)	Ampl. (dBuV) (pk)	Ant. (dB/m)	Cable (dB)	Pre-Ampl. (dB)	Ampl. (dBuV/m)	Limit (dBuV/m) (av)	Margin (dB)	Height (cm)	Position (°)
1034.97	58.45	24.65	0.69	46.02	37.77	54.00	-16.23	100	22
2311.19	60.98	30.58	1.12	46.21	46.47	54.00	-7.53	106	12
3741.26	48.35	31.69	1.60	46.39	35.25	54.00	-18.75	100	51
6968.53	36.51	39.82	2.31	46.33	32.31	54.00	-21.69	101	10
8696.3	40.16	40.76	2.62	42.62	40.93	54.00	-13.07	100	160
11489.5	35.80	42.36	3.02	41.57	39.62	54.00	-14.38	102	73

‘pk’ ---- peak, ‘av’ ----average

**1GHz~ 25 GHz (Vertical), , The Emission Data While Bluetooth Channel 10 : 2412 MHz
& 802.11g WLAN Channel 1 : 2412 MHz operating**

Meter Reading		Correction Factor			Corrected Emissions			Antenna	Turntable
Freq. (MHz)	Ampl. (dBuV) (pk)	Ant. (dB/m)	Cable (dB)	Pre-Am pl. (dB)	Ampl. (dBuV/m)	Limit (dBuV/m) (av)	Margin (dB)	Height (cm)	Position (°)
2311.19	59.19	30.58	1.12	46.21	44.67	54.00	-9.33	100	32
2376.12	61.98	30.55	1.14	46.21	47.46	54.00	-6.54	100	19
4258.74	42.34	32.72	1.77	46.36	30.47	54.00	-23.53	102	24
6965.04	37.10	39.80	2.31	46.33	32.88	54.00	-21.12	100	129
8384.62	39.74	41.05	2.57	42.77	40.59	54.00	-13.41	109	253
11495.5	35.88	42.38	3.02	41.58	39.71	54.00	-14.29	101	23

‘pk’ ---- peak, ‘av’ ----average

Note:

The Spectrum noise level + Correction Factor < Limit - 6 dB

Margin = Corrected Amplitude – Limit

Corrected Amplitude = Radiated Amplitude + Antenna Correction Factor + Cable Loss -

Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

All frequencies from 1GHz to 25 GHz have been tested.

The worst data of the Radiated Emission over 1GHz are listed above when the bluetooth device is co-located with the WLAN device.

6.3 Band Edge Measurement (when Bluetooth and WLAN are operating at the same time)

!! Measuring the Peak / Average Mode when Bluetooth Channel 0 is co-located with the WLAN Channel 1 and Bluetooth Channel 78 is co-located with the WLAN Channel 11.

6.3.1 Band Edge measurement Test Procedure (Radiated)

1. Antenna and Turntable test procedure same as *Radiated Emission Measurement*
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN:100MHz
RBW: 1MHz
VBW: 1MHz
Center frequency: 2.395GHz, 2.48 GHz.
2. Using Peak Search to read the peak power of Carrier frequencies after Maximun Hold function is completed.
3. Find the next peak frequency outside the operation frequency band.
4. For peak frequency emission level measurement in Restricted Band ,
Change RBW: 1MHz ,
VBW: 10Hz,
Span: 100MHz.
5. Get the spectrum reading after Maximun Hold function is completed.

6.3.2 Test Setup (Radiated)

Same as *Radiated Emission Measurement*

6.3.3 Test Data (bluetooth & 802.11b):**Band Edge measurement (Radiated)**

Channel	Frequency (MHz)	Spectrum Reading (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	dBc (Limit: > 20dBc)	Limit (dBuV/m)	Equip. Setup VBW	Pass or Fail
1(WLAN peak mode)	2411.3	62.90	31.67	94.57	---	---	1MHz	---
0(blue tooth peak mode)	2401.9	59.34	31.67	91.01	---	---	1MHz	---
Outside band	2400.0	34.82	31.67	66.49	24.52	---	1MHz	Pass
1(WLAN average mode)	2412.8	55.98	31.67	87.65	---	---	10Hz	---
0(blue tooth average mode)	2402.5	42.4	31.67	74.07	---	---	10Hz	---
Restricted band	2385.4	7.23	31.67	38.9	-----	54	10Hz	Pass
11(WLAN peak mode)	2461.2	61.30	31.64	92.94	----	---	1MHz	---
11(blue tooth peak mode)	2479.9	52.14	31.64	83.78	----	---	1MHz	---
Outside band	2483.5	13.87	31.64	45.51	38.27	---	1MHz	Pass
11(WLAN average mode)	2462.8	53.41	31.64	85.05	----	---	10Hz	---
11(blue tooth average mode)	2480.1	25.08	31.64	56.72	----	---	10Hz	---
Restricted band	2488.3	5.98	31.64	37.62	-----	54	10Hz	Pass

Note: The Spectrum plot of emission level measurement in Restricted band is attached.

Emission Level = Spectrum Reading + Correction Factor

Correction Factor = Antenna Factor + cable loss – amplifier gain

**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Peak Mode (Bluetooth Channel 0 is co-located with the WLAN Channel 1)**



**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Average Mode (Bluetooth Channel 0 is co-located with the WLAN Channel 1)**



Band Edge measurement for radiated emission in Restricted Band(Radiated)

Peak Mode (Bluetooth Channel 78 is co-located with the WLAN Channel 11)



Band Edge measurement for radiated emission in Restricted Band(Radiated)

Average Mode (Bluetooth Channel 78 is co-located with the WLAN Channel 11)



6.3.4 Test Data (bluetooth & 802.11g):**Band Edge measurement (Radiated)**

Channel	Frequency (MHz)	Spectrum Reading (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	dBc (Limit: > 20dBc)	Limit (dBuV/m)	Equip. Setup VBW	Pass or Fail
1(WLAN peak mode)	2405.6	62.63	31.67	94.30	---	---	1MHz	---
0(blue tooth peak mode)	2402.2	61.09	31.67	92.76	---	---	1MHz	---
Outside band	2400.0	38.83	31.67	70.50	22.26	---	1MHz	Pass
1(WLAN average mode)	2404.6	47.88	31.67	79.55	---	---	10Hz	---
0(blue tooth average mode)	2402.0	34.17	31.67	65.84	---	---	10Hz	---
Restricted band	2390.0	9.24	31.67	40.91	-----	54	10Hz	Pass
11(WLAN peak mode)	2464.3	59.93	31.64	91.57	----	---	1MHz	---
11(blue tooth peak mode)	2479.9	52.13	31.64	83.77	----	---	1MHz	---
Outside band	2483.5	22.42	31.64	54.06	29.71	---	1MHz	Pass
11(WLAN average mode)	2469.3	43.63	31.64	75.27	----	---	10Hz	---
11(blue tooth average mode)	2480.0	23.70	31.64	55.34	----	---	10Hz	---
Restricted band	2483.5	7.18	31.64	38.82	-----	54	10Hz	Pass

Note: The Spectrum plot of emission level measurement in Restricted band is attached.

Emission Level = Spectrum Reading + Correction Factor

Correction Factor = Antenna Factor + cable loss – amplifier gain

**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Peak Mode (Bluetooth Channel 0 is co-located with the WLAN Channel 1)**



**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Average Mode (Bluetooth Channel 0 is co-located with the WLAN Channel 1)**



**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Peak Mode (Bluetooth Channel 78 is co-located with the WLAN Channel 11)**



**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Average Mode (Bluetooth Channel 78 is co-located with the WLAN Channel 11)**



7. Appendix

7.1 Appendix A: Measurement Procedure for Powerline Conducted Emissions

The EUT is set up in accordance with the suggested configuration given in ANSI C63.4-2001, CFR 47 Part 15 Subpart B; or EN55022:1994/ A1:1995/A2:1997; CISPR 22:1993/A1:1995/A2:1996. The measurements are performed in a 3.5m x 3.4m x 2.5m shielded room, which referred as Conduction 01 test site, or a 3m x 3m x 2.3m test site, which referred as Conduction 02 test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the Figure 1 of the ANSI C63.4-2001 or CISPR16. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

If the EUT is supplied with a flexible power cord, the power cord length in excess of the distance separating the EUT from the LISN shall be folded back and forth at the center of the lead so as to form a bundle not exceeding 40cm in length. If the EUT is provided with a permanently coiled power cord, bundling of the cord is not required. If the EUT is supplied without a power cord, the EUT shall be connected to the LISN by a power cord of the type specified by the manufacturer which shall not be longer than 1 meter. The excess power cord shall be bundled as described above. If a non-flexible power cord is provided with the EUT, it shall be cut to the length necessary to attach the EUT to the LISN and shall not be bundled.

The interconnecting cables were arranged and moved to get the maximum according to ANSI C63.4-2001, CFR 47 Part 15 Subpart B; or EN55022:1994/ A1:1995/A2:1997; CISPR 22:1993/A1:1995/A2:1996. Both the line of power cord, hot and neutral, were measured.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

7.2 Appendix B: Test Procedure for Radiated Emissions

Preliminary Measurements in the Anechoic Chamber

The radiated emissions are initially measured in the anechoic chamber at a measurement distance of 3 meters. Desktop EUT are placed on a wooden stand 0.8 meter in height. The measurement antenna is 3 meters from the EUT. The test setup in anechoic chamber is the same as open site. The turntable rotated 360°. The antenna height is varied from 1-2.5m. The primary objective of the radiated measurements in the anechoic chamber is to identify the frequency spectrum in the absence of the electromagnetic environment existing on the open test site. The frequencies can then be pre-selected on the open test site to obtain the corresponding amplitude. The initial scan is made with the spectrum analyzer in automatic sweep mode. The spectrum peaks are then measured manually to determine the exact frequencies.

Measurements on the Open Site or 10m EMC Chamber

The radiated emissions test will then be repeated on the open site or 10m EMC chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of the 3 or 10 meter open field sites. Desktop EUT are set up on a wooden stand 0.8 meter above the ground.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. Both readings are recorded with the quasi-peak detector with 120KHz bandwidth. For frequency between 30 MHz and 1000MHz, the reading is recorded with peak detector or quasi-peak detector. For frequency above 1 GHz, the reading is recorded with peak detector or average detector with 1 MHz bandwidth.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum according to ANSI C63.4-2001, CFR 47 Part 15 Subpart B; or EN55022:1994/ A1:1995/A2:1997; CISPR 22:1993/A1:1995/A2:1996. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings.

7.3 Appendix C: Test Equipment

7.3.1 Test Equipment List

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction	50 Ohms Load Conduction 02	EMCO	N/A	ISL-50ohms conduction 02	11/21/2003	11/21/2004
Conduction	Coaxial Cable 1F-C2	Harbourindustries	RG400	1F-C2	06/03/2003	06/03/2004
Conduction	Digital Hygro-Thermometer Conduct	MicroLife	HT-2126G	ISL-Conduction02	12/16/2003	12/16/2004
Conduction	EMI Receiver 02	HP	85460A	3448A00183	08/21/2003	08/21/2004
Conduction	ISN T4	Schaffner	ISN T400	16593	08/20/2002	08/20/2004
Conduction	LISN 01	R&S	ESH2-Z5	890485/013	05/07/2003	05/07/2004
Conduction	LISN 03	R&S	ESH3-Z5 831.5518.52	828874/D10	10/31/2003	10/31/2004
Radiation	Spectrum Analyzer 06	Advantest	R3162	91700295	09/25/2003	09/24/2004
Radiation	EMI Receiver 05	AFJ	ER 55CR	55390143234	11/07/2003	11/07/2004
Radiation	BILOG Antenna 08	Schaffner	CBL6112B	2756	06/04/2003	06/04/2004
Radiation	Microwave Cable Chmb 02 3M	HUBER+SUHNER AG.	Sucoflex 103	42731/3 & 42729/3	03/21/2003	03/21/2004
Radiation	Coaxial Cable Chmb 02-10M	Belden	RG-8/U	Chmb 02-10M	01/14/2003	01/14/2004
Radiation	Digital Hygro-Thermometer Chmb 02	MicroLife	HT-2126G	Chmb 02	02/07/2003	02/07/2004
Rad. Above 1Ghz	Horn Antenna 02	Com-Power	AH-118	10088	02/25/2003	02/25/2004
Rad. Above 1Ghz	Horn Antenna 04	Com-Power	AH-826	081-001	10/17/2003	10/17/2004
Rad. above 1Ghz	Horn Antenna 05	Com-Power	AH-640	100A	09/13/2003	09/13/2004
Rad. above 1Ghz	Microwave Cable Chmb 05	HUBER+SUHNER AG.	Sucoflex 103	42726/3 & 42727/3	09/11/2003	09/11/2004
Rad. Above 1Ghz	Preamplifier 02	MITEQ	AFS44-00102 650-40-10P-44	728229	05/07/2003	05/07/2004
Rad. Above 1Ghz	Preamplifier 09	MITEQ	AFS44-00102 650-40-10P-44	858687	02/28/2003	02/28/2004

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
RF	Peak Power Analyzer	HP	8990A	3621A01269	09/12/2003	09/12/2004
Rad. Above 1Ghz	Preamplifier 10	MITEQ	JS-26004000-27-5A	818471	02/28/2003	02/28/2004
Rad. Above 1Ghz	Signal Generator 03	Anritsu	MG3642A	6200162550	02/05/2003	02/05/2004
Rad. Above 1Ghz	Signal Generator 04	Anritsu	MG3692A	020311	02/06/2002	02/06/2004
Rad. Above 1Ghz	Spectrum Analyzer 07	Advantest	R3182	110600649	10/17/2003	10/17/2004


Note: Calibration traceable to NIST or national or international standards.

7.3.2 Software for Controlling Spectrum/Receiver and Calculating Test Data


Radiation/Conduction	Filename	Version	Issued Date
Conduction	Tile.exe	1.12E	7/7/2000
Radiation	Tile.exe	1.12C	6/16/2000

7.4 Appendix D: Layout of EUT and Support Equipment


7.4.1 General Conducted Test Configuration



7.4.2 General Radiation Test Configuration



Metal Full Soldered Ground Plane



7.5 Appendix E: Description of Support Equipment

7.5.1 Description of Support Equipment

Support Unit 1.

Description:	Logitech USB Mouse
Model Number:	M-u48a
Serial Number:	LZE02050204
Power Supply Type:	N/A
Power Cord:	N/A
FCC ID:	JNZ211360

Support Unit 2.

Description:	Acer USB Keyboard
Model Number:	6511-UV
Serial Number:	N/A
Power Supply Type:	N/A
Power Cord:	N/A
FCC ID:	N/A (comply with FCC DOC)

Support Unit 3.

Description:	Acer Monitor
Model:	G781
Serial Number:	999007101214400445T7AA31T
Power Cord:	Non-shielded, Detachable
FCC ID:	(Comply with FCC Standards)

7.5.2 Software for Controlling Support Unit

Test programs exercising various part of EUT were used. The programs were executed as follows:

- A. Read and write to the disk drives.
- B. Send H pattern to the video port device (Monitor).
- C. Repeat the above steps.

	Filename	Issued Date
Monitor	HH.bat	8/20/1991

7.5.3 I/O Cable Condition of EUT and Support Units

Description	Path	Cable Length	Cable Type	Connector Type
AC Power Cord	110V (~240V) to AC Power Cord Inlet (3-pin)	1.8M	Nonshielded, Detachable	Plastic Head
Monitor Data Cable	Monitor to PC VGA port	1.6M	Shielded, Un-detachable	Metal Head
USB Mouse Data Cable	USB Mouse to PC USB port	1.8M	Shielded, Un-detachable	Metal Head
USB Keyboard Data Cable	USB Keyboard to PC USB port	1.8M	Shielded, Undetachable	Metal Head

7.6 Appendix F: Accuracy of Measurement

Test Site: Conduction 02

Item	Source of Uncertainty	Probability Distribution	Total Uncertainties (dB)		Standard Uncertainty (dB)	
1	Systematic Effects: (Assessment from 20 repeat observation; 1 reading on EUT)	Normal	k=2	0.104	k=1	0.052
2	Random Effects: (Assessment from 20 random observations; 1 reading on EUT)	Normal	k=2	0.330	k=1	0.165
3	Receiver Calibration	Rectangular	k=1.73	1.000	k=1	0.577
4	LISN Factor Calibration	Normal	k=2	1.200	k=1	0.600
5	Cable Loss Calibration	Normal	k=2	1.000	k=1	0.500
6	Combined Standard Uncertainty $U_c(y)$	Normal			k=1	0.850
7	Total Uncertainty @95% mim. Confidence Level	Normal	k=2	1.701		

Measurement Uncertainty Calculations:

$$U_c(y) = \text{square root} (u_1(y)^2 + u_2(y)^2 + \dots + u_n(y)^2)$$

$$U = 2 * U_c(y)$$

Note: The measurement Uncertainties mentioned above also refer to NIS 81-1994 of NAMAS :
The treatment of Uncertainty in EMC Measurement.

Test Site: Chamber 02-3M

Item	Source of Uncertainty	Probability Distribution	Total Uncertainties (dB)		Standard Uncertainty (dB)	
1	Systematic Effects: (Assessment from 20 repeat observation; 1 reading on EUT)	Normal	k=2	0.067	k=1	0.034
2	Random Effects: (Assessment from 20 random observations; 1 reading on EUT)	Normal	k=2	0.103	k=1	0.052
3	Receiver Calibration	Rectangular	k=1.73	1.000	k=1	0.577
4	Antenna Factor Calibration	Normal	k=2	1.700	k=1	0.850
5	Cable Loss Calibration	Normal	k=2	1.000	k=1	0.500
6	Combined Standard Uncertainty Uc(y)	Normal			k=1	1.029
7	Total Uncertainty @95% mim. Confidence Level	Normal	k=2	2.059		

Measurement Uncertainty Calculations:


$$Uc(y) = \text{square root} (u_1(y)^2 + u_2(y)^2 + \dots + u_n(y)^2)$$

$$U = 2 * Uc(y)$$

Note: The measurement Uncertainties mentioned above also refer to NIS 81-1994 of NAMAS :
The treatment of Uncertainty in EMC Measurement.

7.7 Appendix G: Photographs of EUT Configuration Test Set Up


The Front View of Highest Conducted Set-up For EUT



The Front View of Highest Radiated Set-up For EUT



The Back View of Highest Radiated Set-up For EUT



7.8 Appendix H: Antenna Spec.

Please refer to the attached file.