



Shenzhen xingtong wireless technology co.,
Telephone: +86-755- 27850514 Fax: +86- 0755-27850514
Address: 3/F, Building A1, Qiangrongdong Industrial Zone,
Jiuwei, Xixiang, Baoan District, Shenzhen

Product specification

Product number: E150

Product name: E150-FPC-WIFI-ANT

Product item number: ANT-E150WIFISF-XT001

Producer	Audit	Date
Huangjiajun	Wu Yanlong	2024-10-15

Customer confirmation:

Customer name: Shenzhen Xinruizhi Industrial Co., Ltd
Approval :
Date :
Notes :

Please accept your signature and seal and return one copy to our company for filing. Thank you for your cooperation!

 Shenzhen Xingtong Wieress Technology Co., Ltd		Date	2024-10-15
		Version	A0
		File number	XT-YF-004
Product model	E150-WIFI antenna	Product number	E150-WIFI-APP

1.Product Constrution:


- 1. Antenna material: FPC
- 2. Adhesive tvne: 3M9471
- 3. Antenna size: 28.9*16.55 (Tolerance+0.2)
- 4. Coaxial line size: 90 * 0.81 single head third-generation IPEX terminal (tolerance $\pm 1.0\text{mm}$)

2. parameters


- Scope of use: customer-supplied machines
- Antenna frequency: 2400-2500Mhz
- Polarization method: horizontal/vertical
- Antenna free space gain: 2.4G/2.9dhi (max)
- Installation mode: terminal wire is welded to motherboard OUT
- Packing method: use PE bag+packing box

3.S11 value of antenna (S11)

- 3.1: antenna standing wave ratio



- 3.2: Antenna return loss value



4. Antenna performance (OTA)

4.1: Antenna matching recommendations


Matching without modification

4.2: Antenna OTA/ efficiency/gain (test instruments: network analyzer, oscilloscope, customer engineering prototype, various standard cards, etc.)

2.4G-2D

Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Efficiency (dBi)	-3.39	-3.39	-3.30	-3.30	-3.41	-3.32	-3.38	-3.49	-3.36	-3.42	-3.40
Gain (dBi)	2.41	2.56	2.73	2.67	2.56	2.63	2.67	2.67	2.90	2.88	2.91
Efficiency (%)	45.78	45.84	46.72	46.77	45.60	46.53	45.87	44.82	46.09	45.51	45.76
Directivity (dB)	5.81	5.94	6.04	5.97	5.97	5.95	6.06	6.16	6.26	6.30	6.31
Peak Gain Position (Theta)	150.00	150.00	150.00	150.00	150.00	150.00	150.00	150.00	150.00	150.00	150.00
Peak Gain Position (Phi)	75.00	75.00	60.00	75.00	60.00	75.00	300.00	300.00	300.00	300.00	300.00
Efficiency ThetaPol (%)	27.08	26.94	27.40	27.29	26.03	26.01	25.48	25.10	25.85	25.63	25.99
Efficiency PhiPol (%)	18.70	18.89	19.32	19.48	19.57	20.52	20.40	19.72	20.24	19.88	19.76
Upper Hem. Efficiency (%)	16.25	16.47	17.12	17.53	17.52	18.14	18.08	17.74	18.33	18.21	18.50
Lower Hem. Efficiency (%)	29.53	29.36	29.60	29.24	28.08	28.39	27.79	27.08	27.76	27.29	27.25


3D-OTA-2.4G



 Shenzhen Xingtong Wieress Technology Co., Ltd		Date	2024-10-15
		Version	A0
		File number	XT-YF-004
Product model	E150-WIFI antenna	Product number	E150-WIFI-APP

5. Attached figure:

5.1: Finished antenna drawing



 Shenzhen Xingtong Wieress Technology Co., Ltd		Date	2024-10-15
		Version	A0
		File number	XT-YF-004
Product model	E150-WIFI antenna	Product number	E150-WIFI-APP

6. Maintenance verification:

Tests/test items	Maintainability	Inspection order number
Product name/specification	2.4G WIFI built-in fpc antenna	Test quantity: 5PCS
Date of inspection: 2024/10/15		Completiondate: 2024/10/15

Test/inspection equipment:

1. The tensile tester tests 5 times. (The tester is shown in the figure)



Note: Uniform speed test is required, not extreme speed test.

Projects Condition	Maintaining force between terminal and cable $\geq 0.6\text{kgf}$.				
Test times	1	2	3	4	5
test result	0.6	0.7	0.7	0.9	0.7

Test/inspection result: acceptable

Test/inspection judgment: ☒ Qualified ☐ Unqualified ☐ Make no judgment

Test: Zhu Yongjian

Audit: Wu Yanlong

 Shenzhen Xingtong Wieress Technology Co., Ltd		Date	2024-10-15
		Version	A0
		File number	XT-YF-004
Product model	E150-WIFI antenna	Product number	E150-WIFI-APP

7. Reliability test:

Serialnumber	test item	Test requirements	testing tool	test result
1	Resistance to tin melting	288℃, 10S, no delamination, no foaming	Tin furnace	0k
2	weldability	245℃, 5s, smooth tin surface, solder surface≥95%	Tin furnace	0k
3	Pulling force	N/A	tautness meter	0k
4	Reverse pulling force	N/A	tautness meter	0k
5	Peel strength (covering film)	≥0.35kg/cm	peel strength	0k
6	Peel strength (copper foil)	≥0.8kg/cm	peel strength	0k
7	Hot melt adhesive fluidity	0.1~0.15	/	0k

 Shenzhen Xingtong Wieress Technology Co., Ltd		Date	2024-10-15
		Version	A0
		File number	XT-YF-004
Product model	E150-WIFI antenna	Product number	E150-WIFI-APP

7. Matters needing attention:



After opening, please carefully check whether the goods are complete. If there is any damage, please contact us immediately.