

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard:	47 CFR FCC Part 15, Subpart C (Section 15.249)		
Report No.:	RFBCTR-WTW-P24080501		
FCC ID:	JVPCR23CCTR		
Product:	ScreenBar Halo 2 Controller		
Brand:	BenQ		
Model No.:	CR23_C Controller		
Received Date:	2024/9/3		
Test Date:	2024/9/11 ~ 2024/9/19		
Issued Date:	2024/12/10		
Applicant:	BenQ CORPORATION		
Address:	No. 16, Jihu Rd., Neihu Dist., Taipei City 114066, Taiwan (R.O.C.)		
Issued By:	y: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory		
Lab Address:	E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan		
Test Location:	E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan		
FCC Registration / 723255 / TW2022			
Designation Number:			
	\mathcal{M}		
Approved by:	// , Date: 2024/12/10		

May Chen / Manager

This test report consists of 33 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by: Vito Lung / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/ver-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the report contents.



Table of Contents

R	eleas	se Control Record	3
1		Certificate	4
2		Summary of Test Results	5
	2.1 2.2	Measurement Uncertainty Supplementary Information	5 5
3		General Information	6
	3.1 3.2 3.3 3.4 3.5 3.6 3.7 3.8	General Description Antenna Description of EUT Channel List Test Mode Applicability and Tested Channel Detail Duty Cycle of Test Signal Test Program Used and Operation Descriptions Connection Diagram of EUT and Peripheral Devices Configuration of Peripheral Devices and Cable Connections	6 7 9 10 11 11
4		Test Instruments	12
	4.1 4.2 4.3 4.4	AC Power Conducted Emissions Radiated Emissions below 1 GHz Radiated Emissions above 1 GHz 20 dB Bandwidth	12 12 13 14
5		Limits of Test Items	15
	5.1 5.2 5.3 5.4	AC Power Conducted Emissions Radiated Emissions below 1 GHz Radiated Emissions above 1 GHz 20 dB Bandwidth	15 15 16 16
6		Test Arrangements	17
	6.1 6.1.2 6.2 6.2 6.3 6.3 6.3 6.3 6.4 6.4.2	AC Power Conducted Emissions 1 Test Setup 2 Test Procedure Radiated Emissions below 1 GHz 1 Test Setup 2 Test Procedure Radiated Emissions above 1 GHz 1 Test Setup 2 Test Procedure 2 Test Procedure 2 Test Setup 2 Test Procedure 2 Dest Procedure 2 Test Procedure 2 OdB Bandwidth 1 Test Setup 2 Test Procedure 2 Test Procedure 20 dB Bandwidth Test Setup 2 Test Procedure 2 Test Procedure	17 17 18 18 19 20 20 20 21 21 21 21
7		Test Results of Test Item	22
	7.1 7.2 7.3 7.4	AC Power Conducted Emissions Radiated Emissions below 1 GHz Radiated Emissions above 1 GHz 20 dB Bandwidth	22 24 26 31
8		Pictures of Test Arrangements	32
9		Information of the Testing Laboratories	33



Release Control Record

Issue No.	Description	Date Issued
RFBCTR-WTW-P24080501	Original release.	2024/12/10



1 Certificate

Product:	ScreenBar Halo 2 Controller	
Brand:	BenQ	
Test Model:	CR23_C Controller	
Sample Status:	Engineering sample	
Applicant:	BenQ CORPORATION	
Test Date:	2024/9/11 ~ 2024/9/19	
Standard:	47 CFR FCC Part 15, Subpart C (Section 15.249)	
Measurement procedure:	ANSI C63.10-2013	

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.



2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.249)					
Standard / Clause	Test Item	Result	Remark		
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -9.83 dB at 0.46641 MHz		
15.209 / 15.249(d)	Radiated Emissions below 1 GHz	Pass	Minimum passing margin is -13.0 dB at 787.04 MHz		
15.209 / 15.249(a) / 15.249(d) / 15.249(e)	Radiated Emissions above 1 GHz	Pass	Minimum passing margin is -10.0 dB at 2400.00 MHz		
15.215 (c)	20 dB Bandwidth	Pass	Meet the requirement of limit.		
15.203	Antenna Requirement	Pass	No antenna connector is used.		

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
AC Power Conducted Emissions	150 kHz ~ 30 MHz	1.9 dB
Padiatad Emissiana balaw 1 CHz	9 kHz ~ 30 MHz	3.1 dB
Radiated Emissions below 1 GHZ	30 MHz ~ 1 GHz	5.1 dB
Padiated Emissions above 1 CHz	1 GHz ~ 18 GHz	5.0 dB
	18 GHz ~ 40 GHz	5.3 dB
20 dB Bandwidth	-	1050.00 Hz

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.



3 General Information

3.1 General Description

Product	ScreenBar Halo 2 Controller
Brand BenQ	
Test Model	CR23_C Controller
Status of EUT	Engineering sample
Dower Supply Dating	5 Vdc from USB interface;
Power Supply Rating	3.7 Vdc from battery
Modulation Type GFSK	
Modulation Technology	DTS
Transfer Rate	125 kbps
Operating Frequency	2.405 GHz ~ 2.475 GHz
Number of Channel 3	
Field Strength Of	64.8 d Pu/(m (A)) arga) at 2 maters
Fundamental	04.0 ubu v/iii (Avelage) at 5 meters

Note:

1. The EUT could be supplied with a battery as the following table:

Brand	Model	Specification
Guangdong Pow-Tech New Power Co., Ltd	PT803040-A3	Power Rating: 3.7 Vdc, 1000 mAh, 3.7 Wh

2. Qisda Ref. no: AL-31796-1

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
Qisda	CR23	-4.09	2.4~2.4835	PIFA	None

* Due to radiated measurements are made and the antenna gain is already accounted for this device, so provide an antenna datasheet and/or antenna measurement report is not required. The antenna dimensions and pictures (include antenna wire length if have) are stated in EUT photo exhibit.



3.3 Channel List

3 channels are provided to this EUT:

Channel	Frequency	Channel	Frequency
1	2405 MHz	2	2446 MHz
3	2475 MHz		



3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. For Radiated Emissions item have support power supply modes: Battery 3.7V/ USB DC 5V. Pre- scan these modes and find the worst case as a representative test condition.
Worst Case:	1. Radiated emissions item the worst case: USB DC 5V

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Tested Channel	Modulation	Data Rate Parameter
AC Power Conducted Emissions	3	GFSK	125kbps
Radiated Emissions below 1 GHz	3	GFSK	125kbps
Radiated Emissions above 1 GHz	1, 2, 3	GFSK	125kbps
20 dB Bandwidth	1, 2, 3	GFSK	125kbps



3.5 Duty Cycle of Test Signal







3.6 Test Program Used and Operation Descriptions

Controlling software (RF sample button control) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.		Serial No.		Serial No. FC		FCC ID	Remarks
А	Adapter	BenQ	-S15J050K3000UC		00UC N/A		N/A	Supplied by applicant		
ID	Cable Descriptions		Qty.	Ler (r	ngth n)	Shielding (Yes/No)	Cores (Qty.)	Remarks		
1	Type C to C	Cable	1		1	Yes	0	Provided by Lab		



4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance Telegartner	50 ohm	3	2023/10/20	2024/10/19
EMI Test Receiver R&S	ESCS 30	100375	2024/5/20	2025/5/19
Fixed Attenuator STI	STI02-2200-10	005	2024/2/19	2025/2/18
LISN		835239/001	2024/4/3	2025/4/2
R&S	E3H3-Z3	848773/004	2023/10/13	2024/10/12
RF Coaxial Cable JYEBAO	5D-FB	COCCAB-001	2024/2/19	2025/2/18
Software BVADT	BVADT_Cond_V7.3.7.4	N/A	N/A	N/A

Notes:

1. The test was performed in Conduction 1

2. Tested Date: 2024/9/12

4.2 Radiated Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-0842	2023/10/12	2024/10/11
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	N/A	N/A
EMI Test Receiver R&S	ESR7	102026	2024/3/25	2025/3/24
Fixed Attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-02	2024/3/30	2025/3/29
Loop Antenna TESEQ	HLA 6121	63620	2023/10/13	2024/10/12
Preamplifier	EMC330N	980538	2024/3/30	2025/3/29
EMCI	EMC001340	980142	2024/2/19	2025/2/18
PXA Signal Analyzer Keysight	N9030B	MY57141948	2024/5/20	2025/5/19
RF Coaxial Cable		LOOPCAB-001	2024/2/19	2025/2/18
JYEBAO	JD-FD	LOOPCAB-002	2024/2/19	2025/2/18
		966-5-1	2024/3/30	2025/3/29
	8D	966-5-2	2024/3/30	2025/3/29
		966-5-3	2024/3/30	2025/3/29
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A

Notes:

1. The test was performed in 966 Chamber No. 5.

2. Tested Date: 2024/9/11



4.3 Radiated Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	N/A	N/A
Horn Antenna	BBHA 9120D	9120D-2035	2023/11/12	2024/11/11
Schwarzbeck	BBHA 9170	BBHA9170519	2023/11/12	2024/11/11
MXA Signal Analyzer Keysight	N9020B	MY60112410	2024/3/13	2025/3/12
MXE EMI Receiver Keysight	N9038A	MY59050100	2024/6/19	2025/6/18
Preamplifier	EMC12630SE	980385	2024/6/1	2025/5/31
EMCI	EMC184045SE	980387	2024/8/8	2025/8/7
	EMC104-SM-SM-1300	210205	2024/6/1	2025/5/31
RF Coaxiai Cable	EMC104-SM-SM-2000	210203	2024/6/1	2025/5/31
	EMC104-SM-SM-8000	221015	2024/6/1	2025/5/31
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A

Notes:

1. The test was performed in 966 Chamber No. 5.

2. Tested Date: 2024/9/19

Plot of Band Edge

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	N/A	N/A
EMI Test Receiver R&S	ESR7	102026	2024/3/25	2025/3/24
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-1819	2023/11/12	2024/11/11
Preamplifier EMCI	EMC12630SE	980509	2024/1/29	2025/1/28
PXA Signal Analyzer Keysight	N9030B	MY57141948	2024/5/20	2025/5/19
	EMC104-SM-SM-1500	180503	2024/3/16	2025/3/15
RF Coaxial Cable	EMC104-SM-SM-2000	180501	2024/3/16	2025/3/15
	EMC104-SM-SM-6000	180506	2024/3/16	2025/3/15
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A

Notes:

1. The test was performed in 966 Chamber No. 5.

2. Tested Date: 2024/9/11



20 dB Bandwidth 4.4

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
MXA Signal Analyzer Keysight	N9020B	MY60112408	2024/3/7	2025/3/6
Software	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

The test was performed in Oven room 2.
 Tested Date: 2024/9/19



5 Limits of Test Items

5.1 AC Power Conducted Emissions

	Conducted Limit (dBuV)				
	Quasi-peak	Average			
0.15 - 0.5	66 - 56	56 - 46			
0.50 - 5.0	56	46			
5.0 - 30.0	60	50			

Notes:

- 1. The lower limit shall apply at the transition frequencies.
- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.2 Radiated Emissions below 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).



5.3 Radiated Emissions above 1 GHz

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following.

Fundamental	Field Strength of Fundamental	Field Strength of Harmonics		
Frequency	(millivolts/meter)	(microvolts/meter)		
2400 ~ 2483.5 MHz	50	500		

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits as below table, whichever is the lesser attenuation.

Frequencies	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
Above 960	500	3

Notes:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

5.4 20 dB Bandwidth

The 20dB bandwidth shall be specified in operating frequency band.



6 Test Arrangements

6.1 AC Power Conducted Emissions

6.1.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.1.2 Test Procedure

- a. The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit 20 dB) was not recorded.
- Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.



6.2 Radiated Emissions below 1 GHz

6.2.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).



6.2.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
- 2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
- 3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- 2. All modes of operation were investigated and the worst-case emissions are reported.



6.3 Radiated Emissions above 1 GHz

6.3.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

- 6.3.2 Test Procedure
 - a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
 - b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
 - e. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- 1. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- 2. According to ANSI C63.10 section 6.6.4 and 4.1.4.2.2. For fundamental and harmonic signal measurement, according to ANSI C63.10 section 7.5, the average value = peak value + duty cycle correction factor. For duty cycle correction factor values, see the Test Signal Duty Cycle section in this report.
- 3. All modes of operation were investigated and the worst-case emissions are reported.



6.4 20 dB Bandwidth

6.4.1 Test Setup



6.4.2 Test Procedure

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-spectrum system was set to Peak Detect Function and Maximum Hold.
- f. Set resolution bandwidth (RBW) = 1% to 5% of the OBW.
- g. Set the video bandwidth (VBW) \ge 3 x RBW.
- h. Sweep = auto couple.
- i. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.



7 Test Results of Test Item

7.1 AC Power Conducted Emissions

RF Mode	GFSK	Channel	CH 3:2475 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	24 °C, 64 % RH
Tested By	Willy Lin		

	Phase Of Power : Line (L)									
No	Frequency	Correction Factor	Reading Value (dBuV)		Reading Value Emission Level (dBuV) (dBuV)		Limit (dBuV)		Margin (dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	9.94	31.76	17.54	41.70	27.48	65.79	55.79	-24.09	-28.31
2	0.46641	9.95	28.08	26.80	38.03	36.75	56.58	46.58	-18.55	-9.83
3	0.84141	9.98	14.80	12.05	24.78	22.03	56.00	46.00	-31.22	-23.97
4	2.15234	10.06	12.93	10.78	22.99	20.84	56.00	46.00	-33.01	-25.16
5	9.82031	10.64	15.14	7.15	25.78	17.79	60.00	50.00	-34.22	-32.21
6	25.29688	11.51	31.42	15.96	42.93	27.47	60.00	50.00	-17.07	-22.53

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value





RF Mode	GFSK	Channel	CH 3:2475 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function &	Quasi-Peak (QP) /
		Resolution Bandwidth	Average (AV), 9 KHZ
Input Power	120 Vac. 60 Hz	Environmental	24 °C 64 % BH
(System)		Conditions	
Tested By	Willy Lin		

	Phase Of Power : Neutral (N)									
No	Frequency	Correction Factor	Readin (dB	g Value suV)	Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.01	31.86	16.78	41.87	26.79	65.79	55.79	-23.92	-29.00
2	0.46641	10.02	31.69	25.40	41.71	35.42	56.58	46.58	-14.87	-11.16
3	0.88828	10.04	16.53	12.11	26.57	22.15	56.00	46.00	-29.43	-23.85
4	5.45703	10.31	13.48	6.47	23.79	16.78	60.00	50.00	-36.21	-33.22
5	9.85156	10.58	15.36	8.61	25.94	19.19	60.00	50.00	-34.06	-30.81
6	25.27344	11.15	32.32	22.82	43.47	33.97	60.00	50.00	-16.53	-16.03

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value





7.2 Radiated Emissions below 1 GHz

RF Mode	GFSK	Channel	CH 3:2475 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	21 °C, 61 % RH
Tested By	Willy Lin		

	Antenna Polarity & Test Distance : Horizontal at 3 m									
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)		
1	52.80	19.5 QP	40.0	-20.5	1.00 H	8	32.0	-12.5		
2	151.93	20.7 QP	43.5	-22.8	3.00 H	75	32.9	-12.2		
3	327.98	22.3 QP	46.0	-23.7	3.00 H	334	33.1	-10.8		
4	554.48	26.5 QP	46.0	-19.5	4.00 H	64	32.3	-5.8		
5	663.53	29.9 QP	46.0	-16.1	3.00 H	1	33.5	-3.6		
6	892.82	31.9 QP	46.0	-14.1	4.00 H	242	32.2	-0.3		

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. Margin value = Emission Level Limit value
- 4. The other emission levels were very low against the limit of frequency range 30 MHz \sim 1 GHz.
- 5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.





RF Mode	GFSK	Channel	CH 3:2475 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	21 °C, 61 % RH
Tested By	Willy Lin		

	Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	61.23	23.7 QP	40.0	-16.3	1.00 V	360	37.0	-13.3	
2	138.30	21.1 QP	43.5	-22.4	3.00 V	147	33.9	-12.8	
3	398.96	23.0 QP	46.0	-23.0	4.00 V	326	32.3	-9.3	
4	661.28	28.3 QP	46.0	-17.7	4.00 V	1	32.0	-3.7	
5	787.04	33.0 QP	46.0	-13.0	2.00 V	300	34.3	-1.3	
6	890.15	31.8 QP	46.0	-14.2	1.00 V	40	32.1	-0.3	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. Margin value = Emission Level Limit value
- 4. The other emission levels were very low against the limit of frequency range 30 MHz \sim 1 GHz.
- 5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.





7.3 Radiated Emissions above 1 GHz

RF Mode	GFSK	Channel	CH 1:2405 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	21 °C, 64 % RH
Tested By	Willy Lin		

	Antenna Polarity & Test Distance : Horizontal at 3 m									
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)		
1	2400.00	54.9 PK	74.0	-19.1	1.13 H	309	58.5	-3.6		
2	2400.00	43.7 AV	54.0	-10.3	1.13 H	309	47.3	-3.6		
3	*2405.00	89.1 PK	114.0	-24.9	1.13 H	309	92.7	-3.6		
4	*2405.00	61.6 AV	94.0	-32.4	1.13 H	309	65.2	-3.6		
5	4810.00	38.5 PK	74.0	-35.5	1.49 H	113	36.8	1.7		
6	4810.00	11.0 AV	54.0	-43.0	1.49 H	113	9.3	1.7		
7	7215.00	42.1 PK	74.0	-31.9	1.52 H	255	34.8	7.3		
8	7215.00	14.6 AV	54.0	-39.4	1.52 H	255	7.3	7.3		

	Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	2400.00	55.6 PK	74.0	-18.4	3.96 V	178	59.2	-3.6	
2	2400.00	44.0 AV	54.0	-10.0	3.96 V	178	47.6	-3.6	
3	*2405.00	92.1 PK	114.0	-21.9	3.96 V	178	95.7	-3.6	
4	*2405.00	64.6 AV	94.0	-29.4	3.96 V	178	68.2	-3.6	
5	4810.00	37.6 PK	74.0	-36.4	1.53 V	220	35.9	1.7	
6	4810.00	10.1 AV	54.0	-43.9	1.53 V	220	8.4	1.7	
7	7215.00	41.2 PK	74.0	-32.8	1.48 V	158	33.9	7.3	
8	7215.00	13.7 AV	54.0	-40.3	1.48 V	158	6.4	7.3	

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

3. Margin value = Emission Level – Limit value

4. The other emission levels were very low against the limit.

- 5. " * ": Fundamental frequency.
- The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
 20 log(Duty cycle) = 20 log(2.135 ms / 50.68 ms) = -27.5 dB

Report No.: RFBCTR-WTW-P24080501



RF Mode	GFSK	Channel	CH 2:2446 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	21 °C, 64 % RH
Tested By	Willy Lin		

	Antenna Polarity & Test Distance : Horizontal at 3 m							
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2446.00	88.6 PK	114.0	-25.4	1.12 H	301	92.0	-3.4
2	*2446.00	61.1 AV	94.0	-32.9	1.12 H	301	64.5	-3.4
3	4892.00	38.1 PK	74.0	-35.9	1.46 H	113	36.6	1.5
4	4892.00	10.6 AV	54.0	-43.4	1.46 H	113	9.1	1.5
5	7338.00	42.6 PK	74.0	-31.4	1.49 H	258	34.8	7.8
6	7338.00	15.1 AV	54.0	-38.9	1.49 H	258	7.3	7.8
			Antenna Pola	rity & Test Dis	stance : Vertic	al at 3 m		
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2446.00	91.8 PK	114.0	-22.2	3.84 V	165	95.2	-3.4
2	*2446.00	64.3 AV	94.0	-29.7	3.84 V	165	67.7	-3.4
3	4892.00	37.3 PK	74.0	-36.7	1.53 V	221	35.8	1.5
4	4892.00	9.8 AV	54.0	-44.2	1.53 V	221	8.3	1.5
5	7338.00	41.6 PK	74.0	-32.4	1.47 V	149	33.8	7.8
6	7338.00	14.1 AV	54.0	-39.9	1.47 V	149	6.3	7.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

3. Margin value = Emission Level – Limit value

4. The other emission levels were very low against the limit.

5. " * ": Fundamental frequency.

The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
 20 log(Duty cycle) = 20 log(2.135 ms / 50.68 ms) = -27.5 dB

Report No.: RFBCTR-WTW-P24080501



RF Mode	GFSK	Channel	CH 3:2475 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	21 °C, 64 % RH
Tested By	Willy Lin		

Antenna Polarity & Test Distance : Horizontal at 3 m									
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	*2475.00	89.3 PK	114.0	-24.7	1.14 H	306	92.7	-3.4	
2	*2475.00	61.8 AV	94.0	-32.2	1.14 H	306	65.2	-3.4	
3	2483.50	53.9 PK	74.0	-20.1	1.14 H	306	57.3	-3.4	
4	2483.50	43.9 AV	54.0	-10.1	1.14 H	306	47.3	-3.4	
5	4950.00	38.6 PK	74.0	-35.4	1.55 H	105	37.0	1.6	
6	4950.00	11.1 AV	54.0	-42.9	1.55 H	105	9.5	1.6	
7	7425.00	42.5 PK	74.0	-31.5	1.53 H	240	34.8	7.7	
8	7425.00	15.0 AV	54.0	-39.0	1.53 H	240	7.3	7.7	
Antenna Polarity & Test Distance : Vertical at 3 m									
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	

No	(MHz)	(dBuV/m)	(dBuV/m)	(dB)	(m)	(Degree)	(dBuV)	(dB/m)
1	*2475.00	92.3 PK	114.0	-21.7	3.67 V	142	95.7	-3.4
2	*2475.00	64.8 AV	94.0	-29.2	3.67 V	142	68.2	-3.4
3	2483.50	53.8 PK	74.0	-20.2	3.67 V	142	57.2	-3.4
4	2483.50	43.8 AV	54.0	-10.2	3.67 V	142	47.2	-3.4
5	4950.00	37.4 PK	74.0	-36.6	1.50 V	228	35.8	1.6
6	4950.00	9.9 AV	54.0	-44.1	1.50 V	228	8.3	1.6
7	7425.00	42.6 PK	74.0	-31.4	1.46 V	143	34.9	7.7
8	7425.00	15.1 AV	54.0	-38.9	1.46 V	143	7.4	7.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

3. Margin value = Emission Level – Limit value

4. The other emission levels were very low against the limit.

5. " * ": Fundamental frequency.

The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
 20 log(Duty cycle) = 20 log(2.135 ms / 50.68 ms) = -27.5 dB



Plot of Band Edge



7.4 20 dB Bandwidth

Input Power:	3.7 Vdc		Environmental Conditions:	25°C, 60% RH		Tested By:	Willy Lin	
	Channel	20 dB Bandwidth (MHz)	Measured Frequencies			victing Frequency		
Channel	Frequency (MHz)		FL (MHz)	FH (MHz)	(MHz)			Test Result
1	2405	0.4	2404.8	2405.2		2400 ~ 2483.5		Pass
2	2446	0.41	2445.79	2446.2				Pass
3	2475	0.4	2474.8	2475.2				Pass

Notes:

1. FL is the lowest frequency of the 20 dB bandwidth of power envelope.

2. FH is the highest frequency of the 20 dB bandwidth of power envelope.

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab Tel: 886-2-26052180 Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <u>service.adt@bureauveritas.com</u> Web Site: <u>http://ee.bureauveritas.com.tw</u>

The address and road map of all our labs can be found in our web site also.

--- END ---