

FCC Test Report

Report No.: AGC00137240903FR02

FCC ID	:	2AJIV-EF1240
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Creative Aurvana Ace 3
BRAND NAME	:	CREATIVE
MODEL NAME	:	EF1240
APPLICANT	:	Creative Labs Pte. Ltd.
DATE OF ISSUE	:	Nov. 22, 2024
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov. 22, 2024	Valid	Initial Release



Table of Contents

1. General Information	5
2. Product Information	
2.1 Product Technical Description	
2.2 Test Frequency List	
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Special Accessories	7
2.6 Equipment Modifications	7
2.7 Antenna Requirement	7
3. Test Environment	
3.1 Address of the Test Laboratory	
3.2 Test Facility	
3.3 Environmental Conditions	
3.4 Measurement Uncertainty	
3.5 List of Equipment Use	
4. System Test Configuration	12
4.1 EUT Configuration	
4.2 EUT Exercise	
4.3 Configuration of Tested System	
4.4 Equipment Used In Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	14
6. Duty Cycle Measurement	
7. RF Output Power Measurement	
7.1 Provisions Applicable	
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Result	
8. 6dB Bandwidth Measurement	
8.1 Provisions Applicable	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
8.4 Measurement Results	
9. Power Spectral Density Measurement	
9.1 Provisions Applicable	
9.2 Measurement Procedure	
9.3 Measurement Setup (Block Diagram of Configuration)	
9.4 Measurement Results	
10. Conducted Band Edge and Out-of-Band Emissions	



10.1 Provisions Applicable	
10.2 Measurement Procedure	
10.3 Measurement Setup (Block Diagram of Configuration)	
10.4 Measurement Results	
11. Radiated Spurious Emission	50
11.1 Measurement Limit	
11.2 Measurement Procedure	
11.3 Measurement Setup (Block Diagram of Configuration)	53
11.4 Measurement Result	54
12. AC Power Line Conducted Emission Test	67
12.1 Measurement Limit	67
12.2 Measurement Setup (Block Diagram of Configuration)	67
12.3 Preliminary Procedure of Line Conducted Emission Test	
12.4 Final Procedure of Line Conducted Emission Test	
12.5 Measurement Results	
Appendix I: Photographs of Test Setup	69
Appendix II: Photographs of Test EUT	69



1. General Information


Applicant	Creative Labs Pte. Ltd.
Address	31 International Business Park, #03-01 Singapore 609921, Singapore
Manufacturer	Creative Labs Pte. Ltd.
Address	31 International Business Park, #03-01 Singapore 609921, Singapore
Factory	N/A
Address	N/A
Product Designation	Creative Aurvana Ace 3
Brand Name	CREATIVE
Test Model	EF1240
Series Model(s)	N/A
Difference Description	N/A
Date of receipt of test item	Oct. 22, 2024
Date of Test	Oct. 22, 2024 to Nov. 21, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BLE-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Thea Huang Prepared By Thea Huang Nov. 22, 2024 (Project Engineer) Calvin Lin **Reviewed By** Calvin Liu Nov. 22, 2024 (Reviewer) Approved By Angela Li

(Authorized Officer)

Nov. 22, 2024





2. Product Information

2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.4
Modulation Type	BLE GFSK 1Mbps GFSK 2Mbps
Number of channels	40 Channels
Carrier Frequency of Each Channel	40 Channels (37 Data channels + 3 advertising channels)
Channel Separation	2 MHz
Maximum Transmitter Power	Right earbud: BLE GFSK 1Mbps: 0.376dBm BLE GFSK 2Mbps: 0.593dBm Left earbud: BLE GFSK 1Mbps: 1.274dBm BLE GFSK 2Mbps: 1.339dBm
Hardware Version	V2.0
Software Version	V0.2
Antenna Designation	FPC Antenna
Antenna Gain	Right earbud: 2.39dBi Left earbud: 1.84dBi
Power Supply	DC 3.7V by battery or DC 5V by adapter or DC 5V by wireless charging
Note:	

Note:

The EUT comprises left and right channel earbuds, both are the same. The RF output power of each earbud has been tested and recorded in the report. For other test items, the left earbud has been tested and recorded in this report, which is the worst case.

2.2 Test Frequency List

Frequency Band	Channel Number	Frequency			
	0	2402 MHz			
	1	2404 MHz			
2400~2483.5MHz	:	:			
	19	2440MHz			
	:	:			
	38	2478 MHz			
	39	2480 MHz			
Note: f = 2402 + 2*k MHz, k = 0,, 39 f is the operating frequency (MHz); k is the operating channel.					



2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2AJIV-EF1240**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

2.5 Special Accessories

Not available for this EUT intended for grant.

2.6 Equipment Modifications

Not available for this EUT intended for grant.

2.7 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The right earphone gain of the antenna is 2.39dBi. The left earphone gain of the antenna is 1.84dBi.



3. Test Environment

3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.7V

3.4 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	U _c = ±2 %
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %



3.5 List of Equipment Use

• R	RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
\boxtimes	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23	
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31	
	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31	
\boxtimes	AGC-EM-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-09-21	2025-09-20	
	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22	
	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A	
\boxtimes	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A	

• R	Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
\boxtimes	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31	
	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30	
\boxtimes	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23	
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03	
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23	
\boxtimes	AGC-EM-A119	2.4GHz Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22	
\square	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	

• A	AC Power Line Conducted Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27	
	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08	
	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27	



Test Software							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information		
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71		
\boxtimes	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A		
	AGC-EM-S004	RE Test System	Tonscend	TS ⁺ Ver2.1(JS32-RE)	4.0.0.0		
\boxtimes	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6		
	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0		



4. System Test Configuration

4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable		
1	Control board	Control board TRBI200					
	Test Accessories Come From The Manufacturer						
No.	o. Equipment Manufacturer Model No. Specification Information				Cable		
1							



4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(3)	RF Output Power	Pass
3	§15.247 (a)(2)	6 dB Bandwidth	Pass
4	§15.247 (e)	Power Spectral Density	Pass
5	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
6	§15.209	Radiated Emission& Band Edge	Pass
7	§15.207	AC Power Line Conducted Emission	Not applicable

Note: The BT function cannot transmit when charging.



5. Description of Test Modes

	Summary Table of Test Cases					
	Data Rate / Modulation					
Test Item	Bluetooth – LE(1Mbps/2Mbps) / GFSK					
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps(Battery powered)					
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps(Battery powered)					
Radiated & Conducted	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps(Battery powered)					
Test Cases	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps(Battery powered)					
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps(Battery powered)					
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps(Battery powered)					
AC Conducted Emission	Not applicable					
 The battery is full-cha For Radiated Emission 	on, 3axis were chosen for testing for each applicable mode. nethod, a temporary antenna connector is provided by the manufacture.					
I	Image: Software Setting Diagram Image: Software Setting Diagram					
	Set Freq. Trims Bit pattern Fseudo-rdm 9 Execute Set PIO PHY 2M Execute Read PIO PHY 2M Reset					
	Test Results Save to file Browse for f Display : © Standard C BER C:\Wsers\AGC-dianchi\AppData\Local\QTIL\BlueTest3\testapplog.txt BLE TEST TX successful BLE TEST TX successful BLE TEST TX successful WARNING: The 2M PHY option is not supported for channels 0, 12 and 39 in end user scenarios, as per the BT specification. Therefore, product certification testing should not be performed with the 2M PHY on these channels. BLE TEST TX successful					

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

v

channels.

BLE TEST TX successful




6. Duty Cycle Measurement

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
BLE_1Mbps	400	63.49	1.97	2.5
BLE_2Mbps	220	35.48	4.5	4.55

Remark:

2. The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value



The test plots as follows:

^{1.} Duty Cycle factor = 10 * log (1/ Duty cycle)



7. RF Output Power Measurement

7.1 Provisions Applicable

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.


7.2 Measurement Procedure

For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.1 Method Max peak power:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the RBW≥DTS bandwidth
- 3. Set the VBW \geq [3 × RBW].
- 4. Span≥[3 x RBW].
- 5. Sweep= auto couple.
- 6. Detector Function= Peak.
- 7. Trace mode= Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

7.3 Measurement Setup (Block Diagram of Configuration)

For peak power test setup






7.4 Measurement Result

Right earbud:


Test Data of Conducted Output Power							
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail			
	2402	0.376	≤30	Pass			
GFSK_1Mbps	2440	0.201	≤30	Pass			
	2480	-0.095	≤30	Pass			
	2402	0.593	≤30	Pass			
GFSK_2Mbps	2440	0.146	≤30	Pass			
	2480	-0.250	≤30	Pass			






Test Graphs of Conducted Output Power












Left earbud:


Test Data of Conducted Output Power							
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail			
	2402	1.152	≤30	Pass			
GFSK_1Mbps	2440	1.035	≤30	Pass			
	2480	1.274	≤30	Pass			
	2402	1.128	≤30	Pass			
GFSK_2Mbps	2440	1.093	≤30	Pass			
	2480	1.339	≤30	Pass			






Test Graphs of Conducted Output Power











8. 6dB Bandwidth Measurement

8.1 Provisions Applicable


The minimum 6 dB bandwidth shall be 500 kHz.

8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).

- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 5. Measure and record the results in the test report.

8.3 Measurement Setup (Block Diagram of Configuration)






8.4 Measurement Results

Test Data of Occupied Bandwidth and DTS Bandwidth							
Test Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	DTS BW (MHz)	DTS BW Limits	Pass or Fail		
	2402	1.048	0.715	≥0.5	Pass		
GFSK_1Mbps	2440	1.049	0.719	≥0.5	Pass		
	2480	1.047	0.719	≥0.5	Pass		
	2402	2.062	1.213	≥0.5	Pass		
GFSK_2Mbps	2440	2.062	1.213	≥0.5	Pass		
	2480	2.060	1.258	≥0.5	Pass		

Test Graphs of Occupied Bandwidth


























Test Graphs of DTS Bandwidth











9. Power Spectral Density Measurement

9.1 Provisions Applicable


The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

9.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.

- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz in order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 5. Measure and record the results in the test report.
- The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

9.3 Measurement Setup (Block Diagram of Configuration)







9.4 Measurement Results

Test Data of Conducted Output Power Spectral Density							
Test Mode	Test Frequency (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail			
	2402	-14.448	≤8	Pass			
GFSK_1Mbps	2440	-14.591	≤8	Pass			
	2480	-14.283	≤8	Pass			
	2402	-18.070	≤8	Pass			
GFSK_2Mbps	2440	-18.066	≤8	Pass			
	2480	-17.674	≤8	Pass			


Test Graphs of Conducted Output Power Spectral Density


















10. Conducted Band Edge and Out-of-Band Emissions

10.1 Provisions Applicable


The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

10.2 Measurement Procedure

- Reference level measurement
- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to \geq 1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- 4. Set the VBW \geq 3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Allow trace to fully stabilize
- Emission level measurement
- 1. Set the center frequency and span to encompass frequency range to be measured
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize

10.3 Measurement Setup (Block Diagram of Configuration)

Spectrum Analyzer






10.4 Measurement Results




Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands

Any report having not esting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.










































Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands







11. Radiated Spurious Emission

11.1 Measurement Limit

FCC Part 15.209 Limit in the below table to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.



As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
	1MHz/3MHz for Peak, 1MHz/3MHz for Average

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP



• Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize


<u>Average Measurements above 1GHz</u>

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW \geq [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- The applicable correction factor is [10*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




11.3 Measurement Setup (Block Diagram of Configuration)






Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com




11.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

			Radia	ted Emiss	ion Test Res	ults at 30MHz	z-1GHz		
EUT N	lame	Cre	Creative Aurvana Ace 3				me	EF1240	
Tempe	erature	23.1°C Relative Humidity				56.2%			
Press	ure	960hPa Test Voltage Normal Voltage			ltage				
Test M	lode	Mod	de 6			Antenna	Antenna Polarity Horizontal		
	72.0	dBuV/π	1						
		straat the		annan marin		And	A. M.	Limit: — Margin: —	
	-8 30.00	00 4	0 50 60 70	80	(MHz)	300	400 500 60	0 700 1000.00	00
Final D	Data List								
NO.	Freq [MHz		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	39.714	46	19.36	13.78	40.00	20.64	100	100	Horizontal
2	101.64	43	22.12	16.22	43.50	21.38	100	210	Horizontal
3	129.01	46	22.07	15.86	43.50	21.43	100	205	Horizontal
4	449.55	58	30.38	24.77	46.00	15.62	100	180	Horizontal
5	601.42	65	31.05	25.11	46.00	14.95	100	161	Horizontal
6	903.30	94	36.97	31.34	46.00	9.03	100	120	Horizontal





		Radia	ted Emiss	ion Test Resu	ults at 30MH	z-1GHz		
EUT Na	me C	Creative Aurvana Ace 3				ame	EF1240	
Temper	ature 23	23.1℃			Relative	Relative Humidity 56.2%		
Pressur	r e 96	60hPa			Test Volt	age	Normal Vo	ltage
Test Mo	ode M	lode 6			Antenna	Polarity	Vertical	
	72.0 dBu\	√/m					·	
	-8	40 50 60 70		X X (MHz)			.imit: Aargin: 	0
Final Da			Factor	Limit	Morgin	Hoight	Anglo	
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	[dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	69.3568	24.90	17.01	40.00	15.1	100	100	Vertical
	143.8295	25.48	18.20	43.50	18.02	100	210	Vertical
2	143.0295			10.00	10.20	100	205	
2 3	323.3204	26.61	20.18	46.00	19.39		200	Vertical
		26.61 31.96	20.18 25.60	46.00 46.00	14.04	100	180	Vertical Vertical
3	323.3204							

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin= Limit-Level.

2. All test modes had been pre-tested. The mode 6 is the worst case and recorded in the report.



EUT Name	Creative Aur	Creative Aurvana Ace 3				EF1240)
Temperature	23.1 ℃		Re	Relative Humidity Test Voltage		56.2% Normal Voltage	
Pressure	960hPa		Те				
Fest Mode	Mode 4	Mode 4		ntenna Polarity		Horizon	ital
Frequency	Meter Reading	Factor	Emission Lev	el Limits		Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)		(dB)	value Type
4804.000	46.26	0.08	46.34	74		-27.66	peak
4804.000	37.44	0.08	37.52	54		-16.48	AVG
7206.000	42.53	2.21	44.74	74		-29.26	peak
7206.000	34.82	2.21	37.03	54		-16.97	AVG
Remark:							
Eactor = Anter	nna Factor + Cabl		a manalifi a m				
		e Loss – Pre-	amplifier.				
EUT Name	Creative Aur			odel Name		EF1240)
			M	odel Name elative Humidity		EF1240 56.2%)
EUT Name	Creative Aur		Re			56.2%) Voltage
EUT Name Femperature Pressure	Creative Aur 23.1℃		Ma Re Te	elative Humidity		56.2%	Voltage
EUT Name Femperature Pressure Fest Mode	Creative Aur 23.1℃ 960hPa Mode 4	vana Ace 3	Ma Re Te Ar	elative Humidity st Voltage ntenna Polarity		56.2% Normal Vertical	Voltage
EUT Name Femperature Pressure Fest Mode	Creative Aur 23.1℃ 960hPa Mode 4 Meter Reading	vana Ace 3	Ma Re Te Ar Emission Lev	elative Humidity st Voltage ntenna Polarity rel Limits		56.2% Normal Vertical	Voltage
EUT Name Temperature Pressure Test Mode Frequency (MHz)	Creative Aur 23.1℃ 960hPa Mode 4 Meter Reading (dBµV)	vana Ace 3 Factor (dB)	Ma Re Te Ar Emission Lev (dBµV/m)	elative Humidity st Voltage ntenna Polarity /el Limits (dBµV/m)		56.2% Normal Vertical Margin (dB)	Voltage Value Type
EUT Name Femperature Pressure Fest Mode Frequency (MHz) 4804.000	Creative Aur 23.1°C 960hPa Mode 4 Meter Reading (dBµV) 45.61	Vana Ace 3 Factor (dB) 0.08	Ma Re Te Ar Emission Lev (dBµV/m) 45.69	elative Humidity st Voltage ntenna Polarity /el Limits (dBµV/m) 74		56.2% Normal Vertical Margin (dB) -28.31	Voltage Value Type peak
EUT Name Femperature Fressure Frequency (MHz) 4804.000	Creative Aur 23.1℃ 960hPa Mode 4 Meter Reading (dBµV) 45.61 37.51	Vana Ace 3 Factor (dB) 0.08 0.08	Ма Re Те Аг Етти Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Аг Сте Аг Аг Аг Аг Аг Аг Аг Аг Аг Аг	elative Humidity st Voltage ntenna Polarity ////////////////////////////////////		56.2% Normal Vertical Margin (dB) -28.31 -16.41	Voltage Value Type peak AVG
EUT Name Femperature Fressure Fest Mode Frequency (MHz) 4804.000 4804.000 7206.000	Creative Aur 23.1℃ 960hPa Mode 4 Meter Reading (dBµV) 45.61 37.51 43.28	Vana Ace 3 Factor (dB) 0.08 0.08 2.21	Ма Re Те Аг Еттерности (dBµV/m) 45.69 37.59 45.49	elative Humidity st Voltage ntenna Polarity ////////////////////////////////////		56.2% Normal Vertical Margin (dB) -28.31 -16.41 -28.51	Voltage Value Type peak AVG peak
EUT Name Femperature Pressure Fest Mode Frequency (MHz) 4804.000 4804.000	Creative Aur 23.1℃ 960hPa Mode 4 Meter Reading (dBµV) 45.61 37.51	Vana Ace 3 Factor (dB) 0.08 0.08	Ма Re Те Аг Етти Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Сте Аг Аг Сте Аг Аг Аг Аг Аг Аг Аг Аг Аг Аг	elative Humidity st Voltage ntenna Polarity ////////////////////////////////////		56.2% Normal Vertical Margin (dB) -28.31 -16.41	Voltage Value Type peak AVG
EUT Name Temperature Pressure Test Mode Frequency (MHz) 4804.000 4804.000 7206.000	Creative Aur 23.1℃ 960hPa Mode 4 Meter Reading (dBµV) 45.61 37.51 43.28	Vana Ace 3 Factor (dB) 0.08 0.08 2.21	Ма Re Те Аг Еттерности (dBµV/m) 45.69 37.59 45.49	elative Humidity st Voltage ntenna Polarity ////////////////////////////////////		56.2% Normal Vertical Margin (dB) -28.31 -16.41 -28.51	Voltage Value Type peak AVG peak

Radiated Emissions Test Results Above 1GHz

RESULT: Pass



EUT Name	Creative Aur	rvana Ace 3	Mod	el Name	EF12	240	
Temperature	23.1 ℃		Rela	tive Humidity	56.2	56.2%	
Pressure	960hPa		Test	Test Voltage		Normal Voltage	
Test Mode	Mode 5	Mode 5 Antenna Polarity		Horiz	zontal		
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4880.000	47.09	0.14	47.23	74	-26.77	peak	
4880.000	38.17	0.14	38.31	54	-15.69	AVG	
7320.000	44.62	2.36	46.98	74	-27.02	peak	
7320.000	34.91	2.36	37.27	54	-16.73	AVG	
David							
Remark:							
	nna Factor + Cabl	e Loss – Pre-	amplifier.				
Factor = Ante	nna Factor + Cabl			el Name	EF12	240	
			Mod	el Name tive Humidity			
Factor = Ante EUT Name Femperature	Creative Aur		Mod Rela		56.2		
Factor = Ante EUT Name Femperature Pressure	Creative Aur 23.1℃		Mod Rela Test	tive Humidity	56.2	% nal Voltage	
Factor = Ante	Creative Aur 23.1°C 960hPa Mode 5	rvana Ace 3	Mod Rela Test Ante	tive Humidity Voltage enna Polarity	56.2 Norn Verti	% nal Voltage	
Factor = Ante	Creative Aur 23.1 °C 960hPa Mode 5 Meter Reading	rvana Ace 3	Mod Rela Test Ante	tive Humidity Voltage enna Polarity	56.2 Norn Verti Margin	% nal Voltage	
Factor = Ante EUT Name Femperature Pressure Fest Mode Frequency (MHz)	Creative Aur 23.1℃ 960hPa Mode 5 Meter Reading (dBµV)	vana Ace 3 Factor (dB)	Mod Rela Test Ante Emission Level (dBµV/m)	tive Humidity Voltage enna Polarity Limits (dBµV/m)	56.2 Norn Verti Margin (dB)	% nal Voltage cal Value Type	
Factor = Ante EUT Name Temperature Pressure Test Mode Frequency (MHz) 4880.000	Creative Aur 23.1℃ 960hPa Mode 5 Meter Reading (dBµV) 44.92	Factor (dB) 0.14	Mod Rela Test Ante (dBµV/m) 45.06	tive Humidity Voltage enna Polarity Limits (dBµV/m) 74	56.2 Norn Verti Margin (dB) -28.94	% nal Voltage cal Value Type peak	
Factor = Ante EUT Name Femperature Pressure Test Mode Frequency (MHz) 4880.000 4880.000	Creative Aur 23.1 °C 960hPa Mode 5 Meter Reading (dBµV) 44.92 39.08	Factor (dB) 0.14 0.14	Мос Rela Теst Ante Emission Level (dBµV/m) 45.06 39.22	tive Humidity Voltage enna Polarity Limits (dBµV/m) 74 54	56.2 Norn Verti Margin (dB) -28.94 -14.78	% nal Voltage cal Value Type peak AVG	
Factor = Ante EUT Name Femperature Pressure Test Mode Frequency (MHz) 4880.000 7320.000	Creative Aur 23.1 °C 960hPa Mode 5 Meter Reading (dBµV) 44.92 39.08 43.17	Factor (dB) 0.14 0.14 2.36	Мос Rela Теst Ante Emission Level (dBµV/m) 45.06 39.22 45.53	tive Humidity Voltage enna Polarity Limits (dBµV/m) 74 54 74	56.2 Norn Verti Margin (dB) -28.94 -14.78 -28.47	% nal Voltage cal Value Type peak AVG peak	
Factor = Ante EUT Name Temperature Pressure Test Mode Frequency (MHz) 4880.000 4880.000	Creative Aur 23.1 °C 960hPa Mode 5 Meter Reading (dBµV) 44.92 39.08	Factor (dB) 0.14 0.14	Мос Rela Теst Ante Emission Level (dBµV/m) 45.06 39.22	tive Humidity Voltage enna Polarity Limits (dBµV/m) 74 54	56.2 Norn Verti Margin (dB) -28.94 -14.78	% nal Voltage cal Value Type peak AVG	
Factor = Ante EUT Name Femperature Pressure Test Mode Frequency (MHz) 4880.000 7320.000	Creative Aur 23.1 °C 960hPa Mode 5 Meter Reading (dBµV) 44.92 39.08 43.17	Factor (dB) 0.14 0.14 2.36	Мос Rela Теst Ante Emission Level (dBµV/m) 45.06 39.22 45.53	tive Humidity Voltage enna Polarity Limits (dBµV/m) 74 54 74	56.2 Norn Verti Margin (dB) -28.94 -14.78 -28.47	% nal Voltage cal Value Type peak AVG peak	
Factor = Ante EUT Name Femperature Pressure Fest Mode Frequency (MHz) 4880.000 7320.000	Creative Aur 23.1 °C 960hPa Mode 5 Meter Reading (dBµV) 44.92 39.08 43.17	Factor (dB) 0.14 0.14 2.36	Мос Rela Теst Ante Emission Level (dBµV/m) 45.06 39.22 45.53	tive Humidity Voltage enna Polarity Limits (dBµV/m) 74 54 74	56.2 Norn Verti Margin (dB) -28.94 -14.78 -28.47	% nal Voltage cal Value Type peak AVG peak	

Radiated Emissions Test Results for Above 1GHz

RESULT: Pass

JT Name	Creative Aur	Creative Aurvana Ace 3			Name	EF1240		
emperature	23.1 ℃	23.1 ℃		Relative Humidity		56.2%	56.2%	
essure	960hPa			Test Voltage		Normal	Normal Voltage	
est Mode	Mode 6			Anten	na Polarity	Horizont	al	
			1					
Frequency	Meter Reading	Factor	Emissio	on Level	Limits	Margin		
(MHz)	(dBµV)	(dB)	(dBµ'	V/m)	(dBµV/m)	(dB)	Value Type	
4960.000	48.49	0.22	48.	.71	74	-25.29	peak	
4960.000	36.12	0.22	36.	.34	54	-17.66	AVG	
7440.000	41.93	2.64	44.	.57	74	-29.43	peak	
7440.000	34.57	2.64	37.	.21	54	-16.79	AVG	
Remark:								
	nna Factor + Cabl	e Loss – Pre-	amplifier.					
	nna Factor + Cabl		amplifier.	Model	Name	EF1240		
Factor = Anter			amplifier.		Name ve Humidity	EF1240 56.2%		
Factor = Anter	Creative Aur		amplifier.		ve Humidity		/oltage	
Factor = Anter	Creative Aur 23.1℃		amplifier.	Relativ Test V	ve Humidity	56.2%	/oltage	
Factor = Anter	Creative Aur 23.1℃ 960hPa Mode 6	vana Ace 3		Relativ Test V Anten	ve Humidity oltage na Polarity	56.2% Normal Vertical		
Factor = Anter	Creative Auro 23.1 °C 960hPa Mode 6		Emissio	Relativ Test V Anten	ve Humidity oltage na Polarity Limits	56.2% Normal V Vertical Margin		
Factor = Anter	Creative Aur 23.1℃ 960hPa Mode 6 Meter Reading (dBµV)	vana Ace 3 Factor	Emissic (dBµ	Relativ Test V Anten on Level V/m)	ve Humidity oltage na Polarity Limits (dBµV/m)	56.2% Normal Vertical Margin (dB)	1	
Factor = Anter JT Name emperature ressure est Mode Frequency (MHz) 4960.000	Creative Aur 23.1℃ 960hPa Mode 6 Meter Reading (dBµV) 51.47	Factor (dB) 0.22	Emissic (dBµ 51.	Relativ Test V Anten on Level V/m) 69	ve Humidity oltage na Polarity Limits (dBµV/m) 74	56.2% Normal V Vertical Margin (dB) -22.31	Value Type	
Factor = Anter JT Name emperature ressure est Mode Frequency (MHz) 4960.000 4960.000	Creative Aur 23.1℃ 960hPa Mode 6 Meter Reading (dBµV) 51.47 43.29	Factor (dB) 0.22 0.22	Emissic (dBµ 51. 43.	Relativ Test V Anten on Level V/m) 69 51	ve Humidity oltage na Polarity Limits (dBµV/m) 74 54	56.2% Normal Vertical Margin (dB) -22.31 -10.49	- Value Type peak	
Factor = Anter JT Name emperature ressure est Mode Frequency (MHz) 4960.000 7440.000	Creative Aur 23.1℃ 960hPa Mode 6 Meter Reading (dBµV) 51.47 43.29 39.51	Factor (dB) 0.22	Emissic (dBµ 51.	Relativ Test V Anten on Level V/m) 69 51 15	ve Humidity oltage na Polarity Limits (dBµV/m) 74	56.2% Normal Vertical Vertical (dB) -22.31 -10.49 -31.85	- Value Type peak AVG	
Factor = Anter JT Name emperature ressure est Mode Frequency (MHz) 4960.000 4960.000	Creative Aur 23.1℃ 960hPa Mode 6 Meter Reading (dBµV) 51.47 43.29	Vana Ace 3 Factor (dB) 0.22 0.22 2.64	Emissio (dBµ' 51. 43. 42.	Relativ Test V Anten on Level V/m) 69 51 15	ve Humidity oltage na Polarity Limits (dBµV/m) 74 54 74	56.2% Normal Vertical Margin (dB) -22.31 -10.49	- Value Type peak AVG peak	

Radiated Emissions Test Results for Above 1GHz

RESULT: Pass


Note:

- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.
- 4. All mode rates are tested and evaluated, BLE GFSK 2Mbps mode is the worst case and documented in the report.




EUT Name	Creative Aurvana Ace 3	Model Name	EF1240
Temperature	23.1 ℃	Relative Humidity	56.2%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Horizontal

Test Graph for Peak Measurement




Test Graph for Average Measurement




RESULT: Pass




EUT Name	Creative Aurvana Ace 3	Model Name	EF1240
Temperature	23.1 ℃	Relative Humidity	56.2%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Vertical



Test Graph for Average Measurement




RESULT: Pass






EUT Name	Creative Aurvana Ace 3	Model Name	EF1240
Temperature	23.1 ℃	Relative Humidity	56.2%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Horizontal



Test Graph for Average Measurement




RESULT: Pass




EUT Name	Creative Aurvana Ace 3	Model Name	EF1240
Temperature	23.1 ℃	Relative Humidity	56.2%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass




EUT Name	Creative Aurvana Ace 3	Model Name	EF1240
Temperature	23.1 ℃	Relative Humidity	56.2%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna Polarity	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass







EUT Name	Creative Aurvana Ace 3	Model Name	EF1240
Temperature	23.1 ℃	Relative Humidity	56.2%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna Polarity	Vertical



Test Graph for Average Measurement



RESULT: Pass





EUT Name	Creative Aurvana Ace 3	Model Name	EF1240
Temperature	23.1 ℃	Relative Humidity	56.2%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna Polarity	Horizontal



#VBW 3.0 MHz

96.364 dBµV 56.112 dBµV

2.480 552 GHz 2.483 500 GHz Stop 2.50000 GHz 1.066 ms (1000 pts)


Sweep

CF Step 2.450000 MHz Man

Freq Offset 0 Hz

Auto

Test Graph for Peak Measurement




RESULT: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

t 2.47550 GHz s BW 1.0 MHz




EUT Name	Creative Aurvana Ace 3	Model Name	EF1240
Temperature	23.1 ℃	Relative Humidity	56.2%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna Polarity	Vertical





Test Graph for Average Measurement



RESULT: Pass

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



12. AC Power Line Conducted Emission Test

12.1 Measurement Limit


Frequency	Maximum RF Line Voltage		
Frequency	Q.P. (dBµV)	Average (dBµV)	
150kHz~500kHz	66-56	56-46	
500kHz~5MHz	56	46	
5MHz~30MHz	60	50	

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

12.2 Measurement Setup (Block Diagram of Configuration)





12.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

12.5 Measurement Results

N/A

Note: The BT function cannot transmit when charging



Report No.: AGC00137240903FR02 Page 69 of 69

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC00137240903AP02

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC00137240903AP03

-----End of Report-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.