

FCC SAR Test Report

Report No. : SA160303C04

Applicant : HTC Corporation

Address : 1F, 6-3 Baoqiang Road, Xindian District, New Taipei City, Taiwan 231

Product : Smartphone

FCC ID : NM82PS6700A

Brand : HTC

Model No. : 2PS6700A

Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE Std 1528:2013
KDB 865664 D01 v01r04 / KDB 865664 D02 v01r02
KDB 248227 D01 v02r02 / KDB 447498 D01 v06 / KDB 648474 D04 v01r03
KDB 941225 D01 v03r01 / KDB 941225 D05 v02r05 / KDB 941225 D05A v01r02
KDB 941225 D06 v02r01

Sample Received Date : Mar. 03, 2016

Date of Testing : Mar. 11, 2016 ~ Apr. 12, 2016

CERTIFICATION: The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By : 
Ivonne Wu / Supervisor

Approved By : 
Eli Hsu / Supervisor



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

FCC SAR Test Report

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement System	6
3.1 Definition of Specific Absorption Rate (SAR)	6
3.2 SPEAG DASY System	6
3.2.1 Robot.....	7
3.2.2 Probes.....	8
3.2.3 Data Acquisition Electronics (DAE)	8
3.2.4 Phantoms	9
3.2.5 Device Holder.....	10
3.2.6 System Validation Dipoles.....	10
3.2.7 Tissue Simulating Liquids.....	11
3.3 SAR System Verification	14
3.4 SAR Measurement Procedure	15
3.4.1 Area & Zoom Scan Procedure	15
3.4.2 Volume Scan Procedure.....	15
3.4.3 Power Drift Monitoring.....	16
3.4.4 Spatial Peak SAR Evaluation	16
3.4.5 SAR Averaged Methods	16
4. SAR Measurement Evaluation	17
4.1 EUT Configuration and Setting.....	17
4.2 EUT Testing Position	25
4.2.1 Head Exposure Conditions.....	25
4.2.2 Body-worn Accessory Exposure Conditions.....	27
4.2.3 Hotspot Mode Exposure Conditions	28
4.2.4 Simultaneous Transmission Possibilities.....	29
4.3 Tissue Verification	30
4.4 System Validation.....	31
4.5 System Verification.....	32
4.6 Maximum Output Power.....	33
4.6.1 Maximum Conducted Power	33
4.6.2 Measured Conducted Power Result.....	34
4.7 SAR Testing Results	43
4.7.1 SAR Test Reduction Considerations	43
4.7.2 SAR Results for Head Exposure Condition	45
4.7.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap).....	49
4.7.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap).....	51
4.7.5 SAR Measurement Variability.....	56
4.7.6 Simultaneous Multi-band Transmission Evaluation	57
5. Calibration of Test Equipment.....	67
6. Measurement Uncertainty.....	68
7. Information on the Testing Laboratories.....	70

Appendix A. SAR Plots of System Verification

Appendix B. SAR Plots of SAR Measurement

Appendix C. Calibration Certificate for Probe and Dipole

Appendix D. Photographs of EUT and Setup



Release Control Record

Report No.	Reason for Change	Date Issued
SA160303C04	Initial release	Apr. 22, 2016

1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported Head SAR _{1g} (W/kg)	Highest Reported Body-worn SAR _{1g} (1.0 cm Gap) (W/kg)	Highest Reported Hotspot SAR _{1g} (1.0 cm Gap) (W/kg)
PCE	GSM850	0.33	0.42	0.42
	GSM1900	0.35	0.22	0.24
	WCDMA II	0.87	0.54	0.64
	WCDMA V	0.38	0.42	0.42
	LTE 5	0.18	0.20	0.20
	LTE 7	0.48	0.55	0.55
	LTE 13	0.07	0.42	0.42
	LTE 17	0.17	0.36	0.36
	LTE 26	0.26	0.27	0.27
	LTE 41	0.34	0.32	0.32
DTS	2.4G WLAN	0.77	0.19	0.19
NII	5.3G WLAN	0.79	0.04	N/A
	5.6G WLAN	0.75	0.06	N/A
	5.8G WLAN	0.57	0.03	0.03
DSS	Bluetooth	N/A	<0.01	N/A
DXX	ANT+	N/A	N/A	N/A
DXX	NFC	N/A	N/A	N/A
Highest Simultaneous Transmission SAR		Head (W/kg)	Body-worn (W/kg)	Hotspot (W/kg)
PCE + DTS		1.26	0.74	0.74
PCE + NII		1.30	0.61	0.64
PCE + DTS + DSS		N/A	0.74	N/A
PCE + NII + DSS		N/A	0.61	N/A

Note:

- The SAR limit (Head & Body: SAR_{1g} 1.6 W/kg, Extremity: SAR_{10g} 4.0 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

2. Description of Equipment Under Test

EUT Type	Smartphone
FCC ID	NM82PS6700A
Brand Name	HTC
Model Name	2PS6700A
Tx Frequency Bands (Unit: MHz)	GSM850 : 824.2 ~ 848.8 GSM1900 : 1850.2 ~ 1909.8 WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band V : 826.4 ~ 846.6 LTE Band 5 : 824.7 ~ 848.3 (1.4M), 825.5 ~ 847.5 (3M), 826.5 ~ 846.5 (5M), 829 ~ 844 (10M) LTE Band 7 : 2502.5 ~ 2567.5 (5M), 2505 ~ 2565 (10M), 2507.5 ~ 2562.5 (15M), 2510 ~ 2560 (20M) LTE Band 13 : 779.5 ~ 784.5 (5M), 782 (10M) LTE Band 17 : 706.5 ~ 713.5 (5M), 709 ~ 711 (10M) LTE Band 26 : 814.7 ~ 848.3 (1.4M), 815.5 ~ 847.5 (3M), 816.5 ~ 846.5 (5M), 819 ~ 844 (10M), 821.5 ~ 841.5 (15M) LTE Band 41 : 2498.5 ~ 2687.5 (5M), 2501 ~ 2685 (10M), 2503.5 ~ 2682.5 (15M), 2506 ~ 2680 (20M) WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825 Bluetooth : 2402 ~ 2480 ANT+ : 2402 ~ 2480 NFC : 13.56
Uplink Modulations	GSM & GPRS : GMSK EDGE : 8PSK WCDMA : QPSK LTE : QPSK, 16QAM 802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK ANT+ : GFSK NFC : ASK
Maximum Tune-up Conducted Power (Unit: dBm)	GSM850 : 33.5 GSM1900 : 30.5 WCDMA Band II : 24.0 WCDMA Band V : 24.0 LTE Band 5 : 23.0 LTE Band 7 : 23.0 LTE Band 13 : 23.5 LTE Band 17 : 23.5 LTE Band 26 : 23.5 LTE Band 41 : 23.5 WLAN 2.4G : 20.0 WLAN 5.2G : 17.5 WLAN 5.3G : 17.5 WLAN 5.6G : 17.5 WLAN 5.8G : 17.5 Bluetooth : 10.5
Antenna Type	Fixed Internal Antenna
EUT Stage	Production Unit

Note:

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY4/5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

FCC SAR Test Report




Fig-3.1 SPEAG DASY52 System Setup

3.2.1 Robot

The SPEAG DASY52 systems use the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



Fig-3.2 SPEAG DASY52 System

FCC SAR Test Report

3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5 μ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

FCC SAR Test Report


3.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	

Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	


3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

FCC SAR Test Report

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
For Body				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

The following table gives the recipes for tissue simulating liquids.


Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

FCC SAR Test Report

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

FCC SAR Test Report

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ($\Delta x, \Delta y$)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

FCC SAR Test Report

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

4. SAR Measurement Evaluation

4.1 EUT Configuration and Setting

<Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C is used for GSM/WCDMA/CDMA, and Anritsu MT8820C is used for LTE). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

<Considerations Related to GSM / GPRS / EDGE for Setup and Testing>

The maximum multi-slot capability supported by this device is as below.

1. This EUT is class B device
2. This EUT supports GPRS multi-slot class 12 (max. uplink: 4, max. downlink: 4, total timeslots: 5)
3. This EUT supports EDGE multi-slot class 12 (max. uplink: 4, max. downlink: 4, total timeslots: 5)

For GSM850 frequency band, the power control level is set to 5 for GSM mode and GPRS (GMSK: CS1), and set to 8 for EDGE (GMSK: MCS1, 8PSK: MCS9). For GSM1900 frequency band, the power control level is set to 0 for GSM mode and GPRS (GMSK: CS1), and set to 2 for EDGE (GMSK: MCS1, 8PSK: MCS9).

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

<Considerations Related to WCDMA for Setup and Testing>

WCDMA Handsets Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode.

WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the "Release 5 HSDPA Data Devices", for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

Handsets with Release 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the “Release 6 HSPA Data Devices”, for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	CM (dB) ⁽²⁾	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	12 / 15 ⁽³⁾	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$.

Note 3: For subtest 2 the β_c / β_d ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11 / 15$ and $\beta_d = 15 / 15$.

Release 6 HSUPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	11 / 15 ⁽³⁾	22 / 15	209 / 225	1039 / 225	4	1	1.0	0.0	20	75
2	6 / 15	15 / 15	64	6 / 15	12 / 15	12 / 15	94 / 75	4	1	3.0	2.0	12	67
3	15 / 15	9 / 15	64	15 / 9	30 / 15	30 / 15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2 / 15	15 / 15	64	2 / 15	4 / 15	2 / 15	56 / 75	4	1	3.0	2.0	17	71
5	15 / 15 ⁽⁴⁾	15 / 15 ⁽⁴⁾	64	15 / 15 ⁽⁴⁾	30 / 15	24 / 15	134 / 15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c / β_d ratio of 11 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10 / 15$ and $\beta_d = 15 / 15$.

Note 4: For subtest 5 the β_c / β_d ratio of 15 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14 / 15$ and $\beta_d = 15 / 15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

<Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 3, supports both QPSK and 16QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK and 16QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
5	V	V	V	V		
7			V	V	V	V
13			V	V		
17			V	V		
26	V	V	V	V	V	
41			V	V	V	V

FCC SAR Test Report

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2


Note: MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2

Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592 • Ts	2192 • Ts	2560 • Ts	7680 • Ts	2192 • Ts	2560 • Ts
1	19760 • Ts			20480 • Ts		
2	21952 • Ts			23040 • Ts		
3	24144 • Ts			25600 • Ts		
4	26336 • Ts	4384 • Ts	5120 • Ts	7680 • Ts	4384 • Ts	5120 • Ts
5	6592 • Ts			20480 • Ts		
6	19760 • Ts			23040 • Ts		
7	21952 • Ts			12800 • Ts		
8	24144 • Ts			-	-	-
9	13168 • Ts			-	-	-

3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

3GPP TS 36.211 Table 4.2-2: Uplink-Downlink Configurations

The variety of different TD-LTE uplink-downlink configurations allows a network operator to allocate the network's capacity between uplink and downlink traffic to meet the needs of the network. The uplink duty cycle of these seven configurations can readily be computed and shown in below.

UL-DL Configuration	0	1	2	3	4	5	6
Highest Duty-Cycle	63.33%	43.33%	23.33%	31.67%	21.67%	11.67%	53.33%

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

LTE Downlink Carrier Aggregation (CA) Setup Configurations

LTE Carrier Aggregation (CA) was defined in 3GPP release 10 and higher. The LTE device in CA mode has one Primary Component Carrier (PCC) and one or more Secondary Component Carriers (SCC). PCC acts as the anchor carrier and can optionally cross-schedule data transmission on SCC. The RRC connection is only handled by one cell, the PCC for downlink and uplink communications. After making a data connection to the PCC, the LTE device adds the SCC on the downlink only. All uplink communications and acknowledgements remain identical to release 8 specifications on the PCC. The combinations of downlink carrier aggregation supported by this device are listed in below.

EUT Supported Combinations of Downlink Carrier Aggregation							
Intra-Band Contiguous CA Operating Bands							
CA_41							
Intra-Band Non-Contiguous CA Operating Bands (with Two Sub-Blocks)							
CA_41-41							

FCC SAR Test Report

<Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

FCC SAR Test Report

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

<Considerations Related to Bluetooth for Setup and Testing>

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

FCC SAR Test Report

4.2 EUT Testing Position

According to KDB 648474 D04, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

4.2.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2003 using the SAM phantom illustrated as below.

1. Define two imaginary lines on the handset
 - (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
 - (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
 - (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig-4.1 Illustration for Handset Vertical and Horizontal Reference Lines

FCC SAR Test Report

2. Cheek Position

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig-4.2).




Fig-4.2 Illustration for Cheek Position

3. Tilted Position

- To position the device in the "cheek" position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig-4.3).



Fig-4.3 Illustration for Tilted Position

FCC SAR Test Report

4.2.2 Body-worn Accessory Exposure Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 D01 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.

A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance $\leq 5 \text{ mm}$ to support compliance.





Fig-4.4 Illustration for Body Worn Position

FCC SAR Test Report

4.2.3 Hotspot Mode Exposure Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225 D06. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



Based on the antenna location shown on appendix D of this report, the SAR testing required for hotspot mode is listed as below.

Antenna	Front Face	Rear Face	Left Side	Right Side	Top Side	Bottom Side
WWAN Ant-0	✓	✓	✓	✓		✓
WWAN Ant-1	✓	✓	✓	✓	✓	
WLAN / BT Ant-0	✓	✓		✓	✓	
WLAN Ant-1	✓	✓		✓		✓
WLAN Ant-0+1	✓	✓		✓	✓	✓

4.2.4 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Head (Voice / VoIP)	Body-worn (Voice / VoIP)	Hotspot (Data)
1	GSM850 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
2	GSM1900 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
3	WCDMA II (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
4	WCDMA V (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
5	LTE 5 (Data) + WLAN (Data)	Yes	Yes	Yes
6	LTE 7 (Data) + WLAN (Data)	Yes	Yes	Yes
7	LTE 13 (Data) + WLAN (Data)	Yes	Yes	Yes
8	LTE 17 (Data) + WLAN (Data)	Yes	Yes	Yes
9	LTE 26 (Data) + WLAN (Data)	Yes	Yes	Yes
10	LTE 41 (Data) + WLAN (Data)	Yes	Yes	Yes
11	GSM850 (Voice / Data) + BT (Data)	No	Yes	No
12	GSM1900 (Voice / Data) + BT (Data)	No	Yes	No
13	WCDMA II (Voice / Data) + BT (Data)	No	Yes	No
14	WCDMA V (Voice / Data) + BT (Data)	No	Yes	No
15	LTE 5 (Data) + BT (Data)	No	Yes	No
16	LTE 7 (Data) + BT (Data)	No	Yes	No
17	LTE 13 (Data) + BT (Data)	No	Yes	No
18	LTE 17 (Data) + BT (Data)	No	Yes	No
19	LTE 26 (Data) + BT (Data)	No	Yes	No
20	LTE 41 (Data) + BT (Data)	No	Yes	No
21	GSM850 (Voice / Data) + WLAN (Data) + BT (Data)	No	Yes	No
22	GSM1900 (Voice / Data) + WLAN (Data) + BT (Data)	No	Yes	No
23	WCDMA II (Voice / Data) + WLAN (Data) + BT (Data)	No	Yes	No
24	WCDMA V (Voice / Data) + WLAN (Data) + BT (Data)	No	Yes	No
25	LTE 5 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
26	LTE 7 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
27	LTE 13 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
28	LTE 17 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
29	LTE 26 (Data) + WLAN (Data) + BT (Data)	No	Yes	No
30	LTE 41 (Data) + WLAN (Data) + BT (Data)	No	Yes	No

Note :

1. The 2.4G WLAN and 5G WLAN cannot transmit simultaneously.
2. Both GSM/WCDMA and LTE can transmit through either antenna-0 or antenna-1. However, only one technology (GSM/WCDMA or LTE) can transmit from an antenna at a time, and the other technology transmits through the other antenna.

4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Apr. 09, 2016	Head	750	23.4	0.894	42.885	0.89	41.9	0.45	2.35
Mar. 25, 2016	Head	835	23.5	0.930	42.552	0.90	41.5	3.33	2.53
Apr. 09, 2016	Head	835	23.3	0.902	42.106	0.90	41.5	0.22	1.46
Mar. 25, 2016	Head	1900	23.3	1.463	38.454	1.40	40.0	4.50	-3.87
Apr. 01, 2016	Head	1900	23.5	1.455	38.358	1.40	40.0	3.93	-4.11
Mar. 30, 2016	Head	2450	23.5	1.865	37.815	1.80	39.2	3.61	-3.53
Mar. 30, 2016	Head	2600	23.6	2.016	37.255	1.96	39.0	2.86	-4.47
Apr. 12, 2016	Head	2600	23.5	2.037	38.800	1.96	39.0	3.93	-0.51
Apr. 08, 2016	Head	5300	23.2	4.839	34.792	4.76	35.9	1.66	-3.09
Apr. 08, 2016	Head	5600	23.3	5.123	34.361	5.07	35.5	1.05	-3.21
Apr. 09, 2016	Head	5800	23.2	5.319	34.073	5.27	35.3	0.93	-3.48
Apr. 10, 2016	Body	750	23.4	0.966	55.758	0.96	55.5	0.63	0.46
Apr. 10, 2016	Body	835	23.1	0.999	54.355	0.97	55.2	2.99	-1.53
Apr. 06, 2016	Body	1900	23.3	1.563	51.895	1.52	53.3	2.83	-2.64
Apr. 11, 2016	Body	2450	23.5	2.012	51.524	1.95	52.7	3.18	-2.23
Mar. 24, 2016	Body	2600	23.6	2.216	52.037	2.16	52.5	2.59	-0.88
Apr. 12, 2016	Body	2600	23.5	2.179	51.181	2.16	52.5	0.88	-2.51
Apr. 11, 2016	Body	5300	23.3	5.461	48.242	5.42	48.9	0.76	-1.35
Apr. 12, 2016	Body	5600	23.5	5.863	47.943	5.77	48.5	1.61	-1.15
Apr. 10, 2016	Body	5800	23.1	5.948	47.862	6.00	48.2	-0.87	-0.70

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Apr. 09, 2016	3864	Head	750	0.894	42.885	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 25, 2016	3650	Head	835	0.930	42.552	Pass	Pass	Pass	GMSK	Pass	N/A
Apr. 09, 2016	3864	Head	835	0.902	42.106	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 25, 2016	3650	Head	1900	1.463	38.454	Pass	Pass	Pass	GMSK	Pass	N/A
Apr. 01, 2016	3650	Head	1900	1.455	38.358	Pass	Pass	Pass	N/A	N/A	N/A
Mar. 30, 2016	3650	Head	2450	1.865	37.815	Pass	Pass	Pass	OFDM	N/A	Pass
Mar. 30, 2016	3650	Head	2600	2.016	37.255	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 12, 2016	3650	Head	2600	2.037	38.800	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 08, 2016	3864	Head	5300	4.839	34.792	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 08, 2016	3864	Head	5600	5.123	34.361	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 09, 2016	3864	Head	5800	5.319	34.073	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 10, 2016	3864	Body	750	0.966	55.758	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 10, 2016	3864	Body	835	0.999	54.355	Pass	Pass	Pass	GMSK	Pass	N/A
Apr. 06, 2016	3650	Body	1900	1.563	51.895	Pass	Pass	Pass	GMSK	Pass	N/A
Apr. 11, 2016	3650	Body	2450	2.012	51.524	Pass	Pass	Pass	OFDM	N/A	Pass
Mar. 24, 2016	3650	Body	2600	2.216	52.037	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 12, 2016	3650	Body	2600	2.179	51.181	Pass	Pass	Pass	N/A	N/A	N/A
Apr. 11, 2016	3650	Body	5300	5.461	48.242	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 12, 2016	3650	Body	5600	5.863	47.943	Pass	Pass	Pass	OFDM	N/A	Pass
Apr. 10, 2016	3864	Body	5800	5.948	47.862	Pass	Pass	Pass	OFDM	N/A	Pass

4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Apr. 09, 2016	Head	750	8.07	1.92	7.68	-4.83	1013	3864	861
Mar. 25, 2016	Head	835	9.11	2.22	8.88	-2.52	4d121	3650	1277
Apr. 09, 2016	Head	835	9.11	2.34	9.36	2.74	4d121	3864	861
Mar. 25, 2016	Head	1900	38.90	8.99	35.96	-7.56	5d036	3650	1277
Apr. 01, 2016	Head	1900	38.90	9.80	39.20	0.77	5d036	3650	1277
Mar. 30, 2016	Head	2450	53.00	13.10	52.40	-1.13	737	3650	1277
Mar. 30, 2016	Head	2600	56.70	13.60	54.40	-4.06	1020	3650	1277
Apr. 12, 2016	Head	2600	56.70	14.40	57.60	1.59	1020	3650	1277
Apr. 08, 2016	Head	5300	85.00	8.05	80.50	-5.29	1019	3864	861
Apr. 08, 2016	Head	5600	83.90	8.36	83.60	-0.36	1019	3864	861
Apr. 09, 2016	Head	5800	81.80	8.30	83.00	1.47	1019	3864	861
Apr. 10, 2016	Body	750	8.44	2.12	8.48	0.47	1013	3864	861
Apr. 10, 2016	Body	835	9.20	2.34	9.36	1.74	4d121	3864	861
Apr. 06, 2016	Body	1900	40.70	10.00	40.00	-1.72	5d036	3650	1277
Apr. 11, 2016	Body	2450	51.10	12.50	50.00	-2.15	737	3650	1277
Mar. 24, 2016	Body	2600	55.40	13.10	52.40	-5.42	1020	3650	1277
Apr. 12, 2016	Body	2600	55.40	13.40	53.60	-3.25	1020	3650	1277
Apr. 11, 2016	Body	5300	76.60	8.07	80.70	5.35	1019	3650	1277
Apr. 12, 2016	Body	5600	79.80	8.22	82.20	3.01	1019	3650	1277
Apr. 10, 2016	Body	5800	77.30	7.57	75.70	-2.07	1019	3864	861

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

4.6 Maximum Output Power

4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	Maximum Burst-Averaged Output Power		Maximum Frame-Averaged Output Power	
	GSM850	GSM1900	GSM850	GSM1900
GSM (GMSK, 1Tx-slot)	33.5	30.5	24.5	21.5
GPRS (GMSK, 1Tx-slot)	33.5	30.5	24.5	21.5
GPRS (GMSK, 2Tx-slot)	32.0	29.0	26.0	23.0
GPRS (GMSK, 3Tx-slot)	28.0	27.0	23.7	22.7
GPRS (GMSK, 4Tx-slot)	27.0	26.0	24.0	23.0
EDGE (8PSK, 1Tx-slot)	28.0	26.0	19.0	17.0
EDGE (8PSK, 2Tx-slot)	27.0	26.0	21.0	20.0
EDGE (8PSK, 3Tx-slot)	27.0	25.0	22.7	20.7
EDGE (8PSK, 4Tx-slot)	25.0	24.0	22.0	21.0

Note:

1. SAR testing was performed on the maximum frame-averaged power mode.
2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:

$$\text{Frame-averaged power} = 10 \times \log (\text{Burst-averaged power mW} \times \text{Slot used} / 8)$$

Mode	WCDMA Band II	WCDMA Band V
RMC 12.2K	24.0	24.0
HSDPA	22.5	22.5
HSUPA	22.0	22.0

Mode	LTE 5	LTE 7	LTE 13	LTE 17
QPSK / 16QAM	23.0	23.0	23.5	23.5

Mode	LTE 26	LTE 41
QPSK / 16QAM	23.5	23.5

FCC SAR Test Report

A D T

Mode	Tx Antenna	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
802.11b	Ant-0	20.0	N/A	N/A	N/A	N/A
	Ant-1					
802.11g	Ant-0	18.0	N/A	N/A	N/A	N/A
	Ant-1					
802.11a	Ant-0	N/A	17.5	17.5	17.5	17.5
	Ant-1					
	Ant-0+Ant-1					
802.11n HT20	Ant-0	18.0	17.5	17.5	17.5	17.5
	Ant-1					
	Ant-0+Ant-1					
802.11n HT40	Ant-0	18.0	17.5	17.5	17.5	17.5
	Ant-1					
	Ant-0+Ant-1					
802.11ac VHT80	Ant-0	N/A	17.5	17.5	17.5	17.5
	Ant-1					
	Ant-0+Ant-1					

Mode	2.4G Bluetooth
Bluetooth DH	Ch 0: 10.5 Ch 39: 10.5 Ch 78: 10.1

4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
Maximum Burst-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	32.63	32.67	32.86	29.83	29.41	29.29
GPRS (GMSK, 1Tx-slot)	32.55	32.65	32.82	29.81	29.39	29.23
GPRS (GMSK, 2Tx-slot)	30.62	30.71	30.91	28.06	27.67	27.60
GPRS (GMSK, 3Tx-slot)	27.70	27.74	27.93	25.77	25.44	25.24
GPRS (GMSK, 4Tx-slot)	26.47	26.51	26.70	25.44	24.96	24.85
EDGE (8PSK, 1Tx-slot)	26.58	26.62	26.81	25.43	25.01	24.89
EDGE (8PSK, 2Tx-slot)	26.42	26.46	26.65	25.35	24.93	24.81
EDGE (8PSK, 3Tx-slot)	26.28	26.32	26.51	23.79	23.37	23.25
EDGE (8PSK, 4Tx-slot)	24.89	24.91	24.96	23.04	22.62	22.50

FCC SAR Test Report

A D T

Band	WCDMA Band II			WCDMA Band V			3GPP MPR (dB)
Channel	9262	9400	9538	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.4	846.6	
RMC 12.2K	22.57	22.62	22.60	22.90	22.93	22.91	-
HSDPA Subtest-1	21.91	22.01	21.98	21.94	21.98	21.96	0
HSDPA Subtest-2	21.66	21.80	21.78	21.85	21.95	21.93	0
HSDPA Subtest-3	21.34	21.39	21.37	21.54	21.57	21.55	0.5
HSDPA Subtest-4	21.35	21.41	21.39	21.47	21.50	21.48	0.5
HSUPA Subtest-1	21.82	21.88	21.85	21.94	21.98	21.96	0
HSUPA Subtest-2	20.04	20.09	20.07	20.02	20.05	20.03	2
HSUPA Subtest-3	21.06	21.11	21.09	21.02	21.05	21.03	1
HSUPA Subtest-4	20.06	20.10	20.08	20.01	20.09	20.05	2
HSUPA Subtest-5	21.86	21.98	21.96	21.95	22.00	21.98	0

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20407	Mid CH 20525	High CH 20643		Low CH 20407	Mid CH 20525	High CH 20643	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
5 / 1.4M	1	0	22.22	22.02	21.99	0	21.28	21.09	21.02	1
	1	2	22.29	22.14	22.07	0	21.35	21.19	21.14	1
	1	5	22.10	21.99	21.89	0	21.22	21.02	20.93	1
	3	0	21.11	21.86	21.83	0	20.01	20.81	20.77	1
	3	1	21.19	21.55	21.47	0	20.24	20.74	20.95	1
	3	3	21.73	21.91	21.84	0	20.10	20.86	20.78	1
	6	0	20.13	20.95	20.86	1	19.18	19.95	19.86	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20415	Mid CH 20525	High CH 20635		Low CH 20415	Mid CH 20525	High CH 20635	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
5 / 3M	1	0	22.29	22.11	22.07	0	21.32	21.14	21.08	1
	1	7	22.34	22.20	22.15	0	21.38	21.22	21.19	1
	1	14	22.19	22.07	21.98	0	21.32	21.08	20.98	1
	8	0	21.21	21.04	21.00	1	20.15	19.97	19.92	2
	8	3	21.31	21.15	21.08	1	20.30	20.15	20.08	2
	8	7	21.18	21.06	20.98	1	20.20	19.99	19.94	2
	15	0	21.24	21.10	21.06	1	20.25	20.04	19.99	2

FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20425	Mid CH 20525	High CH 20625		Low CH 20425	Mid CH 20525	High CH 20625	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
5 / 5M	1	0	22.31	22.18	22.15	0	21.38	21.23	21.19	1
	1	12	22.39	22.24	22.19	0	21.44	21.30	21.27	1
	1	24	22.30	22.15	22.04	0	21.32	21.19	21.12	1
	12	0	21.36	21.17	21.12	1	20.27	20.10	20.07	2
	12	6	21.42	21.28	21.24	1	20.42	20.26	20.19	2
	12	13	21.32	21.19	21.15	1	20.26	20.11	20.08	2
	25	0	21.36	21.22	21.17	1	20.37	20.15	20.10	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20450	Mid CH 20525	High CH 20600		Low CH 20450	Mid CH 20525	High CH 20600	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
5 / 10M	1	0	22.39	22.26	22.23	0	21.43	21.29	21.26	1
	1	24	22.45	22.32	22.29	0	21.50	21.36	21.31	1
	1	49	22.35	22.23	22.13	0	21.34	21.26	21.17	1
	25	0	21.38	21.30	21.27	1	20.39	20.25	20.23	2
	25	12	21.48	21.38	21.36	1	20.48	20.38	20.31	2
	25	25	21.43	21.31	21.28	1	20.45	20.28	20.23	2
	50	0	21.46	21.33	21.30	1	20.47	20.31	20.28	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20775	Mid CH 21100	High CH 21425		Low CH 20775	Mid CH 21100	High CH 21425	
			2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz	
7 / 5M	1	0	21.72	21.64	21.57	0	20.77	20.71	20.65	1
	1	12	21.36	21.22	21.19	0	20.41	20.27	20.22	1
	1	24	21.60	21.51	21.42	0	20.65	20.58	20.51	1
	12	0	20.99	20.88	20.79	1	20.06	19.92	19.83	2
	12	6	20.32	20.16	20.11	1	19.27	19.12	19.08	2
	12	13	20.61	20.57	20.55	1	19.68	19.59	19.51	2
	25	0	20.54	20.46	20.40	1	19.55	19.44	19.39	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20800	Mid CH 21100	High CH 21400		Low CH 20800	Mid CH 21100	High CH 21400	
			2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz	
7 / 10M	1	0	21.77	21.70	21.66	0	20.81	20.72	20.68	1
	1	24	21.46	21.33	21.28	0	20.40	20.34	20.31	1
	1	49	21.63	21.59	21.47	0	20.66	20.62	20.50	1
	25	0	21.03	20.99	20.91	1	20.12	20.00	19.91	2
	25	12	20.36	20.30	20.26	1	19.33	19.26	19.21	2
	25	25	20.74	20.70	20.59	1	19.73	19.69	19.64	2
	50	0	20.70	20.55	20.51	1	19.62	19.56	19.53	2

FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20825	Mid CH 21100	High CH 21375		Low CH 20825	Mid CH 21100	High CH 21375	
			2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz	
7 / 15M	1	0	21.82	21.75	21.72	0	20.87	20.81	20.78	1
	1	37	21.54	21.41	21.38	0	20.60	20.45	20.41	1
	1	74	21.73	21.66	21.56	0	20.76	20.71	20.59	1
	36	0	21.21	21.11	21.04	1	20.27	20.12	20.04	2
	36	19	20.61	20.46	20.41	1	19.59	19.43	19.37	2
	36	39	20.86	20.82	20.80	1	19.90	19.84	19.79	2
	75	0	20.76	20.71	20.68	1	19.75	19.71	19.66	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20850	Mid CH 21100	High CH 21350		Low CH 20850	Mid CH 21100	High CH 21350	
			2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz	
7 / 20M	1	0	21.87	21.81	21.78	0	20.92	20.85	20.82	1
	1	50	21.62	21.49	21.46	0	20.64	20.50	20.47	1
	1	99	21.77	21.73	21.67	0	20.82	20.75	20.72	1
	50	0	21.31	21.20	21.09	1	20.24	20.19	20.16	2
	50	25	20.73	20.59	20.57	1	19.67	19.54	19.52	2
	50	50	20.98	20.93	20.86	1	19.96	19.90	19.87	2
	100	0	20.88	20.83	20.80	1	19.88	19.80	19.77	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23205	Mid CH 23230	High CH 23255		Low CH 23205	Mid CH 23230	High CH 23255	
			779.5 MHz	782.0 MHz	784.5 MHz		779.5 MHz	782.0 MHz	784.5 MHz	
13 / 5M	1	0	21.91	22.01	22.12	0	20.93	21.05	21.17	1
	1	12	21.79	21.98	22.07	0	20.82	21.01	21.13	1
	1	24	21.52	21.62	21.70	0	20.55	20.63	20.71	1
	12	0	20.63	20.70	20.86	1	19.60	19.69	19.89	2
	12	6	20.58	20.68	20.79	1	19.55	19.67	19.80	2
	12	13	20.56	20.66	20.77	1	19.53	19.63	19.77	2
	25	0	20.54	20.64	20.75	1	19.52	19.60	19.71	2

LTE Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)
			Mid CH 23230		Mid CH 23230	
			782.0 MHz		782.0 MHz	
13 / 10M	1	0	22.26	0	21.28	1
	1	24	22.23	0	21.25	1
	1	49	22.20	0	21.21	1
	25	0	21.30	1	20.25	2
	25	12	21.29	1	20.24	2
	25	25	21.27	1	20.22	2
	50	0	21.28	1	20.23	2

FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23755	Mid CH 23790	High CH 23825		Low CH 23755	Mid CH 23790	High CH 23825	
			706.5 MHz	710.0 MHz	713.5 MHz		706.5 MHz	710.0 MHz	713.5 MHz	
17 / 5M	1	0	21.78	21.83	21.75	0	20.82	20.88	20.78	1
	1	12	21.74	21.81	21.66	0	20.77	20.85	20.71	1
	1	24	21.62	21.71	21.60	0	20.66	20.71	20.58	1
	12	0	20.84	20.89	20.75	1	19.84	19.87	19.72	2
	12	6	20.69	20.78	20.67	1	19.69	19.75	19.63	2
	12	13	20.74	20.82	20.73	1	19.75	19.80	19.69	2
	25	0	20.69	20.75	20.65	1	19.61	19.71	19.60	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 23780	Mid CH 23790	High CH 23800		Low CH 23780	Mid CH 23790	High CH 23800	
			709.0 MHz	710.0 MHz	711.0 MHz		709.0 MHz	710.0 MHz	711.0 MHz	
17 / 10M	1	0	21.83	21.88	21.80	0	20.86	20.93	20.82	1
	1	24	21.80	21.86	21.76	0	20.84	20.90	20.75	1
	1	49	21.74	21.77	21.63	0	20.75	20.78	20.71	1
	25	0	20.94	20.99	20.92	1	19.94	19.99	19.86	2
	25	12	20.84	20.89	20.81	1	19.80	19.86	19.76	2
	25	25	20.90	20.93	20.85	1	19.83	19.91	19.81	2
	50	0	20.83	20.87	20.80	1	19.78	19.82	19.74	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26697	Mid CH 26865	High CH 27033		Low CH 26697	Mid CH 26865	High CH 27033	
			814.7 MHz	831.5 MHz	848.3 MHz		814.7 MHz	831.5 MHz	848.3 MHz	
26 / 1.4M	1	0	21.82	21.74	21.58	0	20.81	20.75	20.57	1
	1	2	22.80	22.77	22.67	0	21.85	21.82	21.60	1
	1	5	21.62	21.53	21.51	0	20.66	20.53	20.57	1
	3	0	21.56	21.55	21.58	0	20.71	20.68	20.58	1
	3	1	21.83	21.70	21.51	0	20.88	20.75	20.53	1
	3	3	21.61	21.53	21.54	0	20.59	20.56	20.52	1
	6	0	20.88	20.80	20.66	1	19.84	19.72	19.62	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26705	Mid CH 26865	High CH 27025		Low CH 26705	Mid CH 26865	High CH 27025	
			815.5 MHz	831.5 MHz	847.5 MHz		815.5 MHz	831.5 MHz	847.5 MHz	
26 / 3M	1	0	21.87	21.80	21.67	0	20.88	20.82	20.68	1
	1	7	22.86	22.82	22.64	0	21.90	21.85	21.73	1
	1	14	21.69	21.60	21.52	0	20.74	20.60	20.51	1
	8	0	20.71	20.64	20.55	1	19.61	19.57	19.51	2
	8	3	21.08	20.94	20.69	1	19.97	19.91	19.64	2
	8	7	20.84	20.77	20.57	1	19.82	19.74	19.57	2
	15	0	20.96	20.89	20.75	1	19.95	19.84	19.67	2

FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26715	Mid CH 26865	High CH 27015		Low CH 26715	Mid CH 26865	High CH 27015	
			816.5 MHz	831.5 MHz	846.5 MHz		816.5 MHz	831.5 MHz	846.5 MHz	
26 / 5M	1	0	21.92	21.87	21.73	0	20.95	20.90	20.76	1
	1	12	22.91	22.88	22.72	0	21.96	21.92	21.71	1
	1	24	21.78	21.68	21.52	0	20.82	20.72	20.56	1
	12	0	20.85	20.80	20.68	1	19.84	19.74	19.63	2
	12	6	21.17	21.02	20.87	1	20.12	20.05	19.78	2
	12	13	20.95	20.91	20.75	1	19.95	19.89	19.65	2
	25	0	21.06	21.00	20.90	1	20.07	20.00	19.80	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26740	Mid CH 26865	High CH 26990		Low CH 26740	Mid CH 26865	High CH 26990	
			819.0 MHz	831.5 MHz	844.0 MHz		819.0 MHz	831.5 MHz	844.0 MHz	
26 / 10M	1	0	21.99	21.94	21.82	0	21.02	20.96	20.85	1
	1	24	22.97	22.93	22.87	0	22.02	21.96	21.85	1
	1	49	21.84	21.77	21.66	0	20.88	20.80	20.67	1
	25	0	20.98	20.91	20.84	1	19.93	19.90	19.79	2
	25	12	21.28	21.13	21.03	1	20.18	20.13	19.90	2
	25	25	21.09	21.02	20.85	1	20.09	20.01	19.85	2
	50	0	21.15	21.11	21.02	1	20.16	20.11	19.98	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 26765	Mid CH 26865	High CH 26965		Low CH 26765	Mid CH 26865	High CH 26965	
			821.5 MHz	831.5 MHz	841.5 MHz		821.5 MHz	831.5 MHz	841.5 MHz	
26 / 15M	1	0	22.05	22.01	21.90	0	21.09	21.03	20.91	1
	1	37	22.91	22.98	23.02	0	22.07	22.03	21.85	1
	1	74	21.97	21.86	21.77	0	21.00	20.87	20.71	1
	36	0	21.12	21.06	20.97	1	20.09	20.03	19.95	2
	36	19	21.16	21.24	21.37	1	20.35	20.24	20.15	2
	36	39	21.18	21.14	21.01	1	20.17	20.12	19.97	2
	75	0	21.26	21.22	21.14	1	20.25	20.21	20.10	2

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39675	M-CH 40148	M-CH 40620	M-CH 41093	H-CH 41565		L-CH 39675	M-CH 40148	M-CH 40620	M-CH 41093	H-CH 41565	
			2498.5 MHz	2545.8 MHz	2593.0 MHz	2640.3 MHz	2687.5 MHz		2498.5 MHz	2545.8 MHz	2593.0 MHz	2640.3 MHz	2687.5 MHz	
41 / 5M	1	0	22.63	23.04	22.91	22.91	22.99	0	21.65	22.07	21.93	21.93	22.01	1
	1	12	22.30	22.70	22.50	22.50	22.60	0	21.26	21.69	21.50	21.50	21.62	1
	1	24	22.20	22.62	22.45	22.45	22.55	0	21.20	21.65	21.48	21.48	21.55	1
	12	0	21.26	21.77	21.56	21.56	21.74	1	20.24	20.74	20.53	20.53	20.73	2
	12	6	21.23	21.76	21.49	21.49	21.64	1	20.15	20.73	20.45	20.45	20.63	2
	12	13	21.17	21.66	21.45	21.45	21.54	1	20.12	20.63	20.38	20.38	20.50	2
	25	0	21.30	21.74	21.47	21.54	21.61	1	20.17	20.73	20.41	20.42	20.60	2

FCC SAR Test Report

A D T

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39700	M-CH 40160	M-CH 40620	M-CH 41080	H-CH 41540		L-CH 39700	M-CH 40160	M-CH 40620	M-CH 41080	H-CH 41540	
			2501.0 MHz	2547.0 MHz	2593.0 MHz	2639.0 MHz	2685.0 MHz		2501.0 MHz	2547.0 MHz	2593.0 MHz	2639.0 MHz	2685.0 MHz	
41 / 10M	1	0	22.70	23.09	22.95	22.95	23.04	0	21.73	22.14	22.00	22.00	22.09	1
	1	24	22.30	22.73	22.55	22.55	22.67	0	21.33	21.80	21.57	21.57	21.70	1
	1	49	22.21	22.71	22.52	22.52	22.59	0	21.29	21.73	21.56	21.56	21.63	1
	25	0	21.41	21.84	21.67	21.67	21.78	1	20.43	20.90	20.68	20.68	20.76	2
	25	12	21.37	21.81	21.62	21.62	21.74	1	20.32	20.84	20.61	20.61	20.73	2
	25	25	21.33	21.75	21.57	21.57	21.68	1	20.27	20.73	20.53	20.53	20.62	2
	50	0	21.35	21.78	21.58	21.62	21.71	1	20.35	20.79	20.57	20.61	20.73	2

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39725	M-CH 40173	M-CH 40620	M-CH 41068	H-CH 41515		L-CH 39725	M-CH 40173	M-CH 40620	M-CH 41068	H-CH 41515	
			2503.5 MHz	2548.3 MHz	2593.0 MHz	2637.8 MHz	2682.5 MHz		2503.5 MHz	2548.3 MHz	2593.0 MHz	2637.8 MHz	2682.5 MHz	
41 / 15M	1	0	22.77	23.14	23.01	23.01	23.09	0	21.82	22.19	22.06	22.06	22.14	1
	1	37	22.41	22.79	22.65	22.65	22.75	0	21.40	21.87	21.67	21.67	21.77	1
	1	74	22.39	22.77	22.63	22.63	22.70	0	21.36	21.79	21.64	21.64	21.71	1
	36	0	21.59	21.97	21.80	21.80	21.89	1	20.55	20.96	20.78	20.78	20.86	2
	36	19	21.50	21.91	21.75	21.75	21.83	1	20.46	20.92	20.72	20.72	20.84	2
	36	39	21.47	21.86	21.71	21.71	21.81	1	20.42	20.84	20.68	20.68	20.80	2
	75	0	21.48	21.89	21.72	21.75	21.83	1	20.44	20.92	20.69	20.74	20.82	2

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39750	M-CH 40185	M-CH 40620	M-CH 41055	H-CH 41490		L-CH 39750	M-CH 40185	M-CH 40620	M-CH 41055	H-CH 41490	
			2506.0 MHz	2549.5 MHz	2593.0 MHz	2636.5 MHz	2680.0 MHz		2506.0 MHz	2549.5 MHz	2593.0 MHz	2636.5 MHz	2680.0 MHz	
41 / 20M	1	0	22.83	23.19	23.06	23.06	23.14	0	21.85	22.24	22.11	22.11	22.19	1
	1	50	22.57	22.89	22.72	22.72	22.81	0	21.51	21.93	21.74	21.74	21.83	1
	1	99	22.39	22.82	22.71	22.71	22.75	0	21.49	21.86	21.73	21.73	21.80	1
	50	0	21.75	22.07	21.92	21.92	21.98	1	20.66	21.06	20.91	20.91	20.99	2
	50	25	21.65	22.01	21.88	21.88	21.97	1	20.60	21.02	20.86	20.86	20.94	2
	50	50	21.62	21.97	21.85	21.85	21.93	1	20.57	20.98	20.81	20.81	20.91	2
	100	0	21.65	22.00	21.86	21.86	21.94	1	20.64	21.03	20.84	20.84	20.93	2

Conducted Power Measurement for LTE-CA (Carrier Aggregation)									
PCC (Primary Component Carrier)					SCC (Secondary Component Carrier)			PCC Tx Power With Out CA	Tx Power With DL-CA Active
LTE Band	BW (MHz)	Uplink Channel	RB Size	RB Offset	LTE Band	BW (MHz)	Downlink Channel		
41	20	40185	1	0	41	20	40383	23.11	23.15
41	20	40185	1	0	41	20	41490	23.11	23.12

Note:

1. The LTE-CA for this device is supported to downlink only, and there is no uplink carrier aggregation.
2. The PCC Tx power is measured with SCC downlink carrier aggregation active, using the channel with highest measured maximum output power when downlink carrier aggregation is inactive, to confirm that when downlink carrier aggregation is active, uplink maximum output power remains within the specified tune-up tolerance limits and not more than 1/4 dB higher than the maximum output power measured when downlink carrier aggregation inactive.
3. This device does not support all LTE-CA configurations. The LTE-CA power was measured for those combinations supported by this device.

<WLAN 2.4G>

Mode	802.11b		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power (Ant-0)	18.36	18.46	18.49
Average Power (Ant-1)	18.06	18.02	18.43
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	3 (2422)	6 (2437)	9 (2452)
Average Power (Ant-0 + Ant-1)	16.28	16.06	16.12

<WLAN 5.3G>

Mode	802.11ac (VHT80)
Channel / Frequency (MHz)	58 (5290)
Average Power (Ant-0)	15.76
Average Power (Ant-1)	15.75
Average Power (Ant-0 + Ant-1)	15.98

<WLAN 5.6G>

Mode	802.11ac (VHT80)
Channel / Frequency (MHz)	106 (5530)
Average Power (Ant-0)	16.01
Average Power (Ant-1)	15.94
Average Power (Ant-0 + Ant-1)	16.33

<WLAN 5.8G>

Mode	802.11ac (VHT80)
Channel / Frequency (MHz)	155 (5775)
Average Power (Ant-0)	15.77
Average Power (Ant-1)	15.65
Average Power (Ant-0 + Ant-1)	16.37

<Bluetooth>

Mode	Bluetooth		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	9.18	8.77	8.13

FCC SAR Test Report

4.7 SAR Testing Results

4.7.1 SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 941225 D01, 3G SAR Measurement Procedures>

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

(1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

(2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

(3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

(4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

FCC SAR Test Report

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.
- (4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

4.7.2 SAR Results for Head Exposure Condition

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
01	GSM850	GPRS10	Right Cheek	251	0	32.0	30.91	1.29	0.01	0.254	0.33
	GSM850	GPRS10	Right Cheek	251	1	32.0	30.91	1.29	0.05	0.07	0.09
	GSM850	GPRS10	Right Tilted	251	0	32.0	30.91	1.29	-0.03	0.139	0.18
	GSM850	GPRS10	Right Tilted	251	1	32.0	30.91	1.29	0.06	0.033	0.04
	GSM850	GPRS10	Left Cheek	251	0	32.0	30.91	1.29	0.02	0.206	0.26
	GSM850	GPRS10	Left Cheek	251	1	32.0	30.91	1.29	0.03	0.036	0.05
	GSM850	GPRS10	Left Tilted	251	0	32.0	30.91	1.29	0.01	0.142	0.18
	GSM850	GPRS10	Left Tilted	251	1	32.0	30.91	1.29	0.07	0.014	0.02
	GSM1900	GPRS12	Right Cheek	512	0	26.0	25.44	1.14	0.07	0.067	0.08
02	GSM1900	GPRS12	Right Cheek	512	1	26.0	25.44	1.14	0.02	0.309	0.35
	GSM1900	GPRS12	Right Tilted	512	0	26.0	25.44	1.14	0.02	0.023	0.03
	GSM1900	GPRS12	Right Tilted	512	1	26.0	25.44	1.14	0.05	0.2	0.23
	GSM1900	GPRS12	Left Cheek	512	0	26.0	25.44	1.14	-0.08	0.122	0.14
	GSM1900	GPRS12	Left Cheek	512	1	26.0	25.44	1.14	-0.05	0.135	0.15
	GSM1900	GPRS12	Left Tilted	512	0	26.0	25.44	1.14	0.08	0.035	0.04
	GSM1900	GPRS12	Left Tilted	512	1	26.0	25.44	1.14	-0.14	0.127	0.14
	WCDMA II	RMC12.2K	Right Cheek	9400	0	24.0	22.62	1.37	0.05	0.171	0.23
	WCDMA II	RMC12.2K	Right Cheek	9400	1	24.0	22.62	1.37	0.03	0.626	0.86
	WCDMA II	RMC12.2K	Right Cheek	9262	1	24.0	22.57	1.39	0.01	0.619	0.86
03	WCDMA II	RMC12.2K	Right Cheek	9538	1	24.0	22.60	1.38	0.01	0.628	0.87
	WCDMA II	RMC12.2K	Right Tilted	9400	0	24.0	22.62	1.37	0.06	0.066	0.09
	WCDMA II	RMC12.2K	Right Tilted	9400	1	24.0	22.62	1.37	0.06	0.492	0.68
	WCDMA II	RMC12.2K	Left Cheek	9400	0	24.0	22.62	1.37	0.09	0.355	0.49
	WCDMA II	RMC12.2K	Left Cheek	9400	1	24.0	22.62	1.37	-0.08	0.307	0.42
	WCDMA II	RMC12.2K	Left Tilted	9400	0	24.0	22.62	1.37	-0.05	0.133	0.18
	WCDMA II	RMC12.2K	Left Tilted	9400	1	24.0	22.62	1.37	-0.02	0.335	0.46
04	WCDMA V	RMC12.2K	Right Cheek	4182	0	24.0	22.93	1.28	0.04	0.297	0.38
	WCDMA V	RMC12.2K	Right Cheek	4182	1	24.0	22.93	1.28	-0.12	0.083	0.11
	WCDMA V	RMC12.2K	Right Tilted	4182	0	24.0	22.93	1.28	-0.03	0.171	0.22
	WCDMA V	RMC12.2K	Right Tilted	4182	1	24.0	22.93	1.28	-0.14	0.031	0.04
	WCDMA V	RMC12.2K	Left Cheek	4182	0	24.0	22.93	1.28	0.14	0.211	0.27
	WCDMA V	RMC12.2K	Left Cheek	4182	1	24.0	22.93	1.28	0.03	0.045	0.06
	WCDMA V	RMC12.2K	Left Tilted	4182	0	24.0	22.93	1.28	0.11	0.146	0.19
	WCDMA V	RMC12.2K	Left Tilted	4182	1	24.0	22.93	1.28	0.03	0.018	0.02

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
05	LTE 5	QPSK10M	Right Cheek	20450	0	1	24	23.0	22.45	1.14	0	0.158	0.18
	LTE 5	QPSK10M	Right Cheek	20450	0	25	12	22.0	21.48	1.13	0.04	0.117	0.13
	LTE 5	QPSK10M	Right Cheek	20450	1	1	24	23.0	22.45	1.14	-0.11	0.071	0.08
	LTE 5	QPSK10M	Right Cheek	20450	1	25	12	22.0	21.48	1.13	-0.17	0.057	0.06
	LTE 5	QPSK10M	Right Tilted	20450	0	1	24	23.0	22.45	1.14	0	0.113	0.13
	LTE 5	QPSK10M	Right Tilted	20450	0	25	12	22.0	21.48	1.13	-0.02	0.095	0.11
	LTE 5	QPSK10M	Right Tilted	20450	1	1	24	23.0	22.45	1.14	-0.02	0.03	0.03
	LTE 5	QPSK10M	Right Tilted	20450	1	25	12	22.0	21.48	1.13	-0.03	0.023	0.03
	LTE 5	QPSK10M	Left Cheek	20450	0	1	24	23.0	22.45	1.14	0.08	0.134	0.15
	LTE 5	QPSK10M	Left Cheek	20450	0	25	12	22.0	21.48	1.13	0.06	0.105	0.12
	LTE 5	QPSK10M	Left Cheek	20450	1	1	24	23.0	22.45	1.14	0.07	0.039	0.04
	LTE 5	QPSK10M	Left Cheek	20450	1	25	12	22.0	21.48	1.13	0.1	0.032	0.04
	LTE 5	QPSK10M	Left Tilted	20450	0	1	24	23.0	22.45	1.14	0.09	0.095	0.11
	LTE 5	QPSK10M	Left Tilted	20450	0	25	12	22.0	21.48	1.13	-0.11	0.063	0.07
	LTE 5	QPSK10M	Left Tilted	20450	1	1	24	23.0	22.45	1.14	0.02	0.021	0.02
	LTE 5	QPSK10M	Left Tilted	20450	1	25	12	22.0	21.48	1.13	-0.02	0.017	0.02



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
06	LTE 7	QPSK20M	Right Cheek	20850	0	1	0	23.0	21.87	1.30	0.03	0.153	0.20
	LTE 7	QPSK20M	Right Cheek	20850	0	50	0	22.0	21.31	1.17	0.03	0.165	0.19
	LTE 7	QPSK20M	Right Cheek	20850	1	1	0	23.0	21.87	1.30	0.11	0.372	0.48
	LTE 7	QPSK20M	Right Cheek	20850	1	50	0	22.0	21.31	1.17	0.08	0.288	0.34
	LTE 7	QPSK20M	Right Tilted	20850	0	1	0	23.0	21.87	1.30	0.09	0.168	0.22
	LTE 7	QPSK20M	Right Tilted	20850	0	50	0	22.0	21.31	1.17	0.05	0.132	0.15
	LTE 7	QPSK20M	Right Tilted	20850	1	1	0	23.0	21.87	1.30	0.12	0.224	0.29
	LTE 7	QPSK20M	Right Tilted	20850	1	50	0	22.0	21.31	1.17	-0.06	0.18	0.21
	LTE 7	QPSK20M	Left Cheek	20850	0	1	0	23.0	21.87	1.30	0.08	0.333	0.43
	LTE 7	QPSK20M	Left Cheek	20850	0	50	0	22.0	21.31	1.17	-0.05	0.257	0.30
	LTE 7	QPSK20M	Left Cheek	20850	1	1	0	23.0	21.87	1.30	0.05	0.115	0.15
	LTE 7	QPSK20M	Left Cheek	20850	1	50	0	22.0	21.31	1.17	0.07	0.089	0.10
	LTE 7	QPSK20M	Left Tilted	20850	0	1	0	23.0	21.87	1.30	0.06	0.046	0.06
	LTE 7	QPSK20M	Left Tilted	20850	0	50	0	22.0	21.31	1.17	0.07	0.033	0.04
	LTE 7	QPSK20M	Left Tilted	20850	1	1	0	23.0	21.87	1.30	0.13	0.078	0.10
	LTE 7	QPSK20M	Left Tilted	20850	1	50	0	22.0	21.31	1.17	0.14	0.063	0.07
07	LTE 13	QPSK10M	Right Cheek	23230	0	1	0	23.5	22.26	1.33	0.11	0.053	0.07
	LTE 13	QPSK10M	Right Cheek	23230	0	25	0	22.5	21.30	1.32	0.06	0.047	0.06
	LTE 13	QPSK10M	Right Cheek	23230	1	1	0	23.5	22.26	1.33	-0.10	0.055	0.07
	LTE 13	QPSK10M	Right Cheek	23230	1	25	0	22.5	21.30	1.32	0.10	0.039	0.05
	LTE 13	QPSK10M	Right Tilted	23230	0	1	0	23.5	22.26	1.33	0.03	0.021	0.03
	LTE 13	QPSK10M	Right Tilted	23230	0	25	0	22.5	21.30	1.32	0.06	0.017	0.02
	LTE 13	QPSK10M	Right Tilted	23230	1	1	0	23.5	22.26	1.33	0.15	0.028	0.04
	LTE 13	QPSK10M	Right Tilted	23230	1	25	0	22.5	21.30	1.32	0.09	0.018	0.02
	LTE 13	QPSK10M	Left Cheek	23230	0	1	0	23.5	22.26	1.33	-0.04	0.038	0.05
	LTE 13	QPSK10M	Left Cheek	23230	0	25	0	22.5	21.30	1.32	0.14	0.036	0.05
	LTE 13	QPSK10M	Left Cheek	23230	1	1	0	23.5	22.26	1.33	0.12	0.032	0.04
	LTE 13	QPSK10M	Left Cheek	23230	1	25	0	22.5	21.30	1.32	0.10	0.025	0.03
	LTE 13	QPSK10M	Left Tilted	23230	0	1	0	23.5	22.26	1.33	0.03	0.015	0.02
	LTE 13	QPSK10M	Left Tilted	23230	0	25	0	22.5	21.30	1.32	-0.05	0.012	0.02
	LTE 13	QPSK10M	Left Tilted	23230	1	1	0	23.5	22.26	1.33	0.09	0.016	0.02
	LTE 13	QPSK10M	Left Tilted	23230	1	25	0	22.5	21.30	1.32	-0.02	0.011	0.01
08	LTE 17	QPSK10M	Right Cheek	23790	0	1	0	23.5	21.88	1.45	-0.08	0.118	0.17
	LTE 17	QPSK10M	Right Cheek	23790	0	25	0	22.5	20.99	1.42	0.13	0.095	0.13
	LTE 17	QPSK10M	Right Cheek	23790	1	1	0	23.5	21.88	1.45	-0.06	0.031	0.05
	LTE 17	QPSK10M	Right Cheek	23790	1	25	0	22.5	20.99	1.42	0	0.026	0.04
	LTE 17	QPSK10M	Right Tilted	23790	0	1	0	23.5	21.88	1.45	0.04	0.085	0.12
	LTE 17	QPSK10M	Right Tilted	23790	0	25	0	22.5	20.99	1.42	0.06	0.068	0.10
	LTE 17	QPSK10M	Right Tilted	23790	1	1	0	23.5	21.88	1.45	-0.09	0.016	0.02
	LTE 17	QPSK10M	Right Tilted	23790	1	25	0	22.5	20.99	1.42	0.03	0.014	0.02
	LTE 17	QPSK10M	Left Cheek	23790	0	1	0	23.5	21.88	1.45	0.04	0.093	0.14
	LTE 17	QPSK10M	Left Cheek	23790	0	25	0	22.5	20.99	1.42	0.05	0.075	0.11
	LTE 17	QPSK10M	Left Cheek	23790	1	1	0	23.5	21.88	1.45	0.07	0.020	0.03
	LTE 17	QPSK10M	Left Cheek	23790	1	25	0	22.5	20.99	1.42	0.06	0.017	0.02
	LTE 17	QPSK10M	Left Tilted	23790	0	1	0	23.5	21.88	1.45	0.12	0.067	0.10
	LTE 17	QPSK10M	Left Tilted	23790	0	25	0	22.5	20.99	1.42	-0.01	0.043	0.06
	LTE 17	QPSK10M	Left Tilted	23790	1	1	0	23.5	21.88	1.45	0.01	0.011	0.02
	LTE 17	QPSK10M	Left Tilted	23790	1	25	0	22.5	20.99	1.42	0.09	0.007	0.01



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
09	LTE 26	QPSK15M	Right Cheek	26965	0	1	37	23.5	23.02	1.12	0.11	0.234	0.26
	LTE 26	QPSK15M	Right Cheek	26965	0	36	19	22.5	21.37	1.30	0.03	0.153	0.20
	LTE 26	QPSK15M	Right Cheek	26965	1	1	37	23.5	23.02	1.12	0	0.135	0.15
	LTE 26	QPSK15M	Right Cheek	26965	1	36	19	22.5	21.37	1.30	0.11	0.059	0.08
	LTE 26	QPSK15M	Right Tilted	26965	0	1	37	23.5	23.02	1.12	-0.1	0.145	0.16
	LTE 26	QPSK15M	Right Tilted	26965	0	36	19	22.5	21.37	1.30	-0.01	0.087	0.11
	LTE 26	QPSK15M	Right Tilted	26965	1	1	37	23.5	23.02	1.12	-0.02	0.062	0.07
	LTE 26	QPSK15M	Right Tilted	26965	1	36	19	22.5	21.37	1.30	-0.02	0.027	0.04
	LTE 26	QPSK15M	Left Cheek	26965	0	1	37	23.5	23.02	1.12	0.15	0.184	0.21
	LTE 26	QPSK15M	Left Cheek	26965	0	36	19	22.5	21.37	1.30	0.02	0.115	0.15
	LTE 26	QPSK15M	Left Cheek	26965	1	1	37	23.5	23.02	1.12	0.05	0.069	0.08
	LTE 26	QPSK15M	Left Cheek	26965	1	36	19	22.5	21.37	1.30	0.12	0.031	0.04
	LTE 26	QPSK15M	Left Tilted	26965	0	1	37	23.5	23.02	1.12	0.08	0.113	0.13
	LTE 26	QPSK15M	Left Tilted	26965	0	36	19	22.5	21.37	1.30	0.17	0.066	0.09
	LTE 26	QPSK15M	Left Tilted	26965	1	1	37	23.5	23.02	1.12	0.03	0.032	0.04
	LTE 26	QPSK15M	Left Tilted	26965	1	36	19	22.5	21.37	1.30	0.11	0.014	0.02
	LTE 41	QPSK20M	Right Cheek	40185	0	1	0	23.5	23.19	1.07	-0.18	0.087	0.09
	LTE 41	QPSK20M	Right Cheek	40185	0	50	0	22.5	22.07	1.10	-0.07	0.058	0.06
	LTE 41	QPSK20M	Right Cheek	40185	1	1	0	23.5	23.19	1.07	0.06	0.316	0.34
	LTE 41	QPSK20M	Right Cheek	40185	1	50	0	22.5	22.07	1.10	0.11	0.231	0.26
10	LTE 41	QPSK20M	Right Tilted	40185	0	1	0	23.5	23.19	1.07	0.13	0.075	0.08
	LTE 41	QPSK20M	Right Tilted	40185	0	50	0	22.5	22.07	1.10	-0.13	0.058	0.06
	LTE 41	QPSK20M	Right Tilted	40185	1	1	0	23.5	23.19	1.07	0.13	0.161	0.17
	LTE 41	QPSK20M	Right Tilted	40185	1	50	0	22.5	22.07	1.10	0.1	0.116	0.13
	LTE 41	QPSK20M	Left Cheek	40185	0	1	0	23.5	23.19	1.07	0.12	0.26	0.28
	LTE 41	QPSK20M	Left Cheek	40185	0	50	0	22.5	22.07	1.10	0.11	0.190	0.21
	LTE 41	QPSK20M	Left Cheek	40185	1	1	0	23.5	23.19	1.07	0.14	0.082	0.09
	LTE 41	QPSK20M	Left Cheek	40185	1	50	0	22.5	22.07	1.10	0.01	0.056	0.06
	LTE 41	QPSK20M	Left Tilted	40185	0	1	0	23.5	23.19	1.07	0.14	0.052	0.06
	LTE 41	QPSK20M	Left Tilted	40185	0	50	0	22.5	22.07	1.10	0.12	0.033	0.04
	LTE 41	QPSK20M	Left Tilted	40185	1	1	0	23.5	23.19	1.07	0.11	0.062	0.07
	LTE 41	QPSK20M	Left Tilted	40185	1	50	0	22.5	22.07	1.10	0.11	0.052	0.06

FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	2.4G WLAN	802.11b	Right Cheek	11	0	20.0	18.49	1.42	0.04	0.17	0.24
	2.4G WLAN	802.11b	Right Cheek	11	1	20.0	18.43	1.44	0	0.000487	0.00
	2.4G WLAN	802.11n HT40	Right Cheek	3	0+1	18.0	16.28	1.49	0.04	0.037	0.05
	2.4G WLAN	802.11b	Right Tilted	11	0	20.0	18.49	1.42	0.11	0.076	0.11
	2.4G WLAN	802.11b	Right Tilted	11	1	20.0	18.43	1.44	0	0.000456	0.00
	2.4G WLAN	802.11n HT40	Right Tilted	3	0+1	18.0	16.28	1.49	0.05	0.00704	0.01
11	2.4G WLAN	802.11b	Left Cheek	11	0	20.0	18.49	1.42	0.10	0.544	0.77
	2.4G WLAN	802.11b	Left Cheek	11	1	20.0	18.43	1.44	0.12	0	0.00
	2.4G WLAN	802.11n HT40	Left Cheek	3	0+1	18.0	16.28	1.49	0.1	0.157	0.23
	2.4G WLAN	802.11b	Left Tilted	11	0	20.0	18.49	1.42	0.06	0.279	0.40
	2.4G WLAN	802.11b	Left Tilted	11	1	20.0	18.43	1.44	0.12	0	0.00
	2.4G WLAN	802.11n HT40	Left Tilted	3	0+1	18.0	16.28	1.49	0.03	0.073	0.11
	5.3G WLAN	802.11ac VH80	Right Cheek	58	0	17.5	15.76	1.49	0.11	0.217	0.32
	5.3G WLAN	802.11ac VH80	Right Cheek	58	1	17.5	15.75	1.50	0.01	0	0.00
	5.3G WLAN	802.11ac VH80	Right Cheek	58	0+1	17.5	15.98	1.42	-0.16	0.147	0.21
	5.3G WLAN	802.11ac VH80	Right Tilted	58	0	17.5	15.76	1.49	0.12	0.174	0.26
	5.3G WLAN	802.11ac VH80	Right Tilted	58	1	17.5	15.75	1.50	0.12	0	0.00
	5.3G WLAN	802.11ac VH80	Right Tilted	58	0+1	17.5	15.98	1.42	0.11	0.119	0.17
12	5.3G WLAN	802.11ac VH80	Left Cheek	58	0	17.5	15.76	1.49	-0.13	0.526	0.79
	5.3G WLAN	802.11ac VH80	Left Cheek	58	1	17.5	15.75	1.50	0	0	0.00
	5.3G WLAN	802.11ac VH80	Left Cheek	58	0+1	17.5	15.98	1.42	0.07	0.425	0.60
	5.3G WLAN	802.11ac VH80	Left Tilted	58	0	17.5	15.76	1.49	0.14	0.421	0.63
	5.3G WLAN	802.11ac VH80	Left Tilted	58	1	17.5	15.75	1.50	0.12	0	0.00
	5.3G WLAN	802.11ac VH80	Left Tilted	58	0+1	17.5	15.98	1.42	0.12	0.035	0.05
	5.6G WLAN	802.11ac VH80	Right Cheek	106	0	17.5	16.01	1.41	-0.01	0.198	0.28
	5.6G WLAN	802.11ac VH80	Right Cheek	106	1	17.5	15.94	1.43	0	0	0.00
	5.6G WLAN	802.11ac VH80	Right Cheek	106	0+1	17.5	16.33	1.31	0.16	0.191	0.25
	5.6G WLAN	802.11ac VH80	Right Tilted	106	0	17.5	16.01	1.41	0.11	0.144	0.20
	5.6G WLAN	802.11ac VH80	Right Tilted	106	1	17.5	15.94	1.43	0	0	0.00
	5.6G WLAN	802.11ac VH80	Right Tilted	106	0+1	17.5	16.33	1.31	0	0	0.00
13	5.6G WLAN	802.11ac VH80	Left Cheek	106	0	17.5	16.01	1.41	-0.16	0.535	0.75
	5.6G WLAN	802.11ac VH80	Left Cheek	106	1	17.5	15.94	1.43	0	0	0.00
	5.6G WLAN	802.11ac VH80	Left Cheek	106	0+1	17.5	16.33	1.31	0.02	0.504	0.66
	5.6G WLAN	802.11ac VH80	Left Tilted	106	0	17.5	16.01	1.41	0.1	0.389	0.55
	5.6G WLAN	802.11ac VH80	Left Tilted	106	1	17.5	15.94	1.43	0	0	0.00
	5.6G WLAN	802.11ac VH80	Left Tilted	106	0+1	17.5	16.33	1.31	0	0	0.00
	5.8G WLAN	802.11ac VH80	Right Cheek	155	0	17.5	15.77	1.49	0	0.291	0.43
	5.8G WLAN	802.11ac VH80	Right Cheek	155	1	17.5	15.65	1.53	0	0	0.00
	5.8G WLAN	802.11ac VH80	Right Cheek	155	0+1	17.5	16.37	1.30	0	0.037	0.05
	5.8G WLAN	802.11ac VH80	Right Tilted	155	0	17.5	15.77	1.49	0	0.155	0.23
	5.8G WLAN	802.11ac VH80	Right Tilted	155	1	17.5	15.65	1.53	0	0	0.00
	5.8G WLAN	802.11ac VH80	Right Tilted	155	0+1	17.5	16.37	1.30	0	0.043	0.06
14	5.8G WLAN	802.11ac VH80	Left Cheek	155	0	17.5	15.77	1.49	0.11	0.384	0.57
	5.8G WLAN	802.11ac VH80	Left Cheek	155	1	17.5	15.65	1.53	0	0	0.00
	5.8G WLAN	802.11ac VH80	Left Cheek	155	0+1	17.5	16.37	1.30	0.16	0.16	0.21
	5.8G WLAN	802.11ac VH80	Left Tilted	155	0	17.5	15.77	1.49	0.1	0.231	0.34
	5.8G WLAN	802.11ac VH80	Left Tilted	155	1	17.5	15.65	1.53	0	0	0.00
	5.8G WLAN	802.11ac VH80	Left Tilted	155	0+1	17.5	16.37	1.30	0	0.106	0.14

4.7.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	GSM850	GPRS 10	Front Face	251	0	32.0	30.91	1.29	0.02	0.282	0.36
	GSM850	GPRS 10	Front Face	251	1	32.0	30.91	1.29	0.11	0.024	0.03
15	GSM850	GPRS 10	Rear Face	251	0	32.0	30.91	1.29	-0.09	0.326	0.42
	GSM850	GPRS 10	Rear Face	251	1	32.0	30.91	1.29	-0.06	0.032	0.04
	GSM1900	GPRS12	Front Face	512	0	26.0	25.44	1.14	0.13	0.170	0.19
	GSM1900	GPRS12	Front Face	512	1	26.0	25.44	1.14	-0.03	0.056	0.06
16	GSM1900	GPRS12	Rear Face	512	0	26.0	25.44	1.14	-0.02	0.195	0.22
	GSM1900	GPRS12	Rear Face	512	1	26.0	25.44	1.14	-0.06	0.058	0.07
	WCDMA II	RMC12.2K	Front Face	9400	0	24.0	22.62	1.37	0.13	0.274	0.38
	WCDMA II	RMC12.2K	Front Face	9400	1	24.0	22.62	1.37	0.05	0.115	0.16
17	WCDMA II	RMC12.2K	Rear Face	9400	0	24.0	22.62	1.37	-0.09	0.390	0.54
	WCDMA II	RMC12.2K	Rear Face	9400	1	24.0	22.62	1.37	0.11	0.121	0.17
	WCDMA V	RMC12.2K	Front Face	4182	0	24.0	22.93	1.28	-0.01	0.275	0.35
	WCDMA V	RMC12.2K	Front Face	4182	1	24.0	22.93	1.28	0.1	0.020	0.03
18	WCDMA V	RMC12.2K	Rear Face	4182	0	24.0	22.93	1.28	0.15	0.330	0.42
	WCDMA V	RMC12.2K	Rear Face	4182	1	24.0	22.93	1.28	0.06	0.027	0.03

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 5	QPSK10M	Front Face	20450	0	1	24	23.0	22.45	1.14	0.01	0.148	0.17
	LTE 5	QPSK10M	Front Face	20450	0	25	12	22.0	21.48	1.13	0.08	0.129	0.15
	LTE 5	QPSK10M	Front Face	20450	1	1	24	23.0	22.45	1.14	0.1	0.0047	0.01
	LTE 5	QPSK10M	Front Face	20450	1	25	12	22.0	21.48	1.13	0.15	0.0037	0.00
19	LTE 5	QPSK10M	Rear Face	20450	0	1	24	23.0	22.45	1.14	0.01	0.177	0.20
	LTE 5	QPSK10M	Rear Face	20450	0	25	12	22.0	21.48	1.13	-0.11	0.152	0.17
	LTE 5	QPSK10M	Rear Face	20450	1	1	24	23.0	22.45	1.14	-0.13	0.00797	0.01
	LTE 5	QPSK10M	Rear Face	20450	1	25	12	22.0	21.48	1.13	0.06	0.0061	0.01
20	LTE 7	QPSK20M	Front Face	20850	0	1	0	23.0	21.87	1.30	0.01	0.425	0.55
	LTE 7	QPSK20M	Front Face	20850	0	50	0	22.0	21.31	1.17	-0.07	0.348	0.41
	LTE 7	QPSK20M	Front Face	20850	1	1	0	23.0	21.87	1.30	0.06	0.051	0.07
	LTE 7	QPSK20M	Front Face	20850	1	50	0	22.0	21.31	1.17	-0.06	0.039	0.05
	LTE 7	QPSK20M	Rear Face	20850	0	1	0	23.0	21.87	1.30	0.11	0.337	0.44
	LTE 7	QPSK20M	Rear Face	20850	0	50	0	22.0	21.31	1.17	-0.06	0.266	0.31
	LTE 7	QPSK20M	Rear Face	20850	1	1	0	23.0	21.87	1.30	0.07	0.073	0.09
	LTE 7	QPSK20M	Rear Face	20850	1	50	0	22.0	21.31	1.17	0.02	0.056	0.07
	LTE 13	QPSK10M	Front Face	23230	0	1	0	23.5	22.26	1.33	0.06	0.274	0.36
	LTE 13	QPSK10M	Front Face	23230	0	25	0	22.5	21.30	1.32	-0.01	0.219	0.29
	LTE 13	QPSK10M	Front Face	23230	1	1	0	23.5	22.26	1.33	-0.06	0.0111	0.01
	LTE 13	QPSK10M	Front Face	23230	1	25	0	22.5	21.30	1.32	0.1	0.0091	0.01
21	LTE 13	QPSK10M	Rear Face	23230	0	1	0	23.5	22.26	1.33	-0.02	0.316	0.42
	LTE 13	QPSK10M	Rear Face	23230	0	25	0	22.5	21.30	1.32	0.01	0.261	0.34
	LTE 13	QPSK10M	Rear Face	23230	1	1	0	23.5	22.26	1.33	0.13	0.014	0.02
	LTE 13	QPSK10M	Rear Face	23230	1	25	0	22.5	21.30	1.32	-0.05	0.01278	0.02



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 17	QPSK10M	Front Face	23790	0	1	0	23.5	21.88	1.45	0.01	0.202	0.29
	LTE 17	QPSK10M	Front Face	23790	0	25	0	22.5	20.99	1.42	0.06	0.179	0.25
	LTE 17	QPSK10M	Front Face	23790	1	1	0	23.5	21.88	1.45	0.11	0.00575	0.01
	LTE 17	QPSK10M	Front Face	23790	1	25	0	22.5	20.99	1.42	-0.02	0.00338	0.00
22	LTE 17	QPSK10M	Rear Face	23790	0	1	0	23.5	21.88	1.45	0	0.250	0.36
	LTE 17	QPSK10M	Rear Face	23790	0	25	0	22.5	20.99	1.42	0.07	0.217	0.31
	LTE 17	QPSK10M	Rear Face	23790	1	1	0	23.5	21.88	1.45	0.08	0.00613	0.01
	LTE 17	QPSK10M	Rear Face	23790	1	25	0	22.5	20.99	1.42	0.04	0.00556	0.01
	LTE 26	QPSK15M	Front Face	26965	0	1	37	23.5	23.02	1.12	0.1	0.194	0.22
	LTE 26	QPSK15M	Front Face	26965	0	36	19	22.5	21.37	1.30	0.02	0.139	0.18
	LTE 26	QPSK15M	Front Face	26965	1	1	37	23.5	23.02	1.12	-0.05	0.012	0.01
	LTE 26	QPSK15M	Front Face	26965	1	36	19	22.5	21.37	1.30	-0.13	0.011	0.01
23	LTE 26	QPSK15M	Rear Face	26965	0	1	37	23.5	23.02	1.12	0.06	0.246	0.27
	LTE 26	QPSK15M	Rear Face	26965	0	36	19	22.5	21.37	1.30	0.15	0.171	0.22
	LTE 26	QPSK15M	Rear Face	26965	1	1	37	23.5	23.02	1.12	0.02	0.027	0.03
	LTE 26	QPSK15M	Rear Face	26965	1	36	19	22.5	21.37	1.30	0.01	0.0157	0.02
24	LTE 41	QPSK20M	Front Face	40185	0	1	0	23.5	23.19	1.07	0.05	0.296	0.32
	LTE 41	QPSK20M	Front Face	40185	0	50	0	22.5	22.07	1.10	0.02	0.222	0.25
	LTE 41	QPSK20M	Front Face	40185	1	1	0	23.5	23.19	1.07	-0.16	0.028	0.03
	LTE 41	QPSK20M	Front Face	40185	1	50	0	22.5	22.07	1.10	0.03	0.019	0.02
	LTE 41	QPSK20M	Rear Face	40185	0	1	0	23.5	23.19	1.07	0.09	0.232	0.25
	LTE 41	QPSK20M	Rear Face	40185	0	50	0	22.5	22.07	1.10	0	0.168	0.19
	LTE 41	QPSK20M	Rear Face	40185	1	1	0	23.5	23.19	1.07	0.11	0.038	0.04
	LTE 41	QPSK20M	Rear Face	40185	1	50	0	22.5	22.07	1.10	0.06	0.019322	0.02

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
25	2.4G WLAN	802.11b	Front Face	11	0	20.0	18.49	1.42	0.13	0.136	0.19
	2.4G WLAN	802.11b	Front Face	11	1	20.0	18.43	1.44	0.01	0.006	0.01
	2.4G WLAN	802.11n HT40	Front Face	3	0+1	18.0	16.28	1.49	0.16	0.012	0.02
	2.4G WLAN	802.11b	Rear Face	11	0	20.0	18.49	1.42	0.06	0.079	0.11
	2.4G WLAN	802.11b	Rear Face	11	1	20.0	18.43	1.44	-0.11	0.0065	0.01
	2.4G WLAN	802.11n HT40	Rear Face	3	0+1	18.0	16.28	1.49	0.11	0.006	0.01
	5.3G WLAN	802.11ac VH80	Front Face	58	0	17.5	15.76	1.49	0.04	0.020	0.03
26	5.3G WLAN	802.11ac VH80	Front Face	58	1	17.5	15.75	1.50	-0.09	0.029	0.04
	5.3G WLAN	802.11ac VH80	Front Face	58	0+1	17.5	15.98	1.42	0.02	0.021	0.03
	5.3G WLAN	802.11ac VH80	Rear Face	58	0	17.5	15.76	1.49	0.03	0.001	0.00
	5.3G WLAN	802.11ac VH80	Rear Face	58	1	17.5	15.75	1.50	0.06	0	0.00
	5.3G WLAN	802.11ac VH80	Rear Face	58	0+1	17.5	15.98	1.42	0.07	0	0.00
	5.6G WLAN	802.11ac VH80	Front Face	106	0	17.5	16.01	1.41	0.06	0.021	0.03
27	5.6G WLAN	802.11ac VH80	Front Face	106	1	17.5	15.94	1.43	0.08	0.040	0.06
	5.6G WLAN	802.11ac VH80	Front Face	106	0+1	17.5	16.33	1.31	0.01	0.027	0.04
	5.6G WLAN	802.11ac VH80	Rear Face	106	0	17.5	16.01	1.41	0	7.767E-05	0.00
	5.6G WLAN	802.11ac VH80	Rear Face	106	1	17.5	15.94	1.43	0	0.000837	0.00
	5.6G WLAN	802.11ac VH80	Rear Face	106	0+1	17.5	16.33	1.31	0.12	0.00375	0.00
28	5.8G WLAN	802.11ac VH80	Front Face	155	0	17.5	15.77	1.49	0.03	0.023	0.03
	5.8G WLAN	802.11ac VH80	Front Face	155	1	17.5	15.65	1.53	0.05	0.00496	0.01
	5.8G WLAN	802.11ac VH80	Front Face	155	0+1	17.5	16.37	1.30	-0.01	0	0.00
	5.8G WLAN	802.11ac VH80	Rear Face	155	0	17.5	15.77	1.49	0.01	0	0.00
	5.8G WLAN	802.11ac VH80	Rear Face	155	1	17.5	15.65	1.53	0.05	0	0.00
	5.8G WLAN	802.11ac VH80	Rear Face	155	0+1	17.5	16.37	1.30	0.09	0	0.00

Plot No.	Band	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
29	Bluetooth	Front Face	0	10.5	9.18	1.36	0.17	0.000623	0.00
	Bluetooth	Rear Face	0	10.5	9.18	1.36	0.11	0.000189	0.00

4.7.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
15	GSM850	GPRS 10	Front Face	251	0	32.0	30.91	1.29	0.02	0.282	0.36
	GSM850	GPRS 10	Front Face	251	1	32.0	30.91	1.29	0.11	0.024	0.03
	GSM850	GPRS 10	Rear Face	251	0	32.0	30.91	1.29	-0.09	0.326	0.42
	GSM850	GPRS 10	Rear Face	251	1	32.0	30.91	1.29	-0.06	0.032	0.04
	GSM850	GPRS 10	Left Side	251	0	32.0	30.91	1.29	0.08	0.211	0.27
	GSM850	GPRS 10	Left Side	251	1	32.0	30.91	1.29	-0.05	0.032	0.04
	GSM850	GPRS 10	Right Side	251	0	32.0	30.91	1.29	-0.11	0.233	0.30
	GSM850	GPRS 10	Right Side	251	1	32.0	30.91	1.29	-0.06	0.019	0.02
	GSM850	GPRS 10	Bottom Side	251	0	32.0	30.91	1.29	-0.15	0	0.00
	GSM850	GPRS 10	Top Side	251	1	32.0	30.91	1.29	0.1	0.002	0.00
	GSM1900	GPRS12	Front Face	512	0	26.0	25.44	1.14	0.13	0.170	0.19
	GSM1900	GPRS12	Front Face	512	1	26.0	25.44	1.14	-0.03	0.056	0.06
	GSM1900	GPRS12	Rear Face	512	0	26.0	25.44	1.14	-0.02	0.195	0.22
	GSM1900	GPRS12	Rear Face	512	1	26.0	25.44	1.14	-0.06	0.058	0.07
	GSM1900	GPRS12	Left Side	512	0	26.0	25.44	1.14	-0.02	0.169	0.19
	GSM1900	GPRS12	Left Side	512	1	26.0	25.44	1.14	0.09	0.052	0.06
	GSM1900	GPRS12	Right Side	512	0	26.0	25.44	1.14	0.1	0.016	0.02
	GSM1900	GPRS12	Right Side	512	1	26.0	25.44	1.14	-0.04	0.00573	0.01
	GSM1900	GPRS12	Bottom Side	512	0	26.0	25.44	1.14	0.15	0.209	0.24
	GSM1900	GPRS12	Top Side	512	1	26.0	25.44	1.14	0.04	0.07	0.08
	WCDMA II	RMC12.2K	Front Face	9400	0	24.0	22.62	1.37	0.13	0.274	0.38
	WCDMA II	RMC12.2K	Front Face	9400	1	24.0	22.62	1.37	0.05	0.115	0.16
	WCDMA II	RMC12.2K	Rear Face	9400	0	24.0	22.62	1.37	-0.09	0.39	0.54
	WCDMA II	RMC12.2K	Rear Face	9400	1	24.0	22.62	1.37	0.11	0.121	0.17
	WCDMA II	RMC12.2K	Left Side	9400	0	24.0	22.62	1.37	0.09	0.299	0.41
	WCDMA II	RMC12.2K	Left Side	9400	1	24.0	22.62	1.37	0.04	0.12	0.16
	WCDMA II	RMC12.2K	Right Side	9400	0	24.0	22.62	1.37	0.02	0.013	0.02
	WCDMA II	RMC12.2K	Right Side	9400	1	24.0	22.62	1.37	0.07	0.018	0.02
	WCDMA II	RMC12.2K	Bottom Side	9400	0	24.0	22.62	1.37	0.14	0.463	0.64
	WCDMA II	RMC12.2K	Top Side	9400	1	24.0	22.62	1.37	0.12	0.143	0.20
18	WCDMA V	RMC12.2K	Front Face	4182	0	24.0	22.93	1.28	-0.01	0.275	0.35
	WCDMA V	RMC12.2K	Front Face	4182	1	24.0	22.93	1.28	0.1	0.020	0.03
	WCDMA V	RMC12.2K	Rear Face	4182	0	24.0	22.93	1.28	0.15	0.330	0.42
	WCDMA V	RMC12.2K	Rear Face	4182	1	24.0	22.93	1.28	0.06	0.027	0.03
	WCDMA V	RMC12.2K	Left Side	4182	0	24.0	22.93	1.28	-0.12	0.196	0.25
	WCDMA V	RMC12.2K	Left Side	4182	1	24.0	22.93	1.28	0.02	0.025	0.03
	WCDMA V	RMC12.2K	Right Side	4182	0	24.0	22.93	1.28	-0.17	0.223	0.29
	WCDMA V	RMC12.2K	Right Side	4182	1	24.0	22.93	1.28	0.16	0.01	0.01
	WCDMA V	RMC12.2K	Bottom Side	4182	0	24.0	22.93	1.28	0.11	0.044	0.06
	WCDMA V	RMC12.2K	Top Side	4182	1	24.0	22.93	1.28	0.13	0.00789	0.01



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
19	LTE 5	QPSK10M	Front Face	20450	0	1	24	23.0	22.45	1.14	0.01	0.148	0.17
	LTE 5	QPSK10M	Front Face	20450	0	25	12	22.0	21.48	1.13	0.08	0.129	0.15
	LTE 5	QPSK10M	Front Face	20450	1	1	24	23.0	22.45	1.14	0.1	0.0047	0.01
	LTE 5	QPSK10M	Front Face	20450	1	25	12	22.0	21.48	1.13	0.15	0.0037	0.00
	LTE 5	QPSK10M	Rear Face	20450	0	1	24	23.0	22.45	1.14	0.01	0.177	0.20
	LTE 5	QPSK10M	Rear Face	20450	0	25	12	22.0	21.48	1.13	-0.11	0.152	0.17
	LTE 5	QPSK10M	Rear Face	20450	1	1	24	23.0	22.45	1.14	-0.13	0.00797	0.01
	LTE 5	QPSK10M	Rear Face	20450	1	25	12	22.0	21.48	1.13	0.06	0.0061	0.01
	LTE 5	QPSK10M	Left Side	20450	0	1	24	23.0	22.45	1.14	-0.05	0.106	0.12
	LTE 5	QPSK10M	Left Side	20450	0	25	12	22.0	21.48	1.13	-0.02	0.109	0.12
	LTE 5	QPSK10M	Left Side	20450	1	1	24	23.0	22.45	1.14	-0.16	0.0035	0.00
	LTE 5	QPSK10M	Left Side	20450	1	25	12	22.0	21.48	1.13	-0.18	0.0029	0.00
	LTE 5	QPSK10M	Right Side	20450	0	1	24	23.0	22.45	1.14	-0.08	0.127	0.14
	LTE 5	QPSK10M	Right Side	20450	0	25	12	22.0	21.48	1.13	-0.17	0.092	0.10
	LTE 5	QPSK10M	Right Side	20450	1	1	24	23.0	22.45	1.14	0.01	0.0022	0.00
	LTE 5	QPSK10M	Right Side	20450	1	25	12	22.0	21.48	1.13	0.15	0.0022	0.00
	LTE 5	QPSK10M	Bottom Side	20450	0	1	24	23.0	22.45	1.14	0	0	0.00
	LTE 5	QPSK10M	Bottom Side	20450	0	25	12	22.0	21.48	1.13	0.01	0	0.00
	LTE 5	QPSK10M	Top Side	20450	1	1	24	23.0	22.45	1.14	-0.06	0.0003	0.00
	LTE 5	QPSK10M	Top Side	20450	1	25	12	22.0	21.48	1.13	0.07	0.0001	0.00
20	LTE 7	QPSK20M	Front Face	20850	0	1	0	23.0	21.87	1.30	0.01	0.425	0.55
	LTE 7	QPSK20M	Front Face	20850	0	50	0	22.0	21.31	1.17	-0.07	0.348	0.41
	LTE 7	QPSK20M	Front Face	20850	1	1	0	23.0	21.87	1.30	0.06	0.051	0.07
	LTE 7	QPSK20M	Front Face	20850	1	50	0	22.0	21.31	1.17	-0.06	0.039	0.05
	LTE 7	QPSK20M	Rear Face	20850	0	1	0	23.0	21.87	1.30	0.11	0.337	0.44
	LTE 7	QPSK20M	Rear Face	20850	0	50	0	22.0	21.31	1.17	-0.06	0.266	0.31
	LTE 7	QPSK20M	Rear Face	20850	1	1	0	23.0	21.87	1.30	0.07	0.073	0.09
	LTE 7	QPSK20M	Rear Face	20850	1	50	0	22.0	21.31	1.17	0.02	0.056	0.07
	LTE 7	QPSK20M	Left Side	20850	0	1	0	23.0	21.87	1.30	0.12	0.38	0.49
	LTE 7	QPSK20M	Left Side	20850	0	50	0	22.0	21.31	1.17	0.11	0.299	0.35
	LTE 7	QPSK20M	Left Side	20850	1	1	0	23.0	21.87	1.30	0.05	0.083	0.11
	LTE 7	QPSK20M	Left Side	20850	1	50	0	22.0	21.31	1.17	-0.03	0.064	0.08
	LTE 7	QPSK20M	Right Side	20850	0	1	0	23.0	21.87	1.30	0.08	0.00575	0.01
	LTE 7	QPSK20M	Right Side	20850	0	50	0	22.0	21.31	1.17	0.08	0.00299	0.00
	LTE 7	QPSK20M	Right Side	20850	1	1	0	23.0	21.87	1.30	0	0	0.00
	LTE 7	QPSK20M	Right Side	20850	1	50	0	22.0	21.31	1.17	0	0	0.00
	LTE 7	QPSK20M	Bottom Side	20850	0	1	0	23.0	21.87	1.30	0.09	0.215	0.28
	LTE 7	QPSK20M	Bottom Side	20850	0	50	0	22.0	21.31	1.17	0.04	0.165	0.19
	LTE 7	QPSK20M	Top Side	20850	1	1	0	23.0	21.87	1.30	0.05	0.02	0.03
	LTE 7	QPSK20M	Top Side	20850	1	50	0	22.0	21.31	1.17	0.03	0.013	0.02



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 13	QPSK10M	Front Face	23230	0	1	0	23.5	22.26	1.33	0.06	0.274	0.36
	LTE 13	QPSK10M	Front Face	23230	0	25	0	22.5	21.30	1.32	-0.01	0.219	0.29
	LTE 13	QPSK10M	Front Face	23230	1	1	0	23.5	22.26	1.33	-0.06	0.0111	0.01
	LTE 13	QPSK10M	Front Face	23230	1	25	0	22.5	21.30	1.32	0.1	0.0091	0.01
21	LTE 13	QPSK10M	Rear Face	23230	0	1	0	23.5	22.26	1.33	-0.02	0.316	0.42
	LTE 13	QPSK10M	Rear Face	23230	0	25	0	22.5	21.30	1.32	0.01	0.261	0.34
	LTE 13	QPSK10M	Rear Face	23230	1	1	0	23.5	22.26	1.33	0.13	0.014	0.02
	LTE 13	QPSK10M	Rear Face	23230	1	25	0	22.5	21.30	1.32	-0.05	0.01278	0.02
	LTE 13	QPSK10M	Left Side	23230	0	1	0	23.5	22.26	1.33	0.08	0.185	0.25
	LTE 13	QPSK10M	Left Side	23230	0	25	0	22.5	21.30	1.32	0.11	0.155	0.20
	LTE 13	QPSK10M	Left Side	23230	1	1	0	23.5	22.26	1.33	0.07	0.00441	0.01
	LTE 13	QPSK10M	Left Side	23230	1	25	0	22.5	21.30	1.32	0.02	0.00415	0.01
	LTE 13	QPSK10M	Right Side	23230	0	1	0	23.5	22.26	1.33	0.03	0.227	0.30
	LTE 13	QPSK10M	Right Side	23230	0	25	0	22.5	21.30	1.32	-0.02	0.185	0.24
	LTE 13	QPSK10M	Right Side	23230	1	1	0	23.5	22.26	1.33	0.01	0.00301	0.00
	LTE 13	QPSK10M	Right Side	23230	1	25	0	22.5	21.30	1.32	0.07	0.00214	0.00
	LTE 13	QPSK10M	Bottom Side	23230	0	1	0	23.5	22.26	1.33	0.08	0.06	0.08
	LTE 13	QPSK10M	Bottom Side	23230	0	25	0	22.5	21.30	1.32	0	0	0.00
	LTE 13	QPSK10M	Top Side	23230	1	1	0	23.5	22.26	1.33	-0.04	0.00096	0.00
	LTE 13	QPSK10M	Top Side	23230	1	25	0	22.5	21.30	1.32	0.04	0.00017	0.00
	LTE 17	QPSK10M	Front Face	23790	0	1	0	23.5	21.88	1.45	0.01	0.202	0.29
	LTE 17	QPSK10M	Front Face	23790	0	25	0	22.5	20.99	1.42	0.06	0.179	0.25
	LTE 17	QPSK10M	Front Face	23790	1	1	0	23.5	21.88	1.45	0.11	0.00575	0.01
	LTE 17	QPSK10M	Front Face	23790	1	25	0	22.5	20.99	1.42	-0.02	0.00338	0.00
22	LTE 17	QPSK10M	Rear Face	23790	0	1	0	23.5	21.88	1.45	0	0.250	0.36
	LTE 17	QPSK10M	Rear Face	23790	0	25	0	22.5	20.99	1.42	0.07	0.217	0.31
	LTE 17	QPSK10M	Rear Face	23790	1	1	0	23.5	21.88	1.45	0.08	0.00613	0.01
	LTE 17	QPSK10M	Rear Face	23790	1	25	0	22.5	20.99	1.42	0.04	0.00556	0.01
	LTE 17	QPSK10M	Left Side	23790	0	1	0	23.5	21.88	1.45	-0.02	0.192	0.28
	LTE 17	QPSK10M	Left Side	23790	0	25	0	22.5	20.99	1.42	0.05	0.162	0.23
	LTE 17	QPSK10M	Left Side	23790	1	1	0	23.5	21.88	1.45	0.04	0.00344	0.00
	LTE 17	QPSK10M	Left Side	23790	1	25	0	22.5	20.99	1.42	-0.12	0.00311	0.00
	LTE 17	QPSK10M	Right Side	23790	0	1	0	23.5	21.88	1.45	-0.01	0.214	0.31
	LTE 17	QPSK10M	Right Side	23790	0	25	0	22.5	20.99	1.42	0.1	0.182	0.26
	LTE 17	QPSK10M	Right Side	23790	1	1	0	23.5	21.88	1.45	-0.08	0.00028	0.00
	LTE 17	QPSK10M	Right Side	23790	1	25	0	22.5	20.99	1.42	0.05	0.00024	0.00
	LTE 17	QPSK10M	Bottom Side	23790	0	1	0	23.5	21.88	1.45	0	0	0.00
	LTE 17	QPSK10M	Bottom Side	23790	0	25	0	22.5	20.99	1.42	0	0	0.00
	LTE 17	QPSK10M	Top Side	23790	1	1	0	23.5	21.88	1.45	0.01	0	0.00
	LTE 17	QPSK10M	Top Side	23790	1	25	0	22.5	20.99	1.42	0	0	0.00



FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 26	QPSK15M	Front Face	26965	0	1	37	23.5	23.02	1.12	0.1	0.194	0.22
	LTE 26	QPSK15M	Front Face	26965	0	36	19	22.5	21.37	1.30	0.02	0.139	0.18
	LTE 26	QPSK15M	Front Face	26965	1	1	37	23.5	23.02	1.12	-0.05	0.012	0.01
	LTE 26	QPSK15M	Front Face	26965	1	36	19	22.5	21.37	1.30	-0.13	0.011	0.01
23	LTE 26	QPSK15M	Rear Face	26965	0	1	37	23.5	23.02	1.12	0.06	0.246	0.27
	LTE 26	QPSK15M	Rear Face	26965	0	36	19	22.5	21.37	1.30	0.15	0.171	0.22
	LTE 26	QPSK15M	Rear Face	26965	1	1	37	23.5	23.02	1.12	0.02	0.027	0.03
	LTE 26	QPSK15M	Rear Face	26965	1	36	19	22.5	21.37	1.30	0.01	0.0157	0.02
	LTE 26	QPSK15M	Left Side	26965	0	1	37	23.5	23.02	1.12	-0.1	0.129	0.14
	LTE 26	QPSK15M	Left Side	26965	0	36	19	22.5	21.37	1.30	0.09	0.087	0.11
	LTE 26	QPSK15M	Left Side	26965	1	1	37	23.5	23.02	1.12	0.06	0.0131	0.01
	LTE 26	QPSK15M	Left Side	26965	1	36	19	22.5	21.37	1.30	0.03	0.0068	0.01
	LTE 26	QPSK15M	Right Side	26965	0	1	37	23.5	23.02	1.12	0.05	0.165	0.18
	LTE 26	QPSK15M	Right Side	26965	0	36	19	22.5	21.37	1.30	0.12	0.121	0.16
	LTE 26	QPSK15M	Right Side	26965	1	1	37	23.5	23.02	1.12	0.05	0.0087	0.01
	LTE 26	QPSK15M	Right Side	26965	1	36	19	22.5	21.37	1.30	-0.02	0.0045	0.01
	LTE 26	QPSK15M	Bottom Side	26965	0	1	37	23.5	23.02	1.12	-0.01	0.046	0.05
	LTE 26	QPSK15M	Bottom Side	26965	0	36	19	22.5	21.37	1.30	0	0	0.00
	LTE 26	QPSK15M	Top Side	26965	1	1	37	23.5	23.02	1.12	0.02	0.0020	0.00
	LTE 26	QPSK15M	Top Side	26965	1	36	19	22.5	21.37	1.30	0.1	0.00014	0.00
24	LTE 41	QPSK20M	Front Face	40185	0	1	0	23.5	23.19	1.07	0.05	0.296	0.32
	LTE 41	QPSK20M	Front Face	40185	0	50	0	22.5	22.07	1.10	0.02	0.222	0.25
	LTE 41	QPSK20M	Front Face	40185	1	1	0	23.5	23.19	1.07	-0.16	0.028	0.03
	LTE 41	QPSK20M	Front Face	40185	1	50	0	22.5	22.07	1.10	0.03	0.019	0.02
	LTE 41	QPSK20M	Rear Face	40185	0	1	0	23.5	23.19	1.07	0.09	0.232	0.25
	LTE 41	QPSK20M	Rear Face	40185	0	50	0	22.5	22.07	1.10	0	0.168	0.19
	LTE 41	QPSK20M	Rear Face	40185	1	1	0	23.5	23.19	1.07	0.11	0.038	0.04
	LTE 41	QPSK20M	Rear Face	40185	1	50	0	22.5	22.07	1.10	0.06	0.019322	0.02
	LTE 41	QPSK20M	Left Side	40185	0	1	0	23.5	23.19	1.07	-0.05	0.275	0.30
	LTE 41	QPSK20M	Left Side	40185	0	50	0	22.5	22.07	1.10	0.02	0.203	0.22
	LTE 41	QPSK20M	Left Side	40185	1	1	0	23.5	23.19	1.07	-0.07	0.0360678	0.04
	LTE 41	QPSK20M	Left Side	40185	1	50	0	22.5	22.07	1.10	0.12	0.0251186	0.03
	LTE 41	QPSK20M	Right Side	40185	0	1	0	23.5	23.19	1.07	-0.02	0.016	0.02
	LTE 41	QPSK20M	Right Side	40185	0	50	0	22.5	22.07	1.10	0.06	0.010	0.01
	LTE 41	QPSK20M	Top Side	40185	0	1	0	23.5	23.19	1.07	0.11	0.0065	0.01
	LTE 41	QPSK20M	Top Side	40185	0	50	0	22.5	22.07	1.10	0.12	0.0055	0.01
	LTE 41	QPSK20M	Right Side	40185	1	1	0	23.5	23.19	1.07	-0.11	0.0006132	0.00
	LTE 41	QPSK20M	Right Side	40185	1	50	0	22.5	22.07	1.10	-0.11	0.0005983	0.00
	LTE 41	QPSK20M	Bottom Side	40185	0	1	0	23.5	23.19	1.07	0	0.164	0.18
	LTE 41	QPSK20M	Bottom Side	40185	0	50	0	22.5	22.07	1.10	0.1	0.162	0.18
	LTE 41	QPSK20M	Top Side	40185	1	1	0	23.5	23.19	1.07	0.13	0.0050173	0.01
	LTE 41	QPSK20M	Top Side	40185	1	50	0	22.5	22.07	1.10	0.14	0.0041736	0.00

FCC SAR Test Report

A D T

Plot No.	Band	Mode	Test Position	Ch.	Tx Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
25	2.4G WLAN	802.11b	Front Face	11	0	20.0	18.49	1.42	0.13	0.136	0.19
	2.4G WLAN	802.11b	Front Face	11	1	20.0	18.43	1.44	0.01	0.006	0.01
	2.4G WLAN	802.11n HT40	Front Face	3	0+1	18.0	16.28	1.49	0.16	0.012	0.02
	2.4G WLAN	802.11b	Rear Face	11	0	20.0	18.49	1.42	0.06	0.079	0.11
	2.4G WLAN	802.11b	Rear Face	11	1	20.0	18.43	1.44	-0.11	0.0065	0.01
	2.4G WLAN	802.11n HT40	Rear Face	3	0+1	18.0	16.28	1.49	0.11	0.006	0.01
	2.4G WLAN	802.11b	Right Side	11	0	20.0	18.49	1.42	0.11	0.086	0.12
	2.4G WLAN	802.11b	Right Side	11	1	20.0	18.43	1.44	0.11	0.004	0.01
	2.4G WLAN	802.11n HT40	Right Side	3	0+1	18.0	16.28	1.49	0.14	0.006	0.01
	2.4G WLAN	802.11b	Top Side	11	0	20.0	18.49	1.42	0.17	0.019	0.03
	2.4G WLAN	802.11n HT40	Top Side	3	0+1	18.0	16.28	1.49	0.11	0.001	0.00
	2.4G WLAN	802.11b	Bottom Side	11	1	20.0	18.43	1.44	0.11	0.001	0.00
	2.4G WLAN	802.11n HT40	Bottom Side	3	0+1	18.0	16.28	1.49	-0.11	0	0.00
28	5.8G WLAN	802.11ac VH80	Front Face	155	0	17.5	15.77	1.49	0.03	0.023	0.03
	5.8G WLAN	802.11ac VH80	Front Face	155	1	17.5	15.65	1.53	0.05	0.00496	0.01
	5.8G WLAN	802.11ac VH80	Front Face	155	0+1	17.5	16.37	1.30	-0.01	0	0.00
	5.8G WLAN	802.11ac VH80	Rear Face	155	0	17.5	15.77	1.49	0.01	0	0.00
	5.8G WLAN	802.11ac VH80	Rear Face	155	1	17.5	15.65	1.53	0.05	0	0.00
	5.8G WLAN	802.11ac VH80	Rear Face	155	0+1	17.5	16.37	1.30	0.09	0	0.00
	5.8G WLAN	802.11ac VH80	Right Side	155	0	17.5	15.77	1.49	-0.02	0.0059	0.01
	5.8G WLAN	802.11ac VH80	Right Side	155	1	17.5	15.65	1.53	0	0	0.00
	5.8G WLAN	802.11ac VH80	Right Side	155	0+1	17.5	16.37	1.30	0	0	0.00
	5.8G WLAN	802.11ac VH80	Top Side	155	0	17.5	15.77	1.49	0	0	0.00
	5.8G WLAN	802.11ac VH80	Top Side	155	0+1	17.5	16.37	1.30	0.04	7.65E-05	0.00
	5.8G WLAN	802.11ac VH80	Bottom Side	155	1	17.5	15.65	1.53	0.02	0.000878	0.00
	5.8G WLAN	802.11ac VH80	Bottom Side	155	0+1	17.5	16.37	1.30	0	0	0.00

FCC SAR Test Report

4.7.5 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

Since all the measured SAR are less than 0.8 W/kg, the repeated measurement is not required.

4.7.6 Simultaneous Multi-band Transmission Evaluation

<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
1	GSM 850 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.33	0.24	-	0.57	Σ SAR < 1.6, Not required
			Right Tilted	0.18	0.11	-	0.29	Σ SAR < 1.6, Not required
			Left Cheek	0.26	0.77	-	1.03	Σ SAR < 1.6, Not required
			Left Tilted	0.18	0.40	-	0.58	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.36	0.19	0.00	0.55	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.11	0.00	0.53	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.36	0.19	-	0.55	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.11	-	0.53	Σ SAR < 1.6, Not required
			Left Side	0.27	0.00	-	0.27	Σ SAR < 1.6, Not required
			Right Side	0.30	0.12	-	0.42	Σ SAR < 1.6, Not required
			Top Side	0.00	0.03	-	0.03	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
2	GSM 850 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.33	0.43	-	0.76	Σ SAR < 1.6, Not required
			Right Tilted	0.18	0.26	-	0.44	Σ SAR < 1.6, Not required
			Left Cheek	0.26	0.79	-	1.05	Σ SAR < 1.6, Not required
			Left Tilted	0.18	0.63	-	0.81	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.36	0.06	0.00	0.42	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.00	0.00	0.42	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.36	0.03	-	0.39	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.00	-	0.42	Σ SAR < 1.6, Not required
			Left Side	0.27	0.00	-	0.27	Σ SAR < 1.6, Not required
			Right Side	0.30	0.01	-	0.31	Σ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
3	GSM 1900 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.35	0.24	-	0.59	Σ SAR < 1.6, Not required
			Right Tilted	0.23	0.11	-	0.34	Σ SAR < 1.6, Not required
			Left Cheek	0.15	0.77	-	0.92	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.40	-	0.54	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.19	0.19	0.00	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.22	0.11	0.00	0.33	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.19	0.19	-	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.22	0.11	-	0.33	Σ SAR < 1.6, Not required
			Left Side	0.19	0.00	-	0.19	Σ SAR < 1.6, Not required
			Right Side	0.02	0.12	-	0.14	Σ SAR < 1.6, Not required
			Top Side	0.08	0.03	-	0.11	Σ SAR < 1.6, Not required
			Bottom Side	0.24	0.00	-	0.24	Σ SAR < 1.6, Not required
4	GSM 1900 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.35	0.43	-	0.78	Σ SAR < 1.6, Not required
			Right Tilted	0.23	0.26	-	0.49	Σ SAR < 1.6, Not required
			Left Cheek	0.15	0.79	-	0.94	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.63	-	0.77	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.19	0.06	0.00	0.25	Σ SAR < 1.6, Not required
			Rear Face	0.22	0.00	0.00	0.22	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.19	0.03	-	0.22	Σ SAR < 1.6, Not required
			Rear Face	0.22	0.00	-	0.22	Σ SAR < 1.6, Not required
			Left Side	0.19	0.00	-	0.19	Σ SAR < 1.6, Not required
			Right Side	0.02	0.01	-	0.03	Σ SAR < 1.6, Not required
			Top Side	0.08	0.00	-	0.08	Σ SAR < 1.6, Not required
			Bottom Side	0.24	0.00	-	0.24	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
5	WCDMA II + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.87	0.24	-	1.11	Σ SAR < 1.6, Not required
			Right Tilted	0.68	0.11	-	0.79	Σ SAR < 1.6, Not required
			Left Cheek	0.49	0.77	-	1.26	Σ SAR < 1.6, Not required
			Left Tilted	0.46	0.40	-	0.86	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.38	0.19	0.00	0.57	Σ SAR < 1.6, Not required
			Rear Face	0.54	0.11	0.00	0.65	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.38	0.19	-	0.57	Σ SAR < 1.6, Not required
			Rear Face	0.54	0.11	-	0.65	Σ SAR < 1.6, Not required
			Left Side	0.41	0.00	-	0.41	Σ SAR < 1.6, Not required
			Right Side	0.02	0.12	-	0.14	Σ SAR < 1.6, Not required
			Top Side	0.20	0.03	-	0.23	Σ SAR < 1.6, Not required
			Bottom Side	0.64	0.00	-	0.64	Σ SAR < 1.6, Not required
6	WCDMA II + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.87	0.43	-	1.30	Σ SAR < 1.6, Not required
			Right Tilted	0.68	0.26	-	0.94	Σ SAR < 1.6, Not required
			Left Cheek	0.49	0.79	-	1.28	Σ SAR < 1.6, Not required
			Left Tilted	0.46	0.63	-	1.09	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.38	0.06	0.00	0.44	Σ SAR < 1.6, Not required
			Rear Face	0.54	0.00	0.00	0.54	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.38	0.03	-	0.41	Σ SAR < 1.6, Not required
			Rear Face	0.54	0.00	-	0.54	Σ SAR < 1.6, Not required
			Left Side	0.41	0.00	-	0.41	Σ SAR < 1.6, Not required
			Right Side	0.02	0.01	-	0.03	Σ SAR < 1.6, Not required
			Top Side	0.20	0.00	-	0.20	Σ SAR < 1.6, Not required
			Bottom Side	0.64	0.00	-	0.64	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
7	WCDMA V + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.38	0.24	-	0.62	Σ SAR < 1.6, Not required
			Right Tilted	0.22	0.11	-	0.33	Σ SAR < 1.6, Not required
			Left Cheek	0.27	0.77	-	1.04	Σ SAR < 1.6, Not required
			Left Tilted	0.19	0.40	-	0.59	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.35	0.19	0.00	0.54	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.11	0.00	0.53	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.35	0.19	-	0.54	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.11	-	0.53	Σ SAR < 1.6, Not required
			Left Side	0.25	0.00	-	0.25	Σ SAR < 1.6, Not required
			Right Side	0.29	0.12	-	0.41	Σ SAR < 1.6, Not required
			Top Side	0.01	0.03	-	0.04	Σ SAR < 1.6, Not required
			Bottom Side	0.06	0.00	-	0.06	Σ SAR < 1.6, Not required
8	WCDMA V + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.38	0.43	-	0.81	Σ SAR < 1.6, Not required
			Right Tilted	0.22	0.26	-	0.48	Σ SAR < 1.6, Not required
			Left Cheek	0.27	0.79	-	1.06	Σ SAR < 1.6, Not required
			Left Tilted	0.19	0.63	-	0.82	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.35	0.06	0.00	0.41	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.00	0.00	0.42	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.35	0.03	-	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.00	-	0.42	Σ SAR < 1.6, Not required
			Left Side	0.25	0.00	-	0.25	Σ SAR < 1.6, Not required
			Right Side	0.29	0.01	-	0.30	Σ SAR < 1.6, Not required
			Top Side	0.01	0.00	-	0.01	Σ SAR < 1.6, Not required
			Bottom Side	0.06	0.00	-	0.06	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
9	LTE 5 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.18	0.24	-	0.42	Σ SAR < 1.6, Not required
			Right Tilted	0.13	0.11	-	0.24	Σ SAR < 1.6, Not required
			Left Cheek	0.15	0.77	-	0.92	Σ SAR < 1.6, Not required
			Left Tilted	0.11	0.40	-	0.51	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.17	0.19	0.00	0.36	Σ SAR < 1.6, Not required
			Rear Face	0.20	0.11	0.00	0.31	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.17	0.19	-	0.36	Σ SAR < 1.6, Not required
			Rear Face	0.20	0.11	-	0.31	Σ SAR < 1.6, Not required
			Left Side	0.12	0.00	-	0.12	Σ SAR < 1.6, Not required
			Right Side	0.14	0.12	-	0.26	Σ SAR < 1.6, Not required
			Top Side	0.00	0.03	-	0.03	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
10	LTE 5 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.18	0.43	-	0.61	Σ SAR < 1.6, Not required
			Right Tilted	0.13	0.26	-	0.39	Σ SAR < 1.6, Not required
			Left Cheek	0.15	0.79	-	0.94	Σ SAR < 1.6, Not required
			Left Tilted	0.11	0.63	-	0.74	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.17	0.06	0.00	0.23	Σ SAR < 1.6, Not required
			Rear Face	0.20	0.00	0.00	0.20	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.17	0.03	-	0.20	Σ SAR < 1.6, Not required
			Rear Face	0.20	0.00	-	0.20	Σ SAR < 1.6, Not required
			Left Side	0.12	0.00	-	0.12	Σ SAR < 1.6, Not required
			Right Side	0.14	0.01	-	0.15	Σ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
11	LTE 7 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.48	0.24	-	0.72	Σ SAR < 1.6, Not required
			Right Tilted	0.29	0.11	-	0.40	Σ SAR < 1.6, Not required
			Left Cheek	0.43	0.77	-	1.20	Σ SAR < 1.6, Not required
			Left Tilted	0.10	0.40	-	0.50	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.55	0.19	0.00	0.74	Σ SAR < 1.6, Not required
			Rear Face	0.44	0.11	0.00	0.55	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.55	0.19	-	0.74	Σ SAR < 1.6, Not required
			Rear Face	0.44	0.11	-	0.55	Σ SAR < 1.6, Not required
			Left Side	0.49	0.00	-	0.49	Σ SAR < 1.6, Not required
			Right Side	0.01	0.12	-	0.13	Σ SAR < 1.6, Not required
			Top Side	0.03	0.03	-	0.06	Σ SAR < 1.6, Not required
			Bottom Side	0.28	0.00	-	0.28	Σ SAR < 1.6, Not required
12	LTE 7 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.48	0.43	-	0.91	Σ SAR < 1.6, Not required
			Right Tilted	0.29	0.26	-	0.55	Σ SAR < 1.6, Not required
			Left Cheek	0.43	0.79	-	1.22	Σ SAR < 1.6, Not required
			Left Tilted	0.10	0.63	-	0.73	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.55	0.06	0.00	0.61	Σ SAR < 1.6, Not required
			Rear Face	0.44	0.00	0.00	0.44	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.55	0.03	-	0.58	Σ SAR < 1.6, Not required
			Rear Face	0.44	0.00	-	0.44	Σ SAR < 1.6, Not required
			Left Side	0.49	0.00	-	0.49	Σ SAR < 1.6, Not required
			Right Side	0.01	0.01	-	0.02	Σ SAR < 1.6, Not required
			Top Side	0.03	0.00	-	0.03	Σ SAR < 1.6, Not required
			Bottom Side	0.28	0.00	-	0.28	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
13	LTE 13 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.07	0.24	-	0.31	Σ SAR < 1.6, Not required
			Right Tilted	0.04	0.11	-	0.15	Σ SAR < 1.6, Not required
			Left Cheek	0.05	0.77	-	0.82	Σ SAR < 1.6, Not required
			Left Tilted	0.02	0.40	-	0.42	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.36	0.19	0.00	0.55	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.11	0.00	0.53	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.36	0.19	-	0.55	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.11	-	0.53	Σ SAR < 1.6, Not required
			Left Side	0.25	0.00	-	0.25	Σ SAR < 1.6, Not required
			Right Side	0.30	0.12	-	0.42	Σ SAR < 1.6, Not required
			Top Side	0.00	0.03	-	0.03	Σ SAR < 1.6, Not required
			Bottom Side	0.08	0.00	-	0.08	Σ SAR < 1.6, Not required
14	LTE 13 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.07	0.43	-	0.50	Σ SAR < 1.6, Not required
			Right Tilted	0.04	0.26	-	0.30	Σ SAR < 1.6, Not required
			Left Cheek	0.05	0.79	-	0.84	Σ SAR < 1.6, Not required
			Left Tilted	0.02	0.63	-	0.65	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.36	0.06	0.00	0.42	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.00	0.00	0.42	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.36	0.03	-	0.39	Σ SAR < 1.6, Not required
			Rear Face	0.42	0.00	-	0.42	Σ SAR < 1.6, Not required
			Left Side	0.25	0.00	-	0.25	Σ SAR < 1.6, Not required
			Right Side	0.30	0.01	-	0.31	Σ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
			Bottom Side	0.08	0.00	-	0.08	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
15	LTE 17 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.17	0.24	-	0.41	Σ SAR < 1.6, Not required
			Right Tilted	0.12	0.11	-	0.23	Σ SAR < 1.6, Not required
			Left Cheek	0.14	0.77	-	0.91	Σ SAR < 1.6, Not required
			Left Tilted	0.10	0.40	-	0.50	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.29	0.19	0.00	0.48	Σ SAR < 1.6, Not required
			Rear Face	0.36	0.11	0.00	0.47	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.29	0.19	-	0.48	Σ SAR < 1.6, Not required
			Rear Face	0.36	0.11	-	0.47	Σ SAR < 1.6, Not required
			Left Side	0.28	0.00	-	0.28	Σ SAR < 1.6, Not required
			Right Side	0.31	0.12	-	0.43	Σ SAR < 1.6, Not required
			Top Side	0.00	0.03	-	0.03	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
16	LTE 17 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.17	0.43	-	0.60	Σ SAR < 1.6, Not required
			Right Tilted	0.12	0.26	-	0.38	Σ SAR < 1.6, Not required
			Left Cheek	0.14	0.79	-	0.93	Σ SAR < 1.6, Not required
			Left Tilted	0.10	0.63	-	0.73	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.29	0.06	0.00	0.35	Σ SAR < 1.6, Not required
			Rear Face	0.36	0.00	0.00	0.36	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.29	0.03	-	0.32	Σ SAR < 1.6, Not required
			Rear Face	0.36	0.00	-	0.36	Σ SAR < 1.6, Not required
			Left Side	0.28	0.00	-	0.28	Σ SAR < 1.6, Not required
			Right Side	0.31	0.01	-	0.32	Σ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
			Bottom Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
17	LTE 26 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.26	0.24	-	0.50	Σ SAR < 1.6, Not required
			Right Tilted	0.16	0.11	-	0.27	Σ SAR < 1.6, Not required
			Left Cheek	0.21	0.77	-	0.98	Σ SAR < 1.6, Not required
			Left Tilted	0.13	0.40	-	0.53	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.22	0.19	0.00	0.41	Σ SAR < 1.6, Not required
			Rear Face	0.27	0.11	0.00	0.38	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.22	0.19	-	0.41	Σ SAR < 1.6, Not required
			Rear Face	0.27	0.11	-	0.38	Σ SAR < 1.6, Not required
			Left Side	0.14	0.00	-	0.14	Σ SAR < 1.6, Not required
			Right Side	0.18	0.12	-	0.30	Σ SAR < 1.6, Not required
			Top Side	0.00	0.03	-	0.03	Σ SAR < 1.6, Not required
			Bottom Side	0.05	0.00	-	0.05	Σ SAR < 1.6, Not required
18	LTE 26 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.26	0.43	-	0.69	Σ SAR < 1.6, Not required
			Right Tilted	0.16	0.26	-	0.42	Σ SAR < 1.6, Not required
			Left Cheek	0.21	0.79	-	1.00	Σ SAR < 1.6, Not required
			Left Tilted	0.13	0.63	-	0.76	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.22	0.06	0.00	0.28	Σ SAR < 1.6, Not required
			Rear Face	0.27	0.00	0.00	0.27	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.22	0.03	-	0.25	Σ SAR < 1.6, Not required
			Rear Face	0.27	0.00	-	0.27	Σ SAR < 1.6, Not required
			Left Side	0.14	0.00	-	0.14	Σ SAR < 1.6, Not required
			Right Side	0.18	0.01	-	0.19	Σ SAR < 1.6, Not required
			Top Side	0.00	0.00	-	0.00	Σ SAR < 1.6, Not required
			Bottom Side	0.05	0.00	-	0.05	Σ SAR < 1.6, Not required

FCC SAR Test Report

A D T

No.	Conditions (SAR1 + SAR2 + SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
19	LTE 41 + WLAN (DTS) + BT (DSS)	Head	Right Cheek	0.34	0.24	-	0.58	Σ SAR < 1.6, Not required
			Right Tilted	0.17	0.11	-	0.28	Σ SAR < 1.6, Not required
			Left Cheek	0.28	0.77	-	1.05	Σ SAR < 1.6, Not required
			Left Tilted	0.07	0.40	-	0.47	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.32	0.19	0.00	0.51	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.11	0.00	0.36	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.32	0.19	-	0.51	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.11	-	0.36	Σ SAR < 1.6, Not required
			Left Side	0.30	0.00	-	0.30	Σ SAR < 1.6, Not required
			Right Side	0.02	0.12	-	0.14	Σ SAR < 1.6, Not required
			Top Side	0.01	0.03	-	0.04	Σ SAR < 1.6, Not required
			Bottom Side	0.18	0.00	-	0.18	Σ SAR < 1.6, Not required
20	LTE 41 + WLAN (NII) + BT (DSS)	Head	Right Cheek	0.34	0.43	-	0.77	Σ SAR < 1.6, Not required
			Right Tilted	0.17	0.26	-	0.43	Σ SAR < 1.6, Not required
			Left Cheek	0.28	0.79	-	1.07	Σ SAR < 1.6, Not required
			Left Tilted	0.07	0.63	-	0.70	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.32	0.06	0.00	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.00	0.00	0.25	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.32	0.03	-	0.35	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.00	-	0.25	Σ SAR < 1.6, Not required
			Left Side	0.30	0.00	-	0.30	Σ SAR < 1.6, Not required
			Right Side	0.02	0.01	-	0.03	Σ SAR < 1.6, Not required
			Top Side	0.01	0.00	-	0.01	Σ SAR < 1.6, Not required
			Bottom Side	0.18	0.00	-	0.18	Σ SAR < 1.6, Not required

Test Engineer : Terry Huang, and Mars Chang

5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D750V3	1013	Aug. 24, 2015	1 Year
System Validation Dipole	SPEAG	D835V2	4d121	Aug. 24, 2015	1 Year
System Validation Dipole	SPEAG	D1900V2	5d036	Jan. 22, 2016	1 Year
System Validation Dipole	SPEAG	D2450V2	737	Aug. 20, 2015	1 Year
System Validation Dipole	SPEAG	D2600V2	1020	Aug. 19, 2015	1 Year
System Validation Dipole	SPEAG	D5GHzV2	1019	Aug. 28, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3650	Jul. 23, 2015	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3864	Jul. 23, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE4	861	Apr. 28, 2015	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1277	Jul. 22, 2015	1 Year
Wireless Communication Test Set	Agilent	E5515C	MY50266628	Nov. 05, 2015	2 Years
Radio Communication Analyzer	Anritsu	MT8820C	6201010285	Aug. 23, 2015	1 Year
ENA Series Network Analyzer	Agilent	E5071C	MY46214281	Jun. 23, 2015	1 Year
EXA Spectrum Analyzer	Agilent	N9010A	MY52220314	Oct. 23, 2015	1 Year
EXG-B MW Analog Signal Generator	Agilent	N5173B	MY53270724	Jan. 20, 2016	1 Year
Power Meter	Anritsu	ML2495A	1218009	Jul. 06, 2015	1 Year
Power Sensor	Anritsu	MA2411B	1207252	Jul. 06, 2015	1 Year
Thermometer	YFE	YF-160A	130504579	Aug. 20, 2015	1 Year

6. Measurement Uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.0	Normal	1	1	1	6.0	6.0	∞
Axial Isotropy	4.7	Rectangular	√3	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.707	0.707	3.9	3.9	∞
Boundary Effect	1.0	Rectangular	√3	1	1	0.6	0.6	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
System Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	∞
RF Ambient Conditions - Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	2.0	Rectangular	√3	1	1	1.2	1.2	∞
Test Sample Related								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.2	Rectangular	√3	1	1	4.2	4.2	∞
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
Combined Standard Uncertainty						± 11.2 %	± 10.4 %	
Expanded Uncertainty (K=2)						± 22.4 %	± 20.8 %	

Uncertainty budget for frequency range 300 MHz to 3 GHz

FCC SAR Test Report

A D T

Source of Uncertainty	Tolerance ($\pm$ %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty ($\pm$ %, 1g)	Standard Uncertainty ($\pm$ %, 10g)	Vi
Measurement System								
Probe Calibration	6.55	Normal	1	1	1	6.55	6.55	∞
Axial Isotropy	4.7	Rectangular	$\sqrt{3}$	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	$\sqrt{3}$	0.707	0.707	3.9	3.9	∞
Boundary Effect	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	∞
Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
System Detection Limits	0.25	Rectangular	$\sqrt{3}$	1	1	0.14	0.14	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	$\sqrt{3}$	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	$\sqrt{3}$	1	1	1.0	1.0	∞
RF Ambient Conditions - Noise	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	Rectangular	$\sqrt{3}$	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	6.7	Rectangular	$\sqrt{3}$	1	1	3.9	3.9	∞
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	4.0	Rectangular	$\sqrt{3}$	1	1	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.6	Rectangular	$\sqrt{3}$	1	1	4.4	4.4	∞
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	$\sqrt{3}$	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
Combined Standard Uncertainty						± 12.3 %	± 11.5 %	
Expanded Uncertainty (K=2)						± 24.6 %	± 23.0 %	

Uncertainty budget for frequency range 3 GHz to 6 GHz

FCC SAR Test Report

7. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Taiwan HwaYa EMC/RF/Safety/Telecom Lab:

Add: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-318-3232

Fax: 886-3-327-0892

Taiwan LinKo EMC/RF Lab:

Add: No. 47-2, 14th Ling, Chia Pau Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C.

Tel: 886-2-2605-2180

Fax: 886-2-2605-1924

Taiwan HsinChu EMC/RF Lab:

Add: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Vil., Chiung Lin Township, Hsinchu County 307, Taiwan, R.O.C.

Tel: 886-3-593-5343

Fax: 886-3-593-5342

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The road map of all our labs can be found in our web site also.

---END---