

17.9 SAR test plots for LTE Band13

LTE Band13 QPSK Allocation1 Start49 782MHz Edge1 0mm Power Reduction

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,

E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration

Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn509; Calibrated: 2016/07/07

Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (51x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.36 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 40.64 V/m; Power Drift = -0.10 dB


Peak SAR (extrapolated) = 1.78 W/kg

SAR(1 g) = 0.952 W/kg; SAR(10 g) = 0.523 W/kg

Maximum value of SAR (measured) = 1.35 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation25 Start0 782MHz Edge1 0mm Power Reduction


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (51x111x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 1.35 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 40.66 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.77 W/kg
SAR(1 g) = 0.939 W/kg; SAR(10 g) = 0.516 W/kg
Maximum value of SAR (measured) = 1.34 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation50 Start0 782MHz Edge1 0mm Power Reduction


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (51x111x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 1.37 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 40.95 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 1.80 W/kg
SAR(1 g) = 0.955 W/kg; SAR(10 g) = 0.524 W/kg
Maximum value of SAR (measured) = 1.37 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation1 Start49 782MHz Rear 0mm Power Reduction


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (51x111x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.638 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 27.26 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.741 W/kg
SAR(1 g) = 0.496 W/kg; SAR(10 g) = 0.326 W/kg
Maximum value of SAR (measured) = 0.626 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation25 Start0 782MHz Rear 0mm Power Reduction


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (51x111x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.632 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 27.26 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.731 W/kg
SAR(1 g) = 0.490 W/kg; SAR(10 g) = 0.322 W/kg
Maximum value of SAR (measured) = 0.614 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation1 Start49 782MHz Edge1 37mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 54.672$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (51x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$
Maximum value of SAR (interpolated) = 0.153 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 13.41 V/m ; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.173 W/kg
SAR(1 g) = 0.131 W/kg ; SAR(10 g) = 0.096 W/kg
Maximum value of SAR (measured) = 0.156 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C Liquid Temp.; 23.5 degree.C .



LTE Band13 QPSK Allocation25 Start0 782MHz Edge1 37mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 54.672$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (51x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$
Maximum value of SAR (interpolated) = 0.106 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 11.17 V/m ; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.119 W/kg
SAR(1 g) = 0.090 W/kg ; SAR(10 g) = 0.066 W/kg
Maximum value of SAR (measured) = 0.107 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C Liquid Temp.; 23.5 degree.C .



LTE Band13 QPSK Allocation1 Start49 782MHz Edge2 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (51x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0186 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.887 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 0.0240 W/kg
SAR(1 g) = 0.015 W/kg; SAR(10 g) = 0.00987 W/kg
Maximum value of SAR (measured) = 0.0192 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation25 Start0 782MHz Edge2 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (51x111x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0131 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.005 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 0.0170 W/kg
SAR(1 g) = 0.010 W/kg; SAR(10 g) = 0.00671 W/kg
Maximum value of SAR (measured) = 0.0135 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation1 Start49 782MHz Edge2 tilt 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.993$ S/m; $\epsilon_r = 53.839$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3917; ConvF(9.69, 9.69, 9.69); Calibrated: 2016/05/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1369; Calibrated: 2016/05/13
Phantom: ELI v5.0 (30deg probe tilt); Type: QDOVA002AA; Serial: TP:1203
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (91x91x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.0247 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 5.343 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.0370 W/kg
SAR(1 g) = 0.021 W/kg
Maximum value of SAR (measured) = 0.0284 W/kg

Date: 2017/02/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation25 Start0 782MHz Edge2 tilt 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.993$ S/m; $\epsilon_r = 53.839$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3917; ConvF(9.69, 9.69, 9.69); Calibrated: 2016/05/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1369; Calibrated: 2016/05/13
Phantom: ELI v5.0 (30deg probe tilt); Type: QDOVA002AA; Serial: TP:1203
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (91x91x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.0180 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 4.547 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.0280 W/kg
SAR(1 g) = 0.016 W/kg
Maximum value of SAR (measured) = 0.0223 W/kg

Date: 2017/02/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation1 Start49 782MHz Edge3 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (41x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.0784 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 9.672 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.0970 W/kg
SAR(1 g) = 0.062 W/kg; SAR(10 g) = 0.041 W/kg
Maximum value of SAR (measured) = 0.0783 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation25 Start0 782MHz Edge3 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (41x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.0515 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 7.692 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 0.0620 W/kg
SAR(1 g) = 0.040 W/kg; SAR(10 g) = 0.026 W/kg
Maximum value of SAR (measured) = 0.0500 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation1 Start49 782MHz Edge4 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.336 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 20.71 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.440 W/kg
SAR(1 g) = 0.268 W/kg; SAR(10 g) = 0.167 W/kg
Maximum value of SAR (measured) = 0.355 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation25 Start0 782MHz Edge4 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)),
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.281 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 19.21 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 0.370 W/kg
SAR(1 g) = 0.227 W/kg; SAR(10 g) = 0.143 W/kg
Maximum value of SAR (measured) = 0.301 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation1 Start49 782MHz Edge4 tilt 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.993$ S/m; $\epsilon_r = 53.839$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3917; ConvF(9.69, 9.69, 9.69); Calibrated: 2016/05/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1369; Calibrated: 2016/05/13
Phantom: ELI v5.0 (30deg probe tilt); Type: QDOVA002AA; Serial: TP:1203
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.406 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 22.55 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.500 W/kg
SAR(1 g) = 0.317 W/kg; SAR(10 g) = 0.206 W/kg
Maximum value of SAR (measured) = 0.415 W/kg

Date: 2017/02/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation25 Start0 782MHz Edge4 tilt 0mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.993$ S/m; $\epsilon_r = 53.839$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3917; ConvF(9.69, 9.69, 9.69); Calibrated: 2016/05/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1369; Calibrated: 2016/05/13
Phantom: ELI v5.0 (30deg probe tilt); Type: QDOVA002AA; Serial: TP:1203
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.318 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 19.80 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.386 W/kg
SAR(1 g) = 0.248 W/kg; SAR(10 g) = 0.162 W/kg
Maximum value of SAR (measured) = 0.323 W/kg

Date: 2017/02/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation1 Start49 782MHz Rear 20mm


Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)),
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x111x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.234 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 16.67 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.262 W/kg
SAR(1 g) = 0.194 W/kg; SAR(10 g) = 0.135 W/kg
Maximum value of SAR (measured) = 0.233 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.



LTE Band13 QPSK Allocation25 Start0 782MHz Rear 20mm

Communication System: UID 0, Generic LTE (0); Communication System Band: Band 13,
E-UTRA/FDD (777.0 - 787.0 MHz); Frequency: 782 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.963$ S/m; $\epsilon_r = 54.672$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration
Probe: EX3DV4 - SN3825; ConvF(9.98, 9.98, 9.98); Calibrated: 2016/12/12;
Sensor-Surface: 2mm (Mechanical Surface Detection)
Electronics: DAE4 Sn509; Calibrated: 2016/07/07
Phantom: ELI v4.0 (20deg probe tilt); Type: QDOVA001BB; Serial: TP:1045
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Area Scan (61x111x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.238 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 16.63 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.266 W/kg
SAR(1 g) = 0.195 W/kg; SAR(10 g) = 0.136 W/kg
Maximum value of SAR (measured) = 0.235 W/kg

Date: 2017/01/17

Ambient Temp. : 24.0 degree.C. Liquid Temp.; 23.5 degree.C.

