

# Radio Exposure Evaluation Report

FCC ID : RYK-WPEA352ACNRB  
Equipment : 802.11ac/b/g/n Mini PCIe Module  
Brand Name : Sparklan  
Model Name : WPEA-352ACNRB  
WPEA-352ACNRBI  
Applicant/ : SparkLAN Communications, Inc.  
Manufacturer : 8F., No. 257, Sec. 2, Tiding Blvd., Neihu District,  
Taipei City 11493, Taiwan  
Standard : 47 CFR Part 2.1091

The product was received on Dec. 10, 2018, and testing was started from Jan. 15, 2019 and completed on Jan. 15, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of United States government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



# Table of Contents

**HISTORY OF THIS TEST REPORT .....3**

**1 GENERAL DESCRIPTION .....5**

1.1 EUT General Information .....5

1.2 Table for Existing Change .....5

1.3 Table for Multiple Listing .....5

1.4 Testing Location .....5

**2 MAXIMUM PERMISSIBLE EXPOSURE .....6**

2.1 Limit of Maximum Permissible Exposure .....6

2.2 MPE Calculation Method .....6

2.3 Calculated Result and Limit .....7

**Photographs of EUT V01**

History of this test report

Report No.	Version	Description	Issued Date
FA8D0606-01	01	Initial issue of report	Jun. 30, 2020



### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
None.

Reviewed by: Jackson Tsai

Report Producer: Michelle Tsai

# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)

## 1.2 Table for Existing Change

This product is an extension of original one reported under Sporton project number: FA8D0606

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
PIFA Antenna (Ethertronics/1000423) is added.	Photographs of EUT

## 1.3 Table for Multiple Listing

Model Name	Description
WPEA-352ACNRB	Differences between all models are for different marketing requirement.
WPEA-352ACNRBI	

## 1.4 Testing Location

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

#### WLAN 2.4G

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;G1D	5.00	25.61	30.61	2.00	32.61	1.82390	20	0.36285	1.00000
2.4G;D1D	5.00	25.93	30.93	2.00	32.93	1.96336	20	0.39060	1.00000

#### WLAN 5G

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
5.2G;D1D	5.53	15.43	20.96	2.00	22.96	0.19770	20	0.03933	1.00000
5.3G;D1D	5.53	22.46	27.99	2.00	29.99	0.99770	20	0.19849	1.00000
5.6G;D1D	5.80	22.18	27.98	2.00	29.98	0.99541	20	0.19803	1.00000
5.8G;D1D	5.80	27.34	33.14	2.00	35.14	3.26588	20	0.64973	1.00000

—————THE END—————