

Environmental evaluation and exposure limit according to FCC CFR 47part 1, §1.1307, §1.1310

The booster may be installed indoors or outdoors as stated in the User's manual page V, the calculation was done to confirm a safe distance.

Limit for power density for general population/uncontrolled exposure is $f/1500 \text{ mW/cm}^2$ for 300 – 1500 MHz frequency range:

$$P = 806/1500 = 0.53 \text{ mW/cm}^2$$

The power density $P \text{ (mW/cm}^2\text{)} = P_T / 4\pi r^2$, where

P_T is the transmitted power, which is equal to the peak transmitter output power plus maximum antenna gain.

Indoor antenna installation

The maximum equivalent isotropically radiated power EIRP is

$$P_T = 36.98 \text{ dBm} + 0.2 \text{ dBi} = 37.18 \text{ dBm} = 5224 \text{ mW}, \text{ where}$$

36.98 dBm is the EUT maximum output power for CMRS application;
0.2 dBi – antenna assembly gain.

The minimum safe distance "r", where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{5224 / (0.53 \times 12.56)} = 28 \text{ cm}.$$

Outdoor antenna installation

The maximum equivalent isotropically radiated power EIRP is

$$P_T = 36.98 \text{ dBm} + 7 \text{ dBi} = 43.69 \text{ dBm} = 25003 \text{ mW}, \text{ where}$$

36.98 dBm is the EUT maximum output power for CMRS application;
7 dBi – antenna assembly gain (please refer to page 7 of User_manual_28127).

The minimum safe distance "r", where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{25003 / (0.53 \times 12.56)} = 61.3 \text{ cm}.$$

A warning about a safe distance is contained in the user manual.