

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806


Page: 1 of 56

SAR TEST REPORT

Application No.: SZCR2404001138AT
Applicant: SZ DJI Osmo Technology Co., Ltd.
Address of Applicant: 4F, Jingkou Community Comprehensive Service Building, No. 83 Bishui Road North, Guangming Street, Guangming District, Shenzhen, China
Manufacturer: SZ DJI Osmo Technology Co., Ltd.
Address of Manufacturer: 4F, Jingkou Community Comprehensive Service Building, No. 83 Bishui Road North, Guangming Street, Guangming District, Shenzhen, China
Factory: SZ DJI Ronin Technology Co., Ltd.
Address of Factory: Floor 4-5, Block 13, Area 7, Baiwangxin Industrial Park, Songbai Rd, Nanshan District, Shenzhen City, Guangdong Province, P. R. China
Product Name: Osmo Action 5 Pro
Model No.(EUT): AC004
Trade mark: DJI
FCC ID: 2ANDR-AC0042024
Standard(s) : FCC 47CFR §2.1093
Date of Receipt: 2024-04-26
Date of Test: 2024-04-27 to 2024-05-09
Date of Issue: 2024-05-15

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Inspection Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区W-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 2 of 56

Revision Record			
Version	Description	Date	Remark
01	Original	2024-05-15	/

Authorized for issue by:				
		<i>Roman Pan</i>		
		_____ Roman Pan/ Project Engineer		
		<i>Eric Fu</i>		
		_____ Eric Fu / Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 3 of 56

TEST SUMMARY

Test Summary		
Frequency Band	Max Reported SAR1g(W/kg)	Max Reported SAR10g(W/kg)
	Head & Body	Extremity
WI-FI (2.4GHz)	0.842	2.281
WI-FI (5GHz)	1.425	2.489
BT	0.401	0.342
Maximum Simultaneous SAR	1.575	2.831
SAR Limited(W/kg)	1.6	4.0



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

CONTENTS

1	GENERAL INFORMATION	6
1.1	GENERAL DESCRIPTION OF EUT	6
1.1.1	DUT Antenna Locations	7
1.2	TEST SPECIFICATION	8
1.3	RF EXPOSURE LIMITS	9
1.4	TEST LOCATION	10
1.5	TEST FACILITY	10
2	LABORATORY ENVIRONMENT	11
3	SAR MEASUREMENTS SYSTEM CONFIGURATION	12
3.1	THE SAR MEASUREMENT SYSTEM	12
3.2	ISOTROPIC E-FIELD PROBE EX3DV4	14
3.3	DATA ACQUISITION ELECTRONICS (DAE)	15
3.4	SAM TWIN PHANTOM	15
3.5	ELI PHANTOM	16
3.6	DEVICE HOLDER FOR TRANSMITTERS	17
3.7	MEASUREMENT PROCEDURE	18
	Scanning procedure	18
3.7.1	Data Storage	20
3.7.2	Data Evaluation by SEMCAD	20
4	SAR MEASUREMENT VARIABILITY AND UNCERTAINTY	22
4.1	SAR MEASUREMENT VARIABILITY	22
4.2	SAR MEASUREMENT UNCERTAINTY	23
5	DESCRIPTION OF TEST POSITION	24
5.1	THE TEST POSITION	24
6	SAR SYSTEM VERIFICATION PROCEDURE	25
6.1	TISSUE SIMULATE LIQUID	25
6.1.1	Recipes for Tissue Simulate Liquid	25
6.1.2	Test Liquids Confirmation	26
6.1.3	Measurement for Tissue Simulate Liquid	27
6.2	SAR SYSTEM CHECK	28
6.2.1	Justification for Extended SAR Dipole Calibrations	29
6.2.2	Summary System Check Result(s)	30
6.2.3	Detailed System Check Results	30
7	TEST CONFIGURATION	31
7.1	OPERATION CONFIGURATIONS	31
7.1.1	WiFi Test Configuration	31
7.1.2	Bluetooth Test Configuration	37
8.1	MEASUREMENT OF RF CONDUCTED POWER	38
8.1.1	CONDUCTED POWER OF WIFI	38



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 5 of 56

8.1.2	CONDUCTED POWER OF BT	45
8.2	MULTIPLE TRANSMITTER EVALUATION.....	46
8.3	MEASUREMENT OF SAR DATA.....	47
8.3.1	SAR Result Of WIFI 2.4GHz	48
8.3.2	SAR Result Of WIFI 5GHz	50
8.3.3	SAR Result Of Bluetooth	54
9	EQUIPMENT LIST	55
10	CALIBRATION CERTIFICATE.....	56
11	PHOTOGRAPHS	56



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

1 General Information

1.1 General Description of EUT

Product Phase:	Production unit		
Device Type:	Portable device		
Exposure Category:	Uncontrolled environment / general population		
SN:	82JDM370000027		
Hardware Version:	V01.00.00.00		
Software Version:	V01.00.00.00		
Antenna Gain:	2.4G Wi-Fi: ANT0: -0.7dBi, ANT1: -0.2dBi; 5G Wi-Fi: ANT0: 1dBi, ANT1: 0dBi; 5.8G Wi-Fi: ANT0: -3dBi, ANT1: 0.9dBi BT: -0.7dBi; BLE: -0.7dBi;		
Antenna Type:	Integral Antenna		
Device Operating Configurations:			
Modulation Mode:	WIFI: DSSS, OFDM; BT: GFSK, $\pi/4$ DQPSK,8DPSK		
Frequency Bands:	Band	Tx (MHz)	Rx (MHz)
	WIFI(2.4GHz)	2412~2462	2412~2462
	WIFI(U-NII-1)	5150~5250	5150~5250
	WIFI(U-NII-3)	5725~5850	5725~5850
	BT	2402~2480	2402~2480
Battery 1# Information:	Model:	BCX202-1770-3.85	
	Normal Voltage :	3.85V	
	Rated capacity :	1770mAh 6.81Wh	
	Battery Type :	Lithium Ion Polymer Rechargeable Battery	
	Manufacturer	ICON ENERGY SYSTEM (SHENZHEN) CO., LTD.	
Battery 2# Information:	Model:	BCX204-1950-3.87	
	Normal Voltage :	3.87V	
	Rated capacity :	1950mAh 7.55Wh	
	Battery Type :	Lithium Ion Rechargeable Battery	
	Manufacturer	Guangdong Highpower New Energy Technology Co.,Ltd.	



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 7 of 56

1.1.1 DUT Antenna Locations

Please see the Appendix D



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 8 of 56

1.2 Test Specification

Identity	Document Title
FCC 47CFR §2.1093	Radio frequency Radiation Exposure Evaluation: Portable Devices
IEEE Std C95.1 – 1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
KDB 865664 D01 v01r04	SAR Measurement Requirements for 100 MHz to 6 GHz
KDB 865664 D02 v01r02	RF Exposure Compliance Reporting and Documentation Considerations
KDB 248227 D01v02r02	SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

1.3 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain*Trunk)	1.60 W/kg	8.00 W/kg
Spatial Average SAR** (Whole Body)	0.08 W/kg	0.40 W/kg
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 W/kg	20.00 W/kg

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.)

1.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

1.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

2 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards.	
Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

3 SAR Measurements System Configuration

3.1 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|^2) / \rho$ where σ and ρ are the conductivity and mass density of the tissue-Simulate.


The DASY system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software. An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.



F-1. SAR Measurement System Configuration


- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows system.
- DASY software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validate the proper functioning of the system.

3.2 Isotropic E-field Probe EX3DV4

	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μW/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μW/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY52 SAR and higher, EASY4/MRI



3.3 Data Acquisition Electronics (DAE)

Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV,400mV)	
Input Offset Voltage	< 5μV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	

3.4 SAM Twin Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	
Wooden Support	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE Std. 1528-2013 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.

3.5 ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)
Shell Thickness	2.0 ± 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	approx. 30 liters
Wooden Support	SPEAG standard phantom table



Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure.

3.6 Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

3.7 Measurement procedure

Scanning procedure

Step 1: Power reference measurement

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm*15mm or 12mm*12mm or 10mm*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Zoom scan

Around this point, a volume of 30mm*30mm*30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5x5x7 points ($\leq 2\text{GHz}$) and 7x7x7 points ($\geq 2\text{GHz}$). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std. 1528-2013.

		$\leq 3 \text{ GHz}$	$> 3 \text{ GHz}$
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		$5 \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location		$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$		$\leq 2 \text{ GHz}: \leq 15 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 12 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 12 \text{ mm}$ $4 - 6 \text{ GHz}: \leq 10 \text{ mm}$
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$		$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$	$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 4 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 3 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	graded grid $\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 3 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z	$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz}: \geq 28 \text{ mm}$ $4 - 5 \text{ GHz}: \geq 25 \text{ mm}$ $5 - 6 \text{ GHz}: \geq 22 \text{ mm}$
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB 447498 is $\leq 1.4 \text{ W/kg}$, $\leq 8 \text{ mm}$, $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.			

Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT's output power and should vary max. $\pm 5 \%$



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3.7.1 Data Storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DAE3". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

3.7.2 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi	
- Diode compression point	Dcpi	
Device parameters:	- Frequency	f
- Crest factor	cf	
Media parameters:	- Conductivity	ε
- Density	ρ	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcpi$$

With V_i = compensated signal of channel i (i = x, y, z)

U_i = input signal of channel i (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcpi = diode compression point (DASY parameter)



From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = (V_i / \text{Norm}_i \cdot \text{ConvF})^{1/2}$$

H-field probes:

$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$$

With V_i = compensated signal of channel i (i = x, y, z)

Norm_i = sensor sensitivity of channel i (i = x, y, z)

[mV/(V/m)] for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{\text{tot}}^2 \cdot \sigma) / (\epsilon \cdot 1000)$$

With SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ϵ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{\text{pwe}} = E_{\text{tot}}^2 / 3770 \quad \text{or} \quad P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

4 SAR measurement variability and uncertainty

4.1 SAR measurement variability

Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 23 of 56

4.2 SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

Measurement uncertainty evaluation									
A	b1	c	d	e=f(d,K)	f	g	i=C*g/e	i=C*g/e	k
Uncertainty Component	Section in P1528	Tol (%)	Prob. Dist	Div.	C _i (1g)	C _i (10g)	1-g ui(%)	10-g ui(%)	V _i (Veff)
Measurement System									
Probe Calibration (k=1)	E.2.1	6.3	N	1	1	1	6.30	6.30	∞
Axial Isotropy	E.2.2	0.5	R	√3	0.7	0.7	0.20	0.20	∞
Hemispherical Isotropy	E.2.2	2.6	R	√3	0.7	0.7	1.06	1.06	∞
Boundary Effect	E.2.3	1.0	R	√3	1	1	0.58	0.58	∞
Linearity	E.2.4	0.6	R	√3	1	1	0.35	0.35	∞
System Detection LimitS	E.2.4	0.25	R	√3	1	1	0.14	0.14	∞
Modulation Response	E.2.5	2.4	R	√3	1	1	1.39	1.39	∞
Readout Electronics	E.2.6	0.3	N	1	1	1	0.30	0.30	∞
Response Time	E.2.7	0.0	R	√3	1	1	0.00	0.00	∞
Integration Time	E.2.8	2.6	R	√3	1	1	1.50	1.50	∞
RF Ambient Condition-Noise	E.6.1	3.0	R	√3	1	1	1.73	1.73	∞
RF Ambient Condition-Reflections	E.6.1	3.0	R	√3	1	1	1.73	1.73	∞
Probe Positioning-Mechanical Tolerance	E.6.2	1.5	R	√3	1	1	0.87	0.87	∞
Probe Positioning-with Respect to Phantom	E.6.3	2.9	R	√3	1	1	1.67	1.67	∞
Max. SAR Evaluation	E.5	1.0	R	√3	1	1	0.58	0.58	∞
Test sample Related									
Test sample Positioning	E.4.2	3.7	N	1	1	1	3.70	3.70	9
Device Holder Uncertainty	E.4.1	3.6	N	1	1	1	3.60	3.60	∞
Output Power Variation-SAR Drift Measurement	E.2.9	5	R	√3	1	1	2.89	2.89	∞
Output Power Variation-SAR Drift Measurement	E.6.5	0	R	√3	1	1	0.00	0.00	∞
Phantom and Tissue Parameters									
Phantom Uncertainty(Shape and Thickness Tolerances)	E.3.1	4	R	√3	1	1	2.31	2.31	∞
SAR Correction	E.3.2	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid Conductivity (Measurement Uncertainty)	E.3.3	3.75	N	1	0.78	0.71	2.93	2.663	5
Liquid Permittivity (Measurement Uncertainty)	E.3.3	1.62	N	1	0.23	0.26	0.37	0.421	5
Liquid Conductivity (Temperature Uncertainty)	E.3.4	4.2	R	√3	0.78	0.71	1.89	1.72	∞
Liquid Permittivity ((Temperature Uncertainty)	E.3.4	3.7	R	√3	0.23	0.26	0.49	0.56	∞
Combined Standard Uncertainty				RSS			10.58	10.43	430
Expanded Uncertainty (95% Confidence Interval)				k=2			21.16%	20.87%	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

5 Description of Test Position

5.1 The Test Position

SAR can test the sides near the antenna, the surface of the device should be tested for SAR compliance with device touching the phantom. The SAR Exclusion Threshold in KDB 447498 D04 for FCC can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent device surface is used to determine if SAR testing is required for the adjacent surfaces, with the adjacent surface positioned against the phantom and the surface containing the antenna positioned perpendicular to the phantom.

Because this product is a hand-held Sports Camera, it supports the body to wear and use, and the display screen will face the face during use. So Extremity SAR is evaluated with 0mm and Head & Body SAR is evaluated with 5mm.

6 SAR System Verification Procedure

6.1 Tissue Simulate Liquid

6.1.1 Recipes for Tissue Simulate Liquid

The bellowing tables give the recipes for tissue simulating liquids to be used in different frequency bands:

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

HSL5GHz is composed of the following ingredients:

Water: 50-65%

Mineral oil: 10-30%

Emulsifiers: 8-25%

Sodium salt: 0-1.5%

MSL5GHz is composed of the following ingredients:

Water: 64-78%

Mineral oil: 11-18%

Emulsifiers: 9-15%

Sodium salt: 2-3%

6.1.2 Test Liquids Confirmation

Simulated tissue liquid parameter confirmation

The dielectric parameters were checked prior to assessment using the SPEAG DAK3.5 dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

IEEE SCC-34/SC-2 P1528 recommended tissue dielectric parameters

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)


6.1.3 Measurement for Tissue Simulate Liquid

The dielectric properties for this Tissue Simulate Liquids were measured by using the SPEAG DAK3.5 dielectric probe kit in conjunction with Agilent Network Analyzer (300 KHz-8500 MHz). The Conductivity (σ) and Permittivity (ρ) are listed in bellow table. For the SAR measurement given in this report. The temperature variation of the Tissue Simulate Liquids was $22\pm 2^{\circ}\text{C}$.

Measurement for Tissue Simulate Liquid									
Tissue Type	Measured Frequency (MHz)	Measured Tissue		Target Tissue ($\pm 5\%$)		Deviation (Within $\pm 5\%$)		Liquid Temp. ($^{\circ}\text{C}$)	Test Date
		ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$		
2450 Head	2450	38.100	1.870	39.20	1.80	-2.81%	3.89%	22.0	2024/5/7
5250 Head	5250	37.000	4.880	35.90	4.66	3.06%	4.72%	21.8	2024/5/8
5750 Head	5750	35.600	5.460	35.40	5.22	0.56%	4.60%	21.8	2024/5/9

6.2 SAR System Check

The microwave circuit arrangement for system check is sketched in bellow figure. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within $\pm 10\%$ from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the following table. During the tests, the ambient temperature of the laboratory was in the range $22\pm 2^{\circ}\text{C}$, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-3. the microwave circuit arrangement used for SAR system verification

6.2.1 Justification for Extended SAR Dipole Calibrations

1) Referring to KDB865664 D01 requirements for dipole calibration, instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 10% of calibrated measurement;
- d) Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

6.2.2 Summary System Check Result(s)

SAR System Validation Result(s)											
Validation Kit		Measured SAR 250mW	Measured SAR 250mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W)	Target SAR (normalized to 1W)	Deviation (Within ±10%)		Liquid Temp. (°C)	Test Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1- g(W/kg)	10- g(W/kg)		
D2450V2	Head	13.16	6.12	52.64	24.48	52.20	24.30	0.84%	0.74%	22.0	2024/5/7
Validation Kit		Measured SAR 100mW	Measured SAR 100mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W)	Target SAR (normalized to 1W)	Deviation (Within ±10%)		Liquid Temp. (°C)	Test Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)	1- g(W/kg)	10- g(W/kg)		
D5GHzV2	Head(5.25GHz)	7.86	2.24	78.60	22.40	77.30	22.10	1.68%	1.36%	21.8	2024/5/8
	Head(5.75GHz)	7.68	2.11	76.80	21.10	77.10	21.30	-0.39%	-0.94%	21.8	2024/5/9

6.2.3 Detailed System Check Results

Please see the Appendix A

7 Test Configuration

7.1 Operation Configurations


7.1.1 WiFi Test Configuration

For the 802.11b/g/n SAR tests, a communication link is set up with the test mode software for Wi-Fi mode test. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 1, 6 and 11 respectively in the case of 2450 MHz during the test at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Each channel should be tested at the lowest rate. 802.11b/g/n operating modes are tested independently according to the service requirements in each frequency band. 802.11b/g/n modes are tested on channel 1, 6, 11; However if output power reduction is necessary for channels 1 and/or 11 to meet restricted band requirements the highest output channel closest to each of these channels must be tested instead.


SAR is not required for 802.11g/n channels when the maximum average output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels.

7.1.1.1 Duty cycle

WIFI 2.4GHz duty cycle: 98.93%



WLAN 5G duty cycle: 99.29%



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.1.1.2 Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) .When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) .When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) .For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

7.1.1.3 Initial Test Configuration Procedures

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required. SAR test reduction for subsequent highest output test channels is determined according to *reported* SAR of the initial test configuration.

For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration.

When the *reported* SAR of the initial test configuration is > 0.8 W/kg, SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until *reported* SAR is ≤ 1.2 W/kg or all required channels are tested.

7.1.1.4 Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- 2) . When the highest *reported* SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.
- 3) . The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
 - a) SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
 - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the *reported* SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is > 1.2 W/kg or until all required channels are tested. i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
- 4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
 - a) replace "subsequent test configuration" with "next subsequent test configuration" (i.e., subsequent next highest specified maximum output power configuration)
 - b) replace "initial test configuration" with "all tested higher output power configurations"

7.1.1.5 2.4 GHz Wi-Fi SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

• 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) . When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

- 2) . When the reported SAR is $> 0.8 \text{ W/kg}$, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is $> 1.2 \text{ W/kg}$, SAR is required for the third channel; i.e., all channels require testing.
 - **2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements**

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2 \text{ W/kg}$.

7.1.1.6 5 GHz Wi-Fi SAR Procedures

• U-NII-1 and U-NII-2A Bands

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following:

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is $\leq 1.2 \text{ W/kg}$, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is $\leq 1.2 \text{ W/kg}$, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.
- 3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is $> 1.2 \text{ W/kg}$, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

• U-NII-2C and U-NII-3 Bands

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. when Terminal Doppler Weather Radar (TDWR) restriction applies, all channels that operate at 5.60 – 5.65 GHz must be included to apply the SAR test reduction and measurement procedures.

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap channels is limited to the lower of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support



SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

• OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements

The initial test configuration for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

- 1) The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.
- 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n. After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.
 - a) The channel closest to mid-band frequency is selected for SAR measurement.
 - b) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

• SAR Test Requirements for OFDM configurations


When SAR measurement is required for 802.11 a/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

7.1.2 Bluetooth Test Configuration

For the Bluetooth SAR tests, a communication link is set up with the test mode software for BT mode test. Bluetooth USES frequency hopping technology to divide the transmitted data into packets and transmit the packets respectively through 79 designated Bluetooth channels, 1MHz Bandwidth, frequency hops at 1600 hops/second per the Bluetooth standard. The Radio Frequency Channel Number (RFCN) is allocated to 0, 39 and 78 respectively in the case of 2402~2480 MHz during the test at each test frequency channel, the EUT is operated at the RF continuous emission mode.

7.1.2.1 Duty cycle

Bluetooth duty cycle: 77.21%



8 Test Result

8.1 Measurement of RF Conducted Power

8.1.1 Conducted Power Of WIFI

WIFI 2.4G Ant0					
Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11b	1	2412	1	19.82	21.00
	6	2437		20.09	21.00
	11	2462		20.30	21.00
802.11g	1	2412	6	15.82	17.50
	6	2437		16.47	17.50
	11	2462		17.06	17.50
802.11n HT20	1	2412	6.5	15.01	16.50
	6	2437		15.55	16.50
	11	2462		16.03	16.50
802.11n HT40	3	2422	13.5	14.34	15.00
	6	2437		13.96	15.00
	9	2452		14.33	15.00
802.11ax HT20	1	2412	MCS0	16.48	18.00
	6	2437		16.87	18.00
	11	2462		17.56	18.00
802.11ax HT40	3	2422	MCS0	14.08	15.50
	6	2437		15.00	15.50
	9	2452		14.56	15.50

WIFI 2.4G Ant1					
Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11b	1	2412	1	19.14	21.00
	6	2437		19.62	21.00
	11	2462		19.97	21.00
802.11g	1	2412	6	16.04	17.50
	6	2437		16.56	17.50
	11	2462		16.80	17.50
802.11n HT20	1	2412	6.5	15.28	16.50
	6	2437		15.46	16.50
	11	2462		16.03	16.50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 39 of 56

802.11n HT40	3	2422	13.5	14.37	15.00
	6	2437		14.19	15.00
	9	2452		14.44	15.00
802.11ax HT20	1	2412	MCS0	16.35	18.00
	6	2437		17.01	18.00
	11	2462		17.38	18.00
802.11ax HT40	3	2422	MCS0	14.30	15.50
	6	2437		15.14	15.50
	9	2452		14.24	15.50

WIFI 2.4G MIMO							
Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11b	1	2412	1	\	\	\	\
	6	2437		\	\	\	\
	11	2462		\	\	\	\
802.11g	1	2412	6	\	\	\	\
	6	2437		\	\	\	\
	11	2462		\	\	\	\
802.11n HT20	1	2412	6.5	15.01	15.28	18.16	19.50
	6	2437		15.55	15.46	18.52	19.50
	11	2462		16.03	16.03	19.04	19.50
802.11n HT40	3	2422	13.5	14.34	14.37	17.37	18.00
	6	2437		13.96	14.19	17.09	18.00
	9	2452		14.33	14.44	17.40	18.00
802.11ax HT20	1	2412	MCS0	16.48	16.35	19.43	21.00
	6	2437		16.87	17.01	19.95	21.00
	11	2462		17.56	17.38	20.48	21.00
802.11ax HT40	3	2422	MCS0	14.08	14.30	17.20	18.50
	6	2437		15.00	15.14	18.08	18.50
	9	2452		14.56	14.24	17.41	18.50



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 40 of 56

WIFI 5G Ant0						
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11a	U-NII-1	36	5180	6	15.33	17.00
		40	5200		15.45	17.00
		48	5240		16.15	17.00
	U-NII-3	149	5745		21.75	22.00
		157	5785		21.60	22.00
		165	5825		21.77	22.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11n-HT20	U-NII-1	36	5180	MCS0	12.54	14.00
		40	5200		12.88	14.00
		48	5240		13.54	14.00
	U-NII-3	149	5745		16.63	17.00
		153	5765		16.70	17.00
		165	5825		16.76	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11n-HT40	U-NII-1	38	5190	MCS0	12.53	14.00
		46	5230		12.96	14.00
	U-NII-3	151	5755		16.63	17.00
		159	5795		16.76	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ac 20M	U-NII-1	36	5180	MCS0	12.67	14.00
		40	5200		13.02	14.00
		48	5240		13.66	14.00
	U-NII-3	149	5745		16.86	17.00
		157	5785		16.51	17.00
		165	5825		16.78	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ac 40M	U-NII-1	38	5190	MCS0	12.48	14.00
		46	5230		12.97	14.00
	U-NII-3	151	5755		16.75	17.00
		159	5795		16.73	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
	U-NII-1	42	5210	MCS0	12.85	14.00



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Not a CMA Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 41 of 56

802.11ac 80M	U-NII-3	155	5775		17.74	18.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ax 20M	U-NII-1	36	5180	MCS0	12.85	14.00
		40	5200		13.18	14.00
		48	5240		13.63	14.00
	U-NII-3	149	5745		16.73	17.00
		157	5785		16.51	17.00
		165	5825		16.69	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ax 40M	U-NII-1	38	5190	MCS0	12.77	14.00
		46	5230		13.13	14.00
	U-NII-3	151	5755		16.80	17.00
		159	5795		16.96	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ax 80M	U-NII-1	42	5210	MCS0	13.09	14.00
	U-NII-3	155	5775		16.88	17.00

WIFI 5G Ant1						
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11a	U-NII-1	36	5180	6	15.43	17.00
		40	5200		15.65	17.00
		48	5240		16.14	17.00
	U-NII-3	149	5745		18.62	20.00
		157	5785		18.56	20.00
		165	5825		18.79	20.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11n- HT20	U-NII-1	36	5180	MCS0	12.46	14.00
		40	5200		12.83	14.00
		48	5240		13.18	14.00
	U-NII-3	149	5745		15.44	17.00
		153	5765		15.53	17.00
		165	5825		16.04	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 42 of 56

802.11n-HT40	U-NII-1	38	5190	MCS0	12.28	14.00
		46	5230		12.71	14.00
	U-NII-3	151	5755		16.01	17.00
		159	5795		16.06	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ac 20M	U-NII-1	36	5180	MCS0	12.76	14.00
		40	5200		12.84	14.00
		48	5240		13.21	14.00
	U-NII-3	149	5745		15.65	17.00
		157	5785		15.56	17.00
		165	5825		16.17	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ac 40M	U-NII-1	38	5190	MCS0	12.38	14.00
		46	5230		12.65	14.00
	U-NII-3	151	5755		15.82	17.00
		159	5795		16.00	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ac 80M	U-NII-1	42	5210	MCS0	12.68	14.00
	U-NII-3	155	5775		17.18	18.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ax 20M	U-NII-1	36	5180	MCS0	12.96	14.00
		40	5200		12.92	14.00
		48	5240		13.50	14.00
	U-NII-3	149	5745		15.76	17.00
		157	5785		15.65	17.00
		165	5825		16.17	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ax 40M	U-NII-1	38	5190	MCS0	12.59	14.00
		46	5230		12.99	14.00
	U-NII-3	151	5755		16.09	17.00
		159	5795		16.25	17.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up
802.11ax 80M	U-NII-1	42	5210	MCS0	13.02	14.00
	U-NII-3	155	5775		16.32	17.00



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection and Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 43 of 56

WIFI 5G MIMO								
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11a	U-NII-1	36	5180	6	\	\	\	\
		40	5200		\	\	\	\
		48	5240		\	\	\	\
	U-NII-3	149	5745		\	\	\	\
		157	5785		\	\	\	\
		165	5825		\	\	\	\
					\	\	\	\
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11n-HT20	U-NII-1	36	5180	MCS0	12.54	12.46	15.51	17.00
		40	5200		12.88	12.83	15.87	17.00
		48	5240		13.54	13.18	16.37	17.00
	U-NII-3	149	5745		16.63	15.44	19.09	20.00
		153	5765		16.70	15.53	19.16	20.00
		165	5825		16.76	16.04	19.43	20.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11n-HT40	U-NII-1	38	5190	MCS0	12.53	12.28	15.42	17.00
		46	5230		12.96	12.71	15.85	17.00
	U-NII-3	151	5755		16.63	16.01	19.34	20.00
		159	5795		16.76	16.06	19.43	20.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11ac 20M	U-NII-1	36	5180	MCS0	12.67	12.76	15.73	17.00
		40	5200		13.02	12.84	15.94	17.00
		48	5240		13.66	13.21	16.45	17.00
	U-NII-3	149	5745		16.86	15.65	19.31	20.00
		157	5785		16.51	15.56	19.07	20.00
		165	5825		16.78	16.17	19.50	20.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11ac 40M	U-NII-1	38	5190	MCS0	12.48	12.38	15.44	17.00
		46	5230		12.97	12.65	15.82	17.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 44 of 56

	U-NII-3	151	5755		16.75	15.82	19.32	20.00
		159	5795		16.73	16.00	19.39	20.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11ac 80M	U-NII-1	42	5210	MCS0	12.85	12.68	15.78	17.00
	U-NII-3	155	5775		17.74	17.18	20.48	21.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11ax-20	U-NII-1	36	5180	MCS0	12.85	12.96	15.92	17.00
		40	5200		13.18	12.92	16.06	17.00
		48	5240		13.63	13.50	16.58	17.00
	U-NII-3	149	5745		16.73	15.76	19.28	20.00
		157	5785		16.51	15.65	19.11	20.00
		165	5825		16.69	16.17	19.45	20.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11ax-40	U-NII-1	38	5190	MCS0	12.77	12.59	15.69	17.00
		46	5230		13.13	12.99	16.07	17.00
	U-NII-3	151	5755		16.80	16.09	19.47	20.00
		159	5795		16.96	16.25	19.63	20.00
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	ANT0 Average Power (dBm)	ANT1 Average Power (dBm)	MIMO Average Power (dBm)	Tune up
802.11ax 80M	U-NII-1	42	5210	MCS0	13.09	13.02	16.07	17.00
	U-NII-3	155	5775		16.88	16.32	19.62	20.00



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

8.1.2 Conducted Power Of BT

Band	Channel	0	39	78	Tune up
BT	GFSK	10.55	10.99	11.46	12
	$\pi/4$ DQPSK	7.97	8.27	8.14	9
	8DPSK	8.23	8.59	8.60	9

Band	Channel	0	19	39	Tune up
BLE 1M	GFSK	9.41	8.62	9.22	10
BLE 2M	GFSK	9.53	8.69	9.28	10



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

8.2 Multiple Transmitter Evaluation

8.2.1 Simultaneous SAR test evaluation

NO.	Simultaneous Transmission Configuration	Head & Body	Extremity
1	BT + WIFI 2.4GHz	Yes	Yes
2	BT + WIFI 5G	Yes	Yes

8.2.2 Simultaneous Transmission SAR Summation Scenario for Head & Body

10mm

Test position									Summed SAR	
		WiFi 2.4G ANT0	WiFi 2.4G ANT1	WiFi 2.4G MIMO	WiFi 5G ANT0	WiFi 5G ANT1	WiFi 5G MIMO	BT Ant0		
		1	2	3	4	5	6	7	2+7	5+7
WLAN	Front side	0.188	0.086	0.055	0.194	0.206	0.167	0.056	0.142	0.262
	Back side	0.209	0.268	0.065	0.313	0.526	0.565	0.066	0.334	0.592
	Left side	0.442	0.054	0.128	0.390	0.031	0.546	0.137	0.191	0.168
	Right side	0.070	0.318	0.051	0.063	0.321	0.373	0.009	0.327	0.330
	Top side	0.842	0.415	0.271	1.110	1.174	1.425	0.401	0.816	1.575
	Bottom side	0.106	0.044	0.050	0.053	0.107	0.056	0.009	0.053	0.116

8.2.3 Simultaneous Transmission SAR Summation Scenario for Extremity

0mm

Test position									Summed SAR	
		WiFi 2.4G ANT0	WiFi 2.4G ANT1	WiFi 2.4G MIMO	WiFi 5G ANT0	WiFi 5G ANT1	WiFi 5G MIMO	BT Ant0		
		1	2	3	4	5	6	7	2+7	5+7
WLAN	Front side	0.418	0.251	0.116	0.152	0.181	0.157	0.053	0.304	0.234
	Back side	0.226	0.449	0.069	0.177	0.292	0.405	0.029	0.478	0.321
	Left side	1.223	0.110	0.373	0.743	0.035	0.987	0.191	0.301	0.226
	Right side	0.053	0.428	0.050	0.049	0.432	0.570	0.006	0.434	0.438
	Top side	2.281	1.110	0.749	1.662	2.489	2.032	0.342	1.452	2.831
	Bottom side	0.091	0.140	0.045	0.031	0.084	0.045	0.013	0.153	0.097

8.3 Measurement of SAR Data

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) Per FCC KDB Publication 447498 D04, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg (2.0W/kg for 10g) then testing at the other channels is not required for such test configuration(s).
- 3) The scaled SAR = Measured SAR(W/kg) * Duty Cycle Scaled factor * Scaled factor
- 4) Duty Cycle Scaled factor = 100% / Measured Duty Cycle

WiFi

- 1) When the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR test for the other 802.11 modes are not required.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

8.3.1 SAR Result Of WIFI 2.4GHz

Wi-Fi 2.4G SAR Test Record ANT0												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Head&Body Test data (Separate 10mm)												
Front side	802.11b	11/2462	98.92%	1.011	0.158	0.087	0.16	20.30	21.00	1.175	0.188	22.0
Back side	802.11b	11/2462	98.92%	1.011	0.176	0.099	0.01	20.30	21.00	1.175	0.209	22.0
Left side	802.11b	11/2462	98.92%	1.011	0.372	0.211	0.02	20.30	21.00	1.175	0.442	22.0
Right side	802.11b	11/2462	98.92%	1.011	0.059	0.030	0.03	20.30	21.00	1.175	0.070	22.2
Top side	802.11b	11/2462	98.92%	1.011	0.679	0.271	-0.07	20.30	21.00	1.175	0.807	21.8
Bottom side	802.11b	11/2462	98.92%	1.011	0.089	0.048	0.00	20.30	21.00	1.175	0.106	22.2
Top side	802.11b	1/2412	98.92%	1.011	0.404	0.160	0.00	19.82	21.00	1.312	0.536	21.8
Top side	802.11b	6/2437	98.93%	1.011	0.675	0.268	0.00	20.09	21.00	1.233	0.842	21.8
Top side with Battery2#	802.11b	6/2437	98.93%	1.011	0.613	0.224	-0.12	20.09	21.00	1.233	0.764	21.8
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)												
Front side	802.11b	11/2462	98.92%	1.011	0.700	0.352	-0.07	20.30	21.00	1.175	0.418	21.9
Back side	802.11b	11/2462	98.92%	1.011	0.395	0.190	0.05	20.30	21.00	1.175	0.226	21.9
Left side	802.11b	11/2462	98.92%	1.011	2.030	1.030	0.12	20.30	21.00	1.175	1.223	21.9
Right side	802.11b	11/2462	98.92%	1.011	0.097	0.045	0.08	20.30	21.00	1.175	0.053	21.9
Top side	802.11b	11/2462	98.92%	1.011	6.010	1.920	0.00	20.30	21.00	1.175	2.281	22.2
Bottom side	802.11b	11/2462	98.92%	1.011	0.140	0.077	0.03	20.30	21.00	1.175	0.091	21.9
Top side	802.11b	1/2412	98.92%	1.011	4.430	1.440	-0.01	19.82	21.00	1.312	1.910	22.2
Top side	802.11b	6/2437	98.93%	1.011	5.560	1.810	-0.09	20.09	21.00	1.233	2.256	22.2
Top side with Battery2#	802.11b	11/2462	98.92%	1.011	5.570	1.810	0.03	20.30	21.00	1.175	2.150	22.2
Wi-Fi 2.4G SAR Test Record ANT1												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Head&Body Test data (Separate 10mm)												
Front side	802.11b	11/2462	98.92%	1.011	0.067	0.035	-0.07	19.97	21.00	1.268	0.086	22.1
Back side	802.11b	11/2462	98.92%	1.011	0.209	0.109	0.08	19.97	21.00	1.268	0.268	22.1
Left side	802.11b	11/2462	98.92%	1.011	0.042	0.022	-0.05	19.97	21.00	1.268	0.054	22.1
Right side	802.11b	11/2462	98.92%	1.011	0.248	0.135	-0.01	19.97	21.00	1.268	0.318	22.1
Top side	802.11b	11/2462	98.92%	1.011	0.324	0.158	-0.06	19.97	21.00	1.268	0.415	22.0
Bottom side	802.11b	11/2462	98.92%	1.011	0.034	0.017	0.04	19.97	21.00	1.268	0.044	22.1
Top side	802.11b	1/2412	98.92%	1.011	0.248	0.123	0.09	19.14	21.00	1.535	0.385	22.0
Top side	802.11b	6/2437	98.93%	1.011	0.281	0.138	0.14	19.62	21.00	1.374	0.390	22.0
Top side with Battery2#	802.11b	11/2462	98.92%	1.011	0.289	0.140	0.11	19.97	21.00	1.268	0.370	22.0



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 49 of 56

Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)												
Front side	802.11b	11/2462	98.92%	1.011	0.367	0.196	-0.05	19.97	21.00	1.268	0.251	22.1
Back side	802.11b	11/2462	98.92%	1.011	0.654	0.350	-0.02	19.97	21.00	1.268	0.449	22.1
Left side	802.11b	11/2462	98.92%	1.011	0.169	0.086	-0.05	19.97	21.00	1.268	0.110	22.1
Right side	802.11b	11/2462	98.92%	1.011	0.652	0.334	0.16	19.97	21.00	1.268	0.428	22.1
Top side	802.11b	11/2462	98.92%	1.011	2.140	0.866	-0.16	19.97	21.00	1.268	1.110	22.1
Bottom side	802.11b	11/2462	98.92%	1.011	0.205	0.109	-0.01	19.97	21.00	1.268	0.140	22.1
Top side	802.11b	1/2412	98.92%	1.011	1.580	0.649	-0.12	19.14	21.00	1.535	1.007	22.1
Top side	802.11b	6/2437	98.93%	1.011	1.920	0.784	-0.02	19.62	21.00	1.374	1.089	22.1
Top side with Battery2#	802.11b	11/2462	98.92%	1.011	1.850	0.761	0.08	19.97	21.00	1.268	0.975	22.1
Wi-Fi 2.4G SAR Test Record MIMO												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Head&Body Test data (Separate 10mm)												
Front side	802.11ax HEW20M	11/2462	96.88%	1.032	0.047	0.026	0.01	20.48	21.00	1.127	0.055	22.0
Back side	802.11ax HEW20M	11/2462	96.88%	1.032	0.056	0.032	-0.01	20.48	21.00	1.127	0.065	22.0
Left side	802.11ax HEW20M	11/2462	96.88%	1.032	0.110	0.061	-0.01	20.48	21.00	1.127	0.128	22.0
Right side	802.11ax HEW20M	11/2462	96.88%	1.032	0.044	0.023	0.07	20.48	21.00	1.127	0.051	22.1
Top side	802.11ax HEW20M	11/2462	96.88%	1.032	0.222	0.090	-0.05	20.48	21.00	1.127	0.258	22.0
Bottom side	802.11ax HEW20M	11/2462	96.88%	1.032	0.043	0.023	-0.15	20.48	21.00	1.127	0.050	22.1
Top side	802.11ax HEW20M	1/2412	96.88%	1.032	0.136	0.057	0.01	19.43	21.00	1.435	0.201	22.0
Top side	802.11ax HEW20M	6/2437	96.88%	1.032	0.206	0.084	-0.11	19.95	21.00	1.274	0.271	22.0
Top side with Battery2#	802.11ax HEW20M	6/2437	96.88%	1.032	0.201	0.080	0.06	19.95	21.00	1.274	0.264	22.0
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)												
Front side	802.11ax HEW20M	11/2462	96.88%	1.032	0.203	0.100	0.06	20.48	21.00	1.127	0.116	22.0
Back side	802.11ax HEW20M	11/2462	96.88%	1.032	0.114	0.059	0.11	20.48	21.00	1.127	0.069	22.0
Left side	802.11ax HEW20M	11/2462	96.88%	1.032	0.619	0.321	-0.05	20.48	21.00	1.127	0.373	22.0
Right side	802.11ax HEW20M	11/2462	96.88%	1.032	0.089	0.043	-0.08	20.48	21.00	1.127	0.050	22.1
Top side	802.11ax HEW20M	11/2462	96.88%	1.032	1.660	0.532	-0.03	20.48	21.00	1.127	0.619	22.0
Bottom side	802.11ax HEW20M	11/2462	96.88%	1.032	0.075	0.039	-0.05	20.48	21.00	1.127	0.045	22.1
Top side	802.11ax HEW20M	1/2412	96.88%	1.032	1.400	0.451	0.19	19.43	21.00	1.435	0.668	22.0
Top side	802.11ax HEW20M	6/2437	96.88%	1.032	1.780	0.570	-0.02	19.95	21.00	1.274	0.749	22.0
Top side with Battery2#	802.11ax HEW20M	6/2437	96.88%	1.032	1.650	0.521	-0.17	19.95	21.00	1.274	0.685	22.0



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

8.3.2 SAR Result Of WIFI 5GHz

Wi-Fi 5GSAR Test Record ANT0												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Head&Body Test Data U-NII-1 (Separate 10mm)												
Front side	802.11a	48/5240	98.76%	1.013	0.069	0.027	0.05	16.15	17.00	1.216	0.085	21.9
Back side	802.11a	48/5240	98.76%	1.013	0.247	0.100	-0.03	16.15	17.00	1.216	0.304	21.9
Left side	802.11a	48/5240	98.76%	1.013	0.284	0.117	0.16	16.15	17.00	1.216	0.350	21.9
Right side	802.11a	48/5240	98.76%	1.013	0.045	0.020	0.02	16.15	17.00	1.216	0.055	22.2
Top side	802.11a	48/5240	98.76%	1.013	0.712	0.214	0.10	16.15	17.00	1.216	0.877	21.8
Bottom side	802.11a	48/5240	98.76%	1.013	0.043	0.020	0.01	16.15	17.00	1.216	0.053	22.2
Top side	802.11a	36/5180	98.69%	1.013	0.767	0.233	0.05	15.45	17.00	1.429	1.110	21.8
Top side	802.11a	40/5200	98.69%	1.013	0.699	0.212	-0.01	15.33	17.00	1.469	1.040	21.8
Top side with Battery2#	802.11a	36/5180	98.69%	1.013	0.688	0.193	0.04	15.45	17.00	1.429	0.996	21.8
Head&Body Test Data U-NII-3 (Separate 10mm)												
Front side	802.11a	165/5825	98.76%	1.013	0.182	0.075	-0.03	21.77	22.00	1.054	0.194	21.9
Back side	802.11a	165/5825	98.76%	1.013	0.293	0.105	-0.13	21.77	22.00	1.054	0.313	21.9
Left side	802.11a	165/5825	98.76%	1.013	0.365	0.138	0.01	21.77	22.00	1.054	0.390	21.9
Right side	802.11a	165/5825	98.76%	1.013	0.059	0.021	0.03	21.77	22.00	1.054	0.063	21.9
Top side	802.11a	165/5825	98.76%	1.013	0.768	0.243	-0.04	21.77	22.00	1.054	0.820	21.8
Bottom side	802.11a	165/5825	98.76%	1.013	0.031	0.012	0.08	21.77	22.00	1.054	0.033	21.9
Top side	802.11a	149/5745	98.82%	1.012	0.885	0.279	0.05	21.75	22.00	1.059	0.949	21.8
Top side	802.11a	157/5785	98.76%	1.013	0.752	0.239	-0.09	21.60	22.00	1.096	0.835	21.8
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data U-NII-1 (Separate 0mm)												
Front side	802.11a	48/5240	98.76%	1.013	0.179	0.066	-0.06	16.15	17.00	1.216	0.081	21.9
Back side	802.11a	48/5240	98.76%	1.013	0.315	0.120	0.11	16.15	17.00	1.216	0.148	21.9
Left side	802.11a	48/5240	98.76%	1.013	1.580	0.526	-0.09	16.15	17.00	1.216	0.648	21.9
Right side	802.11a	48/5240	98.76%	1.013	0.106	0.040	-0.09	16.15	17.00	1.216	0.049	21.9
Top side	802.11a	48/5240	98.76%	1.013	4.060	0.946	0.16	16.15	17.00	1.216	1.165	22.2
Bottom side	802.11a	48/5240	98.76%	1.013	0.048	0.020	-0.11	16.15	17.00	1.216	0.025	21.9
Top side	802.11a	36/5180	98.69%	1.013	3.860	0.898	0.04	15.45	17.00	1.429	1.300	22.2
Top side	802.11a	40/5200	98.69%	1.013	3.950	0.917	0.12	15.33	17.00	1.469	1.365	22.2
Extremity Test data U-NII-3 (Separate 0mm)												
Front side	802.11a	165/5825	98.76%	1.013	0.369	0.142	0.05	21.77	22.00	1.054	0.152	21.9
Back side	802.11a	165/5825	98.76%	1.013	0.476	0.166	0.01	21.77	22.00	1.054	0.177	21.9
Left side	802.11a	165/5825	98.76%	1.013	1.990	0.696	0.11	21.77	22.00	1.054	0.743	21.9
Right side	802.11a	165/5825	98.76%	1.013	0.069	0.027	-0.04	21.77	22.00	1.054	0.029	21.9



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 51 of 56

Top side	802.11a	165/5825	98.76%	1.013	5.090	1.300	-0.16	21.77	22.00	1.054	1.389	21.9
Bottom side	802.11a	165/5825	98.76%	1.013	0.068	0.029	0.01	21.77	22.00	1.054	0.031	21.9
Top side	802.11a	149/5745	98.82%	1.012	6.140	1.550	0.00	21.75	22.00	1.059	1.662	21.9
Top side	802.11a	157/5785	98.76%	1.013	5.830	1.480	0.01	21.60	22.00	1.096	1.644	21.9
Top side with Battery2#	802.11a	149/5745	98.82%	1.012	5.520	1.390	0.09	21.75	22.00	1.059	1.490	21.9
Wi-Fi 5G SAR Test Record ANT1												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Head&Body Test Data U-NII-1 (Separate 10mm)												
Front side	802.11a	48/5240	98.76%	1.013	0.041	0.017	0.01	16.14	17.00	1.219	0.051	22.2
Back side	802.11a	48/5240	98.76%	1.013	0.230	0.090	0.12	16.14	17.00	1.219	0.284	21.9
Left side	802.11a	48/5240	98.76%	1.013	0.010	0.002	0.05	16.14	17.00	1.219	0.012	22.2
Right side	802.11a	48/5240	98.76%	1.013	0.152	0.063	-0.18	16.14	17.00	1.219	0.188	21.9
Top side	802.11a	48/5240	98.76%	1.013	0.316	0.121	-0.08	16.14	17.00	1.219	0.390	21.9
Bottom side	802.11a	48/5240	98.76%	1.013	0.028	0.009	0.09	16.14	17.00	1.219	0.035	22.2
Top side	802.11a	36/5180	98.69%	1.013	0.267	0.103	0.03	15.43	17.00	1.435	0.388	21.9
Top side	802.11a	40/5200	98.69%	1.013	0.279	0.107	-0.09	15.65	17.00	1.365	0.386	21.9
Head&Body Test Data U-NII-3 (Separate 10mm)												
Front side	802.11a	165/5825	98.76%	1.013	0.154	0.063	0.02	18.79	20.00	1.321	0.206	21.9
Back side	802.11a	165/5825	98.76%	1.013	0.393	0.149	0.05	18.79	20.00	1.321	0.526	21.9
Left side	802.11a	165/5825	98.76%	1.013	0.023	0.008	0.16	18.79	20.00	1.321	0.031	21.9
Right side	802.11a	165/5825	98.76%	1.013	0.240	0.100	0.03	18.79	20.00	1.321	0.321	21.9
Top side	802.11a	165/5825	98.76%	1.013	0.448	0.178	-0.04	18.79	20.00	1.321	0.600	21.9
Bottom side	802.11a	165/5825	98.76%	1.013	0.080	0.024	0.09	18.79	20.00	1.321	0.107	21.9
Top side	802.11a	149/5745	98.82%	1.012	0.844	0.336	-0.04	18.62	20.00	1.374	1.174	21.8
Top side	802.11a	157/5785	98.76%	1.013	0.524	0.207	-0.02	18.52	20.00	1.406	0.746	21.8
Top side with Battery2#	802.11a	149/5745	98.82%	1.012	0.712	0.285	0.08	18.62	20.00	1.374	0.990	21.8
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data U-NII-1 (Separate 0mm)												
Front side	802.11a	48/5240	98.76%	1.013	0.093	0.037	-0.03	16.14	17.00	1.219	0.046	22.2
Back side	802.11a	48/5240	98.76%	1.013	0.507	0.187	0.02	16.14	17.00	1.219	0.231	22.2
Left side	802.11a	48/5240	98.76%	1.013	0.034	0.010	0.06	16.14	17.00	1.219	0.012	22.2
Right side	802.11a	48/5240	98.76%	1.013	0.818	0.252	-0.05	16.14	17.00	1.219	0.311	22.2
Top side	802.11a	48/5240	98.76%	1.013	1.250	0.397	0.09	16.14	17.00	1.219	0.490	22.2
Bottom side	802.11a	48/5240	98.76%	1.013	0.076	0.011	0.13	16.14	17.00	1.219	0.014	22.2
Top side	802.11a	36/5180	98.69%	1.013	1.290	0.393	0.11	15.43	17.00	1.435	0.571	22.2
Top side	802.11a	40/5200	98.69%	1.013	1.300	0.407	-0.02	15.65	17.00	1.365	0.563	22.2
Extremity Test data U-NII-3 (Separate 0mm)												
Front side	802.11a	165/5825	98.76%	1.013	0.361	0.135	-0.05	18.79	20.00	1.321	0.181	21.9



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 52 of 56

Back side	802.11a	165/5825	98.76%	1.013	0.664	0.218	0.05	18.79	20.00	1.321	0.292	21.9
Left side	802.11a	165/5825	98.76%	1.013	0.063	0.026	0.15	18.79	20.00	1.321	0.035	21.9
Right side	802.11a	165/5825	98.76%	1.013	1.110	0.323	-0.02	18.79	20.00	1.321	0.432	21.9
Top side	802.11a	165/5825	98.76%	1.013	2.720	0.851	-0.03	18.79	20.00	1.321	1.139	22.2
Bottom side	802.11a	165/5825	98.76%	1.013	0.157	0.063	0.08	18.79	20.00	1.321	0.084	21.9
Top side	802.11a	149/5745	98.82%	1.012	5.610	1.790	-0.11	18.62	20.00	1.374	2.489	22.2
Top side	802.11a	157/5785	98.76%	1.013	2.940	0.942	0.00	18.52	20.00	1.406	1.342	22.2
Top side with Battery2#	802.11a	149/5745	98.82%	1.012	4.880	1.570	-0.11	18.62	20.00	1.374	2.183	22.2

Wi-Fi 5G SAR Test Record MIMO

Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Head&Body Test Data U-NII-1 (Separate 10mm)												
Front side	802.11ac 80M	42/5210	90.57%	1.104	0.032	0.012	0.18	15.78	17.00	1.324	0.047	21.7
Back side	802.11ac 80M	42/5210	90.57%	1.104	0.117	0.047	0.16	15.78	17.00	1.324	0.171	21.7
Left side	802.11ac 80M	42/5210	90.57%	1.104	0.130	0.055	-0.02	15.78	17.00	1.324	0.190	21.7
Right side	802.11ac 80M	42/5210	90.57%	1.104	0.094	0.037	-0.05	15.78	17.00	1.324	0.137	21.7
Top side	802.11ac 80M	42/5210	90.57%	1.104	0.343	0.101	-0.04	15.78	17.00	1.324	0.501	21.7
Bottom side	802.11ac 80M	42/5210	90.57%	1.104	0.009	0.004	-0.10	15.78	17.00	1.324	0.013	21.7
Head&Body Test Data U-NII-3 (Separate 10mm)												
Front side	802.11ac 80M	155/5775	91.00%	1.099	0.135	0.052	0.08	20.48	21.00	1.127	0.167	21.7
Back side	802.11ac 80M	155/5775	91.00%	1.099	0.456	0.178	-0.11	20.48	21.00	1.127	0.565	21.7
Left side	802.11ac 80M	155/5775	91.00%	1.099	0.441	0.184	0.00	20.48	21.00	1.127	0.546	21.7
Right side	802.11ac 80M	155/5775	91.00%	1.099	0.301	0.121	0.02	20.48	21.00	1.127	0.373	21.7
Top side	802.11ac 80M	155/5775	91.00%	1.099	1.150	0.347	0.01	20.48	21.00	1.127	1.425	21.7
Bottom side	802.11ac 80M	155/5775	91.00%	1.099	0.045	0.019	0.08	20.48	21.00	1.127	0.056	21.7
Top side with repeat	802.11ac 80M	155/5775	91.00%	1.099	1.095	0.330	0.03	20.48	21.00	1.127	1.356	21.7
Top side with Battery2#	802.11ac 80M	155/5775	91.00%	1.099	1.060	0.315	0.09	20.48	21.00	1.127	1.313	21.7
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data U-NII-1 (Separate 0mm)												
Front side	802.11ac 80M	42/5210	90.57%	1.104	0.075	0.027	-0.15	15.78	17.00	1.324	0.039	21.7
Back side	802.11ac 80M	42/5210	90.57%	1.104	0.229	0.085	0.02	15.78	17.00	1.324	0.124	21.7
Left side	802.11ac 80M	42/5210	90.57%	1.104	0.742	0.252	-0.07	15.78	17.00	1.324	0.368	21.7
Right side	802.11ac 80M	42/5210	90.57%	1.104	0.365	0.123	-0.08	15.78	17.00	1.324	0.180	21.7
Top side	802.11ac 80M	42/5210	90.57%	1.104	1.940	0.429	0.16	15.78	17.00	1.324	0.627	21.7
Bottom side	802.11ac 80M	42/5210	90.57%	1.104	0.025	0.009	-0.03	15.78	17.00	1.324	0.013	21.7
Extremity Test data U-NII-3 (Separate 0mm)												
Front side	802.11ac 80M	155/5775	91.00%	1.099	0.336	0.127	-0.16	20.48	21.00	1.127	0.157	21.7
Back side	802.11ac 80M	155/5775	91.00%	1.099	0.930	0.327	0.03	20.48	21.00	1.127	0.405	21.7
Left side	802.11ac 80M	155/5775	91.00%	1.099	2.150	0.797	0.11	20.48	21.00	1.127	0.987	21.7



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZSAR-TRF-01 Rev. A/0 May15,2023

Report No.: SZCR240400113806

Page: 53 of 56

Right side	802.11ac 80M	155/5775	91.00%	1.099	1.390	0.460	0.03	20.48	21.00	1.127	0.570	21.7
Top side	802.11ac 80M	155/5775	91.00%	1.099	7.080	1.640	-0.07	20.48	21.00	1.127	2.032	21.7
Bottom side	802.11ac 80M	155/5775	91.00%	1.099	0.089	0.036	-0.03	20.48	21.00	1.127	0.045	21.7
Top side with Battery2#	802.11ac 80M	155/5775	91.00%	1.099	6.550	1.490	-0.07	20.48	21.00	1.127	1.846	21.7



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Technical Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

8.3.3 SAR Result Of Bluetooth

Bluetooth SAR Test Record ANT0												
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 1-g (W/kg)	Liquid Temp.(°C)
Head&Body Test Data (10mm)												
Front side	DH5	78/2480	77.09%	1.297	0.038	0.020	-0.19	11.46	12.00	1.132	0.056	22.2
Back side	DH5	78/2480	77.09%	1.297	0.045	0.021	0.09	11.46	12.00	1.132	0.066	22.2
Left side	DH5	78/2480	77.09%	1.297	0.093	0.051	0.04	11.46	12.00	1.132	0.137	22.2
Right side	DH5	78/2480	77.09%	1.297	0.006	0.002	0.07	11.46	12.00	1.132	0.009	22.2
Top side	DH5	78/2480	77.09%	1.297	0.273	0.099	-0.03	11.46	12.00	1.132	0.401	22.2
Bottom side	DH5	78/2480	77.09%	1.297	0.006	0.003	-0.08	11.46	12.00	1.132	0.009	22.2
Top side	DH5	0/2402	77.10%	1.297	0.089	0.034	-0.01	10.55	12.00	1.396	0.161	22.2
Top side	DH5	39/2441	77.10%	1.297	0.144	0.055	-0.05	10.99	12.00	1.262	0.236	22.2
Top side with Battery2#	DH5	78/2480	77.09%	1.297	0.211	0.072	-0.17	11.46	12.00	1.132	0.310	22.2
Test position	Test mode	Test ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	SAR (W/kg) 10-g	Power drift (dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR 10-g (W/kg)	Liquid Temp.(°C)
Extremity Test data (Separate 0mm)												
Front side	DH5	78/2480	77.09%	1.297	0.081	0.036	-0.02	11.46	12.00	1.132	0.053	22.2
Back side	DH5	78/2480	77.09%	1.297	0.045	0.020	-0.04	11.46	12.00	1.132	0.029	22.2
Left side	DH5	78/2480	77.09%	1.297	0.251	0.130	0.05	11.46	12.00	1.132	0.191	22.2
Right side	DH5	78/2480	77.09%	1.297	0.010	0.004	-0.07	11.46	12.00	1.132	0.006	22.2
Top side	DH5	78/2480	77.09%	1.297	0.725	0.233	0.09	11.46	12.00	1.132	0.342	22.2
Bottom side	DH5	78/2480	77.09%	1.297	0.019	0.009	0.02	11.46	12.00	1.132	0.013	22.2
Top side	DH5	0/2402	77.10%	1.297	0.317	0.109	0.09	10.99	12.00	1.262	0.178	22.2
Top side	DH5	39/2441	77.10%	1.297	0.490	0.161	0.06	10.99	12.00	1.262	0.263	22.2
Top side with Battery2#	DH5	78/2480	77.09%	1.297	0.615	0.198	0.04	11.46	12.00	1.132	0.291	22.2

9 Equipment list

Test Platform		SPEAG DASY8 Professional				
Location		SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch				
Software Reference		cDASY8 V16.2.4.2524				
Hardware Reference						
Equipment		Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
☒	Power sensor	Agilent	8481H	SZ-WSR-M-008	2024/1/30	2025/1/29
☒	DAE	SPEAG	DAE4ip	SZ-WSR-M-074	2023/7/14	2024/7/13
☒	E-field PROBE	SPEAG	EX3DV4	SZ-WSR-M-075	2023/7/17	2024/7/16
☒	Dipole	SPEAG	D2450V2	SZ-WSR-M-039	2022/11/2	2025/11/1
☒	Dipole	SPEAG	D5GHzV2	SZ-WSR-M-046	2022/11/1	2025/10/31
☒	Signal Generator	Agilent	N5171B	SZ-WSR-M-006	2024/1/30	2025/1/29
☒	Preamplifier	Mini-Circuits	ZHL-42W	SZ-WSR-A-001	NCR	NCR
☒	Preamplifier	Compliance Directions Systems Inc.	AMP28-3W	SZ-WSR-A-002	NCR	NCR
☒	Power Meter	Agilent	E4416A	SZ-WSR-M-007	2024/1/30	2025/1/29
☒	Power Sensor	Agilent	8481H	SZ-WSR-M-008	2024/1/30	2025/1/29
☒	Power Sensor	R&S	NRP-Z92	SZ-WSR-M-009	2024/1/30	2025/1/29
☒	Attenuator	SHX	TS2-3dB	SZ-WSR-A-012	NCR	NCR
☒	Amplifier	Mini-circuits	ZHL-42W	SZ-WSR-A-001	N/A	N/A
☒	Amplifier	Mini-circuits	AMP28-3W	SZ-WSR-A-002	N/A	N/A
☒	Humidity and Temperature Indicator	CHIGAO	HTC-1	SZ-WSR-M-011	2023/5/26	2024/5/25
☒	Humidity and Temperature Indicator	CHIGAO	HTC-1	SZ-WSR-M-012	2023/5/26	2024/5/25

10 Calibration certificate

Please see the Appendix C

11 Photographs

Please see the Appendix D

Appendix A: Detailed System Check Results

Appendix B: Detailed Test Results

Appendix C: Calibration certificate

Appendix D: Photographs

---END---