

FCC Test Report

Applicant : Shenzhen Qianyan Technology LTD

Address : No.3301,Block C,Section 1,Chuangzhi
Yuncheng, Building,Liuxian Avenue,Xili
Community, Xili Street, Nanshan District,
Shenzhen, 518000, China

Product Name : Govee RGBIC LED Neon Rope Light for desks

Report Date : Jul. 20, 2023

Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Configuration	6
1.5. Description Of Test Setup	7
1.6. Test Equipment List	8
1.7. Measurement Uncertainty	9
1.8. Description of Test Facility	9
2. Summary of Test Results	10
3. Conducted Emission Test	11
3.1. Test Standard and Limit	11
3.2. Test Setup	11
3.3. Test Procedure	11
3.4. Test Data	11
4. Radiation Spurious Emission and Band Edge	16
4.1. Test Standard and Limit	16
4.2. Test Setup	16
4.3. Test Procedure	17
4.4. Test Data	18
5. Maximum Peak Output Power Test	26
5.1. Test Standard and Limit	26
5.2. Test Setup	26
5.3. Test Procedure	26
5.4. Test Data	26
6. Antenna Requirement	27
6.1. Test Standard and Requirement	27
6.2. Antenna Connected Construction	27
APPENDIX I -- TEST SETUP PHOTOGRAPH	28
APPENDIX II -- EXTERNAL PHOTOGRAPH	28
APPENDIX III -- INTERNAL PHOTOGRAPH	28



TEST REPORT

Applicant : Shenzhen Qianyan Technology LTD
Manufacturer : Shenzhen Qianyan Technology LTD
Product Name : Govee RGBIC LED Neon Rope Light for desks
Model No. : H61C5, H61C2
Trade Mark : Govee
Rating(s) : H61C2 Input: 24V $\equiv$ 1A
H61C5 Input: 24V $\equiv$ 2A

Test Standard(s) : FCC Part15 Subpart C, Section 15.247
Test Method(s) : ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Jun. 02, 2023

Date of Test

Jun. 02 ~ Jul. 07, 2023

Prepared By

Nian xiu Chen

(Nianxiu Chen)

Approved & Authorized Signer

Kingkong Jin

(Kingkong Jin)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Jul. 20, 2023

Note 1:

This is a Class II application which was based on the original report 18220WC30025001. The difference between the original device and current one described as following:

1. Change the model name to "H61C5, H61C2".

Base on the changes, models have different strip lengths and inputs, only conducted emission and spurious emission were retested. The changes will not related with the other RF parameters.



1. General Information

1.1. Client Information

Applicant	:	Shenzhen Qianyan Technology LTD
Address	:	No.3301,Block C,Section 1,Chuangzhi Yuncheng, Building,Liuxian Avenue,Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China
Manufacturer	:	Shenzhen Qianyan Technology LTD
Address	:	No.3301,Block C,Section 1,Chuangzhi Yuncheng, Building,Liuxian Avenue,Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China

1.2. Description of Device (EUT)

Product Name	:	Govee RGBIC LED Neon Rope Light for desks
Model No.	:	H61C5, H61C2 (Note: All samples are the same except the model number, Lamp strip length and input, so we prepare all models for test.)
Trade Mark	:	Govee
Test Power Supply	:	AC 120V, 60Hz for Adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter(H61C5 for Light strip length 5m)	:	Model No.: CW2402000US Input: 100-240V~50/60Hz 1.2A MAX Output: 24V= 2000mA
Adapter(H61C2 for Light strip length 2m)	:	Model No.: BI24GL-240100-AdU Input: 100-240V~50/60Hz 0.8A Output : 24V= 1A

RF Specification

Operation Mode	:	☒ BT BLE
Support Rate	:	☒ 1Mbps ☐ 2Mbps
Operation Frequency	:	2402~2480MHz
Number of Channel	:	40 Channels
Modulation Type	:	GFSK
Antenna Type	:	PCB Antenna



Antenna Gain(Peak)	:	4.51 dBi (Provided by customer)
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
--	--

1.4. Description of Test Configuration



Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	09	2420	18	2438	27	2456	36	2474
01	2404	10	2422	19	2440	28	2458	37	2476
02	2406	11	2424	20	2442	29	2460	38	2478
03	2408	12	2426	21	2444	30	2462	39	2480
04	2410	13	2428	22	2446	31	2464		
05	2412	14	2430	23	2448	32	2466		
06	2414	15	2432	24	2450	33	2468		
07	2416	16	2434	25	2452	34	2470		
08	2418	17	2436	26	2454	35	2472		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with channel 0, 19 and 39.



1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2023	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2022	1 Year
6.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
7.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Oct. 13, 2022	1 Year
8.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
10.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
11.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Oct. 23, 2022	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
15.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
16.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
17.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
18.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 19, 2022	1 Year
19.	Power Meter	Agilent	N1914A	MY50001102	Oct.26, 2022	1 Year



1.7. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark:(1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.


AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2440MHz
Test Specification: AC 120V, 60Hz for Adapter
Comment: Live Line
Temp.(°C)/Hum.(%RH): 22.5°C/49%RH
Model: H61C5




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1980	44.81	9.83	54.64	63.69	-9.05	QP	
2	0.1980	35.12	9.83	44.95	53.69	-8.74	AVG	
3	0.2500	38.69	9.82	48.51	61.75	-13.24	QP	
4	0.2500	27.59	9.82	37.41	51.75	-14.34	AVG	
5	0.3540	35.41	9.82	45.23	58.87	-13.64	QP	
6	0.4780	22.44	9.84	32.28	46.37	-14.09	AVG	
7	0.6540	30.59	9.87	40.46	56.00	-15.54	QP	
8	1.1220	18.71	9.85	28.56	46.00	-17.44	AVG	
9	1.1260	29.54	9.85	39.39	56.00	-16.61	QP	
10	7.7380	25.47	9.90	35.37	50.00	-14.63	AVG	
11	20.2540	37.28	10.34	47.62	60.00	-12.38	QP	
12	20.2540	27.83	10.34	38.17	50.00	-11.83	AVG	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2440MHz
Test Specification: AC 120V, 60Hz for Adapter
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 22.5°C/49%RH
Model: H61C5




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1980	44.00	9.83	53.83	63.69	-9.86	QP	
2	0.1980	35.71	9.83	45.54	53.69	-8.15	AVG	
3	0.3140	37.54	9.83	47.37	59.86	-12.49	QP	
4	0.3140	25.68	9.83	35.51	49.86	-14.35	AVG	
5	0.4180	33.34	9.82	43.16	57.49	-14.33	QP	
6	0.4180	22.78	9.82	32.60	47.49	-14.89	AVG	
7	0.4900	33.01	9.85	42.86	56.17	-13.31	QP	
8	0.6660	19.54	9.87	29.41	46.00	-16.59	AVG	
9	7.8940	25.70	9.90	35.60	50.00	-14.40	AVG	
10	8.0940	34.23	9.91	44.14	60.00	-15.86	QP	
11	20.2540	36.70	10.34	47.04	60.00	-12.96	QP	
12	20.2540	27.68	10.34	38.02	50.00	-11.98	AVG	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2440MHz
Test Specification: AC 120V, 60Hz for Adapter
Comment: Live Line
Temp.(°C)/Hum.(%RH): 22.5°C/49%RH
Model: H61C2




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1620	44.58	9.83	54.41	65.36	-10.95	QP	
2	0.1620	31.41	9.83	41.24	55.36	-14.12	AVG	
3	0.4020	33.13	9.81	42.94	57.81	-14.87	QP	
4	0.5140	23.05	9.85	32.90	46.00	-13.10	AVG	
5	0.5980	19.27	9.86	29.13	46.00	-16.87	AVG	
6	1.4980	36.47	9.83	46.30	56.00	-9.70	QP	
7	6.7460	35.27	9.86	45.13	60.00	-14.87	QP	
8	11.2540	42.68	10.03	52.71	60.00	-7.29	QP	
9	11.9940	23.82	10.06	33.88	50.00	-16.12	AVG	
10	14.4060	22.49	10.15	32.64	50.00	-17.36	AVG	
11	22.4980	38.51	10.72	49.23	60.00	-10.77	QP	
12	22.4980	26.86	10.72	37.58	50.00	-12.42	AVG	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2440MHz
Test Specification: AC 120V, 60Hz for Adapter
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 22.5°C/49%RH
Model: H61C2



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1539	45.23	9.83	55.06	65.78	-10.72	QP	
2	0.5140	25.69	9.85	35.54	46.00	-10.46	AVG	
3	0.5180	34.96	9.85	44.81	56.00	-11.19	QP	
4	1.5020	36.45	9.83	46.28	56.00	-9.72	QP	
5	1.5020	21.70	9.83	31.53	46.00	-14.47	AVG	
6	3.7460	16.16	9.85	26.01	46.00	-19.99	AVG	
7	8.2539	40.31	9.92	50.23	60.00	-9.77	QP	
8	11.2499	25.97	10.03	36.00	50.00	-14.00	AVG	
9	11.9979	30.61	10.06	40.67	50.00	-9.33	AVG	
10	14.2539	41.53	10.15	51.68	60.00	-8.32	QP	
11	22.4980	38.58	10.72	49.30	60.00	-10.70	QP	
12	22.4980	25.95	10.72	36.67	50.00	-13.33	AVG	



4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.



For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement:

–VBW=10Hz, When duty cycle is no less than 98 percent

–VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.4 duty cycle.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.



Test Results (30~1000MHz)

Test Mode: 2440MHz
Power Source: AC 120V, 60Hz for Adapter
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 24.5°C/57%RH
Model: H61C5



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	61.3462	49.39	-18.23	31.16	40.00	-8.84	QP			
2	73.6170	53.26	-21.67	31.59	40.00	-8.41	QP			
3	134.5592	53.91	-21.06	32.85	43.50	-10.65	QP			
4	159.2247	56.24	-20.57	35.67	43.50	-7.83	QP			
5	184.4898	55.31	-19.09	36.22	43.50	-7.28	QP			
6	221.3916	53.16	-17.26	35.90	46.00	-10.10	QP			



Test Results (30~1000MHz)

Test Mode: 2440MHz
Power Source: AC 120V, 60Hz for Adapter
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 24.5°C/57%RH
Model: H61C5




No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	31.2893	56.46	-18.04	38.42	40.00	-1.58	QP			
2	32.1794	56.88	-18.04	38.84	40.00	-1.16	QP			
3	48.6719	51.14	-17.13	34.01	40.00	-5.99	QP			
4	54.4515	52.18	-17.41	34.77	40.00	-5.23	QP			
5	73.6170	54.78	-21.67	33.11	40.00	-6.89	QP			
6	121.9753	52.83	-19.81	33.02	43.50	-10.48	QP			



Test Results (30~1000MHz)

Test Mode: 2440MHz
Power Source: AC 120V, 60Hz for Adapter
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 24.5°C/57%RH
Model: H61C2




No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	106.7587	56.73	-17.83	38.90	43.50	-4.60	QP			
2	133.6184	61.34	-21.01	40.33	43.50	-3.17	QP			
3	138.3873	61.93	-21.27	40.66	43.50	-2.84	QP			
4	176.8874	60.73	-19.54	41.19	43.50	-2.31	QP			
5	222.9500	57.65	-17.21	40.44	46.00	-5.56	QP			
6	247.6819	57.21	-16.16	41.05	46.00	-4.95	QP			



Test Results (30~1000MHz)

Test Mode: 2440MHz
Power Source: AC 120V, 60Hz for Adapter
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 24.5°C/57%RH
Model: H61C2



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	35.2511	54.08	-17.98	36.10	40.00	-3.90	QP			
2	46.9947	54.56	-17.07	37.49	40.00	-2.51	QP			
3	93.4402	55.38	-17.85	37.53	43.50	-5.97	QP			
4	129.9225	60.77	-20.80	39.97	43.50	-3.53	QP			
5	158.1123	57.94	-20.64	37.30	43.50	-6.20	QP			
6	240.8300	53.61	-16.46	37.15	46.00	-8.85	QP			



Test Results (1GHz-25GHz)

Test Mode: CH00			Test channel: Lowest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	27.74	15.27	43.01	74.00	-30.99	Vertical
7206.00	27.92	18.09	46.01	74.00	-27.99	Vertical
9608.00	28.53	23.76	52.29	74.00	-21.71	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	27.47	15.27	42.74	74.00	-31.26	Horizontal
7206.00	28.18	18.09	46.27	74.00	-27.73	Horizontal
9608.00	27.80	23.76	51.56	74.00	-22.44	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	16.01	15.27	31.28	54.00	-22.72	Vertical
7206.00	16.97	18.09	35.06	54.00	-18.94	Vertical
9608.00	18.00	23.76	41.76	54.00	-12.24	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	15.80	15.27	31.07	54.00	-22.93	Horizontal
7206.00	17.21	18.09	35.30	54.00	-18.70	Horizontal
9608.00	17.31	23.76	41.07	54.00	-12.93	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH19			Test channel: Middle			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	27.29	15.42	42.71	74.00	-31.29	Vertical
7320.00	27.89	18.02	45.91	74.00	-28.09	Vertical
9760.00	28.03	23.80	51.83	74.00	-22.17	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	27.28	15.42	42.70	74.00	-31.30	Horizontal
7320.00	28.05	18.02	46.07	74.00	-27.93	Horizontal
9760.00	27.52	23.80	51.32	74.00	-22.68	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	16.10	15.42	31.52	54.00	-22.48	polarization
7320.00	16.83	18.02	34.85	54.00	-19.15	Vertical
9760.00	17.85	23.80	41.65	54.00	-12.35	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	15.91	15.42	31.33	54.00	-22.67	Vertical
7320.00	17.56	18.02	35.58	54.00	-18.42	Horizontal
9760.00	17.61	23.80	41.41	54.00	-12.59	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH39			Test channel: Highest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	27.42	15.58	43.00	74.00	-31.00	Vertical
7440.00	28.05	17.93	45.98	74.00	-28.02	Vertical
9920.00	28.73	23.83	52.56	74.00	-21.44	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	27.42	15.58	43.00	74.00	-31.00	Horizontal
7440.00	28.26	17.93	46.19	74.00	-27.81	Horizontal
9920.00	27.90	23.83	51.73	74.00	-22.27	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	17.22	15.58	32.80	54.00	-21.20	Vertical
7440.00	18.10	17.93	36.03	54.00	-17.97	Vertical
9920.00	18.50	23.83	42.33	54.00	-11.67	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	17.09	15.58	32.67	54.00	-21.33	Horizontal
7440.00	18.36	17.93	36.29	54.00	-17.71	Horizontal
9920.00	17.76	23.83	41.59	54.00	-12.41	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1.Result =Reading + Factor

2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.




5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm)

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW $\geq$ DTS bandwidth.
2. Set the VBW $\geq 3 \times$ RBW.
3. Set the span $\geq 3 \times$ RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Pass

Note: For pre-scan, the result is equal to original, so the original data is referenced.

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE_1M	Ant1	2402	2.39	≤ 30	PASS
		2440	6.01	≤ 30	PASS
		2480	2.37	≤ 30	PASS



6. Antenna Requirement

6.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

6.2. Antenna Connected Construction

The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is 4.51dBi . It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

