

TEST REPORT

FCC MPE Test for RF2216d-D1A
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2112-FC003

DATE OF ISSUE
December 1, 2021

Tested by
Kyung Soo Kang



Technical Manager
Jong Seok Lee



HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO

**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

TEST REPORT

FCC MPE Test for
RF2216d-D1A

REPORT NO.

HCT-RF-2112-FC003

DATE OF ISSUE

December 01, 2021

Additional Model

-

Applicant**SAMSUNG Electronics Co., Ltd.**

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

**Eut Type
Model Name**

RRU(RF2216d)
RF2216d-D1A

FCC ID

A3LRF2216D-D1A

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	December 01, 2021	Initial Release

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

If this report is required to confirmation of authenticity, please contact to www.hct.co.kr

RF Exposure Statement

1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures				
Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. RESULTS

3.1 MPE calculation for standalone operations

- B13 LTE 5 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	746.00	MHz
Antenna Gain(typical)	7.50	dBi
Antenna Gain(numeric)	5.623	-
Power density at prediction frequency(S)	0.3093	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.4973	mW/cm ²

- B13 LTE 10 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	746.00	MHz
Antenna Gain(typical)	7.50	dBi
Antenna Gain(numeric)	5.623	-
Power density at prediction frequency(S)	0.3093	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.4973	mW/cm ²

- 5G NR B13 5 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	746.00	MHz
Antenna Gain(typical)	7.50	dBi
Antenna Gain(numeric)	5.623	-
Power density at prediction frequency(S)	0.3093	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.4973	mW/cm ²

- 5G NR B13 10 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	746.00	MHz
Antenna Gain(typical)	7.50	dBi
Antenna Gain(numeric)	5.623	-
Power density at prediction frequency(S)	0.3093	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.4973	mW/cm ²

- B66 LTE 5 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 10 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 15 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 20 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 5 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 10 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 15 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 20 MHz 1 Carrier

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 5 MHz 1 Carrier + 5G NR B66 5 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 20 MHz 1 Carrier + 5G NR B66 5 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 20 MHz 1 Carrier + 5G NR B66 10 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 20 MHz 1 Carrier + 5G NR B66 5 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 20 MHz 1 Carrier + 5G NR B66 10 MHz 1 Carrier [2 Carrier] (Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 5 MHz 1 Carrier + 5G NR B66 5 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 20 MHz 1 Carrier + 5G NR B66 5 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 20 MHz 1 Carrier + 5G NR B66 10 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 5 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 20 MHz 1 Carrier + B66 LTE 5 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- 5G NR B66 20 MHz 1 Carrier + B66 LTE 10 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 20 MHz 1 Carrier + 5G NR B66 5 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

- B66 LTE 20 MHz 1 Carrier + 5G NR B66 10 MHz 1 Carrier [2 Carrier] (Non-Contiguous)

Max Peak output Power at antenna input terminal	26.00	dBm
Max Peak output Power at antenna input terminal	398.11	mW
Prediction distance	24.00	cm
Prediction frequency	2110.00	MHz
Antenna Gain(typical)	8.00	dBi
Antenna Gain(numeric)	6.310	-
Power density at prediction frequency(S)	0.3470	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

3.2 Simultaneous band emission conditions

Band	MPE Ratio (Power density / Limit)	Sum of MPE Ratio	
B13	0.6219	0.9689	≤ 1
B66	0.3470		

***Note**

1. The result of each band was applied to the worst value.
2. MPE ratios are calculated as
$$[(\text{Power density1} / \text{MPE Limit}) + [(\text{Power density2} / \text{MPE Limit}) + \dots] \leq 1$$