



# RF TEST REPORT

**Applicant** ZTE Corporation  
**FCC ID** SRQ-T3000  
**Product** WiFi6 Router  
**Model** T3000  
**Report No.** R2201A0022-R2  
**Issue Date** March 14, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15E (2021)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Peng Tao

Approved by: Kai Xu

---

## TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



## TABLE OF CONTENT

|                                                     |     |
|-----------------------------------------------------|-----|
| 1. Test Laboratory .....                            | 4   |
| 1.1. Notes of the test report.....                  | 4   |
| 1.2. Test facility .....                            | 4   |
| 1.3. Testing Location .....                         | 4   |
| 2. General Description of Equipment under Test..... | 5   |
| 2.1. Applicant and Manufacturer Information.....    | 5   |
| 2.2. General information.....                       | 5   |
| 3. Applied Standards .....                          | 7   |
| 4. Test Configuration .....                         | 8   |
| 5. Test Case Results .....                          | 10  |
| 5.1. Occupied Bandwidth .....                       | 10  |
| 5.2. Average Power Output.....                      | 25  |
| 5.3. Frequency Stability.....                       | 35  |
| 5.4. Power Spectral Density .....                   | 38  |
| 5.5. Unwanted Emission .....                        | 78  |
| 5.6. Conducted Emission .....                       | 154 |
| 6. Main Test Instruments .....                      | 157 |
| ANNEX A: The EUT Appearance .....                   | 158 |
| ANNEX B: Test Setup Photos .....                    | 159 |

## Summary of measurement results

| Number                                                                                                                                                                                                                                                                                                                                                                                                                                             | Test Case              | Clause in FCC rules | Verdict |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|---------------------|---------|
| 1                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Average output power   | 15.407(a)           | PASS    |
| 2                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Occupied bandwidth     | 15.407(e)           | PASS    |
| 3                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Frequency stability    | 15.407(g)           | PASS    |
| 4                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Power spectral density | 15.407(a)           | PASS    |
| 5                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Unwanted Emissions     | 15.407(b)           | PASS    |
| 6                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Conducted Emissions    | 15.207              | PASS    |
| Date of Testing: January 12, 2022~ March 14, 2022                                                                                                                                                                                                                                                                                                                                                                                                  |                        |                     |         |
| Date of Sample Received: January 6, 2022                                                                                                                                                                                                                                                                                                                                                                                                           |                        |                     |         |
| Note: PASS: The EUT complies with the essential requirements in the standard.<br>FAIL: The EUT does not comply with the essential requirements in the standard.<br>All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. |                        |                     |         |



## 1. Test Laboratory

### 1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2. Test facility

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

### 1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

## 2. General Description of Equipment under Test

### 2.1. Applicant and Manufacturer Information

|                             |                                                                                                                |
|-----------------------------|----------------------------------------------------------------------------------------------------------------|
| <b>Applicant</b>            | ZTE Corporation                                                                                                |
| <b>Applicant address</b>    | ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China |
| <b>Manufacturer</b>         | ZTE Corporation                                                                                                |
| <b>Manufacturer address</b> | ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China |

### 2.2. General information

| EUT Description              |                                                                                                                    |
|------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Model                        | T3000                                                                                                              |
| SN                           | 324215830103                                                                                                       |
| Hardware Version             | T3000GHW1.0                                                                                                        |
| Software Version             | T3000GV0.0.0B01                                                                                                    |
| Power Supply                 | AC adapter                                                                                                         |
| Antenna Type                 | Internal Antenna                                                                                                   |
| Antenna Gain                 | Antenna 1: 6.20 dBi<br>Antenna 2: 6.10 dBi                                                                         |
| Directional Gain             | For Power: 6.20 dBi<br>For PSD: 9.21dBi                                                                            |
| Operating Frequency Range(s) | U-NII-1: 5150MHz-5250MHz<br>U-NII-3: 5725MHz -5850MHz                                                              |
| Modulation Type              | 802.11a/n (HT20/HT40) : OFDM<br>802.11ac (VHT20/VHT40/VHT80/VHT160): OFDM<br>802.11ax (HE20/HE40/HE80/HE160): OFDM |
| Max. Conducted Power         | 24.21 dBm                                                                                                          |
| Testing temperature range:   | -20 ° C to 50° C                                                                                                   |
| Operating temperature range: | 0 ° C to 45° C                                                                                                     |
| Operating voltage range:     | 10.8 V to 13.2 V                                                                                                   |
| State DC voltage:            | 12V                                                                                                                |
| EUT Accessory                |                                                                                                                    |
| Adapter 1                    | Manufacturer: BAIJUNDA<br>Model: STC-A1215C55A-Z                                                                   |
| Adapter 2                    | Manufacturer: RUIJING<br>Model: STC-A1215C55A-Z                                                                    |



Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.

2. This device support automatically discontinue transmission, while the device is not transmitting any information, the device can automatically discontinue transmission and become standby mode for power saving. The device can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3. There is more than one Adapter, each one should be applied throughout the compliance test respectively, and however, only the worst case (Adapter 2) will be recorded in this report.



### 3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**Test standards:**

**FCC CFR47 Part 15E (2021)** Unlicensed National Information Infrastructure Devices

**ANSI C63.10 (2013)**

**Reference standard:**

**KDB 789033 D02 General UNII Test Procedures New Rules v02r01**

**KDB 662911 D01 Multiple Transmitter Output v02r01**

## 4. Test Configuration

### Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Preliminary tests have been done on all the configuration for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates are shown as following table.

| Mode            | Data Rate |           |        |
|-----------------|-----------|-----------|--------|
|                 | Antenna 1 | Antenna 2 | MIMO   |
| 802.11a         | 6 Mbps    | 6 Mbps    | 6 Mbps |
| 802.11n HT20    | MCS0      | MCS0      | MCS8   |
| 802.11n HT40    | MCS0      | MCS0      | MCS8   |
| 802.11ac VHT20  | MCS0      | MCS0      | MCS0   |
| 802.11ac VHT40  | MCS0      | MCS0      | MCS0   |
| 802.11ac VHT80  | MCS0      | MCS0      | MCS0   |
| 802.11ac VHT160 | MCS0      | MCS0      | MCS0   |
| 802.11ax HE20   | MCS0      | MCS0      | MCS0   |
| 802.11ax HE40   | MCS0      | MCS0      | MCS0   |
| 802.11ax HE80   | MCS0      | MCS0      | MCS0   |
| 802.11ax HE160  | MCS0      | MCS0      | MCS0   |

The worst case Antenna mode for each of the following tests for Wi-Fi:

| Test Cases                     | Antenna 1 | Antenna 2 | CDD     |
|--------------------------------|-----------|-----------|---------|
| Average conducted output power | O         | O         | O       |
| Occupied bandwidth             | --        | --        | O       |
| Frequency stability            | --        | --        | 802.11a |
| Power Spectral Density         | O         | O         | O       |
| Unwanted Emissions             | --        | --        | O       |
| Conducted Emissions            | --        | --        | O       |
| Note: "O": test all bands      |           |           |         |



**Wireless Technology and Frequency Range**

| Wireless Technology                                                                                        |         | Bandwidth | Channel | Frequency |
|------------------------------------------------------------------------------------------------------------|---------|-----------|---------|-----------|
| Wi-Fi                                                                                                      | U-NII-1 | 20 MHz    | 36      | 5180MHz   |
|                                                                                                            |         |           | 40      | 5200MHz   |
|                                                                                                            |         |           | 44      | 5220MHz   |
|                                                                                                            |         |           | 48      | 5240MHz   |
|                                                                                                            |         | 40 MHz    | 38      | 5190MHz   |
|                                                                                                            |         |           | 46      | 5230MHz   |
|                                                                                                            |         | 80 MHz    | 42      | 5210MHz   |
|                                                                                                            | U-NII-3 | 20 MHz    | 149     | 5745MHz   |
|                                                                                                            |         |           | 153     | 5765MHz   |
|                                                                                                            |         |           | 157     | 5785MHz   |
|                                                                                                            |         |           | 161     | 5805MHz   |
|                                                                                                            |         |           | 165     | 5825MHz   |
|                                                                                                            |         | 40 MHz    | 151     | 5755MHz   |
|                                                                                                            |         |           | 159     | 5795MHz   |
|                                                                                                            |         | 80 MHz    | 155     | 5775MHz   |
| Does this device support TPC Function? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |         |           |         |           |

## 5. Test Case Results

### 5.1. Occupied Bandwidth

#### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

#### Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable.


For U-NII-1, set RBW  $\approx 1\%$  OCB kHz, VBW  $\geq 3 \times$  RBW, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 26 dB relative to the maximum level measured in the fundamental emission.

For U-NII-3, Set RBW = 100 kHz, VBW  $\geq 3 \times$  RBW, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

Use the 99 % power bandwidth function of the instrument

#### Test Setup



#### Limits

Rule FCC Part §15.407(e)

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 936$  Hz.

**Test Results:****U-NII-1**


| Mode            | Carrier frequency (MHz) | 99% bandwidth (MHz) | Minimum 26 dB bandwidth (MHz) | Conclusion |
|-----------------|-------------------------|---------------------|-------------------------------|------------|
| 802.11a         | 5180                    | 16.54               | 22.65                         | PASS       |
|                 | 5200                    | 16.77               | 29.78                         | PASS       |
|                 | 5240                    | 16.57               | 28.21                         | PASS       |
| 802.11n HT20    | 5180                    | 17.72               | 21.50                         | PASS       |
|                 | 5200                    | 17.72               | 20.82                         | PASS       |
|                 | 5240                    | 17.71               | 20.84                         | PASS       |
| 802.11n HT40    | 5190                    | 36.42               | 43.32                         | PASS       |
|                 | 5230                    | 36.39               | 42.34                         | PASS       |
| 802.11ac VHT20  | 5180                    | 17.73               | 22.94                         | PASS       |
|                 | 5200                    | 17.73               | 21.18                         | PASS       |
|                 | 5240                    | 17.78               | 29.20                         | PASS       |
| 802.11ac VHT40  | 5190                    | 36.48               | 57.47                         | PASS       |
|                 | 5230                    | 36.39               | 42.36                         | PASS       |
| 802.11ac VHT80  | 5210                    | 76.01               | 85.98                         | PASS       |
| 802.11ac VHT160 | 5250                    | 155.04              | 169.50                        | PASS       |
| 802.11ax HE20   | 5180                    | 19.04               | 22.07                         | PASS       |
|                 | 5200                    | 19.05               | 21.90                         | PASS       |
|                 | 5240                    | 19.03               | 22.20                         | PASS       |
| 802.11ax HE40   | 5190                    | 38.05               | 42.51                         | PASS       |
|                 | 5230                    | 37.99               | 41.73                         | PASS       |
| 802.11ax HE80   | 5210                    | 77.53               | 84.84                         | PASS       |
| 802.11ax HE160  | 5250                    | 156.69              | 187.20                        | PASS       |




## U-NII-3

| Mode           | Carrier frequency (MHz) | 99% bandwidth (MHz) | Minimum 6 dB bandwidth (MHz) | Limit (kHz) | Conclusion |
|----------------|-------------------------|---------------------|------------------------------|-------------|------------|
| 802.11a        | 5745                    | 16.52               | 16.39                        | 500         | PASS       |
|                | 5785                    | 16.51               | 16.39                        | 500         | PASS       |
|                | 5825                    | 16.61               | 16.38                        | 500         | PASS       |
| 802.11n HT20   | 5745                    | 17.70               | 17.64                        | 500         | PASS       |
|                | 5785                    | 17.72               | 17.66                        | 500         | PASS       |
|                | 5825                    | 17.76               | 17.61                        | 500         | PASS       |
| 802.11n HT40   | 5755                    | 36.41               | 36.51                        | 500         | PASS       |
|                | 5795                    | 36.37               | 36.36                        | 500         | PASS       |
| 802.11ac VHT20 | 5745                    | 17.70               | 17.71                        | 500         | PASS       |
|                | 5785                    | 17.72               | 17.62                        | 500         | PASS       |
|                | 5825                    | 17.76               | 17.68                        | 500         | PASS       |
| 802.11ac VHT40 | 5755                    | 36.44               | 36.38                        | 500         | PASS       |
|                | 5795                    | 36.39               | 36.35                        | 500         | PASS       |
| 802.11ac VHT80 | 5775                    | 76.04               | 76.35                        | 500         | PASS       |
| 802.11ax HE20  | 5745                    | 19.06               | 18.96                        | 500         | PASS       |
|                | 5785                    | 19.03               | 18.88                        | 500         | PASS       |
|                | 5825                    | 19.09               | 18.99                        | 500         | PASS       |
| 802.11ax HE40  | 5755                    | 37.95               | 38.12                        | 500         | PASS       |
|                | 5795                    | 37.96               | 38.26                        | 500         | PASS       |
| 802.11ax HE80  | 5775                    | 77.59               | 78.01                        | 500         | PASS       |


U-NII-1, 802.11a  
Carrier frequency (MHz): 5180



U-NII-1, 802.11n HT20  
Carrier frequency (MHz): 5180




U-NII-1, 802.11a  
Carrier frequency (MHz): 5200



U-NII-1, 802.11n HT20  
Carrier frequency (MHz): 5200



U-NII-1, 802.11a  
Carrier frequency (MHz): 5240




U-NII-1, 802.11n HT20  
Carrier frequency (MHz): 5240






U-NII-1, 802.11n HT40  
Carrier frequency (MHz): 5190



U-NII-1, 802.11n HT40  
Carrier frequency (MHz): 5230




U-NII-1, 802.11ac VHT20  
Carrier frequency (MHz): 5180




U-NII-1, 802.11ax HE20  
Carrier frequency (MHz): 5180




U-NII-1, 802.11ac VHT20  
Carrier frequency (MHz): 5200



U-NII-1, 802.11ax HE20  
Carrier frequency (MHz): 5200




### U-NII-1, 802.11ac VHT20 Carrier frequency (MHz):5240



### U-NII-1, 802.11ax HE20 Carrier frequency (MHz):5240




### U-NII-1, 802.11ac VHT40 Carrier frequency (MHz): 5190



### U-NII-1, 802.11ax HE40 Carrier frequency (MHz): 5190



### U-NII-1, 802.11ac VHT40 Carrier frequency (MHz): 5230



### U-NII-1, 802.11ax HE40 Carrier frequency (MHz): 5230





### U-NII-1, 802.11ac VHT80 Carrier frequency (MHz): 5210



### U-NII-1, 802.11ax HE80 Carrier frequency (MHz): 5210



### U-NII-1, 802.11ac VHT160 Carrier frequency (MHz): 5250



### U-NII-1, 802.11ax HE160 Carrier frequency (MHz): 5250








## 99% bandwidth


U-NII-3, 802.11a

Carrier frequency (MHz): 5745




U-NII-3, 802.11n HT20

Carrier frequency (MHz): 5745




U-NII-3, 802.11a

Carrier frequency (MHz): 5785




U-NII-3, 802.11n HT20

Carrier frequency (MHz): 5785




U-NII-3, 802.11a

Carrier frequency (MHz): 5825



U-NII-3, 802.11n HT20


Carrier frequency (MHz): 5825




U-NII-3, 802.11n HT40  
Carrier frequency (MHz): 5755



U-NII-3, 802.11n HT40  
Carrier frequency (MHz): 5795




U-NII-3, 802.11ac VHT20  
Carrier frequency (MHz): 5745



U-NII-3, 802.11ax HE20  
Carrier frequency (MHz): 5745



U-NII-3, 802.11ac VHT20  
Carrier frequency (MHz): 5785




U-NII-3, 802.11ax HE20  
Carrier frequency (MHz): 5785





### U-NII-3, 802.11ac VHT20 Carrier frequency (MHz): 5825



### U-NII-3, 802.11ax HE20 Carrier frequency (MHz): 5825




### U-NII-3, 802.11ac VHT40 Carrier frequency (MHz): 5755



### U-NII-3, 802.11ax HE40 Carrier frequency (MHz): 5755



### U-NII-3, 802.11ac VHT40 Carrier frequency (MHz): 5795



### U-NII-3, 802.11ax HE40 Carrier frequency (MHz): 5795





U-NII-3, 802.11ac VHT80  
Carrier frequency (MHz): 5775



U-NII-3, 802.11ax HE80  
Carrier frequency (MHz): 5775





## Minimum 6 dB bandwidth

U-NII-3, 802.11a

Carrier frequency (MHz): 5745




U-NII-3, 802.11n HT20

Carrier frequency (MHz): 5745



U-NII-3, 802.11a

Carrier frequency (MHz): 5785




U-NII-3, 802.11n HT20

Carrier frequency (MHz): 5785



U-NII-3, 802.11a

Carrier frequency (MHz): 5825



U-NII-3, 802.11n HT20

Carrier frequency (MHz): 5825





U-NII-3, 802.11n HT40  
Carrier frequency (MHz): 5755



U-NII-3, 802.11n HT40  
Carrier frequency (MHz): 5795



U-NII-3, 802.11ac VHT20  
Carrier frequency (MHz): 5745




U-NII-3, 802.11ax HE20  
Carrier frequency (MHz): 5745



U-NII-3, 802.11ac VHT20  
Carrier frequency (MHz): 5785



U-NII-3, 802.11ax HE20  
Carrier frequency (MHz): 5785



### U-NII-3, 802.11ac VHT20 Carrier frequency (MHz): 5825



### U-NII-3, 802.11ax HE20 Carrier frequency (MHz): 5825



### U-NII-3, 802.11ac VHT40 Carrier frequency (MHz): 5755



### U-NII-3, 802.11ax HE40 Carrier frequency (MHz): 5755



### U-NII-3, 802.11ac VHT40 Carrier frequency (MHz): 5795




### U-NII-3, 802.11ax HE40 Carrier frequency (MHz): 5795








U-NII-3, 802.11ac VHT80  
Carrier frequency (MHz): 5775



U-NII-3, 802.11ax HE80  
Carrier frequency (MHz): 5775



## 5.2. Average Power Output

### Ambient condition


| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

### Methods of Measurement

During the process of the testing, The EUT was connected to the average power meter through an external attenuator and a known loss cable. The EUT is max power transmission with proper modulation. We use Maximum average Conducted Output Power Level Method in KDB789033 for this test

The conducted Power is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically.

### Test Setup



### Limits

Rule FCC Part 15.407(a)(1) (3)

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23



dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.44$  dB.

**Test Results**

| Mode            | T <sub>on</sub> (ms) | T <sub>(on+off)</sub> (ms) | Duty cycle | Duty cycle correction Factor(dB) |
|-----------------|----------------------|----------------------------|------------|----------------------------------|
| 802.11a         | 1.97                 | 2.13                       | 0.93       | 0.32                             |
| 802.11n HT20    | 5.22                 | 5.76                       | 0.91       | 0.41                             |
| 802.11n HT40    | 5.20                 | 5.98                       | 0.87       | 0.60                             |
| 802.11ac VHT20  | 5.20                 | 5.82                       | 0.89       | 0.51                             |
| 802.11ac VHT40  | 5.20                 | 5.88                       | 0.88       | 0.56                             |
| 802.11ac VHT80  | 5.20                 | 5.92                       | 0.88       | 0.56                             |
| 802.11ac VHT160 | 5.44                 | 6.10                       | 0.89       | 0.51                             |
| 802.11ax HE20   | 5.24                 | 5.78                       | 0.91       | 0.41                             |
| 802.11ax HE40   | 5.22                 | 5.80                       | 0.90       | 0.46                             |
| 802.11ax HE80   | 5.24                 | 5.80                       | 0.90       | 0.46                             |
| 802.11ax HE160  | 5.44                 | 6.12                       | 0.89       | 0.51                             |

Note: when Duty cycle  $\geq 0.98$ , Duty cycle correction Factor not required.





| SISO Antenna 1 Power Index |         |         |          |          |         |         |          |          |         |          |          |         |          |          |
|----------------------------|---------|---------|----------|----------|---------|---------|----------|----------|---------|----------|----------|---------|----------|----------|
| Channel                    | 802.11a | 802.11n | 802.11ac | 802.11ax | Channel | 802.11n | 802.11ac | 802.11ax | Channel | 802.11ac | 802.11ax | Channel | 802.11ac | 802.11ax |
|                            |         | HT20    | VHT20    | HE20     |         | HT40    | VHT40    | HE40     |         | VHT80    | HE80     |         | VHT160   | HE160    |
| CH36                       | 12      | 13      | 13       | 12       | CH38    | 12      | 12       | 11       | CH42    | 12       | 11       | CH50    | 10       | 15       |
| CH40                       | 12      | 13      | 13       | 12       | CH46    | 12      | 12       | 11       | /       | /        | /        | /       | /        | /        |
| CH48                       | 12      | 13      | 13       | 12       | /       | /       | /        | /        | /       | /        | /        | /       | /        | /        |
| CH149                      | 21      | 21      | 21       | 21       | CH151   | 18      | 18       | 16       | CH155   | 16       | 16       | /       | /        | /        |
| CH157                      | 21      | 21      | 21       | 21       | CH159   | 18      | 18       | 16       | /       | /        | /        | /       | /        | /        |
| CH165                      | 21      | 21      | 21       | 21       | /       | /       | /        | /        | /       | /        | /        | /       | /        | /        |
| SISO Antenna 2 Power Index |         |         |          |          |         |         |          |          |         |          |          |         |          |          |
| Channel                    | 802.11a | 802.11n | 802.11ac | 802.11ax | Channel | 802.11n | 802.11ac | 802.11ax | Channel | 802.11ac | 802.11ax | Channel | 802.11ac | 802.11ax |
|                            |         | HT20    | VHT20    | HE20     |         | HT40    | VHT40    | HE40     |         | VHT80    | HE80     |         | VHT160   | HE160    |
| CH36                       | 12      | 13      | 13       | 12       | CH38    | 12      | 12       | 11       | CH42    | 12       | 11       | CH50    | 10       | 13       |
| CH40                       | 12      | 13      | 13       | 12       | CH46    | 12      | 12       | 11       | /       | /        | /        | /       | /        | /        |
| CH48                       | 12      | 13      | 13       | 12       | /       | /       | /        | /        | /       | /        | /        | /       | /        | /        |
| CH149                      | 21      | 21      | 21       | 21       | CH151   | 18      | 18       | 16       | CH155   | 16       | 16       | /       | /        | /        |
| CH157                      | 21      | 21      | 21       | 21       | CH159   | 18      | 18       | 16       | /       | /        | /        | /       | /        | /        |
| CH165                      | 21      | 21      | 21       | 21       | /       | /       | /        | /        | /       | /        | /        | /       | /        | /        |
| CDD Antenna Power Index    |         |         |          |          |         |         |          |          |         |          |          |         |          |          |
| Channel                    | 802.11a | 802.11n | 802.11ac | 802.11ax | Channel | 802.11n | 802.11ac | 802.11ax | Channel | 802.11ac | 802.11ax | Channel | 802.11ac | 802.11ax |
|                            |         | HT20    | VHT20    | HE20     |         | HT40    | VHT40    | HE40     |         | VHT80    | HE80     |         | VHT160   | HE160    |
| CH36                       | 12      | 13      | 13       | 12       | CH38    | 12      | 12       | 11       | CH42    | 12       | 11       | CH50    | 10       | 13       |
| CH40                       | 12      | 13      | 13       | 12       | CH46    | 12      | 12       | 11       | /       | /        | /        | /       | /        | /        |
| CH48                       | 12      | 13      | 13       | 12       | /       | /       | /        | /        | /       | /        | /        | /       | /        | /        |
| CH149                      | 21      | 21      | 21       | 21       | CH151   | 18      | 18       | 16       | CH155   | 16       | 16       | /       | /        | /        |
| CH157                      | 21      | 21      | 21       | 21       | CH159   | 18      | 18       | 16       | /       | /        | /        | /       | /        | /        |
| CH165                      | 21      | 21      | 21       | 21       | /       | /       | /        | /        | /       | /        | /        | /       | /        | /        |

**SISO Antenna 1****U-NII-1**

| Test Mode                                                                                   | Channel/<br>Frequency<br>(MHz) | Average<br>Power<br>Measured<br>(dBm) | Average<br>Power with<br>duty factor<br>(dBm) | Limit<br>(dBm) | Conclusion |
|---------------------------------------------------------------------------------------------|--------------------------------|---------------------------------------|-----------------------------------------------|----------------|------------|
| 802.11a                                                                                     | 36/5180                        | 12.03                                 | 12.35                                         | 30.00          | PASS       |
|                                                                                             | 40/5200                        | 12.23                                 | 12.55                                         | 30.00          | PASS       |
|                                                                                             | 48/5240                        | 12.17                                 | 12.49                                         | 30.00          | PASS       |
| 802.11n<br>HT20                                                                             | 36/5180                        | 13.25                                 | 13.66                                         | 30.00          | PASS       |
|                                                                                             | 40/5200                        | 13.11                                 | 13.52                                         | 30.00          | PASS       |
|                                                                                             | 48/5240                        | 13.16                                 | 13.57                                         | 30.00          | PASS       |
| 802.11n<br>HT40                                                                             | 38/5190                        | 12.15                                 | 12.75                                         | 30.00          | PASS       |
|                                                                                             | 46/5230                        | 12.18                                 | 12.78                                         | 30.00          | PASS       |
| 802.11ac<br>VHT20                                                                           | 36/5180                        | 13.22                                 | 13.73                                         | 30.00          | PASS       |
|                                                                                             | 40/5200                        | 13.18                                 | 13.69                                         | 30.00          | PASS       |
|                                                                                             | 48/5240                        | 13.27                                 | 13.78                                         | 30.00          | PASS       |
| 802.11ac<br>VHT40                                                                           | 38/5190                        | 12.08                                 | 12.64                                         | 30.00          | PASS       |
|                                                                                             | 46/5230                        | 12.09                                 | 12.65                                         | 30.00          | PASS       |
| 802.11ac VHT80                                                                              | 42/5210                        | 12.24                                 | 12.80                                         | 30.00          | PASS       |
| 802.11ac VHT160                                                                             | 50/5250                        | 10.21                                 | 10.72                                         | 30.00          | PASS       |
| 802.11ax<br>HE20                                                                            | 36/5180                        | 12.07                                 | 12.48                                         | 30.00          | PASS       |
|                                                                                             | 40/5200                        | 12.21                                 | 12.62                                         | 30.00          | PASS       |
|                                                                                             | 48/5240                        | 12.28                                 | 12.69                                         | 30.00          | PASS       |
| 802.11ax<br>HE40                                                                            | 38/5190                        | 11.27                                 | 11.73                                         | 30.00          | PASS       |
|                                                                                             | 46/5230                        | 11.09                                 | 11.55                                         | 30.00          | PASS       |
| 802.11ax HE80                                                                               | 42/5210                        | 11.22                                 | 11.68                                         | 30.00          | PASS       |
| 802.11ax HE160                                                                              | 50/5250                        | 14.89                                 | 15.40                                         | 30.00          | PASS       |
| Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor |                                |                                       |                                               |                |            |

### U-NII-3

| Test Mode                                                                                   | Channel/<br>Frequency<br>(MHz) | Average Power<br>Measured<br>(dBm) | Average<br>Power with<br>duty factor<br>(dBm) | Limit<br>(dBm) | Conclusion |
|---------------------------------------------------------------------------------------------|--------------------------------|------------------------------------|-----------------------------------------------|----------------|------------|
| 802.11a                                                                                     | 149/5745                       | 20.23                              | 20.55                                         | 30.00          | PASS       |
|                                                                                             | 157/5785                       | 20.15                              | 20.47                                         | 30.00          | PASS       |
|                                                                                             | 165/5825                       | 20.16                              | 20.48                                         | 30.00          | PASS       |
| 802.11n<br>HT20                                                                             | 149/5745                       | 20.31                              | 20.72                                         | 30.00          | PASS       |
|                                                                                             | 157/5785                       | 20.26                              | 20.67                                         | 30.00          | PASS       |
|                                                                                             | 165/5825                       | 20.51                              | 20.92                                         | 30.00          | PASS       |
| 802.11n<br>HT40                                                                             | 151/5755                       | 16.89                              | 17.49                                         | 30.00          | PASS       |
|                                                                                             | 159/5795                       | 16.81                              | 17.41                                         | 30.00          | PASS       |
| 802.11ac<br>VHT20                                                                           | 149/5745                       | 20.41                              | 20.92                                         | 30.00          | PASS       |
|                                                                                             | 157/5785                       | 20.17                              | 20.68                                         | 30.00          | PASS       |
|                                                                                             | 165/5825                       | 20.18                              | 20.69                                         | 30.00          | PASS       |
| 802.11ac<br>VHT40                                                                           | 151/5755                       | 16.86                              | 17.42                                         | 30.00          | PASS       |
|                                                                                             | 159/5795                       | 16.76                              | 17.32                                         | 30.00          | PASS       |
| 802.11ac VHT80                                                                              | 155/5775                       | 14.64                              | 15.20                                         | 30.00          | PASS       |
| 802.11ax<br>HE20                                                                            | 149/5745                       | 20.33                              | 20.74                                         | 30.00          | PASS       |
|                                                                                             | 157/5785                       | 20.51                              | 20.92                                         | 30.00          | PASS       |
|                                                                                             | 165/5825                       | 20.03                              | 20.44                                         | 30.00          | PASS       |
| 802.11ax<br>HE40                                                                            | 151/5755                       | 14.93                              | 15.39                                         | 30.00          | PASS       |
|                                                                                             | 159/5795                       | 15.09                              | 15.55                                         | 30.00          | PASS       |
| 802.11ax HE80                                                                               | 155/5775                       | 14.99                              | 15.45                                         | 30.00          | PASS       |
| Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor |                                |                                    |                                               |                |            |

**SISO Antenna 2****U-NII-1**

| Test Mode                                                                                   | Channel/<br>Frequency<br>(MHz) | Average<br>Power<br>Measured<br>(dBm) | Average<br>Power with<br>duty factor<br>(dBm) | Limit<br>(dBm) | Conclusion |
|---------------------------------------------------------------------------------------------|--------------------------------|---------------------------------------|-----------------------------------------------|----------------|------------|
| 802.11a                                                                                     | 36/5180                        | 12.64                                 | 12.96                                         | 30.00          | PASS       |
|                                                                                             | 40/5200                        | 12.64                                 | 12.96                                         | 30.00          | PASS       |
|                                                                                             | 48/5240                        | 11.81                                 | 12.13                                         | 30.00          | PASS       |
| 802.11n<br>HT20                                                                             | 36/5180                        | 13.34                                 | 13.75                                         | 30.00          | PASS       |
|                                                                                             | 40/5200                        | 13.52                                 | 13.93                                         | 30.00          | PASS       |
|                                                                                             | 48/5240                        | 13.09                                 | 13.50                                         | 30.00          | PASS       |
| 802.11n<br>HT40                                                                             | 38/5190                        | 12.60                                 | 13.20                                         | 30.00          | PASS       |
|                                                                                             | 46/5230                        | 11.79                                 | 12.39                                         | 30.00          | PASS       |
| 802.11ac<br>VHT20                                                                           | 36/5180                        | 13.40                                 | 13.91                                         | 30.00          | PASS       |
|                                                                                             | 40/5200                        | 13.43                                 | 13.94                                         | 30.00          | PASS       |
|                                                                                             | 48/5240                        | 13.03                                 | 13.54                                         | 30.00          | PASS       |
| 802.11ac<br>VHT40                                                                           | 38/5190                        | 12.52                                 | 13.08                                         | 30.00          | PASS       |
|                                                                                             | 46/5230                        | 11.77                                 | 12.33                                         | 30.00          | PASS       |
| 802.11ac VHT80                                                                              | 42/5210                        | 12.03                                 | 12.59                                         | 30.00          | PASS       |
| 802.11ac VHT160                                                                             | 50/5250                        | 10.03                                 | 10.54                                         | 30.00          | PASS       |
| 802.11ax<br>HE20                                                                            | 36/5180                        | 12.24                                 | 12.65                                         | 30.00          | PASS       |
|                                                                                             | 40/5200                        | 12.16                                 | 12.57                                         | 30.00          | PASS       |
|                                                                                             | 48/5240                        | 11.98                                 | 12.39                                         | 30.00          | PASS       |
| 802.11ax<br>HE40                                                                            | 38/5190                        | 11.16                                 | 11.62                                         | 30.00          | PASS       |
|                                                                                             | 46/5230                        | 11.41                                 | 11.87                                         | 30.00          | PASS       |
| 802.11ax HE80                                                                               | 42/5210                        | 11.21                                 | 11.67                                         | 30.00          | PASS       |
| 802.11ax HE160                                                                              | 50/5250                        | 13.74                                 | 14.25                                         | 30.00          | PASS       |
| Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor |                                |                                       |                                               |                |            |



## U-NII-3

| Test Mode                                                                                   | Channel/<br>Frequency<br>(MHz) | Average Power<br>Measured<br>(dBm) | Average<br>Power with<br>duty factor<br>(dBm) | Limit<br>(dBm) | Conclusion |
|---------------------------------------------------------------------------------------------|--------------------------------|------------------------------------|-----------------------------------------------|----------------|------------|
| 802.11a                                                                                     | 149/5745                       | 20.35                              | 20.67                                         | 30.00          | PASS       |
|                                                                                             | 157/5785                       | 20.12                              | 20.44                                         | 30.00          | PASS       |
|                                                                                             | 165/5825                       | 20.19                              | 20.51                                         | 30.00          | PASS       |
| 802.11n<br>HT20                                                                             | 149/5745                       | 20.35                              | 20.76                                         | 30.00          | PASS       |
|                                                                                             | 157/5785                       | 19.89                              | 20.30                                         | 30.00          | PASS       |
|                                                                                             | 165/5825                       | 21.20                              | 21.61                                         | 30.00          | PASS       |
| 802.11n<br>HT40                                                                             | 151/5755                       | 17.16                              | 17.76                                         | 30.00          | PASS       |
|                                                                                             | 159/5795                       | 17.83                              | 18.43                                         | 30.00          | PASS       |
| 802.11ac<br>VHT20                                                                           | 149/5745                       | 20.33                              | 20.84                                         | 30.00          | PASS       |
|                                                                                             | 157/5785                       | 20.12                              | 20.63                                         | 30.00          | PASS       |
|                                                                                             | 165/5825                       | 21.00                              | 21.51                                         | 30.00          | PASS       |
| 802.11ac<br>VHT40                                                                           | 151/5755                       | 17.15                              | 17.71                                         | 30.00          | PASS       |
|                                                                                             | 159/5795                       | 17.90                              | 18.46                                         | 30.00          | PASS       |
| 802.11ac VHT80                                                                              | 155/5775                       | 15.15                              | 15.71                                         | 30.00          | PASS       |
| 802.11ax<br>HE20                                                                            | 149/5745                       | 20.37                              | 20.78                                         | 30.00          | PASS       |
|                                                                                             | 157/5785                       | 20.04                              | 20.45                                         | 30.00          | PASS       |
|                                                                                             | 165/5825                       | 21.01                              | 21.42                                         | 30.00          | PASS       |
| 802.11ax<br>HE40                                                                            | 151/5755                       | 15.06                              | 15.52                                         | 30.00          | PASS       |
|                                                                                             | 159/5795                       | 15.86                              | 16.32                                         | 30.00          | PASS       |
| 802.11ax HE80                                                                               | 155/5775                       | 15.08                              | 15.54                                         | 30.00          | PASS       |
| Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor |                                |                                    |                                               |                |            |





## CDD

## U-NII-1

| Test Mode          | Channel/<br>Frequency<br>(MHz) | MIMO<br>Antenna 1                     |                                               | MIMO<br>Antenna 2                     |                                               | Total<br>Power<br>(dBm) | Limit<br>(dBm) | Conclusion |
|--------------------|--------------------------------|---------------------------------------|-----------------------------------------------|---------------------------------------|-----------------------------------------------|-------------------------|----------------|------------|
|                    |                                | Average<br>Power<br>Measured<br>(dBm) | Average<br>Power with<br>duty factor<br>(dBm) | Average<br>Power<br>Measured<br>(dBm) | Average<br>Power with<br>duty factor<br>(dBm) |                         |                |            |
| 802.11a            | 36/5180                        | 12.25                                 | 12.57                                         | 12.45                                 | 12.77                                         | 15.68                   | 29.80          | PASS       |
|                    | 44/5220                        | 12.25                                 | 12.57                                         | 12.55                                 | 12.87                                         | 15.73                   | 29.80          | PASS       |
|                    | 48/5240                        | 12.22                                 | 12.54                                         | 12.21                                 | 12.53                                         | 15.54                   | 29.80          | PASS       |
| 802.11n<br>HT20    | 36/5180                        | 13.12                                 | 13.53                                         | 13.44                                 | 13.85                                         | 16.70                   | 29.80          | PASS       |
|                    | 44/5220                        | 13.33                                 | 13.74                                         | 13.69                                 | 14.10                                         | 16.93                   | 29.80          | PASS       |
|                    | 48/5240                        | 12.93                                 | 13.34                                         | 12.79                                 | 13.20                                         | 16.28                   | 29.80          | PASS       |
| 802.11n<br>HT40    | 38/5190                        | 11.99                                 | 12.59                                         | 12.48                                 | 13.08                                         | 15.86                   | 29.80          | PASS       |
|                    | 46/5230                        | 12.14                                 | 12.74                                         | 12.18                                 | 12.78                                         | 15.78                   | 29.80          | PASS       |
| 802.11ac<br>VHT20  | 36/5180                        | 12.94                                 | 13.45                                         | 13.20                                 | 13.71                                         | 16.59                   | 29.80          | PASS       |
|                    | 44/5220                        | 12.72                                 | 13.23                                         | 13.46                                 | 13.97                                         | 16.62                   | 29.80          | PASS       |
|                    | 48/5240                        | 12.91                                 | 13.42                                         | 12.90                                 | 13.41                                         | 16.42                   | 29.80          | PASS       |
| 802.11ac<br>VHT40  | 38/5190                        | 11.30                                 | 11.86                                         | 12.34                                 | 12.90                                         | 15.42                   | 29.80          | PASS       |
|                    | 46/5230                        | 12.34                                 | 12.90                                         | 11.89                                 | 12.45                                         | 15.69                   | 29.80          | PASS       |
| 802.11ac<br>VHT80  | 42/5210                        | 12.25                                 | 12.81                                         | 11.71                                 | 12.27                                         | 15.55                   | 29.80          | PASS       |
| 802.11ac<br>VHT160 | 50/5250                        | 10.09                                 | 10.60                                         | 10.12                                 | 10.63                                         | 13.62                   | 29.80          | PASS       |
| 802.11ax<br>HE20   | 36/5180                        | 12.29                                 | 12.70                                         | 12.28                                 | 12.69                                         | 15.70                   | 29.80          | PASS       |
|                    | 44/5220                        | 12.14                                 | 12.55                                         | 12.34                                 | 12.75                                         | 15.66                   | 29.80          | PASS       |
|                    | 48/5240                        | 12.41                                 | 12.82                                         | 12.39                                 | 12.80                                         | 15.82                   | 29.80          | PASS       |
| 802.11ax<br>HE40   | 38/5190                        | 11.68                                 | 12.14                                         | 11.28                                 | 11.74                                         | 14.95                   | 29.80          | PASS       |
|                    | 46/5230                        | 11.17                                 | 11.63                                         | 10.98                                 | 11.44                                         | 14.54                   | 29.80          | PASS       |
| 802.11ax<br>HE80   | 42/5210                        | 11.23                                 | 11.69                                         | 10.85                                 | 11.31                                         | 14.51                   | 29.80          | PASS       |
| 802.11ax<br>HE160  | 50/5250                        | 13.37                                 | 13.88                                         | 13.68                                 | 14.19                                         | 17.04                   | 29.80          | PASS       |

Note: 1. For Total Power, according to KDB 662911 D01 Multiple Transmitter Output v02r01 1),

The Total Power =  $10\log(10^{(\text{Power antenna1 in dBm}/10)} + 10^{(\text{Power antenna2 in dBm}/10)})$ .

2. The manufacturer declared the transmitter output signals is CDD mode And Nss=1. According to KDB 662911 D01

Multiple Transmitter Output v02r01 F)2)f(ii): If antenna gains are not equal, the user may use either of the following methods to calculate directional gain, provided that each transmit antenna is driven by only one spatial stream: Directional gain may be calculated by using the formulas applicable to equal gain antennas with  $G_{\text{ANT}}$  set equal to the gain of the antenna having the highest gain.

Directional gain =  $G_{\text{ANT MAX}} + \text{Array Gain}$ , For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $N_{\text{ANT}} \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any  $N_{\text{ANT}}$ ;



Array Gain =  $5 \log(N_{\text{ANT}}/N_{\text{SS}})$  dB or 3 dB, whichever is less, for 20-MHz channel widths with  $N_{\text{ANT}} \geq 5$ .

So directional gain =  $G_{\text{ANT MAX}} + \text{Array Gain} = 6.2 + 0 = 6.2 \text{ dBi} > 6 \text{ dBi}$ . So the power limit is  $30 - (\text{directional gain} - 6 \text{ dBi}) = 29.80 \text{ dBm}$

**U-NII-3**

| Test Mode         | Channel/<br>Frequency<br>(MHz) | MIMO<br>Antenna 1                     |                                               | MIMO<br>Antenna 2                     |                                               | Total<br>Power<br>(dBm) | Limit<br>(dBm) | Conclusion |
|-------------------|--------------------------------|---------------------------------------|-----------------------------------------------|---------------------------------------|-----------------------------------------------|-------------------------|----------------|------------|
|                   |                                | Average<br>Power<br>Measured<br>(dBm) | Average<br>Power with<br>duty factor<br>(dBm) | Average<br>Power<br>Measured<br>(dBm) | Average<br>Power with<br>duty factor<br>(dBm) |                         |                |            |
| 802.11a           | 149/5745                       | 20.30                                 | 20.62                                         | 20.05                                 | 20.37                                         | 23.50                   | 29.80          | PASS       |
|                   | 157/5785                       | 20.05                                 | 20.37                                         | 20.27                                 | 20.59                                         | 23.49                   | 29.80          | PASS       |
|                   | 165/5825                       | 20.31                                 | 20.63                                         | 21.14                                 | 21.46                                         | 24.07                   | 29.80          | PASS       |
| 802.11n<br>HT20   | 149/5745                       | 20.15                                 | 20.56                                         | 19.64                                 | 20.05                                         | 23.32                   | 29.80          | PASS       |
|                   | 157/5785                       | 19.86                                 | 20.27                                         | 20.26                                 | 20.67                                         | 23.48                   | 29.80          | PASS       |
|                   | 165/5825                       | 20.08                                 | 20.49                                         | 20.71                                 | 21.12                                         | 23.83                   | 29.80          | PASS       |
| 802.11n<br>HT40   | 151/5755                       | 16.78                                 | 17.38                                         | 16.97                                 | 17.57                                         | 20.49                   | 29.80          | PASS       |
|                   | 159/5795                       | 17.30                                 | 17.90                                         | 17.87                                 | 18.47                                         | 21.21                   | 29.80          | PASS       |
| 802.11ac<br>VHT20 | 149/5745                       | 20.05                                 | 20.56                                         | 20.18                                 | 20.69                                         | 23.63                   | 29.80          | PASS       |
|                   | 157/5785                       | 19.89                                 | 20.40                                         | 20.24                                 | 20.75                                         | 23.58                   | 29.80          | PASS       |
|                   | 165/5825                       | 20.03                                 | 20.54                                         | 20.90                                 | 21.41                                         | 24.00                   | 29.80          | PASS       |
| 802.11ac<br>VHT40 | 151/5755                       | 16.77                                 | 17.33                                         | 16.92                                 | 17.48                                         | 20.41                   | 29.80          | PASS       |
|                   | 159/5795                       | 17.30                                 | 17.86                                         | 17.88                                 | 18.44                                         | 21.17                   | 29.80          | PASS       |
| 802.11ac<br>VHT80 | 155/5775                       | 15.11                                 | 15.67                                         | 15.04                                 | 15.60                                         | 18.64                   | 29.80          | PASS       |
| 802.11ax<br>HE20  | 149/5745                       | 20.35                                 | 20.81                                         | 20.09                                 | 20.50                                         | 23.67                   | 29.80          | PASS       |
|                   | 157/5785                       | 20.30                                 | 20.76                                         | 20.13                                 | 20.54                                         | 23.66                   | 29.80          | PASS       |
|                   | 165/5825                       | 20.38                                 | 20.84                                         | 21.12                                 | 21.53                                         | 24.21                   | 29.80          | PASS       |
| 802.11ax<br>HE40  | 151/5755                       | 15.71                                 | 16.22                                         | 14.93                                 | 15.39                                         | 18.83                   | 29.80          | PASS       |
|                   | 159/5795                       | 15.35                                 | 15.86                                         | 16.30                                 | 16.76                                         | 19.34                   | 29.80          | PASS       |
| 802.11ax<br>HE80  | 155/5775                       | 15.15                                 | 15.15                                         | 15.13                                 | 15.59                                         | 18.38                   | 29.80          | PASS       |

Note: 1. For Total Power, according to KDB 662911 D01 Multiple Transmitter Output v02r01 1),

The Total Power =  $10 \log(10^{(\text{Power antenna1 in dBm}/10)} + 10^{(\text{Power antenna2 in dBm}/10)})$ .

2. The manufacturer declared the transmitter output signals is CDD mode And Nss=1. According to KDB 662911 D01

Multiple Transmitter Output v02r01 F)2)f)(ii): If antenna gains are not equal, the user may use either of the following methods to calculate directional gain, provided that each transmit antenna is driven by only one spatial stream: Directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain.

Directional gain =  $G_{\text{ANT MAX}} + \text{Array Gain}$ ,

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $N_{\text{ANT}} \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any  $N_{\text{ANT}}$ ;

Array Gain =  $5 \log(N_{\text{ANT}}/N_{\text{SS}})$  dB or 3 dB, whichever is less, for 20-MHz channel widths with  $N_{\text{ANT}} \geq 5$ .

So directional gain =  $G_{\text{ANT MAX}} + \text{Array Gain} = 6.2 + 0 = 6.2 \text{ dBi} > 6 \text{ dBi}$ . So the power limit is  $30 - (\text{directional gain} - 6 \text{ dBi}) = 29.80 \text{ dBm}$

### 5.3. Frequency Stability

#### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

#### Method of Measurement

##### 1. Frequency stability with respect to ambient temperature

- a) Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.
- b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.
- c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).
- d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.
- e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.
- f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.
- g) Measure the frequency at each of frequencies specified in 5.6.
- h) Switch OFF the EUT but do not switch OFF the oscillator heater.
- i) Lower the chamber temperature by not more than 10°C, and allow the temperature inside the chamber to stabilize.
- j) Repeat step f) through step i) down to the lowest specified temperature.

##### 2. Frequency stability when varying supply voltage

Unless otherwise specified, these tests shall be made at ambient room temperature (+15°C to +25 °C). An antenna shall be connected to the antenna output terminals of the EUT if possible. If the EUT is equipped with or uses an adjustable-length antenna, then it shall be fully extended.

- a) Supply the EUT with nominal voltage or install a new or fully charged battery in the EUT. Turn ON the EUT and couple its output to a frequency counter or other frequency-measuring instrument.



- b) Tune the EUT to one of the number of frequencies required in 5.6. Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).
- c) Measure the frequency at each of the frequencies specified in 5.6.
- d) Repeat the above procedure at 85% and 115% of the nominal supply voltage.

**Limit**

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 936\text{Hz}$

**Test Results**

| Voltage<br>(V) | Temperature<br>(°C) | U-NII-1 Test Results |              |              |              |
|----------------|---------------------|----------------------|--------------|--------------|--------------|
|                |                     | 5200MHz              |              |              |              |
|                |                     | 1min                 | 2min         | 5min         | 10min        |
| 12             | -20                 | 5200.000561          | 5199.997089  | 5199.990886  | 5199.983726  |
| 12             | -10                 | 5200.000745          | 5199.992471  | 5199.984168  | 5199.982967  |
| 12             | 0                   | 5199.994382          | 5199.987670  | 5199.983341  | 5199.979216  |
| 12             | 10                  | 5199.984855          | 5199.983406  | 5199.981088  | 5199.969511  |
| 12             | 20                  | 5199.980290          | 5199.980579  | 5199.975074  | 5199.961816  |
| 12             | 30                  | 5199.977891          | 5199.974836  | 5199.973429  | 5199.952302  |
| 12             | 40                  | 5199.971097          | 5199.969448  | 5199.967965  | 5199.950300  |
| 12             | 50                  | 5199.967509          | 5199.967568  | 5199.958395  | 5199.942075  |
| 10.8           | 20                  | 5199.967049          | 5199.960293  | 5199.954071  | 5199.938869  |
| 13.2           | 20                  | 5199.962378          | 5199.953813  | 5199.948955  | 5199.928916  |
| Max. ΔMHz      |                     | -0.03762222          | -0.046187026 | -0.051044634 | -0.071083763 |
| PPM            |                     | -7.235042302         | -8.882120371 | -9.81627585  | -13.66995441 |

| Voltage<br>(V) | Temperature<br>(°C) | U-NII-3 Test Results |              |              |              |
|----------------|---------------------|----------------------|--------------|--------------|--------------|
|                |                     | 5785MHz              |              |              |              |
|                |                     | 1min                 | 2min         | 5min         | 10min        |
| 12             | -20                 | 5784.994727          | 5784.989973  | 5784.982857  | 5784.975560  |
| 12             | -10                 | 5784.985024          | 5784.980132  | 5784.977757  | 5784.967779  |
| 12             | 0                   | 5784.984673          | 5784.976494  | 5784.976692  | 5784.966952  |
| 12             | 10                  | 5784.978751          | 5784.972150  | 5784.971672  | 5784.958524  |
| 12             | 20                  | 5784.972611          | 5784.969904  | 5784.971160  | 5784.950854  |
| 12             | 30                  | 5784.966839          | 5784.962182  | 5784.965088  | 5784.945347  |
| 12             | 40                  | 5784.965840          | 5784.955716  | 5784.964667  | 5784.941578  |
| 12             | 50                  | 5784.965827          | 5784.946231  | 5784.956989  | 5784.935546  |
| 10.8           | 20                  | 5784.965617          | 5784.946166  | 5784.953743  | 5784.933280  |
| 13.2           | 20                  | 5784.964268          | 5784.941165  | 5784.944437  | 5784.924850  |
| Max. ΔMHz      |                     | -0.035731996         | -0.058834832 | -0.055563106 | -0.075149732 |
| PPM            |                     | -6.17666317          | -10.17023894 | -9.60468557  | -12.99044629 |



## 5.4. Power Spectral Density

### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

### Method of Measurement


The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable.

Set RBW = 1MHz, VBW =3MHz for the band 5.150-5.250GHz.

Set RBW = 470kHz, VBW =1.5MHz for the band 5.725-5.850GHz

The conducted PSD is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically.

### Test setup



### Limits

Rule FCC Part 15.407(a)(1)/ Part 15.407(a)(2) / Part 15.407(a)(3)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



| Frequency Bands/MHz | Limits       |
|---------------------|--------------|
| 5150-5250           | 17dBm/MHz    |
| 5725-5850           | 30dBm/500kHz |

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.75\text{dB}$ .

**Test Results:**

Note: Power Spectral Density =Read Value+Duty cycle correction factor

**SISO Antenna 1****U-NII-1**

| Mode            | Channel Number | Read Value (dBm /MHz) | Power Spectral Density (dBm /MHz) | Limit (dBm /MHz) | Conclusion |
|-----------------|----------------|-----------------------|-----------------------------------|------------------|------------|
| 802.11a         | 36             | -0.34                 | -0.02                             | 17               | PASS       |
|                 | 40             | -0.25                 | 0.07                              | 17               | PASS       |
|                 | 48             | -0.62                 | -0.30                             | 17               | PASS       |
| 802.11n HT20    | 36             | 0.65                  | 1.06                              | 17               | PASS       |
|                 | 40             | 0.27                  | 0.68                              | 17               | PASS       |
|                 | 48             | 0.04                  | 0.45                              | 17               | PASS       |
| 802.11n HT40    | 38             | -3.75                 | -3.15                             | 17               | PASS       |
|                 | 46             | -4.15                 | -3.55                             | 17               | PASS       |
| 802.11ac VHT20  | 36             | 0.96                  | 1.47                              | 17               | PASS       |
|                 | 40             | 0.98                  | 1.49                              | 17               | PASS       |
|                 | 48             | 1.01                  | 1.52                              | 17               | PASS       |
| 802.11ac VHT40  | 38             | -2.56                 | -2.00                             | 17               | PASS       |
|                 | 46             | -2.67                 | -2.11                             | 17               | PASS       |
| 802.11ac VHT80  | 42             | -7.37                 | -6.81                             | 17               | PASS       |
| 802.11ac VHT160 | 50             | -11.57                | -11.06                            | 17               | PASS       |
| 802.11ax HE20   | 36             | -0.37                 | 0.04                              | 17               | PASS       |
|                 | 40             | -0.77                 | -0.36                             | 17               | PASS       |
|                 | 48             | -0.94                 | -0.53                             | 17               | PASS       |
| 802.11ax HE40   | 38             | -4.46                 | -4.00                             | 17               | PASS       |
|                 | 46             | -3.01                 | -2.55                             | 17               | PASS       |
| 802.11ax HE80   | 42             | -7.49                 | -7.03                             | 17               | PASS       |
| 802.11ax HE160  | 50             | -5.77                 | -5.26                             | 17               | PASS       |



## U-NII-3

| Mode                                                               | Channel Number | Read Value (dBm/470kHz) | Power Spectral Density (dBm/500kHz) | Limit (dBm/500kHz) | Conclusion |
|--------------------------------------------------------------------|----------------|-------------------------|-------------------------------------|--------------------|------------|
| 802.11a                                                            | 149            | 6.10                    | 6.69                                | 30                 | PASS       |
|                                                                    | 157            | 5.91                    | 6.50                                | 30                 | PASS       |
|                                                                    | 165            | 6.34                    | 6.93                                | 30                 | PASS       |
| 802.11n HT20                                                       | 149            | 5.97                    | 6.65                                | 30                 | PASS       |
|                                                                    | 157            | 5.67                    | 6.35                                | 30                 | PASS       |
|                                                                    | 165            | 5.73                    | 6.41                                | 30                 | PASS       |
| 802.11n HT40                                                       | 151            | -0.41                   | 0.46                                | 30                 | PASS       |
|                                                                    | 159            | -0.29                   | 0.58                                | 30                 | PASS       |
| 802.11ac VHT20                                                     | 149            | 5.92                    | 6.70                                | 30                 | PASS       |
|                                                                    | 157            | 5.66                    | 6.44                                | 30                 | PASS       |
|                                                                    | 165            | 5.75                    | 6.53                                | 30                 | PASS       |
| 802.11ac VHT40                                                     | 151            | -0.24                   | 0.59                                | 30                 | PASS       |
|                                                                    | 159            | -0.22                   | 0.61                                | 30                 | PASS       |
| 802.11ac VHT80                                                     | 155            | -5.63                   | -4.80                               | 30                 | PASS       |
| 802.11ax HE20                                                      | 149            | 5.70                    | 6.38                                | 30                 | PASS       |
|                                                                    | 157            | 6.33                    | 7.01                                | 30                 | PASS       |
|                                                                    | 165            | 5.90                    | 6.58                                | 30                 | PASS       |
| 802.11ax HE40                                                      | 151            | -2.49                   | -1.76                               | 30                 | PASS       |
|                                                                    | 159            | -1.96                   | -1.23                               | 30                 | PASS       |
| 802.11ax HE80                                                      | 155            | -5.60                   | -4.87                               | 30                 | PASS       |
| Note: PSD=Read Value+ Duty cycle+10*log(500/470) correction factor |                |                         |                                     |                    |            |



## SISO Antenna 2

## U-NII-1

| Mode            | Channel Number | Read Value (dBm /MHz) | Power Spectral Density (dBm /MHz) | Limit (dBm /MHz) | Conclusion |
|-----------------|----------------|-----------------------|-----------------------------------|------------------|------------|
| 802.11a         | 36             | 2.19                  | 2.51                              | 17               | PASS       |
|                 | 40             | 2.19                  | 2.51                              | 17               | PASS       |
|                 | 48             | 1.49                  | 1.81                              | 17               | PASS       |
| 802.11n HT20    | 36             | 2.94                  | 3.35                              | 17               | PASS       |
|                 | 40             | 2.64                  | 3.05                              | 17               | PASS       |
|                 | 48             | 2.23                  | 2.64                              | 17               | PASS       |
| 802.11n HT40    | 38             | -1.16                 | -0.56                             | 17               | PASS       |
|                 | 46             | -1.95                 | -1.35                             | 17               | PASS       |
| 802.11ac VHT20  | 36             | 2.84                  | 3.35                              | 17               | PASS       |
|                 | 40             | 2.84                  | 3.35                              | 17               | PASS       |
|                 | 48             | 2.27                  | 2.78                              | 17               | PASS       |
| 802.11ac VHT40  | 38             | -1.09                 | -0.53                             | 17               | PASS       |
|                 | 46             | -2.07                 | -1.51                             | 17               | PASS       |
| 802.11ac VHT80  | 42             | -4.65                 | -4.09                             | 17               | PASS       |
| 802.11ac VHT160 | 50             | -10.33                | -9.82                             | 17               | PASS       |
| 802.11ax HE20   | 36             | 1.10                  | 1.51                              | 17               | PASS       |
|                 | 40             | 1.25                  | 1.66                              | 17               | PASS       |
|                 | 48             | 0.36                  | 0.77                              | 17               | PASS       |
| 802.11ax HE40   | 38             | -2.96                 | -2.50                             | 17               | PASS       |
|                 | 46             | -4.02                 | -3.56                             | 17               | PASS       |
| 802.11ax HE80   | 42             | -5.67                 | -5.21                             | 17               | PASS       |
| 802.11ax HE160  | 50             | -5.43                 | -4.92                             | 17               | PASS       |



## U-NII-3

| Mode           | Channel Number | Read Value (dBm/470kHz) | Power Spectral Density (dBm/500kHz) | Limit (dBm/500kHz) | Conclusion |
|----------------|----------------|-------------------------|-------------------------------------|--------------------|------------|
| 802.11a        | 149            | 6.31                    | 6.90                                | 30                 | PASS       |
|                | 157            | 6.11                    | 6.70                                | 30                 | PASS       |
|                | 165            | 6.50                    | 7.09                                | 30                 | PASS       |
| 802.11n HT20   | 149            | 6.44                    | 7.12                                | 30                 | PASS       |
|                | 157            | 6.04                    | 6.72                                | 30                 | PASS       |
|                | 165            | 7.19                    | 7.87                                | 30                 | PASS       |
| 802.11n HT40   | 151            | 0.04                    | 0.91                                | 30                 | PASS       |
|                | 159            | 0.53                    | 1.40                                | 30                 | PASS       |
| 802.11ac VHT20 | 149            | 6.19                    | 6.97                                | 30                 | PASS       |
|                | 157            | 5.93                    | 6.71                                | 30                 | PASS       |
|                | 165            | 7.06                    | 7.84                                | 30                 | PASS       |
| 802.11ac VHT40 | 151            | -0.20                   | 0.63                                | 30                 | PASS       |
|                | 159            | 0.11                    | 0.94                                | 30                 | PASS       |
| 802.11ac VHT80 | 155            | -5.46                   | -4.63                               | 30                 | PASS       |
| 802.11ax HE20  | 149            | 5.88                    | 6.56                                | 30                 | PASS       |
|                | 157            | 5.69                    | 6.37                                | 30                 | PASS       |
|                | 165            | 6.67                    | 7.35                                | 30                 | PASS       |
| 802.11ax HE40  | 151            | -2.68                   | -1.95                               | 30                 | PASS       |
|                | 159            | -1.24                   | -0.51                               | 30                 | PASS       |
| 802.11ax HE80  | 155            | -5.43                   | -4.70                               | 30                 | PASS       |

Note: PSD=Read Value+ Duty cycle+10\*log(500/470) correction factor





## CDD

## U-NII-1

| Mode               | Channel/<br>Frequency<br>(MHz) | Power Spectral Density     |                  |                            |                  |                                 | Limit<br>(dBm<br>/MHz) | Conclusion |
|--------------------|--------------------------------|----------------------------|------------------|----------------------------|------------------|---------------------------------|------------------------|------------|
|                    |                                | Antenna 1                  |                  | Antenna 2                  |                  | Total<br>Power<br>(dBm<br>/MHz) |                        |            |
|                    |                                | Read<br>Value<br>(dBm/MHz) | PSD<br>(dBm/MHz) | Read<br>Value<br>(dBm/MHz) | PSD<br>(dBm/MHz) |                                 |                        |            |
| 802.11a            | 36/5180                        | 2.01                       | 2.33             | 1.87                       | 2.19             | 5.27                            | 13.79                  | PASS       |
|                    | 40/5200                        | 2.23                       | 2.55             | 1.96                       | 2.28             | 5.42                            | 13.79                  | PASS       |
|                    | 48/5240                        | 1.95                       | 2.27             | 1.54                       | 1.86             | 5.08                            | 13.79                  | PASS       |
| 802.11n<br>HT20    | 36/5180                        | 2.29                       | 2.70             | 2.15                       | 2.56             | 5.64                            | 13.79                  | PASS       |
|                    | 40/5200                        | 2.04                       | 2.45             | 2.41                       | 2.82             | 5.65                            | 13.79                  | PASS       |
|                    | 48/5240                        | 2.09                       | 2.50             | 2.27                       | 2.68             | 5.60                            | 13.79                  | PASS       |
| 802.11n<br>HT40    | 38/5190                        | -1.40                      | -0.80            | -1.76                      | -1.16            | 2.04                            | 13.79                  | PASS       |
|                    | 46/5230                        | -1.65                      | -1.05            | -2.13                      | -1.53            | 1.73                            | 13.79                  | PASS       |
| 802.11ac<br>VHT20  | 36/5180                        | 2.38                       | 2.89             | 2.61                       | 3.12             | 6.01                            | 13.79                  | PASS       |
|                    | 40/5200                        | 2.13                       | 2.64             | 2.71                       | 3.22             | 5.95                            | 13.79                  | PASS       |
|                    | 48/5240                        | 1.84                       | 2.35             | 2.29                       | 2.80             | 5.59                            | 13.79                  | PASS       |
| 802.11ac<br>VHT40  | 38/5190                        | -1.72                      | -1.16            | -1.87                      | 6.00             | 6.76                            | 13.79                  | PASS       |
|                    | 46/5230                        | -1.72                      | -1.16            | -1.93                      | -1.37            | 1.74                            | 13.79                  | PASS       |
| 802.11ac<br>VHT80  | 42/5210                        | -4.67                      | -4.11            | -5.51                      | -4.95            | -1.50                           | 13.79                  | PASS       |
| 802.11ac<br>VHT160 | 50/5250                        | -9.68                      | -9.17            | -10.24                     | -9.73            | -6.43                           | 13.79                  | PASS       |
| 802.11ax<br>HE20   | 36/5180                        | 1.29                       | 1.70             | 1.33                       | 1.74             | 4.73                            | 13.79                  | PASS       |
|                    | 40/5200                        | 1.26                       | 1.67             | 1.33                       | 1.74             | 4.72                            | 13.79                  | PASS       |
|                    | 48/5240                        | 1.12                       | 1.53             | 0.96                       | 1.37             | 4.46                            | 13.79                  | PASS       |
| 802.11ax<br>HE40   | 38/5190                        | -2.78                      | -2.32            | -2.59                      | -2.13            | 0.78                            | 13.79                  | PASS       |
|                    | 46/5230                        | -2.76                      | -2.30            | -2.94                      | -2.48            | 0.62                            | 13.79                  | PASS       |
| 802.11ax<br>HE80   | 42/5210                        | -5.68                      | -5.22            | -6.13                      | -5.67            | -2.43                           | 13.79                  | PASS       |
| 802.11ax<br>HE160  | 50/5250                        | -6.40                      | -5.89            | -6.69                      | -6.18            | -3.03                           | 13.79                  | PASS       |

Note: 1. Power Spectral Density = Read Value + Duty cycle correction factor

2. For Total PSD, according to KDB 662911 D01 Multiple Transmitter Output v02r01 2)a), the power spectral density =  $10\log(10^{(\text{PSD antenna1 in dBm/10})} + 10^{(\text{PSD antenna2 in dBm/10})})$

3. The manufacturer declared the transmitter output signals is CDD mode And Nss=1. According to KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)f)(ii): If antenna gains are not equal, the user may use either of the following methods to calculate directional gain, provided that each transmit antenna is driven by only one spatial stream: Directional gain may be calculated by using the formulas applicable to equal gain antennas with  $G_{\text{ANT}}$  set equal to the gain of the antenna having the highest gain.

Directional gain =  $G_{\text{ANT MAX}} + \text{Array Gain}$ , For PSD measurements on all devices,

Array Gain =  $10\log(\text{Nant}/\text{Nss})\text{dB}$ ,

so directional gain =  $G_{\text{ANT MAX}} + \text{Array Gain} = 6.2 + 10\log(2/1) = 9.21 > 6\text{ dBi}$ .



So the PSD limit is  $17 - (\text{directional gain} - 6 \text{ dBi}) = 17 - (9.21 - 6) = 13.79 \text{ dBm}$ .

## U-NII-3

| Mode                  | Channel<br>/Frequency<br>(MHz) | Power Spectral Density     |                      |                            |                      |                        | Limit<br>(dBm<br>/MHz) | Conclusion |
|-----------------------|--------------------------------|----------------------------|----------------------|----------------------------|----------------------|------------------------|------------------------|------------|
|                       |                                | ANT1                       |                      | ANT2                       |                      | Total PSD<br>(dBm/MHz) |                        |            |
|                       |                                | Read Value<br>(dBm/470kHz) | PSD<br>(dBm/5000kHz) | Read Value<br>(dBm/470kHz) | PSD<br>(dBm/5000kHz) |                        |                        |            |
| 802.11a               | 149/5745                       | 6.45                       | 7.04                 | 6.48                       | 7.07                 | 10.06                  | 26.79                  | PASS       |
|                       | 157/5785                       | 6.46                       | 7.05                 | 6.65                       | 7.24                 | 10.15                  | 26.79                  | PASS       |
|                       | 165/5825                       | 6.50                       | 7.09                 | 7.32                       | 7.91                 | 10.52                  | 26.79                  | PASS       |
| 802.11n<br>HT20       | 149/5745                       | 5.63                       | 6.31                 | 5.56                       | 6.24                 | 9.29                   | 26.79                  | PASS       |
|                       | 157/5785                       | 5.78                       | 6.46                 | 5.72                       | 6.40                 | 9.44                   | 26.79                  | PASS       |
|                       | 165/5825                       | 5.83                       | 6.51                 | 6.75                       | 7.43                 | 10.00                  | 26.79                  | PASS       |
| 802.11n<br>HT40       | 151/5755                       | -0.24                      | 0.63                 | -0.41                      | 0.46                 | 3.56                   | 26.79                  | PASS       |
|                       | 159/5795                       | -0.15                      | 0.72                 | 0.59                       | 1.46                 | 4.12                   | 26.79                  | PASS       |
| 802.11<br>ac<br>VHT20 | 149/5745                       | 5.57                       | 6.35                 | 5.82                       | 6.60                 | 9.48                   | 26.79                  | PASS       |
|                       | 157/5785                       | 5.74                       | 6.52                 | 5.76                       | 6.54                 | 9.54                   | 26.79                  | PASS       |
|                       | 165/5825                       | 5.81                       | 6.59                 | 6.72                       | 7.50                 | 10.08                  | 26.79                  | PASS       |
| 802.11<br>ac<br>VHT40 | 151/5755                       | -0.02                      | 0.81                 | -0.41                      | 0.42                 | 3.62                   | 26.79                  | PASS       |
|                       | 159/5795                       | -0.08                      | 0.75                 | 0.63                       | 1.46                 | 4.12                   | 26.79                  | PASS       |
| 802.11ac<br>VHT80     | 155/5775                       | -5.29                      | -4.46                | -5.77                      | -4.94                | -1.69                  | 26.79                  | PASS       |
| 802.11<br>ax<br>HE20  | 149/5745                       | 5.88                       | 6.56                 | 5.79                       | 6.47                 | 9.53                   | 26.79                  | PASS       |
|                       | 157/5785                       | 6.40                       | 7.08                 | 5.85                       | 6.53                 | 9.82                   | 26.79                  | PASS       |
|                       | 165/5825                       | 6.08                       | 6.76                 | 6.75                       | 7.43                 | 10.12                  | 26.79                  | PASS       |
| 802.11<br>ax<br>HE40  | 151/5755                       | -1.91                      | -1.18                | -2.55                      | -1.82                | 1.52                   | 26.79                  | PASS       |
|                       | 159/5795                       | -2.01                      | -1.28                | -1.47                      | -0.74                | 2.01                   | 26.79                  | PASS       |
| 802.11ax<br>HE80      | 155/5775                       | -5.41                      | -4.68                | -5.38                      | -4.65                | -1.66                  | 26.79                  | PASS       |

Note: 1. For Total PSD, according to KDB 662911 D01 Multiple Transmitter Output v02r01 2)a), the power spectral density  $= 10 \log(10^{(\text{PSD antenna1 in dBm}/10)} + 10^{(\text{PSD antenna2 in dBm}/10)})$

2. The manufacturer declared the transmitter output signals is CDD mode And Nss=1. According to KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)f(ii): If antenna gains are not equal, the user may use either of the following methods to calculate directional gain, provided that each transmit antenna is driven by only one spatial stream: Directional gain may be calculated by using the formulas applicable to equal gain antennas with  $G_{\text{ANT}}$  set equal to the gain of the antenna having the highest gain.

Directional gain =  $G_{\text{ANT MAX}} + \text{Array Gain}$ , For PSD measurements on all devices,

Array Gain =  $10 \log(N_{\text{ant}}/N_{\text{ss}}) \text{ dB}$ ,


so directional gain =  $G_{\text{ANT MAX}} + \text{Array Gain} = 6.2 + 10 \log(2/1) = 9.21 > 6 \text{ dBi}$ .

So the PSD limit is  $30 - (\text{directional gain} - 6 \text{ dBi}) = 30 - (9.21 - 6) = 26.79 \text{ dBm}$ .



## SISO Antenna 1

U-NII-1, 802.11a, Channel No.: 36




U-NII-1, 802.11n HT20, Channel No.: 36




U-NII-1, 802.11a, Channel No.: 40




U-NII-1, 802.11n HT20, Channel No.: 40




U-NII-1, 802.11a, Channel No.: 48




U-NII-1, 802.11n HT20, Channel No.: 48



U-NII-1, 802.11n HT40, Channel No.: 38



U-NII-1, 802.11n HT40, Channel No.: 46




U-NII-1, 802.11ac VHT20, Channel No.: 36



U-NII-1, 802.11ax HE20, Channel No.: 36



U-NII-1, 802.11ac VHT20, Channel No.: 40




U-NII-1, 802.11ax HE20, Channel No.: 40






U-NII-1, 802.11ac VHT20, Channel No.: 48




U-NII-1, 802.11ax HE20, Channel No.: 48




U-NII-1, 802.11ac VHT40, Channel No.: 38



U-NII-1, 802.11ax HE40, Channel No.: 38




U-NII-1, 802.11ac VHT40, Channel No.: 46




U-NII-1, 802.11ax HE40, Channel No.: 46




U-NII-1, 802.11ac VHT80, Channel No.: 42



U-NII-1, 802.11ax HE80, Channel No.: 42



U-NII-1, 802.11ac VHT160, Channel No.: 50




U-NII-1, 802.11ax HE160, Channel No.: 50






U-NII-3, 802.11a, Channel No.: 149



U-NII-3, 802.11n HT20, Channel No.: 149



U-NII-3, 802.11a, Channel No.: 157




U-NII-3, 802.11n HT20, Channel No.: 157



U-NII-3, 802.11a, Channel No.: 165




U-NII-3, 802.11n HT20, Channel No.: 165



U-NII-3, 802.11n HT40, Channel No.: 151




U-NII-3, 802.11n HT40, Channel No.: 159



U-NII-3, 802.11ac VHT20, Channel No.: 149




U-NII-3, 802.11ax HE20, Channel No.: 149




U-NII-3, 802.11ac VHT20, Channel No.: 157




U-NII-3, 802.11ax HE20, Channel No.: 157



U-NII-3, 802.11ac VHT20, Channel No.: 165



U-NII-3, 802.11ax HE20, Channel No.: 165




U-NII-3, 802.11ac VHT40, Channel No.: 151




U-NII-3, 802.11ax HE40, Channel No.: 151



U-NII-3, 802.11ac VHT40, Channel No.: 159




U-NII-3, 802.11ax HE40, Channel No.: 159








U-NII-3, 802.11ac VHT80, Channel No.: 155




U-NII-3, 802.11ax HE80, Channel No.: 155






## SISO Antenna 2


U-NII-1, 802.11a, Channel No.: 36



U-NII-1, 802.11n HT20, Channel No.: 36




U-NII-1, 802.11a, Channel No.: 40



U-NII-1, 802.11n HT20, Channel No.: 40




U-NII-1, 802.11a, Channel No.: 48




U-NII-1, 802.11n HT20, Channel No.: 48




U-NII-1, 802.11n HT40, Channel No.: 38



U-NII-1, 802.11n HT40, Channel No.: 46




U-NII-1, 802.11ac VHT20, Channel No.: 36




U-NII-1, 802.11ax HE20, Channel No.: 36



U-NII-1, 802.11ac VHT20, Channel No.: 40




U-NII-1, 802.11ax HE20, Channel No.: 40







U-NII-1, 802.11ac VHT20, Channel No.: 48




U-NII-1, 802.11ax HE20, Channel No.: 48




U-NII-1, 802.11ac VHT40, Channel No.: 38




U-NII-1, 802.11ax HE40, Channel No.: 38



U-NII-1, 802.11ac VHT40, Channel No.: 46




U-NII-1, 802.11ax HE40, Channel No.: 46






U-NII-1, 802.11ac VHT80, Channel No.: 42



U-NII-1, 802.11ax HE80, Channel No.: 42



U-NII-1, 802.11ac VHT160, Channel No.: 50



U-NII-1, 802.11ax HE160, Channel No.: 50



U-NII-3, 802.11a, Channel No.: 149



U-NII-3, 802.11n HT20, Channel No.: 149



U-NII-3, 802.11a, Channel No.: 157



U-NII-3, 802.11n HT20, Channel No.: 157



U-NII-3, 802.11a, Channel No.: 165



U-NII-3, 802.11n HT20, Channel No.: 165







U-NII-3, 802.11n HT40, Channel No.: 151



U-NII-3, 802.11n HT40, Channel No.: 159




U-NII-3, 802.11ac VHT20, Channel No.: 149



U-NII-3, 802.11ax HE20, Channel No.: 149



U-NII-3, 802.11ac VHT20, Channel No.: 157



U-NII-3, 802.11ax HE20, Channel No.: 157




U-NII-3, 802.11ac VHT20, Channel No.: 165




U-NII-3, 802.11ax HE20, Channel No.: 165



U-NII-3, 802.11ac VHT40, Channel No.: 151




U-NII-3, 802.11ax HE40, Channel No.: 151



U-NII-3, 802.11ac VHT40, Channel No.: 159




U-NII-3, 802.11ax HE40, Channel No.: 159








U-NII-3, 802.11ac VHT80, Channel No.: 155



U-NII-3, 802.11ax HE80, Channel No.: 155





## CDD Antenna 1


U-NII-1, 802.11a, Channel No.: 36



U-NII-1, 802.11n HT20, Channel No.: 36




U-NII-1, 802.11a, Channel No.: 40




U-NII-1, 802.11n HT20, Channel No.: 40




U-NII-1, 802.11a, Channel No.: 48




U-NII-1, 802.11n HT20, Channel No.: 48




U-NII-1, 802.11n HT40, Channel No.: 38



U-NII-1, 802.11n HT40, Channel No.: 46



U-NII-1, 802.11ac VHT20, Channel No.: 36



U-NII-1, 802.11ax HE20, Channel No.: 36



U-NII-1, 802.11ac VHT20, Channel No.: 40



U-NII-1, 802.11ax HE20, Channel No.: 40







U-NII-1, 802.11ac VHT20, Channel No.: 48




U-NII-1, 802.11ax HE20, Channel No.: 48




U-NII-1, 802.11ac VHT40, Channel No.: 38



U-NII-1, 802.11ax HE40, Channel No.: 38



U-NII-1, 802.11ac VHT40, Channel No.: 46




U-NII-1, 802.11ax HE40, Channel No.: 46






U-NII-1, 802.11ac VHT80, Channel No.: 42




U-NII-1, 802.11ax HE80, Channel No.: 42



U-NII-1, 802.11ac VHT160, Channel No.: 50



U-NII-1, 802.11ax HE160, Channel No.: 50







U-NII-3, 802.11a, Channel No.: 149



U-NII-3, 802.11n HT20, Channel No.: 149




U-NII-3, 802.11a, Channel No.: 157




U-NII-3, 802.11n HT20, Channel No.: 157




U-NII-3, 802.11a, Channel No.: 165



U-NII-3, 802.11n HT20, Channel No.: 165



U-NII-3, 802.11n HT40, Channel No.: 151



U-NII-3, 802.11n HT40, Channel No.: 159




U-NII-3, 802.11ac VHT20, Channel No.: 149




U-NII-3, 802.11ax HE20, Channel No.: 149



U-NII-3, 802.11ac VHT20, Channel No.: 157




U-NII-3, 802.11ax HE20, Channel No.: 157




U-NII-3, 802.11ac VHT20, Channel No.: 165




U-NII-3, 802.11ax HE20, Channel No.: 165




U-NII-3, 802.11ac VHT40, Channel No.: 151




U-NII-3, 802.11ax HE40, Channel No.: 151



U-NII-3, 802.11ac VHT40, Channel No.: 159




U-NII-3, 802.11ax HE40, Channel No.: 159








U-NII-3, 802.11ac VHT80, Channel No.: 155



U-NII-3, 802.11ax HE80, Channel No.: 155






## CDD Antenna 2


U-NII-1, 802.11a, Channel No.: 36




U-NII-1, 802.11n HT20, Channel No.: 36




U-NII-1, 802.11a, Channel No.: 40



U-NII-1, 802.11n HT20, Channel No.: 40



U-NII-1, 802.11a, Channel No.: 48




U-NII-1, 802.11n HT20, Channel No.: 48






U-NII-1, 802.11n HT40, Channel No.: 38




U-NII-1, 802.11n HT40, Channel No.: 46



U-NII-1, 802.11ac VHT20, Channel No.: 36



U-NII-1, 802.11ax HE20, Channel No.: 36



U-NII-1, 802.11ac VHT20, Channel No.: 40




U-NII-1, 802.11ax HE20, Channel No.: 40




U-NII-1, 802.11ac VHT20, Channel No.: 48




U-NII-1, 802.11ax HE20, Channel No.: 48



U-NII-1, 802.11ac VHT40, Channel No.: 38




U-NII-1, 802.11ax HE40, Channel No.: 38



U-NII-1, 802.11ac VHT40, Channel No.: 46




U-NII-1, 802.11ax HE40, Channel No.: 46







U-NII-1, 802.11ac VHT80, Channel No.: 42



U-NII-1, 802.11ax HE80, Channel No.: 42



U-NII-1, 802.11ac VHT160, Channel No.: 50




U-NII-1, 802.11ax HE160, Channel No.: 50







U-NII-3, 802.11a, Channel No.: 149




U-NII-3, 802.11n HT20, Channel No.: 149




U-NII-3, 802.11a, Channel No.: 157




U-NII-3, 802.11n HT20, Channel No.: 157



U-NII-3, 802.11a, Channel No.: 165




U-NII-3, 802.11n HT20, Channel No.: 165







U-NII-3, 802.11n HT40, Channel No.: 151



U-NII-3, 802.11n HT40, Channel No.: 159



U-NII-3, 802.11ac VHT20, Channel No.: 149



U-NII-3, 802.11ax HE20, Channel No.: 149



U-NII-3, 802.11ac VHT20, Channel No.: 157



U-NII-3, 802.11ax HE20, Channel No.: 157






U-NII-3, 802.11ac VHT20, Channel No.: 165




U-NII-3, 802.11ax HE20, Channel No.: 165




U-NII-3, 802.11ac VHT40, Channel No.: 151




U-NII-3, 802.11ax HE40, Channel No.: 151



U-NII-3, 802.11ac VHT40, Channel No.: 159




U-NII-3, 802.11ax HE40, Channel No.: 159






U-NII-3, 802.11ac VHT80, Channel No.: 155



U-NII-3, 802.11ax HE80, Channel No.: 155



## 5.5. Unwanted Emission

### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

### Method of Measurement

The test set-up was made in accordance to the general provisions of ANSI C63.10. The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna. The radiated emissions measurements were made in a typical installation configuration.

Sweep the whole frequency band range from 9kHz to the 10th harmonic of the carrier, and the emissions less than 20 dB below the permissible value are reported.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turntable shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing.

Set the spectrum analyzer in the following:

9kHz~150 kHz

RBW=200Hz, VBW=1kHz/ Sweep=AUTO

150 kHz~30MHz

RBW=9KHz, VBW=30KHz,/ Sweep=AUTO

Below 1GHz

RBW=100kHz / VBW=300kHz / Sweep=AUTO

a) Peak emission levels are measured by setting the instrument as follows:

Above 1GHz

PEAK: RBW=1MHz VBW=3MHz/ Sweep=AUTO

b) Average emission levels are measured by setting the instrument as follows:

Above 1GHz

AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO

c) Detector: The measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)

e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific





emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is  $[10 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.

2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.


3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Reduce the video bandwidth until no significant variations in the displayed signal are observed in subsequent traces, provided the video bandwidth is no less than 1 Hz. For regulatory requirements that specify averaging only over the transmit duration (e.g., digital transmission system [DTS] and Unlicensed National Information Infrastructure [U-NII]), the video bandwidth shall be greater than  $[1 / (\text{minimum transmitter on time})]$  and no less than 1 Hz.


The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the loop antenna is vertical, others antenna are vertical and horizontal.

The test is in transmitting mode.


### 9KHz~~~30MHz



### 30MHz~~~ 1GHz



### Above 1GHz



Note: Area side:2.4mX3.6m

**Limits**

- (1) For transmitters operating in the 5725-5850 MHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz(68.2dBμV/m).
- (3) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz(68.2dBμV/m).
- (4) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz(68.2dBμV/m).

Note: the following formula is used to convert the EIRP to field strength

§1、 $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{meters}]) + 104.77$ , where E = field strength and

d = distance at which field strength limit is specified in the rules;

§2、 $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$ , for d = 3 meters

- (5) Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table.

| Frequency of emission (MHz) | Field strength(uV/m) | Field strength(dBuV/m) |
|-----------------------------|----------------------|------------------------|
| 0.009–0.490                 | 2400/F(kHz)          | /                      |
| 0.490–1.705                 | 24000/F(kHz)         | /                      |
| 1.705–30.0                  | 30                   | /                      |
| 30-88                       | 100                  | 40                     |
| 88-216                      | 150                  | 43.5                   |
| 216-960                     | 200                  | 46                     |
| Above960                    | 500                  | 54                     |

| MHz                        | MHz                   | MHz             | GHz              |
|----------------------------|-----------------------|-----------------|------------------|
| 0.090 - 0.110              | 16.42 - 16.423        | 399.9 - 410     | 4.5 - 5.15       |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525   | 608 - 614       | 5.35 - 5.46      |
| 2.1735 - 2.1905            | 16.80425 - 16.80475   | 960 - 1240      | 7.25 - 7.75      |
| 4.125 - 4.128              | 25.5 - 25.67          | 1300 - 1427     | 8.025 - 8.5      |
| 4.17725 - 4.17775          | 37.5 - 38.25          | 1435 - 1626.5   | 9.0 - 9.2        |
| 4.20725 - 4.20775          | 73 - 74.6             | 1645.5 - 1646.5 | 9.3 - 9.5        |
| 6.215 - 6.218              | 74.8 - 75.2           | 1660 - 1710     | 10.6 - 12.7      |
| 6.26775 - 6.26825          | 108 - 121.94          | 1718.8 - 1722.2 | 13.25 - 13.4     |
| 6.31175 - 6.31225          | 123 - 138             | 2200 - 2300     | 14.47 - 14.5     |
| 8.291 - 8.294              | 149.9 - 150.05        | 2310 - 2390     | 15.35 - 16.2     |
| 8.362 - 8.366              | 156.52475 - 156.52525 | 2483.5 - 2500   | 17.7 - 21.4      |
| 8.37625 - 8.38675          | 156.7 - 156.9         | 2690 - 2900     | 22.01 - 23.12    |
| 8.41425 - 8.41475          | 162.0125 - 167.17     | 3260 - 3267     | 23.6 - 24.0      |
| 12.29 - 12.293             | 167.72 - 173.2        | 3332 - 3339     | 31.2 - 31.8      |
| 12.51975 - 12.52025        | 240 - 285             | 3345.8 - 3358   | 36.43 - 36.5     |
| 12.57675 - 12.57725        | 322 - 335.4           | 3600 - 4400     | ( <sup>2</sup> ) |
| 13.36 - 13.41              |                       |                 |                  |

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .

| Frequency     | Uncertainty |
|---------------|-------------|
| 9KHz-30MHz    | 3.55 dB     |
| 30MHz-200MHz  | 4.17 dB     |
| 200MHz-1GHz   | 4.84 dB     |
| 1-18GHz       | 4.35 dB     |
| 18-26.5GHz    | 5.90 dB     |
| 26.5GHz~40GHz | 5.92 dB     |














**Test Results:**

The modulation and bandwidth are similar for 802.11n mode for 20MHz/40MHz and 802.11ac mode for V20MHz/V40MHz, therefore investigated worst case to representative mode in test report.



A font (dB $\mu$ V/m) in the test plot =(dB  $\mu$  V/m)

The signal beyond the limit is carrier.


**U-NII-1****802.11a-Channel 36: Peak & Average****802.11a-Channel 48: Peak & Average****802.11n HT20 -Channel 36: Peak & Average****802.11n HT20 -Channel 48: Peak & Average****802.11n HT40-Channel 38: Peak & Average****802.11n HT40-Channel 46: Peak & Average****802.11ac VHT80-Channel 42: Peak & Average****802.11ac VHT160-Channel 50: Peak & Average****802.11ax HE20 -Channel 36: Peak & Average****802.11ax HE20 -Channel 48: Peak & Average**




802.11ax HE40-Channel 38: Peak &amp; Average




802.11ax HE40-Channel 46: Peak &amp; Average



802.11ax HE80-Channel 42: Peak &amp; Average




802.11ax HE160-Channel 50: Peak &amp; Average






## U-NII-3


802.11a-Channel 149: Peak




802.11a-Channel 165: Peak &amp; Average




802.11n HT20-Channel 149: Peak




802.11n HT20-Channel 165: Peak




802.11n HT40-Channel 151: Peak




802.11n HT40-Channel 159: Peak




802.11ac VHT80- Channel 155: Peak




### 802.11ax HE20-Channel 149: Peak




### 802.11ax HE20-Channel 165: Peak




### 802.11ax HE40-Channel 151: Peak



### 802.11ax HE40-Channel 159: Peak



### 802.11ax HE80- Channel 155: Peak





## Result of RE

### Test result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the Emissions in the frequency band 9kHz-30MHz are more than 20dB below the limit are not reported.

**After the pretest, CDD was selected as the worst antenna.**


A font (Level in dB $\mu$ V/m) in the test plot =(level in dB  $\mu$  V/m)

A font (Level in dB $\mu$ V) in the test plot =(level in dB  $\mu$  V/m)

A font (Level in dB V) in the test plot =(level in dB  $\mu$  V/m)

During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes with all channels, 802.11n (HT40) CH46 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

### Continuous TX mode:



Radiates Emission from 30MHz to 1GHz


| Frequency (MHz) | Quasi-Peak (dB $\mu$ V/m) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) | Margin (dB) | Limit (dB $\mu$ V/m) |
|-----------------|---------------------------|-------------|--------------|---------------|---------------------|-------------|----------------------|
| 50.43           | 29.20                     | 100.0       | V            | 22.00         | 21                  | 10.80       | 40.00                |
| 61.59           | 24.96                     | 100.0       | V            | 7.00          | 19                  | 15.04       | 40.00                |
| 144.73          | 19.24                     | 225.0       | H            | 243.00        | 15                  | 20.76       | 40.00                |
| 220.45          | 19.19                     | 125.0       | H            | 30.00         | 18                  | 20.81       | 40.00                |
| 526.95          | 16.07                     | 175.0       | H            | 188.00        | 25                  | 30.93       | 47.00                |
| 755.91          | 18.98                     | 184.0       | V            | 7.00          | 29                  | 28.02       | 47.00                |

**Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)**

**2. Margin = Limit – Quasi-Peak**




## 802.11a CH36



Note: The signal beyond the limit is carrier.  
Radiates Emission from 1GHz to 8GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 1263.67         | 45.26         | ---              | 68.20          | 22.94       | 100.0       | V            | 86.00         | -8                  |
| 1350.47         | ---           | 36.12            | 54.00          | 17.88       | 200.0       | H            | 217.00        | -7                  |
| 1414.63         | ---           | 36.09            | 54.00          | 17.91       | 200.0       | V            | 108.00        | -7                  |
| 1967.17         | 46.59         | ---              | 68.20          | 21.61       | 200.0       | V            | 122.00        | -5                  |
| 2652.00         | 49.14         | ---              | 68.20          | 19.06       | 200.0       | V            | 149.00        | -4                  |
| 2809.03         | ---           | 40.03            | 54.00          | 13.97       | 100.0       | V            | 0.00          | -3                  |
| 3542.87         | 50.31         | ---              | 68.20          | 17.89       | 100.0       | V            | 201.00        | -3                  |
| 3959.13         | ---           | 41.55            | 54.00          | 12.45       | 100.0       | V            | 349.00        | -1                  |
| 4800.07         | ---           | 51.91            | 54.00          | 2.09        | 100.0       | V            | 160.00        | 1                   |
| 5148.67         | 66.47         | ---              | 74.00          | 7.53        | 100.0       | V            | 160.00        | 2                   |
| 7305.13         | ---           | 47.80            | 54.00          | 6.20        | 100.0       | V            | 114.00        | 7                   |
| 7849.03         | 57.90         | ---              | 68.20          | 10.30       | 100.0       | V            | 228.00        | 7                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




Radiates Emission from 8GHz to 18GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 8287.67         | ---           | 41.11            | 54.00          | 12.89       | 200.0       | V            | 199.00        | -3                  |
| 8995.67         | 49.21         | ---              | 68.20          | 18.99       | 200.0       | H            | 0.00          | -2                  |
| 9180.33         | ---           | 39.35            | 54.00          | 14.65       | 200.0       | H            | 276.00        | -2                  |
| 10359.67        | 56.00         | ---              | 68.20          | 12.20       | 100.0       | V            | 163.00        | 0                   |
| 10571.33        | 51.24         | ---              | 68.20          | 16.96       | 200.0       | H            | 14.00         | 0                   |
| 10894.67        | ---           | 42.61            | 54.00          | 11.39       | 100.0       | V            | 94.00         | 0                   |
| 11997.67        | ---           | 41.46            | 54.00          | 12.54       | 100.0       | V            | 6.00          | 1                   |
| 13393.67        | ---           | 43.60            | 54.00          | 10.40       | 100.0       | V            | 121.00        | 3                   |
| 13735.00        | 53.41         | ---              | 68.20          | 14.79       | 100.0       | H            | 254.00        | 4                   |
| 15349.67        | 55.02         | ---              | 68.20          | 13.18       | 200.0       | H            | 0.00          | 4                   |
| 15352.00        | ---           | 45.23            | 54.00          | 8.77        | 200.0       | V            | 128.00        | 4                   |
| 17685.33        | 59.02         | ---              | 68.20          | 9.18        | 100.0       | V            | 4.00          | 7                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

## 802.11a CH40




Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 1002.10         | ---           | 36.41            | 54.00          | 17.59       | 200.0       | V            | 190.00        | -10                 |
| 1299.37         | 45.07         | ---              | 68.20          | 23.13       | 100.0       | V            | 166.00        | -8                  |
| 1503.53         | ---           | 36.33            | 54.00          | 17.67       | 100.0       | H            | 351.00        | -7                  |
| 1809.20         | 46.51         | ---              | 68.20          | 21.69       | 100.0       | H            | 312.00        | -6                  |
| 2687.70         | 48.34         | ---              | 68.20          | 19.86       | 200.0       | H            | 125.00        | -4                  |
| 2813.23         | ---           | 39.43            | 54.00          | 14.57       | 200.0       | V            | 0.00          | -3                  |
| 3053.80         | 50.23         | ---              | 68.20          | 17.97       | 200.0       | H            | 0.00          | -3                  |
| 3968.70         | ---           | 41.36            | 54.00          | 12.64       | 200.0       | V            | 190.00        | -1                  |
| 4476.67         | 51.65         | ---              | 68.20          | 16.55       | 200.0       | H            | 21.00         | 0                   |
| 4800.07         | ---           | 52.91            | 54.00          | 1.09        | 100.0       | V            | 206.00        | 1                   |
| 7524.23         | ---           | 47.73            | 54.00          | 6.27        | 200.0       | V            | 358.00        | 7                   |
| 7980.87         | 57.55         | ---              | 68.20          | 10.65       | 100.0       | V            | 140.00        | 8                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




Radiates Emission from 8GHz to 18GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 8320.00         | ---           | 41.89            | 54.00          | 12.11       | 100.0       | V            | 42.00         | -3                  |
| 8954.33         | 48.84         | ---              | 68.20          | 19.36       | 200.0       | H            | 66.00         | -2                  |
| 9194.67         | ---           | 39.18            | 54.00          | 14.82       | 200.0       | H            | 276.00        | -2                  |
| 10400.00        | 55.66         | ---              | 68.20          | 12.54       | 100.0       | V            | 164.00        | -1                  |
| 10528.00        | 50.55         | ---              | 68.20          | 17.65       | 100.0       | V            | 248.00        | 0                   |
| 10947.67        | ---           | 42.91            | 54.00          | 11.09       | 100.0       | H            | 211.00        | 0                   |
| 12084.00        | ---           | 40.75            | 54.00          | 13.25       | 100.0       | H            | 238.00        | 1                   |
| 13369.67        | ---           | 43.54            | 54.00          | 10.46       | 100.0       | H            | 298.00        | 3                   |
| 13731.00        | 53.47         | ---              | 68.20          | 14.73       | 200.0       | H            | 263.00        | 4                   |
| 14791.33        | 55.02         | ---              | 68.20          | 13.18       | 200.0       | H            | 0.00          | 5                   |
| 15375.67        | ---           | 44.88            | 54.00          | 9.12        | 200.0       | H            | 108.00        | 4                   |
| 17644.67        | 58.34         | ---              | 68.20          | 9.86        | 100.0       | V            | 42.00         | 7                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)



## 802.11a CH48




Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 1033.60         | 53.84         | ---              | 74.00          | 20.16       | 100.0       | V            | 0.00          | -10                 |
| 1036.40         | ---           | 44.39            | 54.00          | 9.61        | 200.0       | V            | 12.00         | -10                 |
| 1588.47         | ---           | 37.51            | 54.00          | 16.49       | 200.0       | V            | 260.00        | -6                  |
| 1940.80         | 48.28         | ---              | 68.20          | 19.92       | 100.0       | V            | 135.00        | -5                  |
| 2623.07         | 50.29         | ---              | 68.20          | 17.91       | 100.0       | V            | 249.00        | -4                  |
| 2810.20         | ---           | 40.82            | 54.00          | 13.18       | 200.0       | V            | 356.00        | -3                  |
| 3492.23         | 51.97         | ---              | 68.20          | 16.23       | 100.0       | H            | 0.00          | -3                  |
| 3988.53         | ---           | 43.56            | 54.00          | 10.44       | 100.0       | V            | 54.00         | -1                  |
| 4800.07         | ---           | 53.25            | 54.00          | 0.75        | 100.0       | V            | 135.00        | 1                   |
| 5550.47         | 58.44         | ---              | 68.20          | 9.76        | 100.0       | V            | 4.00          | 3                   |
| 6973.33         | 63.59         | ---              | 68.20          | 4.61        | 200.0       | V            | 231.00        | 7                   |
| 7705.77         | ---           | 51.47            | 54.00          | 2.53        | 100.0       | V            | 264.00        | 7                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




Radiates Emission from 8GHz to 18GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 8384.00         | ---           | 43.48            | 54.00          | 10.52       | 100.0       | V            | 49.00         | -3                  |
| 8519.33         | 49.25         | ---              | 68.20          | 18.95       | 200.0       | V            | 0.00          | -2                  |
| 9163.67         | ---           | 39.42            | 54.00          | 14.58       | 200.0       | V            | 155.00        | -2                  |
| 10480.33        | 55.54         | ---              | 68.20          | 12.66       | 100.0       | V            | 316.00        | 0                   |
| 10487.67        | 51.83         | ---              | 68.20          | 16.37       | 100.0       | V            | 8.00          | 0                   |
| 10956.67        | ---           | 42.71            | 54.00          | 11.29       | 200.0       | H            | 3.00          | 0                   |
| 11969.00        | ---           | 40.85            | 54.00          | 13.15       | 100.0       | H            | 0.00          | 1                   |
| 13387.00        | ---           | 43.91            | 54.00          | 10.09       | 100.0       | H            | 26.00         | 3                   |
| 13727.00        | 53.57         | ---              | 68.20          | 14.63       | 100.0       | H            | 0.00          | 4                   |
| 15203.67        | 55.91         | ---              | 68.20          | 12.29       | 200.0       | V            | 358.00        | 4                   |
| 15410.67        | ---           | 45.41            | 54.00          | 8.59        | 100.0       | H            | 0.00          | 4                   |
| 17648.00        | 57.84         | ---              | 68.20          | 10.36       | 200.0       | V            | 168.00        | 7                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

## 802.11a CH149




Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 1241.97         | 42.52         | ---              | 68.20          | 25.68       | 200.0       | V            | 359.00        | 6                   |
| 1388.03         | ---           | 33.49            | 54.00          | 20.51       | 200.0       | H            | 352.00        | 7                   |
| 1539.23         | ---           | 37.56            | 54.00          | 16.44       | 200.0       | V            | 259.00        | 7                   |
| 1941.73         | 44.93         | ---              | 68.20          | 23.27       | 200.0       | V            | 177.00        | 9                   |
| 2669.27         | 47.64         | ---              | 68.20          | 20.56       | 100.0       | H            | 22.00         | 11                  |
| 2778.70         | ---           | 38.56            | 54.00          | 15.44       | 200.0       | H            | 300.00        | 11                  |
| 3526.77         | 50.37         | ---              | 68.20          | 17.83       | 100.0       | H            | 236.00        | 12                  |
| 3971.73         | ---           | 40.78            | 54.00          | 13.22       | 100.0       | V            | 234.00        | 13                  |
| 4432.80         | 51.39         | ---              | 68.20          | 16.81       | 200.0       | H            | 218.00        | 14                  |
| 4800.07         | ---           | 47.06            | 54.00          | 6.94        | 100.0       | V            | 165.00        | 14                  |
| 7625.73         | ---           | 48.66            | 54.00          | 5.34        | 100.0       | H            | 358.00        | 22                  |
| 7761.53         | 58.44         | ---              | 68.20          | 9.76        | 200.0       | H            | 355.00        | 22                  |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




Radiates Emission from 8GHz to 18GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 8617.67         | 50.56         | ---              | 68.20          | 17.64       | 100.0       | V            | 10.00         | -3                  |
| 9071.33         | ---           | 39.74            | 54.00          | 14.26       | 100.0       | H            | 237.00        | -2                  |
| 9158.00         | ---           | 39.78            | 54.00          | 14.22       | 100.0       | V            | 350.00        | -2                  |
| 10366.33        | 51.20         | ---              | 68.20          | 17.00       | 200.0       | H            | 1.00          | 0                   |
| 10522.00        | 50.81         | ---              | 68.20          | 17.39       | 100.0       | H            | 182.00        | 0                   |
| 11490.33        | ---           | 46.45            | 54.00          | 7.55        | 100.0       | V            | 1.00          | 1                   |
| 12509.33        | ---           | 42.20            | 54.00          | 11.80       | 200.0       | V            | 335.00        | 2                   |
| 13387.00        | ---           | 42.89            | 54.00          | 11.11       | 100.0       | H            | 141.00        | 3                   |
| 13731.00        | 53.58         | ---              | 68.20          | 14.62       | 200.0       | H            | 1.00          | 4                   |
| 14982.67        | 55.47         | ---              | 68.20          | 12.73       | 100.0       | V            | 6.00          | 5                   |
| 15367.33        | ---           | 44.81            | 54.00          | 9.19        | 200.0       | V            | 355.00        | 4                   |
| 17689.67        | 58.18         | ---              | 68.20          | 10.02       | 100.0       | V            | 189.00        | 7                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

## 802.11a CH157




Note: The signal beyond the limit is carrier.  
Radiates Emission from 1GHz to 8GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 1099.17         | ---           | 31.75            | 54.00          | 22.25       | 200.0       | H            | 82.00         | 5                   |
| 1292.37         | 43.51         | ---              | 68.20          | 24.69       | 200.0       | H            | 218.00        | 6                   |
| 1402.03         | ---           | 33.89            | 54.00          | 20.11       | 100.0       | H            | 98.00         | 7                   |
| 1580.07         | ---           | 37.97            | 54.00          | 16.03       | 200.0       | V            | 208.00        | 8                   |
| 1992.37         | 44.56         | ---              | 68.20          | 23.64       | 200.0       | H            | 300.00        | 9                   |
| 2639.63         | 47.87         | ---              | 68.20          | 20.33       | 200.0       | V            | 0.00          | 11                  |
| 2757.00         | ---           | 38.53            | 54.00          | 15.47       | 200.0       | H            | 359.00        | 11                  |
| 3435.07         | 49.50         | ---              | 68.20          | 18.70       | 200.0       | H            | 346.00        | 12                  |
| 3989.23         | ---           | 41.04            | 54.00          | 12.96       | 100.0       | V            | 357.00        | 13                  |
| 4799.83         | ---           | 47.54            | 54.00          | 6.46        | 100.0       | V            | 164.00        | 14                  |
| 5591.30         | 58.17         | ---              | 68.20          | 10.03       | 200.0       | V            | 335.00        | 16                  |
| 7886.83         | 58.83         | ---              | 68.20          | 9.37        | 200.0       | H            | 352.00        | 22                  |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)






Radiates Emission from 8GHz to 18GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 8333.67         | ---           | 37.01            | 54.00          | 16.99       | 200.0       | H            | 189.00        | -3                  |
| 8677.33         | 51.73         | ---              | 68.20          | 16.47       | 100.0       | V            | 10.00         | -3                  |
| 9070.33         | ---           | 40.04            | 54.00          | 13.96       | 100.0       | V            | 175.00        | -2                  |
| 9192.67         | ---           | 39.26            | 54.00          | 14.74       | 200.0       | V            | 351.00        | -2                  |
| 10325.33        | 51.70         | ---              | 68.20          | 16.50       | 100.0       | H            | 2.00          | 0                   |
| 11569.00        | 57.48         | ---              | 74.00          | 16.52       | 100.0       | V            | 10.00         | 1                   |
| 11569.33        | ---           | 48.53            | 54.00          | 5.47        | 100.0       | V            | 6.00          | 1                   |
| 13397.67        | ---           | 43.05            | 54.00          | 10.95       | 200.0       | V            | 141.00        | 3                   |
| 13581.00        | 53.50         | ---              | 68.20          | 14.70       | 100.0       | V            | 318.00        | 3                   |
| 14689.00        | 55.23         | ---              | 68.20          | 12.97       | 200.0       | H            | 38.00         | 5                   |
| 15371.00        | ---           | 44.87            | 54.00          | 9.13        | 200.0       | H            | 65.00         | 4                   |
| 17674.67        | 58.39         | ---              | 68.20          | 9.81        | 200.0       | V            | 84.00         | 7                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

## 802.11a CH165




N

ote: The signal beyond the limit is carrier.  
Radiates Emission from 1GHz to 8GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 1274.40         | 45.41         | ---              | 68.20          | 22.79       | 200.0       | V            | 2.00          | -8                  |
| 1357.47         | ---           | 36.78            | 54.00          | 17.22       | 200.0       | V            | 2.00          | -7                  |
| 1618.33         | ---           | 39.87            | 54.00          | 14.13       | 200.0       | V            | 0.00          | -6                  |
| 1893.43         | 47.68         | ---              | 68.20          | 20.52       | 200.0       | V            | 111.00        | -5                  |
| 2624.93         | 49.66         | ---              | 68.20          | 18.54       | 200.0       | V            | 20.00         | -4                  |
| 2821.40         | ---           | 40.51            | 54.00          | 13.49       | 200.0       | V            | 193.00        | -3                  |
| 3562.93         | 51.62         | ---              | 68.20          | 16.58       | 200.0       | V            | 1.00          | -3                  |
| 3969.87         | ---           | 43.35            | 54.00          | 10.65       | 200.0       | V            | 137.00        | -1                  |
| 4800.07         | ---           | 51.63            | 54.00          | 2.37        | 100.0       | V            | 128.00        | 1                   |
| 5629.33         | 60.45         | ---              | 68.20          | 7.75        | 200.0       | V            | 193.00        | 3                   |
| 6919.20         | 60.56         | ---              | 68.20          | 7.64        | 200.0       | V            | 12.00         | 7                   |
| 7743.80         | ---           | 51.27            | 54.00          | 2.73        | 200.0       | V            | 193.00        | 7                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)




Radiates Emission from 8GHz to 18GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 8266.67         | ---           | 36.90            | 54.00          | 17.10       | 200.0       | V            | 187.00        | -3                  |
| 8737.33         | 49.53         | ---              | 68.20          | 18.67       | 100.0       | V            | 9.00          | -3                  |
| 9135.00         | ---           | 40.29            | 54.00          | 13.71       | 100.0       | H            | 270.00        | -2                  |
| 9169.67         | ---           | 39.30            | 54.00          | 14.70       | 200.0       | V            | 346.00        | -2                  |
| 10402.00        | 51.55         | ---              | 68.20          | 16.65       | 200.0       | V            | 337.00        | -1                  |
| 11649.33        | 58.15         | ---              | 74.00          | 15.85       | 100.0       | V            | 5.00          | 1                   |
| 11654.00        | ---           | 50.23            | 54.00          | 3.77        | 100.0       | V            | 9.00          | 1                   |
| 13346.67        | ---           | 43.58            | 54.00          | 10.42       | 200.0       | V            | 1.00          | 3                   |
| 13702.67        | 53.02         | ---              | 68.20          | 15.18       | 100.0       | H            | 73.00         | 4                   |
| 14655.00        | 55.21         | ---              | 68.20          | 12.99       | 200.0       | V            | 358.00        | 5                   |
| 15376.67        | ---           | 44.91            | 54.00          | 9.09        | 100.0       | H            | 215.00        | 4                   |
| 17682.00        | 58.44         | ---              | 68.20          | 9.76        | 200.0       | H            | 306.00        | 7                   |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

# 802.11n (HT20) CH36



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz

| Frequency (MHz) | Peak (dBuV/m) | Average (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Polarization | Azimuth (deg) | Correct Factor (dB) |
|-----------------|---------------|------------------|----------------|-------------|-------------|--------------|---------------|---------------------|
| 1293.77         | 43.46         | ---              | 68.20          | 24.74       | 200.0       | V            | 180.00        | 6                   |
| 1354.43         | ---           | 33.50            | 54.00          | 20.50       | 100.0       | H            | 40.00         | 7                   |
| 1487.67         | ---           | 33.65            | 54.00          | 20.35       | 100.0       | H            | 54.00         | 7                   |
| 1987.00         | 44.85         | ---              | 68.20          | 23.35       | 200.0       | H            | 205.00        | 9                   |
| 2666.47         | 48.02         | ---              | 68.20          | 20.18       | 100.0       | V            | 151.00        | 11                  |
| 2724.80         | ---           | 38.70            | 54.00          | 15.30       | 100.0       | H            | 180.00        | 11                  |
| 3562.23         | 49.56         | ---              | 68.20          | 18.64       | 100.0       | V            | 338.00        | 12                  |
| 3958.43         | ---           | 40.83            | 54.00          | 13.17       | 100.0       | H            | 134.00        | 13                  |
| 4800.07         | ---           | 52.71            | 54.00          | 1.29        | 100.0       | V            | 192.00        | 14                  |
| 6005.23         | 51.97         | ---              | 68.20          | 16.23       | 100.0       | H            | 291.00        | 18                  |
| 7739.83         | ---           | 48.89            | 54.00          | 5.11        | 200.0       | H            | 351.00        | 22                  |
| 7785.10         | 58.72         | ---              | 68.20          | 9.48        | 100.0       | H            | 95.00         | 22                  |

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)