

FCC TEST REPORT

REPORT NO.: RF931102L03

MODEL NO.: WAP54GPE

RECEIVED: Nov. 08 2004

TESTED: Nov. 08 ~ Feb. 25, 2005

ISSUED: Mar. 04, 2005

APPLICANT: Cisco-Linksys LLC

ADDRESS: 121 Theory Drive Irvine, CA 92617, U.S.A.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.

This test report consists of 71 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



No. 2177-01



0528
ILAC MRA

Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS.....	5
2.1	MEASUREMENT UNCERTAINTY	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST.....	7
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	8
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	10
3.4	DESCRIPTION OF SUPPORT UNITS	10
4	TEST TYPES AND RESULTS.....	11
4.1	CONDUCTED EMISSION MEASUREMENT	11
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	11
4.1.2	TEST INSTRUMENTS.....	11
4.1.3	TEST PROCEDURES	12
4.1.4	DEVIATION FROM TEST STANDARD.....	12
4.1.5	TEST SETUP	13
4.1.6	EUT OPERATING CONDITIONS	13
4.1.7	TEST RESULTS	14
4.2	RADIATED EMISSION MEASUREMENT	20
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	20
4.2.2	TEST INSTRUMENTS.....	21
4.2.3	TEST PROCEDURES	22
4.2.4	DEVIATION FROM TEST STANDARD	22
4.2.5	TEST SETUP	23
4.2.6	EUT OPERATING CONDITIONS	23
4.2.7	TEST RESULTS	24
4.3	6dB BANDWIDTH MEASUREMENT	38
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	38
4.3.2	TEST INSTRUMENTS.....	38
4.3.3	TEST PROCEDURE.....	39
4.3.4	DEVIATION FROM TEST STANDARD	39
4.3.5	TEST SETUP	39
4.3.6	EUT OPERATING CONDITIONS	39
4.3.7	TEST RESULTS	40
4.4	MAXIMUM PEAK OUTPUT POWER	46
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	46
4.4.2	TEST INSTRUMENTS.....	46
4.4.3	TEST PROCEDURES	47
4.4.4	DEVIATION FROM TEST STANDARD	47
4.4.5	TEST SETUP	47
4.4.6	EUT OPERATING CONDITIONS	47
4.4.7	TEST RESULTS	48
4.5	POWER SPECTRAL DENSITY MEASUREMENT	49

4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	49
4.5.2	TEST INSTRUMENTS.....	49
4.5.3	TEST PROCEDURE.....	50
4.5.4	DEVIATION FROM TEST STANDARD	50
4.5.5	TEST SETUP	50
4.5.6	EUT OPERATING CONDITIONS	50
4.5.7	TEST RESULTS	51
4.6	BAND EDGES MEASUREMENT	57
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	57
4.6.2	TEST INSTRUMENTS.....	57
4.6.3	TEST PROCEDURE.....	57
4.6.4	DEVIATION FROM TEST STANDARD.....	57
4.6.5	EUT OPERATING CONDITION.....	57
4.6.6	TEST RESULTS	58
4.7	ANTENNA REQUIREMENT	67
4.7.1	STANDARD APPLICABLE	67
4.7.2	ANTENNA CONNECTED CONSTRUCTION	67
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	68
6	INFORMATION ON THE TESTING LABORATORIES	71

1 CERTIFICATION

PRODUCT: Wireless-G Exterior Access Point with Power Over Ethernet
BRAND NAME : Linksys
MODEL NO. : WAP54GPE
APPLICANT : Cisco-Linksys LLC
TESTED : Nov. 08 ~ Feb. 25, 2005
TEST SAMPLE : ENGINEERING SAMPLE
STANDARDS : FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Andrea Hsia , **DATE:** Mar. 04, 2005
(Andrea Hsia)

TECHNICAL
ACCEPTANCE : Gary Chang , **DATE:** Mar. 04, 2005
Responsible for RF (Gary Chang)

APPROVED BY : Cody Chang , **DATE:** Mar. 04, 2005
(Cody Chang, Deputy Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -1.47dB at 28.688MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.01dB at 2488.00MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless-G Exterior Access Point with Power Over Ethernet
MODEL NO.	WAP54GPE
POWER SUPPLY	48Vdc from POE
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
MAXIMUM OUTPUT POWER	26.363mW
ANTENNA TYPE	Patch antenna with 9dBi gain Omnidirectional Antenna with 8dBi gain
DATA CABLE	NA
I/O PORTS	RJ45
ASSOCIATED DEVICES	NA

NOTE:


1. The POE is part of the Support Units not EUT.
2. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
3. The EUT complies with IEEE 802.11g standards and backwards compatible with IEEE 802.11b products.
4. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
1	Note 1	x	x	Note 2	Patch antenna
2	Note 1	x	x	Note 2	Omnidirectional Antenna

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

Note 1: Power Line Conducted Emission was chosen worst (mode 1) for final test.

Note 2: Conducted RF measurement is independent of antenna.

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
1	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
2	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
1	802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
2	802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
1	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
2	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

- ☒ Following channel(s) was (were) selected for the final test as listed below.

Bandedge Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6

Antenna Port Conducted Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless-G Exterior Access Point with Power Over Ethernet. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)
ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
2	POE	Gemtek	E110	AE61013962	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA

NOTE: 1. All power cords of the above support units are non shielded (1.8m).

2. Item 1~2 act as a communication partner to transfer data.

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 16, 2005
RF signal cable Woken	5D-FB	Cable-HYC01-01	Jan. 09, 2006
LISN ROHDE & SCHWARZ	ESH3-Z5	100312	Feb. 15, 2006
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Feb. 15, 2006
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. Prepared another Notebook system to act as a communication partner and placed it outside of testing via an RJ45 cable area.
- c. The communication partner and run a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- d. The communication partner sent data to EUT by command "PING".


4.1.7 TEST RESULTS

Conducted Worst-Case Data

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa	TESTED BY	Leo Hung

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.275	0.12	46.82	-	46.94	-	60.97	50.97	-14.02	-
2	0.404	0.13	39.69	-	39.82	-	57.77	47.77	-17.96	-
3	1.238	0.15	45.32	-	45.47	-	56.00	46.00	-10.53	-
4	1.668	0.16	44.94	-	45.10	-	56.00	46.00	-10.90	-
5	10.988	0.39	33.37	-	33.76	-	60.00	50.00	-26.24	-
6	27.340	1.30	48.31	-	49.61	-	60.00	50.00	-10.39	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa	TESTED BY	Leo Hung

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.259	0.11	40.11	-	40.22	-	61.45	51.45	-21.23	-
2	0.404	0.12	35.55	-	35.67	-	57.77	47.77	-22.11	-
3	1.207	0.15	44.87	-	45.02	-	56.00	46.00	-10.98	-
4	1.664	0.16	44.73	-	44.89	-	56.00	46.00	-11.11	-
5	4.637	0.21	36.64	-	36.85	-	56.00	46.00	-19.15	-
6	28.688	0.67	50.33	47.86	51.00	48.53	60.00	50.00	-9.00	-1.47


REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa	TESTED BY	Leo Hung

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.271	0.12	44.73	-	44.85	-	61.08	51.08	-16.23	-
2	0.595	0.13	37.01	-	37.14	-	56.00	46.00	-18.86	-
3	1.203	0.15	45.12	-	45.27	-	56.00	46.00	-10.73	-
4	1.906	0.16	44.14	-	44.30	-	56.00	46.00	-11.70	-
5	10.004	0.30	31.45	-	31.75	-	60.00	50.00	-28.25	-
6	26.547	1.25	48.97	43.93	50.22	45.18	60.00	50.00	-9.78	-4.82


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa	TESTED BY	Leo Hung

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.271	0.11	46.94	-	47.05	-	61.08	51.08	-14.03	-
2	0.396	0.12	39.30	-	39.42	-	57.93	47.93	-18.52	-
3	1.195	0.15	45.21	-	45.36	-	56.00	46.00	-10.64	-
4	1.664	0.16	43.46	-	43.62	-	56.00	46.00	-12.38	-
5	10.953	0.35	35.28	-	35.63	-	60.00	50.00	-24.37	-
6	27.344	0.67	48.80	-	49.47	-	60.00	50.00	-10.53	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa	TESTED BY	Leo Hung

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.271	0.12	44.67	-	44.79	-	61.08	51.08	-16.29	-
2	0.834	0.14	39.45	-	39.59	-	56.00	46.00	-16.41	-
3	1.188	0.15	44.44	-	44.59	-	56.00	46.00	-11.41	-
4	1.668	0.16	45.21	-	45.37	-	56.00	46.00	-10.63	-
5	3.594	0.20	32.69	-	32.89	-	56.00	46.00	-23.11	-
6	29.234	1.41	50.47	47.04	51.88	48.45	60.00	50.00	-8.12	-1.55


REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa	TESTED BY	Leo Hung

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.275	0.11	46.37	-	46.48	-	60.97	50.97	-14.48	-
2	0.404	0.12	39.30	-	39.42	-	57.77	47.77	-18.36	-
3	1.203	0.15	45.17	-	45.32	-	56.00	46.00	-10.68	-
4	1.906	0.16	43.55	-	43.71	-	56.00	46.00	-12.29	-
5	17.887	0.68	36.92	-	37.60	-	60.00	50.00	-22.40	-
6	27.344	0.67	48.37	-	49.04	-	60.00	50.00	-10.96	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Dec. 19, 2005
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Nov. 21, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Jan. 22, 2006
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-407	Jan. 16, 2006
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170241	Feb. 22, 2006
Preamplifier Agilent	8449B	3008A01961	Nov. 09, 2005
Preamplifier Agilent	8447D	2944A10629	Nov. 09, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218182/4	Mar. 04, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218194/4	Mar. 04, 2005
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA
Turn Table ADT.	TT100.	TT93021702	NA
Controller ADT.	SC100.	SC93021702	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 1.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The IC Site Registration No. is IC4924-2.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

Below 1GHz Worst-Case Data (Patch antenna)

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	26 deg. C, 70% RH, 991 hPa	TESTED BY	Steven Lu
TEST MODE	1 (Patch Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	150.10	38.95 QP	43.50	-4.55	1.70 H	265	27.91	11.04
2	199.99	34.48 QP	43.50	-9.02	1.08 H	2	24.21	10.27
3	238.00	39.93 QP	46.00	-6.07	1.01 H	108	27.27	12.66
4	250.00	41.18 QP	46.00	-4.82	1.05 H	167	27.77	13.41
5	325.01	36.53 QP	46.00	-9.47	1.66 H	195	20.69	15.84
6	375.01	39.04 QP	46.00	-6.96	1.00 H	174	21.95	17.09
7	399.98	37.32 QP	46.00	-8.68	2.41 H	197	19.30	18.02
8	500.00	40.52 QP	46.00	-5.48	1.00 H	154	20.80	9.72
9	645.26	42.89 QP	46.00	-3.11	2.34 H	316	20.88	22.01
10	666.62	43.87 QP	46.00	-2.13	1.28 H	218	21.66	22.21
11	799.94	43.39 QP	46.00	-2.61	1.85 H	237	20.02	23.37
12	933.26	42.48 QP	46.00	-3.52	2.66 H	229	17.80	24.68

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	149.15	40.58 QP	43.50	-2.92	1.00 V	267	29.48	11.10
2	199.99	35.34 QP	43.50	-8.16	1.00 V	36	25.07	10.27
3	237.95	36.23 QP	46.00	-9.77	1.21 V	40	23.58	12.65
4	250.20	40.19 QP	46.00	-5.81	1.46 V	40	26.76	13.43
5	325.01	33.98 QP	46.00	-12.02	2.03 V	228	18.14	15.84
6	375.00	33.99 QP	46.00	-12.01	1.67 V	347	16.90	17.09
7	399.98	37.73 QP	46.00	-8.27	1.05 V	56	19.71	18.02
8	599.97	35.61 QP	46.00	-10.39	1.28 V	9	13.67	21.94
9	650.05	33.48 QP	46.00	-12.52	1.52 V	24	11.46	22.02
10	666.61	44.92 QP	46.00	-1.08	1.00 V	277	22.71	22.21
11	799.93	44.00 QP	46.00	-2.00	1.00 V	168	20.63	23.7
12	933.25	44.40 QP	46.00	-1.60	1.26 V	204	19.72	24.68

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

Below 1GHz Worst-Case Data (Omnidirectional Antenna)

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	20deg. C, 85%RH, 991hPa	TESTED BY	Penny Chen
TEST MODE	2 (Omnidirectional Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	249.66	26.29 QP	37.00	-10.71	4.00 H	146	13.38	12.91
2	300.20	26.53 QP	37.00	-10.47	3.00 H	156	11.98	14.55
3	399.34	29.46 QP	37.00	-7.54	3.00 H	121	12.28	17.18
4	449.88	28.08 QP	37.00	-8.92	2.00 H	338	9.57	18.51
5	667.60	30.63 QP	37.00	-6.37	1.00 H	274	7.66	22.96
6	751.18	27.22 QP	37.00	-9.78	1.00 H	31	2.49	24.73
7	799.78	32.99 QP	37.00	-4.01	4.00 H	253	8.06	24.93
8	933.24	34.80 QP	37.00	-2.20	1.00 H	253	8.07	26.73

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.00	26.78 QP	30.00	-3.22	1.00 V	231	14.27	12.51
2	45.55	24.34 QP	30.00	-5.66	1.00 V	182	10.18	14.15
3	64.99	27.42 QP	30.00	-2.58	3.00 V	315	15.36	12.06
4	76.65	27.47 QP	30.00	-2.53	4.00 V	190	17.70	9.77
5	90.34	28.03 QP	30.00	-1.97	2.00 V	147	18.90	9.13
6	142.75	22.76 QP	30.00	-7.24	2.00 V	161	9.33	13.43
7	160.24	25.88 QP	30.00	-4.12	1.00 V	159	12.12	13.76
8	173.85	21.62 QP	30.00	-8.38	3.00 V	113	9.12	12.50
9	799.92	35.87 QP	37.00	-1.13	2.00 V	244	11.35	24.52
10	976.67	31.57 QP	37.00	-5.43	4.00 V	166	5.02	26.55

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

802.11b DSSS modulation (Patch antenna)

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64% RH, 991 hPa	TESTED BY	Match Tsui
TEST MODE	1 (Patch Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	50.20 PK	74.00	-23.80	1.12 H	52	23.19	27.01
1	1200.00	44.56 AV	54.00	-9.44	1.12 H	52	17.55	27.01
2	2386.00	52.55 PK	74.00	-21.45	1.24 H	74	20.76	31.79
2	2386.00	44.82 AV	54.00	-9.18	1.24 H	74	13.03	31.79
3	*2412.00	99.20 PK			1.24 H	74	67.33	31.87
3	*2412.00	95.75 AV			1.24 H	74	63.88	31.87
4	4824.00	51.59 PK	74.00	-22.41	1.21 H	21	13.47	38.11
4	4824.00	46.34 AV	54.00	-7.66	1.21 H	21	8.22	38.11

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1466.00	41.66 PK	74.00	-32.34	1.02 V	360	13.72	27.94
1	1466.00	41.89 AV	54.00	-12.11	1.02 V	360	13.95	27.94
2	2038.00	44.22 PK	74.00	-29.78	1.00 V	1	13.57	30.65
2	2038.00	39.59 AV	54.00	-14.41	1.00 V	1	8.94	30.65
3	2386.00	59.30 PK	74.00	-14.70	1.36 V	185	27.51	31.79
3	2386.00	49.14 AV	54.00	-4.86	1.36 V	185	17.35	31.79
4	*2412.00	109.24 PK			1.36 V	185	77.37	31.87
4	*2412.00	106.34 AV			1.36 V	185	74.47	31.87
5	4824.00	52.05 PK	74.00	-21.95	1.00 V	138	13.93	38.11
5	4824.00	46.52 AV	54.00	-7.48	1.00 V	138	8.40	38.11
6	7236.00	53.11 PK	74.00	-20.89	1.07 V	37	10.06	43.05
6	7236.00	42.41 AV	54.00	-11.59	1.07 V	37	-0.64	43.05

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64% RH, 991 hPa	TESTED BY	Match Tsui
TEST MODE	1 (Patch Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1333.00	44.44 PK	74.00	-29.56	1.53 H	23	16.96	27.48
1	1333.00	41.79 AV	54.00	-12.21	1.53 H	23	14.31	27.48
2	2063.00	44.69 PK	74.00	-29.31	1.19 H	346	14.00	30.69
2	2063.00	38.98 AV	54.00	-15.02	1.19 H	346	8.29	30.69
3	*2437.00	96.93 PK			1.15 H	303	64.98	31.95
3	*2437.00	93.17 AV			1.15 H	303	61.22	31.95
4	4874.00	54.10 PK	74.00	-19.90	1.03 H	303	15.81	38.28
4	4874.00	50.52 AV	54.00	-3.48	1.03 H	303	12.23	38.28
5	7311.00	53.91 PK	74.00	-20.09	1.12 H	26	10.94	42.97
5	7311.00	44.61 AV	54.00	-9.39	1.12 H	26	1.64	42.97

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1066.00	49.39 PK	74.00	-24.61	1.46 V	341	22.81	26.58
1	1066.00	51.93 AV	54.00	-2.07	1.46 V	341	25.35	26.58
2	2063.00	45.24 PK	74.00	-28.76	1.46 V	1	14.55	30.69
2	2063.00	42.15 AV	54.00	-11.85	1.46 V	1	11.46	30.69
3	*2437.00	109.38 PK			1.27 V	354	77.43	31.95
3	*2437.00	106.13 AV			1.27 V	354	74.18	31.95
4	4874.00	55.17 PK	74.00	-18.83	1.00 V	19	16.88	38.28
4	4874.00	51.29 AV	54.00	-2.71	1.00 V	19	13.00	38.28

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 64% RH, 991 hPa	TESTED BY	Match Tsui
TEST MODE	1 (Patch Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	45.85 PK	74.00	-28.15	1.16 H	360	17.22	28.63
1	1600.00	42.91 AV	54.00	-11.09	1.16 H	360	14.28	28.63
2	2088.00	44.20 PK	74.00	-29.80	1.21 H	342	13.47	30.73
2	2088.00	39.89 AV	54.00	-14.11	1.21 H	342	9.16	30.73
3	*2462.00	90.78 PK			1.14 H	312	58.76	32.02
3	*2462.00	87.43 AV			1.14 H	312	55.41	32.02
4	2488.00	55.72 PK	74.00	-18.28	1.14 H	312	23.62	32.10
4	2488.00	47.65 AV	54.00	-6.35	1.14 H	312	15.55	32.10
5	4924.00	47.45 PK	74.00	-26.55	1.14 H	50	8.96	38.49
5	4924.00	37.74 AV	54.00	-16.26	1.14 H	50	-0.75	38.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	48.27 PK	74.00	-25.73	1.28 V	352	21.26	27.01
1	1200.00	45.47 AV	54.00	-8.53	1.28 V	352	18.46	27.01
2	2088.00	48.88 PK	74.00	-25.12	1.21 V	1	18.15	30.73
2	2088.00	46.87 AV	54.00	-7.13	1.21 V	1	16.14	30.73
3	*2462.00	98.12 PK			1.04 V	341	66.10	32.02
3	*2462.00	94.75 AV			1.04 V	341	62.73	32.02
4	2488.00	59.93 PK	74.00	-14.07	1.03 V	341	27.83	32.10
4	2488.00	52.94 AV	54.00	-1.06	1.03 V	341	20.84	32.10
5	4924.00	48.10 PK	74.00	-25.90	1.28 V	22	9.61	38.49
5	4924.00	37.39 AV	54.00	-16.61	1.28 V	22	-1.10	38.49

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

802.11b DSSS modulation (Omnidirectional Antenna)

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20deg. C, 70% RH, 991 hPa	TESTED BY	Match Tsui
TEST MODE	2 (Omnidirectional Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	44.56 PK	74.00	-29.44	1.08 H	106	17.07	27.49
1	1200.00	40.42 AV	54.00	-13.58	1.08 H	106	12.93	27.49
2	2038.00	43.83 PK	74.00	-30.17	1.10 H	288	13.76	30.07
2	2038.00	38.67 AV	54.00	-15.33	1.10 H	288	8.60	30.07
3	2386.00	53.88 PK	74.00	-20.12	1.08 H	14	22.28	31.60
3	2386.00	44.01 AV	54.00	-9.99	1.08 H	14	12.41	31.60
4	*2412.00	90.89 PK			1.08 H	14	59.18	31.71
4	*2412.00	88.34 AV			1.08 H	14	56.63	31.71
5	4824.00	49.91 PK	74.00	-24.09	1.40 H	360	12.36	37.55
5	4824.00	45.19 AV	54.00	-8.81	1.40 H	360	7.64	37.55
6	7236.00	53.85 PK	74.00	-20.15	1.38 H	1	10.21	43.64
6	7236.00	43.42 AV	54.00	-10.58	1.38 H	1	-0.22	43.64

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	43.34 PK	74.00	-30.66	1.22 V	360	15.85	27.49
1	1200.00	42.46 AV	54.00	-11.54	1.22 V	360	14.97	27.49
2	2038.00	40.68 PK	74.00	-33.32	1.16 V	43	10.61	30.07
2	2038.00	33.04 AV	54.00	-20.96	1.16 V	43	2.97	30.07
3	2386.00	56.39 PK	74.00	-17.61	1.21 V	3	24.79	31.60
3	2386.00	45.96 AV	54.00	-8.04	1.21 V	3	14.36	31.60
4	*2412.00	107.29 PK			1.21 V	3	75.58	31.71
4	*2412.00	104.07 AV			1.21 V	3	72.36	31.71
5	4824.00	47.49 PK	74.00	-26.51	1.43 V	303	9.94	37.55
5	4824.00	40.06 AV	54.00	-13.94	1.43 V	303	2.51	37.55

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20deg. C, 70% RH, 991 hPa	TESTED BY	Match Tsui
TEST MODE	2 (Omnidirectional Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1066.00	43.33 PK	74.00	-30.67	1.17 H	1	16.09	27.24
1	1066.00	40.03 AV	54.00	-13.97	1.17 H	1	12.79	27.24
2	2063.00	44.12 PK	74.00	-29.88	1.10 H	200	13.95	30.17
2	2063.00	39.56 AV	54.00	-14.44	1.10 H	200	9.39	30.17
3	*2437.00	92.45 PK			1.59 H	305	60.63	31.82
3	*2437.00	89.13 AV			1.59 H	305	57.31	31.82
4	4874.00	48.86 PK	74.00	-25.14	1.26 H	360	11.18	37.67
4	4874.00	42.98 AV	54.00	-11.02	1.26 H	360	5.30	37.67
5	7311.00	52.56 PK	74.00	-21.44	1.38 H	1	8.76	43.80
5	7311.00	41.91 AV	54.00	-12.09	1.38 H	1	-1.89	43.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	42.86 PK	74.00	-31.14	1.20 V	350	15.37	27.49
1	1200.00	43.18 AV	54.00	-10.82	1.20 V	350	15.69	27.49
2	2063.00	41.25 PK	74.00	-32.75	1.15 V	100	11.08	30.17
2	2063.00	33.51 AV	54.00	-20.49	1.15 V	100	3.34	30.17
3	*2437.00	107.21 PK			1.36 V	360	75.39	31.82
3	*2437.00	103.86 AV			1.36 V	360	72.04	31.82
4	4874.00	46.49 PK	74.00	-27.51	1.17 V	35	8.81	37.67
4	4874.00	39.19 AV	54.00	-14.81	1.17 V	35	1.51	37.67

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency.

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20deg. C, 70% RH, 991 hPa	TESTED BY	Match Tsui
TEST MODE	2 (Omnidirectional Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1066.00	43.56 PK	74.00	-30.44	1.29 H	1	16.32	27.24
1	1066.00	40.30 AV	54.00	-13.70	1.29 H	1	13.06	27.24
2	2088.00	43.76 PK	74.00	-30.24	1.16 H	360	13.48	30.28
2	2088.00	39.81 AV	54.00	-14.19	1.16 H	360	9.53	30.28
3	*2462.00	83.61 PK			1.25 H	47	51.68	31.93
3	*2462.00	79.93 AV			1.25 H	47	48.00	31.93
4	2488.00	53.38 PK	74.00	-20.62	1.25 H	47	21.33	32.05
4	2488.00	44.74 AV	54.00	-9.26	1.25 H	47	12.69	32.05
5	4924.00	45.67 PK	74.00	-28.33	1.15 H	333	7.86	37.81
5	4924.00	32.39 AV	54.00	-21.61	1.15 H	333	-5.42	37.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1333.00	42.87 PK	74.00	-31.13	1.12 V	307	14.78	28.10
1	1333.00	38.31 AV	54.00	-15.69	1.12 V	307	10.22	28.10
2	2088.00	45.21 PK	74.00	-28.79	1.19 V	12	14.93	30.28
2	2088.00	41.71 AV	54.00	-12.29	1.19 V	12	11.43	30.28
3	*2462.00	97.33 PK			1.54 V	327	65.40	31.93
3	*2462.00	94.10 AV			1.54 V	327	62.17	31.93
4	2488.00	57.86 PK	74.00	-16.14	1.54 V	327	25.81	32.05
4	2488.00	50.15 AV	54.00	-3.85	1.54 V	327	18.10	32.05
5	4924.00	45.40 PK	74.00	-28.60	1.00 V	35	7.59	37.81
5	4924.00	32.67 AV	54.00	-21.33	1.00 V	35	-5.14	37.81

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency.

802.11g OFDM modulation (Patch Antenna)

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 991hPa	TESTED BY	Match Tsui
TEST MODE	1 (Patch Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	44.08 PK	74.00	-29.92	1.15 H	187	15.45	28.63
1	1600.00	40.04 AV	54.00	-13.96	1.15 H	187	11.41	28.63
2	2390.00	53.30 PK	74.00	-20.70	1.07 H	172	21.50	31.80
2	2390.00	44.83 AV	54.00	-9.17	1.07 H	172	13.03	31.80
3	*2412.00	97.49 PK			1.07 H	172	65.62	31.87
3	*2412.00	88.73 AV			1.07 H	172	56.86	31.87
4	4824.00	49.58 PK	74.00	-24.42	1.07 H	117	11.46	38.11
4	4824.00	36.55 AV	54.00	-17.45	1.07 H	117	-1.57	38.11
5	7236.00	57.19 PK	74.00	-16.81	1.00 H	211	14.14	43.05
5	7236.00	42.52 AV	54.00	-11.48	1.00 H	211	-0.53	43.05

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	48.30 PK	74.00	-25.70	1.12 V	1	21.29	27.01
1	1200.00	47.46 AV	54.00	-6.54	1.12 V	1	20.45	27.01
2	2038.00	45.44 PK	74.00	-28.56	1.10 V	187	14.79	30.65
2	2038.00	41.31 AV	54.00	-12.69	1.10 V	187	10.66	30.65
3	2390.00	59.06 PK	74.00	-14.94	1.30 V	185	27.26	31.80
3	2390.00	47.70 AV	54.00	-6.30	1.30 V	185	15.90	31.80
4	*2412.00	109.42 PK			1.30 V	185	77.55	31.87
4	*2412.00	100.36 AV			1.30 V	185	68.49	31.87
5	4824.00	50.11 PK	74.00	-23.89	1.04 V	194	11.99	38.11
5	4824.00	37.21 AV	54.00	-16.79	1.04 V	194	-0.91	38.11
6	7236.00	57.09 PK	74.00	-16.91	1.03 V	121	14.04	43.05
6	7236.00	41.77 AV	54.00	-12.23	1.03 V	121	-1.28	43.05

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 991hPa	TESTED BY	Match Tsui
TEST MODE	1 (Patch Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	43.90 PK	74.00	-30.10	1.16 H	174	15.27	28.63
1	1600.00	40.44 AV	54.00	-13.56	1.16 H	174	11.81	28.63
2	*2437.00	97.37 PK			1.16 H	177	65.42	31.95
2	*2437.00	88.30 AV			1.16 H	177	56.35	31.95
3	7311.00	49.56 PK	74.00	-24.44	1.16 H	226	6.59	42.97
3	7311.00	40.44 AV	54.00	-13.56	1.16 H	226	-2.53	42.97

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	45.90 PK	74.00	-28.10	1.11 V	1	18.89	27.01
1	1200.00	46.98 AV	54.00	-7.02	1.11 V	1	19.97	27.01
2	*2437.00	108.32 PK			1.32 V	179	76.37	31.95
2	*2437.00	99.57 AV			1.32 V	179	67.62	31.95
3	4874.00	50.39 PK	74.00	-23.61	1.20 V	198	12.10	38.28
3	4874.00	36.99 AV	54.00	-17.01	1.20 V	198	-1.30	38.28
4	7311.00	53.45 PK	74.00	-20.55	1.12 V	220	10.48	42.97
4	7311.00	39.72 AV	54.00	-14.28	1.12 V	220	-3.25	42.97

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 991hPa	TESTED BY	Match Tsui
TEST MODE	1 (Patch Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1333.00	45.53 PK	74.00	-28.47	1.36 H	122	18.05	27.48
1	1333.00	42.27 AV	54.00	-11.73	1.36 H	122	14.79	27.48
2	2088.00	43.21 PK	74.00	-30.79	1.30 H	140	12.48	30.73
2	2088.00	38.73 AV	54.00	-15.27	1.30 H	140	8.00	30.73
3	*2462.00	86.10 PK			1.16 H	181	54.08	32.02
3	*2462.00	77.32 AV			1.16 H	181	45.30	32.02
4	2488.00	55.56 PK	74.00	-18.44	1.16 H	181	23.46	32.10
4	2488.00	45.98 AV	54.00	-8.02	1.16 H	181	13.88	32.10
5	7386.00	49.37 PK	74.00	-24.63	1.30 H	15	6.82	42.55
5	7386.00	36.76 AV	54.00	-17.24	1.30 H	15	-5.79	42.55

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	46.33 PK	74.00	-27.67	1.30 V	151	19.32	27.01
1	1200.00	45.52 AV	54.00	-8.48	1.30 V	151	18.51	27.01
2	*2462.00	97.01 PK			1.31 V	173	64.99	32.02
2	*2462.00	88.35 AV			1.31 V	173	56.33	32.02
3	2488.00	58.83 PK	74.00	-15.17	1.31 V	173	26.73	32.10
3	2488.00	52.99 AV	54.00	-1.01	1.31 V	173	20.89	32.10
4	2544.00	52.27 PK	74.00	-21.73	1.01 V	178	19.96	32.31
4	2544.00	46.52 AV	54.00	-7.48	1.01 V	178	14.21	32.31
5	7386.00	49.47 PK	74.00	-24.53	1.23 V	264	6.92	42.55
5	7386.00	36.68 AV	54.00	-17.32	1.23 V	264	-5.87	42.55

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.

802.11g OFDM modulation (Omnidirectional Antenna)

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20deg. C, 70%RH, 991hPa	TESTED BY	Match Tsui
TEST MODE	2 (Omnidirectional Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1066.00	43.25 PK	74.00	-30.75	1.24 H	1	16.01	27.24
1	1066.00	40.39 AV	54.00	-13.61	1.24 H	1	13.15	27.24
2	2038.00	41.43 PK	74.00	-32.57	1.43 H	318	11.36	30.07
2	2038.00	35.80 AV	54.00	-18.20	1.43 H	318	5.73	30.07
3	*2412.00	92.99 PK			1.57 H	305	61.28	31.71
3	*2412.00	84.22 AV			1.57 H	305	52.51	31.71
4	4824.00	46.81 PK	74.00	-27.19	1.18 H	336	9.26	37.55
4	4824.00	35.02 AV	54.00	-18.98	1.18 H	336	-2.53	37.55
5	7236.00	55.57 PK	74.00	-18.43	1.22 H	297	11.93	43.64
5	7236.00	41.00 AV	54.00	-13.00	1.22 H	297	-2.64	43.64

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1466.00	41.77 PK	74.00	-32.23	1.07 V	358	13.32	28.45
1	1466.00	37.14 AV	54.00	-16.86	1.07 V	358	8.69	28.45
2	2038.00	42.62 PK	74.00	-31.38	1.00 V	324	12.55	30.07
2	2038.00	37.00 AV	54.00	-17.00	1.00 V	324	6.93	30.07
3	2390.00	57.81 PK	74.00	-16.19	1.00 V	52	26.19	31.62
3	2390.00	45.25 AV	54.00	-8.75	1.00 V	52	13.63	31.62
4	*2412.00	107.42 PK			1.00 V	52	75.71	31.71
4	*2412.00	98.55 AV			1.00 V	52	66.84	31.71

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency.

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20deg. C, 70%RH, 991hPa	TESTED BY	Match Tsui
TEST MODE	2 (Omnidirectional Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	44.25 PK	74.00	-29.75	1.12 H	300	17.26	26.99
1	1200.00	41.90 AV	54.00	-12.10	1.12 H	300	14.91	26.99
2	2063.00	41.50 PK	74.00	-32.50	1.20 H	250	11.87	29.63
2	2063.00	36.12 AV	54.00	-17.88	1.20 H	250	6.49	29.63
3	*2437.00	93.01 PK			1.08 H	280	61.84	31.17
3	*2437.00	85.15 AV			1.08 H	280	53.98	31.17
4	4874.00	45.22 PK	74.00	-28.78	1.11 H	300	8.68	36.54
4	4874.00	34.68 AV	54.00	-19.32	1.11 H	300	-1.86	36.54
5	7311.00	55.60 PK	74.00	-18.40	1.20 H	290	13.14	42.46
5	7311.00	41.35 AV	54.00	-12.65	1.20 H	290	-1.11	42.46

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1332.00	42.15 PK	74.00	-31.85	1.11 V	200	14.06	28.09
1	1332.00	38.07 AV	54.00	-15.93	1.11 V	200	9.98	28.09
2	2063.00	42.51 PK	74.00	-31.49	1.00 V	300	12.34	30.17
2	2063.00	38.11 AV	54.00	-15.89	1.00 V	300	7.94	30.17
3	*2437.00	107.51 PK			1.00 V	350	75.69	31.82
3	*2437.00	98.77 AV			1.00 V	350	66.95	31.82
4	4874.00	45.68 PK	74.00	-28.32	1.20 V	120	8.00	37.67
4	4874.00	32.58 AV	54.00	-21.42	1.20 V	120	-5.10	37.67

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency.

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20deg. C, 70%RH, 991hPa	TESTED BY	Match Tsui
TEST MODE	2 (Omnidirectional Antenna)		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1066.00	43.49 PK	74.00	-30.51	1.27 H	339	16.25	27.24
1	1066.00	41.02 AV	54.00	-12.98	1.27 H	339	13.78	27.24
2	2088.00	44.01 PK	74.00	-29.99	1.19 H	4	13.73	30.28
2	2088.00	40.00 AV	54.00	-14.00	1.19 H	4	9.72	30.28
3	*2462.00	83.68 PK			1.46 H	339	51.75	31.93
3	*2462.00	74.95 AV			1.46 H	339	43.02	31.93
4	2488.00	54.34 PK	74.00	-19.66	1.46 H	339	22.29	32.05
4	2488.00	44.77 AV	54.00	-9.23	1.46 H	339	12.72	32.05
5	4924.00	43.13 PK	74.00	-30.87	1.03 H	1	5.32	37.81
5	4924.00	30.95 AV	54.00	-23.05	1.03 H	1	-6.86	37.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1200.00	43.45 PK	74.00	-30.55	1.23 V	15	15.96	27.49
1	1200.00	39.98 AV	54.00	-14.02	1.23 V	15	12.49	27.49
2	2088.00	45.29 PK	74.00	-28.71	1.00 V	360	15.01	30.28
2	2088.00	41.97 AV	54.00	-12.03	1.00 V	360	11.69	30.28
3	*2462.00	97.33 PK			1.13 V	56	65.40	31.93
3	*2462.00	89.06 AV			1.13 V	56	57.13	31.93
4	2488.00	57.27 PK	74.00	-16.73	1.13 V	56	25.22	32.05
4	2488.00	50.45 AV	54.00	-3.55	1.13 V	56	18.40	32.05
5	4924.00	44.17 PK	74.00	-29.83	1.13 V	317	6.36	37.81
5	4924.00	31.84 AV	54.00	-22.16	1.13 V	317	-5.97	37.81

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency.ue.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


4.3.7 TEST RESULTS

802.11b DSSS modulation


EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	12.28	0.5	PASS
6	2437	12.12	0.5	PASS
11	2462	12.12	0.5	PASS


CH 1



CH 6



CH 11




802.11g OFDM modulation


EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.52	0.5	PASS
6	2437	16.52	0.5	PASS
11	2462	16.48	0.5	PASS


CH 1



CH 6



CH 11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 06, 2005
TEKTRONIX OSCILLOSCOPE	TDS 1012	C019167	Feb. 01, 2006
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to peak the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS modulation

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	26.062	14.16	27	PASS
6	2437	26.363	14.21	27	PASS
11	2462	5.297	7.24	27	PASS

NOTE: According to 15.247 (b) (4), the maximum antenna gain 6dBi is higher than 6dBi, so the limit of peak power shall be reduce by 3dB.

802.11g OFDM modulation

EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	25.351	14.04	27	PASS
6	2437	25.645	14.09	27	PASS
11	2462	4.188	6.22	27	PASS

NOTE: According to 15.247 (b) (4), the maximum antenna gain 9dBi is higher than 6dBi, so the limit of peak power shall be reduce by 3dB.

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6


4.5.7 TEST RESULTS

802.11b DSSS modulation


EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-16.30	5	PASS
6	2437	-16.36	5	PASS
11	2462	-25.96	5	PASS


CH 1



CH 6



CH 11




802.11g OFDM modulation


EUT	Wireless-G Exterior Access Point with Power Over Ethernet	MODEL	WAP54GPE
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-17.30	5	PASS
6	2437	-18.20	5	PASS
11	2462	-27.35	5	PASS


CH 1



CH 6



CH 11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 12 images. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS modulation

Patch Antenna

NOTE 1: The band edge emission plot of DSSS technique on page 61 show 50.84dBc delta between carrier maximum power and local maximum emission in restrict band (2.3884GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 109.24dBuV/m (Peak), so the maximum field strength in restrict band is $109.24 - 50.84 = 58.40$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on page 61 show 59.43dBc delta between carrier maximum power and local maximum emission in restrict band (2.3862GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 106.34dBuV/m (Average), so the maximum field strength in restrict band is $106.34 - 59.43 = 46.91$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot of DSSS technique on the page 62 show 37.83dBc delta between carrier maximum power and local maximum emission in restrict band (2.4879GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 98.12dBuV/m (Peak), so the maximum field strength in restrict band is $98.12 - 37.83 = 60.29$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on the page 63 show 43.78dBc delta between carrier maximum power and local maximum emission in restrict band (2.4880GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 94.75dBuV/m (Average), so the maximum field strength in restrict band is $94.75 - 43.78 = 50.97$ dBuV/m which is under 54dBuV/m limit.

Omnidirectional Antenna

NOTE 1: The band edge emission plot of DSSS technique on page 61 show 50.84dBc delta between carrier maximum power and local maximum emission in restrict band (2.3884GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 107.29dBuV/m (Peak), so the maximum field strength in restrict band is $107.29 - 50.84 = 56.45$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on page 61 show 59.43dBc delta between carrier maximum power and local maximum emission in restrict band (2.3862GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 104.07dBuV/m (Average), so the maximum field strength in restrict band is $104.07 - 59.43 = 44.64$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot of DSSS technique on the page 62 show 37.83dBc delta between carrier maximum power and local maximum emission in restrict band (2.4879GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 97.33dBuV/m (Peak), so the maximum field strength in restrict band is $97.33 - 37.83 = 59.50$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on the page 63 show 43.78dBc delta between carrier maximum power and local maximum emission in restrict band (2.4880GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 94.10dBuV/m (Average), so the maximum field strength in restrict band is $94.10 - 43.78 = 50.32$ dBuV/m which is under 54dBuV/m limit.

802.11g OFDM modulation

Patch Antenna

NOTE 1: The band edge emission plot of OFDM technique on page 64 show 46.03dBc delta between carrier maximum power and local maximum emission in restrict band (2.3892GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 109.42dBuV/m (Peak), so the maximum field strength in restrict band is $109.42 - 46.03 = 63.39$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on page 64 show 55.39dBc delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 100.36dBuV/m (Average), so the maximum field strength in restrict band is $100.36 - 55.39 = 44.97$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot of OFDM technique on page 65 show 33.51dBc delta between carrier maximum power and local maximum emission in restrict band (2.4879GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 97.01dBuV/m (Peak), so the maximum field strength in restrict band is $97.01 - 33.51 = 63.50$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on page 66 show 37.06dBc delta between carrier maximum power and local maximum emission in restrict band (2.4880GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 88.35dBuV/m (Average), so the maximum field strength in restrict band is $88.35 - 37.06 = 51.29$ dBuV/m which is under 54dBuV/m limit.

Omnidirectional Antenna



NOTE 1: The band edge emission plot of OFDM technique on page 64 show 46.03dBc delta between carrier maximum power and local maximum emission in restrict band (2.3892GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 107.42dBuV/m (Peak), so the maximum field strength in restrict band is $107.42 - 46.03 = 61.39$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot of OFDM technique on page 64 show 55.39dBc delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 98.55dBuV/m (Average), so the maximum field strength in restrict band is $98.55 - 55.39 = 43.16$ dBuV/m which is under 54dBuV/m limit.



NOTE 2: The band edge emission plot of OFDM technique on page 65 show 33.51dBc delta between carrier maximum power and local maximum emission in restrict band (2.4879GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 97.33dBuV/m (Peak), so the maximum field strength in restrict band is $97.33 - 33.51 = 63.82$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on page 66 show 37.06dBc delta between carrier maximum power and local maximum emission in restrict band (2.4880GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 89.06dBuV/m (Average), so the maximum field strength in restrict band is $89.06 - 37.06 = 52.00$ dBuV/m which is under 54dBuV/m limit.



802.11b DSSS modulation











802.11g OFDM modulation







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION



The antennas used in this product are Patch antenna with UFL connector and Omnidirectional antenna with N-Type connector. And the maximum Gain of this antenna is 9dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION



CONDUCTED EMISSION TEST



RADIATED EMISSION TEST
(Patch Antenna)



(Omnidirectional Antenna)



6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Linko RF Lab.

Tel: 886-3-3270910

Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.