

FCC PART 15.247
TEST REPORT

For

Sky Phone LLC

1348 Washington Av. Suite 350, Miami Beach, Florida, United States

FCC ID: 2ABOSSKYELITE4T

Report Type: Class II Permissive Change	Product Type: 4G Smart Phone
Report Number: RSZ180115028-00CA1	
Report Date: 2018-03-28	
Reviewed By: RF Engineer	Rocky Kang <i>Rocky Kang</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP* or any agency of the Federal Government. * This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk

“*”

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	8
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	12
TEST EQUIPMENT LIST	13
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	14
APPLICABLE STANDARD	14
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	18

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RSZ180115028-00CA1	Original Report	2018-02-07
1	RSZ180115028-00CA1	Updated Report *	2018-03-20
2	RSZ180115028-00CA1	Updated Report **	2018-03-28

Note:

1. *Added the FCC Part 15B JBP into the related submittal(s)/grant(s).
2. **Updated the model of Adapter, it not affect any test data, so we only updated the information of adapter and the adapter label view.

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Sky Phone LLC's product, model number: Elite 45T (FCC ID: 2ABOSSKYELITE4T) or the "EUT" in this report was a 4G Smart Phone, which was measured approximately:
13.4 cm (L) × 6.9cm (W) × 1.1 cm (H), rated with input voltage: DC 3.7 V battery or DC 5V from adapter.

Adapter Information:

Model: Elite 45T

Input: AC 100-240V, 50/60Hz, 0.15 A

Output: DC 5.0V, 0.5 A

**All measurement and test data in this report was gathered from production sample serial number: 1800063. (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-01-15.*

Objective

This report is prepared on behalf of Sky Phone LLC in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

This is a CIIPC application of the device, the differences between the original device and the current one are as follows:

1. Change the Model name to "Elite 45T"
2. Change the size and color of EUT.
3. Change all the size of antenna and antenna gain for marketing purpose.
4. Change the battery capacity.

For the change made to the device, the test item "RF Exposure", "Antenna Requirement", and "Spurious Emissions" was performed.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DSS and Part 22H /24E/27 PCE submissions with
FCC ID: 2ABOSSKYELITE4T.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±3℃
Humidity		±6%
Supply voltages		±0.4%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 382179, the FCC Designation No. : CN5001.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

BLE & Wi-Fi test in the engineer mode.


The device was tested with 100% duty cycle and the worst case was performed as below:

Mode	Data rate	Power level		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	14	14	14
802.11g	6 Mbps	12	12	12
802.11n-HT20	MCS0	12	12	12
BLE	/	Default	Default	Default

Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.


Duty cycle

802.11b mode




Date: 22.JAN.2018 10:43:51

802.11g mode




Date: 22.JAN.2018 10:44:33

802.11n-HT20 Mode



Date: 22.JAN.2018 10:45:22

BLE Mode



Date: 16.JAN.2018 20:19:36


Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	10log(1/ Duty Cycle)
802.11b	100	-	-	10Hz	-
802.11g	100	-	-	10Hz	-
802.11n-HT20	100	-	-	10Hz	-
BLE	80	506	1.98	3kHz	0.97

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance*
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance*
§15.247(b)(3)	Maximum Conducted Output Power	Compliance*
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance*
§15.247(e)	Power Spectral Density	Compliance*

Compliance*: Please referred to FCC ID: 2ABOSSKYELITE4T granted on 2018-02-13.
Report No.: RSZ180110001-00C, which was tested by Hill He, Bay Area Compliance Laboratories Corp.
(Shenzhen).

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
A.H.System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-05-21	2018-05-21
HP	Amplifier	HP8447E	1937A01046	2017-11-19	2018-05-21
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2017-12-17	2020-12-16
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2017-12-07	2018-12-07
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	104PEA	218124002	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	RG-214	1	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	RG-214	2	2017-11-19	2018-05-21
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28
Ducommun Technologies	Pre-amplifier	ALN-22093530-01	991373-01	2017-08-03	2018-08-03
Sinoscite	Band Reject Filter	BSF2402-2480MN-0898-001	N/A	2017-05-21	2018-05-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE**Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	2.5	1.8	5	0.6	3.0	Yes
Wi-Fi	2472	9.0	7.9	5	2.5	3.0	Yes

Result: No SAR test is required.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 1.15 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2018-01-31.

EUT operation mode: Transmitting

30 MHz~1 GHz: (worst case at 802.11g Mode, High channel)



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
31.321500	25.63	100.0	V	0.0	-0.6	40.00	14.37
37.249250	25.98	114.0	V	186.0	-4.4	40.00	14.02
86.318000	24.92	400.0	H	91.0	-10.8	40.00	15.08
699.185375	28.77	144.0	V	257.0	6.7	46.00	17.23
828.985375	30.54	148.0	H	0.0	9.0	46.00	15.46
902.205250	31.67	394.0	H	109.0	9.6	46.00	14.33

1 GHz-25 GHz:**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
2412.00	54.60	PK	106	1.9	H	33.92	88.52	/	/
2412.00	49.66	Ave.	106	1.9	H	33.92	83.58	/	/
2412.00	57.86	PK	346	1.8	V	33.92	91.78	/	/
2412.00	52.01	Ave.	346	1.8	V	33.92	85.93	/	/
2379.73	28.05	PK	334	1.5	V	33.92	61.97	74	12.03
2379.73	14.23	Ave.	334	1.5	V	33.92	48.15	54	5.85
2485.69	27.42	PK	127	1.2	V	34.08	61.50	74	12.50
2485.69	13.58	Ave.	127	1.2	V	34.08	47.66	54	6.34
4824.00	43.02	PK	268	1.7	V	5.16	48.18	74	25.82
4824.00	28.54	Ave.	268	1.7	V	5.16	33.70	54	20.30

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2442MHz)									
2442.00	55.69	PK	265	2.0	H	33.92	89.61	/	/
2442.00	50.23	Ave.	265	2.0	H	33.92	84.15	/	/
2442.00	57.94	PK	323	1.9	V	33.92	91.86	/	/
2442.00	52.09	Ave.	323	1.9	V	33.92	86.01	/	/
4884.00	43.20	PK	95	1.3	V	6.21	49.41	74	24.59
4884.00	28.68	Ave.	95	1.3	V	6.21	34.89	54	19.11
High Channel (2472 MHz)									
2472.00	55.78	PK	220	1.8	H	34.08	89.86	/	/
2472.00	50.74	Ave.	220	1.8	H	34.08	84.82	/	/
2472.00	58.80	PK	33	1.6	V	34.08	92.88	/	/
2472.00	53.53	Ave.	33	1.6	V	34.08	87.61	/	/
2388.98	28.63	PK	256	1.9	V	33.92	62.55	74	11.45
2388.98	14.21	Ave.	256	1.9	V	33.92	48.13	54	5.87
2486.64	27.59	PK	242	1.7	V	34.08	61.67	74	12.33
2486.64	13.66	Ave.	242	1.7	V	34.08	47.74	54	6.26
4944.00	42.43	PK	194	1.4	V	6.21	48.64	74	25.36
4944.00	28.23	Ave.	194	1.4	V	6.21	34.44	54	19.56

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
2412.00	59.10	PK	96	2.0	H	33.92	93.02	/	/
2412.00	46.42	Ave.	96	2.0	H	33.92	80.34	/	/
2412.00	61.01	PK	152	1.1	V	33.92	94.93	/	/
2412.00	48.69	Ave.	152	1.1	V	33.92	82.61	/	/
2388.98	28.10	PK	248	2.4	V	33.92	62.02	74	11.98
2388.98	14.18	Ave.	248	2.4	V	33.92	48.10	54	5.90
2489.62	27.28	PK	68	1.5	V	34.08	61.36	74	12.64
2489.62	13.42	Ave.	68	1.5	V	34.08	47.50	54	6.50
4824.00	43.36	PK	140	2.3	V	5.84	49.20	74	24.80
4824.00	28.96	Ave.	140	2.3	V	5.84	34.80	54	19.20
Middle Channel (2442MHz)									
2442.00	59.10	PK	193	2.2	H	33.92	93.02	/	/
2442.00	46.42	Ave.	193	2.2	H	33.92	80.34	/	/
2442.00	60.83	PK	53	1.3	V	33.92	94.75	/	/
2442.00	48.53	Ave.	53	1.3	V	33.92	82.45	/	/
4884.00	43.21	PK	116	2.4	V	6.21	49.42	74	24.58
4884.00	28.47	Ave.	116	2.4	V	6.21	34.68	54	19.32
High Channel (2472 MHz)									
2472.00	60.06	PK	278	2.4	H	34.08	94.14	/	/
2472.00	48.35	Ave.	278	2.4	H	34.08	82.43	/	/
2472.00	63.97	PK	229	1.9	V	34.08	98.05	/	/
2472.00	51.78	Ave.	229	1.9	V	34.08	85.86	/	/
2341.57	27.69	PK	357	1.4	V	33.83	61.52	74	12.48
2341.57	14.15	Ave.	357	1.4	V	33.83	47.98	54	6.02
2483.63	38.69	PK	73	2.0	V	34.08	72.77	74	1.23
2483.63	18.02	Ave.	73	2.0	V	34.08	52.10	54	1.90
4944.00	44.30	PK	51	1.4	V	6.21	50.51	74	23.49
4944.00	30.50	Ave.	51	1.4	V	6.21	36.71	54	17.29

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
2412.00	56.41	PK	280	2.3	H	33.92	90.33	/	/
2412.00	46.25	Ave.	280	2.3	H	33.92	80.17	/	/
2412.00	58.19	PK	250	2.3	V	33.92	92.11	/	/
2412.00	48.12	Ave.	250	2.3	V	33.92	82.04	/	/
2379.89	26.76	PK	108	2.4	V	33.92	60.68	74	13.32
2379.89	13.12	Ave.	108	2.4	V	33.92	47.04	54	6.96
2495.63	27.11	PK	333	2.5	V	34.08	61.19	74	12.81
2495.63	13.34	Ave.	333	2.5	V	34.08	47.42	54	6.58
4824.00	43.74	PK	190	1.5	V	5.84	49.58	74	24.42
4824.00	29.85	Ave.	190	1.5	V	5.84	35.69	54	18.31
Middle Channel (2442MHz)									
2442.00	57.61	PK	325	1.2	H	33.92	91.53	/	/
2442.00	45.37	Ave.	325	1.2	H	33.92	79.29	/	/
2442.00	61.28	PK	23	1.4	V	33.92	95.20	/	/
2442.00	48.94	Ave.	23	1.4	V	33.92	82.86	/	/
4884.00	43.08	PK	189	1.3	V	6.21	49.29	74	24.71
4884.00	28.64	Ave.	189	1.3	V	6.21	34.85	54	19.15
High Channel (2472 MHz)									
2472.00	59.48	PK	356	1.8	H	34.08	93.56	/	/
2472.00	47.23	Ave.	356	1.8	H	34.08	81.31	/	/
2472.00	62.61	PK	306	1.5	V	34.08	96.69	/	/
2472.00	50.11	Ave.	306	1.5	V	34.08	84.19	/	/
2341.57	27.84	PK	322	2.2	V	33.83	61.67	74	12.33
2341.57	14.15	Ave.	322	2.2	V	33.83	47.98	54	6.02
2484.65	36.31	PK	112	1.6	V	34.08	70.39	74	3.61
2484.65	16.78	Ave.	112	1.6	V	34.08	50.86	54	3.14
4944.00	43.89	PK	59	2.4	V	6.21	50.10	74	23.90
4944.00	29.97	Ave.	59	2.4	V	6.21	36.18	54	17.82

For BLE mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2402 MHz)									
2402.00	53.45	PK	289	2.3	H	33.92	87.37	/	/
2402.00	47.54	Ave.	289	2.3	H	33.92	81.46	/	/
2402.00	56.47	PK	323	1.8	V	33.92	90.39	/	/
2402.00	50.53	Ave.	323	1.8	V	33.92	84.45	/	/
2375.37	28.02	PK	213	1.1	V	33.92	61.94	74	12.06
2375.37	14.17	Ave.	213	1.1	V	33.92	48.09	54	5.91
2499.80	28.09	PK	358	1.3	V	34.08	62.17	74	11.83
2499.80	13.64	Ave.	358	1.3	V	34.08	47.72	54	6.28
4804.00	43.48	PK	179	1.3	V	5.84	49.32	74	24.68
4804.00	29.30	Ave.	179	1.3	V	5.84	35.14	54	18.86
Middle Channel (2440 MHz)									
2440.00	55.95	PK	169	1.1	H	33.92	89.87	/	/
2440.00	49.36	Ave.	169	1.1	H	33.92	83.28	/	/
2440.00	57.45	PK	137	1.1	V	33.92	91.37	/	/
2440.00	51.45	Ave.	137	1.1	V	33.92	85.37	/	/
4880.00	44.47	PK	308	2.4	V	6.21	50.68	74	23.32
4880.00	29.38	Ave.	308	2.4	V	6.21	35.59	54	18.41
High Channel (2480 MHz)									
2480.00	57.46	PK	138	1.3	H	34.08	91.54	/	/
2480.00	46.80	Ave.	138	1.3	H	34.08	80.88	/	/
2480.00	57.96	PK	204	1.9	V	34.08	92.04	/	/
2480.00	46.94	Ave.	204	1.9	V	34.08	81.02	/	/
2375.37	28.36	PK	9	2.0	V	33.92	62.28	74	11.72
2375.37	14.20	Ave.	9	2.0	V	33.92	48.12	54	5.88
2486.34	27.56	PK	39	1.8	V	34.08	61.64	74	12.36
2486.34	13.82	Ave.	39	1.8	V	34.08	47.90	54	6.10
4960.00	43.70	PK	94	1.2	V	7.82	51.52	74	22.48
4960.00	29.52	Ave.	94	1.2	V	7.82	37.34	54	16.66

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor



Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude



The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.


Pre-scan with PK 802.11n-20 Mode, High channel
Horizontal




Vertical



**Pre-scan with Average 802.11n-20 Mode, high channel
Horizontal**



Vertical



***** END OF REPORT *****