



# **TEST REPORT**

Applicant	LT Security Inc				
Address	17333 Freedom Way, City of Industry, CA 91748. USA				
Manufacturer or Supplier	LT Security Inc				
Address	17333 Freedom Way, City of Indust	ry, CA 91748. USA			
Product	Mifare Card Reader with Keypad				
Brand Name	LTS				
Model	LTK1107MK				
Additional Model & Model Difference	nce N/A				
Date of tests	tests Apr. 01 2019 to Apr. 19, 2019				
the tests have been	carried out according to the requirer	nents of the following standards:			
SFCC Part 15, S	FCC Part 15, Subpart C, Section 15.225				
CONCLUSION: The submitted sample was found to <u>COMPLY</u> with the test requirement					
Tes Project En	Tested by Lucas ChenApproved by Glyn HeProject Engineer / EMC DepartmentAssistant Manager / EMC Department				

ucar

Aug

Date: Sep. 29, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <a href="https://www.cps.bureauveritas.com/terms-conditions">https://www.cps.bureauveritas.com/terms-conditions</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or or mission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China. Tel.: +86 769 8998 2098 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@bureauveritas.com</u>



# TABLE OF CONTENTS

RE	ELEAS	SE CONTROL RECO	RD			4
1	SU	MMARY OF TEST R	ESULTS			5
2	ME	ASUREMENT UNCE	RTAINTY			5
3	GE		ON			6
	3.1	GENERAL DESCRIP	TION OF EUT			6
	3.2	DESCRIPTION OF T	EST MODES			7
	3.2	.1. CONFIGURATIO	ON OF SYSTEM UNDER TEST			7
	3.2	.2. TEST MODE AF	PLICABILITY AND TESTED CHANN	NEL DI	ETAIL	7
	3.3	GENERAL DESCRIP	TION OF APPLIED STANDARDS			9
	3.4	DESCRIPTION OF S	JPPORT UNITS			9
4	TE	ST TYPES AND RES	ULTS			10
	4.1.	RADIATED EMISS	ION AND BANDEDGE MEASUREM	ENT		10
	4.2	.1 LIMITS OF RAD	IATED EMISSION AND BANDEDGE	E MEA	SUREMENT	10
	4.2	.2 TEST INSTRUM	ENTS			11
	4.2	.3 TEST PROCED	JRES			12
	4.2	.4 DEVIATION FRO	OM TEST STANDARD			12
	4.2	.5 TEST SETUP				13
	4.2	.6 EUT OPERATIN	G CONDITIONS			14
	4.2	.7 TEST RESULTS				14
	4.2.	FREQUENCY TOL	ERANCE			18
	4.2	.1. LIMIT OF FREQ	UENCY TOLERANCE			18
	4.2	.2. TEST INSTRUM	ENTS			18
	4.2	.3. TEST PROCED	JRES			19
	4.2	.4. DEVIATION FRO	OM TEST STANDARD			19
	4.2	.5. TEST SETUP				19
	4.2	.6. EUT OPERATIN	G CONDITIONS			20
	4.2	.7. TEST RESULTS				20
	4.3.	20DB BANDWIDTH	١			21
	4.3	.1 LIMITS OF 20D	3 BANDWIDTH			21
	4.3	.2 TEST INSTRUM	ENTS			21
	4.3	.3 TEST PROCED	JRE			22
	4.3	.4 DEVIATION FRO	OM TEST STANDARD			22
	4.3	.5 TEST SETUP				22
	4.3	.6 EUT OPERATIN	G CONDITION			23
	4.3	.7 TEST RESULTS				23
5.	PH	OTOGRAPHS OF TH	IE TEST CONFIGURATION			24
ureau Veri ongguan E	tas She Branch	enzhen Co., Ltd.	No. 96, Guantai Road (Houjie Section), H Town, Dongguan City, Guangdong Provin 523942. People's Republic of China.	oujie nce.	Tel.: +86 769 8998 2098 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@l</u>	<u>oureauveritas.com</u>



6.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE
EUT	BY THE LAB



# **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2109WDG0116	Original release	Sep. 29, 2021



# 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C						
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK			
15.207	AC Power Conducted Emission	N/A	Power by DC 12V			
15.225 (a)&(b)&(c)	The field strength of any emissions within the band	PASS	Meet the requirement of limit.			
15.225 (d)	The field strength of any emissions appearing outside of the 13.110-14.010 MHz band	PASS	Meet the requirement of limit.			
15.225 (e)	Frequency tolerance	PASS	Meet the requirement of limit.			
15.215 (c)	20dB Bandwidth	PASS	Meet the requirement of limit.			
15.203	Antenna Requirement	PASS	No antenna connector is used.			

Test Lab : Bureau Veritas ( Shenzhen ) Consumer products Service Co. Ltd.

Test Lab Address: Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District Shenzhen, Guangdong, 518108, People's Republic of China.

## 2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY	
Conducted emissions	9kHz~30MHz	3.11dB	
	9KHz ~ 30MHz	3.11dB	
Radiated emissions	30MHz ~ 1GMHz	5.12dB	
Tadiated emissions	1GHz ~ 18GHz	5.34dB	
	18GHz ~ 40GHz	5.20dB	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



## **3 GENERAL INFORMATION**

## 3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mifare Card Reader with Keypad
MODEL NO.	LTK1107MK
ADDITIONAL MODEL	N/A
FCC ID	2A2TG-LTK1107MK
POWER SUPPLY	DC 12V
MODULATION TECHNOLOGY	NFC
MODULATION TYPE	ASK
OPERATING FREQUENCY	13.56MHz
NUMBER OF CHANNEL	1
ANTENNA TYPE	Coil Antenna
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	Unshielded, Non-Detachable 120cm with one Core

## NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

- 2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- 3. Please refer to the EUT photo document for detailed product photo.

Tel.: +86 769 8998 2098

Fax: +86 769 8593 1080



### 3.2 DESCRIPTION OF TEST MODES

The EUT only have one channel.

CHANNEL	FREQUENCY (MHz)
1	13.56

## 3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

## 3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case was found when positioned on X/Y axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DECODIDITION
	RE	FT	PLC	BW	DESCRIPTION
А	$\checkmark$	$\checkmark$	-	$\checkmark$	DC 12V

Where **RE:** Radiated Emission

PLC: Power Line Conducted Emission

FT: Frequency tolerance BW: 20dB Bandwidth

#### **RADIATED EMISSION TEST:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
А	1	13.56	ASK	X/Y

Tel.: +86 769 8998 2098

Fax: +86 769 8593 1080



#### **FREQUENCY TOLERANCE:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
А	1	13.56	ASK	Х

#### POWER LINE CONDUCTED EMISSION TEST:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
А	1	13.56	ASK	х

#### 20dB BANDWIDTH:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL	TESTED FREQUENCY (MHZ)	MODULATION TYPE	AXIS
А	1	13.56	ASK	Х



#### **TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE	23deg. C, 59%RH	DC 12V	Simon
FT	25deg. C, 60%RH	DC 12V	Aaron Liang
BW	25deg. C, 60%RH	DC 12V	Aaron Liang

#### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

## FCC Part 15, Subpart C. Section 15.225 ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

**NOTE:** 1. All test items have been performed and recorded as per the above standards.

2. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (sDOC). The test report has been issued separately.

## 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as a dependent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Valve Regulated Lead-Acid Battery	Panasonic	UP-RW1228ST1	N/A	N/A

NO.	DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	-

Tel.: +86 769 8998 2098



## 4 TEST TYPES AND RESULTS

## 4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT

## 4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

The field strength of any emissions shall not exceed the following limits:

- (a)15.848mV/m(84dBuV/m) at 30m, within the band 13.553-13.567 MHz;
- (b)334uV/m(50.5dBuV/m) at 30m, within the band 13.410-13.553 MHz and 13.567-13.710MHz;
- (c)106uV/m(40.5dBuV/m) at 30m, within the band 13.110-13.410 MHz and 13.710-14.010MHz;

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- 4. The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example: 13.56MHz = 15848uV/m = 84dBuV/m = 84+20log(30/3)<sup>2</sup>

= 124dBuV/m

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

30m

30m 3m



### 4.2.2 TEST INSTRUMENTS

#### 9KHz~30MHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwar z	ESL6	1300.5001K06 -100262-eQ	Jan. 04, 19	Jan. 03, 20
Active Antenna	CMO-POWER	AL-130	121031	Feb. 07, 19	Feb. 06, 20
3m Semi-anechoic Chamber	SAEMC	9m*6m*6m	N/A	Oct. 18,18	Oct. 17,19
Test Software	EZ-EMC	ICP-03A1	N/A	N/A	N/A

#### 30MHz~1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESL6	1300.5001K06-1 00262-eQ	Jan. 05, 19	Jan. 04, 20
Bilog Antenna	Sunol Sciences	JB6	A110712	Feb. 08, 19	Feb. 07, 20
Signal Amplifier	HP	8447E	443008	Jan. 25,19	Jan. 24,20
3m Semi-anechoic Chamber	SAEMC	9m*6m*6m	N/A	Oct. 19,18	Oct. 18,21
Test Software	EZ-EMC	ICP-03A1	N/A	N/A	N/A

NOTE:

1. The test was performed in 966 Chamber (a 3m Semi-anechoic chamber).

2. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

3. The horn antenna is used only for the measurement of emission frequency above1GHz if tested.

4. The FCC Site Registration No. is 749762.

Tel.: +86 769 8998 2098

Fax: +86 769 8593 1080



## 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.
- g. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

#### NOTE:

- 1. The resolution bandwidth of test receiver/spectrum analyzer is 200Hz for Quasi-peak detection (QP) at fundamental frequency 9K-150KHz;
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 9KHz for Quasi-peak detection (QP) at fundamental frequency 150K-30MHz;
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at radiated spurious emission frequency 30MHz-1GHz.

## 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch



#### 4.2.5 TEST SETUP

#### Below 30MHz test setup



#### Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch



### 4.2.6 EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.

#### 4.2.7 TEST RESULTS

#### FIELD STRENGTH (BELOW 30MHZ AT 3M)

#### Antenna polarity: 0°

	Freq.	Correction	Raw	Emission	Limit	Margin
No.	(MHz)	Factor	Value	Level	(dBuV/m)	(dB)
		(dB/m)	(dBuV)	(dBuV/m)		
*	13.56(QP)	20.74	44.71	65.45	124	-58.55
	27.12(QP)	21.75	35.88	57.63	69.5	-11.87

#### Antenna polarity: 90°

	Freq.	Correction	Raw	Emission	Limit	Margin
No.	(MHz)	Factor	Value	Level	(dBuV/m)	(dB)
		(dB/m)	(dBuV)	(dBuV/m)		
*	13.56(QP)	20.74	50.83	71.57	124	-52.43
	27.12(QP)	21.75	34.58	56.33	69.5	-13.17

**REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).

- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.
- 6. For the test results, both 0° and 90° polarizations of the antenna are set to make the measurement, but only the worst case was shown in test report.

Tel.: +86 769 8998 2098

Fax: +86 769 8593 1080







#### **BELOW 1GHz WORST-CASE DATA:**

CHANNEL	Channel 1	DETECTOR	Oursei Bask (OD)
FREQUENCY RANGE	9KHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
Frequency	Reading	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree		
	(MHz)	(dBuV/m)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)		
31.2893	26.13	19.27	22.27	0.14	23.27	40.00	-16.73	100	225		
166.6514	26.92	11.10	22.26	1.37	17.13	43.50	-26.37	100	118		
379.9141	26.15	15.68	22.07	1.90	21.66	46.00	-24.34	100	141		
528.2458	25.85	19.21	21.75	2.21	25.52	46.00	-20.48	100	317		
790.6188	26.93	22.11	21.17	2.54	30.41	46.00	-15.59	100	224		
909.6667	24.50	23.71	20.86	2.66	30.01	46.00	-15.99	100	347		



#### **REMARKS:**

- 1. Result (dBuV/m) = Reading Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor  $(dB/m) = Ant_F (dB/m) + Cab_L (dB) PA_G (dB)$ .
- 3. The emission levels of other frequencies were less than 20dB margin against the limit.
- 4. Margin value = Result level Limit value

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch



	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
Frequency	Reading	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree		
	(MHz)	(dBuV/m)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)		
31.2893	28.47	19.27	22.27	0.14	25.61	40.00	-14.39	100	91		
67.6751	34.79	6.64	22.39	0.32	19.36	40.00	-20.64	100	285		
99.8777	33.58	8.69	22.32	0.82	20.77	43.50	-22.73	100	53		
189.7385	31.84	11.38	22.31	1.50	22.41	43.50	-21.09	200	215		
508.2582	27.92	18.87	21.79	2.15	27.15	46.00	-18.85	100	16		
881.4067	27.80	23.08	20.93	2.64	32.59	46.00	-13.41	100	283		



#### **REMARKS:**

- 1. Result (dBuV/m) = Reading Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor  $(dB/m) = Ant_F (dB/m) + Cab_L (dB) PA_G (dB)$ .
- 3. The emission levels of other frequencies were less than 20dB margin against the limit.
- 4. Margin value = Result level Limit value



## 4.2. FREQUENCY TOLERANCE

### 4.2.1. LIMIT OF FREQUENCY TOLERANCE

The frequency tolerance of the carrier signal shall be maintained within  $\pm -0.01\%$  of the operating frequency over a temperature variation of -20 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

## 4.2.2. TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Digital Multimeter	FLUKE	15B	A1220010DG	Oct.20, 18	Oct.19, 19
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep. 04,18	Sep. 03,19
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 07,18	Nov. 06,19
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 03,18	Nov. 02,19
Spectrum Analyzer	Keysight	N9020A	MY55400499	Mar. 19,19	Mar. 18,20
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jan. 02,19	Jan. 01,20
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A	N/A
DC Source	Keysight	E3642A	MY56146098	N/A	N/A

#### NOTE:

1. The test was performed in RF Oven room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



## 4.2.3. TEST PROCEDURES

- a) The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- b) Turn the EUT on and couple its output to a spectrum analyzer.
- c) Turn the EUT off and set the chamber to the highest temperature specified.
- d) Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- e) Repeat step c) and d) with the temperature chamber set to the lowest temperature.
- f) The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

## 4.2.4. DEVIATION FROM TEST STANDARD

No deviation.

## 4.2.5. TEST SETUP



Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China. Tel.: +86 769 8998 2098 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@bureauveritas.com</u>



## 4.2.6. EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.

## 4.2.7. TEST RESULTS

FREQUEMCY STABILITY VERSUS TEMP.									
		0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
темр. (℃)	POWER SUPPLY (V)	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift
		(MHz)	%	(MHz)	%	(MHz)	%	(MHz)	%
50	120V/60Hz	13.559982	-0.00013	13.560006	0.00004	13.559974	-0.00019	13.559986	-0.0001
40	120V/60Hz	13.559967	-0.00024	13.559977	-0.00017	13.559993	-0.00005	13.559968	-0.00024
30	120V/60Hz	13.559993	-0.00005	13.560001	0.00001	13.559976	-0.00018	13.559971	-0.00021
20	120V/60Hz	13.559977	-0.00017	13.559976	-0.00018	13.559977	-0.00017	13.559997	-0.00002
10	120V/60Hz	13.559969	-0.00023	13.560006	0.00004	13.560005	0.00004	13.559987	-0.0001
0	120V/60Hz	13.559967	-0.00024	13.559989	-0.00008	13.559988	-0.00009	13.559984	-0.00012
-10	120V/60Hz	13.560003	0.00002	13.560005	0.00004	13.559997	-0.00002	13.560005	0.00004
-20	120V/60Hz	13.559992	-0.00006	13.559977	-0.00017	13.559982	-0.00013	13.559975	-0.00018

FREQUEMCY STABILITY VERSUS VOLTAGE									
		0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
<b>ТЕМР.</b> (℃)	POWER SUPPLY (V)	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift
		(MHz)	%	(MHz)	%	(MHz)	%	(MHz)	%
	102V/60Hz	13.559982	-0.00013	13.560006	0.00004	13.559974	-0.00019	13.559986	-0.0001
20	120V/60Hz	13.559967	-0.00024	13.559977	-0.00017	13.559993	-0.00005	13.559968	-0.00024
	138V/60Hz	13.559993	-0.00005	13.560001	0.00001	13.559976	-0.00018	13.559971	-0.00021

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch



## 4.3. 20dB BANDWIDTH

#### 4.3.1 LIMITS OF 20dB BANDWIDTH

The 20dB bandwidth shall be specified in operating frequency band.(13.11MHz – 14.01MHz)

#### 4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Digital Multimeter	FLUKE	15B	A1220010DG	Oct.20, 18	Oct.19, 19
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep. 04,18	Sep. 03,19
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 07,18	Nov. 06,19
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 03,18	Nov. 02,19
Spectrum Analyzer	Keysight	N9020A	MY55400499	Mar. 19,19	Mar. 18,20
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jan. 02,19	Jan. 01,20
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A	N/A
DC Source	Keysight	E3642A	MY56146098	N/A	N/A

#### NOTE:

- 1. The test was performed in RF Oven room.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



#### 4.3.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

## 4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

## 4.3.5 TEST SETUP





## 4.3.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously.

## 4.3.7 TEST RESULTS

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (KHz)	
1	13.56	28.1	

Lower & Upper Test Frequency Point (MHz)	Test Frequency (MHz)	P/F
Lower	13.5461	PASS
Upper	13.5742	PASS



Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel.: +86 769 8998 2098 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@bureauveritas.com</u>



## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END----