ACCREDITED
Certificate # 3939.01

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland

Manufacturer or Supplier:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland
Product:	GSM/WCDMA/LTE Mobile Phone
Brand Name:	Nokia
Model Name:	TA-1282
FCC ID:	2AJOTTA-1282
Date of tests:	Jun. 30, 2020 ~ Jul. 20, 2020

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2013**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Alex Chen	Approved by Luke Lu
Engineer / Mobile Department	Manager / Mobile Department
Alex	Luke Lu
Date: Jul. 20, 2020	Date: Jul. 20, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 5
1 SUMMARY OF TEST RESULTS 6
1.1 MEASUREMENT UNCERTAINTY 6
2 GENERAL INFORMATION 7
2.1 GENERAL DESCRIPTION OF EUT 7
2.2 DESCRIPTION OF TEST MODES 8
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST 9
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 9
2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 11
2.4 DESCRIPTION OF SUPPORT UNITS 11
3 TEST TYPES AND RESULTS 12
3.1 CONDUCTED EMISSION MEASUREMENT 12
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 12
3.1.2 TEST INSTRUMENTS 12
3.1.3 TEST PROCEDURES 12
3.1.4 DEVIATION FROM TEST STANDARD 13
3.1.5 TEST SETUP 13
3.1.6 EUT OPERATING CONDITIONS 13
3.1.7 TEST RESULTS 14
3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT 16
3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 16
3.2.2 TEST INSTRUMENTS 17
3.2.3 TEST PROCEDURES 18
3.2.4 DEVIATION FROM TEST STANDARD 18
3.2.5 TEST SETUP 19
3.2.6 EUT OPERATING CONDITIONS 20
3.2.7 TEST RESULTS 21
3.3 NUMBER OF HOPPING FREQUENCY USED 29
3.3.1 LIMIT OF HOPPING FREQUENCY USED 29
3.3.2 TEST SETUP 29
3.3.3 TEST INSTRUMENTS 29
3.3.4 TEST PROCEDURES 30
3.3.5 DEVIATION FROM TEST STANDARD 30
3.3.6 TEST RESULTS 30
3.4 DWELL TIME ON EACH CHANNEL 34

3.4.1 LIMIT OF DWELL TIME USED 34
3.4.2 TEST SETUP 34
3.4.3 TEST INSTRUMENTS 34
3.4.4 TEST PROCEDURES 34
3.4.5 DEVIATION FROM TEST STANDARD 35
3.4.6 TEST RESULTS 35
3.5 CHANNEL BANDWIDTH 41
3.5.1 LIMITS OF CHANNEL BANDWIDTH 41
3.5.2 TEST SETUP 41
3.5.3 TEST INSTRUMENTS 41
3.5.4 TEST PROCEDURE 41
3.5.5 DEVIATION FROM TEST STANDARD 41
3.5.6 EUT OPERATING CONDITION 42
3.5.7 TEST RESULTS 42
3.6 HOPPING CHANNEL SEPARATION 48
3.6.1 LIMIT OF HOPPING CHANNEL SEPARATION 48
3.6.2 TEST SETUP 48
3.6.3 TEST INSTRUMENTS 48
3.6.4 TEST PROCEDURES 48
3.6.5 DEVIATION FROM TEST STANDARD 48
3.6.6 TEST RESULTS 49
3.7 MAXIMUM OUTPUT POWER 55
3.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT 55
3.7.2 TEST SETUP 55
3.7.3 TEST INSTRUMENTS 55
3.7.4 TEST PROCEDURES 55
3.7.5 DEVIATION FROM TEST STANDARD 55
3.7.6 EUT OPERATING CONDITION 55
3.7.7 TEST RESULTS 56
3.7.7.1 MAXIMUM PEAK OUTPUT POWER 56
3.7.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE) 57
3.8 OUT OF BAND MEASUREMENT 58
3.8.1 LIMITS OF OUT OF BAND MEASUREMENT 58
3.8.2 TEST INSTRUMENTS 58
3.8.3 TEST PROCEDURE 58
3.8.4 DEVIATION FROM TEST STANDARD 58

3.8.5 EUT OPERATING CONDITION..... 58
3.8.6 TEST RESULTS..... 58
4 PHOTOGRAPHS OF THE TEST CONFIGURATION..... 65
5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB..... 66

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF200629W001-1	Original release	Jul. 20, 2020

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C		
STANDARD	**TEST TYPE AND LIMIT**	**RESULT**
15.207	AC Power Conducted Emission	Compliance
15.247(a)(1) (iii)	Number of Hopping Frequency Used	Compliance
15.247(a)(1) (iii)	Dwell Time on Each Channel	Compliance
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	Compliance
15.247(b)	Maximum Peak Output Power	Compliance
15.247(d)& 15.209	Transmitter Radiated Emissions	Compliance
15.247(d)	Out of band Measurement	Compliance
15.203	Antenna Requirement	Compliance

NOTE: If the Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (30MHz~1GMHz)	±4.98dB
Radiated emissions (1GMHz ~6GMHz)	±4.70dB
Radiated emissions (6GMHz ~18GMHz)	±4.60dB
Radiated emissions (18GMHz ~40GMHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	GSM/WCDMA/LTE Mobile Phone
BRAND NAME	Nokia
MODEL NAME	TA-1282
NOMINAL VOLTAGE	5.0Vdc (adapter or host equipment) 3.7Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, π/4 DQPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	11.61mW (Max. Measured)
ANTENNA TYPE	PCB Antenna with 0dBi gain
HW VERSION	0154
SW VERSION	0.2025.11.05
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable: non-shielded, detachable,1meter Earphone: non-shielded, detachable, 1.5meter

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

List of Accessory:

ACCESSORIES	BRAND	MODEL	MANUFACTURER	SPECIFICATION
Battery 1	Nokia	BL-4WL	TM	Power Rating:3.7 Vdc, 1150 mAh
AC Adapter 1	Nokia	AC-18U	DVE	I/P: 100 - 240 Vac, 100mA, O/P: 5Vdc, 550 mA
AC Adapter 2	Nokia	AC-18U	Aohai	I/P: 100 - 240 Vac, 100mA, O/P: 5Vdc, 550 mA
Earphone 1	Nokia	WH-108	RTF	1.5m non-shielded cable w/ core
USB Cable 1	Nokia	CA-190CD	RTF	1m non-shielded cable w/ core

2.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.
The worst case was found when positioned on X axis for radiated emission.
Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G:** Radiated Emission below 1GHz **RE≥1G:** Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0	FHSS	GFSK	DH5

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	78	FHSS	GFSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH1/DH3/DH5
0 to 78	0, 39, 78	FHSS	π/4 DQPSK	2DH1/2DH3/2DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH1/3DH3/3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	23deg. C, 70%RH	DC 5V By Adapter	Jacky Liu
RE≥1G	23deg. C, 70%RH	DC 5V By Adapter	Jacky Liu
PLC	25deg. C, 52%RH	DC 5VBy Adapter	Chase Zhou
APCM	25deg. C, 60%RH	DC 3.7V By Battery	Kevin Zhang

2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247
ANSI C63.10-2013

NOTE: 1. All test items have been performed and recorded as per the above standards.

2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Desktop	Lenovo	M73 SFF	PC04GRQV	N/A
2	Desktop	Lenovo	M73 SFF	PC06CS27	N/A
3	Laptop	Lenovo	Thnikpad L440	R90FTFKN	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Feb. 26,20	Feb. 25,21
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Feb. 26,20	Feb. 25,21

NOTE: 1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

3.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

a. Turned on the power and connected of all equipment.
b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Chase Zhou		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154000	---	30.54	55.78	-25.24	L	ON	9.7
0.154000	44.26	---	65.78	-21.52	L	ON	9.7
0.376000	---	26.52	48.37	-21.85	L	ON	9.7
0.376000	38.83	---	58.37	-19.54	L	ON	9.7
1.176000	---	24.85	46.00	-21.15	L	ON	9.7
1.176000	34.71	---	56.00	-21.29	L	ON	9.7
1.876000	---	29.49	46.00	-16.51	L	ON	9.8
1.876000	38.82	---	56.00	-17.18	L	ON	9.8
2.540000	---	29.83	46.00	-16.17	L	ON	9.8
2.540000	38.24	---	56.00	-17.76	L	ON	9.8
3.616000	---	27.28	46.00	-18.72	L	ON	9.8
3.616000	36.34	---	56.00	-19.66	L	ON	9.8

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Chase Zhou		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.360000	---	36.19	48.73	-12.54	N	ON	9.8
0.360000	44.49	---	58.73	-14.23	N	ON	9.8
0.768000	---	28.31	46.00	-17.69	N	ON	9.8
0.768000	40.00	---	56.00	-16.00	N	ON	9.8
1.048000	---	28.93	46.00	-17.07	N	ON	9.8
1.048000	41.71	---	56.00	-14.29	N	ON	9.8
2.128000	---	35.45	46.00	-10.55	N	ON	9.8
2.128000	**45.72**	**---**	**56.00**	**-10.28**	**N**	**ON**	**9.8**
2.140000	---	33.78	46.00	-12.22	N	ON	9.8
2.140000	44.78	---	56.00	-11.22	N	ON	9.8
3.858000	---	30.31	46.00	-15.69	N	ON	9.9
3.858000	40.04	---	56.00	-15.96	N	ON	9.9

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Mar. 27,20	Mar. 26,21
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 24, 19	Nov. 23, 20
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Nov. 24, 19	Nov. 23, 20
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jun. 03,20	Jun. 02,21
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Apr. 27,20	Apr. 26,21
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 02,20	Jun. 01,21
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 02,20	Jun. 01,21
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Apr. 30,20	Apr. 29,21

NOTE: 1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Chamber.

3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

3.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD

No deviation.

3.2.5 TEST SETUP

< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

a. Set the EUT under full load condition and placed them on a testing table.

b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.

c. The necessary accessories enable the EUT in full functions.

3.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:

GFSK

CHANNEL	Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
31.94	32.11	48.96	40	-7.89	19.93	0.8	37.58	100	0	Peak
97.9	24.35	51.11	43.5	-19.15	8.93	1.3	36.99	100	0	Peak
165.8	25.31	49.91	43.5	-18.19	10.47	1.67	36.74	100	0	Peak
321	22.47	42.55	46	-23.53	14.27	2.3	36.65	100	0	Peak
422.85	26.21	43.02	46	-19.79	17.35	2.7	36.86	100	0	Peak
486.87	22.49	37.66	46	-23.51	18.88	2.94	36.99	100	0	Peak

REMARKS:

1. Emission Level(dBuV/m) = Read Level(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



CHANNEL	Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
30	31.71	47.64	40	-8.29	20.9	0.77	37.6	200	0	Peak
96.93	22.54	49.38	43.5	-20.96	8.85	1.3	36.99	200	0	Peak
165.8	18.69	43.29	43.5	-24.81	10.47	1.67	36.74	200	0	Peak
322.94	18.96	38.99	46	-27.04	14.33	2.3	36.66	200	0	Peak
422.85	24.12	40.93	46	-21.88	17.35	2.7	36.86	200	0	Peak
486.87	24.09	39.26	46	-21.91	18.88	2.94	36.99	200	0	Peak

REMARKS:

1. Emission Level(dBuV/m) = Read Level(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

GFSK

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	54.11	62.7	74	-19.89	32.56	4.88	46.03	105	0	Peak
2390	41.86	50.45	54	-12.14	32.56	4.88	46.03	105	0	Average
2402	101.85	110.42			32.56	4.89	46.02	105	0	Peak
2402	99.84	108.41			32.56	4.89	46.02	105	0	Average
2483.5	52.96	61.37	74	-21.04	32.59	4.98	45.98	105	0	Peak
2483.5	42.26	50.67	54	-11.74	32.59	4.98	45.98	105	0	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	**EMISSION LEVEL (dBuV/m)**	**READ LEVEL (dBuV)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA FACTOR (dB /m)**	**CABLE LOSS (dB)**	**PREAMP FACTOR (dB)**	**ANTENNA HEIGHT (cm)**	**TABLE ANGLE (Degree)**	**REMARK**
2390	56.61	65.2	74	-17.39	32.56	4.88	46.03	150	200	Peak
2390	42.61	51.2	54	-11.39	32.56	4.88	46.03	150	200	Average
2402	97.77	106.34			32.56	4.89	46.02	150	200	Peak
2402	96.65	105.22			32.56	4.89	46.02	150	200	Average
2483.5	53.84	62.25	74	-20.16	32.59	4.98	45.98	150	200	Peak
2483.5	43.3	51.71	54	-10.7	32.59	4.98	45.98	150	200	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	53.04	61.63	74	-20.96	32.56	4.88	46.03	100	0	Peak
2390	42.19	50.78	54	-11.81	32.56	4.88	46.03	100	0	Average
2441	99.41	107.89			32.58	4.94	46	100	0	Peak
2441	97.64	106.12			32.58	4.94	46	100	0	Average
2483.5	54.01	62.42	74	-19.99	32.59	4.98	45.98	100	0	Peak
2483.5	42.58	50.99	54	-11.42	32.59	4.98	45.98	100	0	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.6	61.19	74	-21.4	32.56	4.88	46.03	100	200	Peak
2390	41.73	50.32	54	-12.27	32.56	4.88	46.03	100	200	Average
2441	96.53	105.01			32.58	4.94	46	100	200	Peak
2441	94.09	102.57			32.58	4.94	46	100	200	Average
2483.5	53.48	61.89	74	-20.52	32.59	4.98	45.98	100	200	Peak
2483.5	42.26	50.67	54	-11.74	32.59	4.98	45.98	100	200	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2441MHz: Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.51	61.1	74	-21.49	32.56	4.88	46.03	100	0	Peak
2390	42.66	51.25	54	-11.34	32.56	4.88	46.03	100	0	Average
2480	98.86	107.27			32.59	4.98	45.98	100	0	Peak
2480	96.94	105.35			32.59	4.98	45.98	100	0	Average
2483.5	58.35	66.76	74	-15.65	32.59	4.98	45.98	100	0	Peak
2483.5	42.26	50.67	54	-11.74	32.59	4.98	45.98	100	0	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	55.95	64.54	74	-18.05	32.56	4.88	46.03	100	200	Peak
2390	42.03	50.62	54	-11.97	32.56	4.88	46.03	100	200	Average
2480	96.34	104.75			32.59	4.98	45.98	100	200	Peak
2480	94.27	102.68			32.59	4.98	45.98	100	200	Average
2483.5	63.2	71.61	74	-10.8	32.59	4.98	45.98	100	200	Peak
2483.5	42.82	51.23	54	-11.18	32.59	4.98	45.98	100	200	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.

8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	53.77	62.36	74	-20.23	32.56	4.88	46.03	105	0	Peak
2390	42.3	50.89	54	-11.7	32.56	4.88	46.03	105	0	Average
2402	102.74	111.31			32.56	4.89	46.02	105	0	Peak
2402	98.24	106.81			32.56	4.89	46.02	105	0	Average
2483.5	53.3	61.71	74	-20.7	32.59	4.98	45.98	105	0	Peak
2483.5	42.22	50.63	54	-11.78	32.59	4.98	45.98	105	0	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	55.58	64.17	74	-18.42	32.56	4.88	46.03	100	200	Peak
2390	42.08	50.67	54	-11.92	32.56	4.88	46.03	100	200	Average
2402	97.55	106.12			32.56	4.89	46.02	100	200	Peak
2402	93.04	101.61			32.56	4.89	46.02	100	200	Average
2483.5	52.57	60.98	74	-21.43	32.59	4.98	45.98	100	200	Peak
2483.5	42.37	50.78	54	-11.63	32.59	4.98	45.98	100	200	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.18	60.77	74	-21.82	32.56	4.88	46.03	120	0	Peak
2390	42.19	50.78	54	-11.81	32.56	4.88	46.03	120	0	Average
2441	99.73	108.21			32.58	4.94	46	120	0	Peak
2441	95.2	103.68			32.58	4.94	46	120	0	Average
2483.5	54.19	62.6	74	-19.81	32.59	4.98	45.98	120	0	Peak
2483.5	42.26	50.67	54	-11.74	32.59	4.98	45.98	120	0	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.84	61.43	74	-21.16	32.56	4.88	46.03	100	200	Peak
2390	42.1	50.69	54	-11.9	32.56	4.88	46.03	100	200	Average
2441	97.17	105.65			32.58	4.94	46	100	200	Peak
2441	93.29	101.77			32.58	4.94	46	100	200	Average
2483.5	52.95	61.36	74	-21.05	32.59	4.98	45.98	100	200	Peak
2483.5	42.49	50.9	54	-11.51	32.59	4.98	45.98	100	200	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2441MHz: Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.66	61.25	74	-21.34	32.56	4.88	46.03	100	0	Peak
2390	41.74	50.33	54	-12.26	32.56	4.88	46.03	100	0	Average
2480	99.41	107.82			32.59	4.98	45.98	100	0	Peak
2480	94.37	102.78			32.59	4.98	45.98	100	0	Average
2483.5	59.22	67.63	74	-14.78	32.59	4.98	45.98	100	0	Peak
2483.5	42.12	50.53	54	-11.88	32.59	4.98	45.98	100	0	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	52.24	60.83	74	-21.76	32.56	4.88	46.03	100	200	Peak
2390	41.53	50.12	54	-12.47	32.56	4.88	46.03	100	200	Average
2480	96.19	104.6			32.59	4.98	45.98	100	200	Peak
2480	91.91	100.32			32.59	4.98	45.98	100	200	Average
2483.5	63.3	71.71	74	-10.7	32.59	4.98	45.98	100	200	Peak
2483.5	42.95	51.36	54	-11.05	32.59	4.98	45.98	100	200	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.

3.3 NUMBER OF HOPPING FREQUENCY USED

3.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

3.3.2 TEST SETUP



3.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Feb. 26,20	Feb. 25,21
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510523	Mar. 10,20	Mar. 09,21
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	Jun. 03,20	Jun. 02,20
Power Sensor	ANRITSU	MA2411B	1339352	Feb. 26,20	Feb. 25,21
CBT32 BLUETOOTH TESTER 4HU	Rohde&Schwarz	CBT32	101176	Mar. 10,20	Mar. 09,21

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

3.3.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were completed.

3.3.5 DEVIATION FROM TEST STANDARD

No deviation.

3.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
Marker 1 [T1]
7.24 dBm
2.40200 GHz
Marker 2 [T1]
6.99 dBm
2.44200 GHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
Marker 1 [T1]
6.41 dBm
2.44300 GHz
Marker 2 [T1]
7.06 dBm
2.48000 GHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

8DPSK


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
Marker 1 [T1]
7.38 dBm
2.40200 GHz
Marker 2 [T1]
7.11 dBm
2.44200 GHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
Marker 1 [T1]
6.61 dBm
2.44300 GHz
Marker 2 [T1]
7.22 dBm
2.48000 GHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

π/4DQPSK


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
Marker 1 [T1]
7.19 dBm
2.40200 GHz
Marker 2 [T1]
7.15 dBm
2.44200 GHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 300 kHz
VBW 300 kHz
SWT 1 ms
[T1] MP VIEW
Marker 1 [T1]
6.62 dBm
2.44300 GHz
Marker 2 [T1]
7.34 dBm
2.48000 GHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

3.4 DWELL TIME ON EACH CHANNEL

3.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.4.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 TEST RESULTS

GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	51	322.32	0.465	149.88	400	PASS
DH3	79	31.6	5	25	158	1.72	271.76	400	PASS
DH5	79	31.6	5	16	101.12	2.975	300.83	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

GFSK

DH1





DH3





DH5





8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	5	50	316	0.459	145.04	400	PASS
3DH3	79	31.6	5	24	151.68	1.735	263.16	400	PASS
3DH5	79	31.6	5	16	101.12	2.965	299.82	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

8DPSK

3DH1





3DH3





3DH5





π/4DQPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
2DH1	79	31.6	5	48	303.36	0.447	135.6	400	PASS
2DH3	79	31.6	5	25	158	1.72	271.76	400	PASS
2DH5	79	31.6	5	14	88.48	2.95	261.02	400	PASS

Π/4DQPSK

2DH1	
	
2DH3	
	
2DH5	
	

3.5 CHANNEL BANDWIDTH

3.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.5.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.5.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.94
39	2441	0.94
78	2480	0.94

CH 0



CH 39


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
Marker 1 [T1]
-13.36 dBm
2.44052 GHz
Delta 2 [T1]
0.00 dB
940.00 kHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
D1 6.63 dBm
D2 -13.37 dBm
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
F1
F2
Center 2.441 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
Marker 1 [T1]
-13.40 dBm
2.47952 GHz
Delta 2 [T1]
0.00 dB
940.00 kHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
D1 6.59 dBm
D2 -13.41 dBm
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
F1
F2
Center 2.48 GHz
250 kHz/
Span 2.5 MHz

π/4 DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.30
39	2441	1.30
78	2480	1.29

CH 0



CH 39


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
Marker 1 [T1]
-14.80 dBm
2.44033 GHz
Delta 2 [T1]
0.00 dB
1.30 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
D1 5.19 dBm
D2 -14.81 dBm
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
F1
F2
Center 2.441 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
Marker 1 [T1]
-14.66 dBm
2.47934 GHz
Delta 2 [T1]
0.00 dB
1.29 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
D1 5.33 dBm
D2 -14.67 dBm
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
F1
F2
Center 2.48 GHz
250 kHz/
Span 2.5 MHz

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.30
39	2441	1.30
78	2480	1.32

CH 0



CH 39


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
Marker 1 [T1]
-14.73 dBm
2.44033 GHz
Delta 2 [T1]
0.00 dB
1.30 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
D1 5.26 dBm
D2 -14.74 dBm
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
F1
F2
Center 2.441 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 300 kHz
SWT 2.6 ms
[T1] MP VIEW
Marker 1 [T1]
-15.10 dBm
2.47932 GHz
Delta 2 [T1]
0.00 dB
1.32 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
D1 4.89 dBm
D2 -15.11 dBm
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
F1
F2
Center 2.48 GHz
250 kHz/
Span 2.5 MHz

3.6 HOPPING CHANNEL SEPARATION

3.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 TEST RESULTS

GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	0.94	0.63	PASS
39	2441	1.00	0.94	0.63	PASS
78	2480	1.00	0.94	0.63	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
6.20 dBm
2.44081 GHz
Delta 2 [T2]
0.10 dB
1.00 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
6.89 dBm
2.47881 GHz
Delta 2 [T1]
0.07 dB
1.00 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

8DPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.30	0.87	PASS
39	2441	1.00	1.30	0.87	PASS
78	2480	1.00	1.32	0.88	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
5.17 dBm
2.44097 GHz
Delta 2 [T2]
0.58 dB
1.00 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
5.37 dBm
2.47896 GHz
Delta 2 [T1]
0.03 dB
1.00 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

π/4DQPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.30	0.87	PASS
39	2441	1.00	1.30	0.87	PASS
78	2480	1.00	1.29	0.86	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
5.23 dBm
2.44097 GHz
Delta 2 [T2]
0.88 dB
1.00 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 2.667 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
5.44 dBm
2.47897 GHz
Delta 2 [T1]
0.33 dB
1.00 MHz
Ref 14.5 dBm
Att 20 dB
Offset 4.5 dB
14.5
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-85.5
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

3.7 MAXIMUM OUTPUT POWER

3.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

3.7.2 TEST SETUP



10dB ATTENUATION PAD

3.7.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.7.5 DEVIATION FROM TEST STANDARD

No deviation.

3.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.7.7 TEST RESULTS

3.7.7.1 MAXIMUM PEAK OUTPUT POWER

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	8.35	6.84	125	PASS
39	2441	8.66	7.35	125	PASS
78	2480	8.87	7.71	125	PASS

π/4 DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	9.87	9.71	125	PASS
39	2441	9.94	9.86	125	PASS
78	2480	10.53	11.30	125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	9.79	9.53	125	PASS
39	2441	10.42	11.02	125	PASS
78	2480	10.65	**11.61**	125	PASS

3.7.7.2 Average Output Power (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	7.67	N/A
39	2441	7.64	N/A
78	2480	7.92	N/A

π/4 DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	7.19	N/A
39	2441	7.24	N/A
78	2480	7.43	N/A

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	7.41	N/A
39	2441	7.33	N/A
78	2480	7.62	N/A

3.8 OUT OF BAND MEASUREMENT

3.8.1 LIMITS OF OUT OF BAND MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

3.8.2 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

3.8.4 DEVIATION FROM TEST STANDARD

No deviation.

3.8.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

GFSK

Hopping disabled Low Channel





Hopping disabled_High Channel





Hopping enabled Low Channel





Hopping enabled_High Channel





8DPSK

Hopping disabled Low Channel





Hopping disabled_High Channel





Hopping enabled Low Channel





Hopping enabled_High Channel





π/4DQPSK

Hopping disabled Low Channel





Hopping disabled_High Channel





Hopping enabled Low Channel





Hopping enabled_High Channel





4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---