

RF Exposure Evaluation

LIMIT

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

EVALUATION METHOD

Transmission formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW, **G** = gain of antenna in linear scale;

Pi = 3.1416, **R** = distance between observation point and center of the radiator in cm

TEST RESULT

Passed **Not Applicable**

Type	Conducted Power (dBm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
BLE	4.2	0.0008	1.00	Pass
WCDMA B2	24.5	0.0706	1.00	Pass
WCDMA B5	24.5	0.1119	0.56	Pass
LTE B2	24.0	0.1023	1.00	Pass
LTE B4	24.0	0.1023	1.00	Pass
LTE B5	24.0	0.1023	0.56	Pass
LTE B12	24.0	0.1023	0.47	Pass

Consider the BT and LTE can transmitting simultaneously, the total transmitting MPE rate as below formula:

MPE rate = Power density of BT/limit + Power density of LTE/limit < 1

The worst case is BT and LTE B12 transmitting simultaneously, the result as below:

Evaluation mode	Power density/limit	Sum of the MPE rate	limit
BLE	0.0008	0.2185	1
LTE	0.2177		

Note:

- 1) The exposure evaluation safety distance is 20cm.