



FCC TEST REPORT

FCC ID: 2AP2N-AS3-C04

On Behalf of

Shenzhen Esorun Technology Co., LTD

Magnetic Wireless Charger

Model No.: MagQoo AS3, Maghold C04

Prepared for : Shenzhen Esorun Technology Co., LTD
Address : Room 226, Building A, B, C, Zone B, Yuanfen Industrial Zone, Taoyuan
Community, Dalang Street, Longhua District, Shenzhen

Prepared By : Shenzhen PSI Testing Co., Ltd.
Address : 1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road,
Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number : psi2406038-C01-R05
Date of Receipt : June 17, 2024
Date of Test : June 17, 2024-June 26, 2024
Date of Report : June 27, 2024
Version Number : V0

TABLE OF CONTENTS

	<u>Description</u>	<u>Page</u>
1.	Test Result Summary	5
2.	General Information	6
	2.1. DESCRIPTION OF DEVICE (EUT)	6
	2.2. ACCESSORIES OF DEVICE (EUT)	7
	2.3. TESTED SUPPORTING SYSTEM DETAILS	7
	2.4. BLOCK DIAGRAM OF CONNECTION BETWEEN EUT AND SIMULATORS	7
	2.5. DESCRIPTION OF TEST MODES	7
	2.6. TEST CONDITIONS	7
	2.7. TEST FACILITY	8
	2.8. MEASUREMENT UNCERTAINTY	8
	2.9. TEST EQUIPMENT LIST	9
3.	Test Results and Measurement Data	10
	3.1. CONDUCTED EMISSION	10
	3.2. RADIATED SPURIOUS EMISSION MEASUREMENT	16
	3.3. TEST SPECIFICATION	28
4.	Photos of test setup	31
5.	Photos of EUT	31

TEST REPORT DECLARATION

Applicant : Shenzhen Esorun Technology Co., LTD
Address : Room 226, Building A, B, C, Zone B, Yuanfen Industrial Zone, Taoyuan
Community, Dalang Street, Longhua District, Shenzhen
Manufacturer : Shenzhen Esorun Technology Co., LTD
Address : Room 226, Building A, B, C, Zone B, Yuanfen Industrial Zone, Taoyuan
Community, Dalang Street, Longhua District, Shenzhen
EUT Description : Magnetic Wireless Charger
(A) Model No. : MagQoo AS3, Maghold C04
(B) Trademark : ESORUN


Measurement Standard Used:

FCC CFR Title 47 Part 15 Subpart C

ANSI C63.10:2013

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC CFR Title 47 Part 15 Subpart C requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....: Felix Pang
Test Engineer 

Approved by (name + signature).....: Simple Guan
Project Manager 

Date of issue.....: June 27, 2024

Revision History

Revision	Issue Date	Revisions	Revised By
V0	June 27, 2024	Initial released Issue	Felix Pang

1. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Spurious Emission	§15.209	PASS
Occupied Bandwidth	§15.215 (c)	PASS

Note:

1. *PASS: Test item meets the requirement.*
2. *Fail: Test item does not meet the requirement.*
3. *N/A: Test case does not apply to the test object.*
4. *The test result judgment is decided by the limit of test standard.*
5. Decision rules for the conclusion of this test report: decision by actual test data without considering measurement uncertainty.

2. General Information

2.1. Description of Device (EUT)

EUT Name : Magnetic Wireless Charger
Model No. : MagQoo AS3, Maghold C04
DIFF. : There is no difference except for the appearance, shape and model name. So all the test were performed on the model MagQoo AS3.
Power supply : Type-C Input: 5V $\overline{=}$ 3A, 9V $\overline{=}$ 2.22A
Wireless Output: 15W, 7.5W, 5W

Radio Technology : Wireless power transmission systems

Operation frequency : 115KHz -205KHz, 360KHz(MPP)

Modulation : ASK

Antenna Type : Coil Antenna

Connector cable loss : 0.5dB

Software version : V1.0

Hardware version : V1.0

Note : Antenna information is provided by applicant.
Testing lab is not responsible for the accuracy of the information.


2.2. Accessories of Device (EUT)

Accessories	:	N/A
Manufacturer	:	N/A
Model	:	N/A
specifications	:	N/A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification
1	Adapter	Apple	A2244	N/A	N/A
2	Load	Yuebuzhe	YBZ	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Description of Test Modes

Number	Modes
1	Wireless output: 15W
2	Wireless output: 7.5W
3	Wireless output: 5W
4	No Load

Note:1. All test modes has been tested, this report only reflected the worst mode.

2. Mode 1&2 is worst case for Conducted Emission and Spurious Emission.

2.6. Test Conditions

Items	Required
Temperature range:	15-35°C
Humidity range:	25-75%
Pressure range:	86-106kPa

2.7. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission

Registration Number: 916281

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.17dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	2.74dB(Polarize: V)
	2.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 18GHz)	4.29dB(Polarize: V)
	4.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	48.24KHz
Uncertainty for conducted RF Power	0.41dB
Occupied Bandwidth	968Hz

2.9. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2022.12.20	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2023.12.19	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2023.12.19	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2023.12.19	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2023.04.03	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2022.12.26	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2023.12.19	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2022.12.26	2 Year
9.	Amplifier	SKET	LAPA_01G1 8G-45dB	SK20220329 01	/	2023.12.19	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2022.12.25	2 Year
11.	Amplifier	SKET	LNPA_0118 G-45	SK20200108 01	/	2023.12.19	1 Year
12.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02 -1111533-Fz	/	2023.12.19	1 Year
13.	RF Sensor Unit	Tachoy	TR1029-2	20220428P0 08	/	2023.12.19	1 Year
14.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2023.12.19	1 Year
15.	Temp. & Humid Chamber	Auchno	9606	/	/	2023.12.19	1 Year
16.	Regulated DC Power Supply	Xinouhua	ADC120V10 A	20221125163 8		2023.12.19	1 Year

For Test Software Information

Item	Software Name	Manufacturer	Version
RE	EZ EMC	Farad	PSI-3A1
CE	EZ EMC	Farad	PSI-3A1
RF	RTS	TACHOY	V1.0.0

3. Test Results and Measurement Data

3.1. Conducted Emission

3.1.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane 40cm 80cm E.U.T Adapter LISN Filter AC power EMI Receiver Test table/Insulation plane Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	Transmitting Mode														
Test Procedure:	1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.														
Test Result:	PASS														


3.1.2. Test data

Please refer to following diagram for individual

Test Mode	: Mode 1 & Mode 2
Test Results	: PASS
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

Mode 1:


Temperature	26°C	Humidity	54%
Pol	Line		AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1620	42.63	9.94	52.57	65.36	-12.79	QP	P
2	0.1620	29.38	9.94	39.32	55.36	-16.04	AVG	P
3	0.2460	38.09	9.97	48.06	61.89	-13.83	QP	P
4	0.2460	24.13	9.97	34.10	51.89	-17.79	AVG	P
5	0.3620	36.23	9.76	45.99	58.68	-12.69	QP	P
6	0.3620	31.23	9.76	40.99	48.68	-7.69	AVG	P
7	1.0820	35.12	9.41	44.53	56.00	-11.47	QP	P
8 *	1.0820	29.99	9.41	39.40	46.00	-6.60	AVG	P
9	1.7980	32.46	9.39	41.85	56.00	-14.15	QP	P
10	1.7980	28.10	9.39	37.49	46.00	-8.51	AVG	P
11	4.6779	28.87	9.41	38.28	56.00	-17.72	QP	P
12	4.6779	23.98	9.41	33.39	46.00	-12.61	AVG	P

Level = Reading + Factor Margin = Level - Limit

Pol	Neutral
-----	---------




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1620	41.12	9.84	50.96	65.36	-14.40	QP	P
2	0.1620	27.39	9.84	37.23	55.36	-18.13	AVG	P
3	0.2460	36.73	9.93	46.66	61.89	-15.23	QP	P
4	0.2460	24.35	9.93	34.28	51.89	-17.61	AVG	P
5	0.4740	33.43	9.72	43.15	56.44	-13.29	QP	P
6	0.4740	19.47	9.72	29.19	46.44	-17.25	AVG	P
7	0.6380	33.67	9.78	43.45	56.00	-12.55	QP	P
8	0.6380	19.42	9.78	29.20	46.00	-16.80	AVG	P
9	1.0780	32.41	9.49	41.90	56.00	-14.10	QP	P
10 *	1.0780	25.74	9.49	35.23	46.00	-10.77	AVG	P
11	1.7980	31.43	9.31	40.74	56.00	-15.26	QP	P
12	1.7980	23.25	9.31	32.56	46.00	-13.44	AVG	P

Level = Reading + Factor Margin = Level - Limit

Mode: 2


Temperature	26°C	Humidity	54%
Pol	Line		AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2083	31.23	9.95	41.18	63.27	-22.09	QP	P
2	0.2083	19.89	9.95	29.84	53.27	-23.43	AVG	P
3	0.6419	31.04	9.57	40.61	56.00	-15.39	QP	P
4	0.6419	27.05	9.57	36.62	46.00	-9.38	AVG	P
5	1.6660	31.02	9.40	40.42	56.00	-15.58	QP	P
6 *	1.6660	28.41	9.40	37.81	46.00	-8.19	AVG	P
7	3.9740	28.77	9.39	38.16	56.00	-17.84	QP	P
8	3.9740	27.52	9.39	36.91	46.00	-9.09	AVG	P
9	10.9020	27.65	9.54	37.19	60.00	-22.81	QP	P
10	10.9020	25.53	9.54	35.07	50.00	-14.93	AVG	P
11	29.2380	24.63	10.28	34.91	60.00	-25.09	QP	P
12	29.2380	23.97	10.28	34.25	50.00	-15.75	AVG	P

Level = Reading + Factor Margin = Level – Limit

Pol	Neutral
-----	---------





No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1700	32.63	9.88	42.51	64.96	-22.45	QP	P
2	0.1700	20.47	9.88	30.35	54.96	-24.61	AVG	P
3	0.6419	30.50	9.78	40.28	56.00	-15.72	QP	P
4	0.6419	26.58	9.78	36.36	46.00	-9.64	AVG	P
5	1.6700	31.56	9.34	40.90	56.00	-15.10	QP	P
6	1.6700	27.60	9.34	36.94	46.00	-9.06	AVG	P
7	4.2340	29.29	9.55	38.84	56.00	-17.16	QP	P
8 *	4.2340	28.28	9.55	37.83	46.00	-8.17	AVG	P
9	6.5420	29.04	9.51	38.55	60.00	-21.45	QP	P
10	6.5420	27.90	9.51	37.41	50.00	-12.59	AVG	P
11	29.2460	27.39	10.34	37.73	60.00	-22.27	QP	P
12	29.2460	25.39	10.34	35.73	50.00	-14.27	AVG	P

Level = Reading + Factor Margin = Level - Limit

3.2. Radiated Spurious Emission Measurement

3.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10: 2013				
Frequency Range:	9 kHz to 1 GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Coaxial & Coplanar(9KHz-30MHz) Horizontal & Vertical(30MHz-1GHz)				
Operation mode:	Refer to item 4.1				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 KHz, 110-490 KHz and above 1000 MHZ. Radiated emission limits in these three bands are based on measurements employing an average detector.				
Limit:	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)
	0.009-0.490		2400/F(KHz)		300
	0.490-1.705		24000/F(KHz)		30
	1.705-30		30		30
	30-88		100		3
	88-216		150		3
	216-960		200		3
	Above 960		500		3
	Test setup:	For radiated emissions below 30MHz			
					
	30MHz to 1GHz				

	
Test Procedure:	1. For the radiated emission test below 1GHz: The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level. 2. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold; For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test mode:	Refer to section 4.1 for details
Test results:	PASS


3.2.2. Test Data

Please refer to following diagram for individual

Frequency Range	: 9KHz~30MHz
Test Mode	: Mode 1 & Mode 2
Test Results	: PASS
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the quasi-peak detector need not be carried out.


Mode 1:

Antenna polarity: Coaxial



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0123	13.64	21.44	35.08	125.90	-90.82	peak
2	0.0183	13.63	21.29	34.92	122.46	-87.54	peak
3	0.0284	12.55	21.03	33.58	118.66	-85.08	peak
4	0.0490	12.87	19.95	32.82	113.93	-81.11	peak
5	0.0710	15.03	20.18	35.21	110.72	-75.51	peak
6 *	0.1480	19.24	20.17	39.41	104.36	-64.95	peak

Level = Reading + Factor Margin = Level – Limit




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	0.3598	53.66	19.90	73.56	96.72	-23.16	peak
2	0.8500	20.05	19.91	39.96	69.14	-29.18	peak
3	1.6067	13.79	20.15	33.94	63.52	-29.58	peak
4	5.1634	6.49	21.69	28.18	70.00	-41.82	peak
5	12.1600	5.01	20.58	25.59	70.00	-44.41	peak
6	25.0633	5.80	20.34	26.14	70.00	-43.86	peak

Level = Reading + Factor Margin = Level – Limit

Note: All polarization has been tested and only the worst polarization direction data is displayed.


Mode 2:

Antenna polarity: Coaxial



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0123	14.14	21.44	35.58	125.90	-90.32	peak
2	0.0183	15.13	21.29	36.42	122.46	-86.04	peak
3	0.0371	12.42	20.60	33.02	116.34	-83.32	peak
4	0.0675	12.28	20.16	32.44	111.16	-78.72	peak
5	0.0907	14.77	19.89	34.66	108.60	-73.94	peak
6 *	0.1280	72.09	19.88	91.97	105.62	-13.65	peak

Level = Reading + Factor Margin = Level – Limit



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.1708	33.14	20.17	53.31	103.12	-49.81	peak
2 *	0.6130	22.04	19.77	41.81	72.02	-30.21	peak
3	1.6187	12.69	20.15	32.84	63.46	-30.62	peak
4	5.0930	5.87	21.65	27.52	70.00	-42.48	peak
5	13.2596	5.36	20.56	25.92	70.00	-44.08	peak
6	25.0633	5.80	20.34	26.14	70.00	-43.86	peak

Level = Reading + Factor Margin = Level - Limit


Note: All polarization has been tested and only the worst polarization direction data is displayed.

Frequency Range	: 30MHz~1000MHz
Test Mode	: Mode 1 & Mode 2
Test Results	: PASS
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the quasi-peak detector need not be carried out.

Mode 1:


30MHz-1GHz

Temperature	26°C	Humidity	54%
Pol	Vertical	Test Voltage	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	34.0962	21.61	12.77	34.38	40.00	-5.62	QP
2	53.0613	15.49	12.87	28.36	40.00	-11.64	QP
3	71.8949	21.73	10.60	32.33	40.00	-7.67	QP
4	97.8410	25.38	9.36	34.74	43.50	-8.76	QP
5	196.3376	23.14	10.25	33.39	43.50	-10.11	QP
6	314.9280	17.47	14.04	31.51	46.00	-14.49	QP

Level = Reading + Factor Margin = Level – Limit




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	35.0970	19.80	12.93	32.73	40.00	-7.27	QP
2	53.6225	12.23	12.82	25.05	40.00	-14.95	QP
3	70.5835	12.76	10.94	23.70	40.00	-16.30	QP
4	97.8840	23.48	9.36	32.84	43.50	-10.66	QP
5	137.6613	14.85	12.67	27.52	43.50	-15.98	QP
6	197.9795	25.05	10.15	35.20	43.50	-8.30	QP

Level = Reading + Factor Margin = Level – Limit

Mode 2:

30MHz-1GHz


Temperature	26°C	Humidity	54%
Pol	Vertical	Test Voltage	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	35.9376	15.75	13.05	28.80	40.00	-11.20	QP
2 *	47.4086	23.82	13.32	37.14	40.00	-2.86	QP
3	58.2030	23.52	12.34	35.86	40.00	-4.14	QP
4	67.2022	22.68	11.39	34.07	40.00	-5.93	QP
5	108.9331	22.37	10.41	32.78	43.50	-10.72	QP
6	127.2176	20.97	11.96	32.93	43.50	-10.57	QP

Level = Reading + Factor Margin = Level – Limit

Pol	Horizontal
------------	------------



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	48.8643	10.92	13.25	24.17	40.00	-15.83	QP
2	107.0399	18.91	10.22	29.13	43.50	-14.37	QP
3 *	129.1276	22.36	12.09	34.45	43.50	-9.05	QP
4	172.9017	20.55	11.99	32.54	43.50	-10.96	QP
5	303.2777	14.96	13.74	28.70	46.00	-17.30	QP
6	586.8437	11.06	20.38	31.44	46.00	-14.56	QP

Level = Reading + Factor Margin = Level – Limit

3.3. Test Specification


Test Requirement:	FCC Part15 C Section 15.215(c)
Test Method:	ANSI C63.10: 2013
Limit:	N/A
Test Procedure:	1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel; RBW$\geq$1% of the 20 dB bandwidth; VBW$\geq$RBW; Sweep = auto; Detector function = peak; Trace = max hold. 4. Measure and record the results in the test report.
Test setup:	 The diagram illustrates the test setup. On the left is a green Spectrum Analyzer with a blue screen and two red dots representing ports. A black cable connects this to a small white rectangular component, which is then connected to a yellow EUT (Equipment Under Test) box on the right. The EUT box has a single black dot representing a port. Spectrum Analyzer EUT
Test Mode:	Refer to section 4.1 for details
Test results:	PASS

3.3.1. Test data

Mode 1:

Frequency(kHz)	20dB Occupy Bandwidth (kHz)	Limit (kHz)	Conclusion
360	2.743	---	Pass


Test plots as follows:



Mode 2:

Frequency(kHz)	20dB Occupy Bandwidth (kHz)	Limit (kHz)	Conclusion
128	2.730	---	Pass


Test plots as follows:



Mode 3:

Frequency(kHz)	20dB Occupy Bandwidth (kHz)	Limit (kHz)	Conclusion
128	2.724	---	Pass

Test plots as follows:



Note: Mode 4 is standby mode and does not have a transmission frequency.

4. Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

5. Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

----- END OF REPORT-----