

Radio Frequency Exposure Evaluation Report

For: Lennox Industries Inc.

> Model Name: Lennox L40

Product Description: Thermostat to control residential HVAC system

> FCC ID: 2A6F9-L4024A ISED: 28687-L4024A

Applied Rules and Standards: CFR Part Part1 (1.1307 &1.1310), Part 2 (2.1091), FCC KDB 447498 D01 General RF Exposure Guidance v06 ISED RSS-102 Issue 6

Report number: EMC_LENNX_014_24001_RF_Exposure_Rev1

DATE: 2025-01-22



CETECOM Inc. 411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A. Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecom.com • <u>http://www.cetecom.com</u> CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

© Copyright by CETECOM



TABLE OF CONTENTS

1	Assessment	3
2	Administrative Data	4
2	2.1 Identification of the Testing Laboratory Issuing the EMC Test Report	4
2	2.2 Identification of the Client	4
2	2.3 Identification of the Manufacturer	4
3	Equipment under Assessment	5
3	3.1 EUT Specifications	5
4	RF Exposure Limits and FCC and ISED Basic Rules	6
F	FCC	6
I	ISED RSS 102	6
5	Evaluations	7
5.1	Analysis of RF Exposure	7
5.2	FCC RF Exposure (Standalone)	7
5.3	ISED RF Exposure (Standalone)	7
6	Revision History	8

Test Report #:	EMC_LENNX_014_24001_RF_Exposu	ure_Rev1	FCC ID: 2A6F9-L4024A	a
Date of Report	2025-01-22	Page 3 of 8	ISED: 28687-L4024A	

1 Assessment

This RF Exposure evaluation report provides evidence for compliance of the below identified device with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1 (1.1307 &1.1310), Part 2 (2.1091) and ISED standard RSS-102 issue 6 under worst case conditions (measured or rated RF output power, antenna gain, distance towards human body, multiple transmitter information as presented by the applicant).

cetecom

In addition, maximum antenna gain or minimum distance towards the human body is calculated respectively, where relevant.

The device meets the limits as stipulated by the above given FCC and ISED rule parts based on available specifications for worst-case conditions at 20 cm distance to the body.

Company	Module Model #	
Lennox Industries Inc.	Thermostat to control residential HVAC system	Lennox L40

Responsible for the Report:

	Art Thammanavarat						
2025-01-22	2025-01-22 Compliance (Senior EMC Engineer)						
Date	Section	Name	Signature				
2000			0.9.1				

The test results of this test report relate exclusively to the test item specified in Section3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.



2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Alvin, Ilarina
Responsible Project Leader:	Shane, Hao

2.2 Identification of the Client

Client Firm/Name:	Lennox Industries Inc.		
Street Address:	PO Box 799900		
City/Zip Code	Dallas TX 75379		
Country	USA		

2.3 Identification of the Manufacturer

Manufacturer's Name:	
Manufacturers Address:	Same as Client
City/Zip Code	
Country	



3 Equipment under Assessment

3.1 EUT Specifications

Product Description:	Thermostat to control residential HVAC system
Model Name:	Lennox L40 Yosemite
HW Version:	A
SW Version:	04.33.0167
FCC-ID:	2A6F9-L4024A
ISED:	28687-L4024A
Frequency Range / number of channels:	Nominal band: 2400 MHz – 2483.5 MHz; Center to center: 2412 MHz (ch 1) – 2462 MHz (ch 11), 11 channels
Radio Information:	Wi-Fi & Bluetooth Modules Model Name: Murata - Type 1YN - Wi-Fi and Bluetooth Combo Model Number: LBEE5KL1YN-814 FCC: VPYLB1DX ISED: 772C-LB1DX Wireless Technologies • Wi-Fi 2.4GHz :802.11b,g,n • Bluetooth LE
Antenna Information as declared:	Name: Pulse Electronics Description: FPC 2.4G Antenna Part Number: W3921B0100 Location: Internal Antenna Peak Gain: • 2400-2500GHz: 1.0 dBi
Power Supply/ Rated Operating Voltage Range:	120Vac to 24Vac
Operating Temperature Range	Low: -20 °C - °C High 70 °C
Other Radios included in the device:	N/A
Sample Revision	□Production Unit;■Pre-Production
Note: The information of the EUT sp	pecifications in the table above is provided by the client.



4 RF Exposure Limits and FCC and ISED Basic Rules

FCC

4.1.1 § 2.1093(c)(1)

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for mobile devices with single RF sources having either more than an available maximum time-averaged power of 1 mW or more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), whichever is greater. For mobile devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 of this chapter is necessary if the ERP of the device is greater than ERP20cm in the formula below. If the ERP of a single RF source at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP) in comparison with the following formula only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

$$P_{th}(\text{mW}) = ERP_{20\ cm}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases}$$

4.1.2 § 2.1093(c)(2)

For multiple mobile or portable RF sources within a device operating in the same time averaging period, routine environmental evaluation is required if the formula in § 1.1307(b)(3)(ii)(B) of this chapter is applied to determine the exemption ratio and the result is greater than 1.

4.1.3 § 1.1307(b)(3)(ii)(B)

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$

ISED RSS 102

4.1.4 Clause 2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

 below 20 MHz and the source-based, time-averaged maximum EIRP. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

• at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 4.49/f0.5 W (adjusted for tune-up tolerance), where *f* is in MHz;

• at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);

• at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1.31 x 10-2 f0.6834 W (adjusted for tune-up tolerance), where f is in MHz;

• at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived



5 Evaluations

5.1 Analysis of RF Exposure

5.2 FCC RF Exposure (Standalone)

Radio	Tech-Band	Freq-Low _[GHz]	Pwr _[dBm]	Power _[W]	AG _[dBi]	EIRP _[W]	ERP _[W]	ERP _[mW]	Threshold ERP _[W]	ERP < Threshold ERP _[W]
Bluetooth	LE	2.4050	9.60	0.0091	1.00	0.011	0.007	7.00	0.77	Yes
WLAN	802.11b	2.4120	16.20	0.0417	1.00	0.052	0.032	31.99	0.77	Yes

Conclusion:

 The maximum RF emissions from this equipment fulfills the RF exclusion threshold limits for separation distance between the antenna and the human body greater than 20 cm. No RF Exposure evaluation is required.

5.3 ISED RF Exposure (Standalone)

							RF Exposure			
								RSS-102 2.5.2 D>20 cm (300 ≤ Freq <	6000 MHz)	
Radio	Tech-Band	Freq-Low [MHZ]	Pwr _[dBm]	Power _[W]	Ant-G [dBi]	Ant-G [lin]	EIRP _[W]	EIRP _[mW]	W1 Exemption limit for Routine Evaluation Exemption (Y/	
Bluetooth	LE	2405.00	9.60	0.0091	1.00	1.26	0.01	11.48	2.68	Yes
WLAN	802.11b	2412.00	16.20	0.04	1.00	1.26	0.05	52.48	2.68	Yes

Conclusion:

 The maximum RF emissions from this equipment fulfills the RF exclusion threshold limits for separation distance between the antenna and the human body greater than 20 cm. No RF Exposure evaluation is required.

Test Report #:	EMC_LENNX_014_24001_RF_Exp	osure_Rev1	FCC ID: 2A6F9-L4024A	C	cetecom
Date of Report	2025-01-22	Page 8 of 8	ISED: 28687-L4024A		advanced

6 Revision History

Date	Report Name	Changes to report	Report prepared by
2024-10-11	EMC_LENNX_014_24001_RF_Exposure	Initial Version	Art Thammanavarat
2024-10-11	EMC_LENNX_014_24001_RF_Exposure_Rev1	Report Revised 1. Updated FCC ID and ISED.	Art Thammanavarat

<<< The End >>>