Typical Antennas to be used with HZB-S58-S60C

Antenna Type	Manufacturer	Model Number	Mid-band Gain (dBi)	Notes
Omni	Telex	5830AN	7.5	Vertical
	MTI	MT-482009/N	9	
	MTI	MT-483003/N	12	
1 Foot Flat Panel	Gabriel	DFPD1-52	23.5	
	RFS	MA0528-23AN	23	
	Andrew	FPA5250D12-N	23.6	
2 Foot Flat Panel	Gabriel	DFPD2-52	28	
	RFS	MA0528-28AN	28	
	Andrew	FPA5250D24-N	28.5	
	MTI	MT-20004	28	
	RSI	A57A24-U	26.5	
2 Foot Parabolic	Gabriel	SSP2-52B	28.5	
	Gabriel	SSD2-52A	28.4	Dual Pol
	Gabriel	HSSP2-52	28.1	High Performance
	YDI	A5.8-2'-RW	28.3	
	Radio Waves	SP2-5.2	28.3	Linear or Circular
	Radio Waves	SPD2-5.2	28.1	Dual Pol
	Andrew	P2F-52	29.4	
	Andrew	PX2F-52	29.4	Dual Pol
	RFS	SPF2-52A	27.9	
	RSI	P-57C24	29	
3 Foot Parabolic	Radio Waves	SP3-5.8	31.4	Linear or Circular
	Radio Waves	SPD3-5.8	31.1	Dual Pol
	Radio Waves	SP3-5.2	31.4	Linear or Circular
	Radio Waves	SPD3-5.2	31.1	Dual Pol
	RFS	SPF3-52A	31.4	
	YDI	A5.8-3'-RW	31.4	
	Andrew	P3F-52	33.4	
	Andrew	PX3F-52	33.4	Dual Pol

All Proxim radios require professional installation.

Antennas with gain less than 7.5 dBi are not allowed

Antennas of other make may be used with the HZB-S58-C60C device, but must be of the same type, dimensions and gain as those listed