

FCC Test Report

Report No.: AGC11034220305FE05

FCC ID : 2AYHE-2204C

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: WiFi IP Camera

BRAND NAME : Reolink

MODEL NAME : RLC-510WA

APPLICANT : Reolink Innovation Limited

DATE OF ISSUE : Jun. 22, 2022

STANDARD(S)

TEST PROCEDURE(S) : FCC Part 15.247

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd





Page 2 of 80


REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Jun. 22, 2022	Valid	Initial Release	




TABLE OF CONTENTS

2. GENERAL INFORMATION 6 2.1. PRODUCT DESCRIPTION 6 2.2. TABLE OF CARRIER FREQUENCYS 7 2.3. IEEE 802.11M MODULATION SCHEME 8 2.4. RELATED SUBMITTAL(S) / GRANT (S) 8 2.5. TEST METHODOLOGY 8 2.6. SPECIAL ACCESSORIES 8 2.7. EQUIPMENT MODIFICATIONS 8 2.8. ANTENNA REQUIREMENT 9 3. MEASUREMENT UNCERTAINTY 10 4. DESCRIPTION OF TEST MODES 11 5. SYSTEM TEST CONFIGURATION 12 5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 12 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULTS 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8. LIMITS AND MEASUREMENT RESULTS 17 9. C. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30<	1. VERIFICATION OF CONFORMITY	5
2.2. TABLE OF CARRIER FREQUENCYS 7 2.3. IEEE 802.11N MODULATION SCHEME 8 2.4. RELATED SUBMITTAL(S) / GRANT (S) 8 2.5. TEST METHODOLOGY 8 2.6. SPECIAL ACCESSORIES 8 2.7. EQUIPMENT MODIFICATIONS 8 2.8. ANTENNA REQUIREMENT 9 3. MEASUREMENT UNCERTAINTY 10 4. DESCRIPTION OF TEST MODES 11 5. SYSTEM TEST CONFIGURATION 12 5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.1. IMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF	2. GENERAL INFORMATION	6
2.3. IEEE 802.11N MODULATION SCHEME 8 2.4. RELATED SUBMITTAL(S) / GRANT (S) 8 2.5. TEST METHODOLOGY 8 2.6. SPECIAL ACCESSORIES 8 2.7. EQUIPMENT MODIFICATIONS 8 2.8. ANTENNA REQUIREMENT 9 3. MEASUREMENT UNCERTAINTY 10 4. DESCRIPTION OF TEST MODES 11 5. SYSTEM TEST CONFIGURATION 12 5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT PROCEDURE	2.1. PRODUCT DESCRIPTION	6
2.4. RELATED SUBMITTAL(S) / GRANT (S) 8 2.5. TEST METHODOLOGY 8 2.6. SPECIAL ACCESSORIES 8 2.7. EQUIPMENT MODIFICATIONS 8 2.8. ANTENNA REQUIREMENT 9 3. MEASUREMENT UNCERTAINTY 10 4. DESCRIPTION OF TEST MODES 11 5. SYSTEM TEST CONFIGURATION 12 5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.2. TEST SET-UP (BLOCK	2.2. TABLE OF CARRIER FREQUENCYS	7
2.5. TEST METHODOLOGY 8 2.6. SPECIAL ACCESSORIES 8 2.7. EQUIPMENT MODIFICATIONS 8 2.8. ANTENNA REQUIREMENT 9 3. MEASUREMENT UNCERTAINTY 10 4. DESCRIPTION OF TEST MODES 11 5. SYSTEM TEST CONFIGURATION 12 5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT PROCEDURE	2.3. IEEE 802.11N MODULATION SCHEME	8
2.6. SPECIAL ACCESSORIES 8 2.7. EQUIPMENT MODIFICATIONS 8 2.8. ANTENNA REQUIREMENT 9 3. MEASUREMENT UNCERTAINTY 10 4. DESCRIPTION OF TEST MODES 11 5. SYSTEM TEST CONFIGURATION 12 5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT PROCEDURE 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT	2.4. RELATED SUBMITTAL(S) / GRANT (S)	8
2.7. EQUIPMENT MODIFICATIONS 8 2.8. ANTENNA REQUIREMENT 9 3. MEASUREMENT UNCERTAINTY 10 4. DESCRIPTION OF TEST MODES 11 5. SYSTEM TEST CONFIGURATION 12 5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	2.5. TEST METHODOLOGY	8
2.8. ANTENNA REQUIREMENT 99 3. MEASUREMENT UNCERTAINTY 100 4. DESCRIPTION OF TEST MODES 111 5. SYSTEM TEST CONFIGURATION 112 5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 137 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULT 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT PROCEDURE 30 9.4. LIMITS AND MEASUREMENT RESULT 30 9.5. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.6. MEASUREMENT PROCEDURE 30 9.7. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.8. MEASUREMENT PROCEDURE 30 9.9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT PROCEDURE 30 9.4. LIMITS AND MEASUREMENT RESULT 30 9.5. MEASUREMENT PROCEDURE 30 9.6. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.7. MEASUREMENT PROCEDURE 30 9.8. MEASUREMENT PROCEDURE 30 9.9.1. MEASUREMENT PROCEDURE 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT PROCEDURE 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	2.6. SPECIAL ACCESSORIES	8
3. MEASUREMENT UNCERTAINTY	2.7. EQUIPMENT MODIFICATIONS	8
4. DESCRIPTION OF TEST MODES. 11 5. SYSTEM TEST CONFIGURATION. 12 5.1. CONFIGURATION OF EUT SYSTEM. 12 5.2. EQUIPMENT USED IN EUT SYSTEM. 12 5.3. SUMMARY OF TEST RESULTS. 12 6. TEST FACILITY. 13 7. OUTPUT POWER. 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION). 14 7.3. LIMITS AND MEASUREMENT RESULT. 15 8. BANDWIDTH. 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION). 16 8.3. LIMITS AND MEASUREMENT RESULTS. 17 9. CONDUCTED SPURIOUS EMISSION. 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION). 30 9.3. MEASUREMENT PROCEDURE 30 9.4. LIMITS AND MEASUREMENT RESULT. 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	2.8. ANTENNA REQUIREMENT	9
5. SYSTEM TEST CONFIGURATION 12 5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT PROCEDURE 30 9.4. LIMITS AND MEASUREMENT RESULT 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	3. MEASUREMENT UNCERTAINTY	10
5.1. CONFIGURATION OF EUT SYSTEM 12 5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT PROCEDURE 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45		
5.2. EQUIPMENT USED IN EUT SYSTEM 12 5.3. SUMMARY OF TEST RESULTS 12 6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT PROCEDURE 30 9.4. LIMITS AND MEASUREMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	5. SYSTEM TEST CONFIGURATION	12
5.3. SUMMARY OF TEST RESULTS .12 6. TEST FACILITY .13 7. OUTPUT POWER .14 7.1. MEASUREMENT PROCEDURE .14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .14 7.3. LIMITS AND MEASUREMENT RESULT .15 8. BANDWIDTH .16 8.1. MEASUREMENT PROCEDURE .16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .16 8.3. LIMITS AND MEASUREMENT RESULTS .17 9. CONDUCTED SPURIOUS EMISSION .30 9.1. MEASUREMENT PROCEDURE .30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .30 9.3. MEASUREMENT EQUIPMENT USEDJN .30 9.4. LIMITS AND MEASUREMENT RESULT .30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY .45 10.1 MEASUREMENT PROCEDURE .45	5.1. CONFIGURATION OF EUT SYSTEM	12
6. TEST FACILITY 13 7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	5.2. EQUIPMENT USED IN EUT SYSTEM	12
7. OUTPUT POWER 14 7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	5.3. SUMMARY OF TEST RESULTS	12
7.1. MEASUREMENT PROCEDURE 14 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	6. TEST FACILITY	13
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14 7.3. LIMITS AND MEASUREMENT RESULT 15 8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	7. OUTPUT POWER	14
7.3. LIMITS AND MEASUREMENT RESULT	7.1. MEASUREMENT PROCEDURE	14
8. BANDWIDTH 16 8.1. MEASUREMENT PROCEDURE 16 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	14
8.1. MEASUREMENT PROCEDURE	7.3. LIMITS AND MEASUREMENT RESULT	15
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45	8. BANDWIDTH	16
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16 8.3. LIMITS AND MEASUREMENT RESULTS 17 9. CONDUCTED SPURIOUS EMISSION 30 9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45	8.1. MEASUREMENT PROCEDURE	16
8.3. LIMITS AND MEASUREMENT RESULTS		
9.1. MEASUREMENT PROCEDURE 30 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45		
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	9. CONDUCTED SPURIOUS EMISSION	30
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 30 9.3. MEASUREMENT EQUIPMENT USEDJN 30 9.4. LIMITS AND MEASUREMENT RESULT 30 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45	9.1. MEASUREMENT PROCEDURE	30
9.3. MEASUREMENT EQUIPMENT USEDJN		
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 45 10.1 MEASUREMENT PROCEDURE 45		
10.1 MEASUREMENT PROCEDURE45	9.4. LIMITS AND MEASUREMENT RESULT	30
10.1 MEASUREMENT PROCEDURE45	10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENS	SITY45





10.3 MEASUREMENT EQUIPMENT USED	45
10.4 LIMITS AND MEASUREMENT RESULT	
11. RADIATED EMISSION	52
11.1. MEASUREMENT PROCEDURE	52
11.2. TEST SETUP	53
11.3. LIMITS AND MEASUREMENT RESULT	
11.4. TEST RESULT	54
12. LINE CONDUCTED EMISSION TEST	76
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	76
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	76
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	77
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	77
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	78
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	80
APPENDIX B: PHOTOGRAPHS OF EUT	80





1. VERIFICATION OF CONFORMITY

Applicant	Reolink Innovation Limited
Address	FLAT/RM 705 7/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN STREET MONG KOK KL HONG KONG
manufacturer	Reolink Innovation Limited
Address	FLAT/RM 705 7/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN STREET MONG KOK KL HONG KONG
Factory	Shenzhen Reolink Technology Co., Ltd.
Address	2-4th Floor, Building 2, YuanLing Industrial Park, ShangWu, Shiyan Street, Bao'an District, Shenzhen, China
Product Designation	WiFi IP Camera
Brand Name	Reolink
Test Model	RLC-510WA
Date of test	Mar. 11, 2022~Mar. 28, 2022
Deviation	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-US-BGN/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Prepared By	Foler zhan			
	Eder Zhan (Project Engineer)	Mar. 28, 2022		
Reviewed By	Calin.	Lin		
	Calvin Liu (Reviewer)	Jun. 22, 2022		
Approved By	Max Zha	ng		
	Max Zhang Authorized Officer	Jun. 22, 2022		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Page 6 of 80

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as "WiFi IP Camera". It is designed by way of utilizing the DSSS and OFDM technology to achieve the system operation.

A major technical description of EUT is described as following

Equipment Type	WLAN 2.4G			
Frequency Band	2400MHz ~ 2483.5MHz			
Operation Frequency	2412MHz ~ 2462MHz			
Output Power (Average)	IEEE 802.11b:15.98dBm; IEEE 802.11g:13.55dBm;			
Output Fower (Average)	IEEE 802.11n(HT20):13.79dBm; IEEE 802.11n(HT40):13.71dBm			
Output Power (Peak)	IEEE 802.11b:18.45dBm; IEEE 802.11g:21.14dBm;			
Output Fower (Feak)	IEEE 802.11n(HT20):21.36dBm; IEEE 802.11n(HT40):21.39dBm			
Modulation	802.11b:DQPSK, DBPSK, CCK			
Woddiation	802.11g/n: 64-QAM, 16-QAM, QPSK, BPSK			
	802.11b: 1/2/5.5/11Mbps			
Data Rate	802.11g: 6/9/12/18/24/36/48/54Mbps			
	802.11n: up to 300Mbps			
Number of channels	11			
Hardware Version	S05A10B_V110			
Software Version	V1.0			
Antenna Designation	External antenna (Comply with requirements of the FCC part 15.203)			
Antenna Gain	3dBi			
Power Supply	DC 12V by adapter			



Page 7 of 80

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	1	2412 MHZ
	2	2417 MHZ
	3	2422 MHZ
	4	2427 MHZ
	5	2432 MHZ
2400~2483.5MHZ	6	2437 MHZ
	7	2442 MHZ
	8	2447 MHZ
	9	2452 MHZ
	10	2457 MHZ
	11	2462 MHZ

Note: For 20MHZ bandwidth system use Channel 1 to Channel 11. For 40MHZ bandwidth system use Channel 3 to Channel 9



Page 8 of 80

2.3. IEEE 802.11N MODULATION SCHEME

MCS Index	Nss	Modulation	R	NBPSC	NCI	NCBPS NDBPS			ata Mbps) nsGl	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval

2.4. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AYHE-2204C** filing to comply with the FCC Part 15 requirements.

2.5. TEST METHODOLOGY

KDB 558074 D01 15.247 Meas Guidance v05: Guidance for compliance measurements on Digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

ANSI C63.10:2013: American National Standard for Testing Unlicensed Wireless Devices

2.6. SPECIAL ACCESSORIES

Refer to section 5.2.

2.7. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.



Page 9 of 80

2.8. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.




Page 10 of 80

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$





4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel transmitting (TX)
2	Middle channel transmitting (TX)
3	High channel transmitting (TX)

Note:

Transmit by 802.11b with Date rate (1/2/5.5/11)

Transmit by 802.11g with Date rate (6/9/12/18/24/36/48/54)

Transmit by 802.11n (20MHz) with Date rate (6.5/13/19.5/26/39/52/58.5/65)


Transmit by 802.11n (40MHz) with Date rate (13.5/27/40.5/54/81/108/121.5/135)

The test channel for 20MHZ bandwidth system is channel 1, 6 and 11.

The test channel for 40MHZ bandwidth system is channel 3, 6 and 9.

Note:

- 1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency Individually, and the EUT is operating at its maximum duty cycle>or equal 98%
- 2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.






Page 12 of 80

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure:



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	WiFi IP Camera	RLC-510WA	2AYHE-2204C	EUT
2	Adapter	DCT12W120100US-B0	Input: AC 100-240V 50/60Hz, 0.3A Output: DC 12V 1A	AE
3	LAN Cable	N/A	N/A	AE

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Output Power	Compliant
§15.247	6 dB Bandwidth	Compliant
§15.247	Conducted Spurious Emission	Compliant
§15.247	Maximum Conducted Output Power Spectral Density	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Line Conduction Emission	Compliant



Page 13 of 80

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	May 11, 2021	May 10, 2022
LISN	R&S	ESH2-Z5	100086	Jun. 09, 2021	Jun. 08, 2022
Test software	R&S	ES-K1(Ver.V1.71)	N/A	N/A	N/A

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Apr. 14, 2021	Apr. 13, 2022
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	Mar. 23, 2020	Mar. 22, 2022
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	Mar. 21, 2022	Mar. 20, 2023
Attenuator	ZHINAN	E-002	N/A	Sep. 03, 2020	Sep. 02, 2022
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep. 19, 2021	Sep. 18, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	May 22, 2020	May 21, 2022
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Sep. 03, 2020	Sep. 02, 2022
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A



Page 14 of 80

7. OUTPUT POWER


7.1. MEASUREMENT PROCEDURE

For average power test:

- 1. Connect EUT RF output port to power sensor through an RF attenuator.
- 2. Connect the power sensor to the PC.
- 3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Record the maximum power from the software.

Note: The EUT was tested according to ANSI C63.10 (2013) for compliance to FCC 47CFR 15.247 requirements.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)





Page 15 of 80

7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power					
Test Mode	Test Channel (MHz)	Average Power (dBm)	Peak Power (dBm)	Limits (dBm)	Pass or Fail
	2412	15.72	18.16	≤30	Pass
802.11b	2437	15.98	18.45	≤30	Pass
	2462	15.06	17.54	≤30	Pass
	2412	13.53	21.03	≤30	Pass
802.11g	2437	13.55	21.14	≤30	Pass
	2462	13.03	20.10	≤30	Pass
	2412	13.32	20.81	≤30	Pass
802.11n20	2437	13.79	21.36	≤30	Pass
	2462	12.90	20.02	≤30	Pass
802.11n40	2422	13.71	21.39	≤30	Pass
	2437	13.59	21.23	≤30	Pass
	2452	13.60	20.42	≤30	Pass



Page 16 of 80

8. BANDWIDTH

8.1. MEASUREMENT PROCEDURE

6dB bandwidth:


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW≥3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
 The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video
 bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)






Page 17 of 80


8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail
	2412	12.963	8.085	≥0.5	Pass
802.11b	2437	13.515	8.581	≥0.5	Pass
	2462	13.142	8.540	≥0.5	Pass
	2412	16.410	15.103	≥0.5	Pass
802.11g	2437	16.641	15.706	≥0.5	Pass
	2462	16.484	13.192	≥0.5	Pass
	2412	17.452	15.103	≥0.5	Pass
802.11n20	2437	17.650	16.321	≥0.5	Pass
	2462	17.434	13.803	≥0.5	Pass
802.11n40	2422	35.996	35.095	≥0.5	Pass
	2437	36.303	35.725	≥0.5	Pass
	2452	35.052	20.104	≥0.5	Pass





Test Graphs of Occupied Bandwidth




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11b_ANT1_2437_1Mbps_OBW

0 Hz





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

OBW Power

Test_Graph_802.11g_ANT1_2412_6Mbps_OBW

x dB

99.00 %


-26.00 dB

5.509 kHz

19.80 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





OBW Power

Test_Graph_802.11g_ANT1_2462_6Mbps_OBW

x dB


99.00 %

-26.00 dB


-281.40 kHz

19.96 MHz

Web: http://www.agccert.com/







Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

OBW Power

Test_Graph_802.11n20_ANT1_2437_MCS0_OBW

x dB

99.00 %

-26.00 dB


17.650 MHz

122.01 kHz

20.34 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/






x dB

Test Graph 802.11n40 ANT1 2422 MCS0 OBW

-26.00 dB


40.38 MHz

x dB Bandwidth



0 Hz





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

OBW Power

Test Graph 802.11n40 ANT1 2452 MCS0 OBW

x dB


99.00 %

-26.00 dB

-59.272 kHz


38.48 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





Test Graphs of DTS Bandwidth



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

OBW Power

Test_Graph_802.11g_ANT1_2412_6Mbps_DTSBW

x dB

99.00 %

-6.00 dB


16.267 MHz

934 Hz

15.10 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

OBW Power

Test_Graph_802.11g_ANT1_2462_6Mbps_DTSBW

x dB

99.00 %

-6.00 dB


16.210 MHz

-189.53 kHz

13.19 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

OBW Power

Test Graph 802.11n20 ANT1 2437 MCS0 DTSBW

x dB

99.00 %

-6.00 dB

17.584 MHz


69.573 kHz

16.32 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

0 Hz





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

OBW Power

Test Graph 802.11n40 ANT1 2422 MCS0 DTSBW

x dB

99.00 %

-6.00 dB


-6.056 kHz

35.09 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

0 Hz





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

OBW Power

Test Graph 802.11n40 ANT1 2452 MCS0 DTSBW

x dB

99.00 %

-6.00 dB

-65.363 kHz

20.10 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 30 of 80

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 (2013) for compliance to FCC 47CFR 15.247 requirements. Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW>RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW>RBW) are conform to the requirement.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2.


9.3. MEASUREMENT EQUIPMENT USEDJN

The same as described in section 6.


9.4. LIMITS AND MEASUREMENT RESULT


LIMITS AND MEASUREMENT RESULT				
Applicable Limite	Measurement Result			
Applicable Limits	Test Data	Criteria		
In any 100 KHz Bandwidth Outside the	At least -20dBc than the limit			
frequency band in which the spread spectrum	Specified on the BOTTOM	PASS		
intentional radiator is operating, the radio frequency	Channel			
power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the TOP Channel	PASS		

Note: The limits reference level is according to the test plot of -6dB bandwidth.




















































































Test_Graph_802.11n40_ANT1_2422_MCS0_Higher Band Emissions

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.









Test_Graph_802.11n40_ANT1_2437_MCS0_Higher Band Emissions

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.











Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results

presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report.

Test_Graph_802.11g_ANT1_2412_6Mbps_Lower Band Edge Emissions

Attestation of Global Compliance(Shenzhen)Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.





Note: Emissions from 2483.5-2500MHz which fall in the restricted bands had been considered with the radiated emission limits specified.



Report No.: AGC11034220305FE05

Page 45 of 80

10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

10.1 MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the ANSI C63.10 (2013) item 11.10 was used in this testing.

10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer to Section 8.2.


10.3 MEASUREMENT EQUIPMENT USED

Refer to Section 6.

10.4 LIMITS AND MEASUREMENT RESULT

	Test Data of Conducted Output Power Spectral Density								
Test Mode	Test Channel (MHz)	Power density (dBm/20kHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail				
	2412	0.513	-7.726		Pass				
802.11b	2437	0.867	-7.372	- ₹8	Pass				
	2462	-0.081	-8.32	- ≪8	Pass				
	2412	-3.499	-11.738	- ₹8	Pass				
802.11g	2437	-2.423	-10.662		Pass				
	2462	-2.287	-10.526	- ₹8	Pass				
	2412	-2.712	-10.951		Pass				
802.11n20	2437	-2.796	-11.035	- ₹8	Pass				
	2462	-2.701	-10.94	- ≪8	Pass				
	2422	-5.655	-13.894	- ₹8	Pass				
802.11n40	2437	-6.756	-14.995	- ≪8	Pass				
	2452	-4.249	-12.488	- ₹8	Pass				

Note: Power density(dBm/3kHz) = Power density(dBm/20kHz) - 10*log(20/3).





Test Graphs of Conducted Output Power Spectral Density




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11b_ANT1_2437_1Mbps_PSD

Web: http://www.agccert.com/




































Report No.: AGC11034220305FE05

Page 52 of 80

11. RADIATED EMISSION


11.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.




11.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Report No.: AGC11034220305FE05

Page 54 of 80

11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Note: All modes were tested for restricted band radiated emission.

the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT

Radiated emission below 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.





Radiated emission from 30MHz to 1000MHz

EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Horizontal




NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	49.4	27.82	11.61	40.00	12.18	100	303	Horizontal
2	74.62	28.28	8.27	40.00	11.72	100	111	Horizontal
3	99.84	29.30	11.30	43.50	14.20	100	200	Horizontal
4	215.27	33.29	11.46	43.50	10.21	100	260	Horizontal
5	252.13	36.07	14.19	46.00	9.93	100	276	Horizontal
6	287.05	39.19	15.77	46.00	6.81	100	29	Horizontal

RESULT: PASS



EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Vertical



NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	36.79	29.74	10.73	40.00	10.26	100	51	Vertical
2	49.4	31.34	11.61	40.00	8.66	100	141	Vertical
3	62.98	33.39	10.42	40.00	6.61	100	207	Vertical
4	108.57	31.74	12.27	43.50	11.76	100	276	Vertical
5	259.89	35.45	14.55	46.00	10.55	100	346	Vertical
6	285.11	39.77	15.94	46.00	6.23	100	134	Vertical

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin= Limit-Measurement.

- 2. The "Factor" value can be calculated automatically by software of measurement system.
- 3. All test modes had been pre-tested. The 802.11b at low channel is the worst case and recorded in the report.



Report No.: AGC11034220305FE05 Page 57 of 80


Radiated emission above 1GHz

EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4824.000	53.15	0.08	53.23	74.00	-20.77	peak
4824.000	41.56	0.08	41.64	54.00	-12.36	AVG
7236.000	49.36	2.21	51.57	74.00	-22.43	peak
7236.000	41.37	2.21	43.58	54.00	-10.42	AVG
Remark:			-		•	•
actor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.			

EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHz	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4824.000	52.41	0.08	52.49	74.00	-21.51	peak
4824.000	39.56	0.08	39.64	54.00	-14.36	AVG
7236.000	50.38	2.21	52.59	74.00	-21.41	peak
7236.000	37.45	2.21	39.66	54.00	-14.34	AVG
Remark:	• •		•			•
actor = Anter	na Factor + Cabl	e Loss – Pre-a	amplifier.			





EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHz	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4874.000	51.44	0.14	51.58	74.00	-22.42	peak	
4874.000	40.25	0.14	40.39	54.00	-13.61	AVG	
7311.000	48.34	2.36	50.70	74.00	-23.30	peak	
7311.000	36.75	2.36	39.11	54.00	-14.89	AVG	
Remark:							
Factor = Antenna Factor + Cable Loss – Pre-amplifier.							

EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHz	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Tune
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4874.000	49.85	0.14	49.99	74.00	-24.01	peak
4874.000	41.33	0.14	41.47	54.00	-12.53	AVG
7311.000	47.58	2.36	49.94	74.00	-24.06	peak
7311.000	37.14	2.36	39.50	54.00	-14.50	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						



Report No.: AGC11034220305FE05

Page 59 d	of 80
-----------	-------

EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHz	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4924.000	51.54	0.22	51.76	74.00	-22.24	peak
4924.000	42.28	0.22	42.50	54.00	-11.50	AVG
7386.000	48.05	2.64	50.69	74.00	-23.31	peak
7386.000	39.55	2.64	42.19	54.00	-11.81	AVG
Remark:						
Factor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.			-

EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHz	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	\/alua Tuna
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4924.000	52.32	0.22	52.54	74.00	-21.46	peak
4924.000	41.89	0.22	42.11	54.00	-11.89	AVG
7386.000	47.53	2.64	50.17	74.00	-23.83	peak
7386.000	39.56	2.64	42.20	54.00	-11.80	AVG
Remark:	•		•	•		•
actor = Anter	nna Factor + Cable	Loss – Pre-	amplifier.			

RESULT: PASS


Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been pre-tested. The 802.11b mode is the worst case and recorded in the report.





Test result for band edge emission at restricted bands

EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHz	Antenna	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS





EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHz	Antenna	Vertical

Test Graph for Peak Measurement




Test Graph for Average Measurement



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.





EUT	WiFi IP Camera	Model Name	RLC-510WA
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHz	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS