



## FCC PART 15B

### TEST REPORT

For

### PO FUNG ELECTRONIC (HK) INTERNATIONAL GROUP COMPANY LIMITED

Room 1508, 15/F, Office Tower II, Grand Plaza, 625 Nathan Road, Kowloon, Hong Kong

**FCC ID: 2AJGM-DM32UV**

<b>Report Type:</b>	<b>Product Name:</b>
Original Report	Digital Radio
<b>Report Number:</b>	2407A66953E-EM-01
<b>Report Date:</b>	2025-02-24
<b>Reviewed By:</b>	Ash Lin
<b>Approved By:</b>	Miles Chen
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Xiamen) Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen Tel: +86-592-3200111 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

## **TABLE OF CONTENTS**

<b>REPORT REVISION HISTORY .....</b>	<b>.3</b>
<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
TEST FACILITY .....	4
MEASUREMENT UNCERTAINTY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
TEST MODE AND VOLTAGE.....	6
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>11</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>12</b>
<b>FCC §15.107 - CONDUCTED EMISSION .....</b>	<b>13</b>
APPLICABLE STANDARD .....	13
TEST SYSTEM SETUP.....	13
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE .....	14
RESULT & MARGIN CALCULATION.....	14
TEST DATA .....	15
<b>FCC §15.109 - RADIATED EMISSION.....</b>	<b>17</b>
APPLICABLE STANDARD .....	17
TEST SYSTEM SETUP.....	17
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE .....	18
RESULT & MARGIN CALCULATION.....	18
TEST DATA .....	19
<b>FCC §15.121(B) – SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING RECEIVERS.....</b>	<b>69</b>
APPLICABLE STANDARD .....	69
TEST PROCEDURE .....	69
TEST DATA .....	70
<b>EXHIBIT A - EUT PHOTOGRAPHS.....</b>	<b>71</b>
<b>EXHIBIT B – TEST SETUP PHOTOGRAPHS.....</b>	<b>72</b>

## REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	2407A66953E-EM-01	R1V1	2025-02-24	Initial Release

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant:	PO FUNG ELECTRONIC (HK) INTERNATONAL GROUP COMPANY LIMITED							
Product Name:	Digital Radio							
Tested Model:	DM-32UV							
Series Models:	NA-DM32, AR-32D, AT-32UV, MD-32UV, DM-32							
Adapter Information	Model:	A318-050100W-US2						
	Input:	AC 100-240V, 50-60Hz, 0.2A						
	Output:	DC 5V, 1A						
Charger Information	Model:	TC-UV32						
	Input:	DC 5V, 1A						
	Output:	DC 5V						
Power Supply:	DC 7.4V from battery or DC 5V from adapter or DC 5V from charger							
★Highest Operating Frequency:	470MHz							
EUT Receive Status:	Good							
<i>Note:</i>								
1. The highest operating frequency is provided by the applicant.								
2. The test model is identify with the series model except for the model name, please refer to declaration letter for more detail.								
3 All measurement and test data in this report was gathered from production sample serial number: 2WIG-3 (Assigned by the BACL (Xiamen). The EUT was received on 2024-12-24).								

### Objective

This report is prepared for *PO FUNG ELECTRONIC (HK) INTERNATONAL GROUP COMPANY LIMITED* in accordance with Part 2-Subpart J, and Part 15-Subparts A and B of the Federal Communication Commission's rules.

### Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

## Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the product as specified in CISPR 16-4-2. This uncertainty represents expanded uncertainty expressed at 95% confidence level using a coverage factor of k=2.

$$u_c(y) = \sqrt{\sum_i c_i^2 u^2(x_i)}$$

Item	Frequency Range	$U_{lab} = 2 u_c(y)$ (Confidence of 95%)
Conducted Emission	150kHz-30MHz	2.33dB
Radiated Emission	30MHz~200MHz	4.38dB
	200MHz~1GHz	4.50dB
	1GHz~6GHz	4.58dB
Unwanted Emissions, conducted		1.5dB
Humidity		5%
Temperature		1°C

## SYSTEM TEST CONFIGURATION

### Test Mode and Voltage

The system was configured for testing in a typical mode (as normally used by a typical user).	
<b>Test mode:</b>	Test Mode 1: Charging & Scanning Test Mode 2: Charging & Scanning Test Mode 3: Charging & Receiving Test Mode 4: Charging & Receiving
<b>Test voltage:</b>	Test Mode 1 & 3: DC 5V from charger (AC 120V/60Hz) Test Mode 2 & 4: DC 5V from adapter (AC 120V/60Hz)
<b>Remark:</b>	1. During all emission tests, the EUT was configured to measure its highest possible emission level and the worst case's test data was presented in this test report. 2. Test modes 3 and 4 were tested under FM conditions.

### Description of Test Configuration

Operation Modes	Operation Frequency Range (MHz)	Test Frequency (MHz)
Scanning	108-136 136-174 400-470	108-136 136-174 400-470
VHF Receiving	108-136 136-174	108.0125, 122, 135.9875 136.0125, 155, 173.9875
UHF Receiving	400-470	400.0125, 435, 469.9875

### EUT Exercise Software

No exercise software was used to test.

### Special Accessories

No special accessory was used.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HP	RF Communications test set	8920A	3524A07202
Unknown	Antenna	Unknown	Unknown


**External I/O Cable**

Cable Description	Length (m)	From Port	To Port
Antenna Cable	3.0	8920A	Antenna


**Block Diagram of Test Setup**

Conducted Emission:


Test Mode 1:




Test Mode 2:



Test Mode 3:




Test Mode 4:




Radiated Emission:


Test Mode 1:




Test Mode 2:



## Test Mode 3:



## Test Mode 4:



**SUMMARY OF TEST RESULTS**

Rule Part	Description of Test	Results
FCC§15.107	Conducted Emission	Compliant
FCC§15.109	Radiated Emission	Compliant
FCC §15.121(b)	Scanning receivers and frequency converters used with scanning receivers	Compliant

## TEST EQUIPMENT LIST

Test Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Conducted Emission</b>					
EMI Test Receiver	Rohde & Schwarz	ESR	103105	2024/03/29	2025/03/28
LISN	Rohde & Schwarz	ENV216	100129	2024/03/29	2025/03/28
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	0357.8810.54	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC001	2024/03/29	2025/03/28
Test Software	Audix	E3	18621a	N/A	N/A
<b>Radiated Emission 30 MHz to 1 GHz</b>					
EMI Test Receiver	Rohde & Schwarz	ESR	103103	2024/03/29	2025/03/28
Antenna	Sunol Sciences	JB6	A122022-5	2023/07/27	2026/07/26
Amplifier	Sonoma	310B	120903	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC002	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH460B-N-2M	CC006	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH460B-N-12M	CC007	2024/03/29	2025/03/28
Test Software	Audix	E3	18621a	N/A	N/A
<b>Radiated Emission Above 1 GHz</b>					
Spectrum Analyzer	Rohde & Schwarz	FSU	100405	2024/03/29	2025/03/28
Horn Antenna	EMCO	3115	9002-3355	2024/11/19	2027/11/18
Preamplifier	A.H.Systems	PAM-0118P	489	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH800A-N-6M	CC003	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH800A-N-1M	CC005	2024/03/29	2025/03/28
Test Software	Audix	E3	18621a	N/A	N/A
<b>Scanning Receiver</b>					
Coaxial Cable	N/A	N/A	N/A	Each time	Each time
RF Communications test set	HP	8920A	3524A07202	2024/04/26	2025/04/25
Power Splitter	narda	4426LB-2	1661	N/A	N/A
Microwave Analog Signal Generator	Agilent	N5183A	MY47420335	2024/03/29	2025/03/28
Attenuator	Electronic Corporation	30-WA-FFN-30	1172435	2024/03/29	2025/03/28

**Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Xiamen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC §15.107 - CONDUCTED EMISSION

### Applicable Standard


FCC §15.107

(a) Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

\*Decreases with the logarithm of the frequency.

### Test System Setup



The measurement procedure of test setup is according with ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

## Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

## Result & Margin Calculation

The Result is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

$$\text{Result (dB}\mu\text{V)} = \text{Reading (dB}\mu\text{V)} + \text{Factor (dB)}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:


$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Result (dB}\mu\text{V)}$$

## Test Data

Note: The worst case as below.

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(435MHz)  
EUT Model: DM-32UV

Temp/Humi/ATM: 22.5°C /40%/100.1kPa  
Tested by: Apollo Luo  
Power Source: DC 5V from charger  
(AC 120V/60Hz)




Trace: 1

Condition: QP/AV RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.25	5.36	20.50	25.86	51.85	25.99	Line	Average
0.25	11.74	20.50	32.24	61.85	29.61	Line	QP
0.31	10.51	20.44	30.95	49.99	19.04	Line	Average
0.31	15.69	20.44	36.13	59.99	23.86	Line	QP
0.43	13.85	20.34	34.19	47.33	13.14	Line	Average
0.43	18.13	20.34	38.47	57.33	18.86	Line	QP
0.55	10.56	20.34	30.90	46.00	15.10	Line	Average
0.55	15.43	20.34	35.77	56.00	20.23	Line	QP
0.85	3.48	20.73	24.21	46.00	21.79	Line	Average
0.85	11.05	20.73	31.78	56.00	24.22	Line	QP
3.94	1.28	20.67	21.95	46.00	24.05	Line	Average
3.94	8.90	20.67	29.57	56.00	26.43	Line	QP

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(435MHz)  
EUT Model: DM-32UV

Temp/Humi/ATM: 22.5°C/40%/100.1kPa  
Tested by: Apollo Luo  
Power Source: DC 5V from charger  
(AC 120V/60Hz)



Trace: 1

Condition: QP/AV RBW:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.25	7.10	20.60	27.70	51.87	24.17	Neutral	Average
0.25	15.62	20.60	36.22	61.87	25.65	Neutral	QP
0.31	8.64	20.54	29.18	49.98	20.80	Neutral	Average
0.31	16.96	20.54	37.50	59.98	22.48	Neutral	QP
0.43	11.76	20.44	32.20	47.33	15.13	Neutral	Average
0.43	19.13	20.44	39.57	57.33	17.76	Neutral	QP
0.55	9.95	20.36	30.31	46.00	15.69	Neutral	Average
0.55	17.75	20.36	38.11	56.00	17.89	Neutral	QP
0.61	2.41	20.34	22.75	46.00	23.25	Neutral	Average
0.61	13.57	20.34	33.91	56.00	22.09	Neutral	QP
17.96	0.24	21.18	21.42	50.00	28.58	Neutral	Average
17.96	12.67	21.18	33.85	60.00	26.15	Neutral	QP

## FCC §15.109 - RADIATED EMISSION

### Applicable Standard


FCC§15.109

(a) Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:


Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

### Test System Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance

with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The system was investigated from 30 MHz to 5 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	PK
	120 kHz	/	QP
Above 1 GHz	1 MHz	3 MHz	PK
	1 MHz	10 Hz	AV

### Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

### Result & Margin Calculation

The Result is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Factor (dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

$$\text{Result (dB}\mu\text{V/m)} = \text{Reading (dB}\mu\text{V)} + \text{Factor (dB/m)}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Result (dB}\mu\text{V/m)}$$


## Test Data

Please refer to below plots:

### 1) 30MHz-1GHz:

Project No.: 2407A66953E-EM  
Test Mode: Mode 1(108-136MHz)  
EUT Model: DM-32UV  
Test distance: 3m


Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
150.47	31.62	-11.18	20.44	43.50	23.06	Horizontal	Peak
485.03	30.99	-3.60	27.39	46.00	18.61	Horizontal	Peak
638.48	29.48	-1.18	28.30	46.00	17.70	Horizontal	Peak
734.90	28.65	0.31	28.96	46.00	17.04	Horizontal	Peak
773.02	29.21	0.90	30.11	46.00	15.89	Horizontal	Peak
929.09	25.71	2.85	28.56	46.00	17.44	Horizontal	Peak


Project No.: 2407A66953E-EM  
Test Mode: Mode 1(108-136MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)



Project No.: 2407A66953E-EM  
Test Mode: Mode 1(136-174MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
53.86	33.07	-17.80	15.27	40.00	24.73	Horizontal	Peak
154.35	30.54	-11.28	19.26	43.50	24.24	Horizontal	Peak
178.02	30.30	-12.18	18.12	43.50	25.38	Horizontal	Peak
254.17	30.63	-11.39	19.24	46.00	26.76	Horizontal	Peak
536.34	30.70	-3.09	27.61	46.00	18.39	Horizontal	Peak
772.92	27.72	0.90	28.62	46.00	17.38	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 1(136-174MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
42.61	42.15	-13.59	28.56	40.00	11.44	Vertical	Peak
53.77	46.73	-17.79	28.94	40.00	11.06	Vertical	Peak
67.64	39.48	-17.11	22.37	40.00	17.63	Vertical	Peak
162.31	36.83	-11.46	25.37	43.50	18.13	Vertical	Peak
562.05	30.33	-2.55	27.78	46.00	18.22	Vertical	Peak
865.36	28.06	2.20	30.26	46.00	15.74	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 1(400-470MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.00	25.88	-5.60	20.28	40.00	19.72	Horizontal	Peak
126.81	29.66	-10.01	19.65	43.50	23.85	Horizontal	Peak
155.42	30.19	-11.36	18.83	43.50	24.67	Horizontal	Peak
718.60	28.17	0.01	28.18	46.00	17.82	Horizontal	Peak
813.18	28.44	1.40	29.84	46.00	16.16	Horizontal	Peak
948.01	26.60	3.13	29.73	46.00	16.27	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 1(400-470MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.39	41.84	-14.17	27.67	40.00	12.33	Vertical	Peak
52.80	44.66	-17.72	26.94	40.00	13.06	Vertical	Peak
132.63	32.72	-10.20	22.52	43.50	20.98	Vertical	Peak
161.14	33.58	-11.53	22.05	43.50	21.45	Vertical	Peak
551.57	32.44	-2.71	29.73	46.00	16.27	Vertical	Peak
691.44	29.37	-0.45	28.92	46.00	17.08	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 2(108-136MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
90.43	35.85	-17.01	18.84	43.50	24.66	Horizontal	Peak
153.58	32.02	-11.26	20.76	43.50	22.74	Horizontal	Peak
371.05	32.68	-7.35	25.33	46.00	20.67	Horizontal	Peak
494.63	31.97	-3.54	28.43	46.00	17.57	Horizontal	Peak
557.20	31.29	-2.62	28.67	46.00	17.33	Horizontal	Peak
830.44	28.86	1.77	30.63	46.00	15.37	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 2(108-136MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
42.03	37.57	-13.13	24.44	40.00	15.56	Vertical	Peak
53.28	45.37	-17.75	27.62	40.00	12.38	Vertical	Peak
87.81	43.14	-17.21	25.93	40.00	14.07	Vertical	Peak
132.14	34.16	-10.11	24.05	43.50	19.45	Vertical	Peak
151.06	35.46	-11.14	24.32	43.50	19.18	Vertical	Peak
711.43	29.50	-0.08	29.42	46.00	16.58	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 2(136-174MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.75	28.35	-6.27	22.08	40.00	17.92	Horizontal	Peak
53.57	32.06	-17.78	14.28	40.00	25.72	Horizontal	Peak
91.21	37.07	-17.04	20.03	43.50	23.47	Horizontal	Peak
366.30	32.58	-7.47	25.11	46.00	20.89	Horizontal	Peak
539.64	29.27	-3.01	26.26	46.00	19.74	Horizontal	Peak
724.23	28.55	0.06	28.61	46.00	17.39	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 2(136-174MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.10	38.46	-13.97	24.49	40.00	15.51	Vertical	Peak
53.86	44.61	-17.80	26.81	40.00	13.19	Vertical	Peak
89.27	43.61	-17.13	26.48	43.50	17.02	Vertical	Peak
152.22	36.63	-11.24	25.39	43.50	18.11	Vertical	Peak
600.75	31.68	-2.29	29.39	46.00	16.61	Vertical	Peak
626.16	31.54	-1.39	30.15	46.00	15.85	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 2(400-470MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47% /100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dB <sub>BuV</sub>	Factor dB/m	Result dB <sub>BuV/m</sub>	Limit dB <sub>BuV/m</sub>	Margin dB	Polarity	Remark
31.26	25.44	-6.00	19.44	40.00	20.56	Horizontal	Peak
151.25	30.20	-11.15	19.05	43.50	24.45	Horizontal	Peak
501.42	31.46	-3.39	28.07	46.00	17.93	Horizontal	Peak
529.94	32.45	-3.25	29.20	46.00	16.80	Horizontal	Peak
708.71	30.37	-0.12	30.25	46.00	15.75	Horizontal	Peak
720.74	29.05	0.05	29.10	46.00	16.90	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 2(400-470MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.48	37.40	-14.24	23.16	40.00	16.84	Vertical	Peak
53.77	46.37	-17.79	28.58	40.00	11.42	Vertical	Peak
89.36	41.61	-17.11	24.50	43.50	19.00	Vertical	Peak
136.22	34.28	-10.35	23.93	43.50	19.57	Vertical	Peak
151.06	36.71	-11.14	25.57	43.50	17.93	Vertical	Peak
552.44	32.85	-2.69	30.16	46.00	15.84	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(108.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.65	27.13	-6.21	20.92	40.00	19.08	Horizontal	Peak
143.59	32.21	-10.94	21.27	43.50	22.23	Horizontal	Peak
153.38	33.21	-11.28	21.93	43.50	21.57	Horizontal	Peak
513.35	32.16	-3.41	28.75	46.00	17.25	Horizontal	Peak
538.18	31.83	-3.05	28.78	46.00	17.22	Horizontal	Peak
729.08	29.14	0.09	29.23	46.00	16.77	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(108.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.77	38.30	-14.43	23.87	40.00	16.13	Vertical	Peak
53.18	44.02	-17.74	26.28	40.00	13.72	Vertical	Peak
67.73	39.65	-17.11	22.54	40.00	17.46	Vertical	Peak
132.14	33.28	-10.11	23.17	43.50	20.33	Vertical	Peak
555.93	33.63	-2.62	31.01	46.00	14.99	Vertical	Peak
711.91	30.18	-0.08	30.10	46.00	15.90	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(122MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.00	25.59	-5.60	19.99	40.00	20.01	Horizontal	Peak
153.97	31.03	-11.21	19.82	43.50	23.68	Horizontal	Peak
380.66	31.67	-7.09	24.58	46.00	21.42	Horizontal	Peak
490.56	30.53	-3.66	26.87	46.00	19.13	Horizontal	Peak
552.64	30.02	-2.69	27.33	46.00	18.67	Horizontal	Peak
637.80	29.37	-1.19	28.18	46.00	17.82	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(122MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.48	41.98	-14.24	27.74	40.00	12.26	Vertical	Peak
55.12	43.26	-17.81	25.45	40.00	14.55	Vertical	Peak
273.96	36.70	-9.67	27.03	46.00	18.97	Vertical	Peak
559.52	33.54	-2.60	30.94	46.00	15.06	Vertical	Peak
615.30	33.90	-1.82	32.08	46.00	13.92	Vertical	Peak
745.86	30.29	0.46	30.75	46.00	15.25	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(135.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.16	26.50	-5.94	20.56	40.00	19.44	Horizontal	Peak
129.23	30.25	-10.03	20.22	43.50	23.28	Horizontal	Peak
273.96	33.02	-9.67	23.35	46.00	22.65	Horizontal	Peak
533.33	30.63	-3.16	27.47	46.00	18.53	Horizontal	Peak
697.85	30.40	-0.43	29.97	46.00	16.03	Horizontal	Peak
813.18	29.23	1.40	30.63	46.00	15.37	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(135.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.58	39.11	-14.30	24.81	40.00	15.19	Vertical	Peak
54.06	45.79	-17.81	27.98	40.00	12.02	Vertical	Peak
80.83	39.72	-17.06	22.66	40.00	17.34	Vertical	Peak
154.06	34.40	-11.22	23.18	43.50	20.32	Vertical	Peak
559.91	33.01	-2.60	30.41	46.00	15.59	Vertical	Peak
611.32	32.28	-1.99	30.29	46.00	15.71	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(136.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m


Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
273.96	33.13	-9.67	23.46	46.00	22.54	Horizontal	Peak
465.82	29.27	-4.31	24.96	46.00	21.04	Horizontal	Peak
531.49	30.50	-3.21	27.29	46.00	18.71	Horizontal	Peak
654.97	29.44	-0.98	28.46	46.00	17.54	Horizontal	Peak
753.72	28.20	0.50	28.70	46.00	17.30	Horizontal	Peak
836.17	27.25	1.79	29.04	46.00	16.96	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(136.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
42.90	41.18	-13.82	27.36	40.00	12.64	Vertical	Peak
53.47	44.36	-17.77	26.59	40.00	13.41	Vertical	Peak
67.15	40.82	-17.12	23.70	40.00	16.30	Vertical	Peak
160.27	36.10	-11.48	24.62	43.50	18.88	Vertical	Peak
677.28	31.17	-0.65	30.52	46.00	15.48	Vertical	Peak
837.14	28.89	1.79	30.68	46.00	15.32	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(155MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.36	25.26	-6.04	19.22	40.00	20.78	Horizontal	Peak
527.32	31.32	-3.31	28.01	46.00	17.99	Horizontal	Peak
684.65	30.49	-0.49	30.00	46.00	16.00	Horizontal	Peak
706.58	30.60	-0.17	30.43	46.00	15.57	Horizontal	Peak
749.06	30.82	0.53	31.35	46.00	14.65	Horizontal	Peak
802.99	28.85	1.26	30.11	46.00	15.89	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(155MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.39	38.64	-14.17	24.47	40.00	15.53	Vertical	Peak
53.47	43.88	-17.77	26.11	40.00	13.89	Vertical	Peak
67.44	41.68	-17.11	24.57	40.00	15.43	Vertical	Peak
133.31	34.68	-10.26	24.42	43.50	19.08	Vertical	Peak
556.61	33.30	-2.62	30.68	46.00	15.32	Vertical	Peak
772.92	30.46	0.90	31.36	46.00	14.64	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(173.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.10	25.12	-5.63	19.49	40.00	20.51	Horizontal	Peak
118.17	28.93	-10.49	18.44	43.50	25.06	Horizontal	Peak
695.42	29.67	-0.43	29.24	46.00	16.76	Horizontal	Peak
723.07	31.68	0.06	31.74	46.00	14.26	Horizontal	Peak
773.02	30.06	0.90	30.96	46.00	15.04	Horizontal	Peak
820.84	28.88	1.63	30.51	46.00	15.49	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(173.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
42.42	41.61	-13.44	28.17	40.00	11.83	Vertical	Peak
53.28	45.94	-17.75	28.19	40.00	11.81	Vertical	Peak
66.67	40.23	-17.19	23.04	40.00	16.96	Vertical	Peak
117.88	33.29	-10.51	22.78	43.50	20.72	Vertical	Peak
132.63	33.07	-10.20	22.87	43.50	20.63	Vertical	Peak
552.73	35.14	-2.69	32.45	46.00	13.55	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(400.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m


Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.00	25.54	-5.60	19.94	40.00	20.06	Horizontal	Peak
152.71	31.61	-11.29	20.32	43.50	23.18	Horizontal	Peak
640.71	28.89	-1.13	27.76	46.00	18.24	Horizontal	Peak
738.88	27.47	0.32	27.79	46.00	18.21	Horizontal	Peak
837.33	26.54	1.79	28.33	46.00	17.67	Horizontal	Peak
855.96	25.56	1.98	27.54	46.00	18.46	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(400.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m


Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
42.71	38.86	-13.67	25.19	40.00	14.81	Vertical	Peak
53.77	44.87	-17.79	27.08	40.00	12.92	Vertical	Peak
160.27	34.59	-11.48	23.11	43.50	20.39	Vertical	Peak
273.96	34.79	-9.67	25.12	46.00	20.88	Vertical	Peak
806.00	29.03	1.29	30.32	46.00	15.68	Vertical	Peak
837.53	29.65	1.80	31.45	46.00	14.55	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(435MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.46	26.79	-6.10	20.69	40.00	19.31	Horizontal	Peak
151.15	30.55	-11.15	19.40	43.50	24.10	Horizontal	Peak
263.96	30.84	-10.47	20.37	46.00	25.63	Horizontal	Peak
810.07	28.00	1.39	29.39	46.00	16.61	Horizontal	Peak
872.15	27.48	2.17	29.65	46.00	16.35	Horizontal	Peak
966.05	29.89	3.48	33.37	54.00	20.63	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(435MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
39.60	38.96	-11.38	27.58	40.00	12.42	Vertical	Peak
46.88	43.94	-16.28	27.66	40.00	12.34	Vertical	QP
148.53	34.69	-11.15	23.54	43.50	19.96	Vertical	Peak
629.94	36.20	-1.37	34.83	46.00	11.17	Vertical	QP
713.95	34.35	-0.07	34.28	46.00	11.72	Vertical	Peak
966.05	34.19	3.48	37.67	54.00	16.33	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(469.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m


Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.68	25.66	-5.77	19.89	40.00	20.11	Horizontal	Peak
149.60	29.71	-11.23	18.48	43.50	25.02	Horizontal	Peak
257.95	32.44	-11.17	21.27	46.00	24.73	Horizontal	Peak
629.95	30.45	-1.37	29.08	46.00	16.92	Horizontal	Peak
889.42	26.62	2.49	29.11	46.00	16.89	Horizontal	Peak
966.05	30.89	3.48	34.37	54.00	19.63	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 3(469.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Charger  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
39.80	39.67	-11.55	28.12	40.00	11.88	Vertical	Peak
46.79	43.76	-16.23	27.53	40.00	12.47	Vertical	QP
273.96	33.16	-9.67	23.49	46.00	22.51	Vertical	Peak
630.01	36.65	-1.37	35.28	46.00	10.72	Vertical	QP
714.04	33.89	-0.07	33.82	46.00	12.18	Vertical	Peak
966.05	35.45	3.48	38.93	54.00	15.07	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(108.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.00	26.29	-5.60	20.69	40.00	19.31	Horizontal	Peak
152.12	30.73	-11.23	19.50	43.50	24.00	Horizontal	Peak
273.96	31.92	-9.67	22.25	46.00	23.75	Horizontal	Peak
501.13	30.89	-3.39	27.50	46.00	18.50	Horizontal	Peak
559.43	29.24	-2.60	26.64	46.00	19.36	Horizontal	Peak
825.59	27.86	1.66	29.52	46.00	16.48	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(108.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
42.42	38.40	-13.44	24.96	40.00	15.04	Vertical	Peak
53.77	45.99	-17.79	28.20	40.00	11.80	Vertical	Peak
66.18	41.11	-17.29	23.82	40.00	16.18	Vertical	Peak
536.34	33.43	-3.09	30.34	46.00	15.66	Vertical	Peak
556.61	33.60	-2.62	30.98	46.00	15.02	Vertical	Peak
608.22	31.01	-2.13	28.88	46.00	17.12	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(122MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.65	28.95	-6.21	22.74	40.00	17.26	Horizontal	Peak
273.96	33.40	-9.67	23.73	46.00	22.27	Horizontal	Peak
531.20	32.43	-3.22	29.21	46.00	16.79	Horizontal	Peak
573.78	30.88	-2.51	28.37	46.00	17.63	Horizontal	Peak
794.36	27.18	1.22	28.40	46.00	17.60	Horizontal	Peak
862.65	26.04	2.15	28.19	46.00	17.81	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(122MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
42.22	41.31	-13.29	28.02	40.00	11.98	Vertical	Peak
53.77	43.19	-17.79	25.40	40.00	14.60	Vertical	Peak
66.96	41.53	-17.13	24.40	40.00	15.60	Vertical	Peak
273.96	34.63	-9.67	24.96	46.00	21.04	Vertical	Peak
604.43	32.36	-2.28	30.08	46.00	15.92	Vertical	Peak
873.51	28.13	2.20	30.33	46.00	15.67	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(135.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.87	26.27	-5.82	20.45	40.00	19.55	Horizontal	Peak
273.96	34.08	-9.67	24.41	46.00	21.59	Horizontal	Peak
670.20	30.36	-0.63	29.73	46.00	16.27	Horizontal	Peak
721.61	30.01	0.05	30.06	46.00	15.94	Horizontal	Peak
807.84	29.45	1.34	30.79	46.00	15.21	Horizontal	Peak
914.06	26.69	2.70	29.39	46.00	16.61	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(135.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.19	42.54	-14.03	28.51	40.00	11.49	Vertical	Peak
53.38	44.93	-17.76	27.17	40.00	12.83	Vertical	Peak
66.86	41.43	-17.15	24.28	40.00	15.72	Vertical	Peak
273.96	35.32	-9.67	25.65	46.00	20.35	Vertical	Peak
702.21	29.95	-0.32	29.63	46.00	16.37	Vertical	Peak
950.72	27.16	3.15	30.31	46.00	15.69	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(136.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.10	25.34	-5.63	19.71	40.00	20.29	Horizontal	Peak
273.96	34.08	-9.67	24.41	46.00	21.59	Horizontal	Peak
371.54	30.19	-7.34	22.85	46.00	23.15	Horizontal	Peak
469.12	31.53	-4.23	27.30	46.00	18.70	Horizontal	Peak
525.86	28.94	-3.35	25.59	46.00	20.41	Horizontal	Peak
659.72	30.27	-0.88	29.39	46.00	16.61	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(136.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.29	39.66	-14.10	25.56	40.00	14.44	Vertical	Peak
53.09	44.96	-17.73	27.23	40.00	12.77	Vertical	Peak
66.08	41.53	-17.31	24.22	40.00	15.78	Vertical	Peak
273.96	34.89	-9.67	25.22	46.00	20.78	Vertical	Peak
554.09	33.12	-2.65	30.47	46.00	15.53	Vertical	Peak
836.26	26.65	1.79	28.44	46.00	17.56	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(155MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
32.52	25.98	-6.68	19.30	40.00	20.70	Horizontal	Peak
273.96	34.41	-9.67	24.74	46.00	21.26	Horizontal	Peak
506.95	32.57	-3.37	29.20	46.00	16.80	Horizontal	Peak
558.26	32.45	-2.61	29.84	46.00	16.16	Horizontal	Peak
730.34	30.32	0.10	30.42	46.00	15.58	Horizontal	Peak
859.54	29.05	2.06	31.11	46.00	14.89	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(155MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.00	39.58	-13.90	25.68	40.00	14.32	Vertical	Peak
53.38	46.11	-17.76	28.35	40.00	11.65	Vertical	Peak
510.05	31.33	-3.35	27.98	46.00	18.02	Vertical	Peak
715.98	29.40	-0.05	29.35	46.00	16.65	Vertical	Peak
790.00	29.56	1.11	30.67	46.00	15.33	Vertical	Peak
886.41	28.54	2.41	30.95	46.00	15.05	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(173.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.07	27.33	-5.89	21.44	40.00	18.56	Horizontal	Peak
273.96	32.81	-9.67	23.14	46.00	22.86	Horizontal	Peak
624.03	30.99	-1.44	29.55	46.00	16.45	Horizontal	Peak
657.59	30.90	-0.93	29.97	46.00	16.03	Horizontal	Peak
777.97	27.81	1.03	28.84	46.00	17.16	Horizontal	Peak
951.21	25.27	3.16	28.43	46.00	17.57	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(173.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
43.10	40.38	-13.97	26.41	40.00	13.59	Vertical	Peak
53.57	40.88	-17.78	23.10	40.00	16.90	Vertical	Peak
153.77	33.01	-11.23	21.78	43.50	21.72	Vertical	Peak
273.96	35.58	-9.67	25.91	46.00	20.09	Vertical	Peak
552.83	32.73	-2.68	30.05	46.00	15.95	Vertical	Peak
773.80	29.66	0.92	30.58	46.00	15.42	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(400.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C /47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.16	27.88	-5.94	21.94	40.00	18.06	Horizontal	Peak
178.70	32.75	-12.25	20.50	43.50	23.00	Horizontal	Peak
686.21	29.89	-0.47	29.42	46.00	16.58	Horizontal	Peak
708.32	29.06	-0.12	28.94	46.00	17.06	Horizontal	Peak
881.66	27.30	2.36	29.66	46.00	16.34	Horizontal	Peak
985.45	26.73	3.79	30.52	54.00	23.48	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(400.0125MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
53.09	47.52	-17.73	29.79	40.00	10.21	Vertical	Peak
99.55	42.70	-15.06	27.64	43.50	15.86	Vertical	Peak
151.93	36.35	-11.21	25.14	43.50	18.36	Vertical	Peak
274.05	34.10	-9.67	24.43	46.00	21.57	Vertical	Peak
493.56	32.68	-3.57	29.11	46.00	16.89	Vertical	Peak
560.11	33.00	-2.60	30.40	46.00	15.60	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(435MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.29	26.02	-5.68	20.34	40.00	19.66	Horizontal	Peak
151.64	29.68	-11.18	18.50	43.50	25.00	Horizontal	Peak
545.85	30.80	-2.94	27.86	46.00	18.14	Horizontal	Peak
630.04	32.23	-1.37	30.86	46.00	15.14	Horizontal	Peak
839.76	28.10	1.80	29.90	46.00	16.10	Horizontal	Peak
966.15	28.95	3.48	32.43	54.00	21.57	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(435MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
47.65	46.32	-16.68	29.64	40.00	10.36	Vertical	Peak
87.42	41.72	-17.26	24.46	40.00	15.54	Vertical	Peak
149.41	37.30	-11.23	26.07	43.50	17.43	Vertical	Peak
630.04	35.75	-1.37	34.38	46.00	11.62	Vertical	Peak
714.04	34.25	-0.07	34.18	46.00	11.82	Vertical	Peak
966.05	32.16	3.48	35.64	54.00	18.36	Vertical	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(469.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m


Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.39	26.03	-5.70	20.33	40.00	19.67	Horizontal	Peak
152.22	29.93	-11.24	18.69	43.50	24.81	Horizontal	Peak
273.96	30.95	-9.67	21.28	46.00	24.72	Horizontal	Peak
629.95	30.34	-1.37	28.97	46.00	17.03	Horizontal	Peak
809.69	27.82	1.37	29.19	46.00	16.81	Horizontal	Peak
966.05	31.50	3.48	34.98	54.00	19.02	Horizontal	Peak

Project No.: 2407A66953E-EM  
Test Mode: Mode 4(469.9875MHz)  
EUT Model: DM-32UV  
Test distance: 3m

Temp/Humi/ATM: 23.3°C/47%/100.1kPa  
Tested by: Jason Hu  
Power Source: DC 5V from Adapter  
(AC 120V/60Hz)




Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
39.02	40.10	-10.87	29.23	40.00	10.77	Vertical	Peak
47.75	46.47	-16.73	29.74	40.00	10.26	Vertical	Peak
148.92	38.40	-11.22	27.18	43.50	16.32	Vertical	Peak
630.04	36.96	-1.37	35.59	46.00	10.41	Vertical	Peak
713.95	32.84	-0.07	32.77	46.00	13.23	Vertical	Peak
966.05	34.84	3.48	38.32	54.00	15.68	Vertical	Peak

## 2) 1GHz ~ 5GHz (Worst Case)

Project No.: 2407A66953E-EM  
 Test Mode: Mode 3(435MHz)  
 EUT Model: DM-32UV  
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa  
 Tested by: Jason Hu  
 Power Source: DC 5V from Charger  
 (AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2624.00	27.85	-2.72	25.13	54.00	28.87	horizontal	Average
2624.00	46.36	-2.72	43.64	74.00	30.36	horizontal	Peak
2901.60	27.12	-3.72	23.40	54.00	30.60	horizontal	Average
2901.60	46.52	-3.72	42.80	74.00	31.20	horizontal	Peak
3151.20	25.78	-2.25	23.53	54.00	30.47	horizontal	Average
3151.20	46.54	-2.25	44.29	74.00	29.71	horizontal	Peak
3453.60	27.43	-2.95	24.48	54.00	29.52	horizontal	Average
3453.60	46.73	-2.95	43.78	74.00	30.22	horizontal	Peak
4063.60	27.13	-3.39	23.74	54.00	30.26	horizontal	Average
4063.60	46.68	-3.39	43.29	74.00	30.71	horizontal	Peak
4967.20	26.89	-4.65	22.24	54.00	31.76	horizontal	Average
4967.20	46.52	-4.65	41.87	74.00	32.13	horizontal	Peak

Project No.: 2407A66953E-EM  
 Test Mode: Mode 3(435MHz)  
 EUT Model: DM-32UV  
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa  
 Tested by: Jason Hu  
 Power Source: DC 5V from Charger  
 (AC 120V/60Hz)



Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2510.80	27.25	-3.39	23.86	54.00	30.14	vertical	Average
2510.80	46.61	-3.39	43.22	74.00	30.78	vertical	Peak
2916.40	27.01	-3.66	23.35	54.00	30.65	vertical	Average
2916.40	46.41	-3.66	42.75	74.00	31.25	vertical	Peak
3150.80	26.17	-2.25	23.92	54.00	30.08	vertical	Average
3150.80	46.85	-2.25	44.60	74.00	29.40	vertical	Peak
3476.80	27.63	-3.15	24.48	54.00	29.52	vertical	Average
3476.80	46.76	-3.15	43.61	74.00	30.39	vertical	Peak
3953.20	27.58	-3.54	24.04	54.00	29.96	vertical	Average
3953.20	46.45	-3.54	42.91	74.00	31.09	vertical	Peak
4985.20	26.87	-4.56	22.31	54.00	31.69	vertical	Average
4985.20	47.31	-4.56	42.75	74.00	31.25	vertical	Peak

## FCC §15.121(b) – SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING RECEIVERS


### Applicable Standard

FCC §15.121(b).

(b) Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

### Test Procedure

1. Connected the EUT as the below block diagram;



2. Apply a signal to the EUT antenna port at lowest, middle, highest channel frequencies of the operating band;
3. Adjust the audio output level of the EUT to it's rated value with the distortion less than 10%;
4. Adjust the 8920 output power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB; These output level of the 8920 at each channel frequency is the sensitivity of the EUT;
5. Select the lowest or worst case sensitivity level for all of the bands as the reference sensitivity;
6. Adjust the Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step 5 and its frequency to the frequency point in the Cellular Band;
7. Set the EUT squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level;
8. Set the EUT in a scanning mode and allow it to scan through it's complete receiving range;
9. If the EUT un-squelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38 dB;
10. Repeat above procedure at the frequencies 824, 836, 849 MHz for the mobile band, and 869, 881.5 and 894 MHz for the Cellular Base Band.

**Test Data**

<b>Test Mode:</b>	Scanning	<b>Test Engineer:</b>	Lucas Lin
<b>Test Date:</b>	2025-02-20	<b>Test Result:</b>	Pass

**Environment Conditions:**

Temperature: (°C)	21.7	Relative Humidity: (%)	41	ATM Pressure: (kPa)	100.1
----------------------	------	------------------------------	----	------------------------	-------

<b>Scanning Frequency Range (MHz)</b>	<b>Test Frequency (MHz)</b>	<b>Measurement Result (Worst Case) (dB)</b>	<b>Limit (dB)</b>
108-136	824, 836, 849, 869, 881.5, 895	48	>38
136-174	824, 836, 849, 869, 881.5, 896	46	>38
400-470	824, 836, 849, 869, 881.5, 899	48	>38

---

## **EXHIBIT A - EUT PHOTOGRAPHS**

---

Please refer to the attachment 2407A66953E-RF-EXP EUT EXTERNAL PHOTOS and  
2407A66953E-RF-INP EUT INTERNAL PHOTOS

---

## **EXHIBIT B – TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment 2407A66953E-RF-TSP-01 EUT SETUP PHOTOS.

## Declarations

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor k=2 with the 95 % confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

\*\*\*\*\*END OF REPORT\*\*\*\*\*