




BELKIN INTERNATIONAL

12045 East Waterfront Drive
Playa Vista, CA 90094-2536 USA
P 310 751 5100
F 310 751 5969
belkin.com



Applicant: Belkin International, Inc.	
FCC ID: K7SF8J235	
RF Exposure Requirements (FCC KDB 680106 D01 V03)	
Requirements	Statements
(a) Power transfer frequency is less than 1 MHz	Operates at 127.77KHz & 326.5KHz
(b) Output power from each primary coil is less than 15 watts	Dimension for Phone charging coil: 13.53cm ² (diameter = 41.5mm) Max output Power for Phone charging coil: 10W Dimension for watch inductive charging coil: 7.95cm ² (diameter = 31.82mm) Max output Power for watch inductive charging coil: 5W
(c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils	Two coil one for 127.77KHz the other for 326.5KHz. Single coil per client
(d) Client device is inserted in or placed directly in contact with the transmitter	Client device is placed directly in contact with the transmitter
(e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	It's mobile device, and provided RF exposure report to evaluate
(f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Please refer to RF Exposure Report.

Rajesh Karki /
Manager, Regulatory Compliance
Belkin International, Inc.
Tel: 310-751-2817
E-mail: rajesh.karki@belkin.com