



**EMC Technologies Pty Ltd**

ABN 82 057 105 549  
176 Harrick Road  
Keilor Park  
Victoria Australia 3042

Ph: + 613 9365 1000  
Fax: + 613 9331 7455  
email: melb@emctech.com.au

## SAR Test Report

**Report Number: M161026FR1\_FCC\_8265NGW\_SAR\_2.4**

**Test Sample:** Portable P Series LIFEBOOK  
Convertible Computer

**Radio Modules:** WLAN & Bluetooth module 8265NGW

**Host PC Model Number:** P727

**FCC ID:** EJE-WB0100

**IC ID:** 337J-WB0100

**Date of Issue:** 28<sup>th</sup> November 2016

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**Table 1**

Table of Revisions				
Report Number	Revision Number	Description	Pages affected	Date
M161026F_FCC_8265NGW_SAR_2.4	1	Original	N/A	25th November 2016
M161026FR1_FCC_8265NGW_SAR_2.4	2	Original	All	28th November 2016



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## CONTENTS

<b>1.0 GENERAL INFORMATION.....</b>	<b>4</b>
<b>2.0 INTRODUCTION.....</b>	<b>5</b>
<b>3.0 TEST SAMPLE TECHNICAL INFORMATION.....</b>	<b>6</b>
3.1 Radio Module (WLAN+BT) Details.....	6
3.2 DUT (Notebook PC) Details .....	11
3.3 Test Sample Accessories.....	11
3.3.1 Battery Types .....	11
<b>4.0 TEST SIGNAL, FREQUENCY AND OUTPUT POWER.....</b>	<b>12</b>
4.1 Battery Status.....	12
<b>5.0 DETAILS OF TEST LABORATORY .....</b>	<b>13</b>
5.1 Location .....	13
5.2 Accreditations.....	13
5.3 Environmental Factors .....	13
<b>6.0 CALIBRATION AND VERIFICATION PROCEDURES AND DATA .....</b>	<b>14</b>
6.1 System verification .....	14
6.1.1 System verification Results @ 2450MHz.....	14
6.1.2 Liquid Temperature and Humidity.....	14
<b>7.0 SAR MEASUREMENT PROCEDURE USING DASY5 .....</b>	<b>15</b>
<b>8.0 MEASUREMENT UNCERTAINTY .....</b>	<b>16</b>
<b>9.0 EQUIPMENT LIST AND CALIBRATION DETAILS.....</b>	<b>19</b>
<b>10.0 TEST METHODOLOGY.....</b>	<b>20</b>
10.1 Positions .....	20
10.1.1 "Lap Held" Position Definition (0mm spacing).....	20
10.1.2 "Edge On" Position (Portrait or Landscape).....	20
10.1.3 "Bystander" Position (25mm spacing).....	20
10.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes).....	21
<b>11.0 SAR MEASUREMENT RESULTS .....</b>	<b>22</b>
11.1 2450MHz SAR Results.....	22
<b>12.0 COMPLIANCE STATEMENT .....</b>	<b>25</b>
<b>13.0 MULTIBAND EVALUATION CONSIDERATIONS.....</b>	<b>26</b>
<b>APPENDIX A1 TEST SAMPLE PHOTOGRAPHS .....</b>	<b>27</b>
<b>APPENDIX A2 TEST SAMPLE PHOTOGRAPHS .....</b>	<b>28</b>
<b>APPENDIX A3 TEST SAMPLE PHOTOGRAPHS .....</b>	<b>29</b>
<b>APPENDIX A4 TEST SETUP PHOTOGRAPHS .....</b>	<b>30</b>
<b>APPENDIX A5 TEST SETUP PHOTOGRAPHS .....</b>	<b>31</b>
<b>APPENDIX A6 TEST SETUP PHOTOGRAPHS .....</b>	<b>32</b>
<b>APPENDIX A7 TEST SETUP PHOTOGRAPHS .....</b>	<b>33</b>
<b>APPENDIX A8 TEST SETUP PHOTOGRAPHS .....</b>	<b>34</b>
<b>APPENDIX B PLOTS OF THE SAR MEASUREMENTS .....</b>	<b>35</b>
<b>APPENDIX C DESCRIPTION OF SAR MEASUREMENT SYSTEM.....</b>	<b>108</b>
Tissue Material Properties .....	109
Simulated Tissue Composition Used for SAR Test.....	109
<b>APPENDIX D CALIBRATION DOCUMENTS .....</b>	<b>110</b>



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**SAR TEST REPORT**

**Report Number: M161026FR1\_FCC\_8265NGW\_SAR\_2.4**  
**FCC ID: EJE-WB0100 IC ID: 337J-WB0100**

**1.0 GENERAL INFORMATION**

**Test Sample:** Portable P Series LIFEBOOK Convertible Computer  
**Model Name:** P727  
**Radio Modules:** WLAN & Bluetooth 8265NGW  
**Interface Type:** M.2 Wireless LAN Module  
**Device Category:** Portable Transmitter  
**Test Device:** Pre-Production Unit  
**FCC ID:** EJE-WB0100  
**IC ID:** 337J-WB0100  
**RF exposure Category:** General Population/Uncontrolled


**Manufacturer:** Fujitsu Limited


**FCC KDB Procedures:** 1\* 248227 D01 802 11 Wi-Fi SAR v02r02  
 447498 D01 General RF Exposure Guidance v06  
 616217 D04 SAR for laptop and tablets v01r02  
 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04  
 865664 D02 RF Exposure Reporting v01r02

**Test Standard/s:** 1\* Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), RSS-102  
 2. **EN 62209-2:2010**  
 Human exposure to radio frequency fields from hand-held and bodymounted wireless communication devices. Human models, instrumentation, and procedures.  
**Part 2:** Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)  
 3. **IEEE 1528: 2013**  
 Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.

**Statement Of Compliance:** The Fujitsu P Series LIFEBOOK Convertible Computer P727 with Wireless LAN and Bluetooth model 8265NGW complied with the FCC General public/uncontrolled RF exposure limits of 1.6mW/g per requirements of 47CFR2.1093(d). It also complied with ISSED RSS-102 requirements.

**Highest Reported SAR:** 2450 MHz WLAN Band – 0.318 mW/g  
**Test Dates:** 26<sup>th</sup> to 28<sup>th</sup> October 2016

**Test Officer:**   
 Peter Jakubiec

**Authorised Signature:**   
 Chris Zombolas  
 Technical Director

\*Not within the current scope of NATA accreditation



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**SAR TEST REPORT****Portable P Series LIFEBOOK Convertible Computer****Model: P727****Report Number: M161026FR1\_FCC\_8265NGW\_SAR\_2.4****2.0 INTRODUCTION**

Testing was performed on the Fujitsu P Series LIFEBOOK Convertible PC, Model: P727 with M.2 integrated Wireless LAN & Bluetooth Module (Windstorm Peak 802.11a/b/g/n/ac), Model: 8265NGW. The 8265NGW WLAN module was originally certified by INTEL Corporation as a modular approval under FCC ID: PD98265NG IC ID: 1000M-8265NG. The Intel Windstorm Peak module is an OEM product, it was tested in the dedicated host – LIFEBOOK P SERIES, Model P727. The system tested will be referred to as the DUT throughout this report.

The Wireless LAN Module incorporates a Bluetooth Transmitter, which can only transmit via Antenna B (2), the Bluetooth maximum power was 11.5 dBm (including tune-up) therefore it requires SAR testing as a stand-alone transmitter.

The measurement test results mentioned herein only apply to the 2450MHz frequency band; an additional report titled "M161026FR1\_FCC\_8265NGW\_SAR\_5.6" applies to the 5GHz range.

**Table 2**

Applicable Head Configurations	: None
Applicable Body Configurations	: Lap Held Position
	: Edge On Position
	: Bystander



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

### 3.0 TEST SAMPLE TECHNICAL INFORMATION

(Information supplied by the client)

#### 3.1 Radio Module (WLAN+BT) Details

Table 3

<b>Transmitter:</b>	M.2 Wireless LAN Module (WLAN parts)
<b>Wireless Module:</b>	Intel Dual Band Wireless-AC 8265 (Windstorm Peak) (11ac/abgn)
<b>Model Number:</b>	8265NGW
<b>Manufacturer:</b>	Intel Corporation
<b>Wi-Fi standard</b>	802.11ac 2x2
<b>Wi-Fi TX/RX chains</b>	2x2 chains
<b>Supported Bands</b>	2.4GHz, 5GHz
<b>Antenna Allocation</b>	Main: Wi-Fi only, Aux: Shared Wi-Fi, BT
<b>Wi-Fi TX/RX Throughput</b>	660 Mbps
<b>Bluetooth Core</b>	Bluetooth 4.1
<b>Antenna Types:</b>	Nissei Inverted F antenna Model: refer to WLAN antenna data Location: refer to Antenna location file For BT: use Aux(right side connect on module)
<b>Antenna gain:</b>	Please refer antenna data provided separately
<b>Power Supply:</b>	3.3 VDC from PCI bus



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**Table 4 WLAN Channels and Output power setting****2.4 GHz (802.11b, 802.11g and 802.11n/ac)**

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)		
					Ch A		Ch B	Power Control Tx A (Main- 1)	Power Control Tx B (Aux -2)	Tx A	Tx B
802.11b 2.4 GHz	1	2412	CCK 1	20MHz 99%DC	15.0		15.0	-	-	-	-
	6	2437						-	-	-	-
	7	2442						15.00	15.50	14.78	14.75
	11	2462						-	-	-	-
	12	2467			14.0	-	-	-	-		
	13	2472			8.0	8.0	-	-	-	-	
802.11g 2.4 GHz	1	2412	OFDM 6	20MHz 99%DC	15.0		15.0	-	-	-	-
	2	2417						-	-	-	-
	6	2437						-	-	-	-
	10	2457						-	-	-	-
	11	2462			15.25	15.125	14.80	14.75			
	12	2467			12.0	13.0	-	-	-	-	
	13	2472			-4.0	-4.0	-	-	-	-	
802.11n 2.4 GHz	3F	2422	CCK HT0	40 98%DC	15.0		15.0	15.125	15.25	14.80	14.76
	4F	2427						-	-	-	-
	5F	2432						-	-	-	-
	6F	2437						15.00	15.25	14.84	14.81
	7F	2442						15.00	15.375	14.98	14.83
	8F	2447			-	-	-	-			
	9F	2452			-	-	-	-			
	10F	2457			14.0	15.125	15.375	14.86	14.89		
	11F	2462			8.0	8.0	-	-	-	-	
	3F	2422	OFDM HT0	40 98%DC	13.0		15.0	-	-	-	-
	4F	2427			15.0			-	-	-	-
	5F	2432						-	-	-	-
	6F	2437						-	-	-	-
7F	2442	-						-	-	-	
8F	2447	-				-	-	-			
9F	2452	-				-	-	-			
10F	2457	12.0			12.0	-	-	-	-		
11F	2462	-5.0			-5.0	-	-	-	-		



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**5 GHz (802.11a)**

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)					
					Ch A		Ch B	Power Control Tx A (Main- 1)	Power Control Tx B (Aux -2)	Tx A	Tx B			
802.11a	5.2 GHz		OFDM 6	20 99%DC	13.5	13.5								
	36	5180					-	-	-	-				
	40	5200					-	-	-	-				
	44	5220					-	-	-	-				
	48	5240					-	-	-	-				
	5.3 GHz				13.5	13.5								
	52	5260					-	-	-	-				
	56	5280					-	-	-	-				
	60	5300					-	-	-	-				
	64	5320					-	-	-	-				
	5.6 GHz				13.5	13.5								
	100	5500					-	-	-	-				
	104	5520					-	-	-	-				
	108	5540					-	-	-	-				
	112	5560					-	-	-	-				
	116	5580					-	-	-	-				
	120	5600					-	-	-	-				
	124	5620					-	-	-	-				
	128	5640					-	-	-	-				
	5.65 to 5.835 GHz	132					5660	-	-	-	-			
		136					5680	-	-	-	-			
		140					5700	-	-	-	-			
		5.8 GHz					13.5	13.5						
		149							5745	-	-	-	-	
	153	5765			-	-			-	-				
	157	5785			-	-			-	-				
	161	5805			-	-			-	-				
	165	5825			-	-	-	-						



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



**5 GHz (802.11n)**

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)				
					Ch A	Ch B	Power Control Tx A (Main- 1)	Power Control Tx B (Aux -2)	Tx A	Tx B			
802.11n	5.2 GHz		OFDM HT0	20 99%DC									
	36	5180			13.5	13.5	-	-	-	-			
	40	5200					-	-	-	-			
	44	5220					-	-	-	-			
	48	5240					-	-	-	-			
	5.3 GHz												
	52	5260			13.5	13.5	-	-	-	-			
	56	5280					-	-	-	-			
	60	5300					-	-	-	-			
	64	5320					-	-	-	-			
	5.6 GHz												
	100	5500			13.5	13.5	-	-	-	-			
	104	5520					-	-	-	-			
	108	5540					-	-	-	-			
	112	5560					-	-	-	-			
	116	5580					-	-	-	-			
	120	5600					-	-	-	-			
	124	5620					-	-	-	-			
	128	5640					-	-	-	-			
	5.65 to 5.835 GHz	132					5660	13.5	13.5	-	-	-	-
		136					5680			-	-	-	-
		140			5700	-	-			-	-		
		5.8 GHz			-	-	-			-			
		149			5745	-	-			-	-		
		153			5765	-	-			-	-		
	5.65 to 5.835 GHz	157			5785	13.5	13.5	-	-	-	-		
		161			5805			-	-	-	-		
		165			5825			-	-	-	-		
								-	-	-	-		
	5.2 GHz												
	38	5190			13.5	13.5	12.75	13.125	13.37	13.40			
	46	5230		12.875			13.375	13.41	13.39				
	5.3 GHz												
	54	5270		13.5	13.5	12.75	13.00	13.43	13.40				
	62	5310				12.75	13.00	13.47	13.43				
	5.6 GHz												
	102	5510		13.5	13.5	13.50	-	13.37	-				
	110	5550				13.375	-	13.42	-				
	118	5590		13.5	13.5	-	-	-	-				
	126	5630				-	-	-	-				
	5.65 to 5.835 GHz	134				5670	-	-	-	-			
		142				5710	-	-	-	-			
		5.8 GHz		-	-	-	-						
	5.65 to 5.835 GHz	151		5755	13.5	13.5	-	-	-	-			
159		5795	-	-			-	-					

**5 GHz (802.11ac)**

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)		
					Ch A	Ch B	Power Control Tx A (Main- 1)	Power Control Tx B (Aux -2)	Tx A	Tx B	
802.11 ac	5.2 GHz		VHT0								
	42	5210		13.0	13.0	-	-	-	-		
	5.3 GHz										
	58	5290		11.0	12.0	-	-	-	-		
	5.6 GHz										
	106	5530		13.0	13.5	-	13.50	-	13.33		
	122	5610		13.5	13.5	13.50	14.125	13.49	13.34		
	5.65 to 5.835 GHz	138		5690	13.5	13.5	13.750	13.35	13.37	13.56	
		5.8 GHz									
		155		5775	13.5	13.5	13.50	14.0	13.49	13.42	

**Table 5 Bluetooth Ant Aux (2)(B) Channels and Output power setting**

Channel Number	Frequency (MHz)	Average Power Measured (dBm)	Tune-up Power (dBm)	Bluetooth Utility power setting
0	2402	10.36	11.5	BR/EDR in DH5 mode (77% DC) Out Pwr. 12dBm Fine Power + 16
40	2441	10.46	11.5	
79	2480	10.90	11.5	



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

### 3.2 DUT (Notebook PC) Details

Table 6

<b>Host notebook :</b>	LIFEBOOK P series
<b>Model Name:</b>	P727
<b>Serial Number:</b>	Pre-production Sample
<b>Manufacturer:</b>	FUJITSU LIMITED
<b>CPU Type and Speed:</b>	Core i7 2.8GHz
<b>LCD</b>	12.5" FHD : LGD: LP125WF4-SPH1 12.5" HD: BOE: NT125WHM-N43
<b>Graphics chip</b>	Non
<b>Wired LAN:</b>	Intel 219LM: 10 Base-T/100 Base-TX/1000Base-T
<b>Modem:</b>	Non
<b>Port Replicator Model:</b>	NPR44
<b>AC Adapter Model:</b>	90W: A13-090P1A(Chicony), A13-090P2A (Chicony) ADP-90BE D(Delta), ADP-90BE C(Delta) 80W: ADP-80SB A(Delta), ADP-80SB B(Delta) 65W:PC only ADP-65MD B(Delta), ADP-65MD C(Delta) A13-065N2A(Chicony), A13-065N3A(Chicony)
<b>Voltage:</b>	19 V
<b>Current Specs:</b>	4.74A / 4.22A / 3.42A
<b>Watts:</b>	90W / 80W / 65W
<b>Battery type</b>	Li-ion
<b>Brand</b>	FUJITSU
<b>Manufacturer</b>	Tocad
<b>Rating</b>	4170mAh, 10.8Vdc, 45Wh

### 3.3 Test Sample Accessories

#### 3.3.1 Battery Types

One type of Fujitsu Lithium Ion battery is used to power the DUT.

Table 7 Battery Details

Model	CP721833-01
V/Wh	18.8V/46Wh



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 4.0 TEST SIGNAL, FREQUENCY AND OUTPUT POWER

INTEL's DRTU test tool was used to configure the WLAN for testing. The DUT Wireless LAN operates in 2 modes, OFDM and DSSS. For the SAR measurements, the device was operating in continuous transmit mode using programming codes supplied by Fujitsu.

It is possible for the Bluetooth (Antenna 2) to operate simultaneously with the WLAN (Antenna 1) (co-transmission). Also the DUT is capable of using two antennas in WLAN mode transmitting simultaneously.

The test results mentioned in this report only apply to the 2450MHz frequency range. An additional report titled 'M161026FR1\_FCC\_8265NGW\_SAR\_5.6' is specific to the 5GHz range.

At the beginning of the SAR tests, the conducted power of the device was measured after the temporary modification of the antenna connector inside the device's TX RX compartment. Measurements were performed with a calibrated Power Meter and the result of the measurements includes the tune up tolerance of 1 dB for WLAN and 2 dB for Bluetooth. WLAN and Bluetooth SAR results were scaled up to the maximum tune-up RF power levels and to 100% Duty Cycle.

### 4.1 Battery Status

The device battery was fully charged prior to commencement of measurement. The battery condition was monitored by measuring the RF field at a defined position inside the phantom before the commencement of each test and again after the completion of the test. It was not possible to perform conducted power measurements at the output of the device, at the beginning and end of each scan due to lack of a suitable antenna port. The uncertainty associated with the power drift was less than 5% and was assessed in the uncertainty budget.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 5.0 DETAILS OF TEST LABORATORY

### 5.1 Location

EMC Technologies Pty Ltd  
176 Harrick Road  
Keilor Park, (Melbourne) Victoria  
Australia 3042

**Telephone:** +61 3 9365 1000  
**Facsimile:** +61 3 9331 7455  
**email:** [melb@emctech.com.au](mailto:melb@emctech.com.au)  
**website:** [www.emctech.com.au](http://www.emctech.com.au)

### 5.2 Accreditations

EMC Technologies Pty. Ltd. is accredited by the National Association of Testing Authorities, Australia (NATA).

**NATA Accredited Laboratory Number: 5292**

Last assessed in May 2014, next scheduled assessment in June 2017

EMC Technologies Pty Ltd is NATA accredited for the following standards:

<b>AS/NZS 2772.2 2011:</b>	RF and microwave radiation hazard measurement
<b>ACMA:</b>	Radio communications (Electromagnetic Radiation - Human Exposure) Standard 2003
<b>EN 50360: 2001</b>	Product standard to demonstrate the compliance of Mobile Phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)
<b>EN 62209-1:2006</b>	Human exposure to radio frequency fields from hand-held and body-mounted devices-Human models, instrumentation and procedures. <b>Part 1:</b> Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range 300 MHz to 3 GHz)
<b>EN 62209-2:2010</b>	Human Exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models instrumentation and procedures <b>Part 2:</b> Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)
<b>IEEE 1528: 2013</b>	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.

Refer to NATA website [www.nata.asn.au](http://www.nata.asn.au) for the full scope of accreditation.

### 5.3 Environmental Factors

The measurements were performed in a shielded room with no background RF signals. The temperature in the laboratory was controlled to within  $20 \pm 1^\circ\text{C}$ , the humidity was in the range 38% to 48%. The liquid parameters are measured daily prior to the commencement of each test. Tests were performed to check that reflections within the environment did not influence the SAR measurements. DASY5 SAR measurement system using ET3DV6 E-field probe is less than  $5\mu\text{V}$  in both air and liquid mediums.

## 6.0 CALIBRATION AND VERIFICATION PROCEDURES AND DATA

### 6.1 System verification

#### 6.1.1 System verification Results @ 2450MHz

The following table lists the results of the System Verification. The forward power into the reference dipole for SAR System Verification was adjusted to 250 mW.

The reference SAR values are derived using a reference dipole and flat section of the SAM phantom suitable for a centre frequency of 2450MHz. These reference SAR values are obtained from the IEEE Std 1528-2013 and are normalized to 1W.

The SPEAG calibration reference SAR value is the SAR system verification result obtained in a specific dielectric liquid using the validation dipole (D2450V2) during calibration. The measured one-gram SAR should be within 10% of the expected target reference values shown in table below (2450MHz) below.

**Table 8 Deviation from reference system verification values @ 2450MHz**

Frequency and Date	Measured SAR 1g (mW/g)	Measured SAR 1g (Normalized to 1W)	SPEAG Calibration reference SAR Value 1g (mW/g)	Deviation From SPEAG Reference 1g (%)	Last Validation Date
2450MHz 26 <sup>th</sup> Oct. 2016	13.9	55.60	52.5	5.90	23/08/16
2450MHz 27 <sup>th</sup> Oct. 2016	13.6	54.40	52.5	3.62	23/08/16
2450MHz 28 <sup>th</sup> Oct. 2016	13.1	52.40	52.5	-0.19	23/08/16

NOTE: All reference system verification values are referenced to 1W input power.

**Table 9 Linearity Check**

Freq. ( MHz)	Mode	Measured 10mW/g SAR 1g (input power = 740mW)	Measured SAR 1g (Normalized to 1W)	Measured 2mW/g SAR 1g (input power = 250mW)	Measured SAR 1g (Normalized to 1W)	Measured 0.4mW/g SAR 1g (input power = 37mW)	Measured SAR 1g (Normalized to 1W)	Measured 0.08mW/g SAR 1g (input power = 4.6 mW)	Measured SAR 1g (Normalized to 1W)	Date
2450	CW	40.6	54.85	13.2	52.80	2.08	56.22	0.248	53.91	23/08/16
Freq. ( MHz)	Mode	Measured 10mW/g SAR 1g (input power = 550mW)	Measured SAR 1g (Normalized to 1W)	Measured 2mW/g SAR 1g (input power = 250mW)	Measured SAR 1g (Normalized to 1W)	Measured 0.4mW/g SAR 1g (input power = 37mW)	Measured SAR 1g (Normalized to 1W)	Measured 0.08mW/g SAR 1g (input power = 5.5mW)	Measured SAR 1g (Normalized to 1W)	Date
2450	OFDM 5Mbps 20MHz	30.3	55.09	14.3	57.20	2.1	56.76	0.297	53.81	24/08/16

#### 6.1.2 Liquid Temperature and Humidity

The humidity and dielectric/ambient temperatures were recorded during the assessment of the tissue material dielectric parameters. The difference between the ambient temperature of the liquid during the dielectric measurement and the temperature during tests was less than |2|°C.

**Table 10 Temperature and Humidity recorded for each day**

Date	Ambient Temperature (°C)	Liquid Temperature (°C)	Humidity (%)
26 <sup>th</sup> Oct. 2016	19.8	19.7	48
27 <sup>th</sup> Oct. 2016	19.9	19.5	47
28 <sup>th</sup> Oct. 2016	20.1	19.8	38



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 7.0 SAR MEASUREMENT PROCEDURE USING DASY5

The SAR evaluation was performed with the SPEAG DASY5 system. A summary of the procedure follows:

- a) A measurement of the SAR value at a fixed location is used as a reference value for assessing the power drop of the DUT. The SAR at this point is measured at the start of the test, and then again at the end of the test.
- b) The SAR distribution at the exposed flat section of the flat phantom is measured at a distance of 4 mm from the inner surface of the shell. The area covers the entire dimension of the DUT and the horizontal grid spacing is 12 mm x 12 mm. The actual Area Scan has dimensions of 60mm x 90mm surrounding the test device. Based on this data, the area of the maximum absorption is determined by Spline interpolation.
- c) Around this point, a volume of 30 mm x 30 mm x 30 mm is assessed by measuring 7 x 7 x 7 points. On the basis of this data set, the spatial peak SAR value is evaluated with the following procedure:
  - (i) The data at the surface are extrapolated, since the centre of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 4 mm. The extrapolation is based on a least square algorithm. A polynomial of the fourth order is calculated through the points in z-axes. This polynomial is then used to evaluate the points between the surface and the probe tip.
  - (ii) The maximum interpolated value is searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g and 10 g) are computed using the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one-dimensional splines with the "Not a knot"- condition (in x, y and z-direction). The volume is integrated with the trapezoidal – algorithm. One thousand points (10 x 10 x 10) are interpolated to calculate the averages.
  - (iii) All neighbouring volumes are evaluated until no neighbouring volume with a higher average value is found.
  - (iv) The SAR value at the same location as in Step (a) is again measured to evaluate the actual power drift.



## 8.0 MEASUREMENT UNCERTAINTY

The uncertainty analysis is based on the template listed in the IEEE Std 1528-2013 for both device SAR tests and System verification uncertainty. The measurement uncertainty of a specific device is evaluated independently and the total uncertainty for both evaluations (95% confidence level) must be less than 30%.

**Table 11 Uncertainty Budget for DASY5 Version 52 – DUT SAR test 2450MHz**

Error Description	Uncert. Value	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub>	10g u <sub>i</sub>	v <sub>i</sub>
<b>Measurement System</b>								
Probe Calibration	6	N	1.00	1	1	6.00	6.00	∞
Axial Isotropy	4.7	R	1.73	0.7	0.7	1.90	1.90	∞
Hemispherical Isotropy	9.6	R	1.73	0.7	0.7	3.88	3.88	∞
Boundary Effects	2	R	1.73	1	1	1.15	1.15	∞
Linearity	4.7	R	1.73	1	1	2.71	2.71	∞
System Detection Limits	1	R	1.73	1	1	0.58	0.58	∞
Modulation response	2.4	R	1.73	1	1	1.39	1.39	∞
Readout Electronics	0.3	N	1.00	1	1	0.30	0.30	∞
Response Time	0.8	R	1.73	1	1	0.46	0.46	∞
Integration Time	2.6	R	1.73	1	1	1.50	1.50	∞
RF Ambient Noise	3	R	1.73	1	1	1.73	1.73	∞
RF Ambient Reflections	3	R	1.73	1	1	1.73	1.73	∞
Probe Positioner	0.8	R	1.73	1	1	0.46	0.46	∞
Probe Positioning	6.7	R	1.73	1	1	3.87	3.87	∞
Post Processing	4	R	1.73	1	1	2.31	2.31	∞
<b>Test Sample Related</b>								
Power Scaling	0	R	1.73	1	1	0.00	0.00	∞
Test Sample Positioning	2.9	N	1.00	1	1	2.90	2.90	145
Device Holder Uncertainty	3.6	N	1.00	1	1	3.60	3.60	5
Output Power Variation – SAR Drift Measurement	4.72	R	1.73	1	1	2.73	2.73	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	7.6	R	1.73	1	1	4.39	4.39	∞
Liquid Conductivity – Deviation from target values	5	R	1.73	0.64	0.43	1.85	1.24	∞
Liquid Permittivity – Deviation from target values	5	R	1.73	0.6	0.49	1.73	1.41	∞
Liquid Conductivity – Measurement uncertainty	2.5	N	1.00	0.64	0.71	1.60	1.78	∞
Liquid Permittivity – Measurement uncertainty	2.5	N	1.00	0.6	0.26	1.50	0.65	∞
Temp.unc. - Conductivity	3.4	R	1.73	0.78	0.71	0.77	0.70	∞
Temp. unc. - Permittivity	0.4	R	1.73	0.23	0.26	0.04	0.05	∞
Combined standard Uncertainty (u <sub>c</sub> )						12.43	12.26	
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k= 2			24.86	24.52	

Estimated total measurement uncertainty for the DASY5 measurement system was  $\pm 12.43\%$ . The expanded uncertainty ( $K = 2$ ) was assessed to be  $\pm 24.86\%$  based on 95% confidence level. The uncertainty is not added to the measurement result.



**Table 12 Uncertainty Budget for DASY5 Version 52 – DUT SAR test 2450MHz****IEC 62209-2 UNCERTAINTY FOR RSS-102**

Error Description	Uncert. Value	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub>	10g u <sub>i</sub>	v <sub>i</sub>
<b>Measurement System</b>								
Probe Calibration	6	N	1.00	1	1	6.00	6.00	∞
Axial Isotropy	4.7	R	1.73	0.7	0.7	1.90	1.90	∞
Hemispherical Isotropy	9.6	R	1.73	0.7	0.7	3.88	3.88	∞
Boundary Effects	2	R	1.73	1	1	1.15	1.15	∞
Linearity	4.7	R	1.73	1	1	2.71	2.71	∞
System Detection Limits	1	R	1.73	1	1	0.58	0.58	∞
Modulation response	2.4	R	1.73	1	1	1.39	1.39	∞
Readout Electronics	0.3	N	1.00	1	1	0.30	0.30	∞
Response Time	0.8	R	1.73	1	1	0.46	0.46	∞
Integration Time	2.6	R	1.73	1	1	1.50	1.50	∞
RF Ambient Noise	3	R	1.73	1	1	1.73	1.73	∞
RF Ambient Reflections	3	R	1.73	1	1	1.73	1.73	∞
Probe Positioner	0.8	R	1.73	1	1	0.46	0.46	∞
Probe Positioning	6.7	R	1.73	1	1	3.87	3.87	∞
Post Processing	4	R	1.73	1	1	2.31	2.31	∞
<b>Test Sample Related</b>								
Power Scaling	0	R	1.73	1	1	0.00	0.00	∞
Test Sample Positioning	2.9	N	1.00	1	1	2.90	2.90	145
Device Holder Uncertainty	3.6	N	1.00	1	1	3.60	3.60	∞
Output Power Variation – SAR Drift Measurement	4.72	R	1.73	1	1	2.73	2.73	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	7.6	R	1.73	1	1	4.39	4.39	∞
Liquid Conductivity – Deviation from target values	5	R	1.73	0.64	0.43	1.85	1.24	∞
Liquid Permittivity – Deviation from target values	5	R	1.73	0.6	0.49	1.73	1.41	∞
Liquid Conductivity – Measurement uncertainty	2.5	N	1.00	0.78	0.71	1.95	1.78	∞
Liquid Permittivity – Measurement uncertainty	2.5	N	1.00	0.6	0.49	1.50	1.23	∞
Temp.unc. - Conductivity	3.4	R	1.73	0.78	0.71	1.53	1.39	∞
Temp. unc. - Permittivity	0.4	R	1.73	0.23	0.26	0.05	0.06	∞
Combined standard Uncertainty (u <sub>c</sub> )						<b>12.55</b>	<b>12.36</b>	
Expanded Uncertainty (95% CONFIDENCE LEVEL)			<b>k= 2</b>			<b>25.10</b>	<b>24.73</b>	

Estimated total measurement uncertainty for the DASY5 measurement system was  $\pm 12.55\%$ . The expanded uncertainty ( $K = 2$ ) was assessed to be  $\pm 25.10\%$  based on 95% confidence level. The uncertainty is not added to the measurement result.

**Table 13 Uncertainty Budget for DASY5 Version 52 – System verification 2450MHz**

Error Description	Uncert. Value	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub>	10g u <sub>i</sub>	v <sub>i</sub>
<b>Measurement System</b>								
Probe Calibration	6	N	1.00	1	1	6.00	6.00	∞
Axial Isotropy	4.7	R	1.73	1	1	2.71	2.71	∞
Hemispherical Isotropy	9.6	R	1.73	0	0	0.00	0.00	∞
Boundary Effects	1	R	1.73	1	1	0.58	0.58	∞
Linearity	4.7	R	1.73	1	1	2.71	2.71	∞
System Detection Limits	1	R	1.73	1	1	0.58	0.58	∞
Modulation response	0	R	1.73	1	1	0.00	0.00	∞
Readout Electronics	0.3	N	1.00	1	1	0.30	0.30	∞
Response Time	0	R	1.73	1	1	0.00	0.00	∞
Integration Time	0	R	1.73	1	1	0.00	0.00	∞
RF Ambient Noise	1	R	1.73	1	1	0.58	0.58	∞
RF Ambient Reflections	1	R	1.73	1	1	0.58	0.58	∞
Probe Positioner	0.8	R	1.73	1	1	0.46	0.46	∞
Probe Positioning	6.7	R	1.73	1	1	3.87	3.87	∞
Post Processing	2	R	1.73	1	1	1.15	1.15	∞
<b>Dipole Related</b>								
Deviation of exp. dipole	5.5	R	1.73	1	1	3.18	3.18	##
Dipole Axis to Liquid Dist.	2	R	1.73	1	1	1.15	1.15	##
Input power & SAR drift	3.40	R	1.73	1	1	1.96	1.96	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	4	R	1.73	1	1	2.31	2.31	∞
Liquid Conductivity – Deviation from target values	5	R	1.73	0.64	0.43	1.85	1.24	∞
Liquid Permittivity – Deviation from target values	5	R	1.73	0.6	0.49	1.73	1.41	∞
Liquid Conductivity – Measurement uncertainty	2.5	N	1.00	0.78	0.71	1.95	1.78	∞
Liquid Permittivity – Measurement uncertainty	2.5	N	1.00	0.26	0.26	0.65	0.65	∞
Temp.unc. - Conductivity	3.4	R	1.73	0.78	0.71	0.77	0.70	∞
Temp. unc. - Permittivity	0.4	R	1.73	0.23	0.26	0.04	0.05	∞
Combined standard Uncertainty (u <sub>c</sub> )						<b>10.02</b>	<b>9.84</b>	
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k= 2			<b>20.05</b>	<b>19.68</b>	

Estimated total measurement uncertainty for the DASY5 measurement system was  $\pm 10.02\%$ . The expanded uncertainty (K = 2) was assessed to be  $\pm 20.05\%$  based on 95% confidence level. The uncertainty is not added to the System verification measurement result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 9.0 EQUIPMENT LIST AND CALIBRATION DETAILS

Table 14 SPEAG DASY5 Version 52

Equipment Type	Manufacturer	Model Number	Serial Number	Calibration Due	Used For this Test?
Robot - Six Axes	Staubli	RX90BL	N/A	Not applicable	✓
Robot Remote Control	SPEAG	CS7MB	RX90B	Not applicable	✓
SAM Phantom	SPEAG	N/A	1260	Not applicable	
SAM Phantom	SPEAG	N/A	1060	Not applicable	
Flat Phantom	AndreT	10.1	P 10.1	Not Applicable	
Flat Phantom	AndreT	9.1	P 9.1	Not Applicable	
Flat Phantom	SPEAG	ELI 4.0	1101	Not Applicable	✓
Data Acquisition Electronics	SPEAG	DAE3 V1	359	11-Jan-2017	
Data Acquisition Electronics	SPEAG	DAE3 V1	442	07-Dec-2016	✓
Probe E-Field - Dummy	SPEAG	DP1	N/A	Not applicable	
Probe E-Field	SPEAG	ET3DV6	1380	10-Dec-2016	✓
Probe E-Field	SPEAG	ET3DV6	1377	11-June-2016	
Probe E-Field	SPEAG	ES3DV6	3029	Not Used	
Probe E-Field	SPEAG	EX3DV4	3956	15-June-2016	
Probe E-Field	SPEAG	EX3DV4	7358	11-Dec-2016	
Validation Source 150 MHz	SPEAG	CLA150	4003	3-Dec-2016	
Antenna Dipole 300 MHz	SPEAG	D300V3	1012	09-Dec-2018	
Antenna Dipole 450 MHz	SPEAG	D450V3	1074	09-Dec-2018	
Antenna Dipole 600 MHz	SPEAG	D600V3	1008	16-Oct-2018	
Antenna Dipole 750 MHz	SPEAG	D750V2	1051	13-Dec-2016	
Antenna Dipole 900 MHz	SPEAG	D900V2	047	09-Dec-2017	
Antenna Dipole 1640 MHz	SPEAG	D1640V2	314	05-Dec-2017	
Antenna Dipole 1800 MHz	SPEAG	D1800V2	242	05-Dec-2017	
Antenna Dipole 1950 MHz	SPEAG	D1950V3	1113	09-Dec-2018	
Antenna Dipole 2300 MHz	SPEAG	D2300V2	1032	10-Dec-2018	
Antenna Dipole 2450 MHz	SPEAG	D2450V2	724	10-Dec-2018	✓
Antenna Dipole 2600 MHz	SPEAG	D2600V2	1044	13-Dec-2016	
Antenna Dipole 3500 MHz	SPEAG	D3500V2	1002	13-July-2013	
Antenna Dipole 5600 MHz	SPEAG	D5GHzV2	1008	16-Dec-2016	
RF Amplifier	EIN	603L	N/A	*In test	
RF Amplifier	Mini-Circuits	ZHL-42	N/A	*In test	
RF Amplifier	Mini-Circuits	ZVE-8G	N/A	*In test	✓
Synthesized signal generator	Hewlett Packard	86630A	3250A00328	*In test	✓
RF Power Meter	Hewlett Packard	437B	3125012786	*In test	✓
RF Power Sensor 0.01 - 18 GHz	Hewlett Packard	8481H	1545A01634	18-Oct-2017	✓
RF Power Meter	Rohde & Schwarz	NRP	101415	16-Oct-2016	
RF Power Sensor	Rohde & Schwarz	NRP - Z81	100174	19-Oct-2017	
RF Power Meter Dual	Hewlett Packard	435A	1733A05847	*In test	✓
RF Power Sensor	Hewlett Packard	8482A	2349A10114	*In test	✓
Network Analyser	Hewlett Packard	8714B	GB3510035	03-Oct-2016	
Network Analyser	Hewlett Packard	8753ES	JP39240130	03-Dec-2016	
Network Analyser	Hewlett Packard	8753D	3410A04122	04-Feb-2017	✓
Dual Directional Coupler	Hewlett Packard	778D	1144 04700	*In test	
Dual Directional Coupler	NARDA	3022	75453	*In test	✓
Thermometer	Digitech	QM7217	T-103	31-Aug-2017	✓
Thermometer	Digitech	QM7217	T-104	15-Jan-2017	

\* Calibrated during the test for the relevant parameters.

## 10.0 TEST METHODOLOGY

Notebooks should be evaluated in normal use positions, typical for lap-held bottom-face only. However, the number of positions will depend on the number of configurations the laptop can be operated in. The “LIFEBOOK P SERIES” can be used in either a conventional laptop position (see Appendix A) or a Tablet configuration. The antenna location in the “LIFEBOOK P SERIES” is closest to the top of the screen when used in a conventional laptop configuration and due to the separation distances involved between the phantom and the laptop antenna, testing is not required in this position.

### 10.1 Positions

#### 10.1.1 “Lap Held” Position Definition (0mm spacing)

The DUT was tested in the 2.00 mm flat section of the ELI4 Flat phantom for the “Lap Held” position. The Transceiver was placed at the bottom of the phantom and suspended in such way that the back of the DUT was touching the phantom. This device orientation simulates the PC’s normal use – being held on the lap of the user. A spacing of 0mm ensures that the SAR results are conservative and represent a worst-case position.

#### 10.1.2 “Edge On” Position (Portrait or Landscape)

The DUT was tested in the (2.00 mm) flat section of the ELI4 Flat phantom for the “Edge On” position. The Antenna edge of the Transceiver was placed underneath the flat section of the phantom and suspended until the edge touched the phantom. *Refer to Appendix A for photos of measurement positions.*

#### 10.1.3 “Bystander” Position (25mm spacing)

The DUT was tested in the 2.00 mm flat section of the ELI4 Flat phantom for the “Bystander” position. The Transceiver was placed at the bottom of the phantom and suspended in such way that the back of its LCD screen was parallel to phantom and at 25mm distance. This orientation simulates use of the device in a way that allows occasional RF exposure of the nearby person (Bystander).



## 10.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes)

The DUT has fixed antennas. Depending on the measured SAR level up to three test channels with the test sample operating at maximum power were recorded. The following table represents the matrix used to determine what testing was required. All relevant provisions of KDB 447498 are applied for SAR measurements of the host system.

**Table 15 Testing configurations**

Phantom Configuration	Device Mode	Antenna	Test Configurations		
			Channel (Remining)	Channel (Highest)	Channel (Remining)
Lap Held	OFDM 2.4GHz	A		X	
		B		X	
	DSSS 2.4GHz	A		X	
		B		X	
Bystander	OFDM 2.4GHz	A		X	
		B		X	
	DSSS 2.4GHz	A		X	
		B		X	
Edge On	OFDM 2.4GHz	A		X	
		B		X	
	DSSS 2.4GHz	A		X	
		B		X	

### Legend

X	Testing Required in this configuration
	Testing required in this configuration only if SAR of middle channel is more than 3dB below the SAR limit or it is the worst case.

*NOTE: Throughout this report, Antenna A and B refer to Tx1 and Tx2 in the host respectively.*



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

## 11.0 SAR MEASUREMENT RESULTS

The SAR values averaged over 1g tissue masses were determined for the sample DUT for all test configurations listed in section 10.2.

### 11.1 2450MHz SAR Results

There are two modes of operation within the 2450MHz band, they include OFDM and DSSS modulations. Refer to section 10.2 for selection of all device test configurations. Table below displays the SAR results.

**Table 16 SAR MEASUREMENT RESULTS - WLAN**

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. MHz	SAR (1g) mW/g	Drift dB	$\epsilon_r$ (target 52.7 $\pm$ 5% 50.1 to 55.3)	$\sigma$ (target 1.95 $\pm$ 5% 1.85 to 2.05)	Reported mW/g	Tune-up Power dBm	Conducted Power dBm	PWR Scaling factor	DC %
Bystander 25mm Spacing OFDM Antenna 2 26-10-16	1.	OFDM 2450 MHz HT0 (40MHz)	7	2442	0.0212	-0.12	51.1	1.98	0.02	15	14.83	1.04	98
Bystander 25mm Spacing DSSS Antenna 2 26-10-16	2.	DSSS 2450 MHz 1Mbps	7	2442	0.0151	-0.21	51.1	1.98	0.02	15	14.75	1.06	99
Bystander 25mm Spacing OFDM Antenna 1 26-10-16	3.	OFDM 2450 MHz HT0 (40MHz)	7	2442	0.0121	0.03	51.1	1.98	0.01	15	14.98	1.00	98
Bystander 25mm Spacing DSSS Antenna 1 26-10-16	4.	DSSS 2450 MHz 1Mbps	7	2442	0.0127	-0.16	51.1	1.98	0.01	15	14.78	1.05	99
Lap Held OFDM Antenna 2 26-10-16	5.	OFDM 2450 MHz HT0 (40MHz)	7	2442	0.0779	0	51.1	1.98	0.08	15	14.83	1.04	98
Lap Held DSSS Antenna 2 28-10-16	6.	DSSS 2450 MHz 1Mbps	7	2442	0.0723	-0.06	51.0	1.91	0.07	15	14.75	1.06	99
Lap Held OFDM Antenna 1 26-10-16	7.	OFDM 2450 MHz HT0 (40MHz)	7	2442	0.0779	-0.02	51.1	1.98	0.08	15	14.98	1.00	98
Lap Held DSSS Antenna 1 26-10-16	8.	DSSS 2450 MHz 1Mbps	7	2442	0.0857	-0.09	51.1	1.98	0.09	15	14.78	1.05	99
Edge 1 OFDM Antenna 2 27-10-16	9.	OFDM 2450 MHz HT0 (40MHz)	3	2422	0.177	0	51.1	1.90	0.18	15	14.76	1.06	98
Edge 1 OFDM Antenna 2 27-10-16	10.	OFDM 2450 MHz HT0 (40MHz)	6	2437	0.17	0	51.0	1.93	0.17	15	14.81	1.04	98
Edge 1 OFDM Antenna 2 27-10-16	11.	OFDM 2450 MHz HT0 (40MHz)	7	2442	0.174	-0.06	51.0	1.94	0.18	15	14.83	1.04	98
Edge 1 OFDM Antenna 2 27-10-16	12.	OFDM 2450 MHz HT0 (40MHz)	10	2457	0.171	0.02	50.9	1.96	0.17	15	14.89	1.03	98



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Edge 1 DSSS Antenna 2 27-10-16	13.	DSSS 2450 MHz 1Mbps	7	2442	0.157	-0.07	51.0	1.94	0.16	15	14.75	1.06	99
Edge 1 OFDM Antenna 1 27-10-16	14.	OFDM 2450 MHz HT0 (40MHz)	3	2422	0.245	-0.05	51.1	1.90	0.25	15	14.8	1.05	98
Edge 1 OFDM Antenna 1 27-10-16	15.	OFDM 2450 MHz HT0 (40MHz)	6	2437	0.25	-0.05	51.0	1.93	0.26	15	14.84	1.04	98
Edge 1 OFDM Antenna 1 27-10-16	16.	OFDM 2450 MHz HT0 (40MHz)	7	2442	0.255	-0.07	51.0	1.94	0.26	15	14.98	1.00	98
Edge 1 OFDM Antenna 1 27-10-16	17.	OFDM 2450 MHz HT0 (20MHz)	11	2462	<b>0.315</b>	-0.05	50.9	1.97	<b>0.32</b>	15	14.8	1.05	99
Edge 1 DSSS Antenna 1 27-10-16	18.	DSSS 2450 MHz 1Mbps	7	2442	0.242	-0.06	51.0	1.94	0.24	15	14.78	1.05	99
Edge 2 OFDM Antenna 2 27-10-16	19.	OFDM 2450 MHz HT0 (40MHz)	3	2422	0.243	-0.03	51.1	1.90	0.25	15	14.76	1.06	98
Edge 2 OFDM Antenna 2 27-10-16	20.	OFDM 2450 MHz HT0 (40MHz)	6	2437	0.213	-0.05	51.0	1.93	0.22	15	14.81	1.04	98
Edge 2 OFDM Antenna 2 27-10-16	21.	OFDM 2450 MHz HT0 (40MHz)	7	2442	0.222	0.02	51.0	1.94	0.23	15	14.83	1.04	98
Edge 2 OFDM Antenna 2 27-10-16	22.	OFDM 2450 MHz HT0 (40MHz)	10	2457	0.218	-0.07	50.9	1.96	0.22	15	14.89	1.03	98
Edge 2 DSSS Antenna 2 27-10-16	23.	DSSS 2450 MHz 1Mbps	7	2442	0.209	0.05	51.0	1.94	0.21	15	14.75	1.06	99
Edge 4 OFDM Antenna 1 28-10-16	24.	OFDM 2450 MHz HT0 (40MHz)	3	2422	0.144	-0.03	51.1	1.87	0.15	15	14.8	1.05	98
Edge 4 OFDM Antenna 1 28-10-16	25.	OFDM 2450 MHz HT0 (40MHz)	6	2437	0.171	-0.07	51.0	1.90	0.17	15	14.84	1.04	98
Edge 4 OFDM Antenna 1 28-10-16	26.	OFDM 2450 MHz HT0 (40MHz)	7	2442	0.183	-0.03	51.0	1.91	0.19	15	14.98	1.00	98
Edge 4 OFDM Antenna 1 28-10-16	27.	OFDM 2450 MHz HT0 (20MHz)	11	2462	0.157	0.04	50.9	1.94	0.16	15	14.8	1.05	99
Edge 4 DSSS Antenna 1 28-10-16	28.	DSSS 2450 MHz 1Mbps	7	2442	0.192	-0.2	51.0	1.91	0.19	15	14.78	1.05	99
System Check 26-10-16	29.	CW	1	2450	13.9	0.01	51.1	1.99	-	-	-	-	-
System Check 27-10-16	30.	CW	1	2450	13.6	-0.01	50.9	1.95	-	-	-	-	-
System Check 28-10-16	31.	CW	1	2450	13.1	-0.05	51.0	1.92	-	-	-	-	-

NOTE: The measurement uncertainty of 24.86% for 2.45GHz was not added to the result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

**Table 17 SAR MEASUREMENT RESULTS – Bluetooth**

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. MHz	SAR (1g) mW/g	Drift dB	$\epsilon_r$ (target 52.7 $\pm$ 5% 50.1 to 55.3)	$\sigma$ (target 1.95 $\pm$ 5% 1.85 to 2.05)	Reported mW/g	Tune-up Power dBm	Conducted Power dBm	PWR Scaling factor	DC %
Bystander 25mm Spacing Antenna 2 28-10-16	32.	Bluetooth 2.0 DH5	40	2441	0.01	-0.04	51.0	1.91	0.02	11.5	10.46	1.27	77
Lap Held Antenna 2 28-10-16	33.	Bluetooth 2.0 DH5	40	2441	0.036	-0.07	51.0	1.91	0.06	11.5	10.46	1.27	77
Edge 2 Antenna 2 28-10-16	34.	Bluetooth 2.0 DH5	0	2402	0.0713	-0.05	51.1	1.85	0.12	11.5	10.36	1.30	77
Edge 2 Antenna 2 28-10-16	35.	Bluetooth 2.0 DH5	40	2441	0.105	0.2	51.0	1.91	0.17	11.5	10.46	1.27	77
Edge 2 Antenna 2 28-10-16	36.	Bluetooth 2.0 DH5	78	2480	0.0613	-0.03	50.8	1.97	0.09	11.5	10.9	1.15	77

NOTE: The measurement uncertainty of 24.86% for 2.45GHz was not added to the result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.



## 12.0 COMPLIANCE STATEMENT

The Fujitsu P Series LIFEBOOK Convertable PC, Model: P727 with INTEL Wireless LAN Module (Windstorm Peak 802.11a/b/g/n/ac), Model: 8265NGW was found to comply with the FCC and RSS-102 SAR requirements.

The highest Measured SAR level was 0.315 mW/g for a 1g cube. The manufacturer's duty cycle is 99%. Scaling the SAR value, the maximum Reported SAR value is **0.32 mW/g**. This value was measured at 2462 MHz (channel 11) in the "Body Edge 1" position in OFDM (20MHz) modulation mode at the antenna 1. This was below the limit of 1.6 mW/g for uncontrolled exposure, even taking into account the measurement uncertainty of 24.53 %.

The SAR test Variability check was not required because the highest measured SAR was less than 0.8 mW/g.



---

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

### 13.0 MULTIBAND EVALUATION CONSIDERATIONS

Fujitsu P SERIES LIFEBOOK CONVERTIBLE PC, Model: P727 Worst case WLAN SAR was recorded in 5GHz frequency range, report titled "M161026FR1\_FCC\_8265NGW\_SAR\_5.6" contains section that describes multiband evaluation.

