



RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

**Test Result of RF Exposure Evaluation****BLE Antenna gain=3.13dBi**

Mode	Output power (dBm)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
GFSK	3.74	2.37	2.06	0.001	1.0	PASS

2.4G Antenna gain=3.13dBi

Mode	Output power (dBm)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	12.15	16.41	2.06	0.0067	1.0	PASS
802.11g	14.19	26.24	2.06	0.0108	1.0	PASS
802.11n(HT20)	14.00	25.12	2.06	0.0103	1.0	PASS
802.11n(HT40)	13.02	20.04	2.06	0.0082	1.0	PASS

5.2G Antenna gain=3.46dBi

Mode	Output power (dBm)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
TX 802.11a	14.32	27.04	2.22	0.0119	1.0	PASS
TX 802.11 n20	14.27	26.73	2.22	0.0118	1.0	PASS
TX 802.11 ac20	14.35	27.23	2.22	0.0120	1.0	PASS
TX 802.11 n40	12.81	19.10	2.22	0.0084	1.0	PASS
TX 802.11 ac40	12.77	18.92	2.22	0.0083	1.0	PASS
TX 802.11 ac80	11.26	13.37	2.22	0.0059	1.0	PASS

5.8G Antenna gain=3.46dBi

Mode	Output power (dBm)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
TX 802.11a	13.17	20.75	2.22	0.0091	1.0	PASS
TX 802.11 n20	13.05	20.18	2.22	0.0089	1.0	PASS
TX 802.11 ac20	13.08	20.32	2.22	0.0089	1.0	PASS
TX 802.11 n40	11.98	15.78	2.22	0.0069	1.0	PASS
TX 802.11 ac40	11.96	15.70	2.22	0.0069	1.0	PASS
TX 802.11 ac80	10.70	11.75	2.22	0.0052	1.0	PASS

If BLE and 2.4G WIFI operate simultaneously, Total power density=0.001/1+0.0108/1=0.0118<1.0

If BLE and 5.2G WIFI operate simultaneously, Total power density=0.001/1+0.0120/1=0.0130<1.0

If BLE and 5.8G WIFI operate simultaneously, Total power density=0.001/1+0.0091/1=0.0101<1.0

Then SAR evaluation is not require .