

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is an 16 BF Case Maxxum 150 R/C Tractor operating at 2.4G Band. The EUT can be powered by DC 9.0V (1 x 9.0V 6LR61 battery). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The nominal conducted output power specified: -7.0 dBm ( $\pm 3$ dB)

The nominal radiated output power (e.i.r.p) specified: -7.0 dBm ( $\pm 3$ dB)

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 88.2 dB $\mu$ V/m at 3m in the frequency 2462MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -7.03dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 86.6 dB $\mu$ V/m at 3m in the frequency 2418MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -8.63dBm

which is within the production variation.

The maximum conducted output power specified is -4.0dBm= 0.398mW

The source- based time-averaging conducted output power  
=0.398\* Duty cycle mW <0.398 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

$$\begin{aligned} P_{th}(\text{mW}) &= ERP_{20\text{cm}} * (d/20\text{cm})^x \quad (X = -\log_{10} \left( \frac{60}{ERP_{20\text{cm}} \sqrt{f}} \right)) \\ &= 3060 * (0.5/20)^{1.9} \text{ mW} \\ &= 2.72 \text{ mW} \end{aligned}$$

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 8.058ms

Effective period of the cycle = 1014.5 $\mu$ s x1 = 1.0145ms

DC =1.0145ms / 8.058ms =0.1259 or 12.59%