





# Test Report - FCC PART 1.1310 / MPE Applicant: Fiplex Communications Inc.

Approved for Release By:

Signature:	Bruno Churon		
Name & Title:	Bruno Clavier, General Manager		
Date of Signature	5/20/2022		

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



## **Table of Contents**

1.	C	USTOMER INFORMATION	3
2.		OCATION OF TESTING	
	2.1 2.2	Test Laboratory Testing was performed, reviewed by	
3.	TI	EST SAMPLE(S) (EUT/DUT)	5
	3.1	Description of the EUT	
4.	TI	EST METHODS & APPLICABLE REGULATORY LIMITS	7
	4.	Test methods/Standards/Guidance:	7
5.		F EXPOSURE RESULTS	
6.		ISTORY OF TEST REPORT CHANGES	



#### 1. Customer Information

Applicant: Fiplex Communications Inc.
Address: 2101 NW 79th Avenue

Miami Florida, 33122, United States

#### 2. Location of Testing

#### 2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780

FCC Designation # US1070

FCC site registration is under A2LA certificate # 0955.01

ISED Canada test site registration # 2056A

EU Notified Body # 1177

For all designations see A2LA scope # 0955.01

# 2.2 Testing was performed, reviewed by

5/20/2022

Dates of Testing: 5/4/2022 - 5/9/2022

Date of Signature

Signature:	Sr. EMC Engineer EMC-003838-NE	
Name & Title:	Tim Royer, EMC Engineer	
Date of Signature	5/20/2022	
Signature:	Terri Ollen	
signature.		
Name & Title:	Terri Allen, Lab Assistant	

ERTIFIA

## 3. Test Sample(s) (EUT/DUT)

The test sample was received: 5/3/2022

#### 3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification				
FCC ID:	P3TILB4AB			
Brief Description	PE287 IN-LINE BOOSTER			
Type of Modular	ILB4A-WMO			
Model(s) #	N/A			
Firmware version	N/A			
Software version	N/A			
Serial Number	P3TILB4AB			

Technical Characteristics				
Technology	IN-LINE BOOSTER			
Frequency Range	Downlink: 489.5-491 MHz, 496-497 MHz			
	Uplink: 492.5-494 MHz, 499-500 MHz			
<b>RF O/P Power (Max.)</b> DL: 30.88 dBm/ 1.22 W				
	UL: 30.85 dBm/ 1.21 W			
Bandwidth & Emission Class	4K00F1E, 11K3F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W,			
	9K80F1D, 9K80F1E, 9K80D7W			
Number of Channels	4			
Duty Cycle	100%			
Antenna Connector	N Type			
Voltage Rating (AC or Batt.)	AC			



Timco Engineering, Inc., an IIA Company 849 NW State Road 45, Newberry, Florida 32669 (352) 472-5500 / testing@timcoengr.com

Antenna Characteristics						
Antenna	Frequency Range	Mode / BW	Antenna Gain			
1	489.5-491 MHz 496-497 MHz 492.5-494 MHz 499-500 MHz	Operational	0 dBi			

<sup>-</sup> Note: Information such as antenna gain, firmware/software numbers are provided by manufacturer and cannot be validated by the test lab.

Note: This EUT does not include antenna(s).

#### 4. Test methods & Applicable Regulatory Limits

#### 4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

#### 4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz) Electric field strength (V/m)		Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging Time (minutes)				
A Limits for Occupational/Controlled Exposure								
0.3-3.0	614	1.63	*(100)	≤6				
3.0-30	1842/f	4.89/f	*(900/f²)	<6				
30-300	61.4	0.163	1.0	<6				
300-1,500			f/300	<6				
1,500-100,000			5	<6				
B Limits for General Population/Uncontrolled Exposure								
0.3-1.34	614	1.63	*(100)	<30				
1.34-30	824/f	2.19/f	*(180/f²)	<30				
30-300	27.5	0.073	0.2	<30				
300-1,500			f/1500	<30				
1,500-100,000			1.0	<30				

#### 4.2 Equations

#### **POWER DENSITY**

E(V/m) = SQRT (30 \* P \* G) / d

 $Pd(W/m^2) = E^2 / 377$ 

 $S = EIRP / (4 * Pi * D^2v)$ 

Where:

S = Power density, in mW/cm^2 EIRP = Equivalent Isotropic Radiated Power, in mW D = Separation distance in cm

Power density is converted from units of <u>mW/cm^2</u> to units of <u>W/m^2</u> by multiplying by 10.

#### DISTANCE

D = SQRT (EIRP / (4 \* Pi \* S))

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

S = Power density in mW/cm<sup>2</sup>

**SOURCE-BASED DUTY CYCLE** (When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

Source-based time-average EIRP = ( DC / 100 ) \* EIRP

Where:

DC = Duty Cycle in % as applicable. EIRP = Equivalent Isotropic radiated Power, in mW



# 5. RF Exposure Results

Separation Distance: 20 cm

MPE									
Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limt (cm)
492.5-500 MHz	20	32.00	0.00	100%	1.58	0.315 mW/cm2	0.328 mW/cm2	1.642 mW/cm2	20.00

RESULT: Pass at DISTANCE 20 cm

# 6. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
	1	Initial release	5/12/2022
TR_2069-22_Uplink_FCC PT 1.1310/ MPE_	2	Corrected Ant gain pg. 6 and table pg.9	5/19/2022

## **END OF TEST REPORT**