

PAGE NO. 8 of 64. AMNEDED December 11, 2001  
NAME OF TEST: Carrier Output Power (Conducted)  
SPECIFICATION: 47 CFR 2.1046(a)  
TEST EQUIPMENT: As per attached page


MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is  $\pm 3\%$ .

MEASUREMENT RESULTS

| MHz        | dbm  | Lo Watts,<br>Conducted | High Watts,<br>Conducted |
|------------|------|------------------------|--------------------------|
| AMPS MODE: |      |                        |                          |
| 824.040    | 21.6 | 0.148                  | 0.147                    |
| 836.400    | 21.3 | 0.138                  | 0.138                    |
| 848.970    | 20.0 | 0.103                  | 0.104                    |
| TDMA MODE: |      |                        |                          |
| 825.290    | 27.8 | 0.6065                 | 0.606                    |
| 836.400    | 27.6 | 0.578                  | 0.579                    |
| 847.720    | 26.1 | 0.410                  | 0.41                     |

PERFORMED BY:

  
Doug Noble, B.A.S. E.E.T.