



BUREAU
VERITAS



Certificate # 3939.01

FCC SAR Test Report

Report No. : W7L-P23020004SA01

Applicant : Xiaomi Communications Co., Ltd.

Address : #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Manufacturer : Xiaomi Communications Co., Ltd.

Address : #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Product : Mobile Phone

FCC ID : 2AFZZRA44A

Brand : Redmi

Model No. : 2303CRA44A

Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE 1528:2013
KDB 865664 D01 v01r04 / KDB 865664 D02 v01r02 / KDB 248227 D01 v02r02
KDB 447498 D04 v01 / KDB 648474 D04 v01r03 / KDB 941225 D01 v03r01
KDB 941225 D05 v02r05 / KDB 941225 D05A v01r02 / KDB 941225 D06 v02r01

Sample Received Date : Feb. 08, 2023

Date of Testing : Feb. 09, 2023 ~ Feb. 16, 2023

FCC Designation No. : CN1171 FCC Site Registration No. : 525120

CERTIFICATION: The above equipment have been tested by **BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By :

Jerry Chen

Jerry Chen / Engineer

Approved By :

Luke Lu

Luke Lu / Manager

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



BUREAU
VERITAS



ACCREDITED
Certificate # 3939.01

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement System	6
3.1 Definition of Specific Absorption Rate (SAR)	6
3.2 SPEAG DASY System	6
3.2.1 Robot.....	7
3.2.2 Probes.....	8
3.2.3 Data Acquisition Electronics (DAE)	8
3.2.4 Phantoms	9
3.2.5 Device Holder.....	10
3.2.6 System Validation Dipoles.....	10
3.2.7 Tissue Simulating Liquids.....	11
3.3 SAR System Verification	13
3.4 SAR Measurement Procedure	14
3.4.1 Area & Zoom Scan Procedure	14
3.4.2 Volume Scan Procedure.....	14
3.4.3 Power Drift Monitoring.....	15
3.4.4 Spatial Peak SAR Evaluation	15
3.4.5 SAR Averaged Methods.....	15
4. SAR Measurement Evaluation.....	16
4.1 EUT Configuration and Setting.....	16
4.2 EUT Testing Position	33
4.2.1 Head Exposure Conditions.....	33
4.2.2 Body-worn Accessory Exposure Conditions	35
4.2.3 Hotspot Mode Exposure Conditions	36
4.2.4 Extremity Exposure Conditions	37
4.2.5 Simultaneous Transmission Possibilities.....	37
4.3 Tissue Verification	38
4.4 System Verification.....	38
4.5 Maximum Output Power.....	39
4.5.1 Maximum Conducted Power	39
4.5.2 Measured Conducted Power Result.....	42
4.6 SAR Testing Results	70
4.6.1 SAR Test Reduction Considerations	70
4.6.2 SAR Results for Head Exposure Condition	72
4.6.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap).....	72
4.6.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap).....	73
4.6.5 SAR Results for Extremity Exposure Condition (Separation Distance is 0 cm Gap).....	73
4.6.6 SAR Measurement Variability.....	74
4.6.7 Simultaneous Multi-band Transmission Evaluation	75
5. Calibration of Test Equipment.....	79
6. Measurement Uncertainty.....	80
7. Information on the Testing Laboratories	82

Appendix A. SAR Plots of System Verification

Appendix B. SAR Plots of SAR Measurement

Appendix C. Calibration Certificate for Probe and Dipole

Appendix D. Photographs of EUT and Setup



BUREAU
VERITAS

FCC SAR Test Report



ACCREDITED
Certificate # 3939.01

Release Control Record

Report No.	Reason for Change	Date Issued
W7L-P21100026SA01	Initial release	Nov. 29, 2021
W7L-P23020004SA01	Based on the original report W7L-P21100026SA01 (FCC ID: 2AFZZ117SG) changes the rear camera and internal components. The worst case of original report was verified.	Feb. 22, 2023



1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported Head SAR _{1g} (W/kg)	Highest Reported Body-worn SAR _{1g} (1.0 cm Gap) (W/kg)	Highest Reported Hotspot SAR _{1g} (1.0 cm Gap) (W/kg)	Highest Reported Extremity SAR _{10g} (0 cm Gap) (W/kg)
PCE	GSM850	1.05	0.26	0.26	N/A
	WCDMA V	0.94	0.30	0.30	N/A
	LTE 5	0.92	0.35	0.35	N/A
	LTE 7	0.70	0.99	0.94	1.45
	LTE 38	0.69	1.05	1.08	1.40
	LTE 41	0.76	0.65	0.75	1.25
DTS	2.4G WLAN	0.67	0.36	0.36	N/A
NII	5.2G WLAN	N/A	N/A	0.29	N/A
	5.3G WLAN	0.55	0.32	N/A	1.03
	5.6G WLAN	0.62	0.47	N/A	0.43
	5.8G WLAN	0.43	0.34	0.38	N/A
DSS	Bluetooth	0.17	0.06	0.06	N/A
Highest Simultaneous Transmission SAR		Head (W/kg)	Body-worn (W/kg)	Hotspot (W/kg)	Extremity (W/kg)
		1.59	1.58	1.46	1.80

Note:

- The SAR limit (Head & Body: SAR_{1g} 1.6 W/kg, Extremity: SAR_{10g} 4.0 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

2. Description of Equipment Under Test

EUT Type	Mobile Phone
FCC ID	2AFZZRA44A
Brand Name	Redmi
Model Name	2303CRA44A
Sample 1 IMEI Code	IMEI 1: 866988060016788 IMEI 2: 866988060016796
Sample 2 IMEI Code	IMEI 1: 866988060019543 IMEI 2: 866988060019550
HW Version	P1
SW Version	MIUI14
Tx Frequency Bands (Unit: MHz)	GSM850 : 824.2 ~ 848.8 WCDMA Band V : 826.4 ~ 846.6 LTE Band 5 : 824.7 ~ 848.3 LTE Band 7 : 2502.5 ~ 2567.5 LTE Band 38 : 2572.5 ~ 2617.5 LTE Band 41 : 2537.5 ~ 2652.5 WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825 Bluetooth : 2402 ~ 2480
Uplink Modulations	GSM & GPRS & EDGE : GMSK, 8PSK WCDMA : BPSK, QPSK LTE : QPSK, 16QAM, 64QAM 802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 4.5.1 of this report.
Antenna Type	WWAN Ant-0: PIFA Antenna WWAN Ant-1: PIFA Antenna WLAN/BT: PIFA Antenna
EUT Stage	Identical Prototype

Note:

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.
- According to the product equality declaration provided by the manufacturer, these changes will not affect the RF parameters, so the original reported (Report No: W7L-P21100026SA01, FCC ID: 2AFZZ117SG) conducted power and worst-case results are verified and shown in this report.
- Sample 1 and sample 2 are only different in memory size and battery supplier, so sample 2 verifies the worst case of sample 1.
- For WWAN Ant-1 and WLAN, when the audio is actively routed through the earpiece receiver on head exposure condition, power reduction will be activated to limit the maximum power.
- For WWAN Ant-0 / Ant 1, when the SAR sensor is detect close to the body sate, power reduction will be activated to limit the maximum power.

Exposure Condition	WWAN Ant-0		Power reduce
	Audio Receiver	P-sensor	
Head	On	N/A	No
Body	Off	On	Yes

Exposure Condition	WWAN Ant-1		Power reduce
	Audio Receiver	P-sensor	
Head	On	N/A	Yes
Body	Off	On	Yes

Exposure Condition	WLAN		Power reduce
	Audio Receiver	P-sensor	
Head	On	N/A	Yes
Body	Off	N/A	No

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.




Fig-3.1 DASY System Setup

3.2.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



Fig-3.2 DASY5

3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	$< 5\mu$ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

3.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W ($f < 1\text{GHz}$), > 40 W ($f > 1\text{GHz}$)	

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53


The following table gives the recipes for tissue simulating liquids.

Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	28.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ($\Delta x, \Delta y$)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

4. SAR Measurement Evaluation

4.1 EUT Configuration and Setting

<Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C is used for GSM/WCDMA/CDMA, and Anritsu MT8820C is used for LTE). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

< Proximity Sensor Triggering Distances >

The proximity sensor triggering distance was determined per KDB 616217 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed.


In the preliminary triggering distance testing, the tissue-equivalent medium for different frequency bands were used for verification; no other frequency bands tissue-equivalent medium was found to result in shortest triggering than that for 5700MHz, and the tissue-equivalent medium for 5700MHz was used for formal proximity sensor triggering testing.

Summary for power verification per distance was tabulated in the below table.

WWAN Ant-0

Output Power Verification in dBm for EUT Front Face (moving toward phantom)											
Distance (mm)	7	8	9	10	11	12	13	14	15	16	17
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.97	17.97	17.97	17.97	17.97	23.91	23.91	23.91	23.91	23.91	23.91
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.64	19.64	19.64	19.64	19.64	23.73	23.73	23.73	23.73	23.73	23.73
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.09	20.09	20.09	20.09	20.09	23.78	23.78	23.78	23.78	23.78	23.78


**Front Face
(moving toward phantom)**



**Output Power Verification in dBm for EUT Front Face
(moving away phantom)**

Distance (mm)	9	10	11	12	13	14	15	16	17	18	19
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.97	17.97	17.97	17.97	17.97	23.91	23.91	23.91	23.91	23.91	23.91
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.64	19.64	19.64	19.64	19.64	23.73	23.73	23.73	23.73	23.73	23.73
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.09	20.09	20.09	20.09	20.09	23.78	23.78	23.78	23.78	23.78	23.78


**Front Face
(moving away phantom)**



Output Power Verification in dBm for EUT Rear Face
(moving toward phantom)

Distance (mm)	12	13	14	15	16	17	18	19	20	21	22
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.97	17.97	17.97	17.97	17.97	23.91	23.91	23.91	23.91	23.91	23.91
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.64	19.64	19.64	19.64	19.64	23.73	23.73	23.73	23.73	23.73	23.73
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.09	20.09	20.09	20.09	20.09	23.78	23.78	23.78	23.78	23.78	23.78


Rear Face
(moving toward phantom)



Output Power Verification in dBm for EUT Rear Face
(moving away phantom)

Distance (mm)	14	15	16	17	18	19	20	21	22	23	24
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.97	17.97	17.97	17.97	17.97	23.91	23.91	23.91	23.91	23.91	23.91
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.64	19.64	19.64	19.64	19.64	23.73	23.73	23.73	23.73	23.73	23.73
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.09	20.09	20.09	20.09	20.09	23.78	23.78	23.78	23.78	23.78	23.78

**Rear Face
(moving away phantom)**




Output Power Verification in dBm for EUT Bottom Side

(moving toward phantom)

Distance (mm)	16	17	18	19	20	21	22	23	24	25	26
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.97	17.97	17.97	17.97	17.97	23.91	23.91	23.91	23.91	23.91	23.91
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.64	19.64	19.64	19.64	19.64	23.73	23.73	23.73	23.73	23.73	23.73
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.09	20.09	20.09	20.09	20.09	23.78	23.78	23.78	23.78	23.78	23.78

**Bottom Side
(moving toward phantom)**



BUREAU
VERITAS


FCC SAR Test Report



Certificate # 3939.01

Output Power Verification in dBm for EUT Bottom Side
(moving away phantom)


Distance (mm)	18	19	20	21	22	23	24	25	26	27	28
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.97	17.97	17.97	17.97	17.97	23.91	23.91	23.91	23.91	23.91	23.91
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.64	19.64	19.64	19.64	19.64	23.73	23.73	23.73	23.73	23.73	23.73
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.09	20.09	20.09	20.09	20.09	23.78	23.78	23.78	23.78	23.78	23.78

Bottom Side
(moving away phantom)

WWAN Ant-1


Output Power Verification in dBm for EUT Front Face (moving toward phantom)											
Distance (mm)	7	8	9	10	11	12	13	14	15	16	17
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.92	17.92	17.92	17.92	17.92	22.72	22.72	22.72	22.72	22.72	22.72
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.51	19.51	19.51	19.51	19.51	23.98	23.98	23.98	23.98	23.98	23.98
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.02	20.02	20.02	20.02	20.02	23.87	23.87	23.87	23.87	23.87	23.87

**Front Face
(moving toward phantom)**



Output Power Verification in dBm for EUT Front Face (moving away phantom)											
Distance (mm)	9	10	11	12	13	14	15	16	17	18	19
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.92	17.92	17.92	17.92	17.92	22.72	22.72	22.72	22.72	22.72	22.72
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.51	19.51	19.51	19.51	19.51	23.98	23.98	23.98	23.98	23.98	23.98
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.02	20.02	20.02	20.02	20.02	23.87	23.87	23.87	23.87	23.87	23.87

**Front Face
(moving away phantom)**




Output Power Verification in dBm for EUT Rear Face

(moving toward phantom)

Distance (mm)	12	13	14	15	16	17	18	19	20	21	22
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.92	17.92	17.92	17.92	17.92	22.72	22.72	22.72	22.72	22.72	22.72
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.51	19.51	19.51	19.51	19.51	23.98	23.98	23.98	23.98	23.98	23.98
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.02	20.02	20.02	20.02	20.02	23.87	23.87	23.87	23.87	23.87	23.87


**Rear Face
(moving toward phantom)**



Output Power Verification in dBm for EUT Rear Face
(moving away phantom)

Distance (mm)	14	15	16	17	18	19	20	21	22	23	24
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.92	17.92	17.92	17.92	17.92	22.72	22.72	22.72	22.72	22.72	22.72
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.51	19.51	19.51	19.51	19.51	23.98	23.98	23.98	23.98	23.98	23.98
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.02	20.02	20.02	20.02	20.02	23.87	23.87	23.87	23.87	23.87	23.87


Rear Face
(moving away phantom)



Output Power Verification in dBm for EUT Top Side
(moving toward phantom)

Distance (mm)	12	13	14	15	16	17	18	19	20	21	22
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.92	17.92	17.92	17.92	17.92	22.72	22.72	22.72	22.72	22.72	22.72
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.51	19.51	19.51	19.51	19.51	23.98	23.98	23.98	23.98	23.98	23.98
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.02	20.02	20.02	20.02	20.02	23.87	23.87	23.87	23.87	23.87	23.87

Top Side (moving toward phantom)




Output Power Verification in dBm for EUT Top Side

(moving away phantom)

Distance (mm)	14	15	16	17	18	19	20	21	22	23	24
LTE 7 Ch21100 (QPSK20M_1RB_OS50)	17.92	17.92	17.92	17.92	17.92	22.72	22.72	22.72	22.72	22.72	22.72
LTE 38 Ch38000 (QPSK20M_1RB_OS50)	19.51	19.51	19.51	19.51	19.51	23.98	23.98	23.98	23.98	23.98	23.98
LTE 41 Ch40640 (QPSK20M_1RB_OS50)	20.02	20.02	20.02	20.02	20.02	23.87	23.87	23.87	23.87	23.87	23.87

Top Side (moving away phantom)




< Proximity Sensor Coverage >

In KDB 616217 section 6.3, if a sensor is spatially offset from the antenna(s), it is necessary to verify sensor triggering for conditions where the antenna is next to the user but the sensor is laterally further away to ensure sensor coverage is sufficient for reducing the power to maintain compliance. For p-sensor coverage testing, the device is moved and “along the direction of maximum antenna and sensor offset”.

However, this device uses a capacitive proximity sensor that is same metallic component as the transmitting antenna to facilitate triggering in any condition the user may use the device in proximity of the antenna in the device. Therefore, no further sensor coverage assessments were required.

<Proximity Sensor Tilt Angle Influences>

The proximity sensor tilt angle influence was determined per KDB 616217 for applicable edge. Summary for proximity sensor tilt angle influence is shown in below.



Orientation	Separation Distance (mm)	Tilt Angle											
		-45°	-40°	-30°	-20°	-10°	0°	10°	20°	30°	40°	45°	
Top Side	16	On	On	On	On	On	On	On	On	On	On	On	
Bottom Side	20	On	On	On	On	On	On	On	On	On	On	On	

<Summary for Proximity Sensor Triggering Test>

According to the procedures noticed in KDB 616217 D04,

The WWAN for proximity sensor triggering distance is 11 mm for EUT Front Face, 16 mm for EUT Rear Face, 16 mm for EUT Top Side and 20 mm for Bottom Side. The separation distance of 16 mm / 20 mm determined by the smallest triggering distance on Top Side and Bottom Side is used to access the tilt angle influence and the sensor does not release during ± 45 degree. Therefore, the smallest separation distance for tilt angle influence is 16 mm for the Top Side and 20 mm for the Bottom Side. The conservation triggering distances based on the separation distance for the sensor trigger / not triggered as EUT with power reduction at 0 mm, and EUT without power reduction at 10 mm for EUT Front Face, 15 mm for EUT Rear Face, 15 mm for Top Side and 19mm for Bottom Side were used to test SAR.

The power reduction is depends on the proximity sensor input. For a steady SAR test, the power reduction was enabled or disabled manually by engineering software during SAR testing.

WWAN Proximity Sensor Trigger Distance (mm)				
Position	Front Face	Rear Face	Top Side	Bottom Side
Minimum	11	16	16	20

**<Considerations Related to GSM / GPRS / EDGE for Setup and Testing>**

The maximum multi-slot capability supported by this device is as below.

1. This EUT is class B device
2. This EUT supports GPRS multi-slot class 12 (max. uplink: 4, max. downlink: 4, total timeslots: 5)
3. This EUT supports EDGE multi-slot class 12 (max. uplink: 4, max. downlink: 4, total timeslots: 5)

For GSM850 frequency band, the power control level is set to 5 for GSM mode and GPRS (GMSK: CS1), and set to 8 for EDGE (GMSK: MCS1, 8PSK: MCS9). For GSM1900 frequency band, the power control level is set to 0 for GSM mode and GPRS (GMSK: CS1), and set to 2 for EDGE (GMSK: MCS1, 8PSK: MCS9).

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:

Frame-averaged power = 10 x log (Burst-averaged power mW x Slot used / 8)

<Considerations Related to WCDMA for Setup and Testing>**WCDMA Handsets Head SAR**

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode.

WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the "Release 5 HSDPA Data Devices", for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

Handsets with Release 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the "Release 6 HSPA Data Devices", for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	CM (dB) ⁽²⁾	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	12 / 15 ⁽³⁾	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$.

Note 3: For subtest 2 the β_c / β_d ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11 / 15$ and $\beta_d = 15 / 15$.

Release 6 HSPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	11 / 15 ⁽³⁾	22 / 15	209 / 225	1039 / 225	4	1	1.0	0.0	20	75
2	6 / 15	15 / 15	64	6 / 15	12 / 15	12 / 15	94 / 75	4	1	3.0	2.0	12	67
3	15 / 15	9 / 15	64	15 / 9	30 / 15	30 / 15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2 / 15	15 / 15	64	2 / 15	4 / 15	2 / 15	56 / 75	4	1	3.0	2.0	17	71
5	15 / 15 ⁽⁴⁾	15 / 15 ⁽⁴⁾	64	15 / 15 ⁽⁴⁾	30 / 15	24 / 15	134 / 15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c / β_d ratio of 11 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10 / 15$ and $\beta_d = 15 / 15$.

Note 4: For subtest 5 the β_c / β_d ratio of 15 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14 / 15$ and $\beta_d = 15 / 15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

HSPA+ SAR Guidance

The 3G SAR test reduction procedure is applied to HSPA+ (uplink) with 12.2 kbps RMC as the primary mode. Otherwise, when SAR is required for Rel. 6 HSPA, SAR is required for Rel. 7 HSPA+. Power is measured for HSPA+ that supports uplink 16QAM according to configurations in Table C.11.1.4 of 3GPP TS 34.121-1 to determine SAR test reduction.

DC-HSDPA SAR Guidance

The 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Otherwise, when SAR is required for Rel. 5 HSDPA, SAR is required for Rel. 8 DC-HSDPA. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

<Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 5, supports both QPSK 16QAM and 64QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK 16QAM and 64QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
2	V	V	V	V	V	V
4	V	V	V	V	V	V
5	V	V	V	V		
7			V	V	V	V
38			V	V	V	V
41			V	V	V	V

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2
64QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	2
64QAM	> 5	> 4	> 8	> 12	> 16	> 18	3


Note: MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2

Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592 • Ts	2192 • Ts	2560 • Ts	7680 • Ts	2192 • Ts	2560 • Ts
1	19760 • Ts			20480 • Ts		
2	21952 • Ts			23040 • Ts		
3	24144 • Ts			25600 • Ts		
4	26336 • Ts	4384 • Ts	5120 • Ts	7680 • Ts	4384 • Ts	5120 • Ts
5	6592 • Ts			20480 • Ts		
6	19760 • Ts			23040 • Ts		
7	21952 • Ts			12800 • Ts		
8	24144 • Ts			-	-	-

9	13168 • Ts			-	-	-
---	------------	--	--	---	---	---

3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

3GPP TS 36.211 Table 4.2-2: Uplink-Downlink Configurations

The variety of different TD-LTE uplink-downlink configurations allows a network operator to allocate the network's capacity between uplink and downlink traffic to meet the needs of the network. The uplink duty cycle of these seven configurations can readily be computed and shown in below.

UL-DL Configuration	0	1	2	3	4	5	6
Highest Duty-Cycle	63.33%	43.33%	23.33%	31.67%	21.67%	11.67%	53.33%

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 6 with 5 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 53.33%.

LTE Uplink Carrier Aggregation (CA) Setup Configurations

1. The conducted power for uplink CA active was measured on the highest reported SAR configuration for each exposure condition with both two carrier components was set to largest channel bandwidth.
2. The SAR testing was performed with the single carrier (uplink CA is inactive) for all test positions for each exposure condition. The LTE uplink CA active was verified with maximum output power on the highest SAR configuration of single carrier for each exposure condition. For intra-band contiguous CA, the SCC channel was set to closest available contiguous channel.

EUT Supported Combinations of Uplink Carrier Aggregation
Intra-Band 2CC Uplink CA Operating Bands
CA_7C, CA_38C



<Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.

2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).


2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

<Considerations Related to Bluetooth for Setup and Testing>

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

<BT Duty Cycle of Test Signal>

BT_GFSK: Duty cycle = $2.880 / 3.750 = 0.768$



4.2 EUT Testing Position

According to KDB 648474 D04, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

4.2.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.

1. Define two imaginary lines on the handset
 - (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
 - (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
 - (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig-4.1 Illustration for Handset Vertical and Horizontal Reference Lines

2. Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until

contact with the ear is lost (see Fig-4.2).




Fig-4.2 Illustration for Cheek Position

3. Tilted Position

- To position the device in the “cheek” position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig-4.3).




Fig-4.3 Illustration for Tilted Position

4.2.2 Body-worn Accessory Exposure Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 D01 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.

A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance $\leq 5 \text{ mm}$ to support compliance.





Fig-4.4 Illustration for Body Worn Position

4.2.3 Hotspot Mode Exposure Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225 D06. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



Based on the antenna location shown on appendix D of this report, the SAR testing required for hotspot mode is listed as below.

Antenna	Front Face	Rear Face	Left Side	Right Side	Top Side	Bottom Side
WWAN-Ant 0	V	V	V	V		V
WWAN-Ant 1	V	V	V	V	V	
WLAN / BT	V	V		V	V	

4.2.4 Extremity Exposure Conditions

For smart phones with a display diagonal dimension > 15 cm or an overall diagonal dimension > 16 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance.

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg. The normal tablet procedures in KDB 616217 are required when the over diagonal dimension of the device is > 20 cm. Hotspot mode SAR is not required when normal tablet procedures are applied. Extremity 10-g SAR is also not required for the front (top) surface of large form factor full size tablets. The more conservative tablet SAR results can be used to support the 10-g extremity SAR for phablet mode.
3. The simultaneous transmission operating configurations applicable to voice and data transmissions for both phone and mini-tablet modes must be taken into consideration separately for 1-g and 10-g SAR to determine the simultaneous transmission SAR test exclusion and measurement requirements for the relevant wireless modes and exposure conditions.

4.2.5 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Head	Body-worn	Hotspot	Extremity
1	WWAN + WLAN2.4G		Yes		
2	WWAN + WLAN5G		Yes		
3	WWAN + BT		Yes		
4	WLAN2.4G + BT		Yes		
5	WWAN+WLAN2.4 + BT		Yes		
6	WLAN5G + BT		Yes		
7	WWAN+WLAN5G + BT		Yes		



4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Feb. 10, 2023	Head	835	22.7	0.890	42.367	0.90	41.50	-1.11	2.09
Feb. 09, 2023	Head	2450	22.4	1.850	40.901	1.80	39.20	2.78	4.34
Feb. 14, 2023	Head	2600	22.6	2.055	38.321	1.96	39.00	4.85	-1.74
Feb. 15, 2023	Head	5250	22.4	4.744	36.854	4.71	35.90	0.72	2.66
Feb. 15, 2023	Head	5600	22.3	5.182	36.105	5.07	35.50	2.21	1.70
Feb. 16, 2023	Head	5800	22.7	5.415	35.658	5.27	35.30	2.75	1.01

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

4.4 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Feb. 10, 2023	Head	835	9.47	2.49	9.96	5.17	4d139	3873	1389
Feb. 09, 2023	Head	2450	53.60	12.70	50.80	-5.22	893	3873	1389
Feb. 14, 2023	Head	2600	55.80	13.50	54.00	-3.23	1110	3873	1389
Feb. 15, 2023	Head	5250	76.90	7.11	71.10	-7.54	1133	3873	1389
Feb. 15, 2023	Head	5600	81.20	8.00	80.00	-1.48	1133	3873	1389
Feb. 16, 2023	Head	5800	78.00	7.38	73.80	-5.38	1133	3873	1389

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

4.5 Maximum Output Power

4.5.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

WWAN-Ant 0

Mode	GSM850	
	Full Power	Reduced Power(Body)
GSM (GMSK, 1Tx-slot)	33.50	N/A
GPRS (GMSK, 1Tx-slot)	33.50	N/A
GPRS (GMSK, 2Tx-slot)	31.00	N/A
GPRS (GMSK, 3Tx-slot)	29.50	N/A
GPRS (GMSK, 4Tx-slot)	27.50	N/A
EDGE (8PSK, 1Tx-slot)	28.00	N/A
EDGE (8PSK, 2Tx-slot)	25.50	N/A
EDGE (8PSK, 3Tx-slot)	24.00	N/A
EDGE (8PSK, 4Tx-slot)	22.50	N/A

Mode	WCDMA Band V	
	Full Power	Reduced Power(Body)
RMC 12.2K	25.5	N/A
HSDPA	25.0	N/A
DC-HSDPA	24.0	N/A

Mode	LTE 5		LTE 7		LTE 38	
	Full Power	Full Power	Full Power	Reduced Power(Body)	Full Power	Reduced Power(Body)
QPSK	25.5	N/A	25.5	19.5	25.5	21
16QAM	24.5	N/A	24.5	19.5	24.5	21
64QAM	23.5	N/A	23.5	19.5	23.5	21

Mode	LTE 41	
	Full Power	Reduced Power(Body)
QPSK	25.5	22.0
16QAM	24.5	22.0
64QAM	23.5	22.0


WWAN-Ant 1

Mode	GSM850		
	Full Power	Reduced Power(Head)	Reduced Power(Body)
GSM (GMSK, 1Tx-slot)	33.50	N/A	N/A
GPRS (GMSK, 1Tx-slot)	33.50	N/A	N/A
GPRS (GMSK, 2Tx-slot)	31.00	N/A	N/A
GPRS (GMSK, 3Tx-slot)	29.50	N/A	N/A
GPRS (GMSK, 4Tx-slot)	27.50	N/A	N/A
EDGE (8PSK, 1Tx-slot)	28.00	N/A	N/A
EDGE (8PSK, 2Tx-slot)	25.50	N/A	N/A
EDGE (8PSK, 3Tx-slot)	24.00	N/A	N/A
EDGE (8PSK, 4Tx-slot)	22.50	N/A	N/A

Mode	WCDMA Band V		
	Full Power	Reduced Power(Head)	Reduced Power(Body)
RMC 12.2K	25.5	24.5	N/A
HSDPA	25.0	24.5	N/A
DC-HSDPA	24.0	24	N/A

Mode	LTE 5			LTE 7		
	Full Power	Reduced Power(Head)	Reduced Power(Body)	Full Power	Reduced Power(Head)	Reduced Power(Body)
QPSK	25.5	24.5	N/A	24.0	19.0	19.0
16QAM	24.5	23.5	N/A	24.0	19.0	19.0
64QAM	23.5	22.5	N/A	23.5	19.0	19.0

Mode	LTE 38			LTE 41		
	Full Power	Reduced Power(Head)	Reduced Power(Body)	Full Power	Reduced Power(Head)	Reduced Power(Body)
QPSK	25.5	22.0	21.0	25.5	22.0	21.5
16QAM	24.5	22.0	21.0	24.5	22.0	21.5
64QAM	23.5	22.0	21.0	23.5	22.0	21.5



WLAN / BT

Mode	WLAN2.4G		WLAN5.2G		WLAN5.3G	
	Full Power	Reduced Power(Head)	Full Power	Reduced Power(Head)	Full Power	Reduced Power(Head)
802.11a	N/A	N/A	15.5	12.5	15.5	12.5
802.11b	19.5	18.5	N/A	N/A	N/A	N/A
802.11g	19.5	18.5	N/A	N/A	N/A	N/A
802.11n-HT20	18.5	18.5	15.5	12.5	15.5	12.5
802.11n-HT40	N/A	N/A	15.5	12.5	15.5	12.5
802.11ac-VHT20	N/A	N/A	15.5	12.5	15.5	12.5
802.11ac-VHT40	N/A	N/A	15.5	12.5	15.5	12.5
802.11ac-VHT80	N/A	N/A	15.5	12.5	15.5	12.5

Mode	WLAN5.6G		WLAN5.8G	
	Full Power	Reduced Power(Head)	Full Power	Reduced Power(Head)
802.11a	15.5	12.5	15.5	12.5
802.11b	N/A	N/A	N/A	N/A
802.11g	N/A	N/A	N/A	N/A
802.11n-HT20	15.5	12.5	15.5	12.5
802.11n-HT40	15.5	12.5	15.5	12.5
802.11ac-VHT20	15.5	12.5	15.5	12.5
802.11ac-VHT40	15.5	12.5	15.5	12.5
802.11ac-VHT80	15.5	12.5	15.5	12.5

Mode	Bluetooth
BR/EDR	10.5
LE	-1.5

4.5.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

< WWAN-Ant 0 Full Power >

Band	GSM850		
Channel	128	128	128
Frequency (MHz)	824.2	824.2	824.2
Maximum Burst-Averaged Output Power			
GSM (GMSK, 1Tx-slot)	32.77	32.83	32.65
GPRS (GMSK, 1Tx-slot)	32.75	32.82	32.63
GPRS (GMSK, 2Tx-slot)	30.60	30.64	30.51
GPRS (GMSK, 3Tx-slot)	28.89	28.97	28.76
GPRS (GMSK, 4Tx-slot)	26.97	27.02	26.84
EDGE (8PSK, 1Tx-slot)	26.23	26.09	26.06
EDGE (8PSK, 2Tx-slot)	23.72	23.57	23.53
EDGE (8PSK, 3Tx-slot)	22.29	22.14	22.00
EDGE (8PSK, 4Tx-slot)	20.64	20.58	20.52
Maximum Frame-Averaged Output Power			
GSM (GMSK, 1Tx-slot)	23.77	23.83	23.65
GPRS (GMSK, 1Tx-slot)	23.75	23.82	23.63
GPRS (GMSK, 2Tx-slot)	24.60	24.64	24.51
GPRS (GMSK, 3Tx-slot)	24.63	24.71	24.50
GPRS (GMSK, 4Tx-slot)	23.97	24.02	23.84
EDGE (8PSK, 1Tx-slot)	17.23	17.09	17.06
EDGE (8PSK, 2Tx-slot)	17.72	17.57	17.53
EDGE (8PSK, 3Tx-slot)	18.03	17.88	17.74
EDGE (8PSK, 4Tx-slot)	17.64	17.58	17.52

Band	WCDMA Band V			3GPP MPR (dB)
Channel	4132	4182	4233	
Frequency (MHz)	826.4	836.4	846.6	
RMC 12.2K	24.16	24.11	24.09	-
HSDPA Subtest-1	23.12	23.06	23.08	0
HSDPA Subtest-2	23.10	23.09	23.04	0
HSDPA Subtest-3	22.69	22.66	22.67	0.5
HSDPA Subtest-4	22.68	22.69	22.64	0.5
DC-HSDPA Subtest-1	23.14	23.03	23.07	0
DC-HSDPA Subtest-2	23.08	23.05	23.01	0
DC-HSDPA Subtest-3	22.70	22.69	22.63	0.5
DC-HSDPA Subtest-4	22.69	22.66	22.67	0.5
HSUPA Subtest-1	21.22	21.18	21.14	0
HSUPA Subtest-2	21.53	21.46	21.41	2
HSUPA Subtest-3	22.24	22.13	22.15	1
HSUPA Subtest-4	21.24	21.12	21.11	2
HSUPA Subtest-5	22.60	22.56	22.57	0



LTE Band 5															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20450	20525	20600				Channel		20425	20525	20625	
		Frequency(MHz)		829	836.5	844				Frequency(MHz)		826.5	836.5	846.5	
10M	QPSK	1	0	23.83	23.90	23.79	0	5M	QPSK	1	0	23.79	23.85	23.74	0
		1	24	23.77	23.89	23.77	0			1	12	23.69	23.88	23.72	0
		1	49	23.79	23.83	23.79	0			1	24	23.75	23.78	23.78	0
		25	0	22.79	22.88	22.77	1			12	0	22.73	22.86	22.72	1
		25	12	22.91	22.98	22.93	1			12	6	22.84	22.93	22.91	1
		25	25	22.85	22.96	22.85	1			12	13	22.77	22.94	22.80	1
	16QAM	50	0	22.88	22.87	22.85	1			25	0	22.86	22.79	22.83	1
		1	0	23.07	23.14	23.04	1		16QAM	1	0	22.99	23.08	22.96	1
		1	24	23.06	23.15	23.03	1			1	12	23.00	23.13	22.97	1
		1	49	23.11	23.18	23.13	1			1	24	23.04	23.13	23.11	1
		25	0	21.77	21.81	21.75	2			12	0	21.71	21.74	21.70	2
		25	12	21.88	21.95	21.90	2			12	6	21.81	21.90	21.88	2
	64QAM	25	25	21.85	21.96	21.84	2			12	13	21.77	21.94	21.78	2
		50	0	21.84	21.96	21.87	2			25	0	21.76	21.95	21.85	2
		1	0	22.03	22.07	21.96	2		64QAM	1	0	21.99	22.02	21.88	2
		1	24	22.02	22.14	22.05	2			1	12	21.94	22.13	22.03	2
		1	49	22.12	22.16	22.05	2			1	24	22.08	22.11	21.97	2
		25	0	20.79	20.88	20.79	3			12	0	20.73	20.86	20.76	3
		25	12	20.87	20.99	20.90	3			12	6	20.79	20.98	20.88	3
		25	25	20.89	20.93	20.82	3			12	13	20.85	20.88	20.74	3
		50	0	20.84	20.93	20.84	3			25	0	20.78	20.91	20.81	3
BW	MCS Index	Channel		20415	20525	20635	3GPP MPR (dB)	BW	MCS Index	Channel		20407	20525	20643	3GPP MPR (dB)
		Frequency(MHz)		825.5	836.5	847.5				Frequency(MHz)		824.7	836.5	848.3	
3M	QPSK	1	0	23.77	23.83	23.74	0	1.4M	QPSK	1	0	23.82	23.84	23.77	0
		1	7	23.70	23.84	23.75	0			1	2	23.72	23.82	23.72	0
		1	14	23.71	23.81	23.73	0			1	5	23.77	23.75	23.77	0
		8	0	22.71	22.87	22.75	1			3	0	23.44	23.50	23.46	1
		8	3	22.87	22.93	22.85	1			3	1	23.57	23.63	23.58	1
		8	7	22.77	22.95	22.83	1			3	3	23.47	23.65	23.50	1
	16QAM	15	0	22.83	22.82	22.81	1			6	0	22.84	22.82	22.84	1
		1	0	23.05	23.06	23.03	1		16QAM	1	0	23.01	23.12	22.99	1
		1	7	22.98	23.11	22.98	1			1	2	22.99	23.10	23.01	1
		1	14	23.08	23.12	23.11	1			1	5	23.03	23.16	23.08	1
		8	0	21.75	21.74	21.70	2			3	0	22.75	22.73	22.73	2
		8	3	21.82	21.87	21.88	2			3	1	22.80	22.89	22.82	2
	64QAM	8	7	21.84	21.94	21.76	2			3	3	22.79	22.94	22.78	2
		15	0	21.79	21.88	21.81	2			6	0	21.79	21.88	21.86	2
		1	0	22.02	22.01	21.94	2		64QAM	1	0	21.99	22.02	21.91	2
		1	7	21.97	22.12	21.98	2			1	2	21.94	22.12	22.00	2
		1	14	22.10	22.08	22.04	2			1	5	22.10	22.08	22.03	2
		8	0	20.71	20.84	20.74	3			3	0	21.71	21.82	21.71	3
		8	3	20.85	20.91	20.89	3			3	1	21.81	21.97	21.84	3
		8	7	20.81	20.89	20.77	3			3	3	21.84	21.85	21.81	3
		15	0	20.82	20.85	20.83	3			6	0	20.80	20.88	20.79	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 7															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350				Channel		20825	21100	21375	
		Frequency(MHz)		2510	2535	2560				Frequency(MHz)		2507.5	2535	2562.5	
20M	QPSK	1	0	23.80	23.76	23.76	0	15M	QPSK	1	0	23.79	23.74	23.68	0
		1	50	23.95	23.91	23.99	0			1	37	23.88	23.83	23.93	0
		1	99	23.93	23.87	23.97	0			1	74	23.90	23.81	23.95	0
		50	0	23.00	22.92	23.00	1			36	0	22.98	22.85	22.95	1
		50	25	23.03	22.98	23.10	1			36	19	22.97	22.90	23.08	1
		50	50	22.98	22.89	23.02	1			36	39	22.96	22.81	23.01	1
		100	0	22.90	22.91	22.96	1			75	0	22.82	22.87	22.91	1
	16QAM	1	0	23.01	22.92	23.05	1		16QAM	1	0	22.99	22.84	23.04	1
		1	50	23.21	23.22	23.27	1			1	37	23.13	23.18	23.22	1
		1	99	23.15	23.09	23.19	1			1	74	23.12	23.03	23.17	1
		50	0	22.00	21.92	22.00	2			36	0	21.98	21.85	21.95	2
		50	25	22.04	21.99	22.11	2			36	19	21.98	21.91	22.09	2
		50	50	21.96	21.92	21.92	2			36	39	21.95	21.90	21.84	2
		100	0	21.94	21.88	21.96	2			75	0	21.89	21.80	21.90	2
	64QAM	1	0	22.03	21.95	22.05	2		64QAM	1	0	22.02	21.89	22.03	2
		1	50	22.19	22.11	22.19	2			1	37	22.17	22.04	22.14	2
		1	99	22.09	22.04	22.16	2			1	74	22.03	21.96	22.14	2
		50	0	21.01	20.97	20.97	3			36	0	21.00	20.95	20.89	3
		50	25	21.04	21.00	21.08	3			36	19	20.97	20.92	21.02	3
		50	50	20.99	20.97	21.00	3			36	39	20.97	20.96	20.96	3
		100	0	20.96	20.87	21.00	3			75	0	20.94	20.79	20.99	3
BW	MCS Index	Channel		20800	21100	21400	3GPP MPR (dB)	BW	MCS Index	Channel		20775	21100	21425	3GPP MPR (dB)
		Frequency(MHz)		2505	2535	2565				Frequency(MHz)		2502.5	2535	2567.5	
10M	QPSK	1	0	23.74	23.68	23.74	0	5M	QPSK	1	0	23.76	23.71	23.71	0
		1	24	23.93	23.83	23.98	0			1	12	23.87	23.90	23.94	0
		1	49	23.85	23.83	23.92	0			1	24	23.89	23.82	23.96	0
		25	0	22.98	22.84	22.99	1			12	0	22.94	22.90	22.95	1
		25	12	22.95	22.94	23.05	1			12	6	22.96	22.93	23.08	1
		25	25	22.95	22.83	23.00	1			12	13	22.90	22.87	22.97	1
		50	0	22.88	22.84	22.91	1			25	0	22.88	22.83	22.94	1
	16QAM	1	0	22.95	22.84	23.03	1		16QAM	1	0	22.93	22.86	22.97	1
		1	24	23.20	23.20	23.19	1			1	12	23.15	23.20	23.21	1
		1	49	23.10	23.01	23.13	1			1	24	23.08	23.04	23.17	1
		25	0	21.99	21.86	21.98	2			12	0	21.94	21.85	21.95	2
		25	12	22.02	21.91	22.10	2			12	6	21.97	21.94	22.09	2
		25	25	21.88	21.88	21.87	2			12	13	21.88	21.90	21.86	2
		50	0	21.92	21.80	21.95	2			25	0	21.86	21.87	21.94	2
	64QAM	1	0	21.95	21.91	22.00	2		64QAM	1	0	21.99	21.90	21.97	2
		1	24	22.16	22.05	22.17	2			1	12	22.11	22.10	22.17	2
		1	49	22.07	21.97	22.11	2			1	24	22.05	21.99	22.08	2
		25	0	20.95	20.89	20.95	3			12	0	20.95	20.95	20.94	3
		25	12	21.03	20.98	21.00	3			12	6	20.96	20.99	21.06	3
		25	25	20.94	20.89	20.94	3			12	13	20.95	20.92	20.92	3
		50	0	20.95	20.81	20.98	3			25	0	20.90	20.85	20.97	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 38															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37850	38000	38150				Channel		37825	38000	38175	
		Frequency(MHz)		2580	2595	2610				Frequency(MHz)		2577.5	2595	2612.5	
20M	QPSK	1	0	23.65	23.56	23.63	0	15M	QPSK	1	0	23.62	23.50	23.61	0
		1	50	23.84	23.73	23.78	0			1	37	23.82	23.66	23.73	0
		1	99	23.59	23.51	23.60	0			1	74	23.53	23.43	23.58	0
		50	0	22.69	22.62	22.59	1			36	0	22.68	22.60	22.51	1
		50	25	22.75	22.68	22.73	1			36	19	22.68	22.60	22.67	1
		50	50	22.74	22.65	22.72	1			36	39	22.71	22.59	22.70	1
		100	0	22.80	22.69	22.74	1			75	0	22.78	22.62	22.69	1
	16QAM	1	0	22.70	22.62	22.71	1		16QAM	1	0	22.64	22.54	22.69	1
		1	50	22.92	22.80	22.90	1			1	37	22.90	22.72	22.89	1
		1	99	22.70	22.68	22.70	1			1	74	22.62	22.64	22.65	1
		50	0	21.77	21.65	21.75	2			36	0	21.75	21.57	21.74	2
		50	25	21.83	21.81	21.83	2			36	19	21.75	21.77	21.78	2
		50	50	21.84	21.75	21.82	2			36	39	21.81	21.69	21.80	2
		100	0	21.81	21.70	21.75	2			75	0	21.79	21.63	21.70	2
	64QAM	1	0	21.48	21.40	21.49	2		64QAM	1	0	21.42	21.32	21.47	2
		1	50	21.68	21.61	21.58	2			1	37	21.67	21.59	21.50	2
		1	99	21.46	21.37	21.42	2			1	74	21.41	21.29	21.36	2
		50	0	20.85	20.74	20.81	3			36	0	20.84	20.68	20.79	3
		50	25	20.98	20.91	20.88	3			36	19	20.97	20.89	20.80	3
		50	50	20.93	20.86	20.83	3			36	39	20.92	20.84	20.75	3
		100	0	20.84	20.73	20.78	3			75	0	20.82	20.66	20.73	3
BW	MCS Index	Channel		37800	38000	38200	3GPP MPR (dB)	BW	MCS Index	Channel		37775	38000	38225	3GPP MPR (dB)
		Frequency(MHz)		2575	2595	2615				Frequency(MHz)		2572.5	2595	2617.5	
10M	QPSK	1	0	23.61	23.51	23.62	0	5M	QPSK	1	0	23.60	23.48	23.62	0
		1	24	23.78	23.71	23.73	0			1	12	23.80	23.68	23.73	0
		1	49	23.52	23.46	23.58	0			1	24	23.51	23.50	23.55	0
		25	0	22.61	22.60	22.54	1			12	0	22.65	22.57	22.58	1
		25	12	22.73	22.60	22.71	1			12	6	22.69	22.66	22.68	1
		25	25	22.66	22.59	22.64	1			12	13	22.67	22.60	22.70	1
		50	0	22.74	22.67	22.68	1			25	0	22.72	22.67	22.69	1
	16QAM	1	0	22.63	22.57	22.69	1		16QAM	1	0	22.68	22.54	22.69	1
		1	24	22.86	22.73	22.85	1			1	12	22.84	22.74	22.82	1
		1	49	22.63	22.63	22.68	1			1	24	22.64	22.66	22.64	1
		25	0	21.69	21.63	21.69	2			12	0	21.70	21.60	21.73	2
		25	12	21.75	21.80	21.81	2			12	6	21.77	21.74	21.78	2
		25	25	21.80	21.70	21.74	2			12	13	21.77	21.70	21.80	2
		50	0	21.73	21.69	21.73	2			25	0	21.73	21.68	21.69	2
	64QAM	1	0	21.44	21.35	21.41	2		64QAM	1	0	21.40	21.39	21.47	2
		1	24	21.62	21.59	21.55	2			1	12	21.64	21.56	21.50	2
		1	49	21.38	21.36	21.40	2			1	24	21.38	21.36	21.40	2
		25	0	20.78	20.69	20.79	3			12	0	20.81	20.69	20.73	3
		25	12	20.90	20.89	20.83	3			12	6	20.92	20.89	20.85	3
		25	25	20.91	20.78	20.81	3			12	13	20.85	20.85	20.81	3
		50	0	20.78	20.71	20.75	3			25	0	20.77	20.68	20.76	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 41															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		40140	40640	41140				Channel		40115	40640	41165	
		Frequency(MHz)		2545	2595	2645				Frequency(MHz)		2542.5	2595	2647.5	
20M	QPSK	1	0	23.66	23.61	23.57	0	15M	QPSK	1	0	23.58	23.57	23.52	0
		1	50	23.90	23.78	23.79	0			1	37	23.87	23.72	23.77	0
		1	99	23.76	23.62	23.61	0			1	74	23.74	23.55	23.56	0
		50	0	22.83	22.72	22.72	1			36	0	22.77	22.64	22.70	1
		50	25	22.91	22.81	22.75	1			36	19	22.90	22.79	22.67	1
		50	50	22.74	22.64	22.63	1			36	39	22.67	22.56	22.57	1
		100	0	22.88	22.76	22.77	1			75	0	22.85	22.70	22.75	1
	16QAM	1	0	22.82	22.68	22.67	1		16QAM	1	0	22.80	22.61	22.62	1
		1	50	22.96	22.85	22.88	1			1	37	22.90	22.77	22.86	1
		1	99	22.87	22.72	22.76	1			1	74	22.85	22.64	22.75	1
		50	0	21.90	21.85	21.81	2			36	0	21.82	21.81	21.76	2
		50	25	22.00	21.85	21.89	2			36	19	21.98	21.77	21.88	2
		50	50	21.86	21.81	21.77	2			36	39	21.78	21.77	21.72	2
		100	0	21.92	21.80	21.81	2			75	0	21.89	21.74	21.79	2
	64QAM	1	0	21.57	21.43	21.42	2		64QAM	1	0	21.55	21.36	21.37	2
		1	50	21.76	21.65	21.68	2			1	37	21.70	21.57	21.66	2
		1	99	21.65	21.55	21.46	2			1	74	21.64	21.53	21.38	2
		50	0	20.95	20.83	20.82	3			36	0	20.90	20.75	20.76	3
		50	25	21.01	20.87	20.88	3			36	19	21.00	20.81	20.86	3
		50	50	20.95	20.87	20.81	3			36	39	20.93	20.86	20.77	3
		100	0	20.93	20.78	20.82	3			75	0	20.91	20.70	20.81	3
10M	QPSK	Channel		40090	40640	41190	3GPP MPR (dB)	5M	QPSK	Channel		40065	40640	41215	3GPP MPR (dB)
		Frequency(MHz)		2540	2595	2650				Frequency(MHz)		2537.5	2595	2652.5	
		1	0	23.63	23.55	23.55	0			1	0	23.62	23.56	23.52	0
		1	24	23.88	23.71	23.74	0			1	12	23.82	23.77	23.74	0
		1	49	23.70	23.54	23.59	0			1	24	23.72	23.57	23.60	0
		25	0	22.82	22.70	22.64	1			12	0	22.77	22.70	22.67	1
	16QAM	25	12	22.84	22.73	22.69	1			12	6	22.84	22.76	22.73	1
		25	25	22.71	22.58	22.61	1			12	13	22.66	22.62	22.58	1
		50	0	22.86	22.69	22.72	1			25	0	22.86	22.68	22.75	1
		1	0	22.76	22.60	22.65	1		16QAM	1	0	22.74	22.62	22.59	1
		1	24	22.94	22.77	22.87	1			1	12	22.90	22.83	22.82	1
		1	49	22.79	22.68	22.71	1			1	24	22.80	22.67	22.74	1
		25	0	21.88	21.77	21.80	2			12	0	21.84	21.78	21.76	2
		25	12	21.92	21.81	21.84	2			12	6	21.93	21.80	21.87	2
	64QAM	25	25	21.83	21.75	21.75	2			12	13	21.78	21.79	21.71	2
		50	0	21.90	21.73	21.76	2			25	0	21.84	21.79	21.79	2
		1	0	21.51	21.35	21.40	2		64QAM	1	0	21.53	21.38	21.34	2
		1	24	21.75	21.63	21.60	2			1	12	21.68	21.64	21.66	2
		1	49	21.60	21.47	21.40	2			1	24	21.61	21.50	21.38	2
		25	0	20.94	20.77	20.80	3			12	0	20.89	20.81	20.79	3
		25	12	21.00	20.85	20.80	3			12	6	20.99	20.79	20.86	3
		25	25	20.93	20.79	20.80	3			12	13	20.91	20.82	20.73	3
		50	0	20.85	20.74	20.77	3			25	0	20.85	20.76	20.76	3

<Power Confirmation for SAR Testing for LTE Uplink CA>

The conducted power for uplink CA active was measured on the highest reported SAR configuration for each exposure condition with both two carrier components was set to largest channel bandwidth.

CA_7C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
20850	21048	QPSK	1	50	0	0	23.80
		16QAM	1	50	0	0	23.18
		64QAM	1	50	0	0	22.33
21001	21199	QPSK	1	50	0	0	23.76
		16QAM	1	50	0	0	23.45
		64QAM	1	50	0	0	22.42
21152	21350	QPSK	1	50	0	0	23.83
		16QAM	1	50	0	0	23.21
		64QAM	1	50	0	0	22.39

CA_38C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
37850	38048	QPSK	1	50	0	0	23.38
		16QAM	1	50	0	0	22.78
		64QAM	1	50	0	0	21.90
37901	38099	QPSK	1	50	0	0	23.81
		16QAM	1	50	0	0	22.85
		64QAM	1	50	0	0	21.94
37952	38150	QPSK	1	50	0	0	23.57
		16QAM	1	50	0	0	22.70
		64QAM	1	50	0	0	21.88

SAR Measurements for Intra-Band Contiguous CA

The SAR testing was performed with the single carrier (uplink CA is inactive) for all test positions for each exposure condition. The LTE uplink CA active was verified with maximum output power on the highest SAR configuration of single carrier for each exposure condition. For intra-band contiguous CA, the SCC channel was set to closest available contiguous channel.



< WWAN-Ant 0 Reduced Power for Body>

LTE Band 7															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350				Channel		20825	21100	21375	
		Frequency(MHz)		2510	2535	2560				Frequency(MHz)		2507.5	2535	2562.5	
20M	QPSK	1	0	17.79	17.76	17.76	0	15M	QPSK	1	0	17.78	17.74	17.68	0
		1	50	18.02	17.97	18.09	0			1	37	17.95	17.89	18.03	0
		1	99	17.99	17.94	18.04	0			1	74	17.96	17.88	18.02	0
		50	0	17.56	17.49	17.57	1			36	0	17.54	17.42	17.52	1
		50	25	17.63	17.59	17.71	1			36	19	17.57	17.51	17.69	1
		50	50	17.54	17.46	17.59	1			36	39	17.52	17.38	17.58	1
	16QAM	100	0	17.50	17.52	17.57	1			75	0	17.42	17.48	17.52	1
		1	0	17.71	17.63	17.76	1		16QAM	1	0	17.69	17.55	17.75	1
		1	50	17.87	17.89	17.94	1			1	37	17.79	17.85	17.89	1
		1	99	17.86	17.81	17.91	1			1	74	17.83	17.75	17.89	1
		50	0	17.58	17.51	17.59	2			36	0	17.56	17.44	17.54	2
		50	25	17.65	17.61	17.73	2			36	19	17.59	17.53	17.71	2
	64QAM	50	50	17.59	17.56	17.66	2			36	39	17.58	17.54	17.48	2
		100	0	17.52	17.47	17.55	2			75	0	17.47	17.39	17.49	2
		1	0	17.41	17.34	17.44	2		64QAM	1	0	17.40	17.28	17.42	2
		1	50	17.64	17.57	17.65	2			1	37	17.62	17.50	17.60	2
		1	99	17.51	17.47	17.59	2			1	74	17.45	17.39	17.57	2
		50	0	17.49	17.46	17.46	3			36	0	17.48	17.44	17.38	3
		50	25	17.55	17.52	17.60	3			36	19	17.48	17.44	17.54	3
		50	50	17.48	17.47	17.50	3			36	39	17.46	17.46	17.46	3
		100	0	17.46	17.38	17.51	3			75	0	17.44	17.30	17.50	3
BW	MCS Index	Channel		20800	21100	21400	3GPP MPR (dB)	BW	MCS Index	Channel		20775	21100	21425	3GPP MPR (dB)
		Frequency(MHz)		2505	2535	2565				Frequency(MHz)		2502.5	2535	2567.5	
10M	QPSK	1	0	17.73	17.68	17.74	0	5M	QPSK	1	0	17.75	17.71	17.71	0
		1	24	18.00	17.89	18.08	0			1	12	17.94	17.96	18.04	0
		1	49	17.91	17.90	17.99	0			1	24	17.95	17.89	18.03	0
		25	0	17.54	17.41	17.56	1			12	0	17.50	17.47	17.52	1
		25	12	17.55	17.55	17.66	1			12	6	17.56	17.54	17.69	1
		25	25	17.51	17.40	17.57	1			12	13	17.46	17.44	17.54	1
	16QAM	50	0	17.48	17.45	17.52	1			25	0	17.48	17.44	17.55	1
		1	0	17.65	17.55	17.74	1		16QAM	1	0	17.63	17.57	17.68	1
		1	24	17.86	17.87	17.86	1			1	12	17.81	17.87	17.88	1
		1	49	17.81	17.73	17.85	1			1	24	17.79	17.76	17.89	1
		25	0	17.57	17.45	17.57	2			12	0	17.52	17.44	17.54	2
		25	12	17.63	17.53	17.72	2			12	6	17.58	17.56	17.71	2
	64QAM	25	25	17.51	17.52	17.51	2			12	13	17.51	17.54	17.50	2
		50	0	17.50	17.39	17.54	2			25	0	17.44	17.46	17.53	2
		1	0	17.33	17.30	17.39	2		64QAM	1	0	17.37	17.29	17.36	2
		1	24	17.61	17.51	17.63	2			1	12	17.56	17.56	17.63	2
		1	49	17.49	17.40	17.54	2			1	24	17.47	17.42	17.51	2
		25	0	17.43	17.38	17.44	3			12	0	17.43	17.44	17.43	3
		25	12	17.54	17.50	17.52	3			12	6	17.47	17.51	17.58	3
		25	25	17.43	17.39	17.44	3			12	13	17.44	17.42	17.42	3
		50	0	17.45	17.32	17.49	3			25	0	17.40	17.36	17.48	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 38															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37850	38000	38150				Channel		37825	38000	38175	
		Frequency(MHz)		2580	2595	2610				Frequency(MHz)		2577.5	2595	2612.5	
20M	QPSK	1	0	19.60	19.54	19.55	0	15M	QPSK	1	0	19.57	19.48	19.53	0
		1	50	19.72	19.64	19.63	0			1	37	19.70	19.57	19.58	0
		1	99	19.64	19.59	19.62	0			1	74	19.58	19.51	19.60	0
		50	0	19.52	19.48	19.39	1			36	0	19.51	19.46	19.31	1
		50	25	19.58	19.54	19.53	1			36	19	19.51	19.46	19.47	1
		50	50	19.56	19.50	19.51	1			36	39	19.53	19.44	19.49	1
		100	0	19.58	19.50	19.49	1			75	0	19.56	19.43	19.44	1
	16QAM	1	0	19.55	19.50	19.53	1		16QAM	1	0	19.49	19.42	19.51	1
		1	50	19.71	19.62	19.66	1			1	37	19.69	19.54	19.65	1
		1	99	19.62	19.63	19.59	1			1	74	19.54	19.59	19.54	1
		50	0	19.32	19.23	19.27	2			36	0	19.30	19.15	19.26	2
		50	25	19.47	19.48	19.44	2			36	19	19.39	19.44	19.39	2
		50	50	19.33	19.27	19.28	2			36	39	19.30	19.21	19.26	2
	64QAM	100	0	19.58	19.50	19.49	2		75	0	19.56	19.43	19.44	2	
		1	0	19.45	19.40	19.43	2		64QAM	1	0	19.39	19.32	19.41	2
		1	50	19.66	19.62	19.53	2			1	37	19.65	19.60	19.45	2
		1	99	19.44	19.38	19.37	2			1	74	19.39	19.30	19.31	2
		50	0	19.19	19.11	19.12	3			36	0	19.18	19.05	19.10	3
		50	25	19.38	19.34	19.25	3			36	19	19.37	19.32	19.17	3
		50	50	19.22	19.18	19.09	3			36	39	19.21	19.16	19.01	3
		100	0	19.50	19.42	19.41	3			75	0	19.48	19.35	19.36	3
BW	MCS Index	Channel		37800	38000	38200	3GPP MPR (dB)	BW		MCS Index	Channel		37775	38000	38225
		Frequency(MHz)		2575	2595	2615			Frequency(MHz)		2572.5	2595	2617.5		
10M	QPSK	1	0	19.56	19.49	19.54	0	5M	QPSK	1	0	19.55	19.46	19.54	0
		1	24	19.66	19.62	19.58	0			1	12	19.68	19.59	19.58	0
		1	49	19.57	19.54	19.60	0			1	24	19.56	19.58	19.57	0
		25	0	19.44	19.46	19.34	1			12	0	19.48	19.43	19.38	1
		25	12	19.56	19.46	19.51	1			12	6	19.52	19.52	19.48	1
		25	25	19.48	19.44	19.43	1			12	13	19.49	19.45	19.49	1
		50	0	19.52	19.48	19.43	1			25	0	19.50	19.48	19.44	1
	16QAM	1	0	19.48	19.45	19.51	1		16QAM	1	0	19.53	19.42	19.51	1
		1	24	19.65	19.55	19.61	1			1	12	19.63	19.56	19.58	1
		1	49	19.55	19.58	19.57	1			1	24	19.56	19.61	19.53	1
		25	0	19.24	19.21	19.21	2			12	0	19.25	19.18	19.25	2
		25	12	19.39	19.47	19.42	2			12	6	19.41	19.41	19.39	2
		25	25	19.29	19.22	19.20	2			12	13	19.26	19.22	19.26	2
	64QAM	50	0	19.50	19.49	19.47	2		25	0	19.50	19.48	19.43	2	
		1	0	19.41	19.35	19.35	2		64QAM	1	0	19.37	19.39	19.41	2
		1	24	19.60	19.60	19.50	2			1	12	19.62	19.57	19.45	2
		1	49	19.36	19.37	19.35	2			1	24	19.36	19.37	19.35	2
		25	0	19.12	19.06	19.10	3			12	0	19.15	19.06	19.04	3
		25	12	19.30	19.32	19.20	3			12	6	19.32	19.32	19.22	3
		25	25	19.20	19.10	19.07	3			12	13	19.14	19.17	19.07	3
		50	0	19.44	19.40	19.38	3			25	0	19.43	19.37	19.39	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 41															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		40140	40640	41140				Channel		40115	40640	41165	
		Frequency(MHz)		2545	2595	2645				Frequency(MHz)		2542.5	2595	2647.5	
20M	QPSK	1	0	20.04	20.04	19.92	0	15M	QPSK	1	0	19.96	20.00	19.87	0
		1	50	20.16	20.09	20.02	0			1	37	20.13	20.03	20.00	0
		1	99	20.05	19.96	19.87	0			1	74	20.03	19.89	19.82	0
		50	0	19.86	19.80	19.75	1			36	0	19.80	19.72	19.73	1
		50	25	20.12	20.07	19.90	1			36	19	20.11	20.05	19.82	1
		50	50	19.93	19.88	19.79	1			36	39	19.86	19.80	19.73	1
		100	0	20.01	19.94	19.87	1			75	0	19.98	19.88	19.85	1
	16QAM	1	0	20.12	20.03	19.94	1		16QAM	1	0	20.10	19.96	19.89	1
		1	50	20.12	20.06	20.01	1			1	37	20.06	19.98	19.99	1
		1	99	20.05	19.95	19.91	1			1	74	20.03	19.87	19.90	1
		50	0	19.98	19.98	19.86	2			36	0	19.90	19.94	19.81	2
		50	25	20.08	19.98	19.94	2			36	19	20.06	19.90	19.93	2
		50	50	19.90	19.90	19.78	2			36	39	19.82	19.86	19.73	2
		100	0	20.00	19.93	19.86	2			75	0	19.97	19.87	19.84	2
	64QAM	1	0	19.79	19.70	19.61	2		64QAM	1	0	19.77	19.63	19.56	2
		1	50	19.94	19.88	19.83	2			1	37	19.88	19.80	19.81	2
		1	99	19.86	19.81	19.64	2			1	74	19.85	19.79	19.56	2
		50	0	19.57	19.50	19.41	3			36	0	19.52	19.42	19.35	3
		50	25	19.85	19.76	19.69	3			36	19	19.84	19.70	19.67	3
		50	50	19.68	19.65	19.51	3			36	39	19.66	19.64	19.47	3
		100	0	19.94	19.84	19.80	3			75	0	19.92	19.76	19.79	3
BW	MCS Index	Channel		40090	40640	41190	3GPP MPR (dB)	BW	MCS Index	Channel		40065	40640	41215	3GPP MPR (dB)
		Frequency(MHz)		2540	2595	2650				Frequency(MHz)		2537.5	2595	2652.5	
10M	QPSK	1	0	20.01	19.98	19.90	0	5M	QPSK	1	0	20.00	19.99	19.87	0
		1	24	20.14	20.02	19.97	0			1	12	20.08	20.08	19.97	0
		1	49	19.99	19.88	19.85	0			1	24	20.01	19.91	19.86	0
		25	0	19.85	19.78	19.67	1			12	0	19.80	19.78	19.70	1
		25	12	20.05	19.99	19.84	1			12	6	20.05	20.02	19.88	1
		25	25	19.90	19.82	19.77	1			12	13	19.85	19.86	19.74	1
		50	0	19.99	19.87	19.82	1			25	0	19.99	19.86	19.85	1
	16QAM	1	0	20.06	19.95	19.92	1		16QAM	1	0	20.04	19.97	19.86	1
		1	24	20.10	19.98	20.00	1			1	12	20.06	20.04	19.95	1
		1	49	19.97	19.91	19.86	1			1	24	19.98	19.90	19.89	1
		25	0	19.96	19.90	19.85	2			12	0	19.92	19.91	19.81	2
		25	12	20.00	19.94	19.89	2			12	6	20.01	19.93	19.92	2
		25	25	19.87	19.84	19.76	2			12	13	19.82	19.88	19.72	2
		50	0	19.98	19.86	19.81	2			25	0	19.92	19.92	19.84	2
	64QAM	1	0	19.73	19.62	19.59	2		64QAM	1	0	19.75	19.65	19.53	2
		1	24	19.93	19.86	19.75	2			1	12	19.86	19.87	19.81	2
		1	49	19.81	19.73	19.58	2			1	24	19.82	19.76	19.56	2
		25	0	19.56	19.44	19.39	3			12	0	19.51	19.48	19.38	3
		25	12	19.84	19.74	19.61	3			12	6	19.83	19.68	19.67	3
		25	25	19.66	19.57	19.50	3			12	13	19.64	19.60	19.43	3
		50	0	19.86	19.80	19.75	3			25	0	19.86	19.82	19.74	3



CA_7C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
20850	21048	QPSK	50	25	0	0	17.67
		16QAM	50	25	0	0	17.32
		64QAM	50	25	0	0	17.24
21001	21199	QPSK	50	25	0	0	17.82
		16QAM	50	25	0	0	17.36
		64QAM	50	25	0	0	17.25
21152	21350	QPSK	50	25	0	0	17.78
		16QAM	50	25	0	0	17.22
		64QAM	50	25	0	0	17.23

CA_38C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
37850	38048	QPSK	50	25	0	0	19.35
		16QAM	50	25	0	0	19.12
		64QAM	50	25	0	0	19.07
37901	38099	QPSK	50	25	0	0	19.55
		16QAM	50	25	0	0	19.25
		64QAM	50	25	0	0	19.25
37952	38150	QPSK	50	25	0	0	19.22
		16QAM	50	25	0	0	19.17
		64QAM	50	25	0	0	19.07


< WWAN-Ant 1 Full Power >

Band	GSM850		
Channel	128	128	128
Frequency (MHz)	824.2	824.2	824.2
Maximum Burst-Averaged Output Power			
GSM (GMSK, 1Tx-slot)	32.58	32.63	32.50
GPRS (GMSK, 1Tx-slot)	32.55	32.61	32.50
GPRS (GMSK, 2Tx-slot)	30.71	30.74	30.64
GPRS (GMSK, 3Tx-slot)	28.95	29.03	28.99
GPRS (GMSK, 4Tx-slot)	27.04	27.12	26.99
EDGE (8PSK, 1Tx-slot)	26.33	26.40	26.35
EDGE (8PSK, 2Tx-slot)	23.73	23.88	23.96
EDGE (8PSK, 3Tx-slot)	22.09	22.15	22.40
EDGE (8PSK, 4Tx-slot)	20.94	20.90	20.88
Maximum Frame-Averaged Output Power			
GSM (GMSK, 1Tx-slot)	23.58	23.63	23.50
GPRS (GMSK, 1Tx-slot)	23.55	23.61	23.50
GPRS (GMSK, 2Tx-slot)	24.71	24.74	24.64
GPRS (GMSK, 3Tx-slot)	24.69	24.77	24.73
GPRS (GMSK, 4Tx-slot)	24.04	24.12	23.99
EDGE (8PSK, 1Tx-slot)	17.33	17.40	17.35
EDGE (8PSK, 2Tx-slot)	17.73	17.88	17.96
EDGE (8PSK, 3Tx-slot)	17.83	17.89	18.14
EDGE (8PSK, 4Tx-slot)	17.94	17.90	17.88

Band	WCDMA Band V			3GPP MPR (dB)
Channel	4132	4182	4233	
Frequency (MHz)	826.4	836.4	846.6	
RMC 12.2K	24.27	24.16	24.19	-
HSDPA Subtest-1	23.24	23.10	23.17	0
HSDPA Subtest-2	23.25	23.09	23.18	0
HSDPA Subtest-3	22.69	22.51	22.63	0.5
HSDPA Subtest-4	22.73	22.58	22.66	0.5
DC-HSDPA Subtest-1	23.19	23.02	23.12	0
DC-HSDPA Subtest-2	23.24	23.03	23.16	0
DC-HSDPA Subtest-3	22.64	22.44	22.58	0.5
DC-HSDPA Subtest-4	22.71	22.50	22.64	0.5
HSUPA Subtest-1	23.22	23.08	23.11	0
HSUPA Subtest-2	21.18	21.03	21.05	2
HSUPA Subtest-3	22.10	22.02	22.03	1
HSUPA Subtest-4	21.14	20.98	21.04	2
HSUPA Subtest-5	23.16	23.06	23.06	0

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 5															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20450	20525	20600				Channel		20425	20525	20625	
		Frequency(MHz)		829	836.5	844				Frequency(MHz)		826.5	836.5	846.5	
10M	QPSK	1	0	23.81	23.85	23.82	0	5M	QPSK	1	0	23.77	23.80	23.77	0
		1	24	23.81	23.93	23.86	0			1	12	23.73	23.92	23.81	0
		1	49	23.79	23.83	23.84	0			1	24	23.75	23.78	23.83	0
		25	0	22.77	22.86	22.80	1			12	0	22.71	22.84	22.75	1
		25	12	22.87	22.94	22.93	1			12	6	22.80	22.89	22.91	1
		25	25	22.82	22.93	22.87	1			12	13	22.74	22.91	22.82	1
	16QAM	50	0	22.84	22.83	22.86	1			25	0	22.82	22.75	22.84	1
		1	0	23.08	23.15	23.10	1		16QAM	1	0	23.00	23.09	23.02	1
		1	24	23.12	23.21	23.14	1			1	12	23.06	23.19	23.08	1
		1	49	23.12	23.19	23.19	1			1	24	23.05	23.14	23.17	1
		25	0	21.76	21.80	21.79	2			12	0	21.70	21.73	21.74	2
		25	12	21.87	21.94	21.94	2			12	6	21.80	21.89	21.92	2
	64QAM	25	25	21.81	21.92	21.85	2			12	13	21.73	21.90	21.79	2
		50	0	21.83	21.95	21.91	2			25	0	21.75	21.94	21.89	2
		1	0	22.04	22.08	22.02	2		64QAM	1	0	22.00	22.03	21.94	2
		1	24	22.07	22.19	22.15	2			1	12	21.99	22.18	22.13	2
		1	49	22.09	22.13	22.07	2			1	24	22.05	22.08	21.99	2
		25	0	20.77	20.86	20.82	3			12	0	20.71	20.84	20.79	3
		25	12	20.88	21.00	20.96	3			12	6	20.80	20.99	20.94	3
		25	25	20.87	20.91	20.85	3			12	13	20.83	20.86	20.77	3
		50	0	20.86	20.95	20.91	3			25	0	20.80	20.93	20.88	3
BW	MCS Index	Channel		20415	20525	20635	3GPP MPR (dB)	BW	MCS Index	Channel		20407	20525	20643	3GPP MPR (dB)
		Frequency(MHz)		825.5	836.5	847.5				Frequency(MHz)		824.7	836.5	848.3	
3M	QPSK	1	0	23.75	23.78	23.77	0	1.4M	QPSK	1	0	23.80	23.79	23.80	0
		1	7	23.74	23.88	23.84	0			1	2	23.76	23.86	23.81	0
		1	14	23.71	23.81	23.78	0			1	5	23.77	23.75	23.82	0
		8	0	22.69	22.85	22.78	1			3	0	23.72	23.78	23.79	1
		8	3	22.83	22.89	22.85	1			3	1	23.83	23.89	23.88	1
		8	7	22.74	22.92	22.85	1			3	3	23.74	23.92	23.82	1
	16QAM	15	0	22.79	22.78	22.82	1			6	0	22.80	22.78	22.85	1
		1	0	23.06	23.07	23.09	1		16QAM	1	0	23.02	23.13	23.05	1
		1	7	23.04	23.17	23.09	1			1	2	23.05	23.16	23.12	1
		1	14	23.09	23.13	23.17	1			1	5	23.04	23.17	23.14	1
		8	0	21.74	21.73	21.74	2			3	0	22.74	22.72	22.77	2
		8	3	21.81	21.86	21.92	2			3	1	22.79	22.88	22.86	2
	64QAM	8	7	21.80	21.90	21.77	2			3	3	22.75	22.90	22.79	2
		15	0	21.78	21.87	21.85	2			6	0	21.78	21.87	21.90	2
		1	0	22.03	22.02	22.00	2		64QAM	1	0	22.00	22.03	21.97	2
		1	7	22.02	22.17	22.08	2			1	2	21.99	22.17	22.10	2
		1	14	22.07	22.05	22.06	2			1	5	22.07	22.05	22.05	2
		8	0	20.69	20.82	20.77	3			3	0	21.69	21.80	21.74	3
		8	3	20.86	20.92	20.95	3			3	1	21.82	21.98	21.90	3
		8	7	20.79	20.87	20.80	3			3	3	21.82	21.83	21.84	3
		15	0	20.84	20.87	20.90	3			6	0	20.82	20.90	20.86	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 7															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350	Channel			20825	21100	21375			
		Frequency(MHz)		2510	2535	2560	Frequency(MHz)			2507.5	2535	2562.5			
20M	QPSK	1	0	22.56	22.49	22.51	0	15M	QPSK	1	0	22.55	22.47	22.43	0
		1	50	22.79	22.72	22.82	0			1	37	22.72	22.64	22.76	0
		1	99	22.74	22.65	22.77	0			1	74	22.71	22.59	22.75	0
		50	0	22.56	22.45	22.55	1			36	0	22.54	22.38	22.50	1
		50	25	22.56	22.48	22.62	1			36	19	22.50	22.40	22.60	1
		50	50	22.52	22.40	22.55	1			36	39	22.50	22.32	22.54	1
		100	0	22.45	22.43	22.50	1			75	0	22.37	22.39	22.45	1
	16QAM	1	0	22.35	22.23	22.38	1		16QAM	1	0	22.33	22.15	22.37	1
		1	50	22.51	22.49	22.56	1			1	37	22.43	22.45	22.51	1
		1	99	22.53	22.44	22.56	1			1	74	22.50	22.38	22.54	1
		50	0	22.06	21.95	22.05	2			36	0	22.04	21.88	22.00	2
		50	25	22.05	21.97	22.11	2			36	19	21.99	21.89	22.09	2
		50	50	22.04	21.97	21.99	2			36	39	22.03	21.95	21.91	2
		100	0	21.97	21.88	21.98	2			75	0	21.92	21.80	21.92	2
	64QAM	1	0	21.98	21.87	21.99	2		64QAM	1	0	21.97	21.81	21.97	2
		1	50	22.27	22.16	22.26	2			1	37	22.25	22.09	22.21	2
		1	99	22.12	22.04	22.18	2			1	74	22.06	21.96	22.16	2
		50	0	21.08	21.01	21.03	3			36	0	21.07	20.99	20.95	3
		50	25	21.08	21.01	21.11	3			36	19	21.01	20.93	21.05	3
		50	50	21.02	20.97	21.02	3			36	39	21.00	20.96	20.98	3
		100	0	21.04	20.92	21.07	3			75	0	21.02	20.84	21.06	3
BW	MCS Index	Channel		20800	21100	21400	3GPP MPR (dB)	BW	MCS Index	Channel		20775	21100	21425	3GPP MPR (dB)
		Frequency(MHz)		2505	2535	2565	Frequency(MHz)			2502.5	2535	2567.5			
10M	QPSK	1	0	22.50	22.41	22.49	0	5M	QPSK	1	0	22.52	22.44	22.46	0
		1	24	22.77	22.64	22.81	0			1	12	22.71	22.71	22.77	0
		1	49	22.66	22.61	22.72	0			1	24	22.70	22.60	22.76	0
		25	0	22.54	22.37	22.54	1			12	0	22.50	22.43	22.50	1
		25	12	22.48	22.44	22.57	1			12	6	22.49	22.43	22.60	1
		25	25	22.49	22.34	22.53	1			12	13	22.44	22.38	22.50	1
		50	0	22.43	22.36	22.45	1			25	0	22.43	22.35	22.48	1
	16QAM	1	0	22.29	22.15	22.36	1		16QAM	1	0	22.27	22.17	22.30	1
		1	24	22.50	22.47	22.48	1			1	12	22.45	22.47	22.50	1
		1	49	22.48	22.36	22.50	1			1	24	22.46	22.39	22.54	1
		25	0	22.05	21.89	22.03	2			12	0	22.00	21.88	22.00	2
		25	12	22.03	21.89	22.10	2			12	6	21.98	21.92	22.09	2
		25	25	21.96	21.93	21.94	2			12	13	21.96	21.95	21.93	2
		50	0	21.95	21.80	21.97	2			25	0	21.89	21.87	21.96	2
	64QAM	1	0	21.90	21.83	21.94	2		64QAM	1	0	21.94	21.82	21.91	2
		1	24	22.24	22.10	22.24	2			1	12	22.19	22.15	22.24	2
		1	49	22.10	21.97	22.13	2			1	24	22.08	21.99	22.10	2
		25	0	21.02	20.93	21.01	3			12	0	21.02	20.99	21.00	3
		25	12	21.07	20.99	21.03	3			12	6	21.00	21.00	21.09	3
		25	25	20.97	20.89	20.96	3			12	13	20.98	20.92	20.94	3
		50	0	21.03	20.86	21.05	3			25	0	20.98	20.90	21.04	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 38															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37850	38000	38150				Channel		37825	38000	38175	
		Frequency(MHz)		2580	2595	2610				Frequency(MHz)		2577.5	2595	2612.5	
20M	QPSK	1	0	23.89	23.81	23.88	0	15M	QPSK	1	0	23.86	23.75	23.86	0
		1	50	24.08	23.98	24.03	0			1	37	24.06	23.91	23.98	0
		1	99	23.89	23.82	23.91	0			1	74	23.83	23.74	23.89	0
		50	0	22.93	22.87	22.84	1			36	0	22.92	22.85	22.76	1
		50	25	23.00	22.94	22.99	1			36	19	22.93	22.86	22.93	1
		50	50	23.01	22.93	23.00	1			36	39	22.98	22.87	22.98	1
		100	0	23.06	22.96	23.01	1			75	0	23.04	22.89	22.96	1
	16QAM	1	0	22.94	22.87	22.96	1		16QAM	1	0	22.88	22.79	22.94	1
		1	50	23.16	23.05	23.15	1			1	37	23.14	22.97	23.14	1
		1	99	22.98	22.97	22.99	1			1	74	22.90	22.93	22.94	1
		50	0	22.00	21.89	21.99	2			36	0	21.98	21.81	21.98	2
		50	25	22.08	22.07	22.09	2			36	19	22.00	22.03	22.04	2
		50	50	22.14	22.06	22.13	2			36	39	22.11	22.00	22.11	2
		100	0	22.07	21.97	22.02	2			75	0	22.05	21.90	21.97	2
	64QAM	1	0	21.68	21.61	21.70	2		64QAM	1	0	21.62	21.53	21.68	2
		1	50	21.91	21.85	21.82	2			1	37	21.90	21.83	21.74	2
		1	99	21.75	21.67	21.72	2			1	74	21.70	21.59	21.66	2
		50	0	21.07	20.97	21.04	3			36	0	21.06	20.91	21.02	3
		50	25	21.23	21.17	21.14	3			36	19	21.22	21.15	21.06	3
		50	50	21.19	21.13	21.10	3			36	39	21.18	21.11	21.02	3
		100	0	21.10	21.00	21.05	3			75	0	21.08	20.93	21.00	3
BW	MCS Index	Channel		37800	38000	38200	3GPP MPR (dB)	BW	MCS Index	Channel		37775	38000	38225	3GPP MPR (dB)
		Frequency(MHz)		2575	2595	2615				Frequency(MHz)		2572.5	2595	2617.5	
10M	QPSK	1	0	23.85	23.76	23.87	0	5M	QPSK	1	0	23.84	23.73	23.87	0
		1	24	24.02	23.96	23.98	0			1	12	24.04	23.93	23.98	0
		1	49	23.82	23.77	23.89	0			1	24	23.81	23.81	23.86	0
		25	0	22.85	22.85	22.79	1			12	0	22.89	22.82	22.83	1
		25	12	22.98	22.86	22.97	1			12	6	22.94	22.92	22.94	1
		25	25	22.93	22.87	22.92	1			12	13	22.94	22.88	22.98	1
		50	0	23.00	22.94	22.95	1			25	0	22.98	22.94	22.96	1
	16QAM	1	0	22.87	22.82	22.94	1		16QAM	1	0	22.92	22.79	22.94	1
		1	24	23.10	22.98	23.10	1			1	12	23.08	22.99	23.07	1
		1	49	22.91	22.92	22.97	1			1	24	22.92	22.95	22.93	1
		25	0	21.92	21.87	21.93	2			12	0	21.93	21.84	21.97	2
		25	12	22.00	22.06	22.07	2			12	6	22.02	22.00	22.04	2
		25	25	22.10	22.01	22.05	2			12	13	22.07	22.01	22.11	2
		50	0	21.99	21.96	22.00	2			25	0	21.99	21.95	21.96	2
	64QAM	1	0	21.64	21.56	21.62	2		64QAM	1	0	21.60	21.60	21.68	2
		1	24	21.85	21.83	21.79	2			1	12	21.87	21.80	21.74	2
		1	49	21.67	21.66	21.70	2			1	24	21.67	21.66	21.70	2
		25	0	21.00	20.92	21.02	3			12	0	21.03	20.92	20.96	3
		25	12	21.15	21.15	21.09	3			12	6	21.17	21.15	21.11	3
		25	25	21.17	21.05	21.08	3			12	13	21.11	21.12	21.08	3
		50	0	21.04	20.98	21.02	3			25	0	21.03	20.95	21.03	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 41															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		40140	40640	41140				Channel		40115	40640	41165	
		Frequency(MHz)		2545	2595	2645				Frequency(MHz)		2542.5	2595	2647.5	
20M	QPSK	1	0	23.72	23.74	23.70	0	15M	QPSK	1	0	23.64	23.70	23.65	0
		1	50	23.92	23.87	23.88	0			1	37	23.89	23.81	23.86	0
		1	99	23.81	23.74	23.73	0			1	74	23.79	23.67	23.68	0
		50	0	22.87	22.83	22.86	1			36	0	22.81	22.75	22.84	1
		50	25	22.94	22.91	22.82	1			36	19	22.93	22.89	22.74	1
		50	50	22.79	22.76	22.75	1			36	39	22.72	22.68	22.69	1
		100	0	22.95	22.90	22.91	1			75	0	22.92	22.84	22.89	1
	16QAM	1	0	22.83	22.76	22.75	1		16QAM	1	0	22.81	22.69	22.70	1
		1	50	22.97	22.93	22.96	1			1	37	22.91	22.85	22.94	1
		1	99	22.90	22.82	22.86	1			1	74	22.88	22.74	22.85	1
		50	0	21.93	21.95	21.91	2			36	0	21.85	21.91	21.86	2
		50	25	22.01	21.93	21.97	2			36	19	21.99	21.85	21.96	2
		50	50	21.87	21.89	21.85	2			36	39	21.79	21.85	21.80	2
		100	0	21.96	21.91	21.92	2			75	0	21.93	21.85	21.90	2
	64QAM	1	0	21.59	21.52	21.51	2		64QAM	1	0	21.57	21.45	21.46	2
		1	50	21.74	21.70	21.73	2			1	37	21.68	21.62	21.71	2
		1	99	21.66	21.63	21.54	2			1	74	21.65	21.61	21.46	2
		50	0	20.96	20.91	20.90	3			36	0	20.91	20.83	20.84	3
		50	25	21.06	20.99	21.00	3			36	19	21.05	20.93	20.98	3
		50	50	20.99	20.98	20.92	3			36	39	20.97	20.97	20.88	3
		100	0	20.98	20.90	20.94	3			75	0	20.96	20.82	20.93	3
BW	MCS Index	Channel		40090	40640	41190	3GPP MPR (dB)	BW	MCS Index	Channel		40065	40640	41215	3GPP MPR (dB)
		Frequency(MHz)		2540	2595	2650				Frequency(MHz)		2537.5	2595	2652.5	
10M	QPSK	1	0	23.69	23.68	23.68	0	5M	QPSK	1	0	23.68	23.69	23.65	0
		1	24	23.90	23.80	23.83	0			1	12	23.84	23.86	23.83	0
		1	49	23.75	23.66	23.71	0			1	24	23.77	23.69	23.72	0
		25	0	22.86	22.81	22.78	1			12	0	22.81	22.81	22.81	1
		25	12	22.87	22.83	22.76	1			12	6	22.87	22.86	22.80	1
		25	25	22.76	22.70	22.73	1			12	13	22.71	22.74	22.70	1
		50	0	22.93	22.83	22.86	1			25	0	22.93	22.82	22.89	1
	16QAM	1	0	22.77	22.68	22.73	1		16QAM	1	0	22.75	22.70	22.67	1
		1	24	22.95	22.85	22.95	1			1	12	22.91	22.91	22.90	1
		1	49	22.82	22.78	22.81	1			1	24	22.83	22.77	22.84	1
		25	0	21.91	21.87	21.90	2			12	0	21.87	21.88	21.86	2
		25	12	21.93	21.89	21.92	2			12	6	21.94	21.88	21.95	2
		25	25	21.84	21.83	21.83	2			12	13	21.79	21.87	21.79	2
		50	0	21.94	21.84	21.87	2			25	0	21.88	21.90	21.90	2
	64QAM	1	0	21.53	21.44	21.49	2		64QAM	1	0	21.55	21.47	21.43	2
		1	24	21.73	21.68	21.65	2			1	12	21.66	21.69	21.71	2
		1	49	21.61	21.55	21.48	2			1	24	21.62	21.58	21.46	2
		25	0	20.95	20.85	20.88	3			12	0	20.90	20.89	20.87	3
		25	12	21.05	20.97	20.92	3			12	6	21.04	20.91	20.98	3
		25	25	20.97	20.90	20.91	3			12	13	20.95	20.93	20.84	3
		50	0	20.90	20.86	20.89	3			25	0	20.90	20.88	20.88	3

CA_7C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
20850	21048	QPSK	1	50	0	0	22.64
		16QAM	1	50	0	0	22.01
		64QAM	1	50	0	0	21.14
21001	21199	QPSK	1	50	0	0	22.55
		16QAM	1	50	0	0	21.98
		64QAM	1	50	0	0	21.12
21152	21350	QPSK	1	50	0	0	22.44
		16QAM	1	50	0	0	21.88
		64QAM	1	50	0	0	21.07

CA_38C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
37850	38048	QPSK	1	50	0	0	23.86
		16QAM	1	50	0	0	23.10
		64QAM	1	50	0	0	21.93
37901	38099	QPSK	1	50	0	0	23.86
		16QAM	1	50	0	0	22.80
		64QAM	1	50	0	0	21.91
37952	38150	QPSK	1	50	0	0	24.03
		16QAM	1	50	0	0	22.82
		64QAM	1	50	0	0	21.73

< WWAN-Ant 1 Reduced Power for Head >

Band Channel	WCDMA Band V			3GPP MPR (dB)
	4132	4182	4233	
Frequency (MHz)	826.4	836.4	846.6	
RMC 12.2K	23.24	23.21	23.23	-
HSDPA Subtest-1	22.20	22.17	22.15	0
HSDPA Subtest-2	22.16	22.15	22.21	0
HSDPA Subtest-3	22.12	22.08	22.13	0.5
HSDPA Subtest-4	22.14	22.09	22.09	0.5
DC-HSDPA Subtest-1	22.13	22.15	22.08	0
DC-HSDPA Subtest-2	22.08	22.07	22.13	0
DC-HSDPA Subtest-3	22.10	22.02	22.05	0.5
DC-HSDPA Subtest-4	22.06	22.02	22.05	0.5
HSUPA Subtest-1	22.18	22.15	22.15	0
HSUPA Subtest-2	21.11	21.08	21.11	2
HSUPA Subtest-3	22.03	22.00	22.05	1
HSUPA Subtest-4	20.72	20.80	20.84	2
HSUPA Subtest-5	22.14	22.11	22.07	0

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 5																	
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)		
		Channel		20450	20525	20600				Channel		20425	20525	20625			
		Frequency(MHz)		829	836.5	844				Frequency(MHz)		826.5	836.5	846.5			
10M	QPSK	1	0	23.13	23.16	23.07	0	5M	QPSK	1	0	23.09	23.11	23.02	0		
		1	24	23.14	23.27	23.12	0			1	12	23.06	23.26	23.07	0		
		1	49	23.20	23.21	23.18	0			1	24	23.16	23.16	23.17	0		
		25	0	21.81	21.89	21.77	1			12	0	21.75	21.87	21.72	1		
		25	12	21.91	21.97	21.91	1			12	6	21.84	21.92	21.89	1		
		25	25	21.85	21.95	21.83	1			12	13	21.77	21.93	21.78	1		
	16QAM	50	0	21.93	21.91	21.88	1		25	0	21.91	21.83	21.86	1			
		1	0	22.94	23.00	22.89	1		16QAM	1	0	22.86	22.94	22.81	1		
		1	24	22.89	22.97	22.84	1			1	12	22.83	22.95	22.78	1		
		1	49	22.87	22.93	22.87	1			1	24	22.80	22.88	22.85	1		
		25	0	22.82	22.85	22.78	2			12	0	22.76	22.78	22.73	2		
		25	12	22.93	22.99	22.93	2			12	6	22.86	22.94	22.91	2		
	64QAM	25	25	22.85	22.95	22.82	2			12	13	22.77	22.93	22.76	2		
		50	0	22.84	22.95	22.85	2		25	0	22.76	22.94	22.83	2			
		1	0	22.08	22.11	21.99	2		64QAM	1	0	22.04	22.06	21.91	2		
		1	24	22.05	22.16	22.06	2			1	12	21.97	22.15	22.04	2		
		1	49	22.15	22.18	22.06	2			1	24	22.11	22.13	21.98	2		
		25	0	20.83	20.91	20.81	3			12	0	20.77	20.89	20.78	3		
	25	12	20.92	21.03	20.93	3	12			6	20.84	21.02	20.91	3			
	25	25	20.92	20.95	20.83	3	12			13	20.88	20.90	20.75	3			
	3M	QPSK	50	0	20.89	20.97	20.87		3	25	0	20.83	20.95	20.84	3		
			Channel		20415	20525	20635		3GPP MPR (dB)	BW	MCS Index	Channel		20407	20525	20643	3GPP MPR (dB)
			Frequency(MHz)		825.5	836.5	847.5					Frequency(MHz)		824.7	836.5	848.3	
			Frequency(MHz)		825.5	836.5	847.5					Frequency(MHz)		824.7	836.5	848.3	
QPSK			1	0	23.07	23.09	23.02	0	1.4M	QPSK	1	0	23.12	23.10	23.05	0	
			1	7	23.07	23.22	23.10	0			1	2	23.09	23.20	23.07	0	
		1	14	23.12	23.19	23.12	0	1			5	23.18	23.13	23.16	0		
		8	0	21.73	21.88	21.75	1	3			0	21.76	21.81	21.76	1		
		8	3	21.87	21.92	21.83	1	3			1	21.87	21.92	21.86	1		
		8	7	21.77	21.94	21.81	1	3			3	21.77	21.94	21.78	1		
16QAM		15	0	21.88	21.86	21.84	1	6		0	21.89	21.86	21.87	1			
		1	0	22.92	22.92	22.88	1	16QAM		1	0	22.88	22.98	22.84	1		
		1	7	22.81	22.93	22.79	1			1	2	22.82	22.92	22.82	1		
		1	14	22.84	22.87	22.85	1			1	5	22.79	22.91	22.82	1		
		8	0	22.80	22.78	22.73	2			3	0	22.80	22.77	22.76	2		
		8	3	22.87	22.91	22.91	2			3	1	22.85	22.93	22.85	2		
64QAM		8	7	22.84	22.93	22.74	2			3	3	22.79	22.93	22.76	2		
		15	0	22.79	22.87	22.79	2	6		0	22.79	22.87	22.84	2			
		1	0	22.07	22.05	21.97	2	64QAM		1	0	22.04	22.06	21.94	2		
		1	7	22.00	22.14	21.99	2			1	2	21.97	22.14	22.01	2		
		1	14	22.13	22.10	22.05	2			1	5	22.13	22.10	22.04	2		
		8	0	20.75	20.87	20.76	3			3	0	20.75	20.85	20.73	3		
8		3	20.90	20.95	20.92	3	3			1	20.86	21.01	20.87	3			
8		7	20.84	20.91	20.78	3	3			3	20.87	20.87	20.82	3			
1.4M	QPSK	15	0	20.87	20.89	20.86	3	6		0	20.85	20.92	20.82	3			
		Channel		20415	20525	20635	3GPP MPR (dB)	BW		MCS Index	Channel		20407	20525	20643	3GPP MPR (dB)	
		Frequency(MHz)		825.5	836.5	847.5					Frequency(MHz)		824.7	836.5	848.3		
		Frequency(MHz)		825.5	836.5	847.5					Frequency(MHz)		824.7	836.5	848.3		
	QPSK	1	0	23.07	23.09	23.02	0	QPSK	1	0	23.12	23.10	23.05	0			
		1	7	23.07	23.22	23.10	0		1	2	23.09	23.20	23.07	0			
		1	14	23.12	23.19	23.12	0		1	5	23.18	23.13	23.16	0			
		8	0	21.73	21.88	21.75	1		3	0	21.76	21.81	21.76	1			
		8	3	21.87	21.92	21.83	1		3	1	21.87	21.92	21.86	1			
		8	7	21.77	21.94	21.81	1		3	3	21.77	21.94	21.78	1			
	16QAM	15	0	21.88	21.86	21.84	1		6	0	21.89	21.86	21.87	1			
		1	0	22.92	22.92	22.88	1	16QAM	1	0	22.88	22.98	22.84	1			
1	7	22.81	22.93	22.79	1	1	2		22.82	22.92	22.82	1					
1	14	22.84	22.87	22.85	1	1	5		22.79	22.91	22.82	1					
8	0	22.80	22.78	22.73	2	3	0		22.80	22.77	22.76	2					
8	3	22.87	22.91	22.91	2	3	1		22.85	22.93	22.85	2					
8	7	22.84	22.93	22.74	2	3	3		22.79	22.93	22.76	2					
15	0	22.79	22.87	22.79	2	6	0		22.79	22.87	22.84	2					
3M	QPSK	1	0	22.07	22.05	21.97	2	64QAM	1	0	22.04	22.06	21.94	2			
		1	7	22.00	22.14	21.99	2		1	2	21.97	22.14	22.01	2			
		1	14	22.13	22.10	22.05	2		1	5	22.13	22.10	22.04	2			
		8	0	20.75	20.87	20.76	3		3	0	20.75	20.85	20.73	3			
	8	3	20.90	20.95	20.92	3	3		1	20.86	21.01	20.87	3				
	8	7	20.84	20.91	20.78	3	3		3	20.87	20.87	20.82	3				
	15	0	20.87	20.89	20.86	3	6		0	20.85	20.92	20.82	3				

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 7															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350				Channel		20825	21100	21375	
		Frequency(MHz)		2510	2535	2560				Frequency(MHz)		2507.5	2535	2562.5	
20M	QPSK	1	0	17.85	17.79	17.75	0	15M	QPSK	1	0	17.84	17.77	17.67	0
		1	50	17.95	17.92	17.99	0			1	37	17.88	17.84	17.93	0
		1	99	17.93	17.85	17.91	0			1	74	17.90	17.79	17.89	0
		50	0	17.56	17.46	17.50	1			36	0	17.54	17.39	17.45	1
		50	25	17.64	17.57	17.71	1			36	19	17.58	17.49	17.69	1
		50	50	17.65	17.54	17.63	1			36	39	17.63	17.46	17.62	1
		100	0	17.54	17.53	17.54	1			75	0	17.46	17.49	17.49	1
	16QAM	1	0	17.46	17.35	17.44	1		16QAM	1	0	17.44	17.27	17.43	1
		1	50	17.60	17.59	17.60	1			1	37	17.52	17.55	17.55	1
		1	99	17.54	17.46	17.52	1			1	74	17.51	17.40	17.50	1
		50	0	17.49	17.39	17.43	2			36	0	17.47	17.32	17.38	2
		50	25	17.57	17.50	17.58	2			36	19	17.51	17.42	17.56	2
		50	50	17.59	17.53	17.49	2			36	39	17.58	17.51	17.41	2
	64QAM	100	0	17.51	17.43	17.47	2		64QAM	75	0	17.46	17.35	17.41	2
		1	0	17.79	17.69	17.75	2			1	0	17.78	17.63	17.73	2
		1	50	17.97	17.87	17.91	2			1	37	17.95	17.80	17.86	2
		1	99	17.76	17.69	17.77	2			1	74	17.70	17.61	17.75	2
		50	0	17.61	17.55	17.51	3			36	0	17.60	17.53	17.43	3
		50	25	17.66	17.60	17.64	3			36	19	17.59	17.52	17.58	3
		50	50	17.68	17.64	17.63	3			36	39	17.66	17.63	17.59	3
	100	0	17.63	17.52	17.61	3	75		0	17.61	17.44	17.60	3		
BW	MCS Index	Channel		20800	21100	21400	3GPP MPR (dB)	BW	MCS Index	Channel		20775	21100	21425	3GPP MPR (dB)
		Frequency(MHz)		2505	2535	2565				Frequency(MHz)		2502.5	2535	2567.5	
10M	QPSK	1	0	17.79	17.71	17.73	0	5M	QPSK	1	0	17.81	17.74	17.70	0
		1	24	17.93	17.84	17.98	0			1	12	17.87	17.91	17.94	0
		1	49	17.85	17.81	17.86	0			1	24	17.89	17.80	17.90	0
		25	0	17.54	17.38	17.49	1			12	0	17.50	17.44	17.45	1
		25	12	17.56	17.53	17.66	1			12	6	17.57	17.52	17.69	1
		25	25	17.62	17.48	17.61	1			12	13	17.57	17.52	17.58	1
		50	0	17.52	17.46	17.49	1			25	0	17.52	17.45	17.52	1
	16QAM	1	0	17.40	17.27	17.42	1		16QAM	1	0	17.38	17.29	17.36	1
		1	24	17.59	17.57	17.52	1			1	12	17.54	17.57	17.54	1
		1	49	17.49	17.38	17.46	1			1	24	17.47	17.41	17.50	1
		25	0	17.48	17.33	17.41	2			12	0	17.43	17.32	17.38	2
		25	12	17.55	17.42	17.57	2			12	6	17.50	17.45	17.56	2
		25	25	17.51	17.49	17.44	2			12	13	17.51	17.51	17.43	2
	64QAM	50	0	17.49	17.35	17.46	2		64QAM	25	0	17.43	17.42	17.45	2
		1	0	17.71	17.65	17.70	2			1	0	17.75	17.64	17.67	2
		1	24	17.94	17.81	17.89	2			1	12	17.89	17.86	17.89	2
		1	49	17.74	17.62	17.72	2			1	24	17.72	17.64	17.69	2
		25	0	17.55	17.47	17.49	3			12	0	17.55	17.53	17.48	3
		25	12	17.65	17.58	17.56	3			12	6	17.58	17.59	17.62	3
		25	25	17.63	17.56	17.57	3			12	13	17.64	17.59	17.55	3
	50	0	17.62	17.46	17.59	3	25		0	17.57	17.50	17.58	3		

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 38															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37850	38000	38150				Channel		37825	38000	38175	
		Frequency(MHz)		2580	2595	2610				Frequency(MHz)		2577.5	2595	2612.5	
20M	QPSK	1	0	20.66	20.58	20.65	0	15M	QPSK	1	0	20.63	20.52	20.63	0
		1	50	20.74	20.64	20.64	0			1	37	20.72	20.57	20.59	0
		1	99	20.66	20.67	20.64	0			1	74	20.60	20.59	20.62	0
		50	0	20.51	20.48	20.49	1			36	0	20.50	20.46	20.41	1
		50	25	20.52	20.42	20.46	1			36	19	20.45	20.34	20.40	1
		50	50	20.45	20.38	20.38	1			36	39	20.42	20.32	20.36	1
		100	0	20.69	20.59	20.64	1			75	0	20.67	20.52	20.59	1
	16QAM	1	0	20.24	20.17	20.26	1		16QAM	1	0	20.18	20.09	20.24	1
		1	50	20.48	20.37	20.47	1			1	37	20.46	20.29	20.46	1
		1	99	20.27	20.26	20.28	1			1	74	20.19	20.22	20.23	1
		50	0	20.68	20.57	20.67	2			36	0	20.66	20.49	20.66	2
		50	25	20.58	20.57	20.59	2			36	19	20.50	20.53	20.54	2
		50	50	20.50	20.42	20.49	2			36	39	20.47	20.36	20.47	2
	64QAM	100	0	20.69	20.59	20.64	2		75	0	20.67	20.52	20.59	2	
		1	0	20.41	20.34	20.43	2		64QAM	1	0	20.35	20.26	20.41	2
		1	50	20.64	20.58	20.55	2			1	37	20.63	20.56	20.47	2
		1	99	20.45	20.37	20.42	2			1	74	20.40	20.29	20.36	2
		50	0	20.59	20.49	20.56	3			36	0	20.58	20.43	20.54	3
		50	25	20.73	20.67	20.64	3			36	19	20.72	20.65	20.56	3
		50	50	20.70	20.64	20.61	3			36	39	20.69	20.62	20.53	3
		100	0	20.61	20.51	20.56	3			75	0	20.59	20.44	20.51	3
BW	MCS Index	Channel		37800	38000	38200	3GPP MPR (dB)	BW		MCS Index	Channel		37775	38000	38225
		Frequency(MHz)		2575	2595	2615			Frequency(MHz)		2572.5	2595	2617.5		
10M	QPSK	1	0	20.62	20.53	20.64	0	5M	QPSK	1	0	20.61	20.50	20.64	0
		1	24	20.68	20.62	20.59	0			1	12	20.70	20.59	20.59	0
		1	49	20.59	20.62	20.62	0			1	24	20.58	20.66	20.59	0
		25	0	20.43	20.46	20.44	1			12	0	20.47	20.43	20.48	1
		25	12	20.50	20.34	20.44	1			12	6	20.46	20.40	20.41	1
		25	25	20.37	20.32	20.30	1			12	13	20.38	20.33	20.36	1
		50	0	20.63	20.57	20.58	1			25	0	20.61	20.57	20.59	1
	16QAM	1	0	20.17	20.12	20.24	1		16QAM	1	0	20.22	20.09	20.24	1
		1	24	20.42	20.30	20.42	1			1	12	20.40	20.31	20.39	1
		1	49	20.20	20.21	20.26	1			1	24	20.21	20.24	20.22	1
		25	0	20.60	20.55	20.61	2			12	0	20.61	20.52	20.65	2
		25	12	20.50	20.56	20.57	2			12	6	20.52	20.50	20.54	2
		25	25	20.46	20.37	20.41	2			12	13	20.43	20.37	20.47	2
	64QAM	50	0	20.61	20.58	20.62	2		25	0	20.61	20.57	20.58	2	
		1	0	20.37	20.29	20.35	2		64QAM	1	0	20.33	20.33	20.41	2
		1	24	20.58	20.56	20.52	2			1	12	20.60	20.53	20.47	2
		1	49	20.37	20.36	20.40	2			1	24	20.37	20.36	20.40	2
		25	0	20.52	20.44	20.54	3			12	0	20.55	20.44	20.48	3
		25	12	20.65	20.65	20.59	3			12	6	20.67	20.65	20.61	3
		25	25	20.68	20.56	20.59	3			12	13	20.62	20.63	20.59	3
		50	0	20.55	20.49	20.53	3			25	0	20.54	20.46	20.54	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 41															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		40140	40640	41140				Channel		40115	40640	41165	
		Frequency(MHz)		2545	2595	2645				Frequency(MHz)		2542.5	2595	2647.5	
20M	QPSK	1	0	20.37	20.33	20.37	0	15M	QPSK	1	0	20.29	20.29	20.32	0
		1	50	20.67	20.56	20.65	0			1	37	20.64	20.50	20.63	0
		1	99	20.49	20.36	20.43	0			1	74	20.47	20.29	20.38	0
		50	0	20.57	20.47	20.58	1			36	0	20.51	20.39	20.56	1
		50	25	20.64	20.55	20.54	1			36	19	20.63	20.53	20.46	1
		50	50	20.51	20.42	20.49	1			36	39	20.44	20.34	20.43	1
		100	0	20.54	20.43	20.52	1			75	0	20.51	20.37	20.50	1
	16QAM	1	0	20.40	20.27	20.34	1		16QAM	1	0	20.38	20.20	20.29	1
		1	50	20.49	20.39	20.50	1			1	37	20.43	20.31	20.48	1
		1	99	20.37	20.23	20.35	1			1	74	20.35	20.15	20.34	1
		50	0	20.50	20.46	20.50	2			36	0	20.42	20.42	20.45	2
		50	25	20.61	20.47	20.59	2			36	19	20.59	20.39	20.58	2
		50	50	20.45	20.41	20.45	2			36	39	20.37	20.37	20.40	2
	64QAM	100	0	20.50	20.39	20.48	2		75	0	20.47	20.33	20.46	2	
		1	0	20.16	20.03	20.10	2		64QAM	1	0	20.14	19.96	20.05	2
		1	50	20.24	20.14	20.25	2			1	37	20.18	20.06	20.23	2
		1	99	20.22	20.13	20.12	2			1	74	20.21	20.11	20.04	2
		50	0	20.61	20.50	20.57	3			36	0	20.56	20.42	20.51	3
		50	25	20.60	20.47	20.56	3			36	19	20.59	20.41	20.54	3
		50	50	20.58	20.51	20.53	3			36	39	20.56	20.50	20.49	3
	100	0	20.56	20.42	20.54	3	75			0	20.54	20.34	20.53	3	
BW	MCS Index	Channel		40090	40640	41190	3GPP MPR (dB)	BW	MCS Index	Channel		40065	40640	41215	3GPP MPR (dB)
		Frequency(MHz)		2540	2595	2650				Frequency(MHz)		2537.5	2595	2652.5	
10M	QPSK	1	0	20.34	20.27	20.35	0	5M	QPSK	1	0	20.33	20.28	20.32	0
		1	24	20.65	20.49	20.60	0			1	12	20.59	20.55	20.60	0
		1	49	20.43	20.28	20.41	0			1	24	20.45	20.31	20.42	0
		25	0	20.56	20.45	20.50	1			12	0	20.51	20.45	20.53	1
		25	12	20.57	20.47	20.48	1			12	6	20.57	20.50	20.52	1
		25	25	20.48	20.36	20.47	1			12	13	20.43	20.40	20.44	1
		50	0	20.52	20.36	20.47	1			25	0	20.52	20.35	20.50	1
	16QAM	1	0	20.34	20.19	20.32	1		16QAM	1	0	20.32	20.21	20.26	1
		1	24	20.47	20.31	20.49	1			1	12	20.43	20.37	20.44	1
		1	49	20.29	20.19	20.30	1			1	24	20.30	20.18	20.33	1
		25	0	20.48	20.38	20.49	2			12	0	20.44	20.39	20.45	2
		25	12	20.53	20.43	20.54	2			12	6	20.54	20.42	20.57	2
		25	25	20.42	20.35	20.43	2			12	13	20.37	20.39	20.39	2
	64QAM	50	0	20.48	20.32	20.43	2		25	0	20.42	20.38	20.46	2	
		1	0	20.10	19.95	20.08	2		64QAM	1	0	20.12	19.98	20.02	2
		1	24	20.23	20.12	20.17	2			1	12	20.16	20.13	20.23	2
		1	49	20.17	20.05	20.06	2			1	24	20.18	20.08	20.04	2
		25	0	20.60	20.44	20.55	3			12	0	20.55	20.48	20.54	3
		25	12	20.59	20.45	20.48	3			12	6	20.58	20.39	20.54	3
		25	25	20.56	20.43	20.52	3			12	13	20.54	20.46	20.45	3
	50	0	20.48	20.38	20.49	3	25			0	20.48	20.40	20.48	3	

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

CA_7C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
20850	21048	QPSK	50	25	0	0	17.89
		16QAM	50	25	0	0	17.56
		64QAM	50	25	0	0	17.52
21001	21199	QPSK	50	25	0	0	17.78
		16QAM	50	25	0	0	17.53
		64QAM	50	25	0	0	17.45
21152	21350	QPSK	50	25	0	0	17.84
		16QAM	50	25	0	0	17.33
		64QAM	50	25	0	0	17.31

CA_38C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
37850	38048	QPSK	1	50	0	0	20.58
		16QAM	1	50	0	0	20.44
		64QAM	1	50	0	0	20.42
37901	38099	QPSK	1	50	0	0	20.52
		16QAM	1	50	0	0	20.32
		64QAM	1	50	0	0	20.17
37952	38150	QPSK	1	50	0	0	20.48
		16QAM	1	50	0	0	20.38
		64QAM	1	50	0	0	20.29



< WWAN-Ant 1 Reduced Power for Body >

LTE Band 7																	
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)		
		Channel		20850	21100	21350				Channel		20825	21100	21375			
		Frequency(MHz)		2510	2535	2560				Frequency(MHz)		2507.5	2535	2562.5			
20M	QPSK	1	0	17.85	17.79	17.75	0	15M	QPSK	1	0	17.84	17.77	17.67	0		
		1	50	17.95	17.92	17.99	0			1	37	17.88	17.84	17.93	0		
		1	99	17.93	17.85	17.91	0			1	74	17.90	17.79	17.89	0		
		50	0	17.56	17.46	17.50	1			36	0	17.54	17.39	17.45	1		
		50	25	17.64	17.57	17.71	1			36	19	17.58	17.49	17.69	1		
		50	50	17.65	17.54	17.63	1			36	39	17.63	17.46	17.62	1		
		100	0	17.54	17.53	17.54	1			75	0	17.46	17.49	17.49	1		
	16QAM	1	0	17.46	17.35	17.44	1		16QAM	1	0	17.44	17.27	17.43	1		
		1	50	17.60	17.59	17.60	1			1	37	17.52	17.55	17.55	1		
		1	99	17.54	17.46	17.52	1			1	74	17.51	17.40	17.50	1		
		50	0	17.49	17.39	17.43	2			36	0	17.47	17.32	17.38	2		
		50	25	17.57	17.50	17.58	2			36	19	17.51	17.42	17.56	2		
		50	50	17.59	17.53	17.49	2			36	39	17.58	17.51	17.41	2		
	64QAM	100	0	17.51	17.43	17.47	2		75	0	17.46	17.35	17.41	2			
		1	0	17.79	17.69	17.75	2		64QAM	1	0	17.78	17.63	17.73	2		
		1	50	17.97	17.87	17.91	2			1	37	17.95	17.80	17.86	2		
		1	99	17.76	17.69	17.77	2			1	74	17.70	17.61	17.75	2		
		50	0	17.61	17.55	17.51	3			36	0	17.60	17.53	17.43	3		
		50	25	17.66	17.60	17.64	3			36	19	17.59	17.52	17.58	3		
		50	50	17.68	17.64	17.63	3			36	39	17.66	17.63	17.59	3		
	100	0	17.63	17.52	17.61	3	75			0	17.61	17.44	17.60	3			
	BW	MCS Index	Channel		20800	21100	21400		3GPP MPR (dB)	BW	MCS Index	Channel		20775	21100	21425	3GPP MPR (dB)
			Frequency(MHz)		2505	2535	2565					Frequency(MHz)		2502.5	2535	2567.5	
	10M	QPSK	1	0	17.79	17.71	17.73		0	5M	QPSK	1	0	17.81	17.74	17.70	0
1			24	17.93	17.84	17.98	0	1	12			17.87	17.91	17.94	0		
1			49	17.85	17.81	17.86	0	1	24			17.89	17.80	17.90	0		
25			0	17.54	17.38	17.49	1	12	0			17.50	17.44	17.45	1		
25			12	17.56	17.53	17.66	1	12	6			17.57	17.52	17.69	1		
25			25	17.62	17.48	17.61	1	12	13			17.57	17.52	17.58	1		
50			0	17.52	17.46	17.49	1	25	0			17.52	17.45	17.52	1		
16QAM		1	0	17.40	17.27	17.42	1	16QAM	1		0	17.38	17.29	17.36	1		
		1	24	17.59	17.57	17.52	1		1		12	17.54	17.57	17.54	1		
		1	49	17.49	17.38	17.46	1		1		24	17.47	17.41	17.50	1		
		25	0	17.48	17.33	17.41	2		12		0	17.43	17.32	17.38	2		
		25	12	17.55	17.42	17.57	2		12		6	17.50	17.45	17.56	2		
		25	25	17.51	17.49	17.44	2		12		13	17.51	17.51	17.43	2		
64QAM		50	0	17.49	17.35	17.46	2	25	0		17.43	17.42	17.45	2			
		1	0	17.71	17.65	17.70	2	64QAM	1		0	17.75	17.64	17.67	2		
		1	24	17.94	17.81	17.89	2		1		12	17.89	17.86	17.89	2		
		1	49	17.74	17.62	17.72	2		1		24	17.72	17.64	17.69	2		
		25	0	17.55	17.47	17.49	3		12		0	17.55	17.53	17.48	3		
		25	12	17.65	17.58	17.56	3		12		6	17.58	17.59	17.62	3		
		25	25	17.63	17.56	17.57	3		12		13	17.64	17.59	17.55	3		
50		0	17.62	17.46	17.59	3	25		0		17.57	17.50	17.58	3			

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

LTE Band 38															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		37850	38000	38150				Channel		37825	38000	38175	
		Frequency(MHz)		2580	2595	2610				Frequency(MHz)		2577.5	2595	2612.5	
20M	QPSK	1	0	19.47	19.27	19.34	0	15M	QPSK	1	0	19.44	19.21	19.32	0
		1	50	19.73	19.51	19.56	0			1	37	19.71	19.44	19.51	0
		1	99	19.59	19.40	19.49	0			1	74	19.53	19.32	19.47	0
		50	0	19.37	19.19	19.16	1			36	0	19.36	19.17	19.08	1
		50	25	19.44	19.26	19.31	1			36	19	19.37	19.18	19.25	1
		50	50	19.27	19.07	19.14	1			36	39	19.24	19.01	19.12	1
		100	0	19.49	19.27	19.32	1			75	0	19.47	19.20	19.27	1
	16QAM	1	0	19.40	19.21	19.30	1		16QAM	1	0	19.34	19.13	19.28	1
		1	50	19.63	19.40	19.50	1			1	37	19.61	19.32	19.49	1
		1	99	19.46	19.33	19.35	1			1	74	19.38	19.29	19.30	1
		50	0	19.57	19.34	19.44	2			36	0	19.55	19.26	19.43	2
		50	25	19.54	19.41	19.43	2			36	19	19.46	19.37	19.38	2
		50	50	19.52	19.32	19.39	2			36	39	19.49	19.26	19.37	2
		100	0	19.55	19.33	19.38	2			75	0	19.53	19.26	19.33	2
	64QAM	1	0	19.11	18.92	19.01	2		64QAM	1	0	19.05	18.84	18.99	2
		1	50	19.38	19.20	19.17	2			1	37	19.37	19.18	19.09	2
		1	99	19.18	18.98	19.03	2			1	74	19.13	18.90	18.97	2
		50	0	19.58	19.36	19.43	3			36	0	19.57	19.30	19.41	3
		50	25	19.49	19.31	19.28	3			36	19	19.48	19.29	19.20	3
		50	50	19.69	19.51	19.48	3			36	39	19.68	19.49	19.40	3
		100	0	19.56	19.34	19.39	3			75	0	19.54	19.27	19.34	3
BW	MCS Index	Channel		37800	38000	38200	3GPP MPR (dB)	BW	MCS Index	Channel		37775	38000	38225	3GPP MPR (dB)
		Frequency(MHz)		2575	2595	2615				Frequency(MHz)		2572.5	2595	2617.5	
10M	QPSK	1	0	19.43	19.22	19.33	0	5M	QPSK	1	0	19.42	19.19	19.33	0
		1	24	19.67	19.49	19.51	0			1	12	19.69	19.46	19.51	0
		1	49	19.52	19.35	19.47	0			1	24	19.51	19.39	19.44	0
		25	0	19.29	19.17	19.11	1			12	0	19.33	19.14	19.15	1
		25	12	19.42	19.18	19.29	1			12	6	19.38	19.24	19.26	1
		25	25	19.19	19.01	19.06	1			12	13	19.20	19.02	19.12	1
		50	0	19.43	19.25	19.26	1			25	0	19.41	19.25	19.27	1
	16QAM	1	0	19.33	19.16	19.28	1		16QAM	1	0	19.38	19.13	19.28	1
		1	24	19.57	19.33	19.45	1			1	12	19.55	19.34	19.42	1
		1	49	19.39	19.28	19.33	1			1	24	19.40	19.31	19.29	1
		25	0	19.49	19.32	19.38	2			12	0	19.50	19.29	19.42	2
		25	12	19.46	19.40	19.41	2			12	6	19.48	19.34	19.38	2
		25	25	19.48	19.27	19.31	2			12	13	19.45	19.27	19.37	2
		50	0	19.47	19.32	19.36	2			25	0	19.47	19.31	19.32	2
	64QAM	1	0	19.07	18.87	18.93	2		64QAM	1	0	19.03	18.91	18.99	2
		1	24	19.32	19.18	19.14	2			1	12	19.34	19.15	19.09	2
		1	49	19.10	18.97	19.01	2			1	24	19.10	18.97	19.01	2
		25	0	19.51	19.31	19.41	3			12	0	19.54	19.31	19.35	3
		25	12	19.41	19.29	19.23	3			12	6	19.43	19.29	19.25	3
		25	25	19.67	19.43	19.46	3			12	13	19.61	19.50	19.46	3
		50	0	19.50	19.32	19.36	3			25	0	19.49	19.29	19.37	3



LTE Band 41															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		40140	40640	41140				Channel		40115	40640	41165	
		Frequency(MHz)		2545	2595	2645				Frequency(MHz)		2542.5	2595	2647.5	
20M	QPSK	1	0	19.80	19.75	19.79	0	15M	QPSK	1	0	19.72	19.71	19.74	0
		1	50	20.14	20.02	20.11	0			1	37	20.11	19.96	20.09	0
		1	99	19.83	19.69	19.76	0			1	74	19.81	19.62	19.71	0
		50	0	19.99	19.88	19.99	1			36	0	19.93	19.80	19.97	1
		50	25	20.13	20.03	20.02	1			36	19	20.12	20.01	19.94	1
		50	50	19.92	19.82	19.89	1			36	39	19.85	19.74	19.83	1
		100	0	19.97	19.85	19.94	1			75	0	19.94	19.79	19.92	1
	16QAM	1	0	19.93	19.79	19.86	1		16QAM	1	0	19.91	19.72	19.81	1
		1	50	20.01	19.90	20.01	1			1	37	19.95	19.82	19.99	1
		1	99	19.98	19.83	19.95	1			1	74	19.96	19.75	19.94	1
		50	0	19.97	19.92	19.96	2			36	0	19.89	19.88	19.91	2
		50	25	20.07	19.92	20.04	2			36	19	20.05	19.84	20.03	2
		50	50	19.99	19.94	19.98	2			36	39	19.91	19.90	19.93	2
		100	0	20.03	19.91	20.00	2			75	0	20.00	19.85	19.98	2
	64QAM	1	0	19.62	19.48	19.55	2		64QAM	1	0	19.60	19.41	19.50	2
		1	50	19.79	19.68	19.79	2			1	37	19.73	19.60	19.77	2
		1	99	19.67	19.57	19.56	2			1	74	19.66	19.55	19.48	2
		50	0	19.79	19.67	19.74	3			36	0	19.74	19.59	19.68	3
		50	25	19.98	19.84	19.93	3			36	19	19.97	19.78	19.91	3
		50	50	19.74	19.66	19.68	3			36	39	19.72	19.65	19.64	3
		100	0	19.81	19.66	19.78	3			75	0	19.79	19.58	19.77	3
BW	MCS Index	Channel		40090	40640	41190	3GPP MPR (dB)	BW	MCS Index	Channel		40065	40640	41215	3GPP MPR (dB)
		Frequency(MHz)		2540	2595	2650				Frequency(MHz)		2537.5	2595	2652.5	
10M	QPSK	1	0	19.77	19.69	19.77	0	5M	QPSK	1	0	19.76	19.70	19.74	0
		1	24	20.12	19.95	20.06	0			1	12	20.06	20.01	20.06	0
		1	49	19.77	19.61	19.74	0			1	24	19.79	19.64	19.75	0
		25	0	19.98	19.86	19.91	1			12	0	19.93	19.86	19.94	1
		25	12	20.06	19.95	19.96	1			12	6	20.06	19.98	20.00	1
		25	25	19.89	19.76	19.87	1			12	13	19.84	19.80	19.84	1
		50	0	19.95	19.78	19.89	1			25	0	19.95	19.77	19.92	1
	16QAM	1	0	19.87	19.71	19.84	1		16QAM	1	0	19.85	19.73	19.78	1
		1	24	19.99	19.82	20.00	1			1	12	19.95	19.88	19.95	1
		1	49	19.90	19.79	19.90	1			1	24	19.91	19.78	19.93	1
		25	0	19.95	19.84	19.95	2			12	0	19.91	19.85	19.91	2
		25	12	19.99	19.88	19.99	2			12	6	20.00	19.87	20.02	2
		25	25	19.96	19.88	19.96	2			12	13	19.91	19.92	19.92	2
		50	0	20.01	19.84	19.95	2			25	0	19.95	19.90	19.98	2
	64QAM	1	0	19.56	19.40	19.53	2		64QAM	1	0	19.58	19.43	19.47	2
		1	24	19.78	19.66	19.71	2			1	12	19.71	19.67	19.77	2
		1	49	19.62	19.49	19.50	2			1	24	19.63	19.52	19.48	2
		25	0	19.78	19.61	19.72	3			12	0	19.73	19.65	19.71	3
		25	12	19.97	19.82	19.85	3			12	6	19.96	19.76	19.91	3
		25	25	19.72	19.58	19.67	3			12	13	19.70	19.61	19.60	3
		50	0	19.73	19.62	19.73	3			25	0	19.73	19.64	19.72	3

BUREAU
VERITAS

FCC SAR Test Report

ACCREDITED
Certificate # 3939.01

CA_7C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
20850	21048	QPSK	1	50	0	0	17.88
		16QAM	1	50	0	0	17.57
		64QAM	1	50	0	0	17.53
21001	21199	QPSK	1	50	0	0	17.81
		16QAM	1	50	0	0	17.52
		64QAM	1	50	0	0	17.44
21152	21350	QPSK	1	50	0	0	17.91
		16QAM	1	50	0	0	17.28
		64QAM	1	50	0	0	17.30

CA_38C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
37850	38048	QPSK	1	50	0	0	19.43
		16QAM	1	50	0	0	19.22
		64QAM	1	50	0	0	19.11
37901	38099	QPSK	1	50	0	0	19.26
		16QAM	1	50	0	0	19.04
		64QAM	1	50	0	0	19.02
37952	38150	QPSK	1	50	0	0	19.21
		16QAM	1	50	0	0	19.15
		64QAM	1	50	0	0	19.02

WLAN / BT

	Mode	Channel	Frequency (MHz)	Full power (dBm)	Reduced power (dBm)
2.4GHz WLAN	802.11b 1Mbps	1	2412	17.82	17.09
		6	2437	17.84	17.26
		11	2462	18.01	17.36
	802.11g 6Mbps	1	2412	15.17	15.17
		6	2437	15.15	15.15
		11	2462	15.21	15.21
	802.11n-HT20 MCS0	1	2412	13.89	13.89
		6	2437	13.78	13.78
		11	2462	13.84	13.84

	Mode	Channel	Frequency(MHz)	Full power (dBm)
Bluetooth	BR / EDR	0	2402	8.36
		39	2441	9.28
		78	2480	8.99
	BLE 1Mbps	0	2402	-5.08
		19	2440	-3.02
		39	2480	-3.68
	BLE 2Mbps	0	2402	-6.75
		19	2440	-4.69
		39	2480	-5.34

5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Full power (dBm)	Reduced power (dBm)
	802.11a 6Mbps	36	5180	14.02	11.00
		40	5200	14.07	11.07
		44	5220	14.05	11.25
		48	5240	14.16	11.03
	802.11n-HT20 MCS0	36	5180	13.90	11.18
		40	5200	14.02	11.05
		44	5220	14.00	11.06
		48	5240	14.11	11.09
	802.11n-HT40 MCS0	38	5190	14.30	11.09
		46	5230	14.38	11.06
	802.11ac-VHT20 MCS0	36	5180	14.32	11.00
		40	5200	13.98	11.04
		44	5220	14.01	11.22
		48	5240	14.05	11.23
	802.11ac-VHT40 MCS0	38	5190	14.29	11.07
		46	5230	14.43	11.22
	802.11ac-VHT80 MCS0	42	5210	13.52	11.14

5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Full power (dBm)	Reduced power (dBm)
	802.11a 6Mbps	52	5260	14.04	11.30
		56	5280	14.00	11.28
		60	5300	14.12	11.23
		64	5320	14.15	11.25
	802.11n-HT20 MCS0	52	5260	14.15	11.22
		56	5280	14.08	11.18
		60	5300	14.12	11.22
		64	5320	14.51	11.31
	802.11n-HT40 MCS0	54	5270	14.43	11.13
		62	5310	14.00	11.14
	802.11ac-VHT20 MCS0	52	5260	14.16	11.17
		56	5280	14.09	11.26
		60	5300	14.09	11.22
		64	5320	14.01	11.14
	802.11ac-VHT40 MCS0	54	5270	14.05	11.30
		62	5310	14.08	11.27
	802.11ac-VHT80 MCS0	58	5290	13.66	11.01

	Mode	Channel	Frequency (MHz)	Full power (dBm)	Reduced power (dBm)
5.6GHz WLAN	802.11a 6Mbps	100	5500	14.09	11.04
		116	5580	13.75	10.98
		124	5620	13.90	10.96
		132	5660	14.01	11.00
		140	5700	13.80	11.09
	802.11n-HT20 MCS0	100	5500	13.91	11.08
		116	5580	13.56	11.06
		124	5620	13.78	10.95
		132	5660	13.88	10.92
		140	5700	13.71	10.95
	802.11n-HT40 MCS0	102	5510	14.25	11.04
		110	5550	13.91	11.08
		126	5630	14.24	11.02
		134	5670	13.95	10.75
	802.11ac-VHT20 MCS0	100	5500	13.92	11.02
		116	5580	13.62	11.00
		124	5620	13.80	11.00
		132	5660	13.87	10.78
		140	5700	13.71	11.07
	802.11ac-VHT40 MCS0	102	5510	14.26	11.09
		110	5550	13.91	11.00
		126	5630	14.20	10.83
		134	5670	13.93	10.91
	802.11ac-VHT80 MCS0	106	5530	14.03	10.86
		122	5610	13.84	10.75

	Mode	Channel	Frequency (MHz)	Full power (dBm)	Reduced power (dBm)
5.8GHz WLAN	802.11a 6Mbps	149	5745	14.41	11.16
		157	5785	14.17	11.16
		165	5825	14.75	11.18
	802.11n-HT20 MCS0	149	5745	14.36	10.98
		157	5785	14.43	11.15
		165	5825	14.64	11.11
	802.11n-HT40 MCS0	151	5755	14.30	10.82
		159	5795	13.99	10.85
	802.11ac-VHT20 MCS0	149	5745	13.82	10.86
		157	5785	13.98	10.87
		165	5825	14.54	10.83
	802.11ac-VHT40 MCS0	151	5755	14.26	10.82
		159	5795	14.40	10.72
	802.11ac-VHT80 MCS0	155	5775	14.11	10.95

4.6 SAR Testing Results

4.6.1 SAR Test Reduction Considerations

<KDB 447498 D04, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 941225 D01, 3G SAR Measurement Procedures>

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

- (1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

- (2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

- (3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

- (4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.



BUREAU
VERITAS

FCC SAR Test Report



<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.
- (4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.



4.6.2 SAR Results for Head Exposure Condition

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Power Reduction	Antenna	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
1	GSM850	GPRS 3Tx slot	Right Cheek	189	-	-	Full	Ant1	1	-	29.5	29.03	-0.08	0.946	1.00	1.11	1.05
	GSM850	GPRS 3Tx slot	Right Cheek	128	-	-	Full	Ant1	1	-	29.5	28.95	-0.05	0.772	1.00	1.14	0.88
	GSM850	GPRS 3Tx slot	Right Cheek	251	-	-	Full	Ant1	1	-	29.5	28.99	0.01	0.817	1.00	1.12	0.92
	GSM850	GPRS 3Tx slot	Right Cheek	189	-	-	Full	Ant1	2	-	29.5	29.03	0.05	0.903	1.00	1.11	1.01
	WCDMA V	RMC12.2K	Right Cheek	4132	-	-	Reduce	Ant1	1	-	24.5	23.24	-0.01	0.621	1.00	1.34	0.83
2	WCDMA V	RMC12.2K	Right Cheek	4182	-	-	Reduce	Ant1	1	-	24.5	23.21	-0.05	0.695	1.00	1.35	0.94
	WCDMA V	RMC12.2K	Right Cheek	4233	-	-	Reduce	Ant1	1	-	24.5	23.23	-0.02	0.667	1.00	1.34	0.89
	WCDMA V	RMC12.2K	Right Cheek	4182	-	-	Reduce	Ant1	2	-	24.5	23.21	0.19	0.637	1.00	1.35	0.86
	LTE 5	QPSK10M	Right Cheek	20525	1	24	Reduce	Ant1	1	-	24.5	23.27	-0.09	0.667	1.00	1.33	0.89
	LTE 5	QPSK10M	Right Cheek	20450	1	24	Reduce	Ant1	1	-	24.5	23.14	-0.01	0.642	1.00	1.37	0.88
3	LTE 5	QPSK10M	Right Cheek	20600	1	24	Reduce	Ant1	1	-	24.5	23.12	0.02	0.668	1.00	1.37	0.92
	LTE 5	QPSK10M	Right Cheek	20600	1	24	Reduce	Ant1	2	-	24.5	23.12	0.05	0.634	1.00	1.37	0.87
4	LTE 7	QPSK20M	Right Tilted	21350	50	25	Reduce	Ant1	1	-	19	17.71	0.09	0.519	1.00	1.35	0.70
	LTE 7	QPSK20M	Right Tilted	21350	50	25	Reduce	Ant1	2	-	19	17.71	-0.06	0.511	1.00	1.35	0.69
5	LTE 38	QPSK20M	Right Tilted	38150	1	50	Reduce	Ant1	1	62.9	22	20.64	0.02	0.498	1.01	1.37	0.69
	LTE 38	QPSK20M	Right Tilted	38150	1	50	Reduce	Ant1	2	62.9	22	20.64	0.08	0.466	1.01	1.37	0.64
16	LTE 41	QPSK20M	Right Tilted	40140	1	50	Reduce	Ant1	1	62.9	22	20.67	0.07	0.556	1.01	1.36	0.76
	LTE 41	QPSK20M	Right Tilted	40140	1	50	Reduce	Ant1	2	62.9	22	20.67	0.09	0.549	1.01	1.36	0.75
7	WLAN2.4G	802.11b	Left Cheek	11	-	-	Reduce	-	1	99.64	18.5	17.36	0.05	0.516	1.00	1.30	0.67
	WLAN2.4G	802.11b	Left Cheek	11	-	-	Reduce	-	2	99.64	18.5	17.36	-0.15	0.508	1.00	1.30	0.66
8	WLAN5G	802.11ac80	Left Tilted	58	-	-	Reduce	-	1	88.89	12.5	11.01	-0.05	0.350	1.12	1.41	0.55
	WLAN5G	802.11ac80	Left Tilted	58	-	-	Reduce	-	2	88.89	12.5	11.01	0.04	0.337	1.12	1.41	0.53
9	WLAN5G	802.11ac80	Left Tilted	106	-	-	Reduce	-	1	88.89	12.5	10.86	-0.06	0.379	1.12	1.46	0.62
	WLAN5G	802.11ac80	Left Tilted	106	-	-	Reduce	-	2	88.89	12.5	10.86	0.11	0.355	1.12	1.46	0.58
10	WLAN5G	802.11ac80	Left Tilted	155	-	-	Reduce	-	1	88.89	12.5	10.95	-0.05	0.267	1.12	1.43	0.43
	WLAN5G	802.11ac80	Left Tilted	155	-	-	Reduce	-	2	88.89	12.5	10.95	-0.06	0.255	1.12	1.43	0.41
11	BT	GFSK	Left Cheek	39	-	-	Full	-	1	76.8	10.5	9.28	0	0.098	1.30	1.32	0.17
	BT	GFSK	Left Cheek	39	-	-	Full	-	2	76.8	10.5	9.28	0.14	0.085	1.30	1.32	0.15

4.6.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Separation Distance (cm)	Ch.	RB#	RB Offset	Power Reduction	Antenna	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
12	GSM850	GPRS 3Tx slot	Rear Face	1	189	-	-	Full	Ant0	1	-	29.5	28.97	0	0.228	1.00	1.13	0.26
	GSM850	GPRS 3Tx slot	Rear Face	1	189	-	-	Full	Ant0	2	-	29.5	28.97	0.05	0.211	1.00	1.13	0.24
13	WCDMA V	RMC12.2K	Rear Face	1	4132	-	-	Full	Ant0	1	-	25.5	24.16	0.01	0.218	1.00	1.36	0.30
	WCDMA V	RMC12.2K	Rear Face	1	4132	-	-	Full	Ant0	2	-	25.5	24.16	0	0.199	1.00	1.36	0.27
14	LTE 5	QPSK10M	Rear Face	1	20525	1	0	Full	Ant0	1	-	25.5	23.9	-0.02	0.244	1.00	1.45	0.35
	LTE 5	QPSK10M	Rear Face	1	20525	1	0	Full	Ant0	2	-	25.5	23.9	-0.13	0.229	1.00	1.45	0.33
	LTE 7	QPSK20M	Rear Face	1	21350	50	25	Reduce	Ant0	1	-	19.5	17.97	0.11	0.342	1.00	1.42	0.49
15	LTE 7	QPSK20M	Rear Face	1.5	21350	1	50	Full	Ant0	1	-	25.5	23.99	-0.08	0.697	1.00	1.42	0.99
	LTE 7	QPSK20M	Rear Face	1.5	20850	1	50	Full	Ant0	1	-	25.5	23.95	-0.06	0.456	1.00	1.43	0.65
	LTE 7	QPSK20M	Rear Face	1.5	21100	1	50	Full	Ant0	1	-	25.5	23.91	-0.08	0.630	1.00	1.44	0.91
	LTE 7	QPSK20M	Rear Face	1.5	21350	1	50	Full	Ant0	2	-	25.5	23.99	0	0.679	1.00	1.42	0.96
	LTE 38	QPSK20M	Rear Face	1	37850	1	50	Reduce	Ant0	1	62.9	21	19.64	0.08	0.477	1.01	1.37	0.66
	LTE 38	QPSK20M	Rear Face	1.5	37850	1	50	Full	Ant0	1	62.9	25.5	23.84	0.07	0.588	1.01	1.47	0.87
	LTE 38	QPSK20M	Rear Face	1.5	38000	1	50	Full	Ant0	1	62.9	25.5	23.73	-0.05	0.646	1.01	1.50	0.98
16	LTE 38	QPSK20M	Rear Face	1.5	38150	1	50	Full	Ant0	1	62.9	25.5	23.78	0.08	0.701	1.01	1.49	1.05
	LTE 38	QPSK20M	Rear Face	1.5	38150	1	50	Full	Ant0	2	62.9	25.5	23.78	0.05	0.694	1.01	1.49	1.04
	LTE 41	QPSK20M	Rear Face	1	40140	50	25	Reduce	Ant0	1	62.9	21.5	20.12	0.04	0.423	1.01	1.37	0.58
17	LTE 41	QPSK20M	Rear Face	1.5	40140	1	50	Full	Ant0	1	62.9	25.5	23.9	0.02	0.444	1.01	1.45	0.65
	LTE 41	QPSK20M	Rear Face	1.5	40140	1	50	Full	Ant0	2	62.9	25.5	23.9	-0.09	0.426	1.01	1.45	0.62
18	WLAN2.4G	802.11b	Rear Face	1	11	-	-	Full	-	1	99.64	19.5	18.01	-0.14	0.252	1.00	1.41	0.36
	WLAN2.4G	802.11b	Rear Face	1	11	-	-	Full	-	2	99.64	19.5	18.01	0.03	0.213	1.00	1.41	0.30
19	WLAN5G	802.11ac80	Rear Face	1	58	-	-	Full	-	1	88.89	15.5	14.15	0.05	0.208	1.12	1.36	0.32
	WLAN5G	802.11ac80	Rear Face	1	58	-	-	Full	-	2	88.89	15.5	14.15	-0.08	0.189	1.12	1.36	0.29
20	WLAN5G	802.11ac80	Rear Face	1	106	-	-	Full	-	1	88.89	15.5	14.03	-0.02	0.300	1.12	1.40	0.47
	WLAN5G	802.11ac80	Rear Face	1	106	-	-	Full	-	2	88.89	15.5	14.03	0.1	0.293	1.12	1.40	0.46