

FCC RF Test Report

APPLICANT	:	VERTU Corporation Limited
EQUIPMENT	:	GSM Quad-band / UMTS Quad-band /CDMA
		Single-band/WIFI/BT mobile phone
BRAND NAME	:	VERTU
MODEL NAME	:	SIGNATURE S
TYPE	:	VM-06
FCC ID	:	P7QVM-06
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System

The product was received on Jun, 03. 2016 and testing was completed on Sep. 23, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

La

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

RE\	/ISION	I HISTORY	.3
SUI	MMAR	Y OF TEST RESULT	.4
1	GENE	RAL DESCRIPTION	.5
	1.1	Applicant	.5
	1.2	Manufacturer	.5
	1.3	Product Feature of Equipment Under Test	.5
	1.4	Product Specification subjective to this standard	.6
	1.5	Modification of EUT	.6
	1.6	Testing Location	.6
	1.7	Applicable Standards	.7
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	.8
	2.1	Descriptions of Test Mode	.8
	2.2	Test Mode	.9
	2.3	Connection Diagram of Test System	10
	2.4	Support Unit used in test configuration and system	11
	2.5	EUT Operation Test Setup	11
	2.6	Measurement Results Explanation Example	12
3	TEST	RESULT	13
	3.1	6dB and 99% Bandwidth Measurement	13
	3.2	Peak Output Power Measurement	18
	3.3	Power Spectral Density Measurement	19
	3.4	Conducted Band Edges and Spurious Emission Measurement	24
	3.5	Radiated Band Edges and Spurious Emission Measurement	33
	3.6	AC Conducted Emission Measurement	37
	3.7	Antenna Requirements	39
4	LIST	OF MEASURING EQUIPMENT	42
5	UNCE	RTAINTY OF EVALUATION	43
APF	PENDI	X A. CONDUCTED TEST RESULTS	
APF	PENDI	X B. RADIATED TEST RESULTS	
APF	PENDI	X C. DUTY CYCLE PLOTS	

APPENDIX D. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR660304B	Rev. 01	Initial issue of report	Dec. 01, 2016



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-247 5.2(1)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	RSS-Gen 6.6	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	RSS-247 A5.4(4)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	RSS-247 5.2(2)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	RSS-247 5.5	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	RSS-247 5.5	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.54 dB at 46.200 MHz for Quasi-peak
3.6	15.207	RSS-GEN 8.8	AC Conducted Emission	15.207(a)	Pass	Under limit 21.70 dB at 0.150 MHz
3.7	15.203 & 15.247(b)	N/A	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

VERTU Corporation Limited

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom.

1.2 Manufacturer

VERTU Corporation Limited

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom.

1.3 Product Feature of Equipment Under Test

Product Feature			
Equipment	GSM Quad-band / UMTS Quad-band /CDMA Single-band/WIFI/BT mobile phone		
Brand Name	VERTU		
Model Name	SIGNATURE S		
Туре	VM-06		
FCC ID	P7QVM-06		
	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/		
EUT supports Padios application	HSPA+ :(16QAM uplink is not supported)/CDMA/EV-DO		
Lot supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20		
	Bluetooth v3.0 + EDR/Bluetooth v4.1LE		
	Conducted: 004402550074607		
IMEL Codo	Radiation: Sample 1:004402550074623		
IMELCODE	Sample 2:004402550074714		
	Conduction: 004402550074722		
HW Version	LOT0		
SW Version	5.1.1_0.500.0.100		
EUT Stage	Identical Prototype		

Remark:

- 1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 2. There are two types of EUT sample 1 and sample 2, the differences between two samples are only for Gain and shape of 2.4GHz Antenna and the material of shell parts, sample 1 with cortical shell and sample 2 with ceramic shell. After pre-scan two types of EUT, we only chose the sample 1 to perform all tests and sample 2 only verified the worse of Sample 1.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification			
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz		
Number of Channels	40		
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)		
Maximum Output Power to Antenna	3.02 dBm (0.0020 W)		
99% Occupied Bandwidth	1.066MHz		
Antenna Type / Gain	PIFA Antenna with gain -3.9 dBi for sample 1 PIFA Antenna with gain -6.0 dBi for sample 2		
Type of Modulation	Bluetooth LE : GFSK		

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL INC.		
	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park,		
Test Site Location	Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.		
	TEL: +886-3-327-3456		
	FAX: +886-3-328-4978		
Toot Site No	Sporton Site No.		
Test Site No.	TH02-HY	CO05-HY	

Test Site	SPORTON INTERNATIONAL INC.		
	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park,		
Test Site Location	Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.		
	TEL: +886-3-3273456		
	FAX: +886-3-3284978		
Toot Site No	Sporton Site No. FCC/IC Registration		
Test Sile NO.	03CH12-HY	380227/4086H-3	

Note: The test site complies with ANSI C63.4 2014 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ANSI C63.10-2013

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

		Bluetooth v4.1 LE RF Output Power		
Channel	Frequency	Data Rate / Modulation		
	Frequency	GFSK		
		1Mbps		
Ch00	2402MHz	2.49 dBm		
Ch19	2440MHz	<mark>3.02</mark> dBm		
Ch39	2480MHz	3.00 dBm		

The RF output power was recorded in the following table:

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Y plane as worst plane for Sample 1, and Z plane as worst plane for Sample 2) from all possible combinations.
- b. AC power line Conducted Emission was tested under maximum output power.





2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.

	Summary table of Test Cases				
	Data Rate / Modulation				
restitem	Bluetooth v4.1 LE / GFSK				
Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps				
TCc	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps				
IUS	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps				
Dedicted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps				
Raulateu	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps				
105	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps				
AC	Mode 1: CSM850 Idle + Plueteeth Link + WI AN Link + USP Cable (Charging from				
Conducted					
Emission	Adapter)				
Remark: For	Radiated TCs, The tests were performance with Adapter, and USB Cable.				



2.3 Connection Diagram of Test System

<Bluetooth v4.1 LE Tx Mode>



<AC Conducted Emission Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritus	MT8820C	N/A	N/A	Unshielded, 1.8 m
2	Bluetooth				N1/A	N1/A
۷.	2. Speaker	VERTU	3P-1V	P7Q-3P1V	N/A	N/A
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
			Latitude E6320	FCC DoC	N/A	AC I/P:
4.		חבוו				Unshielded, 1.2 m
	NOLEDOOK	NOLEDOOK DELL				DC O/P:
						Shielded, 1.8 m

2.5 EUT Operation Test Setup

For Bluetooth v4.1 LE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 3.8 dB and 20dB attenuator.

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ = 3.8 + 20 = 23.8 (dB)



3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
- 6. Measure and record the results in the test report.

3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Test data refer to Appendix A.



6 dB Bandwidth Plot on Channel 00

Date: 20.SEP.2016 10:05:51





6 dB Bandwidth Plot on Channel 19

Date: 20.SEP.2016 10:11:15



6 dB Bandwidth Plot on Channel 39

Date: 20.SEP.2016 10:13:59

SPORTON INTERNATIONAL INC. TEL : 886-3-327-3456 FAX : 886-3-328-4978 FCC ID : P7QVM-06





3.1.6 Test Result of 99% Occupied Bandwidth

Test data refer to Appendix A.



99% Bandwidth Plot on Channel 00

Date: 20.SEP.2016 10:07:50





99% Occupied Bandwidth Plot on Channel 19

Date: 20.SEP.2016 10:11:45



99% Occupied Bandwidth Plot on Channel 39

Date: 20.SEP.2016 10:15:48

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

- The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05 section 9.1.2 PKPM1 Peak power meter method.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Test data refers to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

- The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz.
 Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.
- 7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



Spectrum Analyzer



3.3.5 Test Result of Power Spectral Density

Test data refers to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)



PSD 100kHz Plot on Channel 00

Date: 20.SEP.2016 10:06:32





PSD 100kHz Plot on Channel 19

Date: 20.SEP.2016 10:12:40



PSD 100kHz Plot on Channel 39

Date: 20.SEP.2016 10:14:46

SPORTON INTERNATIONAL INC. TEL : 886-3-327-3456 FAX : 886-3-328-4978 FCC ID : P7QVM-06



3.3.7 Test Result of Power Spectral Density Plots (3kHz)



PSD 3kHz Plot on Channel 00

Date: 20.SEP.2016 10:06:09



PSD 3kHz Plot on Channel 19



Date: 20.SEP.2016 10:12:14



PSD 3kHz Plot on Channel 39

Date: 20.SEP.2016 10:14:16



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges Plots



Low Band Edge Plot on Channel 00

Date: 20.SEP.2016 10:06:58





High Band Edge Plot on Channel 39

Date: 20.SEP.2016 10:15:01



3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 20.SEP.2016 10:07:22





Date: 20.SEP.2016 10:07:30





Date: 20.SEP.2016 10:12:54





Date: 20.SEP.2016 10:13:02





Date: 20.SEP.2016 10:15:21





Date: 20.SEP.2016 10:15:29



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.



3.5.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
- The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- 7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement. For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.



3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



Spectrum Analyzer / Receiver





For radiated emissions above 1GHz

3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of omission (MHz)	Conducted limit (dBµV)				
Frequency of emission (MHZ)	Quasi-peak	Average			
0.15-0.5	66 to 56*	56 to 46*			
0.5-5	56	46			
5-30	60	50			

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.



3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1		Tem	peratu	re :	24~	24~25 ℃		
Test Engineer :	Kai-Chun Ch	Rela	tive H	umidit	y : 49~	49~50%			
Test Voltage :	120Vac / 60Hz			se :		Line			
		ENV216 /	Auto Test F	CC Power	Bar - L	22-QP Limit a	t Main Ports		
	Final Result	300 400 500 800 1M	Ereque	M 3M A	4M 5M 6	8 10M	20M 30M		
	Frequency		Filter		Corr	Margin	Limit		
	(MHz)	(dBµV)		Line	(dB)	(dB)	(dBµV)		
	0.150000	40.2	Off	L1	19.6	25.8	66.0		
	0.190000	28.4	Off	L1	19.6	35.6	64.0		
	0.270000	22.2	Off	L1	19.6	38.9	61.1		
	0.478000	25.8	Off	L1	19.6	30.6	56.4		
	1.142000	26.9	Off	L1	19.7	29.1	56.0		
	2.758000	21.4	Off	L1	19.5	34.6	56.0		
	18.150000	38.1	Off	L1	20.6	21.9	60.0		
	Final Resul	t : Average							
	Frequency	Average	Filter	Line	Corr.	Margin	Limit		
	(MHz)	(dBµV)	The	Line	(dB)	(dB)	(dBµV)		
	0.150000	22.3	Off	L1	19.6	33.7	56.0		
	0.190000	19.3	Off	L1	19.6	34.7	54.0		
	0.270000	17.4	Off	L1	19.6	33.7	51.1		
	0.478000	20.7	Off	L1	19.6	25.7	46.4		
	1.142000	17.6	Off	L1	19.7	28.4	46.0		
	2.758000	14.7	Off	L1	19.5	31.3	46.0		
	18.150000	22.9	Off	L1	20.6	27.1	50.0		





Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	44.3	Off	Ν	19.6	21.7	66.0
0.198000	31.4	Off	Ν	19.6	32.3	63.7
0.534000	28.3	Off	Ν	19.6	27.7	56.0
1.126000	21.6	Off	Ν	19.6	34.4	56.0
1.782000	20.4	Off	Ν	19.7	35.6	56.0
19.158000	28.2	Off	Ν	20.7	31.8	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	23.0	Off	Ν	19.6	33.0	56.0
0.198000	18.5	Off	Ν	19.6	35.2	53.7
0.534000	22.6	Off	Ν	19.6	23.4	46.0
1.126000	16.7	Off	Ν	19.6	29.3	46.0
1.782000	16.2	Off	Ν	19.7	29.8	46.0
19.158000	17.0	Off	N	20.7	33.0	50.0



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB412923 44	300MHz~40GH z	Jan. 08, 2016	Sep. 07, 2016~ Sep. 20, 2016	Jan. 07, 2017	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US404415 48	300MHz~40GH z	Jan. 07, 2016	Sep. 07, 2016~ Sep. 20, 2016	Jan. 06, 2017	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 17, 2016	Sep. 07, 2016~ Sep. 20, 2016	Jun. 16, 2017	Conducted (TH02-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Sep. 14, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Sep. 14, 2016	Aug. 29, 2017	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Apr. 19, 2016	Sep. 14, 2016	Apr. 18, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Sep. 14, 2016	Dec. 01, 2016	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 06, 2016	Sep. 14, 2016	Jan. 05, 2017	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 08, 2016	Sep. 14, 2016	Jan. 07, 2017	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Sep. 13, 2016~ Sep. 23, 2016	Sep. 01, 2017	Radiation (03CH12-HY)
Loop Cable	Rohde & Schwarz	N/A	N/A	9KHz~30MHz	Dec. 03, 2015	Sep. 13, 2016~ Sep. 23, 2016	Dec. 02, 2016	Radiation (03CH12-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Nov. 16, 2015	Sep. 13, 2016~ Sep. 23, 2016	Nov. 15, 2016	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D	37059	30MHz~1GHz	Dec. 29, 2015	Sep. 13, 2016~ Sep. 23, 2016	Dec. 28, 2016	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 21, 2015	Sep. 13, 2016~ Sep. 23, 2016	Dec. 20, 2016	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-132 8	1GHz ~ 18GHz	Nov. 02, 2015	Sep. 13, 2016~ Sep. 23, 2016	Nov. 01, 2016	Radiation (03CH12-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1815698	1GHz~18GHz	Dec. 14, 2015	Sep. 13, 2016~ Sep. 23, 2016	Dec. 13, 2016	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY532701 48	1GHz~26.5GHz	Jan. 30, 2016	Sep. 13, 2016~ Sep. 23, 2016	Jan. 29, 2017	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Sep. 13, 2016~ Sep. 23, 2016	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Sep. 13, 2016~ Sep. 23, 2016	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Sep. 13, 2016~ Sep. 23, 2016	N/A	Radiation (03CH12-HY)
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Sep. 13, 2016~ Sep. 23, 2016	Jun. 13, 2017	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 02, 2015	Sep. 13, 2016~ Sep. 23, 2016	Nov. 01, 2016	Radiation (03CH12-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2 3dB
of 95% (U = 2Uc(y))	2.500

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence	5 1dP
of 95% (U = 2Uc(y))	5.10B

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.2dB
--	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence	4 740
of 95% (U = 2Uc(y))	4.70B



Appendix A. Conducted Test Results

Report Number : FR660304B

Bluetooth Low Energy

Test Engineer:	AC Chang	Temperature:	21~25	°C
Test Date:	2016/9/7~2016/9/20	Relative Humidity:	50~54	%

	TEST RESULTS DATA 6dB and 99% Occupied Bandwidth											
Γ	Лоd.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail			
E	3LE	1Mbps	1	0	2402	1.07	0.69	0.50	Pass			
E	3LE	1Mbps	1	19	2440	1.06	0.70	0.50	Pass			
E	BLE	1Mbps	1	39	2480	1.06	0.69	0.50	Pass			

<u>TEST RESULTS DATA</u> <u>Peak Power Table</u>											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail	
BLE	1Mbps	1	0	2402	2.49	30.00	-3.90	-1.41	36.00	Pass	
BLE	1Mbps	1	19	2440	3.02	30.00	-3.90	-0.88	36.00	Pass	
BLE	1Mbps	1	39	2480	3.00	30.00	-3.90	-0.90	36.00	Pass	

	<u>TEST RESULTS DATA</u> <u>Average Power Table</u> <u>(Reporting Only)</u>								
	Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)		
Γ	BLE	1Mbps	1	0	2402	2.06	2.01		
ſ	BLE	1Mbps	1	19	2440	2.06	2.55		
[BLE	1Mbps	1	39	2480	2.06	2.52		
-									

						Peak	Power De	ensity		
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail	
BLE	1Mbps	1	0	2402	2.24	-12.85	-3.90	8.00	Pass	
BLE	1Mbps	1	19	2440	2.36	-12.72	-3.90	8.00	Pass	
BLE	1Mbps	1	39	2480	2.42	-12.63	-3.90	8.00	Pass	



Appendix B. Radiated Spurious Emission

Sample 1

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2386.02	55.96	-18.04	74	52.95	27.05	7.45	31.49	264	51	Р	Н
		2375.625	44.88	-9.12	54	41.99	27.01	7.37	31.49	264	51	Α	Н
		2402	88.3	-	-	85.29	27.05	7.45	31.49	264	51	Р	Н
BLE		2402	87.21	-	-	84.2	27.05	7.45	31.49	264	51	Α	Н
2402MH7		2351.58	55.71	-18.29	74	52.87	26.97	7.37	31.5	269	71	Р	V
240210112		2382.45	44.94	-9.06	54	41.97	27.01	7.45	31.49	269	71	Α	V
		2402	87.03	-	-	84.02	27.05	7.45	31.49	269	71	Р	V
		2402	85.99	-	-	82.98	27.05	7.45	31.49	269	71	А	V
		2366.84	56.04	-17.96	74	53.19	26.97	7.37	31.49	286	34	Р	Н
		2384.76	45.29	-8.71	54	42.32	27.01	7.45	31.49	286	34	Α	Н
		2442	87.9	-	-	84.7	27.18	7.49	31.47	286	34	Р	Н
		2442	86.72	-	-	83.52	27.18	7.49	31.47	286	34	А	Н
515		2490.34	56	-18	74	52.64	27.3	7.53	31.47	286	34	Р	Н
BLE		2486.14	45.45	-8.55	54	42.13	27.26	7.53	31.47	286	34	Α	Н
		2373.84	55.64	-18.36	74	52.75	27.01	7.37	31.49	266	70	Р	V
244010172		2370.06	44.85	-9.15	54	41.96	27.01	7.37	31.49	266	70	А	V
		2442	88	-	-	84.8	27.18	7.49	31.47	266	70	Р	V
		2442	84.69	-	-	81.49	27.18	7.49	31.47	266	70	А	V
		2486.56	56.83	-17.17	74	53.51	27.26	7.53	31.47	266	70	Р	V
		2483.55	45.12	-8.88	54	41.8	27.26	7.53	31.47	266	70	А	V



		2482	85.57	-	-	82.25	27.26	7.53	31.47	275	33	Р	Н
		2482	84.58	-	-	81.26	27.26	7.53	31.47	275	33	А	Н
		2492.04	56.22	-17.78	74	52.85	27.3	7.53	31.46	275	33	Р	Н
		2489.32	45.14	-8.86	54	41.78	27.3	7.53	31.47	275	33	А	Н
СП 39 2480МЦ-		2482	83.67	-	-	80.35	27.26	7.53	31.47	257	69	Р	V
240011112		2482	82.61	-	-	79.29	27.26	7.53	31.47	257	69	А	V
		2493.48	56.38	-17.62	74	53.01	27.3	7.53	31.46	257	69	Р	V
		2489.28	45.08	-8.92	54	41.72	27.3	7.53	31.47	257	69	А	V
Remark	1. No 2. Al	o other spurio I results are P	us found. ASS again	st Peak	and Averag	ge limit lin	e.						



BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBµV/m)	Limit (dB)	Line (dBµV/m)	Level (dBµV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
BLE		4804	36.39	-37.61	74	52.72	31.23	10.59	58.15	100	0	Ρ	Н
CH 00 2402MHz		4804	36.92	-37.08	74	53.25	31.23	10.59	58.15	100	0	Р	V
		4878	37.48	-36.52	74	53.36	31.33	10.89	58.1	100	0	Ρ	Н
BLE		7320	42.25	-31.75	74	51.05	36.12	14.18	59.1	100	0	Ρ	Н
CH 19		4878	37.33	-36.67	74	53.21	31.33	10.89	58.1	100	0	Ρ	V
2440101112		7320	42.25	-31.75	74	51.05	36.12	14.18	59.1	100	0	Ρ	V
		4962	37.47	-36.53	74	52.86	31.45	11.19	58.03	100	0	Ρ	Н
BLE		7440	42.76	-31.24	74	51.15	36.46	14.32	59.17	100	0	Ρ	Н
CH 39		4962	37.04	-36.96	74	52.43	31.45	11.19	58.03	100	0	Ρ	V
240010172		7440	43.25	-30.75	74	51.64	36.46	14.32	59.17	100	0	Ρ	V
Remark	1. No 2. Al	o other spuri	ous found. PASS agains	st Peak	and Averag	e limit lin	e.						

BLE (Harmonic @ 3m)



Emission below 1GHz

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		30.27	22.69	-17.31	40	28.57	25.8	0.78	32.46	-	-	Ρ	Н
		74.01	20.94	-19.06	40	39.52	12.81	1.06	32.45	-	-	Р	Н
		96.42	22.07	-21.43	43.5	37.92	15.52	1.06	32.43	-	-	Р	Н
		175.8	25.69	-17.81	43.5	40.78	15.57	1.75	32.41	-	-	Р	Н
		529.6	31.84	-14.16	46	36.76	24.29	3.19	32.4	-	-	Р	Н
2.4GHz BLF		883.8	32.9	-13.1	46	31.32	28.8	4.45	31.67	100	65	Р	Н
BLC		46.47	33.46	-6.54	40	48.51	16.63	0.78	32.46	100	127	QP	V
LI		92.1	27.45	-16.05	43.5	43.78	15.04	1.06	32.43	-	-	Р	V
		162.57	29.3	-14.2	43.5	43.3	16.67	1.75	32.42	-	-	Р	V
		173.64	27	-16.5	43.5	41.99	15.68	1.75	32.42	-	-	Ρ	V
		881	37.3	-8.7	46	35.76	28.78	4.45	31.69	-	-	Р	V
		884.5	33.71	-12.29	46	32.12	28.81	4.45	31.67	-	-	Р	V
Remark	1. No 2. Al	o other spurio I results are P	us found. ASS agains	st limit li	ne.								



Sample 2

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	($dB\mu V/m$)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2326.8	56.25	-17.75	74	53.57	26.89	7.3	31.51	272	55	Р	Н
		2364.74	45.34	-8.66	54	42.49	26.97	7.37	31.49	272	55	Α	Н
		2440	85.89	-	-	82.7	27.18	7.49	31.48	272	55	Р	Н
		2440	84.89	-	-	81.7	27.18	7.49	31.48	272	55	Α	Н
		2491.81	55.82	-18.18	74	52.45	27.3	7.53	31.46	272	55	Р	Н
		2499.79	45.56	-8.44	54	42.19	27.3	7.53	31.46	272	55	Α	Н
2440MHz		2383.22	55.67	-18.33	74	52.7	27.01	7.45	31.49	109	63	Р	V
244010112		2378.32	45.32	-8.68	54	42.43	27.01	7.37	31.49	109	63	Α	V
		2440	87.91	-	-	84.72	27.18	7.49	31.48	109	63	Р	V
		2440	85.97	-	-	82.78	27.18	7.49	31.48	109	63	A	V
		2493.21	56.6	-17.4	74	53.23	27.3	7.53	31.46	109	63	Р	V
		2491.11	45.41	-8.59	54	42.05	27.3	7.53	31.47	109	63	Α	V



				В	LE (Harm	onic @	3m)						
BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBµV/m)	Limit (dB)	Line (dBµV/m)	Level (dBµV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
		4878	36.94	-37.06	74	52.82	31.33	10.89	58.1	100	0	Р	Н
BLE		7320	41.95	-32.05	74	50.75	36.12	14.18	59.1	100	0	Р	Н
CH 19		4878	36.58	-37.42	74	52.46	31.33	10.89	58.1	100	0	Р	V
244011172		7320	42.11	-31.89	74	50.91	36.12	14.18	59.1	100	0	Р	V
Remark	3. No 4. Al	o other spurio results are P	us found. ASS agains	st Peak	and Averag	e limit lin	e.						

2.4GHz 2400~2483.5MHz



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		48.09	29.82	-10.18	40	45.73	15.77	0.78	32.46	390	248	Р	Н
		95.88	31.44	-12.06	43.5	47.29	15.52	1.06	32.43	-	-	Р	Н
		169.86	31.69	-11.81	43.5	46.46	15.9	1.75	32.42	-	-	Р	Н
		255.45	23.54	-22.46	46	35.02	19	1.83	32.31	-	-	Р	Н
		882.4	31.48	-14.52	46	29.91	28.8	4.45	31.68	-	-	Р	Н
2.4GHZ		884.5	31.98	-14.02	46	30.39	28.81	4.45	31.67	-	-	Р	Н
		46.2	35.46	-4.54	40	50.51	16.63	0.78	32.46	100	171	QP	V
		81.03	28.17	-11.83	40	45.74	13.81	1.06	32.44	-	-	Р	V
		106.14	28.46	-15.04	43.5	42.8	16.66	1.43	32.43	-	-	Р	V
		173.91	28.17	-15.33	43.5	43.16	15.68	1.75	32.42	-	-	Р	V
		881.7	35.35	-10.65	46	33.79	28.79	4.45	31.68	-	-	Р	V
		884.5	32.89	-13.11	46	31.3	28.81	4.45	31.67	-	-	Р	V
Remark	3. No 4. Al	o other spurio I results are F	us found. ASS again	st limit li	ne.								



Note symbol

	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall
	not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 01 2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	А	Н

1. Level(dBµV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBµV/m) – Limit Line(dBµV/m)

For Peak Limit @ 2390MHz:

1. Level(dBµV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) - Preamp Factor(dB)

- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- = 55.45 (dBµV/m)
- 2. Over Limit(dB)
- = Level(dBµV/m) Limit Line(dBµV/m)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- = 32.22(dB/m) + 4.58(dB) + 42.6(dBµV) 35.86 (dB)
- = 43.54 (dBµV/m)
- 2. Over Limit(dB)
- = Level(dBµV/m) Limit Line(dBµV/m)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".





Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(mS)	1/T(kHz)	VBW Setting
Bluetooth v4.1 LE	62.18	0.39	2.58	3kHz

Bluetooth 4.1 LE

