



# **RF Exposure Evaluation**

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)	
	(A) Limits	for Occupational/Controlled	Exposures		
0.3–3.0	614	1.63	*(100)	6	
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6	
30–300	61.4	0.163	1.0 6		
300–1500			f/300 6		
1500–100,000			5	6	
	(B) Limits for (	General Population/Uncontro	olled Exposure		
0.3–1.34	614	1.63	*(100) 30		
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30	
30–300	27.5	0.073	0.2	30	
300–1500			f/1500	30	
1500-100,000			1.0	30	

f = frequency in MHz

Friis transmission formula: Pd = (Pout\*G)/(4\*pi\*r<sup>2</sup>)

#### Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.







# Test Result of RF Exposure Evaluation

Wireless function	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
125kHz Bandwidth	21.763	150.072	0.0944	0.602	PASS
500kHz Bandwidth	21.461	139.991	0.0880	0.602	PASS
2.4G WIFI	15.10	32.329	0.01020	1.0	PASS

Note: The device build in a certified Wireless IoT Module, FCC ID: ZHZHE, the WLAN 2.4G, Lora can transmit simultaneously:

S<sub>Limit,i</sub>

 $= S_{2.4}/S_{limit-2.4} + S_{Lora\ 125kHz} / S_{limit-lora\ 125kHz} = 0.0120/1 + 0.0944/0.602 = 0.169 < 1.0$ 

Result: The device meet FCC MPE at 20 cm distance

Shenzhen ZKT Technology Co., Ltd. 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

