


FCC RF Exposure Report

FCC ID : P27RP324
Equipment : AC2100 Wi-Fi Mesh Extender
Model No. : RP324
Multiple Listing : Refer to item 1.1.1 for more details.
Brand Name : Sercomm
Applicant : Sercomm Corporation
Address : 8F, No. 3-1, YuanQu St., NanKang, Taipei 115,
Taiwan, R.O.C.
Standard : 47 CFR FCC Part 2.1091
Received Date : Oct. 02, 2019
Tested Date : Oct. 08 ~ Nov. 21, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	4
1.1	INFORMATION	4
2	MPE EVALUATION OF MOBILE DEVICES	5
2.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE.....	5
2.2	MPE EVALUATION FORMULA	5
2.3	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	5
2.4	MEASUREMENT UNCERTAINTY	5
2.5	MPE EVALUATION RESULTS	6
2.6	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION.....	7
3	TEST LABORATORY INFORMATION	8

Release Record

Report No.	Version	Description	Issued Date
FA9O0208-01	Rev. 01	Initial issue	Dec. 11, 2019

1 General Description

1.1 INFORMATION

This report is issued as a supplementary report to original ICC report no. FA9O0208. The modification is only concerned with adding 5250~5350MHz and 5470~5725 MHz band by software setting.

1.1.1 PRODUCT DETAILS

The following models are provided to this EUT.

Model Name	Description
RP324	Main tested model.
RP324XX	the 1st X should be "blank" or "-"; the rest X could be 0 to 9, A to Z, "blank" or "-", for marketing purpose.
✦ All models are electrically identical, different model names are for marketing purpose.	

2 MPE EVALUATION OF MOBILE DEVICES

2.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm ²)	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

2.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in Mw

Pi= 3.1416

R= Measurement distance

2.3 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

2.4 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Parameters	Uncertainty
Conducted power	±0.808 dB

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

2.5 MPE EVALUATION RESULTS

Non-beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio*	Pass / Fail
2412~2462 ^{Note}	22.77	23.00	3.14	20	0.082	1	0.082	Pass
5180-5240 ^{Note}	25.78	26.00	3.25	20	0.167	1	0.167	Pass
5260~5320	22.59	23.00	3.49	20	0.089	1	0.089	Pass
5500~5700	23.05	23.50	3.53	20	0.100	1	0.100	Pass
5745-5825 ^{Note}	25.73	26.00	3.20	20	0.165	1	0.165	Pass

*Ratio = Power density / Limit.

Note: These frequency bands are certified for original grant (Report No: FA9O0208).

Beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio*	Pass / Fail
5180-5240 ^{Note}	25.48	25.50	8.98	20	0.558	1	0.558	Pass
5260~5320	20.57	21.00	9.29	20	0.213	1	0.213	Pass
5500~5700	20.46	20.50	9.21	20	0.186	1	0.186	Pass
5745-5825 ^{Note}	25.14	25.50	8.97	20	0.557	1	0.557	Pass

*Ratio = Power density / Limit.

Note: These frequency bands are certified for original grant (Report No: FA9O0208).

Note:

For 5250~5350MHz:

Directional gain = $10 \times \log((10^{3.49/20} + 10^{3.32/20} + 10^{3.08/20} + 10^{3.17/20})^2 / 4) = 9.29$ dBi.

For 5470~5725MHz:

Directional gain = $10 \times \log((10^{2.79/20} + 10^{3.53/20} + 10^{3.15/20} + 10^{3.28/20})^2 / 4) = 9.21$ dBi.

2.6 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION

Mode	Max Ratio of Each Mode
WLAN 2.4GHz (<i>Non-beamforming mode</i>)	0.082
WLAN 5GHz (<i>Non-beamforming mode</i>)	0.167
Sum	0.249
Limit	1
Pass / Fail	Pass

Mode	Max Ratio of Each Mode
WLAN 2.4GHz(<i>Non-beamforming mode</i>)	0.082
WLAN 5GHz (<i>Beamforming mode</i>)	0.558
Sum	0.64
Limit	1
Pass / Fail	Pass

3 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==