

**FCC ID: 2AXPW-MD066**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

| Modulation    | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | SAR Exclusion threshold | SAR test exclusion |
|---------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|-------------------------|--------------------|
| GFSK          | 2.402               | 5.413                  | 3.48                  | 5±1                 | 6.00                    | 3.98                   | <5            | 1.23400            | 3.00                    | YES                |
|               | 2.441               | 4.712                  | 2.96                  | 4±1                 | 5.00                    | 3.16                   | <5            | 0.98813            | 3.00                    | YES                |
|               | 2.480               | 5.329                  | 3.41                  | 5±1                 | 6.00                    | 3.98                   | <5            | 1.25388            | 3.00                    | YES                |
| $\pi$ /4DQPSK | 2.402               | 5.302                  | 3.39                  | 5±1                 | 6.00                    | 3.98                   | <5            | 1.23400            | 3.00                    | YES                |
|               | 2.441               | 4.595                  | 2.88                  | 4±1                 | 5.00                    | 3.16                   | <5            | 0.98813            | 3.00                    | YES                |
|               | 2.480               | 5.181                  | 3.30                  | 5±1                 | 6.00                    | 3.98                   | <5            | 1.25388            | 3.00                    | YES                |
| 8DQPSK        | 2.402               | 5.171                  | 3.29                  | 5±1                 | 6.00                    | 3.98                   | <5            | 1.23400            | 3.00                    | YES                |
|               | 2.441               | 4.564                  | 2.86                  | 4±1                 | 5.00                    | 3.16                   | <5            | 0.98813            | 3.00                    | YES                |
|               | 2.480               | 5.167                  | 3.29                  | 5±1                 | 6.00                    | 3.98                   | <5            | 1.25388            | 3.00                    | YES                |

**Conclusion:**

For the max result :  $1.25388 \leq \text{FCC Limit } 3.0$  for 1g SAR.